Package: ABCDscores (via r-universe)

May 16, 2026

Title Summary Scores of the Adolescent Brain Cognitive Development (ABCD) Study

Description Provides functions to compute summary scores (besides proprietary ones) reported in the tabulated data resource that is released by the Adolescent Brain Cognitive Development (ABCD) study.

URL https://software.nbdc-datahub.org/ABCDscores/

Version 7.0.0

Depends R (>= 4.3.0)

Imports chk, cli, dplyr, glue, lubridate, magrittr, purrr, rlang, stringr, tibble, tidyr, stats, utils, hms, data.table

Suggests arrow, rmarkdown, roxyglobals, testthat (>= 3.0.0), knitr, reactable, readr, usethis

License GPL (>= 3)

Encoding UTF-8

Config/testthat/edition 3

Config/Needs/website rmarkdown

VignetteBuilder knitr

LazyData true

Config/roxyglobals/filename globals.R

Config/roxyglobals/unique TRUE

Config/roxygen2/version 8.0.0

RoxygenNote 7.3.3

NeedsCompilation no

Author Le Zhang [aut, cre] (ORCID: <https://orcid.org/0009-0008-0205-2150>), Janosch Linkersdoerfer [aut] (ORCID: <https://orcid.org/0000-0002-1577-1233>), Olivier Celhay [aut] (ORCID: <https://orcid.org/0000-0002-2971-9110>), Biplabendu Das [aut] (ORCID: <https://orcid.org/0000-0003-0855-262X>),

Sammy Berman [aut] (ORCID:
<https://orcid.org/0000-0002-9803-019X>), Laura Ziemer [aut]
(ORCID: <https://orcid.org/0000-0003-0026-3823>), Shermaine
Abad [aut] (ORCID: <https://orcid.org/0009-0009-6013-9147>)

Maintainer Le Zhang <dairc.service@gmail.com>

Config/pak/sysreqs libicu-dev

Repository https://dairc-service.r-universe.dev

Date/Publication 2026-05-16 00:11:15 UTC

RemoteUrl https://github.com/cran/ABCDscores

RemoteRef HEAD

RemoteSha 62cd5af5b5740af70a170f5adbc5d47a3d444fc5

Contents

check_assign_na 24
combine_checkboxes 25
combine_cols 26
combine_levels 27
compute_ab_g_dyn__cohort_income__hhold__3lvl 28
compute_ab_g_dyn_all 29
compute_ab_g_stc_all 30
compute_ab_p_demo__ntvam_all 30
compute_age 31
compute_famhx_endorsement 31
compute_fc_p_fes__cohes_nm 33
compute_fc_p_fes__confl_nm 34
compute_fc_p_fes__expr_nm 35
compute_fc_p_fes__intelcult_nm 36
compute_fc_p_fes__org_nm 37
compute_fc_p_fes__rec_nm 38
compute_fc_p_fes_all 39
compute_fc_p_meim__commattach_nm 39
compute_fc_p_meim__explor_nm 40
compute_fc_p_meim_all 41
compute_fc_p_meim_nm 42
compute_fc_p_nce__cc_nm 43
compute_fc_p_nce__isc_nm 44
compute_fc_p_nce_all 45
compute_fc_p_nce_nm 45
compute_fc_p_nsc__ns_nm 46
compute_fc_p_nsc_all 47
compute_fc_p_pk__knowl_nm 48
compute_fc_p_pk_all 49
compute_fc_p_psb_all 49
compute_fc_p_psb_nm 50
compute_fc_p_vs__famil_nm 51

compute_fc_p_vs__famil_nm__v01 . . . 52
compute_fc_p_vs__indselfrel_nm . . . 53
compute_fc_p_vs__obl_nm . . . 54
compute_fc_p_vs__ref_nm . . . 55
compute_fc_p_vs__relig_nm . . . 56
compute_fc_p_vs__supp_nm . . . 57
compute_fc_p_vs_all . . . 58
compute_fc_y_as__safe_nm . . . 59
compute_fc_y_as_all . . . 60
compute_fc_y_crpbi__cg1_nm . . . 60
compute_fc_y_crpbi__cg2_nm . . . 61
compute_fc_y_crpbi_all . . . 62
compute_fc_y_eut__ethn_nm . . . 63
compute_fc_y_eut_all . . . 64
compute_fc_y_fes__cohes_nm . . . 64
compute_fc_y_fes__confl_nm . . . 65
compute_fc_y_fes_all . . . 66
compute_fc_y_lone_all . . . 67
compute_fc_y_lone_nm . . . 68
compute_fc_y_meim__commattach_nm . . . 69
compute_fc_y_meim__explor_nm . . . 70
compute_fc_y_meim_all . . . 71
compute_fc_y_meim_nm . . . 71
compute_fc_y_mnbs__edusupp_nm . . . 72
compute_fc_y_mnbs__superv_nm . . . 73
compute_fc_y_mnbs_all . . . 74
compute_fc_y_mnbs_nm . . . 75
compute_fc_y_naa_all . . . 76
compute_fc_y_pm_all . . . 76
compute_fc_y_pm_nm . . . 77
compute_fc_y_pnh_all . . . 78
compute_fc_y_pnh_nm . . . 78
compute_fc_y_psb_all . . . 79
compute_fc_y_psb_nm . . . 80
compute_fc_y_rpi_all . . . 81
compute_fc_y_rpi_nm . . . 81
compute_fc_y_srpf__dis_nm . . . 82
compute_fc_y_srpf__env_nm . . . 83
compute_fc_y_srpf__involv_nm . . . 84
compute_fc_y_srpf_all . . . 85
compute_fc_y_vs__famil_nm . . . 86
compute_fc_y_vs__famil_nm__v01 . . . 87
compute_fc_y_vs__indselfrel_nm . . . 88
compute_fc_y_vs__obl_nm . . . 89
compute_fc_y_vs__ref_nm . . . 90
compute_fc_y_vs__relig_nm . . . 91
compute_fc_y_vs__supp_nm . . . 92
compute_fc_y_vs_all . . . 93

compute_fc_y_wpss_all . . . 94
compute_fc_y_wpss_nm . . . 94
compute_fitbit_activity_table . . . 95
compute_fitbit_activity_table_ext . . . 97
compute_fitbit_activity_week . . . 99
compute_fitbit_sleep_table . . . 100
compute_fitbit_sleep_table_ext . . . 102
compute_fitbit_sleep_week . . . 105
compute_fitbit_weekly_summary . . . 106
compute_mh_p_abcl__afs__frnd_sum . . . 107
compute_mh_p_abcl__afs__frnd_tscore . . . 108
compute_mh_p_abcl__critic_sum . . . 110
compute_mh_p_abcl__critic_tscore . . . 111
compute_mh_p_abcl__dsm__adhd_sum . . . 113
compute_mh_p_abcl__dsm__adhd_tscore . . . 114
compute_mh_p_abcl__dsm__antsoc_sum . . . 116
compute_mh_p_abcl__dsm__antsoc_tscore . . . 118
compute_mh_p_abcl__dsm__anx_sum . . . 120
compute_mh_p_abcl__dsm__anx_tscore . . . 121
compute_mh_p_abcl__dsm__avoid_sum . . . 123
compute_mh_p_abcl__dsm__avoid_tscore . . . 124
compute_mh_p_abcl__dsm__dep_sum . . . 126
compute_mh_p_abcl__dsm__dep_tscore . . . 127
compute_mh_p_abcl__dsm__somat_sum . . . 129
compute_mh_p_abcl__dsm__somat_tscore . . . 130
compute_mh_p_abcl__su__drg_sum . . . 132
compute_mh_p_abcl__su__drg_tscore . . . 133
compute_mh_p_abcl__su__drunk_sum . . . 134
compute_mh_p_abcl__su__drunk_tscore . . . 135
compute_mh_p_abcl__su__nic_sum . . . 137
compute_mh_p_abcl__su__nic_tscore . . . 138
compute_mh_p_abcl__su_sum . . . 139
compute_mh_p_abcl__su_tscore . . . 141
compute_mh_p_abcl__synd__aggr_sum . . . 142
compute_mh_p_abcl__synd__aggr_tscore . . . 144
compute_mh_p_abcl__synd__anxdep_sum . . . 145
compute_mh_p_abcl__synd__anxdep_tscore . . . 147
compute_mh_p_abcl__synd__attn_sum . . . 149
compute_mh_p_abcl__synd__attn_tscore . . . 150
compute_mh_p_abcl__synd__ext_sum . . . 152
compute_mh_p_abcl__synd__ext_tscore . . . 154
compute_mh_p_abcl__synd__int_sum . . . 156
compute_mh_p_abcl__synd__int_tscore . . . 158
compute_mh_p_abcl__synd__intru_sum . . . 160
compute_mh_p_abcl__synd__intru_tscore . . . 161
compute_mh_p_abcl__synd__othpr_sum . . . 163
compute_mh_p_abcl__synd__rule_sum . . . 165
compute_mh_p_abcl__synd__rule_tscore . . . 166

compute_mh_p_abcl__synd__som_sum . . . 168
compute_mh_p_abcl__synd__som_tscore . . . 169
compute_mh_p_abcl__synd__tho_sum . . . 171
compute_mh_p_abcl__synd__tho_tscore . . . 172
compute_mh_p_abcl__synd__wthdr_sum . . . 174
compute_mh_p_abcl__synd__wthdr_tscore . . . 175
compute_mh_p_abcl_all . . . 177
compute_mh_p_abcl_sum . . . 178
compute_mh_p_abcl_tscore . . . 182
compute_mh_p_asr__afs__strng_sum . . . 186
compute_mh_p_asr__critic_sum . . . 187
compute_mh_p_asr__dsm__adhd__hypimp_sum . . . 189
compute_mh_p_asr__dsm__adhd__inatt_sum . . . 190
compute_mh_p_asr__dsm__adhd_sum . . . 192
compute_mh_p_asr__dsm__antsoc_sum . . . 193
compute_mh_p_asr__dsm__anx_sum . . . 195
compute_mh_p_asr__dsm__avoid_sum . . . 196
compute_mh_p_asr__dsm__dep_sum . . . 198
compute_mh_p_asr__dsm__somat_sum . . . 199
compute_mh_p_asr__synd__aggr_sum . . . 201
compute_mh_p_asr__synd__anxdep_sum . . . 202
compute_mh_p_asr__synd__attn_sum . . . 204
compute_mh_p_asr__synd__ext_sum . . . 205
compute_mh_p_asr__synd__int_sum . . . 207
compute_mh_p_asr__synd__intru_sum . . . 210
compute_mh_p_asr__synd__othpr_sum . . . 211
compute_mh_p_asr__synd__rule_sum . . . 213
compute_mh_p_asr__synd__som_sum . . . 214
compute_mh_p_asr__synd__tho_sum . . . 216
compute_mh_p_asr__synd__wthdr_sum . . . 217
compute_mh_p_asr_all . . . 219
compute_mh_p_asr_sum . . . 219
compute_mh_p_cbcl__dsm__adhd_sum . . . 223
compute_mh_p_cbcl__dsm__adhd_tscore . . . 225
compute_mh_p_cbcl__dsm__anx_sum . . . 226
compute_mh_p_cbcl__dsm__anx_tscore . . . 228
compute_mh_p_cbcl__dsm__cond_sum . . . 229
compute_mh_p_cbcl__dsm__cond_tscore . . . 231
compute_mh_p_cbcl__dsm__dep_sum . . . 233
compute_mh_p_cbcl__dsm__dep_tscore . . . 234
compute_mh_p_cbcl__dsm__opp_sum . . . 236
compute_mh_p_cbcl__dsm__opp_tscore . . . 237
compute_mh_p_cbcl__dsm__somat_sum . . . 239
compute_mh_p_cbcl__dsm__somat_tscore . . . 240
compute_mh_p_cbcl__ocd_sum . . . 242
compute_mh_p_cbcl__ocd_tscore . . . 243
compute_mh_p_cbcl__sct_sum . . . 245
compute_mh_p_cbcl__sct_tscore . . . 246

compute_mh_p_cbcl__strs_sum . . . 247
compute_mh_p_cbcl__strs_tscore . . . 249
compute_mh_p_cbcl__synd__aggr_sum . . . 251
compute_mh_p_cbcl__synd__aggr_tscore . . . 252
compute_mh_p_cbcl__synd__anxdep_sum . . . 254
compute_mh_p_cbcl__synd__anxdep_tscore . . . 255
compute_mh_p_cbcl__synd__attn_sum . . . 257
compute_mh_p_cbcl__synd__attn_tscore . . . 259
compute_mh_p_cbcl__synd__ext_sum . . . 260
compute_mh_p_cbcl__synd__ext_tscore . . . 262
compute_mh_p_cbcl__synd__int_sum . . . 264
compute_mh_p_cbcl__synd__int_tscore . . . 266
compute_mh_p_cbcl__synd__othpr_sum . . . 268
compute_mh_p_cbcl__synd__rule_sum . . . 270
compute_mh_p_cbcl__synd__rule_tscore . . . 271
compute_mh_p_cbcl__synd__soc_sum . . . 273
compute_mh_p_cbcl__synd__soc_tscore . . . 275
compute_mh_p_cbcl__synd__som_sum . . . 276
compute_mh_p_cbcl__synd__som_tscore . . . 278
compute_mh_p_cbcl__synd__tho_sum . . . 279
compute_mh_p_cbcl__synd__tho_tscore . . . 281
compute_mh_p_cbcl__synd__wthdep_sum . . . 283
compute_mh_p_cbcl__synd__wthdep_tscore . . . 284
compute_mh_p_cbcl_all . . . 286
compute_mh_p_cbcl_sum . . . 286
compute_mh_p_cbcl_tscore . . . 290
compute_mh_p_ders__attun_nm . . . 294
compute_mh_p_ders__catast_nm . . . 296
compute_mh_p_ders__distract_nm . . . 297
compute_mh_p_ders__negscnd_nm . . . 298
compute_mh_p_ders_all . . . 299
compute_mh_p_eatq__actv_nm . . . 300
compute_mh_p_eatq__affl_nm . . . 301
compute_mh_p_eatq__aggr_nm . . . 302
compute_mh_p_eatq__attn_nm . . . 303
compute_mh_p_eatq__depm_nm . . . 304
compute_mh_p_eatq__fear_nm . . . 305
compute_mh_p_eatq__frust_nm . . . 306
compute_mh_p_eatq__inhib_nm . . . 307
compute_mh_p_eatq__shy_nm . . . 308
compute_mh_p_eatq__ss__efcon_mean . . . 309
compute_mh_p_eatq__ss__efcon_nm . . . 310
compute_mh_p_eatq__ss__negaff_mean . . . 312
compute_mh_p_eatq__ss__negaff_nm . . . 313
compute_mh_p_eatq__ss__surg_mean . . . 315
compute_mh_p_eatq__ss__surg_nm . . . 316
compute_mh_p_eatq__surg_nm . . . 317
compute_mh_p_eatq_all . . . 318

compute_mh_p_famhx_all . . . 319
compute_mh_p_gbi_all . . . 320
compute_mh_p_gbi_sum . . . 320
compute_mh_p_ksads__adhd_all . . . 321
compute_mh_p_ksads__agor_all . . . 322
compute_mh_p_ksads__asd_all . . . 322
compute_mh_p_ksads__bpd_all . . . 323
compute_mh_p_ksads__cond_all . . . 323
compute_mh_p_ksads__dep_all . . . 324
compute_mh_p_ksads__dmdd_all . . . 324
compute_mh_p_ksads__ed_all . . . 325
compute_mh_p_ksads__gad_all . . . 325
compute_mh_p_ksads__hom_all . . . 326
compute_mh_p_ksads__ocd_all . . . 326
compute_mh_p_ksads__odd_all . . . 327
compute_mh_p_ksads__panic_all . . . 327
compute_mh_p_ksads__phobia_all . . . 328
compute_mh_p_ksads__psych_all . . . 328
compute_mh_p_ksads__ptsd_all . . . 329
compute_mh_p_ksads__sepanx_all . . . 329
compute_mh_p_ksads__sleep_all . . . 330
compute_mh_p_ksads__socanx_all . . . 330
compute_mh_p_ksads__suic_all . . . 331
compute_mh_p_ksads__tic_all . . . 331
compute_mh_p_ple__exp__bad_count . . . 332
compute_mh_p_ple__exp__bad_count__v01 . . . 333
compute_mh_p_ple__exp__bad_count__v02 . . . 335
compute_mh_p_ple__exp__bad_count__v03 . . . 336
compute_mh_p_ple__exp__bad_count__v04 . . . 338
compute_mh_p_ple__exp__good_count . . . 340
compute_mh_p_ple__exp__good_count__v01 . . . 341
compute_mh_p_ple__exp__good_count__v02 . . . 343
compute_mh_p_ple__exp__good_count__v03 . . . 344
compute_mh_p_ple__exp__good_count__v04 . . . 346
compute_mh_p_ple__exp_nm . . . 348
compute_mh_p_ple__exp_nm__v01 . . . 349
compute_mh_p_ple__exp_nm__v02 . . . 351
compute_mh_p_ple__exp_nm__v03 . . . 352
compute_mh_p_ple__exp_nm__v04 . . . 354
compute_mh_p_ple__severity__bad_mean . . . 355
compute_mh_p_ple__severity__bad_mean__v01 . . . 357
compute_mh_p_ple__severity__bad_mean__v02 . . . 360
compute_mh_p_ple__severity__bad_mean__v03 . . . 363
compute_mh_p_ple__severity__bad_mean__v04 . . . 365
compute_mh_p_ple__severity__bad_sum . . . 367
compute_mh_p_ple__severity__bad_sum__v01 . . . 369
compute_mh_p_ple__severity__bad_sum__v02 . . . 372
compute_mh_p_ple__severity__bad_sum__v03 . . . 374

compute_mh_p_ple__severity__bad_sum__v04 . . . 377
compute_mh_p_ple__severity__good_mean . . . 379
compute_mh_p_ple__severity__good_mean__v01 . . . 381
compute_mh_p_ple__severity__good_mean__v02 . . . 383
compute_mh_p_ple__severity__good_mean__v03 . . . 386
compute_mh_p_ple__severity__good_mean__v04 . . . 388
compute_mh_p_ple__severity__good_sum . . . 390
compute_mh_p_ple__severity_mean . . . 392
compute_mh_p_ple__severity_mean__v01 . . . 394
compute_mh_p_ple__severity_mean__v02 . . . 395
compute_mh_p_ple__severity_mean__v03 . . . 397
compute_mh_p_ple__severity_mean__v04 . . . 399
compute_mh_p_ple__severity_nm . . . 400
compute_mh_p_ple__severity_nm__v01 . . . 402
compute_mh_p_ple__severity_nm__v02 . . . 404
compute_mh_p_ple__severity_nm__v03 . . . 405
compute_mh_p_ple__severity_nm__v04 . . . 407
compute_mh_p_ple_all . . . 408
compute_mh_p_ple_nm . . . 409
compute_mh_p_ple_nm__v01 . . . 410
compute_mh_p_ple_nm__v02 . . . 412
compute_mh_p_ple_nm__v03 . . . 413
compute_mh_p_ple_nm__v04 . . . 415
compute_mh_p_ssrs_all . . . 416
compute_mh_p_ssrs_sum . . . 417
compute_mh_t_bpm__attn_sum . . . 418
compute_mh_t_bpm__attn_tscore . . . 419
compute_mh_t_bpm__ext_sum . . . 421
compute_mh_t_bpm__ext_tscore . . . 422
compute_mh_t_bpm__int_sum . . . 424
compute_mh_t_bpm__int_tscore . . . 425
compute_mh_t_bpm_all . . . 426
compute_mh_t_bpm_sum . . . 427
compute_mh_t_bpm_tscore . . . 428
compute_mh_y_bisbas__bas__dr_sum . . . 430
compute_mh_y_bisbas__bas__fs_sum . . . 431
compute_mh_y_bisbas__bas__rr_sum . . . 433
compute_mh_y_bisbas__bas__rr_sum__v01 . . . 434
compute_mh_y_bisbas__bis_sum . . . 435
compute_mh_y_bisbas__bis_sum__v01 . . . 436
compute_mh_y_bisbas_all . . . 438
compute_mh_y_bpm__attn_sum . . . 438
compute_mh_y_bpm__attn_tscore . . . 440
compute_mh_y_bpm__ext_sum . . . 441
compute_mh_y_bpm__ext_tscore . . . 442
compute_mh_y_bpm__int_sum . . . 444
compute_mh_y_bpm__int_tscore . . . 445
compute_mh_y_bpm_all . . . 447

compute_mh_y_bpm_sum . . . 447
compute_mh_y_bpm_tscore . . . 449
compute_mh_y_erq__reapp_nm . . . 451
compute_mh_y_erq__suppr_nm . . . 452
compute_mh_y_erq_all . . . 453
compute_mh_y_ksads__bpd_all . . . 454
compute_mh_y_ksads__cond_all . . . 454
compute_mh_y_ksads__dep_all . . . 455
compute_mh_y_ksads__dmdd_all . . . 455
compute_mh_y_ksads__ed_all . . . 456
compute_mh_y_ksads__gad_all . . . 456
compute_mh_y_ksads__ocd_all . . . 457
compute_mh_y_ksads__panic_all . . . 457
compute_mh_y_ksads__ptsd_all . . . 458
compute_mh_y_ksads__sleep_all . . . 458
compute_mh_y_ksads__socanx_all . . . 459
compute_mh_y_ksads__suic_all . . . 459
compute_mh_y_pai_all . . . 460
compute_mh_y_pai_sum . . . 460
compute_mh_y_peq__overt__agg_sum . . . 462
compute_mh_y_peq__overt__vict_sum . . . 463
compute_mh_y_peq__rel__agg_sum . . . 464
compute_mh_y_peq__rel__vict_sum . . . 465
compute_mh_y_peq__rep__agg_sum . . . 466
compute_mh_y_peq__rep__vict_sum . . . 468
compute_mh_y_peq_all . . . 469
compute_mh_y_ple__exp__bad_count . . . 470
compute_mh_y_ple__exp__bad_count__v01 . . . 471
compute_mh_y_ple__exp__bad_count__v02 . . . 473
compute_mh_y_ple__exp__bad_count__v03 . . . 474
compute_mh_y_ple__exp__good_count . . . 476
compute_mh_y_ple__exp__good_count__v01 . . . 478
compute_mh_y_ple__exp__good_count__v02 . . . 479
compute_mh_y_ple__exp__good_count__v03 . . . 481
compute_mh_y_ple__exp_nm . . . 483
compute_mh_y_ple__exp_nm__v01 . . . 484
compute_mh_y_ple__exp_nm__v02 . . . 486
compute_mh_y_ple__exp_nm__v03 . . . 487
compute_mh_y_ple__severity__bad_mean . . . 489
compute_mh_y_ple__severity__bad_mean__v01 . . . 491
compute_mh_y_ple__severity__bad_mean__v02 . . . 494
compute_mh_y_ple__severity__bad_mean__v03 . . . 496
compute_mh_y_ple__severity__bad_sum . . . 499
compute_mh_y_ple__severity__bad_sum__v01 . . . 501
compute_mh_y_ple__severity__bad_sum__v02 . . . 503
compute_mh_y_ple__severity__bad_sum__v03 . . . 506
compute_mh_y_ple__severity__good_mean . . . 508
compute_mh_y_ple__severity__good_mean__v01 . . . 511

compute_mh_y_ple__severity__good_mean__v02 . . . 513
compute_mh_y_ple__severity__good_mean__v03 . . . 516
compute_mh_y_ple__severity_mean . . . 518
compute_mh_y_ple__severity_mean__v01 . . . 520
compute_mh_y_ple__severity_mean__v02 . . . 521
compute_mh_y_ple__severity_mean__v03 . . . 523
compute_mh_y_ple__severity_nm . . . 525
compute_mh_y_ple__severity_nm__v01 . . . 526
compute_mh_y_ple__severity_nm__v02 . . . 528
compute_mh_y_ple__severity_nm__v03 . . . 530
compute_mh_y_ple_all . . . 531
compute_mh_y_ple_nm . . . 532
compute_mh_y_ple_nm__v01 . . . 533
compute_mh_y_ple_nm__v02 . . . 535
compute_mh_y_ple_nm__v03 . . . 536
compute_mh_y_pps__bother__no_count . . . 538
compute_mh_y_pps__bother__yes_count . . . 540
compute_mh_y_pps__dist__curr_score . . . 541
compute_mh_y_pps__dist__pers_score . . . 542
compute_mh_y_pps__severity_mean . . . 543
compute_mh_y_pps__severity_score . . . 546
compute_mh_y_pps_all . . . 547
compute_mh_y_pps_nm . . . 548
compute_mh_y_ppsss__dist__curr_count . . . 550
compute_mh_y_ppsss__dist__curr_ever . . . 551
compute_mh_y_ppsss__dist__curr_first . . . 551
compute_mh_y_ppsss__dist__pers_count . . . 552
compute_mh_y_ppsss__dist__pers_ever . . . 553
compute_mh_y_ppsss__dist__pers_first . . . 554
compute_mh_y_ppsss_all . . . 555
compute_mh_y_sup_all . . . 555
compute_mh_y_sup_sum . . . 556
compute_mh_y_upps__nurg_sum . . . 557
compute_mh_y_upps__pers_sum . . . 558
compute_mh_y_upps__plan_sum . . . 559
compute_mh_y_upps__purg_sum . . . 561
compute_mh_y_upps__sens_sum . . . 562
compute_mh_y_upps_all . . . 563
compute_mh_y_ysr__dsm__adhd_sum . . . 564
compute_mh_y_ysr__dsm__adhd_tscore . . . 565
compute_mh_y_ysr__dsm__anx_sum . . . 567
compute_mh_y_ysr__dsm__anx_tscore . . . 568
compute_mh_y_ysr__dsm__cond_sum . . . 570
compute_mh_y_ysr__dsm__cond_tscore . . . 571
compute_mh_y_ysr__dsm__dep_sum . . . 573
compute_mh_y_ysr__dsm__dep_tscore . . . 575
compute_mh_y_ysr__dsm__opp_sum . . . 576
compute_mh_y_ysr__dsm__opp_tscore . . . 577

compute_mh_y_ysr__dsm__somat_sum . . . 579
compute_mh_y_ysr__dsm__somat_tscore . . . 580
compute_mh_y_ysr__pos_sum . . . 582
compute_mh_y_ysr__pos_tscore . . . 583
compute_mh_y_ysr__synd__aggr_sum . . . 585
compute_mh_y_ysr__synd__aggr_tscore . . . 586
compute_mh_y_ysr__synd__anxdep_sum . . . 588
compute_mh_y_ysr__synd__anxdep_tscore . . . 590
compute_mh_y_ysr__synd__attn_sum . . . 591
compute_mh_y_ysr__synd__attn_tscore . . . 593
compute_mh_y_ysr__synd__ext_sum . . . 594
compute_mh_y_ysr__synd__ext_tscore . . . 596
compute_mh_y_ysr__synd__int_sum . . . 598
compute_mh_y_ysr__synd__int_tscore . . . 600
compute_mh_y_ysr__synd__othpr_sum . . . 602
compute_mh_y_ysr__synd__rule_sum . . . 604
compute_mh_y_ysr__synd__rule_tscore . . . 605
compute_mh_y_ysr__synd__soc_sum . . . 607
compute_mh_y_ysr__synd__soc_tscore . . . 608
compute_mh_y_ysr__synd__som_sum . . . 610
compute_mh_y_ysr__synd__som_tscore . . . 611
compute_mh_y_ysr__synd__tho_sum . . . 613
compute_mh_y_ysr__synd__tho_tscore . . . 614
compute_mh_y_ysr__synd__wthdep_sum . . . 616
compute_mh_y_ysr__synd__wthdep_tscore . . . 617
compute_mh_y_ysr_all . . . 619
compute_mh_y_ysr_sum . . . 620
compute_mh_y_ysr_tscore . . . 623
compute_nc_p_bdefs__sympt_count . . . 627
compute_nc_p_bdefs_all . . . 628
compute_nc_p_bdefs_nm . . . 629
compute_nc_y_ehis_all . . . 630
compute_nc_y_ehis_nm . . . 631
compute_nt_p_yst__pmum_nm . . . 632
compute_nt_p_yst__screen__wkdy_nm . . . 633
compute_nt_p_yst__screen__wknd_nm . . . 634
compute_nt_p_yst_all . . . 635
compute_nt_y_stq__screen__wkdy_nm . . . 635
compute_nt_y_stq__screen__wknd_nm . . . 637
compute_nt_y_stq_all . . . 638
compute_ph_meds_catg_all . . . 639
compute_ph_meds_estuse_flags_all . . . 641
compute_ph_p_anthr__fath_height__cm . . . 642
compute_ph_p_anthr__moth_height__cm . . . 643
compute_ph_p_anthr__moth_height__in . . . 644
compute_ph_p_anthr_all . . . 645
compute_ph_p_cna_all . . . 646
compute_ph_p_cna_nm . . . 647

compute_ph_p_otbi__loc__30m_nm . . . 648
compute_ph_p_otbi__loc__tbiage_nm . . . 649
compute_ph_p_otbi__loc_nm . . . 650
compute_ph_p_otbi__rpt_nm . . . 651
compute_ph_p_otbi_all . . . 652
compute_ph_p_pds__f__categ_nm . . . 652
compute_ph_p_pds__f_nm . . . 653
compute_ph_p_pds__m__categ_nm . . . 654
compute_ph_p_pds__m_nm . . . 655
compute_ph_p_pds_all . . . 656
compute_ph_p_sds__da_nm . . . 657
compute_ph_p_sds__dims_nm . . . 658
compute_ph_p_sds__does_nm . . . 659
compute_ph_p_sds__hyphy_nm . . . 660
compute_ph_p_sds__sbd_nm . . . 661
compute_ph_p_sds__swtd_nm . . . 662
compute_ph_p_sds_all . . . 663
compute_ph_p_sds_nm . . . 663
compute_ph_y_anthr__height_nm . . . 665
compute_ph_y_anthr__weight_nm . . . 666
compute_ph_y_anthr_all . . . 667
compute_ph_y_bp__dia_nm . . . 667
compute_ph_y_bp__hrate_nm . . . 669
compute_ph_y_bp__sys_nm . . . 670
compute_ph_y_bp_all . . . 671
compute_ph_y_mctq__fd__bed__end__24h_t . . . 672
compute_ph_y_mctq__fd__bed__end__36h_t . . . 673
compute_ph_y_mctq__fd__bed__start__24h_t . . . 674
compute_ph_y_mctq__fd__bed__start__36h_t . . . 675
compute_ph_y_mctq__fd__bed_sum . . . 676
compute_ph_y_mctq__fd__sleep__end__24h_t . . . 677
compute_ph_y_mctq__fd__sleep__end__36h_t . . . 678
compute_ph_y_mctq__fd__sleep__mid__24h_t . . . 679
compute_ph_y_mctq__fd__sleep__mid__36h_t . . . 680
compute_ph_y_mctq__fd__sleep__onset__24h_t . . . 681
compute_ph_y_mctq__fd__sleep__onset__36h_t . . . 682
compute_ph_y_mctq__fd__sleep__start__24h_t . . . 683
compute_ph_y_mctq__fd__sleep__start__36h_t . . . 684
compute_ph_y_mctq__fd__sleep__waso_sum . . . 685
compute_ph_y_mctq__fd__sleep_dur . . . 686
compute_ph_y_mctq__fd__sleep_inertia . . . 687
compute_ph_y_mctq__fd__sleep_latent . . . 688
compute_ph_y_mctq__fd__sleep_period . . . 689
compute_ph_y_mctq__fd_count . . . 690
compute_ph_y_mctq__raw__36h_chrono . . . 691
compute_ph_y_mctq__school__leave__24h_t . . . 692
compute_ph_y_mctq__school__leave__36h_t . . . 693
compute_ph_y_mctq__school__start__24h_t . . . 694

compute_ph_y_mctq__school__start__36h_t . . . 695
compute_ph_y_mctq__sd__bed__end__24h_t . . . 697
compute_ph_y_mctq__sd__bed__end__36h_t . . . 698
compute_ph_y_mctq__sd__bed__start__24h_t . . . 699
compute_ph_y_mctq__sd__bed__start__36h_t . . . 700
compute_ph_y_mctq__sd__bed_sum . . . 701
compute_ph_y_mctq__sd__sleep__end__24h_t . . . 702
compute_ph_y_mctq__sd__sleep__end__36h_t . . . 703
compute_ph_y_mctq__sd__sleep__mid__24h_t . . . 704
compute_ph_y_mctq__sd__sleep__mid__36h_t . . . 705
compute_ph_y_mctq__sd__sleep__onset__24h_t . . . 706
compute_ph_y_mctq__sd__sleep__onset__36h_t . . . 707
compute_ph_y_mctq__sd__sleep__start__24h_t . . . 708
compute_ph_y_mctq__sd__sleep__start__36h_t . . . 709
compute_ph_y_mctq__sd__sleep__waso_sum . . . 710
compute_ph_y_mctq__sd__sleep_dur . . . 711
compute_ph_y_mctq__sd__sleep_inertia . . . 712
compute_ph_y_mctq__sd__sleep_latent . . . 713
compute_ph_y_mctq__sd__sleep_period . . . 714
compute_ph_y_mctq__sd_count . . . 715
compute_ph_y_mctq__sleep_dur . . . 716
compute_ph_y_mctq__sleep_loss . . . 718
compute_ph_y_mctq__sleep_period . . . 719
compute_ph_y_mctq__socjl_absl . . . 720
compute_ph_y_mctq__socjl_rel . . . 721
compute_ph_y_mctq_all . . . 722
compute_ph_y_mctq_chrono . . . 722
compute_ph_y_mctq_outlier . . . 723
compute_ph_y_pds__f__categ_nm . . . 724
compute_ph_y_pds__f_nm . . . 725
compute_ph_y_pds__m__categ_nm . . . 726
compute_ph_y_pds__m_nm . . . 727
compute_ph_y_pds_all . . . 728
compute_ss_use_onset_age . . . 729
compute_ss_use_onset_event . . . 731
compute_ss_use_yn . . . 733
compute_su_p_ksads__aud_all . . . 736
compute_su_p_ksads__dud_all . . . 736
compute_su_y_alcexp__neg_nm . . . 737
compute_su_y_alcexp__pos_nm . . . 738
compute_su_y_alcexp_all . . . 739
compute_su_y_alchss_all . . . 739
compute_su_y_alchss_count . . . 740
compute_su_y_alchss_nm . . . 741
compute_su_y_alcprob_all . . . 743
compute_su_y_alcprob_nm . . . 744
compute_su_y_alcsre__6mo_count . . . 745
compute_su_y_alcsre__6mo_nm . . . 746

compute_su_y_alcsre__first5_count . . . 747
compute_su_y_alcsre__first5_nm . . . 748
compute_su_y_alcsre__hvy_count . . . 749
compute_su_y_alcsre__hvy_nm . . . 750
compute_su_y_alcsre_all . . . 750
compute_su_y_cigexp__neg_nm . . . 751
compute_su_y_cigexp__neg_prsum__v01 . . . 752
compute_su_y_cigexp__pos_nm . . . 753
compute_su_y_cigexp__pos_prsum__v01 . . . 754
compute_su_y_cigexp_all . . . 755
compute_su_y_drgprob_all . . . 755
compute_su_y_drgprob_nm . . . 756
compute_su_y_ksads__aud_all . . . 757
compute_su_y_ksads__dud_all . . . 758
compute_su_y_mjexp__neg_nm . . . 758
compute_su_y_mjexp__pos_nm . . . 759
compute_su_y_mjexp_all . . . 760
compute_su_y_mjprob_all . . . 760
compute_su_y_mjprob_nm . . . 761
compute_su_y_mjsre__neg_nm . . . 762
compute_su_y_mjsre__pos_nm . . . 763
compute_su_y_mjsre_all . . . 764
compute_su_y_mjsre_nm . . . 764
compute_su_y_nicsre__chew_nm . . . 765
compute_su_y_nicsre__cig_nm . . . 766
compute_su_y_nicsre__vape_nm . . . 767
compute_su_y_nicsre_all . . . 768
compute_su_y_nicvapeexp__neg_nm . . . 768
compute_su_y_nicvapeexp__pos_nm . . . 769
compute_su_y_nicvapeexp_all . . . 770
compute_su_y_sui__last__day_count . . . 771
compute_su_y_sui__reg_useage . . . 772
compute_tlfb_dt . . . 774
compute_tlfb_maxdose . . . 777
compute_tlfb_mean . . . 779
compute_tlfb_totdose . . . 781
compute_tlfb_totdose_sum . . . 784
compute_tlfb_ud . . . 786
convert_time_mctq . . . 788
create_session_num . . . 790
filter_tlfb . . . 791
get_tscore_tbl . . . 793
make_static . . . 794
md_bullet . . . 795
recode_levels . . . 796
ss_count . . . 797
ss_count_cond . . . 800
ss_max . . . 800

ss_mean . . . 802
ss_mean_pos . . . 803
ss_nm . . . 805
ss_prsum . . . 806
ss_sum . . . 808
ss_tscore . . . 809
sui_substances . . . 812
tlfb_substances . . . 814
vars_ab_g_dyn__cohort_edu__cgs . . . 816
vars_ab_g_dyn__cohort_income__hhold__6lvl . . . 817
vars_ab_g_dyn__cohort_prtnrshp__employ . . . 818
vars_ab_g_stc__cohort_ethn . . . 819
vars_ab_g_stc__cohort_ethnrace__leg . . . 820
vars_ab_g_stc__cohort_ethnrace__mblack . . . 822
vars_ab_g_stc__cohort_ethnrace__meim . . . 824
vars_ab_g_stc__cohort_ethnrace__mhisp . . . 825
vars_ab_g_stc__cohort_race__nih . . . 827
vars_ab_p_demo__ntvam . . . 828
vars_fc_p_fes__cohes . . . 830
vars_fc_p_fes__confl . . . 831
vars_fc_p_fes__expr . . . 832
vars_fc_p_fes__intelcult . . . 833
vars_fc_p_fes__org . . . 835
vars_fc_p_fes__rec . . . 836
vars_fc_p_meim . . . 837
vars_fc_p_meim__commattach . . . 838
vars_fc_p_meim__explor . . . 839
vars_fc_p_nce . . . 840
vars_fc_p_nce__cc . . . 841
vars_fc_p_nce__isc . . . 842
vars_fc_p_nsc__ns . . . 843
vars_fc_p_pk__knowl . . . 844
vars_fc_p_psb . . . 845
vars_fc_p_vs__famil . . . 846
vars_fc_p_vs__famil__v01 . . . 848
vars_fc_p_vs__indselfrel . . . 849
vars_fc_p_vs__obl . . . 851
vars_fc_p_vs__ref . . . 852
vars_fc_p_vs__relig . . . 853
vars_fc_p_vs__supp . . . 854
vars_fc_y_as__safe . . . 855
vars_fc_y_crpbi__cg1 . . . 856
vars_fc_y_crpbi__cg2 . . . 857
vars_fc_y_eut__ethn . . . 858
vars_fc_y_fes__cohes . . . 859
vars_fc_y_fes__confl . . . 861
vars_fc_y_lone . . . 862
vars_fc_y_meim . . . 863

vars_fc_y_meim__commattach . . . 864
vars_fc_y_meim__explor . . . 865
vars_fc_y_mnbs . . . 866
vars_fc_y_mnbs__edusupp . . . 867
vars_fc_y_mnbs__superv . . . 868
vars_fc_y_naa . . . 869
vars_fc_y_pm . . . 870
vars_fc_y_pnh . . . 871
vars_fc_y_psb . . . 872
vars_fc_y_rpi . . . 873
vars_fc_y_srpf__dis . . . 874
vars_fc_y_srpf__env . . . 875
vars_fc_y_srpf__involv . . . 876
vars_fc_y_vs__famil . . . 878
vars_fc_y_vs__famil__v01 . . . 879
vars_fc_y_vs__indselfrel . . . 880
vars_fc_y_vs__obl . . . 882
vars_fc_y_vs__ref . . . 883
vars_fc_y_vs__relig . . . 884
vars_fc_y_vs__supp . . . 885
vars_fc_y_wpss . . . 886
vars_mh_p_abcl . . . 887
vars_mh_p_abcl__afs__frnd . . . 891
vars_mh_p_abcl__cg2 . . . 892
vars_mh_p_abcl__critic . . . 893
vars_mh_p_abcl__dsm__adhd . . . 895
vars_mh_p_abcl__dsm__antsoc . . . 896
vars_mh_p_abcl__dsm__anx . . . 898
vars_mh_p_abcl__dsm__avoid . . . 899
vars_mh_p_abcl__dsm__dep . . . 900
vars_mh_p_abcl__dsm__somat . . . 902
vars_mh_p_abcl__su . . . 903
vars_mh_p_abcl__su__drg . . . 905
vars_mh_p_abcl__su__drunk . . . 906
vars_mh_p_abcl__su__nic . . . 907
vars_mh_p_abcl__synd__aggr . . . 908
vars_mh_p_abcl__synd__anxdep . . . 910
vars_mh_p_abcl__synd__attn . . . 911
vars_mh_p_abcl__synd__ext . . . 913
vars_mh_p_abcl__synd__int . . . 915
vars_mh_p_abcl__synd__intru . . . 917
vars_mh_p_abcl__synd__othpr . . . 918
vars_mh_p_abcl__synd__rule . . . 920
vars_mh_p_abcl__synd__som . . . 921
vars_mh_p_abcl__synd__tho . . . 923
vars_mh_p_abcl__synd__wthdr . . . 924
vars_mh_p_asr . . . 926
vars_mh_p_asr__afs__strng . . . 930

vars_mh_p_asr__critic . . . 931
vars_mh_p_asr__dsm__adhd . . . 933
vars_mh_p_asr__dsm__adhd__hypimp . . . 934
vars_mh_p_asr__dsm__adhd__inatt . . . 935
vars_mh_p_asr__dsm__antsoc . . . 937
vars_mh_p_asr__dsm__anx . . . 938
vars_mh_p_asr__dsm__avoid . . . 940
vars_mh_p_asr__dsm__dep . . . 941
vars_mh_p_asr__dsm__somat . . . 943
vars_mh_p_asr__synd__aggr . . . 944
vars_mh_p_asr__synd__anxdep . . . 945
vars_mh_p_asr__synd__attn . . . 947
vars_mh_p_asr__synd__ext . . . 948
vars_mh_p_asr__synd__int . . . 950
vars_mh_p_asr__synd__intru . . . 953
vars_mh_p_asr__synd__othpr . . . 954
vars_mh_p_asr__synd__rule . . . 956
vars_mh_p_asr__synd__som . . . 957
vars_mh_p_asr__synd__tho . . . 959
vars_mh_p_asr__synd__wthdr . . . 960
vars_mh_p_cbcl . . . 961
vars_mh_p_cbcl__dsm__adhd . . . 965
vars_mh_p_cbcl__dsm__anx . . . 967
vars_mh_p_cbcl__dsm__cond . . . 968
vars_mh_p_cbcl__dsm__dep . . . 970
vars_mh_p_cbcl__dsm__opp . . . 971
vars_mh_p_cbcl__dsm__somat . . . 972
vars_mh_p_cbcl__ocd . . . 974
vars_mh_p_cbcl__sct . . . 975
vars_mh_p_cbcl__strs . . . 976
vars_mh_p_cbcl__synd__aggr . . . 978
vars_mh_p_cbcl__synd__anxdep . . . 980
vars_mh_p_cbcl__synd__attn . . . 981
vars_mh_p_cbcl__synd__ext . . . 982
vars_mh_p_cbcl__synd__int . . . 984
vars_mh_p_cbcl__synd__othpr . . . 986
vars_mh_p_cbcl__synd__rule . . . 988
vars_mh_p_cbcl__synd__soc . . . 990
vars_mh_p_cbcl__synd__som . . . 991
vars_mh_p_cbcl__synd__tho . . . 992
vars_mh_p_cbcl__synd__wthdep . . . 994
vars_mh_p_ders__attun . . . 995
vars_mh_p_ders__catast . . . 997
vars_mh_p_ders__distract . . . 998
vars_mh_p_ders__negscnd . . . 1000
vars_mh_p_eatq__actv . . . 1001
vars_mh_p_eatq__affl . . . 1002
vars_mh_p_eatq__aggr . . . 1004

vars_mh_p_eatq__attn . . . 1005
vars_mh_p_eatq__depm . . . 1006
vars_mh_p_eatq__fear . . . 1008
vars_mh_p_eatq__frust . . . 1009
vars_mh_p_eatq__inhib . . . 1011
vars_mh_p_eatq__shy . . . 1012
vars_mh_p_eatq__surg . . . 1013
vars_mh_p_famhx__alc__moth__fath_indicator . . . 1015
vars_mh_p_famhx__alc__moth__fath_score . . . 1016
vars_mh_p_famhx__dep__moth__fath_indicator . . . 1017
vars_mh_p_famhx__dep__moth__fath_score . . . 1018
vars_mh_p_famhx__doc__moth__fath_indicator . . . 1019
vars_mh_p_famhx__doc__moth__fath_score . . . 1020
vars_mh_p_famhx__drg__moth__fath_indicator . . . 1021
vars_mh_p_famhx__drg__moth__fath_score . . . 1022
vars_mh_p_famhx__halluc__moth__fath_indicator . . . 1023
vars_mh_p_famhx__halluc__moth__fath_score . . . 1024
vars_mh_p_famhx__hosp__moth__fath_indicator . . . 1025
vars_mh_p_famhx__hosp__moth__fath_score . . . 1026
vars_mh_p_famhx__mania__moth__fath_indicator . . . 1028
vars_mh_p_famhx__mania__moth__fath_score . . . 1029
vars_mh_p_famhx__nerve__moth__fath_indicator . . . 1030
vars_mh_p_famhx__nerve__moth__fath_score . . . 1031
vars_mh_p_famhx__suic__moth__fath_indicator . . . 1032
vars_mh_p_famhx__suic__moth__fath_score . . . 1033
vars_mh_p_famhx__troub__moth__fath_indicator . . . 1034
vars_mh_p_famhx__troub__moth__fath_score . . . 1035
vars_mh_p_gbi . . . 1036
vars_mh_p_ksads__adhd__past__sx . . . 1038
vars_mh_p_ksads__adhd__pres__sx . . . 1039
vars_mh_p_ksads__agor__past__sx . . . 1041
vars_mh_p_ksads__agor__pres__sx . . . 1042
vars_mh_p_ksads__asd__past__sx . . . 1044
vars_mh_p_ksads__asd__pres__sx . . . 1045
vars_mh_p_ksads__bpd__past__sx . . . 1047
vars_mh_p_ksads__bpd__pres__sx . . . 1048
vars_mh_p_ksads__cond__past__sx . . . 1050
vars_mh_p_ksads__cond__pres__sx . . . 1052
vars_mh_p_ksads__dep__past__sx . . . 1053
vars_mh_p_ksads__dep__pres__sx . . . 1055
vars_mh_p_ksads__dmdd__sx . . . 1057
vars_mh_p_ksads__ed__past__sx . . . 1058
vars_mh_p_ksads__ed__pres__sx . . . 1059
vars_mh_p_ksads__gad__past__sx . . . 1061
vars_mh_p_ksads__gad__pres__sx . . . 1062
vars_mh_p_ksads__hom__past__sx . . . 1064
vars_mh_p_ksads__hom__pres__sx . . . 1065
vars_mh_p_ksads__ocd__past__sx . . . 1066

vars_mh_p_ksads__ocd__pres__sx . . . 1068
vars_mh_p_ksads__odd__past__sx . . . 1069
vars_mh_p_ksads__odd__pres__sx . . . 1071
vars_mh_p_ksads__panic__past__sx . . . 1072
vars_mh_p_ksads__panic__pres__sx . . . 1073
vars_mh_p_ksads__phobia__past__sx . . . 1075
vars_mh_p_ksads__phobia__pres__sx . . . 1076
vars_mh_p_ksads__psych__past__sx . . . 1077
vars_mh_p_ksads__psych__pres__sx . . . 1079
vars_mh_p_ksads__ptsd__past__sx . . . 1080
vars_mh_p_ksads__ptsd__pres__sx . . . 1082
vars_mh_p_ksads__sepanx__past__sx . . . 1084
vars_mh_p_ksads__sepanx__pres__sx . . . 1085
vars_mh_p_ksads__sleep__past__sx . . . 1087
vars_mh_p_ksads__sleep__pres__sx . . . 1088
vars_mh_p_ksads__socanx__past__sx . . . 1089
vars_mh_p_ksads__socanx__pres__sx . . . 1091
vars_mh_p_ksads__suic__past__sx . . . 1092
vars_mh_p_ksads__suic__pres__sx . . . 1094
vars_mh_p_ksads__tic__past__sx . . . 1095
vars_mh_p_ksads__tic__pres__sx . . . 1097
vars_mh_p_ple . . . 1098
vars_mh_p_ple__exp__v01 . . . 1100
vars_mh_p_ple__exp__v02 . . . 1102
vars_mh_p_ple__exp__v03 . . . 1105
vars_mh_p_ple__exp__v04 . . . 1108
vars_mh_p_ple__severity . . . 1110
vars_mh_p_ple__severity__v01 . . . 1111
vars_mh_p_ple__severity__v02 . . . 1113
vars_mh_p_ple__severity__v03 . . . 1115
vars_mh_p_ple__severity__v04 . . . 1117
vars_mh_p_ple__v01 . . . 1118
vars_mh_p_ple__v02 . . . 1120
vars_mh_p_ple__v03 . . . 1122
vars_mh_p_ple__v04 . . . 1124
vars_mh_p_ssrs . . . 1125
vars_mh_t_bpm . . . 1126
vars_mh_t_bpm__attn . . . 1128
vars_mh_t_bpm__ext . . . 1129
vars_mh_t_bpm__int . . . 1130
vars_mh_y_bisbas__bas__dr . . . 1132
vars_mh_y_bisbas__bas__fs . . . 1133
vars_mh_y_bisbas__bas__rr . . . 1134
vars_mh_y_bisbas__bas__rr__v01 . . . 1135
vars_mh_y_bisbas__bis . . . 1137
vars_mh_y_bisbas__bis__v01 . . . 1138
vars_mh_y_bpm . . . 1139
vars_mh_y_bpm__attn . . . 1141

vars_mh_y_bpm__ext . . . 1142
vars_mh_y_bpm__int . . . 1143
vars_mh_y_erq__reapp . . . 1144
vars_mh_y_erq__suppr . . . 1146
vars_mh_y_ksads__bpd__past__sx . . . 1147
vars_mh_y_ksads__bpd__pres__sx . . . 1149
vars_mh_y_ksads__cond__past__sx . . . 1150
vars_mh_y_ksads__cond__pres__sx . . . 1152
vars_mh_y_ksads__dep__past__sx . . . 1154
vars_mh_y_ksads__dep__pres__sx . . . 1155
vars_mh_y_ksads__dmdd__sx . . . 1157
vars_mh_y_ksads__ed__past__sx . . . 1158
vars_mh_y_ksads__ed__pres__sx . . . 1160
vars_mh_y_ksads__gad__past__sx . . . 1161
vars_mh_y_ksads__gad__pres__sx . . . 1163
vars_mh_y_ksads__ocd__past__sx . . . 1164
vars_mh_y_ksads__ocd__pres__sx . . . 1165
vars_mh_y_ksads__panic__past__sx . . . 1167
vars_mh_y_ksads__panic__pres__sx . . . 1168
vars_mh_y_ksads__ptsd__past__sx . . . 1170
vars_mh_y_ksads__ptsd__pres__sx . . . 1172
vars_mh_y_ksads__sleep__past__sx . . . 1174
vars_mh_y_ksads__sleep__pres__sx . . . 1175
vars_mh_y_ksads__socanx__past__sx . . . 1176
vars_mh_y_ksads__socanx__pres__sx . . . 1178
vars_mh_y_ksads__suic__past__sx . . . 1179
vars_mh_y_ksads__suic__pres__sx . . . 1181
vars_mh_y_pai . . . 1182
vars_mh_y_peq__overt__agg . . . 1184
vars_mh_y_peq__overt__vict . . . 1185
vars_mh_y_peq__rel__agg . . . 1186
vars_mh_y_peq__rel__vict . . . 1187
vars_mh_y_peq__rep__agg . . . 1188
vars_mh_y_peq__rep__vict . . . 1190
vars_mh_y_ple . . . 1191
vars_mh_y_ple__exp . . . 1192
vars_mh_y_ple__exp__v01 . . . 1195
vars_mh_y_ple__exp__v02 . . . 1197
vars_mh_y_ple__exp__v03 . . . 1200
vars_mh_y_ple__severity . . . 1203
vars_mh_y_ple__severity__v01 . . . 1204
vars_mh_y_ple__severity__v02 . . . 1206
vars_mh_y_ple__severity__v03 . . . 1208
vars_mh_y_ple__v01 . . . 1210
vars_mh_y_ple__v02 . . . 1212
vars_mh_y_ple__v03 . . . 1214
vars_mh_y_pps__bother . . . 1216
vars_mh_y_pps__severity . . . 1217

vars_mh_y_pps_count . . . 1219
vars_mh_y_sup . . . 1221
vars_mh_y_upps__nurg . . . 1222
vars_mh_y_upps__pers . . . 1223
vars_mh_y_upps__plan . . . 1224
vars_mh_y_upps__purg . . . 1225
vars_mh_y_upps__sens . . . 1227
vars_mh_y_ysr . . . 1228
vars_mh_y_ysr__dsm__adhd . . . 1231
vars_mh_y_ysr__dsm__anx . . . 1233
vars_mh_y_ysr__dsm__cond . . . 1234
vars_mh_y_ysr__dsm__dep . . . 1236
vars_mh_y_ysr__dsm__opp . . . 1237
vars_mh_y_ysr__dsm__somat . . . 1238
vars_mh_y_ysr__pos . . . 1240
vars_mh_y_ysr__synd__aggr . . . 1241
vars_mh_y_ysr__synd__anxdep . . . 1243
vars_mh_y_ysr__synd__attn . . . 1244
vars_mh_y_ysr__synd__ext . . . 1246
vars_mh_y_ysr__synd__int . . . 1248
vars_mh_y_ysr__synd__othpr . . . 1249
vars_mh_y_ysr__synd__rule . . . 1251
vars_mh_y_ysr__synd__soc . . . 1252
vars_mh_y_ysr__synd__som . . . 1254
vars_mh_y_ysr__synd__tho . . . 1255
vars_mh_y_ysr__synd__wthdep . . . 1257
vars_nc_p_bdefs . . . 1258
vars_nc_y_ehis . . . 1260
vars_nt_p_yst__pmum . . . 1261
vars_nt_p_yst__screen__wkdy . . . 1262
vars_nt_p_yst__screen__wknd . . . 1263
vars_nt_y_stq__screen__wkdy . . . 1264
vars_nt_y_stq__screen__wknd . . . 1266
vars_ph_p_anthr__height . . . 1267
vars_ph_p_cna . . . 1268
vars_ph_p_dhx_birthweight . . . 1270
vars_ph_p_otbi . . . 1271
vars_ph_p_otbi__loc__30m_count . . . 1272
vars_ph_p_otbi__loc_before15 . . . 1274
vars_ph_p_otbi__loc_count . . . 1276
vars_ph_p_otbi__loc_tbiage . . . 1277
vars_ph_p_otbi__rpt_count . . . 1280
vars_ph_p_otbi_tbiworst . . . 1281
vars_ph_p_pds__f . . . 1283
vars_ph_p_pds__f_categ . . . 1284
vars_ph_p_pds__m . . . 1286
vars_ph_p_pds__m_categ . . . 1287
vars_ph_p_sds__da . . . 1288

vars_ph_p_sds__dims . . . 1289
vars_ph_p_sds__does . . . 1291
vars_ph_p_sds__hyphy . . . 1292
vars_ph_p_sds__sbd . . . 1293
vars_ph_p_sds__swtd . . . 1295
vars_ph_p_sds_sum . . . 1296
vars_ph_y_anthr__height . . . 1298
vars_ph_y_anthr__weight . . . 1299
vars_ph_y_bp__dia . . . 1301
vars_ph_y_bp__hrate . . . 1302
vars_ph_y_bp__sys . . . 1303
vars_ph_y_pds__f . . . 1304
vars_ph_y_pds__f_categ . . . 1305
vars_ph_y_pds__m . . . 1306
vars_ph_y_pds__m_categ . . . 1308
vars_su_p_ksads__aud__past__sx . . . 1309
vars_su_p_ksads__aud__pres__sx . . . 1310
vars_su_p_ksads__dud__coc__past__sx_mean . . . 1312
vars_su_p_ksads__dud__coc__pres__sx_mean . . . 1314
vars_su_p_ksads__dud__hall__past__sx_mean . . . 1315
vars_su_p_ksads__dud__hall__pres__sx_mean . . . 1317
vars_su_p_ksads__dud__mj__past__sx_mean . . . 1319
vars_su_p_ksads__dud__mj__pres__sx_mean . . . 1320
vars_su_p_ksads__dud__nic__past__sx_mean . . . 1322
vars_su_p_ksads__dud__nic__pres__sx_mean . . . 1324
vars_su_p_ksads__dud__opi__past__sx_mean . . . 1325
vars_su_p_ksads__dud__opi__pres__sx_mean . . . 1327
vars_su_p_ksads__dud__othdrg__past__sx_mean . . . 1329
vars_su_p_ksads__dud__othdrg__pres__sx_mean . . . 1330
vars_su_p_ksads__dud__past__sx_mean . . . 1332
vars_su_p_ksads__dud__pcp__past__sx_mean . . . 1334
vars_su_p_ksads__dud__pcp__pres__sx_mean . . . 1335
vars_su_p_ksads__dud__pres__sx_mean . . . 1337
vars_su_p_ksads__dud__sed__past__sx_mean . . . 1339
vars_su_p_ksads__dud__sed__pres__sx_mean . . . 1340
vars_su_p_ksads__dud__solv__past__sx_mean . . . 1342
vars_su_p_ksads__dud__solv__pres__sx_mean . . . 1344
vars_su_p_ksads__dud__stim__past__sx_mean . . . 1345
vars_su_p_ksads__dud__stim__pres__sx_mean . . . 1347
vars_su_y_alcexp__neg . . . 1349
vars_su_y_alcexp__pos . . . 1350
vars_su_y_alchss . . . 1351
vars_su_y_alcprob . . . 1352
vars_su_y_alcsre__6mo . . . 1354
vars_su_y_alcsre__first5 . . . 1355
vars_su_y_alcsre__hvy . . . 1356
vars_su_y_caff__coffee . . . 1357
vars_su_y_caff__energy . . . 1358

vars_su_y_caff__energy__drink 1359
vars_su_y_caff__energy__shot 1361
vars_su_y_caff__espres 1362
vars_su_y_caff__oth 1363
vars_su_y_caff__soda 1364
vars_su_y_caff__suppl 1365
vars_su_y_caff__tea 1366
vars_su_y_cigexp__neg 1367
vars_su_y_cigexp__pos 1368
vars_su_y_drgprob 1369
vars_su_y_ksads__aud__past__sx 1371
vars_su_y_ksads__aud__pres__sx 1372
vars_su_y_ksads__dud__coc__past__sx_mean 1374
vars_su_y_ksads__dud__coc__pres__sx_mean 1376
vars_su_y_ksads__dud__hall__past__sx_mean 1377
vars_su_y_ksads__dud__hall__pres__sx_mean 1379
vars_su_y_ksads__dud__mj__past__sx_mean 1381
vars_su_y_ksads__dud__mj__pres__sx_mean 1382
vars_su_y_ksads__dud__nic__past__sx_mean 1384
vars_su_y_ksads__dud__nic__pres__sx_mean 1386
vars_su_y_ksads__dud__opi__past__sx_mean 1387
vars_su_y_ksads__dud__opi__pres__sx_mean 1389
vars_su_y_ksads__dud__othdrg__past__sx_mean 1391
vars_su_y_ksads__dud__othdrg__pres__sx_mean 1392
vars_su_y_ksads__dud__past__sx_mean 1394
vars_su_y_ksads__dud__pcp__past__sx_mean 1396
vars_su_y_ksads__dud__pcp__pres__sx_mean 1397
vars_su_y_ksads__dud__pres__sx_mean 1399
vars_su_y_ksads__dud__sed__past__sx_mean 1401
vars_su_y_ksads__dud__sed__pres__sx_mean 1402
vars_su_y_ksads__dud__solv__past__sx_mean 1404
vars_su_y_ksads__dud__solv__pres__sx_mean 1406
vars_su_y_ksads__dud__stim__past__sx_mean 1407
vars_su_y_ksads__dud__stim__pres__sx_mean 1409
vars_su_y_mjexp__neg 1411
vars_su_y_mjexp__pos 1412
vars_su_y_mjprob 1413
vars_su_y_mjsre 1414
vars_su_y_mjsre__neg 1415
vars_su_y_mjsre__pos 1416
vars_su_y_nicsre__chew 1417
vars_su_y_nicsre__cig 1419
vars_su_y_nicsre__vape 1420
vars_su_y_nicvapeexp__neg 1421
vars_su_y_nicvapeexp__pos 1422

Index **1424**

check_assign_na *Check an output field and assign NA when input variables all have NAs*

Description

Checks the specified output column in a data frame and assigns NA to its value depending on the missingness of a set of input columns. If `allow_missingness = TRUE`, the output column is set to NA only when *all* the specified input columns are NA. If `allow_missingness = FALSE`, the output column is set to NA when *any* of the input columns are NA. This function is useful for propagating missingness from input variables to a derived output.

Usage

```
check_assign_na(data, output, input, allow_missingness = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`output`	character of length 1. The name of the first variable/column.
`input`	character. The name of the second variable/column.
`allow_missingness`	logical. Default set to TRUE. If TRUE, `output` field is set to `NA` only when ALL the fields in `input` have missingness. If FALSE, `output` is set to `NA` when ANY of the `input` fields have missingness.

Value

tbl. The input data frame with the `output` column modified.

Examples

```
# Example data
dat <- tibble::tibble(
  a = c(1, NA, 3),
  b = c(NA, NA, 2),
  c = c(1, 2, 3),
  out = c(10, 11, 12)
)

# Assign NA to out when all of a and b are NA
check_assign_na(
  dat,
  output = "out", input = c("a", "b"), allow_missingness = TRUE
)

# Assign NA to out when any of a and b are NA
check_assign_na(
```

```
  dat,
  output = "out", input = c("a", "b"), allow_missingness = FALSE
)
```

`combine_checkboxes` *Combine checkbox variables into a single list column*

Description

Takes a group of checkbox-style variables, have a common prefix and numeric suffixes representing options, and combines them into a single list column where each element is a vector of selected options (numbers).

This function expects the input data to include `participant_id` and `session_id` columns, which are used to group responses. For each participant and session, it collects all checkbox numbers that were selected as a single list. The resulting column can be renamed via the `name` parameter.

Usage

```
combine_checkboxes(data, var_basename, var_sep = "___", name = NULL)
```

Arguments

`data`	tbl. Data frame containing the participant responses.
`var_basename`	character of length 1. The base name of the checkbox field.
`var_sep`	character of length 1. The string separating the base name of the checkbox and the checkbox value. Default is `"___"`. In the default scenario, all checkbox columns to be collapsed are expected in the format, `{ var_basename }___{ value }`, where three underscores separate the checkbox basename and the checkbox value.
`name`	character of length 1 or `NULL`. Optional. The name of the output column that will store the combined checkbox selections. If `NULL`, the value of `var_basename` is used as the output column name.

Value

tbl. The input data frame with an additional column containing a list of integers corresponding to the selected checkbox options for each participant and session.

Examples

```
# Example data
dat <- tibble::tibble(
  participant_id = c(1, 1, 2),
  session_id = c(1, 2, 1),
  q1___1 = c(1, NA, 0),
  q1___2 = c(0, 1, 1),
```

```
  q1___3 = c(NA, NA, 0)
)

# Combine q1 checkboxes into a single list column
combine_checkboxes(dat, var_basename = "q1")

# Combine and rename the output column
combine_checkboxes(dat, var_basename = "q1", name = "q1_combined")
```

`combine_cols` *Combine columns*

Description

Combines two columns into one. The name of the first column is used for the new column, the second column is removed. Used for cases where different versions of the same variable exist that have to be combined before computing a summary score.

Usage

```
combine_cols(data, col_1, col_2, name = NULL, keep_other = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`col_1`	character. The name of the first variable/column.
`col_2`	character. The name of the second variable/column.
`name`	character. The name of the field with the combined data. By default, `name = NULL`, the combined data field is named the same as `col_1`.
`keep_other`	logical. Whether to combine the combined column with the input data frame (Default: TRUE).

Value

tbl. The input data frame with the combined column and the second column removed. The name of the combined column is the same as `col_1`, or user-specified in the `name` argument.

Examples

```
data <- tibble::tibble(
  var_id = c("A", "B", "C"),
  var_orig = c(1, NA, 3),
  var_alt = c(NA, 2, 4)
)

data |>
  combine_cols(
```

```
    col_1 = "var_orig",
    col_2 = "var_alt"
  )

data |>
  combine_cols(
    "var_orig",
    "var_alt",
    name = "out"
  )

data |>
  combine_cols(
    "var_orig",
    "var_alt",
    name = "out",
    keep_other = FALSE
  )
```

`combine_levels` *Combine levels from two variables to create a new variable*

Description

Combines levels from two columns into new level stored into a new column. Allows users to create new classifications using levels defined in existing fields.

Usage

```
combine_levels(data, vars, conds, default = NA, combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the two columns to be summarized.
`vars`	named list of length 1. The name of the list component will be used as the name for the newly created variable/column, and the character elements specifies the two existing fields from which the levels will be combined.
`conds`	named list. The name of the each of the list element will be used as the label for the new level created, and the two character vectors represent the levels in the first and second variables, respectively, that will be combined to create the new level.
`default`	character (or `NA`). One of the two input variables specified in `vars` that will be used to set the levels of the new column after all the combinations in `conds` are exhausted. If `default = NA`, the remaining conditions `conds` have been exhausted will be set to `NA`.
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Value

tbl. The input data frame with the new column with combined levels appended at the end.

Examples

```
data <- tibble::tibble(
  var_1 = c("a", "b", "b", "c"),
  var_2 = c(1, NA, 2, 3)
)

data |>
  combine_levels(
    vars = list(
      "var_3" = c("var_1", "var_2")
    ),
    conds = list(
      "a1" = list("a", 1),
      "b0" = list("b", NA),
      "b2" = list("b", 2)
    ),
    default = "var_1",
    combine = TRUE
  )
```

---

compute_ab_g_dyn__cohort_income__hhold__3lvl

Compute "Cohort description: Household income - 3 levels"

Description

Computes the summary score ab_g_dyn__cohort_income__hhold__3lvl Cohort description: Household income - 3 levels

- *Summarized variables:*
  - ab_p_demo__income__hhold_001
  - ab_p_demo__income__hhold_001__v01

Usage

```
compute_ab_g_dyn__cohort_income__hhold__3lvl(
  data,
  name = "ab_g_dyn__cohort_income__hhold__3lvl",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ab_g_dyn__cohort_income__hhold__6lvl()

---

compute_ab_g_dyn_all *Compute all the ab_g_dyn scores*

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_ab_g_dyn_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ab_g_dyn_all(data)

## End(Not run)
```

compute_ab_g_stc_all *Compute all the ab_g_stc scores*

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_ab_g_stc_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ab_g_stc_all(data)

## End(Not run)
```

compute_ab_p_demo__ntvam_all *Compute all the ab_p_demo__ntvam scores*

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_ab_p_demo__ntvam_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_age *Compute time interval between two dates*

Description

Calculate the time difference between two dates in specified units (years, months, or days). Uses lubridate intervals for accurate calculations across calendar irregularities.

Usage

```
compute_age(date_start, date_end, unit = c("years", "months", "days"))
```

Arguments

date_start	Starting date. Must be a date or datetime object compatible with lubridate.
date_end	Ending date. Must be a date or datetime object compatible with lubridate.
unit	Character string specifying the unit for the result. Must be one of "years", "months", or "days". Defaults to "years".

Value

A numeric value representing the time difference in the specified unit.

Examples

```
# Calculate age in years
compute_age(as.Date("1990-01-01"), as.Date("2024-01-01"))

# Calculate age in months
compute_age(as.Date("2023-01-01"), as.Date("2024-01-01"), unit = "months")

# Calculate age in days
compute_age(as.Date("2023-12-01"), as.Date("2024-01-01"), unit = "days")
```

compute_famhx_endorsement

Compute Family History [Parent] Endorsement indicator

Description

Computes a binary endorsement indicator, for alcohol or drug use computed using a set of variables. Resulting indicator is either 0 (FALSE) or 1 (TRUE), and NA for missing or non-responses (777, 888, or 999).

- *Notes:*
  - Following values are recoded as NA prior to any computation
    - 777
    - 888
    - 999

Usage

```
compute_famhx_endorsement(data, name, var_matches, combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. The name of the summary score.
var_matches	character of length one. The base name of the checkbox field that is used to find all corresponding columns in data that contain the responses of a participant for the check box. This parameter is passed onto combine_checkboxes function.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Value

A tibble with the computed score for each participant/event.

Examples

```
## Not run:
compute_famhx_endorsement(
  data = data,
  name = "mh_p_famhx__alc__fath_indicator",
  var_matches = "mh_p_famhx__alc__fath_001"
)

## End(Not run)
```

compute_fc_p_fes__cohes_nm

Compute "Family Environment Scale [Parent] (Cohesion): Number missing"

Description

Computes the summary score `fc_p_fes__cohes_nm` (Family Environment Scale [Parent] (Cohesion): Number missing)

- *Summarized variables:*
  - `fc_p_fes__cohes_001`
  - `fc_p_fes__cohes_002`
  - `fc_p_fes__cohes_003`
  - `fc_p_fes__cohes_004`
  - `fc_p_fes__cohes_005`
  - `fc_p_fes__cohes_006`
  - `fc_p_fes__cohes_007`
  - `fc_p_fes__cohes_008`
  - `fc_p_fes__cohes_009`
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_fes__cohes_nm(
  data,
  name = "fc_p_fes__cohes_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_fes__cohes_mean()

---

compute_fc_p_fes__confl_nm *Compute "Family Environment Scale [Parent] (Conflict): Number missing"*

Description

Computes the summary score fc_p_fes__confl_nm (Family Environment Scale [Parent] (Conflict): Number missing)

- *Summarized variables:*
  - fc_p_fes__confl_001
  - fc_p_fes__confl_002
  - fc_p_fes__confl_003
  - fc_p_fes__confl_004
  - fc_p_fes__confl_005
  - fc_p_fes__confl_006
  - fc_p_fes__confl_007
  - fc_p_fes__confl_008
  - fc_p_fes__confl_009
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_fes__confl_nm(
  data,
  name = "fc_p_fes__confl_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_fes__confl_mean()

---

compute_fc_p_fes__expr_nm

Compute "Family Environment Scale [Parent] (Expression): Number missing"

Description

Computes the summary score fc_p_fes__expr_nm (Family Environment Scale [Parent] (Expression): Number missing)

- *Summarized variables:*
  - fc_p_fes__expr_001
  - fc_p_fes__expr_002
  - fc_p_fes__expr_003
  - fc_p_fes__expr_004
  - fc_p_fes__expr_005
  - fc_p_fes__expr_006
  - fc_p_fes__expr_007
  - fc_p_fes__expr_008
  - fc_p_fes__expr_009
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_fes__expr_nm(
  data,
  name = "fc_p_fes__expr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_fes__expr_mean()

---

compute_fc_p_fes__intelcult_nm

Compute "Family Environment Scale [Parent] (Intellectual and cultural): Number missing"

Description

Computes the summary score fc_p_fes__intelcult_nm (Family Environment Scale [Parent] (Intellectual and cultural): Number missing)

- *Summarized variables:*
  - fc_p_fes__intelcult_001
  - fc_p_fes__intelcult_002
  - fc_p_fes__intelcult_003
  - fc_p_fes__intelcult_004
  - fc_p_fes__intelcult_005
  - fc_p_fes__intelcult_006
  - fc_p_fes__intelcult_007
  - fc_p_fes__intelcult_008
  - fc_p_fes__intelcult_009
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_fes__intelcult_nm(
  data,
  name = "fc_p_fes__intelcult_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_fes__intelcult_mean()

---

compute_fc_p_fes__org_nm

Compute "Family Environment Scale [Parent] (Organization): Number missing"

Description

Computes the summary score fc_p_fes__org_nm (Family Environment Scale [Parent] (Organization): Number missing)

- *Summarized variables:*
  - fc_p_fes__org_001
  - fc_p_fes__org_002
  - fc_p_fes__org_003
  - fc_p_fes__org_004
  - fc_p_fes__org_005
  - fc_p_fes__org_006
  - fc_p_fes__org_007
  - fc_p_fes__org_008
  - fc_p_fes__org_009
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_fes__org_nm(
  data,
  name = "fc_p_fes__org_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_fes__org_mean()

`compute_fc_p_fes__rec_nm`

Compute "Family Environment Scale [Parent] (Activity and recreational): Number missing"

Description

Computes the summary score `fc_p_fes__rec_nm` (Family Environment Scale [Parent] (Activity and recreational): Number missing)

- *Summarized variables:*
  - `fc_p_fes__rec_001`
  - `fc_p_fes__rec_002`
  - `fc_p_fes__rec_003`
  - `fc_p_fes__rec_004`
  - `fc_p_fes__rec_005`
  - `fc_p_fes__rec_006`
  - `fc_p_fes__rec_007`
  - `fc_p_fes__rec_008`
  - `fc_p_fes__rec_009`
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_fes__rec_nm(
  data,
  name = "fc_p_fes__rec_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_fes__rec_mean()

---

compute_fc_p_fes_all *Compute all the fc_p_fes summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_p_fes_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_p_fes_all(data)

## End(Not run)
```

---

compute_fc_p_meim__commattach_nm *Compute "The Multigroup Ethnic Identity Measure-Revised [Parent] (Commitment and attachment): Number missing"*

Description

Computes the summary score `fc_p_meim__commattach_nm` (The Multigroup Ethnic Identity Measure-Revised [Parent] (Commitment and attachment): Number missing)

- *Summarized variables:*
  - `fc_p_meim__commattach_001`
  - `fc_p_meim__commattach_002`
  - `fc_p_meim__commattach_003`
- *Excluded values:* none

Usage

```
compute_fc_p_meim__commattach_nm(
  data,
  name = "fc_p_meim__commattach_nm",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_p_meim__commattach_mean()`

---

compute_fc_p_meim__explor_nm

Compute "The Multigroup Ethnic Identity Measure-Revised [Parent] (Exploration): Number missing"

Description

Computes the summary score `fc_p_meim__explor_nm` (The Multigroup Ethnic Identity Measure-Revised [Parent] (Exploration): Number missing)

- *Summarized variables:*
  - `fc_p_meim__explor_001`
  - `fc_p_meim__explor_002`
  - `fc_p_meim__explor_003`
- *Excluded values:* none

Usage

```
compute_fc_p_meim__explor_nm(
  data,
  name = "fc_p_meim__explor_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_meim__explor_mean()

---

compute_fc_p_meim_all *Compute all the fc_p_meim summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_p_meim_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_p_meim_all(data)

## End(Not run)
```

compute_fc_p_meim_nm *Compute "The Multigroup Ethnic Identity Measure-Revised [Parent]: Number missing"*

Description

Computes the summary score `fc_p_meim_nm` (The Multigroup Ethnic Identity Measure-Revised [Parent]: Number missing)

- *Summarized variables:*
  - `fc_p_meim__commattach_001`
  - `fc_p_meim__commattach_002`
  - `fc_p_meim__commattach_003`
  - `fc_p_meim__explor_001`
  - `fc_p_meim__explor_002`
  - `fc_p_meim__explor_003`
- *Excluded values:* none

Usage

```
compute_fc_p_meim_nm(data, name = "fc_p_meim_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_p_meim_mean()`

compute_fc_p_nce__cc_nm

Compute "Neighborhood Collective Efficacy [Parent] (Community cohesion): Number missing"

Description

Computes the summary score `fc_p_nce__cc_nm` (Neighborhood Collective Efficacy [Parent] (Community cohesion): Number missing)

- *Summarized variables:*
  - `fc_p_nce__cc_001`
  - `fc_p_nce__cc_002`
  - `fc_p_nce__cc_003`
  - `fc_p_nce__cc_004`
  - `fc_p_nce__cc_005`
- *Excluded values:*
  - 777

Usage

```
compute_fc_p_nce__cc_nm(data, name = "fc_p_nce__cc_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_p_nce__cc_mean()`

compute_fc_p_nce__isc_nm

Compute "Neighborhood Collective Efficacy [Parent] (Informal social control): Number missing"

Description

Computes the summary score `fc_p_nce__isc_nm` (Neighborhood Collective Efficacy [Parent] (Informal social control): Number missing)

- *Summarized variables:*
  - `fc_p_nce__isc_001`
  - `fc_p_nce__isc_002`
  - `fc_p_nce__isc_003`
  - `fc_p_nce__isc_004`
  - `fc_p_nce__isc_005`
- *Excluded values:*
  - 777

Usage

```
compute_fc_p_nce__isc_nm(data, name = "fc_p_nce__isc_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_p_nce__isc_mean()`

compute_fc_p_nce_all *Compute all the fc_p_nce summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_p_nce_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_p_nce_all(data)

## End(Not run)
```

compute_fc_p_nce_nm *Compute "Neighborhood Collective Efficacy [Parent]: Number missing"*

Description

Computes the summary score `fc_p_nce_nm` (Neighborhood Collective Efficacy [Parent]: Number missing)

- *Summarized variables:*
  - `fc_p_nce__cc_001`
  - `fc_p_nce__cc_002`
  - `fc_p_nce__cc_003`
  - `fc_p_nce__cc_004`
  - `fc_p_nce__cc_005`
  - `fc_p_nce__isc_001`
  - `fc_p_nce__isc_002`
  - `fc_p_nce__isc_003`

  - fc_p_nce__isc_004
  - fc_p_nce__isc_005
- *Excluded values:*
  - 777

Usage

```
compute_fc_p_nce_nm(data, name = "fc_p_nce_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_nce_mean()

---

compute_fc_p_nsc__ns_nm

Compute "Neighborhood Safety & Crime [Parent] (Neighborhood safety): Number missing"

Description

Computes the summary score fc_p_nsc__ns_nm (Neighborhood Safety & Crime [Parent] (Neighborhood safety): Number missing)

- *Summarized variables:*
  - fc_p_nsc__ns_001
  - fc_p_nsc__ns_002
  - fc_p_nsc__ns_003
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_nsc__ns_nm(data, name = "fc_p_nsc__ns_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_nsc__ns_mean()

---

compute_fc_p_nsc_all *Compute all the fc_p_nsc summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_p_nsc_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_p_nsc_all(data)

## End(Not run)
```

compute_fc_p_pk__knowl_nm
Compute "Parental Knowledge Scale [Parent]: Number missing"

Description

Computes the summary score `fc_p_pk__knowl_nm` (Parental Knowledge Scale [Parent]: Number missing)

- *Summarized variables:*
  - `fc_p_pk__knowl_001`
  - `fc_p_pk__knowl_002`
  - `fc_p_pk__knowl_003`
  - `fc_p_pk__knowl_004`
  - `fc_p_pk__knowl_005`
  - `fc_p_pk__knowl_006`
  - `fc_p_pk__knowl_007`
  - `fc_p_pk__knowl_008`
  - `fc_p_pk__knowl_009`
- *Excluded values:*
  - 777

Usage

```
compute_fc_p_pk__knowl_nm(data, name = "fc_p_pk__knowl_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_p_pk__knowl_mean()`

compute_fc_p_pk_all *Compute all the fc_p_pk summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_p_pk_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_p_pk_all(data)

## End(Not run)
```

compute_fc_p_psb_all *Compute all the fc_p_psb summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_p_psb_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_p_psb_all(data)

## End(Not run)
```

`compute_fc_p_psb_nm` *Compute "Prosocial Behavior [Parent]: Number missing"*

Description

Computes the summary score `fc_p_psb_nm` (Prosocial Behavior [Parent]: Number missing)

- *Summarized variables:*
  - `fc_p_psb_001`
  - `fc_p_psb_002`
  - `fc_p_psb_003`
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_psb_nm(
  data,
  name = "fc_p_psb_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_p_psb_mean()`

compute_fc_p_vs__famil_nm

Compute "Values Scale [Parent] (Familism): Number missing - Baseline to Year 5"

Description

Computes the summary score `fc_p_vs__famil_nm__v01` (Values Scale [Parent] (Familism): Number missing (Subscales: supp, ref, obl))

- *Summarized variables:*
  - `fc_p_vs__supp_001`
  - `fc_p_vs__supp_002`
  - `fc_p_vs__supp_003`
  - `fc_p_vs__supp_004`
  - `fc_p_vs__supp_005`
  - `fc_p_vs__supp_006`
  - `fc_p_vs__ref_001`
  - `fc_p_vs__ref_002`
  - `fc_p_vs__ref_003`
  - `fc_p_vs__ref_004`
  - `fc_p_vs__ref_005`
  - `fc_p_vs__obl_001`
  - `fc_p_vs__obl_002`
  - `fc_p_vs__obl_003`
  - `fc_p_vs__obl_004`
  - `fc_p_vs__obl_005`
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_vs__famil_nm(
  data,
  name = "fc_p_vs__famil_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_vs__famil_mean()

---

compute_fc_p_vs__famil_nm__v01

Compute "Values Scale [Parent] (Familism): Number missing - Version 1 (Year 5 onwards)"

Description

Computes the summary score fc_p_vs__famil_nm__v01 (Values Scale [Parent] (Familism): Number missing - Version 1 (Year 5 onwards))

- *Summarized variables:*
  - fc_p_vs__supp_001
  - fc_p_vs__supp_002
  - fc_p_vs__supp_003
  - fc_p_vs__supp_004
  - fc_p_vs__supp_005
  - fc_p_vs__supp_006
  - fc_p_vs__ref_001
  - fc_p_vs__ref_002
  - fc_p_vs__ref_003
  - fc_p_vs__ref_004
  - fc_p_vs__ref_005
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_vs__famil_nm__v01(
  data,
  name = "fc_p_vs__famil_nm__v01",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_vs__famil_mean__v01()

---

compute_fc_p_vs__indselfrel_nm

Compute "Values Scale [Parent] (Independence and self-reliance): Number missing"

Description

Computes the summary score fc_p_vs__indselfrel_nm (Values Scale [Parent] (Independence and self-reliance): Number missing)

- *Summarized variables:*
  - fc_p_vs__indselfrel_001
  - fc_p_vs__indselfrel_002
  - fc_p_vs__indselfrel_003
  - fc_p_vs__indselfrel_004
  - fc_p_vs__indselfrel_005
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_vs__indselfrel_nm(
  data,
  name = "fc_p_vs__indselfrel_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_vs__indselfrel_mean()

---

compute_fc_p_vs__obl_nm

Compute "Values Scale [Parent] (Family obligation): Number missing"

Description

Computes the summary score fc_p_vs__obl_nm (Values Scale [Parent] (Family obligation): Number missing)

- *Summarized variables:*
  - fc_p_vs__obl_001
  - fc_p_vs__obl_002
  - fc_p_vs__obl_003
  - fc_p_vs__obl_004
  - fc_p_vs__obl_005
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_vs__obl_nm(
  data,
  name = "fc_p_vs__obl_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_vs__obl_mean()

---

compute_fc_p_vs__ref_nm

Compute "Values Scale [Parent] (Family as referent): Number missing"

Description

Computes the summary score fc_p_vs__ref_nm (Values Scale [Parent] (Family as referent): Number missing)

- *Summarized variables:*
  - fc_p_vs__ref_001
  - fc_p_vs__ref_002
  - fc_p_vs__ref_003
  - fc_p_vs__ref_004
  - fc_p_vs__ref_005
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_vs__ref_nm(
  data,
  name = "fc_p_vs__ref_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_vs__ref_mean()

---

compute_fc_p_vs__relig_nm

Compute "Values Scale [Parent] (Religion): Number missing"

Description

Computes the summary score fc_p_vs__relig_nm (Values Scale [Parent] (Religion): Number missing)

- *Summarized variables:*
  - fc_p_vs__relig_001
  - fc_p_vs__relig_002
  - fc_p_vs__relig_003
  - fc_p_vs__relig_004
  - fc_p_vs__relig_005
  - fc_p_vs__relig_006
  - fc_p_vs__relig_007
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_vs__relig_nm(
  data,
  name = "fc_p_vs__relig_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_vs__relig_mean()

---

compute_fc_p_vs__supp_nm

Compute "Values Scale [Parent] (Family support): Number missing"

Description

Computes the summary score fc_p_vs__supp_nm (Values Scale [Parent] (Family support): Number missing)

- *Summarized variables:*
  - fc_p_vs__supp_001
  - fc_p_vs__supp_002
  - fc_p_vs__supp_003
  - fc_p_vs__supp_004
  - fc_p_vs__supp_005
  - fc_p_vs__supp_006
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_p_vs__supp_nm(
  data,
  name = "fc_p_vs__supp_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_vs__supp_mean()

---

compute_fc_p_vs_all *Compute all the fc_p_vs summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_p_vs_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_p_vs_all(data)

## End(Not run)
```

`compute_fc_y_as__safe_nm`
Compute "Activity Space [Youth] (Safety): Number missing"

Description

Computes the summary score `fc_y_as__safe_nm` (Activity Space [Youth] (Safety): Number missing)

- *Summarized variables:*
  - `fc_y_as__safe_001a`
  - `fc_y_as__safe_001b`
  - `fc_y_as__safe_001c`
- *Excluded values:* none

Usage

```
compute_fc_y_as__safe_nm(data, name = "fc_y_as__safe_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_y_as__safe_mean()`

compute_fc_y_as_all *Compute all the fc_y_as summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_y_as_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_as_all(data)

## End(Not run)
```

compute_fc_y_crpbi__cg1_nm *Compute "Children's Report of Parental Behavioral Inventory [Youth] (Caregiver A): Number missing"*

Description

Computes the summary score `fc_y_crpbi__cg1_nm` (Children's Report of Parental Behavioral Inventory [Youth] (Caregiver A): Number missing)

- *Summarized variables:*
  - `fc_y_crpbi__cg1_002`
  - `fc_y_crpbi__cg1_003`
  - `fc_y_crpbi__cg1_004`
  - `fc_y_crpbi__cg1_005`
  - `fc_y_crpbi__cg1_006`
- *Excluded values:* none

Usage

```
compute_fc_y_crpbi__cg1_nm(data, name = "fc_y_crpbi__cg1_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_crpbi__cg1_mean()

---

compute_fc_y_crpbi__cg2_nm

Compute "Children's Report of Parental Behavioral Inventory [Youth] (Caregiver B): Number missing"

Description

Computes the summary score fc_y_crpbi__cg2_nm (Children's Report of Parental Behavioral Inventory [Youth] (Caregiver B): Number missing)

- *Summarized variables:*
  - fc_y_crpbi__cg2_002
  - fc_y_crpbi__cg2_003
  - fc_y_crpbi__cg2_004
  - fc_y_crpbi__cg2_005
  - fc_y_crpbi__cg2_006
- *Excluded values:* none

Usage

```
compute_fc_y_crpbi__cg2_nm(data, name = "fc_y_crpbi__cg2_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_y_crpbi__cg2_mean()`

`compute_fc_y_crpbi_all`

Compute all the fc_y_crpbi summary scores

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_y_crpbi_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_crpbi_all(data)

## End(Not run)
```

compute_fc_y_eut__ethn_nm

Compute "Experiences with Unfair Treatment [Youth] (Ethnicity): Number missing"

Description

Computes the summary score fc_y_eut__ethn_nm (Experiences with Unfair Treatment [Youth] (Ethnicity): Number missing)

- *Summarized variables:*
  - fc_y_eut__ethn_001a
  - fc_y_eut__ethn_001b
  - fc_y_eut__ethn_001c
  - fc_y_eut__ethn_001d
  - fc_y_eut__ethn_002
  - fc_y_eut__ethn_003a
  - fc_y_eut__ethn_003b
  - fc_y_eut__ethn_003c
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_fc_y_eut__ethn_nm(data, name = "fc_y_eut__ethn_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_eut__ethn_mean()

compute_fc_y_eut_all *Compute all the fc_y_eut summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_y_eut_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_eut_all(data)

## End(Not run)
```

compute_fc_y_fes__cohes_nm *Compute "Family Environment Scale [Youth] (Cohesion): Number missing"*

Description

Computes the summary score `fc_y_fes__cohes_nm` (Family Environment Scale [Youth] (Cohesion): Number missing)

- *Summarized variables:*
  - `fc_y_fes__cohes_001`
  - `fc_y_fes__cohes_002`
  - `fc_y_fes__cohes_003`
  - `fc_y_fes__cohes_004`
  - `fc_y_fes__cohes_005`
  - `fc_y_fes__cohes_006`
  - `fc_y_fes__cohes_007`

  - fc_y_fes__cohes_008
  - fc_y_fes__cohes_009

- *Excluded values:*
  - 777

Usage

```
compute_fc_y_fes__cohes_nm(
  data,
  name = "fc_y_fes__cohes_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_fes__cohes_mean()

---

compute_fc_y_fes__confl_nm

Compute "Family Environment Scale [Youth] (Conflict): Number missing"

Description

Computes the summary score fc_y_fes__confl_nm (Family Environment Scale [Youth] (Conflict): Number missing)

- *Summarized variables:*
  - fc_y_fes__confl_001
  - fc_y_fes__confl_002
  - fc_y_fes__confl_003
  - fc_y_fes__confl_004

  - fc_y_fes__confl_005
  - fc_y_fes__confl_006
  - fc_y_fes__confl_007
  - fc_y_fes__confl_008
  - fc_y_fes__confl_009
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_fes__confl_nm(
  data,
  name = "fc_y_fes__confl_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_fes__confl_mean()

---

compute_fc_y_fes_all *Compute all the fc_y_fes summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_y_fes_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_fes_all(data)

## End(Not run)
```

---

compute_fc_y_lone_all *Compute all the fc_y_lone summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_y_lone_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_lone_all(data)

## End(Not run)
```

compute_fc_y_lone_nm *Compute "UCLA Loneliness Scale [Youth]: Number missing"*

Description

Computes the summary score fc_y_lone_nm (UCLA Loneliness Scale [Youth]: Number missing)

- *Summarized variables:*
  - fc_y_lone_001
  - fc_y_lone_002
  - fc_y_lone_003
  - fc_y_lone_004
  - fc_y_lone_005
  - fc_y_lone_006
  - fc_y_lone_007
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_fc_y_lone_nm(data, name = "fc_y_lone_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_lone_mean()

`compute_fc_y_meim__commattach_nm` *Compute "The Multigroup Ethnic Identity Measure-Revised [Youth] (Commitment and attachment): Number missing"*

Description

Computes the summary score `fc_y_meim__commattach_nm` (The Multigroup Ethnic Identity Measure-Revised [Youth] (Commitment and attachment): Number missing)

- *Summarized variables:*
  - `fc_y_meim__commattach_001`
  - `fc_y_meim__commattach_002`
  - `fc_y_meim__commattach_003`
- *Excluded values:* none

Usage

```
compute_fc_y_meim__commattach_nm(
  data,
  name = "fc_y_meim__commattach_nm",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_y_meim__commattach_mean()`

`compute_fc_y_meim__explor_nm` *Compute "The Multigroup Ethnic Identity Measure-Revised [Youth] (Exploration): Number missing"*

Description

Computes the summary score `fc_y_meim__explor_nm` (The Multigroup Ethnic Identity Measure-Revised [Youth] (Exploration): Number missing)

- *Summarized variables:*
  - `fc_y_meim__explor_001`
  - `fc_y_meim__explor_002`
  - `fc_y_meim__explor_003`
- *Excluded values:* none

Usage

```
compute_fc_y_meim__explor_nm(
  data,
  name = "fc_y_meim__explor_nm",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_y_meim__explor_mean()`

compute_fc_y_meim_all *Compute all the fc_y_meim summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_y_meim_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_meim_all(data)

## End(Not run)
```

compute_fc_y_meim_nm *Compute "The Multigroup Ethnic Identity Measure-Revised [Youth]: Number missing"*

Description

Computes the summary score `fc_y_meim_nm` (The Multigroup Ethnic Identity Measure-Revised [Youth]: Number missing)

- *Summarized variables:*
  - `fc_y_meim__commattach_001`
  - `fc_y_meim__commattach_002`
  - `fc_y_meim__commattach_003`
  - `fc_y_meim__explor_001`
  - `fc_y_meim__explor_002`
  - `fc_y_meim__explor_003`
- *Excluded values:* none

Usage

```
compute_fc_y_meim_nm(data, name = "fc_y_meim_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_meim_mean()

---

compute_fc_y_mnbs__edusupp_nm

Compute "Multidimensional Neglectful Behavior Scale [Youth] (Education support): Number missing"

Description

Computes the summary score fc_y_mnbs__edusupp_nm (Multidimensional Neglectful Behavior Scale [Youth] (Education support): Number missing)

- *Summarized variables:*
  - fc_y_mnbs__edusupp_001
  - fc_y_mnbs__edusupp_002
  - fc_y_mnbs__edusupp_003
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_mnbs__edusupp_nm(
  data,
  name = "fc_y_mnbs__edusupp_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_mnbs__edusupp_mean()

---

compute_fc_y_mnbs__superv_nm

Compute "Multidimensional Neglectful Behavior Scale [Youth] (Supervision): Number missing"

Description

Computes the summary score fc_y_mnbs__superv_nm (Multidimensional Neglectful Behavior Scale [Youth] (Supervision): Number missing)

- *Summarized variables:*
  - fc_y_mnbs__superv_001
  - fc_y_mnbs__superv_002
  - fc_y_mnbs__superv_003
  - fc_y_mnbs__superv_004
  - fc_y_mnbs__superv_005
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_mnbs__superv_nm(
  data,
  name = "fc_y_mnbs__superv_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_y_mnbs__superv_mean()`

`compute_fc_y_mnbs_all` *Compute all the fc_y_mnbs summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_y_mnbs_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_mnbs_all(data)

## End(Not run)
```

`compute_fc_y_mnbs_nm` *Compute "Multidimensional Neglectful Behavior Scale [Youth]: Number missing"*

Description

Computes the summary score `fc_y_mnbs_nm` (Multidimensional Neglectful Behavior Scale [Youth]: Number missing)

- *Summarized variables:*
  - `fc_y_mnbs__edusupp_001`
  - `fc_y_mnbs__edusupp_002`
  - `fc_y_mnbs__edusupp_003`
  - `fc_y_mnbs__superv_001`
  - `fc_y_mnbs__superv_002`
  - `fc_y_mnbs__superv_003`
  - `fc_y_mnbs__superv_004`
  - `fc_y_mnbs__superv_005`
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_mnbs_nm(data, name = "fc_y_mnbs_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_y_mnbs_mean()`

compute_fc_y_naa_all *Compute all the fc_y_naa scores*

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_fc_y_naa_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_fc_y_pm_all *Compute all the fc_y_pm summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_y_pm_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_pm_all(data)

## End(Not run)
```

compute_fc_y_pm_nm *Compute "Parental Monitoring [Youth]: Number missing"*

Description

Computes the summary score `fc_y_pm_nm` (Parental Monitoring [Youth]: Number missing)

- *Summarized variables:*
  - `fc_y_pm_001`
  - `fc_y_pm_002`
  - `fc_y_pm_003`
  - `fc_y_pm_004`
  - `fc_y_pm_005`
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_pm_nm(data, name = "fc_y_pm_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_y_pm_mean()`

compute_fc_y_pnh_all *Compute all the fc_y_pnh summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_y_pnh_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_pnh_all(data)

## End(Not run)
```

compute_fc_y_pnh_nm *Compute "Peer Network Health [Youth]: Number missing"*

Description

Computes the summary score `fc_y_pnh_nm` (Peer Network Health [Youth]: Number missing)

- *Summarized variables:*
  - `fc_y_pnh_001`
  - `fc_y_pnh_002`
  - `fc_y_pnh_002__01`
  - `fc_y_pnh_003`
  - `fc_y_pnh_003__01`
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_pnh_nm(
  data,
  name = "fc_y_pnh_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_pnh_sum()

---

compute_fc_y_psb_all *Compute all the fc_y_psb summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_y_psb_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_psb_all(data)

## End(Not run)
```

`compute_fc_y_psb_nm` *Compute "Prosocial Behavior [Youth]: Number missing"*

Description

Computes the summary score `fc_y_psb_nm` (Prosocial Behavior [Youth]: Number missing)

- *Summarized variables:*
  - `fc_y_psb_001`
  - `fc_y_psb_002`
  - `fc_y_psb_003`
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_psb_nm(
  data,
  name = "fc_y_psb_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_fc_y_psb_mean()`

compute_fc_y_rpi_all *Compute all the fc_y_rpi summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_y_rpi_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_rpi_all(data)

## End(Not run)
```

compute_fc_y_rpi_nm *Compute "Resistance to Peer Influence [Youth]: Number missing"*

Description

Computes the summary score `fc_y_rpi_nm` (Resistance to Peer Influence [Youth]: Number missing)

- *Summarized variables:*
  - `fc_y_rpi_001`
  - `fc_y_rpi_002`
  - `fc_y_rpi_003`
  - `fc_y_rpi_004`
  - `fc_y_rpi_005`
  - `fc_y_rpi_006`
  - `fc_y_rpi_007`
  - `fc_y_rpi_008`
  - `fc_y_rpi_009`
  - `fc_y_rpi_010`
- *Excluded values:* none

Usage

```
compute_fc_y_rpi_nm(data, name = "fc_y_rpi_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_rpi_mean()

---

compute_fc_y_srpf__dis_nm

Compute "School Risk & Protective Factors [Youth] (School disengagement): Number missing"

Description

Computes the summary score fc_y_srpf__dis_nm (School Risk & Protective Factors [Youth] (School disengagement): Number missing)

- *Summarized variables:*
  - fc_y_srpf__dis_001
  - fc_y_srpf__dis_002
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_srpf__dis_nm(
  data,
  name = "fc_y_srpf__dis_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_srpf__dis_mean()

---

compute_fc_y_srpf__env_nm

Compute "School Risk & Protective Factors [Youth] (School environment): Number missing"

Description

Computes the summary score fc_y_srpf__env_nm (School Risk & Protective Factors [Youth] (School environment): Number missing)

- *Summarized variables:*
  - fc_y_srpf__env_001
  - fc_y_srpf__env_002
  - fc_y_srpf__env_003
  - fc_y_srpf__env_004
  - fc_y_srpf__env_005
  - fc_y_srpf__env_006
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_srpf__env_nm(
  data,
  name = "fc_y_srpf__env_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_srpf__env_mean()

---

compute_fc_y_srpf__involv_nm

Compute "School Risk & Protective Factors [Youth] (School involvement): Number missing"

Description

Computes the summary score fc_y_srpf__involv_nm (School Risk & Protective Factors [Youth] (School involvement): Number missing)

- *Summarized variables:*
  - fc_y_srpf__involv_001
  - fc_y_srpf__involv_002
  - fc_y_srpf__involv_003
  - fc_y_srpf__involv_004
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_srpf__involv_nm(
  data,
  name = "fc_y_srpf__involv_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_srpf__involv_mean()

---

compute_fc_y_srpf_all *Compute all the fc_y_srpf summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_y_srpf_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_srpf_all(data)

## End(Not run)
```

compute_fc_y_vs__famil_nm

Compute "Values Scale [Youth] (Familism): Number missing - Baseline to Year 5"

Description

Computes the summary score `fc_y_vs__famil_nm__v01` (Values Scale [Youth] (Familism): Number missing (Subscales: supp, ref, obl))

- *Summarized variables:*
  - `fc_y_vs__supp_001`
  - `fc_y_vs__supp_002`
  - `fc_y_vs__supp_003`
  - `fc_y_vs__supp_004`
  - `fc_y_vs__supp_005`
  - `fc_y_vs__supp_006`
  - `fc_y_vs__ref_001`
  - `fc_y_vs__ref_002`
  - `fc_y_vs__ref_003`
  - `fc_y_vs__ref_004`
  - `fc_y_vs__ref_005`
  - `fc_y_vs__obl_001`
  - `fc_y_vs__obl_002`
  - `fc_y_vs__obl_003`
  - `fc_y_vs__obl_004`
  - `fc_y_vs__obl_005`
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_vs__famil_nm(
  data,
  name = "fc_y_vs__famil_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_vs__famil_mean()

`compute_fc_y_vs__famil_nm__v01`
Compute "Values Scale [Youth] (Familism): Number missing - Version 1 (Year 5 onwards)"

Description

Computes the summary score `fc_y_vs__famil_nm__v01` (Values Scale [Youth] (Familism): Number missing - Version 1 (Year 5 onwards))

- *Summarized variables:*
  - `fc_y_vs__supp_001`
  - `fc_y_vs__supp_002`
  - `fc_y_vs__supp_003`
  - `fc_y_vs__supp_004`
  - `fc_y_vs__supp_005`
  - `fc_y_vs__supp_006`
  - `fc_y_vs__ref_001`
  - `fc_y_vs__ref_002`
  - `fc_y_vs__ref_003`
  - `fc_y_vs__ref_004`
  - `fc_y_vs__ref_005`
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_vs__famil_nm__v01(
  data,
  name = "fc_y_vs__famil_nm__v01",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_vs__famil_mean__v01()

---

compute_fc_y_vs__indselfrel_nm

Compute "Values Scale [Youth] (Independence and self-reliance): Number missing"

Description

Computes the summary score fc_y_vs__indselfrel_nm (Values Scale [Youth] (Independence and self-reliance): Number missing)

- *Summarized variables:*
  - fc_y_vs__indselfrel_001
  - fc_y_vs__indselfrel_002
  - fc_y_vs__indselfrel_003
  - fc_y_vs__indselfrel_004
  - fc_y_vs__indselfrel_005
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_vs__indselfrel_nm(
  data,
  name = "fc_y_vs__indselfrel_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_vs__indselfrel_mean()

---

compute_fc_y_vs__obl_nm

Compute "Values Scale [Youth] (Family obligation): Number missing"

Description

Computes the summary score fc_y_vs__obl_nm (Values Scale [Youth] (Family obligation): Number missing)

- *Summarized variables:*
  - fc_y_vs__obl_001
  - fc_y_vs__obl_002
  - fc_y_vs__obl_003
  - fc_y_vs__obl_004
  - fc_y_vs__obl_005
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_vs__obl_nm(
  data,
  name = "fc_y_vs__obl_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_vs__obl_mean()

---

compute_fc_y_vs__ref_nm

Compute "Values Scale [Youth] (Family as referent): Number missing"

Description

Computes the summary score fc_y_vs__ref_nm (Values Scale [Youth] (Family as referent): Number missing)

- *Summarized variables:*
  - fc_y_vs__ref_001
  - fc_y_vs__ref_002
  - fc_y_vs__ref_003
  - fc_y_vs__ref_004
  - fc_y_vs__ref_005
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_vs__ref_nm(
  data,
  name = "fc_y_vs__ref_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_vs__ref_mean()

---

compute_fc_y_vs__relig_nm

Compute "Values Scale [Youth] (Religion): Number missing"

Description

Computes the summary score fc_y_vs__relig_nm (Values Scale [Youth] (Religion): Number missing)

- *Summarized variables:*
  - fc_y_vs__relig_001
  - fc_y_vs__relig_002
  - fc_y_vs__relig_003
  - fc_y_vs__relig_004
  - fc_y_vs__relig_005
  - fc_y_vs__relig_006
  - fc_y_vs__relig_007
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_vs__relig_nm(
  data,
  name = "fc_y_vs__relig_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_vs__relig_mean()

---

compute_fc_y_vs__supp_nm

Compute "Values Scale [Youth] (Family support): Number missing"

Description

Computes the summary score fc_y_vs__supp_nm (Values Scale [Youth] (Family support): Number missing)

- *Summarized variables:*
  - fc_y_vs__supp_001
  - fc_y_vs__supp_002
  - fc_y_vs__supp_003
  - fc_y_vs__supp_004
  - fc_y_vs__supp_005
  - fc_y_vs__supp_006
- *Excluded values:*
  - 777

Usage

```
compute_fc_y_vs__supp_nm(
  data,
  name = "fc_y_vs__supp_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_vs__supp_mean()

---

compute_fc_y_vs_all *Compute all the fc_y_vs summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_fc_y_vs_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_vs_all(data)

## End(Not run)
```

compute_fc_y_wpss_all *Compute all the fc_y_wpss summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_fc_y_wpss_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_fc_y_wpss_all(data)

## End(Not run)
```

compute_fc_y_wpss_nm *Compute "Wills Problem Solving Scale [Youth]: Number missing"*

Description

Computes the summary score `fc_y_wpss_nm` (Wills Problem Solving Scale [Youth]: Number missing)

- *Summarized variables:*
  - `fc_y_wpss_001`
  - `fc_y_wpss_002`
  - `fc_y_wpss_003`
  - `fc_y_wpss_004`
  - `fc_y_wpss_005`
  - `fc_y_wpss_006`
- *Excluded values:* none

Usage

```
compute_fc_y_wpss_nm(data, name = "fc_y_wpss_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_wpss_mean()

---

compute_fitbit_activity_table

Computes Daily Activity Summaries

Description

Pipeline wrapper that processes Fitbit minute-level activity data into a daily summary table. Applies heart rate-based exclusions and recovery identification, then aggregates minute totals, exclusion summaries, step counts, intensity scores, and sleep presence into a single day-level data frame. Optionally appends Fitbit-generated daily QC measures.

Usage

```
compute_fitbit_activity_table(
  data_activity,
  data_daily,
  hr_low = 50,
  hr_high = NULL,
  hr_rep_day = 10,
  hr_rep_sleep = 30,
  bin_minutes = 1440,
  append_daily_fitbit_qc,
  qc_threshold = 0.8,
  offset = "12:00",
  min_actv_minutes
)
```

Arguments

data_activity	tbl. Data frame with dtt (timestamp), hrate (heart rate), steps, intnst (intensity), mets and is_slp (sleep flag) variables.
data_daily	tbl. Daily-level Fitbit-generated summary data containing hrate_rest_fitb (resting heart rate) and optionally step counts (steps_fitb).
hr_low	numeric. Lower bound threshold for valid heart rate values.
hr_high	numeric or NULL. Optional upper bound threshold for valid heart rate values. If NULL, no upper threshold is applied.
hr_rep_day	numeric. Threshold (number of epochs) for identifying repeated heart rate values during wake/activity periods.
hr_rep_sleep	numeric. Threshold (number of epochs) for identifying repeated heart rate values during sleep periods.
bin_minutes	numeric. Number of minutes used to bin activity data when computing intensity scores (e.g., 1440 for daily aggregation).
append_daily_fitbit_qc	logical. If TRUE, add Fitbit-provided step count and QC measures.
qc_threshold	numeric, between 0 and 1. Minimum percentage of Fitbit step count that must be met by computed active step count for QC to pass (Default: 0.8).
offset	character. Time of day (HH:MM) cutoff.
min_actv_minutes	numeric. Minimum number of active minutes required for a day to pass quality control. Used to create a {qc_Xmin} flag column in the output.

Value

tbl. A daily-level summarized data frame with the following components:

Identifiers and time variables:

- participant_id, session_id
- wk: Study week index
- day: Study day index
- dt: Calendar date
- dt_day: Day of week (labeled)
- dt_wknd: Indicator for weekend days

Activity and sleep measures:

- min_total: Total valid minutes
- min_actv: Active (non-sleep) minutes
- min_slp: Sleep minutes
- min_nap_slp: Nap sleep minutes

Step count measures:

- steps_total: Total steps after exclusions
- steps_actv: Steps during active minutes after exclusions
- steps: Total steps before exclusions
- steps_fitb: Fitbit-reported daily steps

Energy expenditure and intensity-based activity measures:

- mets: Mean METs
- mets_actv: Mean METs during active minutes
- min_intnst_*: Minutes spent in sedentary, light, moderate, and vigorous activity (total and active-only variants)

Heart rate exclusion summaries:

- excl_min_*: Minutes excluded due to heart rate criteria (low, high, missing, repeated) for both activity and sleep domains

Heart rate and QC metrics:

- hrate_rest_fitb: Resting heart rate (Fitbit daily summary)
- qc_600min: Indicator for >= 600 valid active minutes
- qc_steps: Indicator for valid step counts based on Fitbit comparison
- pcnt_steps_fitb: Proportion of calculated steps relative to Fitbit-reported steps

Flags:

- flg_30sec: Indicator that valid 30-second sleep data exists for the day
- flg_any: Indicator that any valid data exists for the day

`compute_fitbit_activity_table_ext` *Computes extended daily activity summaries*

Description

Computes all daily activity scores (extended).

Usage

```
compute_fitbit_activity_table_ext(
  data_activity,
  data_daily = NULL,
  hr_low = 50,
  hr_high = NULL,
  hr_rep_day = 10,
  hr_rep_sleep = 30,
  bin_minutes = 1440,
```

```
  append_daily_fitbit_qc = TRUE,
  qc_threshold = 0.8,
  offset = "12:00",
  min_actv_minutes,
  main_duration,
  gap = 90
)
```

Arguments

data_activity	tbl. Data frame with activity data.
data_daily	tbl. Data frame with daily Fitbit summary data.
hr_low	numeric. Lower bound threshold for valid heart rate values.
hr_high	numeric or NULL. Optional upper bound threshold.
hr_rep_day	numeric. Threshold for identifying repeated HR.
hr_rep_sleep	numeric. Threshold for identifying repeated HR.
bin_minutes	numeric. Number of minutes used to bin data.
append_daily_fitbit_qc	logical. If TRUE, add Fitbit-provided steps.
qc_threshold	numeric, between 0 and 1. Minimum percentage of Fitbit step count that must be met by computed active step count for QC to pass.
offset	character. Time of day (HH:MM) cutoff.
min_actv_minutes	numeric. Minimum number of active minutes required for a day to pass quality control. Used to create a {qc_Xmin} flag column in the output.
main_duration	numeric. Minimum duration in minutes.
gap	numeric. Maximum allowed gap.

Value

tbl. A daily-level extended activity summary.

Note

- data_activity: fitbit_raw_activity or fitbit_covid_raw_activity
- data_daily: fitbit_raw_metrics or fitbit_covid_raw_metrics

See Also

compute_fitbit_activity_table()

compute_fitbit_activity_week
Generates weekly activity summaries

Description

Generates weekly activity summaries from daily Fitbit activity data.

This wrapper function applies a standardized weekly aggregation pipeline using `compute_fitbit_weekly_summary()` and the `summarize_activity()` function to compute weekly activity metrics at the participant-session level.

Only days passing minimum quality control thresholds (`qc_600min` and `qc_steps`) are included in the weekly aggregation.

Usage

```
compute_fitbit_activity_week(df, filter_expr = qc_600min & qc_steps)
```

Arguments

`df`	tbl. Daily-level Fitbit activity dataset (standard or extended), typically `fitbit_ss_activity_day` or `fitbit_ss_ext_activity_day`.
`filter_expr`	expression. Logical filtering condition applied to the input dataset before summarization (e.g., QC thresholds). which retains only days with at least 600 valid minutes and passing step count quality checks.

Details

This function standardizes weekly activity computation across datasets by enforcing consistent filtering, aggregation, and output structure.

Value

tbl. Weekly activity dataset containing:

- Week identifiers (`wk`, `wk_type`)
- Day counts (`n_day`, `n_wkdy`, `n_wknd`)
- Activity summary metrics (steps, METs, intensity minutes, heart rate)
- Weekly quality control flag (`qc_wk`)

Note

- `df`: fitbit_ss_activity_day or fitbit_ss_ext_activity_day (daily Fitbit activity dataset with QC flags)

`compute_fitbit_sleep_table` *Compute daily sleep summaries*

Description

Processes Fitbit minute-level data to generate daily sleep summary scores. This function integrates multiple processing steps, including heart rate-based exclusions and calculation of sleep measures, aggregated at the day level.

Usage

```
compute_fitbit_sleep_table(
  data_activity,
  data_sleep_combined,
  data_daily,
  hr_low = 50,
  hr_high = NULL,
  hr_rep_day = 10,
  hr_rep_sleep = 30,
  bin_minutes = NULL,
  offset = "12:00",
  min_slp_minutes = 300
)
```

Arguments

`data_activity` tbl. Data frame with the following columns with minute-level epoch data with the following columns:

- `participant_id`: Participant identifier
- `session_id`: Session identifier
- `dtt`: POSIXct epoch timestamp
- `dtt` POSIXct epoch timestamp.

`data_sleep_combined` tbl. Data frame with the following columns in 30-second epoch level with the following columns:

- `participant_id`: Participant identifier
- `session_id`: Session identifier
- `dtt`: POSIXct epoch timestamp
- `stage`: Sleep stage classification (e.g., `"light"`, `"deep"`, `"rem"`, `"awake"`).
- `main_slp`: logical. Indicates if epoch is associated with 'main' sleep.

`data_daily` tbl. Daily-level Fitbit-generated summary data containing:

- `participant_id`: Participant identifier
- `session_id`: Session identifier

- dt: Calendar date
- hrate_rest_fitb: Fitbit-reported resting heart rate in beats per minute.

hr_low — numeric. Lower bound threshold for valid heart rate values.

hr_high — numeric or NULL. Optional upper bound threshold for valid heart rate values. If NULL, no upper threshold is applied.

hr_rep_day — numeric. Threshold (number of epochs) for identifying repeated heart rate values during wake/activity periods.

hr_rep_sleep — numeric. Threshold (number of epochs) for identifying repeated heart rate values during sleep periods.

bin_minutes — numeric. Number of minutes used to bin activity data when computing intensity scores (e.g., 1440 for daily aggregation). Default is NULL. When NULL, it uses offset to split days, which by default is 12:00 (noon).

offset — character. Time of day (HH:MM) used as the cutoff for defining the sleep day. Timestamps occuring after this time are assigned to the next day.

min_slp_minutes — numeric. Minimum number of sleep minutes required for a day to pass quality control. Used to create a qc_Xmin flag column in the output.

Value

tbl. A daily-level summarized data frame with the following components:

Identifiers and time variables:

- participant_id, session_id
- wk: Study week index
- day: Study day index
- dt: Calendar date
- dt_day: Day of week (labeled)
- dt_wknd: Indicator for weekend days

Sleep timing measures:

- dtt_start_bed, dtt_end_bed: Bed interval start and end times
- dtt_start_slp, dtt_end_slp: Sleep interval start and end times

Sleep duration measures:

- min_total_slp: Total sleep duration
- min_asleep_slp, min_restless_slp, min_light_slp, min_deep_slp, min_rem_slp: Stage-specific sleep durations
- min_nap_slp: Nap sleep duration
- min_wake: Wake minutes during sleep intervals
- min_waso: Wake after sleep onset (WASO)
- n_waso: Number of WASO episodes

Heart rate summaries by sleep stage:

- `hrate_awake_slp`, `hrate_restless_slp`, `hrate_asleep_slp`
- `hrate_light_slp`, `hrate_deep_slp`, `hrate_rem_slp`
- `hrate_nap_slp`: Mean heart rate during nap sleep
- `hrate_rest_fitb`: Daily resting heart rate from Fitbit

Heart rate exclusion measures:

- `excl_min_total_slp`: Total excluded sleep minutes
- `excl_min_lowhrate_slp`: Minutes excluded due to low heart rate
- `excl_min_nohrate_slp`: Minutes excluded due to missing heart rate
- `excl_min_highhrate_slp`: Minutes excluded due to high heart rate
- `excl_min_repeathrate_slp`: Minutes excluded due to repeated heart rate
- `min_extra_nohrate_slp`: Additional plausible sleep minutes excluded

Quality control and flags:

- `qc_300min`: Indicator for >= 300 minutes of valid sleep
- `flg_slp`: Indicator for implausible sleep structure
- `flg_any`: Indicator that any sleep data are present

Note

`flg_slp`, sleep timing and WASO variables are only calculated when `bin_minutes` is NULL. Calculations depend on offset dates and cannot operate on binned intervals. Returns an empty columns otherwise.

- `data_activity`: fitbit_raw_activity or fitbit_covid_raw_activity
- `data_sleep_combined`: fitbit_raw_sleep or fitbit_covid_raw_sleep
- `data_daily`: fitbit_raw_metrics or fitbit_covid_raw_metrics

`compute_fitbit_sleep_table_ext` *Computes episode-based daily sleep summary measures.*

Description

This function extends the standard sleep pipeline by grouping 30-second sleep epochs into continuous sleep blocks based on a configurable gap threshold, and redefining main sleep periods based on block duration. Heart rate exclusion logic is applied both prior to and after block construction to ensure consistency across raw and reconstructed sleep structures.

Usage

```
compute_fitbit_sleep_table_ext(
  data_activity,
  data_sleep_combined,
  data_daily,
  hr_low = 50,
  hr_high = NULL,
  hr_rep_day = 10,
  hr_rep_sleep = 30,
  bin_minutes = NULL,
  offset = "12:00",
  min_slp_minutes,
  main_duration = 180,
  gap = 90
)
```

Arguments

data_activity	tbl. Epoch-level activity data used to derive heart rate exclusion flags.
data_sleep_combined	tbl. 30-second sleep epoch data containing sleep stage and timestamp information.
data_daily	tbl. Daily Fitbit summary data including resting heart rate.
hr_low	numeric. Lower threshold for valid heart rate values.
hr_high	numeric or NULL. Optional upper threshold for valid heart rate values.
hr_rep_day	numeric. Threshold (number of epochs) for repeated heart rate detection in daytime activity.
hr_rep_sleep	numeric. Threshold (number of epochs) for repeated heart rate detection in sleep.
bin_minutes	numeric. Number of minutes used to bin data.
offset	character. Time-of-day cutoff used to define sleep-day boundaries.
min_slp_minutes	numeric. Minimum number of sleep minutes required for a day to pass quality control. Used to create a `qc_Xmin` flag column in the output.
main_duration	numeric. Minumum duration in minutes for a sleep episode to be qualify as a main sleep episode.
gap	numeric. Maximum allowed gap (in minutes) between consecutive sleep epochs before a new sleep episode is defined.

Details

This extended pipeline differs from the standard sleep table by introducing a episode-based reconstruction step. Sleep epochs are grouped into continuous episodes using a configurable gap threshold, and episode duration is used to define main sleep.

Value

tbl. A daily-level extended sleep summary table containing:

Identifiers and time variables:

- participant_id, session_id
- wk: Study week index
- day: Study day index
- dt: Sleep-aligned date
- dt_day: Day of week
- dt_wknd: Weekend indicator

Sleep timing and block structure:

- dtt_start_bed, dtt_end_bed
- dtt_start_slp, dtt_end_slp

Sleep duration metrics:

- min_total_slp, min_asleep_slp, min_restless_slp, min_light_slp, min_deep_slp, min_rem_slp, min_nap_slp
- min_waso, min_wake, n_waso

Heart rate summaries by sleep stage:

- hrate_awake_slp, hrate_restless_slp, hrate_asleep_slp
- hrate_light_slp, hrate_deep_slp, hrate_rem_slp
- hrate_nap_slp, hrate_rest_fitb

Heart rate exclusion metrics:

- excl_min_total_slp, excl_min_lowhrate_slp
- excl_min_nohrate_slp, excl_min_highhrate_slp
- excl_min_repeathrate_slp, min_extra_nohrate_slp

Quality control flags:

- qc_300min: Indicator for >= 300 minutes of sleep
- flg_slp: Flag for implausible sleep structure
- flg_any: Indicator for any valid sleep data

Note

- data_activity: fitbit_raw_activity or fitbit_covid_raw_activity
- data_sleep_combined: fitbit_raw_sleep or fitbit_covid_raw_sleep
- data_daily: fitbit_raw_metrics or fitbit_covid_raw_metrics

compute_fitbit_sleep_week

Generates weekly sleep summaries from daily Fitbit sleep data.

Description

This wrapper function applies a standardized weekly aggregation pipeline using `compute_fitbit_weekly_summary()` and the `summarize_sleep()` function to compute weekly sleep metrics at the participant-session level.

Only days passing minimum quality control thresholds (`qc_300min`) are included in the weekly aggregation.

Usage

```
compute_fitbit_sleep_week(df, filter_expr = qc_300min)
```

Arguments

`df`	tbl. Daily-level Fitbit sleep dataset (standard or extended), typically `fitbit_ss_sleep_day` or `fitbit_ss_ext_sleep_day`.
`filter_expr`	expression. Logical filtering condition applied to the input dataset before summarization (e.g., QC thresholds).

Details

This function ensures consistent weekly aggregation of sleep metrics across standard and extended Fitbit datasets. It inherits QC filtering from the parent pipeline and preserves both total and stage-specific sleep summaries.

Value

tbl. Weekly sleep dataset containing:

- Week identifiers (`wk`, `wk_type`)
- Day counts (`n_day`, `n_wkdy`, `n_wknd`)
- Sleep timing metrics (bed/sleep onset and offset)
- Sleep duration and stage summaries
- Heart rate–derived sleep metrics
- Wake-after-sleep-onset metrics
- Weekly quality control flag (`qc_wk`)

Note

- `df`: fitbit_ss_sleep_day or fitbit_ss_ext_sleep_day (daily Fitbit sleep dataset with QC flags)

`compute_fitbit_weekly_summary` *Generates weekly summary tables*

Description

Generates weekly summary tables using a user-supplied summarization function, with stratification by weekday, weekend, and full-week estimates.

This function standardizes weekly aggregation by: (1) filtering valid records, (2) computing day counts for quality control, (3) applying a user-defined summarization function, and (4) producing three parallel weekly summaries (whole week, weekday-only, and weekend-only).

Usage

```
compute_fitbit_weekly_summary(
  df,
  wkdy_min = 3,
  wknd_min = 1,
  summarize_fn,
  filter_expr
)
```

Arguments

`df`	tbl. Input daily-level dataset containing at minimum: `participant_id`, `session_id`, `wk`, and `dt_wknd`.
`wkdy_min`	numeric. Minimum number of weekday observations required for a valid weekly weekday estimate.
`wknd_min`	numeric. Minimum number of weekend observations required for a valid weekly weekend estimate.
`summarize_fn`	function. A user-defined function that takes a filtered dataset and returns weekly summaries grouped by `participant_id`, `session_id`, and `wk`.
`filter_expr`	expression. Logical filtering condition applied to the input dataset before summarization (e.g., QC thresholds).

Details

The function uses stratified counting to ensure that weekly estimates are interpretable in the context of data completeness. The QC rule differs by strata:

- Whole week: requires both weekday and weekend minimum counts
- Weekday/weekend: require minimum counts within their respective subsets

The `summarize_fn` argument allows flexible reuse across sleep and activity pipelines while maintaining consistent weekly structure.

Value

tbl. A combined weekly dataset containing three types of summaries:

- `wk_type = 2`: Whole-week estimates (weekday + weekend combined)
- `wk_type = 1`: Weekend-only estimates
- `wk_type = 0`: Weekday-only estimates

Each row includes:

- Weekly summary metrics from `summarize_fn`
- Day count variables (`n_day`, `n_wkdy`, `n_wknd`)
- Quality control flag `qc_wk` indicating sufficient coverage

`compute_mh_p_abcl__afs__frnd_sum` *Compute "Adult Behavior Checklist [Parent] (Adaptive Functioning Scale - Friends): Sum"*

Description

Computes the summary score `mh_p_abcl__afs__frnd_sum` Adult Behavior Checklist [Parent] (Adaptive Functioning Scale - Friends): Sum

- *Summarized variables:*
  - `mh_p_abcl__frnd_001`
  - `mh_p_abcl__frnd_002`
  - `mh_p_abcl__frnd_003`
  - `mh_p_abcl__frnd_004`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
compute_mh_p_abcl__afs__frnd_sum(
  data,
  name = "mh_p_abcl__afs__frnd_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__afs__frnd_nm()

Examples

```
## Not run:
compute_mh_p_abcl__afs__frnd_sum(data) |>
  select(
    any_of(c("mh_p_abcl__afs__frnd_sum", vars_mh_p_abcl__afs__frnd))
  )

## End(Not run)
```

---

compute_mh_p_abcl__afs__frnd_tscore

Compute "Adult Behavior Checklist [Parent] (Adaptive Functioning Scale - Friends): T-score"

Description

Computes the summary score mh_p_abcl__afs__frnd_tscore Adult Behavior Checklist [Parent] (Adaptive Functioning Scale - Friends): T-score

- *Summarized variables:*
  - mh_p_abcl__frnd_001
  - mh_p_abcl__frnd_002
  - mh_p_abcl__frnd_003
  - mh_p_abcl__frnd_004
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
compute_mh_p_abcl__afs__frnd_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__afs__frnd_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__afs__frnd_nm()

Examples

```
## Not run:
compute_mh_p_abcl__afs__frnd_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__afs__frnd_tscore", vars_mh_p_abcl__afs__frnd))
  )

## End(Not run)
```

`compute_mh_p_abcl__critic_sum` *Compute "Adult Behavior Checklist [Parent] (Critical items): Sum"*

Description

Computes the summary score `mh_p_abcl__critic_sum` Adult Behavior Checklist [Parent] (Critical items): Sum

- *Summarized variables:*
  - `mh_p_abcl__rule_001`
  - `mh_p_abcl__attn__adhd_002`
  - `mh_p_abcl__tho_001`
  - `mh_p_abcl__othpr__adhd_001`
  - `mh_p_abcl__anxdep__dep_001`
  - `mh_p_abcl__aggr__antsoc_003`
  - `mh_p_abcl__tho__dep_001`
  - `mh_p_abcl__othpr__antsoc_001`
  - `mh_p_abcl__tho_002`
  - `mh_p_abcl__aggr_001`
  - `mh_p_abcl__aggr__antsoc_006`
  - `mh_p_abcl__tho_003`
  - `mh_p_abcl__tho_004`
  - `mh_p_abcl__tho_006`
  - `mh_p_abcl__rule_002`
  - `mh_p_abcl__tho__dep_002`
  - `mh_p_abcl__rule__antsoc_007`
  - `mh_p_abcl__aggr__antsoc_008`
  - `mh_p_abcl__anxdep__dep_004`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 19 items missing

Usage

```
compute_mh_p_abcl__critic_sum(
  data,
  name = "mh_p_abcl__critic_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__critic_nm()

Examples

```
## Not run:
compute_mh_p_abcl__critic_sum(data) |>
  select(
    any_of(c("mh_p_abcl__critic_sum", vars_mh_p_abcl__critic))
  )

## End(Not run)
```

---

compute_mh_p_abcl__critic_tscore

Compute "Adult Behavior Checklist [Parent] (Critical items): T-score"

Description

Computes the summary score mh_p_abcl__critic_tscore Adult Behavior Checklist [Parent] (Critical items): T-score

- *Summarized variables:*
  - mh_p_abcl__rule_001
  - mh_p_abcl__attn__adhd_002
  - mh_p_abcl__tho_001
  - mh_p_abcl__othpr__adhd_001
  - mh_p_abcl__anxdep__dep_001
  - mh_p_abcl__aggr__antsoc_003

  - mh_p_abcl__tho__dep_001
  - mh_p_abcl__othpr__antsoc_001
  - mh_p_abcl__tho_002
  - mh_p_abcl__aggr_001
  - mh_p_abcl__aggr__antsoc_006
  - mh_p_abcl__tho_003
  - mh_p_abcl__tho_004
  - mh_p_abcl__tho_006
  - mh_p_abcl__rule_002
  - mh_p_abcl__tho__dep_002
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__aggr__antsoc_008
  - mh_p_abcl__anxdep__dep_004
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 19 items missing

Usage

```
compute_mh_p_abcl__critic_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__critic_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__critic_nm()

Examples

```
## Not run:
compute_mh_p_abcl__critic_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__critic_tscore", vars_mh_p_abcl__critic))
  )

## End(Not run)
```

---

compute_mh_p_abcl__dsm__adhd_sum

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): Sum"

Description

Computes the summary score mh_p_abcl__dsm__adhd_sum Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): Sum

- *Summarized variables:*
  - mh_p_abcl__aggr__adhd_001
  - mh_p_abcl__attn__adhd_001
  - mh_p_abcl__attn__adhd_002
  - mh_p_abcl__attn__adhd_003
  - mh_p_abcl__attn__adhd_004
  - mh_p_abcl__attn__adhd_005
  - mh_p_abcl__attn__adhd_006
  - mh_p_abcl__attn__adhd_007
  - mh_p_abcl__othpr__adhd_001
  - mh_p_abcl__othpr__adhd_002
  - mh_p_abcl__othpr__adhd_003
  - mh_p_abcl__othpr__adhd_004
  - mh_p_abcl__rule__adhd_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 13 items missing

Usage

```
compute_mh_p_abcl__dsm__adhd_sum(
  data,
  name = "mh_p_abcl__dsm__adhd_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__adhd_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__adhd_sum(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__adhd_sum", vars_mh_p_abcl__dsm__adhd))
  )

## End(Not run)
```

---

compute_mh_p_abcl__dsm__adhd_tscore

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): T-score"

Description

Computes the summary score `mh_p_abcl__dsm__adhd_tscore` Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): T-score

- *Summarized variables:*
  - `mh_p_abcl__aggr__adhd_001`
  - `mh_p_abcl__attn__adhd_001`
  - `mh_p_abcl__attn__adhd_002`
  - `mh_p_abcl__attn__adhd_003`
  - `mh_p_abcl__attn__adhd_004`
  - `mh_p_abcl__attn__adhd_005`
  - `mh_p_abcl__attn__adhd_006`
  - `mh_p_abcl__attn__adhd_007`
  - `mh_p_abcl__othpr__adhd_001`
  - `mh_p_abcl__othpr__adhd_002`
  - `mh_p_abcl__othpr__adhd_003`
  - `mh_p_abcl__othpr__adhd_004`
  - `mh_p_abcl__rule__adhd_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 13 items missing

Usage

```
compute_mh_p_abcl__dsm__adhd_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__dsm__adhd_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.
`col_sex`	character, name of the sex column. see `ss_tscore()`.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__adhd_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__adhd_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__adhd_tscore", vars_mh_p_abcl__dsm__adhd))
  )

## End(Not run)
```

---

compute_mh_p_abcl__dsm__antsoc_sum

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): Sum"

Description

Computes the summary score mh_p_abcl__dsm__antsoc_sum Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): Sum

- *Summarized variables:*
  - mh_p_abcl__aggr__antsoc_001
  - mh_p_abcl__aggr__antsoc_002
  - mh_p_abcl__aggr__antsoc_003
  - mh_p_abcl__aggr__antsoc_004
  - mh_p_abcl__aggr__antsoc_005
  - mh_p_abcl__aggr__antsoc_006
  - mh_p_abcl__aggr__antsoc_007
  - mh_p_abcl__aggr__antsoc_008
  - mh_p_abcl__attn__antsoc_001
  - mh_p_abcl__othpr__antsoc_001

  - mh_p_abcl__othpr__antsoc_002
  - mh_p_abcl__rule__antsoc_001
  - mh_p_abcl__rule__antsoc_002
  - mh_p_abcl__rule__antsoc_003
  - mh_p_abcl__rule__antsoc_004
  - mh_p_abcl__rule__antsoc_005
  - mh_p_abcl__rule__antsoc_006
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__rule__antsoc_008
  - mh_p_abcl__rule__antsoc_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 20 items missing

Usage

```
compute_mh_p_abcl__dsm__antsoc_sum(
  data,
  name = "mh_p_abcl__dsm__antsoc_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__antsoc_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__antsoc_sum(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__antsoc_sum", vars_mh_p_abcl__dsm__antsoc))
  )

## End(Not run)
```

`compute_mh_p_abcl__dsm__antsoc_tscore`
Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): T-score"

Description

Computes the summary score `mh_p_abcl__dsm__antsoc_tscore` Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): T-score

- *Summarized variables:*
  - `mh_p_abcl__aggr__antsoc_001`
  - `mh_p_abcl__aggr__antsoc_002`
  - `mh_p_abcl__aggr__antsoc_003`
  - `mh_p_abcl__aggr__antsoc_004`
  - `mh_p_abcl__aggr__antsoc_005`
  - `mh_p_abcl__aggr__antsoc_006`
  - `mh_p_abcl__aggr__antsoc_007`
  - `mh_p_abcl__aggr__antsoc_008`
  - `mh_p_abcl__attn__antsoc_001`
  - `mh_p_abcl__othpr__antsoc_001`
  - `mh_p_abcl__othpr__antsoc_002`
  - `mh_p_abcl__rule__antsoc_001`
  - `mh_p_abcl__rule__antsoc_002`
  - `mh_p_abcl__rule__antsoc_003`
  - `mh_p_abcl__rule__antsoc_004`
  - `mh_p_abcl__rule__antsoc_005`
  - `mh_p_abcl__rule__antsoc_006`
  - `mh_p_abcl__rule__antsoc_007`
  - `mh_p_abcl__rule__antsoc_008`
  - `mh_p_abcl__rule__antsoc_009`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 20 items missing

Usage

```
compute_mh_p_abcl__dsm__antsoc_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__dsm__antsoc_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__antsoc_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__antsoc_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__antsoc_tscore", vars_mh_p_abcl__dsm__antsoc))
  )

## End(Not run)
```

`compute_mh_p_abcl__dsm__anx_sum`

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety problems): Sum"

Description

Computes the summary score `mh_p_abcl__dsm__anx_sum` Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety problems): Sum

- *Summarized variables:*
  - `mh_p_abcl__anxdep__anx_001`
  - `mh_p_abcl__anxdep__anx_002`
  - `mh_p_abcl__anxdep__anx_003`
  - `mh_p_abcl__othpr__anx_001`
  - `mh_p_abcl__othpr__anx_002`
  - `mh_p_abcl__othpr__anx_003`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_p_abcl__dsm__anx_sum(
  data,
  name = "mh_p_abcl__dsm__anx_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_p_abcl__dsm__anx_nm()`

Examples

```
## Not run:
compute_mh_p_abcl__dsm__anx_sum(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__anx_sum", vars_mh_p_abcl__dsm__anx))
  )

## End(Not run)
```

---

compute_mh_p_abcl__dsm__anx_tscore

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety problems): T-score"

Description

Computes the summary score `mh_p_abcl__dsm__anx_tscore` Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety problems): T-score

- *Summarized variables:*
  - `mh_p_abcl__anxdep__anx_001`
  - `mh_p_abcl__anxdep__anx_002`
  - `mh_p_abcl__anxdep__anx_003`
  - `mh_p_abcl__othpr__anx_001`
  - `mh_p_abcl__othpr__anx_002`
  - `mh_p_abcl__othpr__anx_003`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_p_abcl__dsm__anx_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__dsm__anx_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__anx_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__anx_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__anx_tscore", vars_mh_p_abcl__dsm__anx))
  )

## End(Not run)
```

`compute_mh_p_abcl__dsm__avoid_sum`
Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): Sum"

Description

Computes the summary score `mh_p_abcl__dsm__avoid_sum` Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): Sum

- *Summarized variables:*
  - `mh_p_abcl__anxdep__avoid_001`
  - `mh_p_abcl__anxdep__avoid_002`
  - `mh_p_abcl__othpr__avoid_001`
  - `mh_p_abcl__wthdr__avoid_001`
  - `mh_p_abcl__wthdr__avoid_002`
  - `mh_p_abcl__wthdr__avoid_003`
  - `mh_p_abcl__wthdr__avoid_004`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_abcl__dsm__avoid_sum(
  data,
  name = "mh_p_abcl__dsm__avoid_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__avoid_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__avoid_sum(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__avoid_sum", vars_mh_p_abcl__dsm__avoid))
  )

## End(Not run)
```

---

compute_mh_p_abcl__dsm__avoid_tscore

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): T-score"

Description

Computes the summary score mh_p_abcl__dsm__avoid_tscore Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): T-score

- *Summarized variables:*
  - mh_p_abcl__anxdep__avoid_001
  - mh_p_abcl__anxdep__avoid_002
  - mh_p_abcl__othpr__avoid_001
  - mh_p_abcl__wthdr__avoid_001
  - mh_p_abcl__wthdr__avoid_002
  - mh_p_abcl__wthdr__avoid_003
  - mh_p_abcl__wthdr__avoid_004
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_abcl__dsm__avoid_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__dsm__avoid_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__avoid_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__avoid_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__avoid_tscore", vars_mh_p_abcl__dsm__avoid))
  )

## End(Not run)
```

`compute_mh_p_abcl__dsm__dep_sum`
Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): Sum"

Description

Computes the summary score `mh_p_abcl__dsm__dep_sum` Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): Sum

- *Summarized variables:*
  - `mh_p_abcl__anxdep__dep_001`
  - `mh_p_abcl__anxdep__dep_002`
  - `mh_p_abcl__anxdep__dep_003`
  - `mh_p_abcl__anxdep__dep_004`
  - `mh_p_abcl__anxdep__dep_005`
  - `mh_p_abcl__attn__dep_001`
  - `mh_p_abcl__attn__dep_002`
  - `mh_p_abcl__attn__dep_003`
  - `mh_p_abcl__othpr__dep_001`
  - `mh_p_abcl__othpr__dep_002`
  - `mh_p_abcl__othpr__dep_003`
  - `mh_p_abcl__som__dep_001`
  - `mh_p_abcl__tho__dep_001`
  - `mh_p_abcl__tho__dep_002`
  - `mh_p_abcl__wthdr__dep_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 15 items missing

Usage

```
compute_mh_p_abcl__dsm__dep_sum(
  data,
  name = "mh_p_abcl__dsm__dep_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__dep_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__dep_sum(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__dep_sum", vars_mh_p_abcl__dsm__dep))
  )

## End(Not run)
```

---

compute_mh_p_abcl__dsm__dep_tscore

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): T-score"

Description

Computes the summary score mh_p_abcl__dsm__dep_tscore Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): T-score

- *Summarized variables:*
  - mh_p_abcl__anxdep__dep_001
  - mh_p_abcl__anxdep__dep_002
  - mh_p_abcl__anxdep__dep_003
  - mh_p_abcl__anxdep__dep_004
  - mh_p_abcl__anxdep__dep_005
  - mh_p_abcl__attn__dep_001

  - mh_p_abcl__attn__dep_002
  - mh_p_abcl__attn__dep_003
  - mh_p_abcl__othpr__dep_001
  - mh_p_abcl__othpr__dep_002
  - mh_p_abcl__othpr__dep_003
  - mh_p_abcl__som__dep_001
  - mh_p_abcl__tho__dep_001
  - mh_p_abcl__tho__dep_002
  - mh_p_abcl__wthdr__dep_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 15 items missing

Usage

```
compute_mh_p_abcl__dsm__dep_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__dsm__dep_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__dep_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__dep_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__dep_tscore", vars_mh_p_abcl__dsm__dep))
  )

## End(Not run)
```

---

compute_mh_p_abcl__dsm__somat_sum

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): Sum"

Description

Computes the summary score mh_p_abcl__dsm__somat_sum Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): Sum

- *Summarized variables:*
  - mh_p_abcl__som__somat_001
  - mh_p_abcl__som__somat_002
  - mh_p_abcl__som__somat_003
  - mh_p_abcl__som__somat_004
  - mh_p_abcl__som__somat_005
  - mh_p_abcl__som__somat_006
  - mh_p_abcl__som__somat_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_abcl__dsm__somat_sum(
  data,
  name = "mh_p_abcl__dsm__somat_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__somat_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__somat_sum(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__somat_sum", vars_mh_p_abcl__dsm__somat))
  )

## End(Not run)
```

---

compute_mh_p_abcl__dsm__somat_tscore

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): T-score"

Description

Computes the summary score mh_p_abcl__dsm__somat_tscore Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): T-score

- *Summarized variables:*
  - mh_p_abcl__som__somat_001
  - mh_p_abcl__som__somat_002
  - mh_p_abcl__som__somat_003
  - mh_p_abcl__som__somat_004
  - mh_p_abcl__som__somat_005
  - mh_p_abcl__som__somat_006

  - mh_p_abcl__som__somat_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_abcl__dsm__somat_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__dsm__somat_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__dsm__somat_nm()

Examples

```
## Not run:
compute_mh_p_abcl__dsm__somat_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__somat_tscore", vars_mh_p_abcl__dsm__somat))
```

```
  )

## End(Not run)
```

`compute_mh_p_abcl__su__drg_sum`
Compute "Adult Behavior Checklist [Parent] (Days drug use): Sum"

Description

Computes the summary score `mh_p_abcl__su__drg_sum` Adult Behavior Checklist [Parent] (Days drug use): Sum

- *Summarized variables:*
  - `mh_p_abcl__drg_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
compute_mh_p_abcl__su__drg_sum(
  data,
  name = "mh_p_abcl__su__drg_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

compute_mh_p_abcl__su__drg_nm()

Examples

```
## Not run:
compute_mh_p_abcl__su__drg_sum(data) |>
  select(
    any_of(c("mh_p_abcl__su__drg_sum", vars_mh_p_abcl__su__drg))
  )

## End(Not run)
```

---

compute_mh_p_abcl__su__drg_tscore

Compute "Adult Behavior Checklist [Parent] (Days drug use): T-score"

Description

Computes the summary score mh_p_abcl__su__drg_tscore Adult Behavior Checklist [Parent] (Days drug use): T-score

- *Summarized variables:*
  - mh_p_abcl__drg_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
compute_mh_p_abcl__su__drg_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__su__drg_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__su__drg_nm()

Examples

```
## Not run:
compute_mh_p_abcl__su__drg_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__su__drg_tscore", vars_mh_p_abcl__su__drg))
  )

## End(Not run)
```

---

compute_mh_p_abcl__su__drunk_sum

Compute "Adult Behavior Checklist [Parent] (Days Drunk): Sum"

Description

Computes the summary score mh_p_abcl__su__drunk_sum Adult Behavior Checklist [Parent] (Days Drunk): Sum

- *Summarized variables:*
  - mh_p_abcl__drunk_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
compute_mh_p_abcl__su__drunk_sum(
  data,
  name = "mh_p_abcl__su__drunk_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__su__drunk_nm()

Examples

```
## Not run:
compute_mh_p_abcl__su__drunk_sum(data) |>
  select(
    any_of(c("mh_p_abcl__su__drunk_sum", vars_mh_p_abcl__su__drunk))
  )

## End(Not run)
```

---

compute_mh_p_abcl__su__drunk_tscore

Compute "Adult Behavior Checklist [Parent] (Days Drunk): T-score"

Description

Computes the summary score `mh_p_abcl__su__drunk_tscore` Adult Behavior Checklist [Parent] (Days Drunk): T-score

- *Summarized variables:*
  - `mh_p_abcl__drunk_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
compute_mh_p_abcl__su__drunk_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__su__drunk_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.
`col_sex`	character, name of the sex column. see `ss_tscore()`.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_p_abcl__su__drunk_nm()`

Examples

```
## Not run:
compute_mh_p_abcl__su__drunk_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__su__drunk_tscore", vars_mh_p_abcl__su__drunk))
  )

## End(Not run)
```

`compute_mh_p_abcl__su__nic_sum`
Compute "Adult Behavior Checklist [Parent] (Tobacco per day): Sum"

Description

Computes the summary score `mh_p_abcl__su__nic_sum` Adult Behavior Checklist [Parent] (Tobacco per day): Sum

- *Summarized variables:*
  - `mh_p_abcl__nic_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
compute_mh_p_abcl__su__nic_sum(
  data,
  name = "mh_p_abcl__su__nic_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__su__nic_nm()

Examples

```
## Not run:
compute_mh_p_abcl__su__nic_sum(data) |>
  select(
    any_of(c("mh_p_abcl__su__nic_sum", vars_mh_p_abcl__su__nic))
  )

## End(Not run)
```

---

compute_mh_p_abcl__su__nic_tscore

Compute "Adult Behavior Checklist [Parent] (Tobacco per day): T-score"

Description

Computes the summary score mh_p_abcl__su__nic_tscore Adult Behavior Checklist [Parent] (Tobacco per day): T-score

- *Summarized variables:*
  - mh_p_abcl__nic_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
compute_mh_p_abcl__su__nic_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__su__nic_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__su__nic_nm()

Examples

```
## Not run:
compute_mh_p_abcl__su__nic_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__su__nic_tscore", vars_mh_p_abcl__su__nic))
  )

## End(Not run)
```

---

compute_mh_p_abcl__su_sum

Compute "Adult Behavior Checklist [Parent] (Substance use): Sum"

Description

Computes the summary score mh_p_abcl__su_sum Adult Behavior Checklist [Parent] (Substance use): Sum

- *Summarized variables:*
  - mh_p_abcl__drg_001
  - mh_p_abcl__drunk_001
  - mh_p_abcl__nic_001
- *Excluded values:*

  - 777
  - 999
- *Validation criterion:* maximally 0 of 3 items missing

Usage

```
compute_mh_p_abcl__su_sum(
  data,
  name = "mh_p_abcl__su_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__su_nm()

Examples

```
## Not run:
compute_mh_p_abcl__su_sum(data) |>
  select(
    any_of(c("mh_p_abcl__su_sum", vars_mh_p_abcl__su))
  )

## End(Not run)
```

`compute_mh_p_abcl__su_tscore` *Compute "Adult Behavior Checklist [Parent] (Substance use): T-score"*

Description

Computes the summary score `mh_p_abcl__su_tscore` Adult Behavior Checklist [Parent] (Substance use): T-score

- *Summarized variables:*
  - `mh_p_abcl__drg_001`
  - `mh_p_abcl__drunk_001`
  - `mh_p_abcl__nic_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 3 items missing

Usage

```
compute_mh_p_abcl__su_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__su_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.
`col_sex`	character, name of the sex column. see `ss_tscore()`.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__su_nm()

Examples

```
## Not run:
compute_mh_p_abcl__su_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__su_tscore", vars_mh_p_abcl__su))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__aggr_sum

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): Sum"

Description

Computes the summary score mh_p_abcl__synd__aggr_sum Adult Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): Sum

- *Summarized variables:*
  - mh_p_abcl__aggr_001
  - mh_p_abcl__aggr_002
  - mh_p_abcl__aggr_003
  - mh_p_abcl__aggr_004
  - mh_p_abcl__aggr_005
  - mh_p_abcl__aggr_006
  - mh_p_abcl__aggr_007
  - mh_p_abcl__aggr__adhd_001
  - mh_p_abcl__aggr__antsoc_001
  - mh_p_abcl__aggr__antsoc_002
  - mh_p_abcl__aggr__antsoc_003
  - mh_p_abcl__aggr__antsoc_004
  - mh_p_abcl__aggr__antsoc_005
  - mh_p_abcl__aggr__antsoc_006
  - mh_p_abcl__aggr__antsoc_007
  - mh_p_abcl__aggr__antsoc_008
- *Excluded values:*

  - 777
  - 999
- *Validation criterion:* maximally 1 of 16 items missing

Usage

```
compute_mh_p_abcl__synd__aggr_sum(
  data,
  name = "mh_p_abcl__synd__aggr_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__aggr_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__aggr_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__aggr_sum", vars_mh_p_abcl__synd__aggr))
  )

## End(Not run)
```

`compute_mh_p_abcl__synd__aggr_tscore`
Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): T-score"

Description

Computes the summary score `mh_p_abcl__synd__aggr_tscore` Adult Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): T-score

- *Summarized variables:*
  - `mh_p_abcl__aggr_001`
  - `mh_p_abcl__aggr_002`
  - `mh_p_abcl__aggr_003`
  - `mh_p_abcl__aggr_004`
  - `mh_p_abcl__aggr_005`
  - `mh_p_abcl__aggr_006`
  - `mh_p_abcl__aggr_007`
  - `mh_p_abcl__aggr__adhd_001`
  - `mh_p_abcl__aggr__antsoc_001`
  - `mh_p_abcl__aggr__antsoc_002`
  - `mh_p_abcl__aggr__antsoc_003`
  - `mh_p_abcl__aggr__antsoc_004`
  - `mh_p_abcl__aggr__antsoc_005`
  - `mh_p_abcl__aggr__antsoc_006`
  - `mh_p_abcl__aggr__antsoc_007`
  - `mh_p_abcl__aggr__antsoc_008`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 16 items missing

Usage

```
compute_mh_p_abcl__synd__aggr_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__aggr_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__aggr_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__aggr_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__aggr_tscore", vars_mh_p_abcl__synd__aggr))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__anxdep_sum

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): Sum"

Description

Computes the summary score mh_p_abcl__synd__anxdep_sum Adult Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): Sum

- *Summarized variables:*
  - mh_p_abcl__anxdep_001
  - mh_p_abcl__anxdep_002
  - mh_p_abcl__anxdep_003

  - mh_p_abcl__anxdep_004
  - mh_p_abcl__anxdep__anx_001
  - mh_p_abcl__anxdep__anx_002
  - mh_p_abcl__anxdep__anx_003
  - mh_p_abcl__anxdep__avoid_001
  - mh_p_abcl__anxdep__avoid_002
  - mh_p_abcl__anxdep__dep_001
  - mh_p_abcl__anxdep__dep_002
  - mh_p_abcl__anxdep__dep_003
  - mh_p_abcl__anxdep__dep_004
  - mh_p_abcl__anxdep__dep_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 14 items missing

Usage

```
compute_mh_p_abcl__synd__anxdep_sum(
  data,
  name = "mh_p_abcl__synd__anxdep_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__anxdep_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__anxdep_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__anxdep_sum", vars_mh_p_abcl__synd__anxdep))
  )

## End(Not run)
```

`compute_mh_p_abcl__synd__anxdep_tscore`

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): T-score"

Description

Computes the summary score `mh_p_abcl__synd__anxdep_tscore` Adult Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): T-score

- *Summarized variables:*
  - `mh_p_abcl__anxdep_001`
  - `mh_p_abcl__anxdep_002`
  - `mh_p_abcl__anxdep_003`
  - `mh_p_abcl__anxdep_004`
  - `mh_p_abcl__anxdep__anx_001`
  - `mh_p_abcl__anxdep__anx_002`
  - `mh_p_abcl__anxdep__anx_003`
  - `mh_p_abcl__anxdep__avoid_001`
  - `mh_p_abcl__anxdep__avoid_002`
  - `mh_p_abcl__anxdep__dep_001`
  - `mh_p_abcl__anxdep__dep_002`
  - `mh_p_abcl__anxdep__dep_003`
  - `mh_p_abcl__anxdep__dep_004`
  - `mh_p_abcl__anxdep__dep_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 14 items missing

Usage

```
compute_mh_p_abcl__synd__anxdep_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__anxdep_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__anxdep_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__anxdep_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__anxdep_tscore", vars_mh_p_abcl__synd__anxdep))
  )

## End(Not run)
```

`compute_mh_p_abcl__synd__attn_sum`
Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Attention problems): Sum"

Description

Computes the summary score `mh_p_abcl__synd__attn_sum` Adult Behavior Checklist [Parent] (Syndrome Scale - Attention problems): Sum

- *Summarized variables:*
  - `mh_p_abcl__attn_001`
  - `mh_p_abcl__attn_002`
  - `mh_p_abcl__attn_003`
  - `mh_p_abcl__attn_004`
  - `mh_p_abcl__attn_005`
  - `mh_p_abcl__attn_006`
  - `mh_p_abcl__attn__adhd_001`
  - `mh_p_abcl__attn__adhd_002`
  - `mh_p_abcl__attn__adhd_003`
  - `mh_p_abcl__attn__adhd_004`
  - `mh_p_abcl__attn__adhd_005`
  - `mh_p_abcl__attn__adhd_006`
  - `mh_p_abcl__attn__adhd_007`
  - `mh_p_abcl__attn__antsoc_001`
  - `mh_p_abcl__attn__dep_001`
  - `mh_p_abcl__attn__dep_002`
  - `mh_p_abcl__attn__dep_003`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 17 items missing

Usage

```
compute_mh_p_abcl__synd__attn_sum(
  data,
  name = "mh_p_abcl__synd__attn_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__attn_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__attn_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__attn_sum", vars_mh_p_abcl__synd__attn))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__attn_tscore

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Attention problems): T-score"

Description

Computes the summary score mh_p_abcl__synd__attn_tscore Adult Behavior Checklist [Parent] (Syndrome Scale - Attention problems): T-score

- *Summarized variables:*
  - mh_p_abcl__attn_001
  - mh_p_abcl__attn_002
  - mh_p_abcl__attn_003
  - mh_p_abcl__attn_004
  - mh_p_abcl__attn_005
  - mh_p_abcl__attn_006

  - mh_p_abcl__attn__adhd_001
  - mh_p_abcl__attn__adhd_002
  - mh_p_abcl__attn__adhd_003
  - mh_p_abcl__attn__adhd_004
  - mh_p_abcl__attn__adhd_005
  - mh_p_abcl__attn__adhd_006
  - mh_p_abcl__attn__adhd_007
  - mh_p_abcl__attn__antsoc_001
  - mh_p_abcl__attn__dep_001
  - mh_p_abcl__attn__dep_002
  - mh_p_abcl__attn__dep_003
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 17 items missing

Usage

```
compute_mh_p_abcl__synd__attn_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__attn_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__attn_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__attn_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__attn_tscore", vars_mh_p_abcl__synd__attn))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__ext_sum

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - External): Sum"

Description

Computes the summary score mh_p_abcl__synd__ext_sum Adult Behavior Checklist [Parent] (Syndrome Scale - External): Sum

- *Summarized variables:*
  - mh_p_abcl__aggr_001
  - mh_p_abcl__aggr_002
  - mh_p_abcl__aggr_003
  - mh_p_abcl__aggr_004
  - mh_p_abcl__aggr_005
  - mh_p_abcl__aggr_006
  - mh_p_abcl__aggr_007
  - mh_p_abcl__aggr__adhd_001
  - mh_p_abcl__aggr__antsoc_001
  - mh_p_abcl__aggr__antsoc_002
  - mh_p_abcl__aggr__antsoc_003
  - mh_p_abcl__aggr__antsoc_004
  - mh_p_abcl__aggr__antsoc_005
  - mh_p_abcl__aggr__antsoc_006
  - mh_p_abcl__aggr__antsoc_007
  - mh_p_abcl__aggr__antsoc_008
  - mh_p_abcl__rule_001

  - mh_p_abcl__rule_002
  - mh_p_abcl__rule_003
  - mh_p_abcl__rule__adhd_001
  - mh_p_abcl__rule__antsoc_001
  - mh_p_abcl__rule__antsoc_002
  - mh_p_abcl__rule__antsoc_003
  - mh_p_abcl__rule__antsoc_004
  - mh_p_abcl__rule__antsoc_005
  - mh_p_abcl__rule__antsoc_006
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__rule__antsoc_008
  - mh_p_abcl__rule__antsoc_009
  - mh_p_abcl__intru_001
  - mh_p_abcl__intru_002
  - mh_p_abcl__intru_003
  - mh_p_abcl__intru_004
  - mh_p_abcl__intru_005
  - mh_p_abcl__intru_006
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 35 items missing

Usage

```
compute_mh_p_abcl__synd__ext_sum(
  data,
  name = "mh_p_abcl__synd__ext_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__ext_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__ext_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__ext_sum", vars_mh_p_abcl__synd__ext))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__ext_tscore

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - External): T-score"

Description

Computes the summary score mh_p_abcl__synd__ext_tscore Adult Behavior Checklist [Parent] (Syndrome Scale - External): T-score

- *Summarized variables:*
  - mh_p_abcl__aggr_001
  - mh_p_abcl__aggr_002
  - mh_p_abcl__aggr_003
  - mh_p_abcl__aggr_004
  - mh_p_abcl__aggr_005
  - mh_p_abcl__aggr_006
  - mh_p_abcl__aggr_007
  - mh_p_abcl__aggr__adhd_001
  - mh_p_abcl__aggr__antsoc_001
  - mh_p_abcl__aggr__antsoc_002
  - mh_p_abcl__aggr__antsoc_003
  - mh_p_abcl__aggr__antsoc_004
  - mh_p_abcl__aggr__antsoc_005
  - mh_p_abcl__aggr__antsoc_006
  - mh_p_abcl__aggr__antsoc_007
  - mh_p_abcl__aggr__antsoc_008
  - mh_p_abcl__rule_001

  - mh_p_abcl__rule_002
  - mh_p_abcl__rule_003
  - mh_p_abcl__rule__adhd_001
  - mh_p_abcl__rule__antsoc_001
  - mh_p_abcl__rule__antsoc_002
  - mh_p_abcl__rule__antsoc_003
  - mh_p_abcl__rule__antsoc_004
  - mh_p_abcl__rule__antsoc_005
  - mh_p_abcl__rule__antsoc_006
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__rule__antsoc_008
  - mh_p_abcl__rule__antsoc_009
  - mh_p_abcl__intru_001
  - mh_p_abcl__intru_002
  - mh_p_abcl__intru_003
  - mh_p_abcl__intru_004
  - mh_p_abcl__intru_005
  - mh_p_abcl__intru_006
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 35 items missing

Usage

```
compute_mh_p_abcl__synd__ext_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__ext_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__ext_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__ext_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__ext_tscore", vars_mh_p_abcl__synd__ext))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__int_sum

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Internalizing): Sum"

Description

Computes the summary score mh_p_abcl__synd__int_sum Adult Behavior Checklist [Parent] (Syndrome Scale - Internalizing): Sum

- *Summarized variables:*
  - mh_p_abcl__anxdep_001
  - mh_p_abcl__anxdep_002
  - mh_p_abcl__anxdep_003
  - mh_p_abcl__anxdep_004
  - mh_p_abcl__anxdep__anx_001
  - mh_p_abcl__anxdep__anx_002
  - mh_p_abcl__anxdep__anx_003
  - mh_p_abcl__anxdep__avoid_001
  - mh_p_abcl__anxdep__avoid_002
  - mh_p_abcl__anxdep__dep_001

  - mh_p_abcl__anxdep__dep_002
  - mh_p_abcl__anxdep__dep_003
  - mh_p_abcl__anxdep__dep_004
  - mh_p_abcl__anxdep__dep_005
  - mh_p_abcl__wthdr_001
  - mh_p_abcl__wthdr_002
  - mh_p_abcl__wthdr_003
  - mh_p_abcl__wthdr_004
  - mh_p_abcl__wthdr__avoid_001
  - mh_p_abcl__wthdr__avoid_002
  - mh_p_abcl__wthdr__avoid_003
  - mh_p_abcl__wthdr__avoid_004
  - mh_p_abcl__wthdr__dep_001
  - mh_p_abcl__som_001
  - mh_p_abcl__som__dep_001
  - mh_p_abcl__som__somat_001
  - mh_p_abcl__som__somat_002
  - mh_p_abcl__som__somat_003
  - mh_p_abcl__som__somat_004
  - mh_p_abcl__som__somat_005
  - mh_p_abcl__som__somat_006
  - mh_p_abcl__som__somat_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 32 items missing

Usage

```
compute_mh_p_abcl__synd__int_sum(
  data,
  name = "mh_p_abcl__synd__int_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.

combine — logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__int_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__int_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__int_sum", vars_mh_p_abcl__synd__int))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__int_tscore

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Internalizing): T-score"

Description

Computes the summary score mh_p_abcl__synd__int_tscore Adult Behavior Checklist [Parent] (Syndrome Scale - Internalizing): T-score

- *Summarized variables:*
  - mh_p_abcl__anxdep_001
  - mh_p_abcl__anxdep_002
  - mh_p_abcl__anxdep_003
  - mh_p_abcl__anxdep_004
  - mh_p_abcl__anxdep__anx_001
  - mh_p_abcl__anxdep__anx_002
  - mh_p_abcl__anxdep__anx_003
  - mh_p_abcl__anxdep__avoid_001
  - mh_p_abcl__anxdep__avoid_002
  - mh_p_abcl__anxdep__dep_001
  - mh_p_abcl__anxdep__dep_002
  - mh_p_abcl__anxdep__dep_003
  - mh_p_abcl__anxdep__dep_004

  - mh_p_abcl__anxdep__dep_005
  - mh_p_abcl__wthdr_001
  - mh_p_abcl__wthdr_002
  - mh_p_abcl__wthdr_003
  - mh_p_abcl__wthdr_004
  - mh_p_abcl__wthdr__avoid_001
  - mh_p_abcl__wthdr__avoid_002
  - mh_p_abcl__wthdr__avoid_003
  - mh_p_abcl__wthdr__avoid_004
  - mh_p_abcl__wthdr__dep_001
  - mh_p_abcl__som_001
  - mh_p_abcl__som__dep_001
  - mh_p_abcl__som__somat_001
  - mh_p_abcl__som__somat_002
  - mh_p_abcl__som__somat_003
  - mh_p_abcl__som__somat_004
  - mh_p_abcl__som__somat_005
  - mh_p_abcl__som__somat_006
  - mh_p_abcl__som__somat_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 32 items missing

Usage

```
compute_mh_p_abcl__synd__int_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__int_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__int_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__int_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__int_tscore", vars_mh_p_abcl__synd__int))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__intru_sum

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Intrusive): Sum"

Description

Computes the summary score mh_p_abcl__synd__intru_sum Adult Behavior Checklist [Parent] (Syndrome Scale - Intrusive): Sum

- *Summarized variables:*
  - mh_p_abcl__intru_001
  - mh_p_abcl__intru_002
  - mh_p_abcl__intru_003
  - mh_p_abcl__intru_004
  - mh_p_abcl__intru_005
  - mh_p_abcl__intru_006
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_p_abcl__synd__intru_sum(
  data,
  name = "mh_p_abcl__synd__intru_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__intru_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__intru_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__intru_sum", vars_mh_p_abcl__synd__intru))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__intru_tscore

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Intrusive): T-score"

Description

Computes the summary score mh_p_abcl__synd__intru_tscore Adult Behavior Checklist [Parent] (Syndrome Scale - Intrusive): T-score

- *Summarized variables:*
  - mh_p_abcl__intru_001
  - mh_p_abcl__intru_002
  - mh_p_abcl__intru_003
  - mh_p_abcl__intru_004
  - mh_p_abcl__intru_005
  - mh_p_abcl__intru_006
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_p_abcl__synd__intru_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__intru_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__intru_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__intru_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__intru_tscore", vars_mh_p_abcl__synd__intru))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__othpr_sum

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Other problems): Sum"

Description

Computes the summary score mh_p_abcl__synd__othpr_sum Adult Behavior Checklist [Parent] (Syndrome Scale - Other problems): Sum

- *Summarized variables:*
  - mh_p_abcl__othpr_001
  - mh_p_abcl__othpr_002
  - mh_p_abcl__othpr_003
  - mh_p_abcl__othpr_004
  - mh_p_abcl__othpr_005
  - mh_p_abcl__othpr_006
  - mh_p_abcl__othpr_007
  - mh_p_abcl__othpr_008
  - mh_p_abcl__othpr_009
  - mh_p_abcl__othpr_010
  - mh_p_abcl__othpr_011
  - mh_p_abcl__othpr_012
  - mh_p_abcl__othpr__adhd_001
  - mh_p_abcl__othpr__adhd_002
  - mh_p_abcl__othpr__adhd_003
  - mh_p_abcl__othpr__adhd_004
  - mh_p_abcl__othpr__antsoc_001
  - mh_p_abcl__othpr__antsoc_002
  - mh_p_abcl__othpr__anx_001
  - mh_p_abcl__othpr__anx_002

  - mh_p_abcl__othpr__anx_003
  - mh_p_abcl__othpr__avoid_001
  - mh_p_abcl__othpr__dep_001
  - mh_p_abcl__othpr__dep_002
  - mh_p_abcl__othpr__dep_003
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 25 items missing

Usage

```
compute_mh_p_abcl__synd__othpr_sum(
  data,
  name = "mh_p_abcl__synd__othpr_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__othpr_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__othpr_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__othpr_sum", vars_mh_p_abcl__synd__othpr))
  )

## End(Not run)
```

compute_mh_p_abcl__synd__rule_sum
Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): Sum"

Description

Computes the summary score mh_p_abcl__synd__rule_sum Adult Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): Sum

- *Summarized variables:*
  - mh_p_abcl__rule_001
  - mh_p_abcl__rule_002
  - mh_p_abcl__rule_003
  - mh_p_abcl__rule__adhd_001
  - mh_p_abcl__rule__antsoc_001
  - mh_p_abcl__rule__antsoc_002
  - mh_p_abcl__rule__antsoc_003
  - mh_p_abcl__rule__antsoc_004
  - mh_p_abcl__rule__antsoc_005
  - mh_p_abcl__rule__antsoc_006
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__rule__antsoc_008
  - mh_p_abcl__rule__antsoc_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 13 items missing

Usage

```
compute_mh_p_abcl__synd__rule_sum(
  data,
  name = "mh_p_abcl__synd__rule_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__rule_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__rule_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__rule_sum", vars_mh_p_abcl__synd__rule))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__rule_tscore

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): T-score"

Description

Computes the summary score mh_p_abcl__synd__rule_tscore Adult Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): T-score

- *Summarized variables:*
  - mh_p_abcl__rule_001
  - mh_p_abcl__rule_002
  - mh_p_abcl__rule_003
  - mh_p_abcl__rule__adhd_001
  - mh_p_abcl__rule__antsoc_001
  - mh_p_abcl__rule__antsoc_002
  - mh_p_abcl__rule__antsoc_003
  - mh_p_abcl__rule__antsoc_004
  - mh_p_abcl__rule__antsoc_005
  - mh_p_abcl__rule__antsoc_006

  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__rule__antsoc_008
  - mh_p_abcl__rule__antsoc_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 13 items missing

Usage

```
compute_mh_p_abcl__synd__rule_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__rule_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__rule_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__rule_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__rule_tscore", vars_mh_p_abcl__synd__rule))
  )

## End(Not run)
```

`compute_mh_p_abcl__synd__som_sum`

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): Sum"

Description

Computes the summary score `mh_p_abcl__synd__som_sum` Adult Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): Sum

- *Summarized variables:*
  - `mh_p_abcl__som_001`
  - `mh_p_abcl__som__dep_001`
  - `mh_p_abcl__som__somat_001`
  - `mh_p_abcl__som__somat_002`
  - `mh_p_abcl__som__somat_003`
  - `mh_p_abcl__som__somat_004`
  - `mh_p_abcl__som__somat_005`
  - `mh_p_abcl__som__somat_006`
  - `mh_p_abcl__som__somat_007`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_abcl__synd__som_sum(
  data,
  name = "mh_p_abcl__synd__som_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__som_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__som_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__som_sum", vars_mh_p_abcl__synd__som))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__som_tscore

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): T-score"

Description

Computes the summary score mh_p_abcl__synd__som_tscore Adult Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): T-score

- *Summarized variables:*
  - mh_p_abcl__som_001
  - mh_p_abcl__som__dep_001
  - mh_p_abcl__som__somat_001
  - mh_p_abcl__som__somat_002
  - mh_p_abcl__som__somat_003
  - mh_p_abcl__som__somat_004

  - mh_p_abcl__som__somat_005
  - mh_p_abcl__som__somat_006
  - mh_p_abcl__som__somat_007

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_abcl__synd__som_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__som_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__som_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__som_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__som_tscore", vars_mh_p_abcl__synd__som))
  )

## End(Not run)
```

`compute_mh_p_abcl__synd__tho_sum`

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Thought problems): Sum"

Description

Computes the summary score `mh_p_abcl__synd__tho_sum` Adult Behavior Checklist [Parent] (Syndrome Scale - Thought problems): Sum

- *Summarized variables:*
  - `mh_p_abcl__tho_001`
  - `mh_p_abcl__tho_002`
  - `mh_p_abcl__tho_003`
  - `mh_p_abcl__tho_004`
  - `mh_p_abcl__tho_005`
  - `mh_p_abcl__tho_006`
  - `mh_p_abcl__tho_007`
  - `mh_p_abcl__tho__dep_001`
  - `mh_p_abcl__tho__dep_002`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_abcl__synd__tho_sum(
  data,
  name = "mh_p_abcl__synd__tho_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__tho_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__tho_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__tho_sum", vars_mh_p_abcl__synd__tho))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__tho_tscore

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Thought problems): T-score"

Description

Computes the summary score mh_p_abcl__synd__tho_tscore Adult Behavior Checklist [Parent] (Syndrome Scale - Thought problems): T-score

- *Summarized variables:*
  - mh_p_abcl__tho_001
  - mh_p_abcl__tho_002
  - mh_p_abcl__tho_003
  - mh_p_abcl__tho_004
  - mh_p_abcl__tho_005
  - mh_p_abcl__tho_006

  - mh_p_abcl__tho_007
  - mh_p_abcl__tho__dep_001
  - mh_p_abcl__tho__dep_002
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_abcl__synd__tho_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__tho_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__tho_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__tho_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__tho_tscore", vars_mh_p_abcl__synd__tho))
  )

## End(Not run)
```

`compute_mh_p_abcl__synd__wthdr_sum`

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Withdrawn): Sum"

Description

Computes the summary score `mh_p_abcl__synd__wthdr_sum` Adult Behavior Checklist [Parent] (Syndrome Scale - Withdrawn): Sum

- *Summarized variables:*
  - `mh_p_abcl__wthdr_001`
  - `mh_p_abcl__wthdr_002`
  - `mh_p_abcl__wthdr_003`
  - `mh_p_abcl__wthdr_004`
  - `mh_p_abcl__wthdr__avoid_001`
  - `mh_p_abcl__wthdr__avoid_002`
  - `mh_p_abcl__wthdr__avoid_003`
  - `mh_p_abcl__wthdr__avoid_004`
  - `mh_p_abcl__wthdr__dep_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_abcl__synd__wthdr_sum(
  data,
  name = "mh_p_abcl__synd__wthdr_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__wthdr_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__wthdr_sum(data) |>
  select(
    any_of(c("mh_p_abcl__synd__wthdr_sum", vars_mh_p_abcl__synd__wthdr))
  )

## End(Not run)
```

---

compute_mh_p_abcl__synd__wthdr_tscore

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Withdrawn): T-score"

Description

Computes the summary score mh_p_abcl__synd__wthdr_tscore Adult Behavior Checklist [Parent] (Syndrome Scale - Withdrawn): T-score

- *Summarized variables:*
  - mh_p_abcl__wthdr_001
  - mh_p_abcl__wthdr_002
  - mh_p_abcl__wthdr_003
  - mh_p_abcl__wthdr_004
  - mh_p_abcl__wthdr__avoid_001
  - mh_p_abcl__wthdr__avoid_002

  - mh_p_abcl__wthdr__avoid_003
  - mh_p_abcl__wthdr__avoid_004
  - mh_p_abcl__wthdr__dep_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_abcl__synd__wthdr_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl__synd__wthdr_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl__synd__wthdr_nm()

Examples

```
## Not run:
compute_mh_p_abcl__synd__wthdr_tscore(data) |>
  select(
    any_of(c("mh_p_abcl__synd__wthdr_tscore", vars_mh_p_abcl__synd__wthdr))
  )

## End(Not run)
```

`compute_mh_p_abcl_all` *Compute all summary scores for mh_p_abcl.*

Description

This function computes all summary scores for the mh_p_abcl form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_abcl_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_p_abcl_all(data)

## End(Not run)
```

compute_mh_p_abcl_sum *Compute "Adult Behavior Checklist [Parent]: Sum"*

Description

Computes the summary score mh_p_abcl_sum Adult Behavior Checklist [Parent]: Sum

- *Summarized variables:*
  - mh_p_abcl__rule_001
  - mh_p_abcl__attn__adhd_002
  - mh_p_abcl__tho_001
  - mh_p_abcl__othpr__adhd_001
  - mh_p_abcl__anxdep__dep_001
  - mh_p_abcl__aggr__antsoc_003
  - mh_p_abcl__tho__dep_001
  - mh_p_abcl__othpr__antsoc_001
  - mh_p_abcl__tho_002
  - mh_p_abcl__aggr_001
  - mh_p_abcl__aggr__antsoc_006
  - mh_p_abcl__tho_003
  - mh_p_abcl__tho_004
  - mh_p_abcl__tho_006
  - mh_p_abcl__rule_002
  - mh_p_abcl__tho__dep_002
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__aggr__antsoc_008
  - mh_p_abcl__anxdep__dep_004
  - mh_p_abcl__aggr__adhd_001
  - mh_p_abcl__attn__adhd_001
  - mh_p_abcl__attn__adhd_003
  - mh_p_abcl__attn__adhd_004
  - mh_p_abcl__attn__adhd_005
  - mh_p_abcl__attn__adhd_006
  - mh_p_abcl__attn__adhd_007
  - mh_p_abcl__othpr__adhd_002
  - mh_p_abcl__othpr__adhd_003
  - mh_p_abcl__othpr__adhd_004
  - mh_p_abcl__rule__adhd_001
  - mh_p_abcl__aggr__antsoc_001
  - mh_p_abcl__aggr__antsoc_002
  - mh_p_abcl__aggr__antsoc_004

- mh_p_abcl__aggr__antsoc_005
- mh_p_abcl__aggr__antsoc_007
- mh_p_abcl__attn__antsoc_001
- mh_p_abcl__othpr__antsoc_002
- mh_p_abcl__rule__antsoc_001
- mh_p_abcl__rule__antsoc_002
- mh_p_abcl__rule__antsoc_003
- mh_p_abcl__rule__antsoc_004
- mh_p_abcl__rule__antsoc_005
- mh_p_abcl__rule__antsoc_006
- mh_p_abcl__rule__antsoc_008
- mh_p_abcl__rule__antsoc_009
- mh_p_abcl__anxdep__anx_001
- mh_p_abcl__anxdep__anx_002
- mh_p_abcl__anxdep__anx_003
- mh_p_abcl__othpr__anx_001
- mh_p_abcl__othpr__anx_002
- mh_p_abcl__othpr__anx_003
- mh_p_abcl__anxdep__avoid_001
- mh_p_abcl__anxdep__avoid_002
- mh_p_abcl__othpr__avoid_001
- mh_p_abcl__wthdr__avoid_001
- mh_p_abcl__wthdr__avoid_002
- mh_p_abcl__wthdr__avoid_003
- mh_p_abcl__wthdr__avoid_004
- mh_p_abcl__anxdep__dep_002
- mh_p_abcl__anxdep__dep_003
- mh_p_abcl__anxdep__dep_005
- mh_p_abcl__attn__dep_001
- mh_p_abcl__attn__dep_002
- mh_p_abcl__attn__dep_003
- mh_p_abcl__othpr__dep_001
- mh_p_abcl__othpr__dep_002
- mh_p_abcl__othpr__dep_003
- mh_p_abcl__som__dep_001
- mh_p_abcl__wthdr__dep_001
- mh_p_abcl__som__somat_001
- mh_p_abcl__som__somat_002
- mh_p_abcl__som__somat_003
- mh_p_abcl__som__somat_004
- mh_p_abcl__som__somat_005
- mh_p_abcl__som__somat_006

- mh_p_abcl__som__somat_007
- mh_p_abcl__aggr_002
- mh_p_abcl__aggr_003
- mh_p_abcl__aggr_004
- mh_p_abcl__aggr_005
- mh_p_abcl__aggr_006
- mh_p_abcl__aggr_007
- mh_p_abcl__anxdep_001
- mh_p_abcl__anxdep_002
- mh_p_abcl__anxdep_003
- mh_p_abcl__anxdep_004
- mh_p_abcl__attn_001
- mh_p_abcl__attn_002
- mh_p_abcl__attn_003
- mh_p_abcl__attn_004
- mh_p_abcl__attn_005
- mh_p_abcl__attn_006
- mh_p_abcl__rule_003
- mh_p_abcl__intru_001
- mh_p_abcl__intru_002
- mh_p_abcl__intru_003
- mh_p_abcl__intru_004
- mh_p_abcl__intru_005
- mh_p_abcl__intru_006
- mh_p_abcl__wthdr_001
- mh_p_abcl__wthdr_002
- mh_p_abcl__wthdr_003
- mh_p_abcl__wthdr_004
- mh_p_abcl__som_001
- mh_p_abcl__othpr_001
- mh_p_abcl__othpr_002
- mh_p_abcl__othpr_003
- mh_p_abcl__othpr_004
- mh_p_abcl__othpr_005
- mh_p_abcl__othpr_006
- mh_p_abcl__othpr_007
- mh_p_abcl__othpr_008
- mh_p_abcl__othpr_009
- mh_p_abcl__othpr_010
- mh_p_abcl__othpr_011
- mh_p_abcl__othpr_012
- mh_p_abcl__tho_005

    - mh_p_abcl__tho_007
  - *Excluded values:*
    - 777
    - 999
  - *Validation criterion:* maximally 8 of 118 items missing

Usage

```
compute_mh_p_abcl_sum(
  data,
  name = "mh_p_abcl_sum",
  max_na = 8,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl_nm()

Examples

```
## Not run:
compute_mh_p_abcl_sum(data) |>
  select(
    any_of(c("mh_p_abcl_sum", vars_mh_p_abcl))
  )

## End(Not run)
```

`compute_mh_p_abcl_tscore` *Compute "Adult Behavior Checklist [Parent]: T-score"*

Description

Computes the summary score `mh_p_abcl_tscore` Adult Behavior Checklist [Parent]: T-score

- *Summarized variables:*
  - `mh_p_abcl__rule_001`
  - `mh_p_abcl__attn__adhd_002`
  - `mh_p_abcl__tho_001`
  - `mh_p_abcl__othpr__adhd_001`
  - `mh_p_abcl__anxdep__dep_001`
  - `mh_p_abcl__aggr__antsoc_003`
  - `mh_p_abcl__tho__dep_001`
  - `mh_p_abcl__othpr__antsoc_001`
  - `mh_p_abcl__tho_002`
  - `mh_p_abcl__aggr_001`
  - `mh_p_abcl__aggr__antsoc_006`
  - `mh_p_abcl__tho_003`
  - `mh_p_abcl__tho_004`
  - `mh_p_abcl__tho_006`
  - `mh_p_abcl__rule_002`
  - `mh_p_abcl__tho__dep_002`
  - `mh_p_abcl__rule__antsoc_007`
  - `mh_p_abcl__aggr__antsoc_008`
  - `mh_p_abcl__anxdep__dep_004`
  - `mh_p_abcl__aggr__adhd_001`
  - `mh_p_abcl__attn__adhd_001`
  - `mh_p_abcl__attn__adhd_003`
  - `mh_p_abcl__attn__adhd_004`
  - `mh_p_abcl__attn__adhd_005`
  - `mh_p_abcl__attn__adhd_006`
  - `mh_p_abcl__attn__adhd_007`
  - `mh_p_abcl__othpr__adhd_002`
  - `mh_p_abcl__othpr__adhd_003`
  - `mh_p_abcl__othpr__adhd_004`
  - `mh_p_abcl__rule__adhd_001`
  - `mh_p_abcl__aggr__antsoc_001`
  - `mh_p_abcl__aggr__antsoc_002`

- mh_p_abcl__aggr__antsoc_004
- mh_p_abcl__aggr__antsoc_005
- mh_p_abcl__aggr__antsoc_007
- mh_p_abcl__attn__antsoc_001
- mh_p_abcl__othpr__antsoc_002
- mh_p_abcl__rule__antsoc_001
- mh_p_abcl__rule__antsoc_002
- mh_p_abcl__rule__antsoc_003
- mh_p_abcl__rule__antsoc_004
- mh_p_abcl__rule__antsoc_005
- mh_p_abcl__rule__antsoc_006
- mh_p_abcl__rule__antsoc_008
- mh_p_abcl__rule__antsoc_009
- mh_p_abcl__anxdep__anx_001
- mh_p_abcl__anxdep__anx_002
- mh_p_abcl__anxdep__anx_003
- mh_p_abcl__othpr__anx_001
- mh_p_abcl__othpr__anx_002
- mh_p_abcl__othpr__anx_003
- mh_p_abcl__anxdep__avoid_001
- mh_p_abcl__anxdep__avoid_002
- mh_p_abcl__othpr__avoid_001
- mh_p_abcl__wthdr__avoid_001
- mh_p_abcl__wthdr__avoid_002
- mh_p_abcl__wthdr__avoid_003
- mh_p_abcl__wthdr__avoid_004
- mh_p_abcl__anxdep__dep_002
- mh_p_abcl__anxdep__dep_003
- mh_p_abcl__anxdep__dep_005
- mh_p_abcl__attn__dep_001
- mh_p_abcl__attn__dep_002
- mh_p_abcl__attn__dep_003
- mh_p_abcl__othpr__dep_001
- mh_p_abcl__othpr__dep_002
- mh_p_abcl__othpr__dep_003
- mh_p_abcl__som__dep_001
- mh_p_abcl__wthdr__dep_001
- mh_p_abcl__som__somat_001
- mh_p_abcl__som__somat_002
- mh_p_abcl__som__somat_003
- mh_p_abcl__som__somat_004
- mh_p_abcl__som__somat_005

- mh_p_abcl__som__somat_006
- mh_p_abcl__som__somat_007
- mh_p_abcl__aggr_002
- mh_p_abcl__aggr_003
- mh_p_abcl__aggr_004
- mh_p_abcl__aggr_005
- mh_p_abcl__aggr_006
- mh_p_abcl__aggr_007
- mh_p_abcl__anxdep_001
- mh_p_abcl__anxdep_002
- mh_p_abcl__anxdep_003
- mh_p_abcl__anxdep_004
- mh_p_abcl__attn_001
- mh_p_abcl__attn_002
- mh_p_abcl__attn_003
- mh_p_abcl__attn_004
- mh_p_abcl__attn_005
- mh_p_abcl__attn_006
- mh_p_abcl__rule_003
- mh_p_abcl__intru_001
- mh_p_abcl__intru_002
- mh_p_abcl__intru_003
- mh_p_abcl__intru_004
- mh_p_abcl__intru_005
- mh_p_abcl__intru_006
- mh_p_abcl__wthdr_001
- mh_p_abcl__wthdr_002
- mh_p_abcl__wthdr_003
- mh_p_abcl__wthdr_004
- mh_p_abcl__som_001
- mh_p_abcl__othpr_001
- mh_p_abcl__othpr_002
- mh_p_abcl__othpr_003
- mh_p_abcl__othpr_004
- mh_p_abcl__othpr_005
- mh_p_abcl__othpr_006
- mh_p_abcl__othpr_007
- mh_p_abcl__othpr_008
- mh_p_abcl__othpr_009
- mh_p_abcl__othpr_010
- mh_p_abcl__othpr_011
- mh_p_abcl__othpr_012

  - mh_p_abcl__tho_005
  - mh_p_abcl__tho_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 8 of 118 items missing

Usage

```
compute_mh_p_abcl_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_abcl_tscore",
  col_age = "mh_p_abcl__cg2__age_001",
  col_sex = "mh_p_abcl__cg2_sex",
  max_na = 8,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_abcl_nm()

Examples

```
## Not run:
compute_mh_p_abcl_tscore(data) |>
  select(
    any_of(c("mh_p_abcl_tscore", vars_mh_p_abcl))
  )

## End(Not run)
```

`compute_mh_p_asr__afs__strng_sum`
Compute "Adult Self Report [Parent] (Adaptive Functioning Scale - Personal strength): Sum"

Description

Computes the summary score `mh_p_asr__afs__strng_sum` Adult Self Report [Parent] (Adaptive Functioning Scale - Personal strength): Sum

- *Summarized variables:*
  - `mh_p_asr__strng_001`
  - `mh_p_asr__strng_002`
  - `mh_p_asr__strng_003`
  - `mh_p_asr__strng_004`
  - `mh_p_asr__strng_005`
  - `mh_p_asr__strng_006`
  - `mh_p_asr__strng_007`
  - `mh_p_asr__strng_008`
  - `mh_p_asr__strng_009`
  - `mh_p_asr__strng_010`
  - `mh_p_asr__strng_011`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 11 items missing

Usage

```
compute_mh_p_asr__afs__strng_sum(
  data,
  name = "mh_p_asr__afs__strng_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__afs__strng_nm()

Examples

```
## Not run:
compute_mh_p_asr__afs__strng_sum(data) |>
  select(
    any_of(c("mh_p_asr__afs__strng_sum", vars_mh_p_asr__afs__strng))
  )

## End(Not run)
```

---

compute_mh_p_asr__critic_sum

Compute "Adult Self Report [Parent] (Critical Items): Sum"

Description

Computes the summary score mh_p_asr__critic_sum Adult Self Report [Parent] (Critical Items): Sum

- *Summarized variables:*
  - mh_p_asr__aggr_001
  - mh_p_asr__aggr__antsoc_003
  - mh_p_asr__aggr__antsoc_006
  - mh_p_asr__aggr__antsoc_008
  - mh_p_asr__anxdep__dep_001
  - mh_p_asr__anxdep__dep_004
  - mh_p_asr__anxdep__dep_005

  - mh_p_asr__attn__inatt_002
  - mh_p_asr__othpr__hypimp_001
  - mh_p_asr__othpr__antsoc_001
  - mh_p_asr__rule_001
  - mh_p_asr__rule_003
  - mh_p_asr__rule__antsoc_007
  - mh_p_asr__tho_001
  - mh_p_asr__tho_002
  - mh_p_asr__tho_005
  - mh_p_asr__tho_006
  - mh_p_asr__tho_007
  - mh_p_asr__tho__dep_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 19 items missing

Usage

```
compute_mh_p_asr__critic_sum(
  data,
  name = "mh_p_asr__critic_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__critic_nm()

Examples

```
## Not run:
compute_mh_p_asr__critic_sum(data) |>
  select(
    any_of(c("mh_p_asr__critic_sum", vars_mh_p_asr__critic))
  )

## End(Not run)
```

`compute_mh_p_asr__dsm__adhd__hypimp_sum`
Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD Hyperactivity-Impulsivity): Sum"

Description

Computes the summary score `mh_p_asr__dsm__adhd__hypimp_sum` Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD Hyperactivity-Impulsivity): Sum

- *Summarized variables:*
  - `mh_p_asr__aggr__hypimp_001`
  - `mh_p_asr__othpr__hypimp_001`
  - `mh_p_asr__othpr__hypimp_002`
  - `mh_p_asr__othpr__hypimp_003`
  - `mh_p_asr__rule__hypimp_001`
  - `mh_p_asr__tho__hypimp_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_p_asr__dsm__adhd__hypimp_sum(
  data,
  name = "mh_p_asr__dsm__adhd__hypimp_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__dsm__adhd__hypimp_nm()

Examples

```
## Not run:
compute_mh_p_asr__dsm__adhd__hypimp_sum(data) |>
  select(
    any_of(c("mh_p_asr__dsm__adhd__hypimp_sum", vars_mh_p_asr__dsm__adhd__hypimp))
  )

## End(Not run)
```

---

compute_mh_p_asr__dsm__adhd__inatt_sum

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD Inattention): Sum"

Description

Computes the summary score mh_p_asr__dsm__adhd__inatt_sum Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD Inattention): Sum

- *Summarized variables:*
  - mh_p_asr__attn__inatt_001
  - mh_p_asr__attn__inatt_002
  - mh_p_asr__attn__inatt_003
  - mh_p_asr__attn__inatt_004
  - mh_p_asr__attn__inatt_005
  - mh_p_asr__attn__inatt_006

  - mh_p_asr__attn__inatt_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_asr__dsm__adhd__inatt_sum(
  data,
  name = "mh_p_asr__dsm__adhd__inatt_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__dsm__adhd__inatt_nm()

Examples

```
## Not run:
compute_mh_p_asr__dsm__adhd__inatt_sum(data) |>
  select(
    any_of(c("mh_p_asr__dsm__adhd__inatt_sum", vars_mh_p_asr__dsm__adhd__inatt))
  )

## End(Not run)
```

compute_mh_p_asr__dsm__adhd_sum *Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD): Sum"*

Description

Computes the summary score mh_p_asr__dsm__adhd_sum Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD): Sum

- *Summarized variables:*
  - mh_p_asr__attn__inatt_001
  - mh_p_asr__attn__inatt_002
  - mh_p_asr__attn__inatt_003
  - mh_p_asr__attn__inatt_004
  - mh_p_asr__attn__inatt_005
  - mh_p_asr__attn__inatt_006
  - mh_p_asr__attn__inatt_007
  - mh_p_asr__aggr__hypimp_001
  - mh_p_asr__othpr__hypimp_001
  - mh_p_asr__othpr__hypimp_002
  - mh_p_asr__othpr__hypimp_003
  - mh_p_asr__rule__hypimp_001
  - mh_p_asr__tho__hypimp_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 13 items missing

Usage

```
compute_mh_p_asr__dsm__adhd_sum(
  data,
  name = "mh_p_asr__dsm__adhd_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__dsm__adhd_nm()

Examples

```
## Not run:
compute_mh_p_asr__dsm__adhd_sum(data) |>
  select(
    any_of(c("mh_p_asr__dsm__adhd_sum", vars_mh_p_asr__dsm__adhd))
  )

## End(Not run)
```

---

compute_mh_p_asr__dsm__antsoc_sum

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): Sum"

Description

Computes the summary score mh_p_asr__dsm__antsoc_sum Adult Self Report [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): Sum

- *Summarized variables:*
  - mh_p_asr__aggr__antsoc_001
  - mh_p_asr__aggr__antsoc_002
  - mh_p_asr__aggr__antsoc_003
  - mh_p_asr__aggr__antsoc_004
  - mh_p_asr__aggr__antsoc_005
  - mh_p_asr__aggr__antsoc_006
  - mh_p_asr__aggr__antsoc_007
  - mh_p_asr__aggr__antsoc_008
  - mh_p_asr__attn__antsoc_001
  - mh_p_asr__othpr__antsoc_001

  - mh_p_asr__othpr__antsoc_002
  - mh_p_asr__rule__antsoc_001
  - mh_p_asr__rule__antsoc_002
  - mh_p_asr__rule__antsoc_003
  - mh_p_asr__rule__antsoc_004
  - mh_p_asr__rule__antsoc_005
  - mh_p_asr__rule__antsoc_006
  - mh_p_asr__rule__antsoc_007
  - mh_p_asr__rule__antsoc_008
  - mh_p_asr__rule__antsoc_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 20 items missing

Usage

```
compute_mh_p_asr__dsm__antsoc_sum(
  data,
  name = "mh_p_asr__dsm__antsoc_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__dsm__antsoc_nm()

Examples

```
## Not run:
compute_mh_p_asr__dsm__antsoc_sum(data) |>
  select(
    any_of(c("mh_p_asr__dsm__antsoc_sum", vars_mh_p_asr__dsm__antsoc))
  )

## End(Not run)
```

`compute_mh_p_asr__dsm__anx_sum`

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Anxiety problems): Sum"

Description

Computes the summary score `mh_p_asr__dsm__anx_sum` Adult Self Report [Parent] (DSM-5 Oriented Scale - Anxiety problems): Sum

- *Summarized variables:*
  - `mh_p_asr__anxdep__anx_001`
  - `mh_p_asr__anxdep__anx_002`
  - `mh_p_asr__anxdep__anx_003`
  - `mh_p_asr__anxdep__anx_004`
  - `mh_p_asr__othpr__anx_001`
  - `mh_p_asr__othpr__anx_002`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_p_asr__dsm__anx_sum(
  data,
  name = "mh_p_asr__dsm__anx_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__dsm__anx_nm()

Examples

```
## Not run:
compute_mh_p_asr__dsm__anx_sum(data) |>
  select(
    any_of(c("mh_p_asr__dsm__anx_sum", vars_mh_p_asr__dsm__anx))
  )

## End(Not run)
```

---

compute_mh_p_asr__dsm__avoid_sum

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): Sum"

Description

Computes the summary score mh_p_asr__dsm__avoid_sum Adult Self Report [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): Sum

- *Summarized variables:*
  - mh_p_asr__anxdep__avoid_001
  - mh_p_asr__anxdep__avoid_002
  - mh_p_asr__othpr__avoid_001
  - mh_p_asr__wthdr__avoid_001
  - mh_p_asr__wthdr__avoid_002
  - mh_p_asr__wthdr__avoid_003

    - mh_p_asr__wthdr__avoid_004
  - *Excluded values:*
    - 777
    - 999
  - *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_asr__dsm__avoid_sum(
  data,
  name = "mh_p_asr__dsm__avoid_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__dsm__avoid_nm()

Examples

```
## Not run:
compute_mh_p_asr__dsm__avoid_sum(data) |>
  select(
    any_of(c("mh_p_asr__dsm__avoid_sum", vars_mh_p_asr__dsm__avoid))
  )

## End(Not run)
```

`compute_mh_p_asr__dsm__dep_sum`
Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Depresssive problems): Sum"

Description

Computes the summary score `mh_p_asr__dsm__dep_sum` Adult Self Report [Parent] (DSM-5 Oriented Scale - Depresssive problems): Sum

- *Summarized variables:*
  - `mh_p_asr__anxdep__dep_001`
  - `mh_p_asr__anxdep__dep_002`
  - `mh_p_asr__anxdep__dep_003`
  - `mh_p_asr__anxdep__dep_004`
  - `mh_p_asr__anxdep__dep_005`
  - `mh_p_asr__anxdep__dep_006`
  - `mh_p_asr__attn__dep_001`
  - `mh_p_asr__attn__dep_002`
  - `mh_p_asr__othpr__dep_001`
  - `mh_p_asr__othpr__dep_002`
  - `mh_p_asr__som__dep_001`
  - `mh_p_asr__som__dep_002`
  - `mh_p_asr__tho__dep_001`
  - `mh_p_asr__wthdr__dep_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 14 items missing

Usage

```
compute_mh_p_asr__dsm__dep_sum(
  data,
  name = "mh_p_asr__dsm__dep_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__dsm__dep_nm()

Examples

```
## Not run:
compute_mh_p_asr__dsm__dep_sum(data) |>
  select(
    any_of(c("mh_p_asr__dsm__dep_sum", vars_mh_p_asr__dsm__dep))
  )

## End(Not run)
```

---

compute_mh_p_asr__dsm__somat_sum

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Somatic complaints): Sum"

Description

Computes the summary score mh_p_asr__dsm__somat_sum Adult Self Report [Parent] (DSM-5 Oriented Scale - Somatic complaints): Sum

- *Summarized variables:*
  - mh_p_asr__som__somat_001
  - mh_p_asr__som__somat_002
  - mh_p_asr__som__somat_003
  - mh_p_asr__som__somat_004
  - mh_p_asr__som__somat_005
  - mh_p_asr__som__somat_006

  - mh_p_asr__som__somat_007
  - mh_p_asr__som__somat_008
  - mh_p_asr__som__somat_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_asr__dsm__somat_sum(
  data,
  name = "mh_p_asr__dsm__somat_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__dsm__somat_nm()

Examples

```
## Not run:
compute_mh_p_asr__dsm__somat_sum(data) |>
  select(
    any_of(c("mh_p_asr__dsm__somat_sum", vars_mh_p_asr__dsm__somat))
  )

## End(Not run)
```

compute_mh_p_asr__synd__aggr_sum
Compute "Adult Self Report [Parent] (Syndrome Scale - Aggressive Behavior): Sum"

Description

Computes the summary score mh_p_asr__synd__aggr_sum Adult Self Report [Parent] (Syndrome Scale - Aggressive Behavior): Sum

- *Summarized variables:*
  - mh_p_asr__aggr_001
  - mh_p_asr__aggr_002
  - mh_p_asr__aggr_003
  - mh_p_asr__aggr_004
  - mh_p_asr__aggr_005
  - mh_p_asr__aggr_006
  - mh_p_asr__aggr__hypimp_001
  - mh_p_asr__aggr__antsoc_001
  - mh_p_asr__aggr__antsoc_002
  - mh_p_asr__aggr__antsoc_003
  - mh_p_asr__aggr__antsoc_004
  - mh_p_asr__aggr__antsoc_005
  - mh_p_asr__aggr__antsoc_006
  - mh_p_asr__aggr__antsoc_007
  - mh_p_asr__aggr__antsoc_008
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 15 items missing

Usage

```
compute_mh_p_asr__synd__aggr_sum(
  data,
  name = "mh_p_asr__synd__aggr_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__aggr_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__aggr_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__aggr_sum", vars_mh_p_asr__synd__aggr))
  )

## End(Not run)
```

---

compute_mh_p_asr__synd__anxdep_sum

Compute "Adult Self Report [Parent] (Syndrome Scale - Anxious/Depressed): Sum"

Description

Computes the summary score mh_p_asr__synd__anxdep_sum Adult Self Report [Parent] (Syndrome Scale - Anxious/Depressed): Sum

- *Summarized variables:*
  - mh_p_asr__anxdep_001
  - mh_p_asr__anxdep_002
  - mh_p_asr__anxdep_003
  - mh_p_asr__anxdep_004
  - mh_p_asr__anxdep_005
  - mh_p_asr__anxdep_006

  - mh_p_asr__anxdep__anx_001
  - mh_p_asr__anxdep__anx_002
  - mh_p_asr__anxdep__anx_003
  - mh_p_asr__anxdep__anx_004
  - mh_p_asr__anxdep__avoid_001
  - mh_p_asr__anxdep__avoid_002
  - mh_p_asr__anxdep__dep_001
  - mh_p_asr__anxdep__dep_002
  - mh_p_asr__anxdep__dep_003
  - mh_p_asr__anxdep__dep_004
  - mh_p_asr__anxdep__dep_005
  - mh_p_asr__anxdep__dep_006
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 18 items missing

Usage

```
compute_mh_p_asr__synd__anxdep_sum(
  data,
  name = "mh_p_asr__synd__anxdep_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__anxdep_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__anxdep_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__anxdep_sum", vars_mh_p_asr__synd__anxdep))
  )

## End(Not run)
```

`compute_mh_p_asr__synd__attn_sum`

Compute "Adult Self Report [Parent] (Syndrome Scale - Attention problems): Sum"

Description

Computes the summary score `mh_p_asr__synd__attn_sum` Adult Self Report [Parent] (Syndrome Scale - Attention problems): Sum

- *Summarized variables:*
  - `mh_p_asr__attn_001`
  - `mh_p_asr__attn_002`
  - `mh_p_asr__attn_003`
  - `mh_p_asr__attn_004`
  - `mh_p_asr__attn_005`
  - `mh_p_asr__attn__inatt_001`
  - `mh_p_asr__attn__inatt_002`
  - `mh_p_asr__attn__inatt_003`
  - `mh_p_asr__attn__inatt_004`
  - `mh_p_asr__attn__inatt_005`
  - `mh_p_asr__attn__inatt_006`
  - `mh_p_asr__attn__inatt_007`
  - `mh_p_asr__attn__antsoc_001`
  - `mh_p_asr__attn__dep_001`
  - `mh_p_asr__attn__dep_002`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 15 items missing

Usage

```
compute_mh_p_asr__synd__attn_sum(
  data,
  name = "mh_p_asr__synd__attn_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__attn_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__attn_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__attn_sum", vars_mh_p_asr__synd__attn))
  )

## End(Not run)
```

---

compute_mh_p_asr__synd__ext_sum

Compute "Adult Self Report [Parent] (Syndrome Scale - Externalizing): Sum"

Description

Computes the summary score `mh_p_asr__synd__ext_sum` Adult Self Report [Parent] (Syndrome Scale - Externalizing): Sum

- *Summarized variables:*
  - `mh_p_asr__intru_001`
  - `mh_p_asr__intru_002`
  - `mh_p_asr__intru_003`
  - `mh_p_asr__intru_004`
  - `mh_p_asr__intru_005`
  - `mh_p_asr__intru_006`
  - `mh_p_asr__rule_001`
  - `mh_p_asr__rule_002`
  - `mh_p_asr__rule_003`
  - `mh_p_asr__rule_004`
  - `mh_p_asr__rule__hypimp_001`
  - `mh_p_asr__rule__antsoc_001`
  - `mh_p_asr__rule__antsoc_002`
  - `mh_p_asr__rule__antsoc_003`
  - `mh_p_asr__rule__antsoc_004`
  - `mh_p_asr__rule__antsoc_005`
  - `mh_p_asr__rule__antsoc_006`
  - `mh_p_asr__rule__antsoc_007`
  - `mh_p_asr__rule__antsoc_008`
  - `mh_p_asr__rule__antsoc_009`
  - `mh_p_asr__aggr_001`
  - `mh_p_asr__aggr_002`
  - `mh_p_asr__aggr_003`
  - `mh_p_asr__aggr_004`
  - `mh_p_asr__aggr_005`
  - `mh_p_asr__aggr_006`
  - `mh_p_asr__aggr__hypimp_001`
  - `mh_p_asr__aggr__antsoc_001`
  - `mh_p_asr__aggr__antsoc_002`
  - `mh_p_asr__aggr__antsoc_003`
  - `mh_p_asr__aggr__antsoc_004`
  - `mh_p_asr__aggr__antsoc_005`
  - `mh_p_asr__aggr__antsoc_006`
  - `mh_p_asr__aggr__antsoc_007`
  - `mh_p_asr__aggr__antsoc_008`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 35 items missing

Usage

```
compute_mh_p_asr__synd__ext_sum(
  data,
  name = "mh_p_asr__synd__ext_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__ext_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__ext_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__ext_sum", vars_mh_p_asr__synd__ext))
  )

## End(Not run)
```

---

compute_mh_p_asr__synd__int_sum

Compute "Adult Self Report [Parent] (Syndrome Scale - Internalizing): Sum"

Description

Computes the summary score `mh_p_asr__synd__int_sum` Adult Self Report [Parent] (Syndrome Scale - Internalizing): Sum

- *Summarized variables:*
  - `mh_p_asr__anxdep_001`
  - `mh_p_asr__anxdep_002`
  - `mh_p_asr__anxdep_003`
  - `mh_p_asr__anxdep_004`
  - `mh_p_asr__anxdep_005`
  - `mh_p_asr__anxdep_006`
  - `mh_p_asr__anxdep__anx_001`
  - `mh_p_asr__anxdep__anx_002`
  - `mh_p_asr__anxdep__anx_003`
  - `mh_p_asr__anxdep__anx_004`
  - `mh_p_asr__anxdep__avoid_001`
  - `mh_p_asr__anxdep__avoid_002`
  - `mh_p_asr__anxdep__dep_001`
  - `mh_p_asr__anxdep__dep_002`
  - `mh_p_asr__anxdep__dep_003`
  - `mh_p_asr__anxdep__dep_004`
  - `mh_p_asr__anxdep__dep_005`
  - `mh_p_asr__anxdep__dep_006`
  - `mh_p_asr__som_001`
  - `mh_p_asr__som__dep_001`
  - `mh_p_asr__som__dep_002`
  - `mh_p_asr__som__somat_001`
  - `mh_p_asr__som__somat_002`
  - `mh_p_asr__som__somat_003`
  - `mh_p_asr__som__somat_004`
  - `mh_p_asr__som__somat_005`
  - `mh_p_asr__som__somat_006`
  - `mh_p_asr__som__somat_007`
  - `mh_p_asr__som__somat_008`
  - `mh_p_asr__som__somat_009`
  - `mh_p_asr__wthdr_001`
  - `mh_p_asr__wthdr_002`
  - `mh_p_asr__wthdr_003`
  - `mh_p_asr__wthdr_004`
  - `mh_p_asr__wthdr__avoid_001`
  - `mh_p_asr__wthdr__avoid_002`
  - `mh_p_asr__wthdr__avoid_003`

  - mh_p_asr__wthdr__avoid_004
  - mh_p_asr__wthdr__dep_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 39 items missing

Usage

```
compute_mh_p_asr__synd__int_sum(
  data,
  name = "mh_p_asr__synd__int_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__int_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__int_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__int_sum", vars_mh_p_asr__synd__int))
  )

## End(Not run)
```

`compute_mh_p_asr__synd__intru_sum` *Compute "Adult Self Report [Parent] (Syndrome Scale - Intrusive): Sum"*

Description

Computes the summary score `mh_p_asr__synd__intru_sum` Adult Self Report [Parent] (Syndrome Scale - Intrusive): Sum

- *Summarized variables:*
  - `mh_p_asr__intru_001`
  - `mh_p_asr__intru_002`
  - `mh_p_asr__intru_003`
  - `mh_p_asr__intru_004`
  - `mh_p_asr__intru_005`
  - `mh_p_asr__intru_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_p_asr__synd__intru_sum(
  data,
  name = "mh_p_asr__synd__intru_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__intru_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__intru_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__intru_sum", vars_mh_p_asr__synd__intru))
  )

## End(Not run)
```

---

compute_mh_p_asr__synd__othpr_sum

Compute "Adult Self Report [Parent] (Syndrome Scale - Other problems): Sum"

Description

Computes the summary score mh_p_asr__synd__othpr_sum Adult Self Report [Parent] (Syndrome Scale - Other problems): Sum

- *Summarized variables:*
  - mh_p_asr__othpr_001
  - mh_p_asr__othpr_002
  - mh_p_asr__othpr_003
  - mh_p_asr__othpr_004
  - mh_p_asr__othpr_005
  - mh_p_asr__othpr_006
  - mh_p_asr__othpr_007
  - mh_p_asr__othpr_008
  - mh_p_asr__othpr_009
  - mh_p_asr__othpr_010
  - mh_p_asr__othpr_011
  - mh_p_asr__othpr__hypimp_001
  - mh_p_asr__othpr__hypimp_002
  - mh_p_asr__othpr__hypimp_003
  - mh_p_asr__othpr__antsoc_001
  - mh_p_asr__othpr__antsoc_002
  - mh_p_asr__othpr__anx_001

  - mh_p_asr__othpr__anx_002
  - mh_p_asr__othpr__avoid_001
  - mh_p_asr__othpr__dep_001
  - mh_p_asr__othpr__dep_002
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 21 items missing

Usage

```
compute_mh_p_asr__synd__othpr_sum(
  data,
  name = "mh_p_asr__synd__othpr_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__othpr_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__othpr_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__othpr_sum", vars_mh_p_asr__synd__othpr))
  )

## End(Not run)
```

compute_mh_p_asr__synd__rule_sum
Compute "Adult Self Report [Parent] (Syndrome Scale - Rule breaking behavior): Sum"

Description

Computes the summary score mh_p_asr__synd__rule_sum Adult Self Report [Parent] (Syndrome Scale - Rule breaking behavior): Sum

- *Summarized variables:*
  - mh_p_asr__rule_001
  - mh_p_asr__rule_002
  - mh_p_asr__rule_003
  - mh_p_asr__rule_004
  - mh_p_asr__rule__hypimp_001
  - mh_p_asr__rule__antsoc_001
  - mh_p_asr__rule__antsoc_002
  - mh_p_asr__rule__antsoc_003
  - mh_p_asr__rule__antsoc_004
  - mh_p_asr__rule__antsoc_005
  - mh_p_asr__rule__antsoc_006
  - mh_p_asr__rule__antsoc_007
  - mh_p_asr__rule__antsoc_008
  - mh_p_asr__rule__antsoc_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 14 items missing

Usage

```
compute_mh_p_asr__synd__rule_sum(
  data,
  name = "mh_p_asr__synd__rule_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__rule_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__rule_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__rule_sum", vars_mh_p_asr__synd__rule))
  )

## End(Not run)
```

---

compute_mh_p_asr__synd__som_sum

Compute "Adult Self Report [Parent] (Syndrome Scale - Somatic complaints): Sum"

Description

Computes the summary score mh_p_asr__synd__som_sum Adult Self Report [Parent] (Syndrome Scale - Somatic complaints): Sum

- *Summarized variables:*
  - mh_p_asr__som_001
  - mh_p_asr__som__dep_001
  - mh_p_asr__som__dep_002
  - mh_p_asr__som__somat_001
  - mh_p_asr__som__somat_002
  - mh_p_asr__som__somat_003

  - mh_p_asr__som__somat_004
  - mh_p_asr__som__somat_005
  - mh_p_asr__som__somat_006
  - mh_p_asr__som__somat_007
  - mh_p_asr__som__somat_008
  - mh_p_asr__som__somat_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 12 items missing

Usage

```
compute_mh_p_asr__synd__som_sum(
  data,
  name = "mh_p_asr__synd__som_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__som_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__som_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__som_sum", vars_mh_p_asr__synd__som))
  )
```

```
## End(Not run)
```

`compute_mh_p_asr__synd__tho_sum`
Compute "Adult Self Report [Parent] (Syndrome Scale - Thought problems): Sum"

Description

Computes the summary score `mh_p_asr__synd__tho_sum` Adult Self Report [Parent] (Syndrome Scale - Thought problems): Sum

- *Summarized variables:*
  - `mh_p_asr__tho_001`
  - `mh_p_asr__tho_002`
  - `mh_p_asr__tho_003`
  - `mh_p_asr__tho_004`
  - `mh_p_asr__tho_005`
  - `mh_p_asr__tho_006`
  - `mh_p_asr__tho_007`
  - `mh_p_asr__tho_008`
  - `mh_p_asr__tho__hypimp_001`
  - `mh_p_asr__tho__dep_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 10 items missing

Usage

```
compute_mh_p_asr__synd__tho_sum(
  data,
  name = "mh_p_asr__synd__tho_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__tho_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__tho_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__tho_sum", vars_mh_p_asr__synd__tho))
  )

## End(Not run)
```

---

compute_mh_p_asr__synd__wthdr_sum

Compute "Adult Self Report [Parent] (Syndrome Scale - Withdrawn): Sum"

Description

Computes the summary score mh_p_asr__synd__wthdr_sum Adult Self Report [Parent] (Syndrome Scale - Withdrawn): Sum

- *Summarized variables:*
  - mh_p_asr__wthdr_001
  - mh_p_asr__wthdr_002
  - mh_p_asr__wthdr_003
  - mh_p_asr__wthdr_004
  - mh_p_asr__wthdr__avoid_001
  - mh_p_asr__wthdr__avoid_002
  - mh_p_asr__wthdr__avoid_003
  - mh_p_asr__wthdr__avoid_004
  - mh_p_asr__wthdr__dep_001
- *Excluded values:*

  - 777
  - 999
- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_asr__synd__wthdr_sum(
  data,
  name = "mh_p_asr__synd__wthdr_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr__synd__wthdr_nm()

Examples

```
## Not run:
compute_mh_p_asr__synd__wthdr_sum(data) |>
  select(
    any_of(c("mh_p_asr__synd__wthdr_sum", vars_mh_p_asr__synd__wthdr))
  )

## End(Not run)
```

compute_mh_p_asr_all *Compute all summary scores for mh_p_asr.*

Description

This function computes all summary scores for the mh_p_asr form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_asr_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_p_asr_all(data)

## End(Not run)
```

compute_mh_p_asr_sum *Compute "Adult Self Report [Parent]: Sum"*

Description

Computes the summary score mh_p_asr_sum Adult Self Report [Parent]: Sum

- *Summarized variables:*
  - mh_p_asr__aggr_001
  - mh_p_asr__aggr__antsoc_003
  - mh_p_asr__aggr__antsoc_006
  - mh_p_asr__aggr__antsoc_008
  - mh_p_asr__anxdep__dep_001
  - mh_p_asr__anxdep__dep_004
  - mh_p_asr__anxdep__dep_005
  - mh_p_asr__attn__inatt_002
  - mh_p_asr__othpr__hypimp_001
  - mh_p_asr__othpr__antsoc_001

- mh_p_asr__rule_001
- mh_p_asr__rule_003
- mh_p_asr__rule__antsoc_007
- mh_p_asr__tho_001
- mh_p_asr__tho_002
- mh_p_asr__tho_005
- mh_p_asr__tho_006
- mh_p_asr__tho_007
- mh_p_asr__tho__dep_001
- mh_p_asr__aggr__hypimp_001
- mh_p_asr__othpr__hypimp_002
- mh_p_asr__othpr__hypimp_003
- mh_p_asr__rule__hypimp_001
- mh_p_asr__tho__hypimp_001
- mh_p_asr__attn__inatt_001
- mh_p_asr__attn__inatt_003
- mh_p_asr__attn__inatt_004
- mh_p_asr__attn__inatt_005
- mh_p_asr__attn__inatt_006
- mh_p_asr__attn__inatt_007
- mh_p_asr__aggr__antsoc_001
- mh_p_asr__aggr__antsoc_002
- mh_p_asr__aggr__antsoc_004
- mh_p_asr__aggr__antsoc_005
- mh_p_asr__aggr__antsoc_007
- mh_p_asr__attn__antsoc_001
- mh_p_asr__othpr__antsoc_002
- mh_p_asr__rule__antsoc_001
- mh_p_asr__rule__antsoc_002
- mh_p_asr__rule__antsoc_003
- mh_p_asr__rule__antsoc_004
- mh_p_asr__rule__antsoc_005
- mh_p_asr__rule__antsoc_006
- mh_p_asr__rule__antsoc_008
- mh_p_asr__rule__antsoc_009
- mh_p_asr__anxdep__anx_001
- mh_p_asr__anxdep__anx_002
- mh_p_asr__anxdep__anx_003
- mh_p_asr__anxdep__anx_004
- mh_p_asr__othpr__anx_001
- mh_p_asr__othpr__anx_002
- mh_p_asr__anxdep__avoid_001

- mh_p_asr__anxdep__avoid_002
- mh_p_asr__othpr__avoid_001
- mh_p_asr__wthdr__avoid_001
- mh_p_asr__wthdr__avoid_002
- mh_p_asr__wthdr__avoid_003
- mh_p_asr__wthdr__avoid_004
- mh_p_asr__anxdep__dep_002
- mh_p_asr__anxdep__dep_003
- mh_p_asr__anxdep__dep_006
- mh_p_asr__attn__dep_001
- mh_p_asr__attn__dep_002
- mh_p_asr__othpr__dep_001
- mh_p_asr__othpr__dep_002
- mh_p_asr__som__dep_001
- mh_p_asr__som__dep_002
- mh_p_asr__wthdr__dep_001
- mh_p_asr__som__somat_001
- mh_p_asr__som__somat_002
- mh_p_asr__som__somat_003
- mh_p_asr__som__somat_004
- mh_p_asr__som__somat_005
- mh_p_asr__som__somat_006
- mh_p_asr__som__somat_007
- mh_p_asr__som__somat_008
- mh_p_asr__som__somat_009
- mh_p_asr__aggr_002
- mh_p_asr__aggr_003
- mh_p_asr__aggr_004
- mh_p_asr__aggr_005
- mh_p_asr__aggr_006
- mh_p_asr__anxdep_001
- mh_p_asr__anxdep_002
- mh_p_asr__anxdep_003
- mh_p_asr__anxdep_004
- mh_p_asr__anxdep_005
- mh_p_asr__anxdep_006
- mh_p_asr__attn_001
- mh_p_asr__attn_002
- mh_p_asr__attn_003
- mh_p_asr__attn_004
- mh_p_asr__attn_005
- mh_p_asr__intru_001

  - mh_p_asr__intru_002
  - mh_p_asr__intru_003
  - mh_p_asr__intru_004
  - mh_p_asr__intru_005
  - mh_p_asr__intru_006
  - mh_p_asr__rule_002
  - mh_p_asr__rule_004
  - mh_p_asr__som_001
  - mh_p_asr__wthdr_001
  - mh_p_asr__wthdr_002
  - mh_p_asr__wthdr_003
  - mh_p_asr__wthdr_004
  - mh_p_asr__othpr_001
  - mh_p_asr__othpr_002
  - mh_p_asr__othpr_003
  - mh_p_asr__othpr_004
  - mh_p_asr__othpr_005
  - mh_p_asr__othpr_006
  - mh_p_asr__othpr_007
  - mh_p_asr__othpr_008
  - mh_p_asr__othpr_009
  - mh_p_asr__othpr_010
  - mh_p_asr__othpr_011
  - mh_p_asr__tho_003
  - mh_p_asr__tho_004
  - mh_p_asr__tho_008

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 8 of 120 items missing

Usage

```
compute_mh_p_asr_sum(
  data,
  name = "mh_p_asr_sum",
  max_na = 8,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_asr_nm()

Examples

```
## Not run:
compute_mh_p_asr_sum(data) |>
  select(
    any_of(c("mh_p_asr_sum", vars_mh_p_asr))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__dsm__adhd_sum

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): Sum"

Description

Computes the summary score mh_p_cbcl__dsm__adhd_sum Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): Sum

- *Summarized variables:*
  - mh_p_cbcl__attn__adhd_001
  - mh_p_cbcl__attn__adhd_002
  - mh_p_cbcl__attn__adhd_003
  - mh_p_cbcl__aggr__adhd_001
  - mh_p_cbcl__attn__adhd_004
  - mh_p_cbcl__attn__adhd_005

    - mh_p_cbcl__othpr__adhd_001
  - *Excluded values:*
    - 777
    - 999
  - *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_cbcl__dsm__adhd_sum(
  data,
  name = "mh_p_cbcl__dsm__adhd_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__adhd_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__adhd_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__adhd_sum", vars_mh_p_cbcl__dsm__adhd))
  )

## End(Not run)
```

`compute_mh_p_cbcl__dsm__adhd_tscore`
Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): T-score"

Description

Computes the summary score `mh_p_cbcl__dsm__adhd_tscore` Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): T-score

- *Summarized variables:*
  - `mh_p_cbcl__attn__adhd_001`
  - `mh_p_cbcl__attn__adhd_002`
  - `mh_p_cbcl__attn__adhd_003`
  - `mh_p_cbcl__aggr__adhd_001`
  - `mh_p_cbcl__attn__adhd_004`
  - `mh_p_cbcl__attn__adhd_005`
  - `mh_p_cbcl__othpr__adhd_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_cbcl__dsm__adhd_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__dsm__adhd_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.
`col_sex`	character, name of the sex column. see `ss_tscore()`.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__adhd_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__adhd_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__adhd_tscore", vars_mh_p_cbcl__dsm__adhd))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__dsm__anx_sum

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety): Sum"

Description

Computes the summary score mh_p_cbcl__dsm__anx_sum Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety): Sum

- *Summarized variables:*
  - mh_p_cbcl__soc__anx_001
  - mh_p_cbcl__anxdep__anx_007
  - mh_p_cbcl__anxdep__anx_001
  - mh_p_cbcl__anxdep__anx_002
  - mh_p_cbcl__anxdep__anx_003
  - mh_p_cbcl__anxdep__anx_004
  - mh_p_cbcl__som__anx_001
  - mh_p_cbcl__anxdep__anx_005
  - mh_p_cbcl__anxdep__anx_006
- *Excluded values:*

  - 777
  - 999

- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_cbcl__dsm__anx_sum(
  data,
  name = "mh_p_cbcl__dsm__anx_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__anx_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__anx_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__anx_sum", vars_mh_p_cbcl__dsm__anx))
  )

## End(Not run)
```

`compute_mh_p_cbcl__dsm__anx_tscore`
Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety): T-score"

Description

Computes the summary score `mh_p_cbcl__dsm__anx_tscore` Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety): T-score

- *Summarized variables:*
  - `mh_p_cbcl__soc__anx_001`
  - `mh_p_cbcl__anxdep__anx_007`
  - `mh_p_cbcl__anxdep__anx_001`
  - `mh_p_cbcl__anxdep__anx_002`
  - `mh_p_cbcl__anxdep__anx_003`
  - `mh_p_cbcl__anxdep__anx_004`
  - `mh_p_cbcl__som__anx_001`
  - `mh_p_cbcl__anxdep__anx_005`
  - `mh_p_cbcl__anxdep__anx_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 9 items missing

Usage

```
compute_mh_p_cbcl__dsm__anx_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__dsm__anx_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.

col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__anx_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__anx_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__anx_tscore", vars_mh_p_cbcl__dsm__anx))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__dsm__cond_sum

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Conduct problems): Sum"

Description

Computes the summary score mh_p_cbcl__dsm__cond_sum Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Conduct problems): Sum

- *Summarized variables:*
  - mh_p_cbcl__rule__cond_010
  - mh_p_cbcl__rule__cond_011
  - mh_p_cbcl__othpr__cond_001
  - mh_p_cbcl__aggr__cond_001
  - mh_p_cbcl__aggr__cond_002
  - mh_p_cbcl__rule__cond_001
  - mh_p_cbcl__rule__cond_002
  - mh_p_cbcl__aggr__cond_003
  - mh_p_cbcl__rule__cond_003

  - mh_p_cbcl__rule__cond_004
  - mh_p_cbcl__aggr__cond_004
  - mh_p_cbcl__rule__cond_005
  - mh_p_cbcl__rule__cond_006
  - mh_p_cbcl__rule__cond_007
  - mh_p_cbcl__rule__cond_008
  - mh_p_cbcl__rule__cond_009
  - mh_p_cbcl__aggr__cond_005

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 17 items missing

Usage

```
compute_mh_p_cbcl__dsm__cond_sum(
  data,
  name = "mh_p_cbcl__dsm__cond_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__cond_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__cond_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__cond_sum", vars_mh_p_cbcl__dsm__cond))
  )

## End(Not run)
```

`compute_mh_p_cbcl__dsm__cond_tscore`
Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Conduct problems): T-score"

Description

Computes the summary score `mh_p_cbcl__dsm__cond_tscore` Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Conduct problems): T-score

- *Summarized variables:*
  - `mh_p_cbcl__rule__cond_010`
  - `mh_p_cbcl__rule__cond_011`
  - `mh_p_cbcl__othpr__cond_001`
  - `mh_p_cbcl__aggr__cond_001`
  - `mh_p_cbcl__aggr__cond_002`
  - `mh_p_cbcl__rule__cond_001`
  - `mh_p_cbcl__rule__cond_002`
  - `mh_p_cbcl__aggr__cond_003`
  - `mh_p_cbcl__rule__cond_003`
  - `mh_p_cbcl__rule__cond_004`
  - `mh_p_cbcl__aggr__cond_004`
  - `mh_p_cbcl__rule__cond_005`
  - `mh_p_cbcl__rule__cond_006`
  - `mh_p_cbcl__rule__cond_007`
  - `mh_p_cbcl__rule__cond_008`
  - `mh_p_cbcl__rule__cond_009`
  - `mh_p_cbcl__aggr__cond_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 17 items missing

Usage

```
compute_mh_p_cbcl__dsm__cond_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__dsm__cond_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__cond_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__cond_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__cond_tscore", vars_mh_p_cbcl__dsm__cond))
  )

## End(Not run)
```

compute_mh_p_cbcl__dsm__dep_sum *Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): Sum"*

Description

Computes the summary score mh_p_cbcl__dsm__dep_sum Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): Sum

- *Summarized variables:*
  - mh_p_cbcl__wthdep__dep_001
  - mh_p_cbcl__tho__dep_003
  - mh_p_cbcl__wthdep__dep_002
  - mh_p_cbcl__wthdep__dep_003
  - mh_p_cbcl__anxdep__dep_001
  - mh_p_cbcl__tho__dep_001
  - mh_p_cbcl__othpr__dep_001
  - mh_p_cbcl__anxdep__dep_002
  - mh_p_cbcl__anxdep__dep_003
  - mh_p_cbcl__som__dep_001
  - mh_p_cbcl__tho__dep_002
  - mh_p_cbcl__othpr__dep_002
  - mh_p_cbcl__anxdep__dep_004
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 13 items missing

Usage

```
compute_mh_p_cbcl__dsm__dep_sum(
  data,
  name = "mh_p_cbcl__dsm__dep_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__dep_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__dep_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__dep_sum", vars_mh_p_cbcl__dsm__dep))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__dsm__dep_tscore

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): T-score"

Description

Computes the summary score mh_p_cbcl__dsm__dep_tscore Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): T-score

- *Summarized variables:*
  - mh_p_cbcl__wthdep__dep_001
  - mh_p_cbcl__tho__dep_003
  - mh_p_cbcl__wthdep__dep_002
  - mh_p_cbcl__wthdep__dep_003
  - mh_p_cbcl__anxdep__dep_001
  - mh_p_cbcl__tho__dep_001
  - mh_p_cbcl__othpr__dep_001
  - mh_p_cbcl__anxdep__dep_002
  - mh_p_cbcl__anxdep__dep_003
  - mh_p_cbcl__som__dep_001

  - mh_p_cbcl__tho__dep_002
  - mh_p_cbcl__othpr__dep_002
  - mh_p_cbcl__anxdep__dep_004
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 13 items missing

Usage

```
compute_mh_p_cbcl__dsm__dep_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__dsm__dep_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__dep_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__dep_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__dep_tscore", vars_mh_p_cbcl__dsm__dep))
  )

## End(Not run)
```

`compute_mh_p_cbcl__dsm__opp_sum`

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Oppositional Defiant problems): Sum"

Description

Computes the summary score `mh_p_cbcl__dsm__opp_sum` Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Oppositional Defiant problems): Sum

- *Summarized variables:*
  - `mh_p_cbcl__aggr__opp_001`
  - `mh_p_cbcl__aggr__opp_002`
  - `mh_p_cbcl__aggr__opp_003`
  - `mh_p_cbcl__aggr__opp_004`
  - `mh_p_cbcl__aggr__opp_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 5 items missing

Usage

```
compute_mh_p_cbcl__dsm__opp_sum(
  data,
  name = "mh_p_cbcl__dsm__opp_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__opp_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__opp_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__opp_sum", vars_mh_p_cbcl__dsm__opp))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__dsm__opp_tscore

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Oppositional Defiant problems): T-score"

Description

Computes the summary score mh_p_cbcl__dsm__opp_tscore Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Oppositional Defiant problems): T-score

- *Summarized variables:*
  - mh_p_cbcl__aggr__opp_001
  - mh_p_cbcl__aggr__opp_002
  - mh_p_cbcl__aggr__opp_003
  - mh_p_cbcl__aggr__opp_004
  - mh_p_cbcl__aggr__opp_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 5 items missing

Usage

```
compute_mh_p_cbcl__dsm__opp_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__dsm__opp_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__opp_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__opp_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__opp_tscore", vars_mh_p_cbcl__dsm__opp))
  )

## End(Not run)
```

`compute_mh_p_cbcl__dsm__somat_sum`
Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): Sum"

Description

Computes the summary score `mh_p_cbcl__dsm__somat_sum` Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): Sum

- *Summarized variables:*
  - `mh_p_cbcl__som__somat_001`
  - `mh_p_cbcl__som__somat_002`
  - `mh_p_cbcl__som__somat_003`
  - `mh_p_cbcl__som__somat_004`
  - `mh_p_cbcl__som__somat_005`
  - `mh_p_cbcl__som__somat_006`
  - `mh_p_cbcl__som__somat_007`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_cbcl__dsm__somat_sum(
  data,
  name = "mh_p_cbcl__dsm__somat_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_p_cbcl__dsm__somat_nm()`

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__somat_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__somat_sum", vars_mh_p_cbcl__dsm__somat))
  )

## End(Not run)
```

`compute_mh_p_cbcl__dsm__somat_tscore`
Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): T-score"

Description

Computes the summary score `mh_p_cbcl__dsm__somat_tscore` Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): T-score

- *Summarized variables:*
  - `mh_p_cbcl__som__somat_001`
  - `mh_p_cbcl__som__somat_002`
  - `mh_p_cbcl__som__somat_003`
  - `mh_p_cbcl__som__somat_004`
  - `mh_p_cbcl__som__somat_005`
  - `mh_p_cbcl__som__somat_006`
  - `mh_p_cbcl__som__somat_007`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_p_cbcl__dsm__somat_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__dsm__somat_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__dsm__somat_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__somat_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__somat_tscore", vars_mh_p_cbcl__dsm__somat))
  )

## End(Not run)
```

`compute_mh_p_cbcl__ocd_sum`

Compute "Child Behavior Checklist [Parent] (Obsessive-Compulsive Problems): Sum"

Description

Computes the summary score `mh_p_cbcl__ocd_sum` Child Behavior Checklist [Parent] (Obsessive-Compulsive Problems): Sum

- *Summarized variables:*
  - `mh_p_cbcl__tho_001`
  - `mh_p_cbcl__anxdep__anx_007`
  - `mh_p_cbcl__anxdep__anx_003`
  - `mh_p_cbcl__anxdep_001`
  - `mh_p_cbcl__anxdep__dep_003`
  - `mh_p_cbcl__tho_007`
  - `mh_p_cbcl__tho_010`
  - `mh_p_cbcl__tho_011`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 8 items missing

Usage

```
compute_mh_p_cbcl__ocd_sum(
  data,
  name = "mh_p_cbcl__ocd_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_p_cbcl__ocd_nm()`

Examples

```
## Not run:
compute_mh_p_cbcl__ocd_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__ocd_sum", vars_mh_p_cbcl__ocd))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__ocd_tscore

Compute "Child Behavior Checklist [Parent] (Obsessive-Compulsive Problems): T-score"

Description

Computes the summary score `mh_p_cbcl__ocd_tscore` Child Behavior Checklist [Parent] (Obsessive-Compulsive Problems): T-score

- *Summarized variables:*
  - `mh_p_cbcl__tho_001`
  - `mh_p_cbcl__anxdep__anx_007`
  - `mh_p_cbcl__anxdep__anx_003`
  - `mh_p_cbcl__anxdep_001`
  - `mh_p_cbcl__anxdep__dep_003`
  - `mh_p_cbcl__tho_007`
  - `mh_p_cbcl__tho_010`
  - `mh_p_cbcl__tho_011`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 8 items missing

Usage

```
compute_mh_p_cbcl__ocd_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__ocd_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__ocd_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__ocd_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__ocd_tscore", vars_mh_p_cbcl__ocd))
  )

## End(Not run)
```

`compute_mh_p_cbcl__sct_sum` *Compute "Child Behavior Checklist [Parent] (Sluggish Cognitive Tempo): Sum"*

Description

Computes the summary score `mh_p_cbcl__sct_sum` Child Behavior Checklist [Parent] (Sluggish Cognitive Tempo): Sum

- *Summarized variables:*
  - `mh_p_cbcl__wthdep__dep_002`
  - `mh_p_cbcl__attn_002`
  - `mh_p_cbcl__attn_003`
  - `mh_p_cbcl__attn_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
compute_mh_p_cbcl__sct_sum(
  data,
  name = "mh_p_cbcl__sct_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

compute_mh_p_cbcl__sct_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__sct_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__sct_sum", vars_mh_p_cbcl__sct))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__sct_tscore

Compute "Child Behavior Checklist [Parent] (Sluggish Cognitive Tempo): T-score"

Description

Computes the summary score mh_p_cbcl__sct_tscore Child Behavior Checklist [Parent] (Sluggish Cognitive Tempo): T-score

- *Summarized variables:*
  - mh_p_cbcl__wthdep__dep_002
  - mh_p_cbcl__attn_002
  - mh_p_cbcl__attn_003
  - mh_p_cbcl__attn_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
compute_mh_p_cbcl__sct_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__sct_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__sct_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__sct_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__sct_tscore", vars_mh_p_cbcl__sct))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__strs_sum

Compute "Child Behavior Checklist [Parent] (Stress): Sum"

Description

Computes the summary score mh_p_cbcl__strs_sum Child Behavior Checklist [Parent] (Stress): Sum

- *Summarized variables:*
  - mh_p_cbcl__aggr__opp_001
  - mh_p_cbcl__attn__adhd_002
  - mh_p_cbcl__tho_001
  - mh_p_cbcl__wthdep__dep_002

  - mh_p_cbcl__soc__anx_001
  - mh_p_cbcl__wthdep_005
  - mh_p_cbcl__anxdep__anx_003
  - mh_p_cbcl__soc_004
  - mh_p_cbcl__anxdep__anx_004
  - mh_p_cbcl__som__anx_001
  - mh_p_cbcl__anxdep__anx_005
  - mh_p_cbcl__anxdep__dep_003
  - mh_p_cbcl__wthdep_003
  - mh_p_cbcl__aggr_004
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 14 items missing

Usage

```
compute_mh_p_cbcl__strs_sum(
  data,
  name = "mh_p_cbcl__strs_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__strs_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__strs_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__strs_sum", vars_mh_p_cbcl__strs))
  )

## End(Not run)
```

`compute_mh_p_cbcl__strs_tscore`
Compute "Child Behavior Checklist [Parent] (Stress): T-score"

Description

Computes the summary score `mh_p_cbcl__strs_tscore` Child Behavior Checklist [Parent] (Stress): T-score

- *Summarized variables:*
  - `mh_p_cbcl__aggr__opp_001`
  - `mh_p_cbcl__attn__adhd_002`
  - `mh_p_cbcl__tho_001`
  - `mh_p_cbcl__wthdep__dep_002`
  - `mh_p_cbcl__soc__anx_001`
  - `mh_p_cbcl__wthdep_005`
  - `mh_p_cbcl__anxdep__anx_003`
  - `mh_p_cbcl__soc_004`
  - `mh_p_cbcl__anxdep__anx_004`
  - `mh_p_cbcl__som__anx_001`
  - `mh_p_cbcl__anxdep__anx_005`
  - `mh_p_cbcl__anxdep__dep_003`
  - `mh_p_cbcl__wthdep_003`
  - `mh_p_cbcl__aggr_004`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 14 items missing

Usage

```
compute_mh_p_cbcl__strs_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__strs_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__strs_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__strs_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__strs_tscore", vars_mh_p_cbcl__strs))
  )

## End(Not run)
```

`compute_mh_p_cbcl__synd__aggr_sum` *Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): Sum"*

Description

Computes the summary score `mh_p_cbcl__synd__aggr_sum` Child Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): Sum

- *Summarized variables:*
  - `mh_p_cbcl__aggr__opp_001`
  - `mh_p_cbcl__aggr__adhd_001`
  - `mh_p_cbcl__aggr__cond_001`
  - `mh_p_cbcl__aggr_001`
  - `mh_p_cbcl__aggr_002`
  - `mh_p_cbcl__aggr__cond_002`
  - `mh_p_cbcl__aggr__opp_002`
  - `mh_p_cbcl__aggr__opp_003`
  - `mh_p_cbcl__aggr__cond_003`
  - `mh_p_cbcl__aggr__cond_004`
  - `mh_p_cbcl__aggr_003`
  - `mh_p_cbcl__aggr__opp_004`
  - `mh_p_cbcl__aggr_004`
  - `mh_p_cbcl__aggr_005`
  - `mh_p_cbcl__aggr_006`
  - `mh_p_cbcl__aggr_007`
  - `mh_p_cbcl__aggr__opp_005`
  - `mh_p_cbcl__aggr__cond_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 18 items missing

Usage

```
compute_mh_p_cbcl__synd__aggr_sum(
  data,
  name = "mh_p_cbcl__synd__aggr_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__aggr_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__aggr_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__aggr_sum", vars_mh_p_cbcl__synd__aggr))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__aggr_tscore

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): T-score"

Description

Computes the summary score mh_p_cbcl__synd__aggr_tscore Child Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): T-score

- *Summarized variables:*
  - mh_p_cbcl__aggr__opp_001
  - mh_p_cbcl__aggr__adhd_001
  - mh_p_cbcl__aggr__cond_001
  - mh_p_cbcl__aggr_001
  - mh_p_cbcl__aggr_002
  - mh_p_cbcl__aggr__cond_002

  - mh_p_cbcl__aggr__opp_002
  - mh_p_cbcl__aggr__opp_003
  - mh_p_cbcl__aggr__cond_003
  - mh_p_cbcl__aggr__cond_004
  - mh_p_cbcl__aggr_003
  - mh_p_cbcl__aggr__opp_004
  - mh_p_cbcl__aggr_004
  - mh_p_cbcl__aggr_005
  - mh_p_cbcl__aggr_006
  - mh_p_cbcl__aggr_007
  - mh_p_cbcl__aggr__opp_005
  - mh_p_cbcl__aggr__cond_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 18 items missing

Usage

```
compute_mh_p_cbcl__synd__aggr_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__aggr_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__aggr_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__aggr_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__aggr_tscore", vars_mh_p_cbcl__synd__aggr))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__anxdep_sum

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): Sum"

Description

Computes the summary score mh_p_cbcl__synd__anxdep_sum Child Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): Sum

- *Summarized variables:*
  - mh_p_cbcl__anxdep__anx_007
  - mh_p_cbcl__anxdep__dep_001
  - mh_p_cbcl__anxdep__anx_001
  - mh_p_cbcl__anxdep__anx_002
  - mh_p_cbcl__anxdep__anx_003
  - mh_p_cbcl__anxdep_001
  - mh_p_cbcl__anxdep_002
  - mh_p_cbcl__anxdep__dep_002
  - mh_p_cbcl__anxdep__anx_004
  - mh_p_cbcl__anxdep__anx_005
  - mh_p_cbcl__anxdep__dep_003
  - mh_p_cbcl__anxdep__anx_006
  - mh_p_cbcl__anxdep__dep_004
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 13 items missing

Usage

```
compute_mh_p_cbcl__synd__anxdep_sum(
  data,
  name = "mh_p_cbcl__synd__anxdep_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__anxdep_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__anxdep_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__anxdep_sum", vars_mh_p_cbcl__synd__anxdep))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__anxdep_tscore

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): T-score"

Description

Computes the summary score `mh_p_cbcl__synd__anxdep_tscore` Child Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): T-score

- *Summarized variables:*
  - `mh_p_cbcl__anxdep__anx_007`
  - `mh_p_cbcl__anxdep__dep_001`
  - `mh_p_cbcl__anxdep__anx_001`
  - `mh_p_cbcl__anxdep__anx_002`
  - `mh_p_cbcl__anxdep__anx_003`
  - `mh_p_cbcl__anxdep_001`
  - `mh_p_cbcl__anxdep_002`
  - `mh_p_cbcl__anxdep__dep_002`
  - `mh_p_cbcl__anxdep__anx_004`
  - `mh_p_cbcl__anxdep__anx_005`
  - `mh_p_cbcl__anxdep__dep_003`
  - `mh_p_cbcl__anxdep__anx_006`
  - `mh_p_cbcl__anxdep__dep_004`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 13 items missing

Usage

```
compute_mh_p_cbcl__synd__anxdep_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__anxdep_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.
`col_sex`	character, name of the sex column. see `ss_tscore()`.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__anxdep_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__anxdep_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__anxdep_tscore", vars_mh_p_cbcl__synd__anxdep))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__attn_sum

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Attention problems): Sum"

Description

Computes the summary score mh_p_cbcl__synd__attn_sum Child Behavior Checklist [Parent] (Syndrome Scale - Attention problems): Sum

- *Summarized variables:*
  - mh_p_cbcl__attn_001
  - mh_p_cbcl__attn__adhd_001
  - mh_p_cbcl__attn__adhd_002
  - mh_p_cbcl__attn__adhd_003
  - mh_p_cbcl__attn_002
  - mh_p_cbcl__attn_003
  - mh_p_cbcl__attn__adhd_004
  - mh_p_cbcl__attn_004
  - mh_p_cbcl__attn__adhd_005
  - mh_p_cbcl__attn_005

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 10 items missing

Usage

```
compute_mh_p_cbcl__synd__attn_sum(
  data,
  name = "mh_p_cbcl__synd__attn_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_p_cbcl__synd__attn_nm()`

Examples

```
## Not run:
compute_mh_p_cbcl__synd__attn_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__attn_sum", vars_mh_p_cbcl__synd__attn))
  )

## End(Not run)
```

`compute_mh_p_cbcl__synd__attn_tscore`
Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Attention problems): T-score"

Description

Computes the summary score `mh_p_cbcl__synd__attn_tscore` Child Behavior Checklist [Parent] (Syndrome Scale - Attention problems): T-score

- *Summarized variables:*
  - `mh_p_cbcl__attn_001`
  - `mh_p_cbcl__attn__adhd_001`
  - `mh_p_cbcl__attn__adhd_002`
  - `mh_p_cbcl__attn__adhd_003`
  - `mh_p_cbcl__attn_002`
  - `mh_p_cbcl__attn_003`
  - `mh_p_cbcl__attn__adhd_004`
  - `mh_p_cbcl__attn_004`
  - `mh_p_cbcl__attn__adhd_005`
  - `mh_p_cbcl__attn_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 10 items missing

Usage

```
compute_mh_p_cbcl__synd__attn_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__attn_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.

col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__attn_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__attn_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__attn_tscore", vars_mh_p_cbcl__synd__attn))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__ext_sum

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Externalizing): Sum"

Description

Computes the summary score mh_p_cbcl__synd__ext_sum Child Behavior Checklist [Parent] (Syndrome Scale - Externalizing): Sum

- *Summarized variables:*
  - mh_p_cbcl__rule_001
  - mh_p_cbcl__rule__cond_010
  - mh_p_cbcl__rule_006
  - mh_p_cbcl__rule__cond_011
  - mh_p_cbcl__rule__cond_001
  - mh_p_cbcl__rule__cond_002
  - mh_p_cbcl__rule__cond_003
  - mh_p_cbcl__rule__cond_004

  - mh_p_cbcl__rule_002
  - mh_p_cbcl__rule__cond_005
  - mh_p_cbcl__rule__cond_006
  - mh_p_cbcl__rule_003
  - mh_p_cbcl__rule__cond_007
  - mh_p_cbcl__rule__cond_008
  - mh_p_cbcl__rule__cond_009
  - mh_p_cbcl__rule_004
  - mh_p_cbcl__rule_005
  - mh_p_cbcl__aggr__opp_001
  - mh_p_cbcl__aggr__adhd_001
  - mh_p_cbcl__aggr__cond_001
  - mh_p_cbcl__aggr_001
  - mh_p_cbcl__aggr_002
  - mh_p_cbcl__aggr__cond_002
  - mh_p_cbcl__aggr__opp_002
  - mh_p_cbcl__aggr__opp_003
  - mh_p_cbcl__aggr__cond_003
  - mh_p_cbcl__aggr__cond_004
  - mh_p_cbcl__aggr_003
  - mh_p_cbcl__aggr__opp_004
  - mh_p_cbcl__aggr_004
  - mh_p_cbcl__aggr_005
  - mh_p_cbcl__aggr_006
  - mh_p_cbcl__aggr_007
  - mh_p_cbcl__aggr__opp_005
  - mh_p_cbcl__aggr__cond_005

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 35 items missing

Usage

```
compute_mh_p_cbcl__synd__ext_sum(
  data,
  name = "mh_p_cbcl__synd__ext_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__ext_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__ext_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__ext_sum", vars_mh_p_cbcl__synd__ext))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__ext_tscore

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Externalizing): T-score"

Description

Computes the summary score mh_p_cbcl__synd__ext_tscore Child Behavior Checklist [Parent] (Syndrome Scale - Externalizing): T-score

- *Summarized variables:*
  - mh_p_cbcl__rule_001
  - mh_p_cbcl__rule__cond_010
  - mh_p_cbcl__rule_006
  - mh_p_cbcl__rule__cond_011
  - mh_p_cbcl__rule__cond_001
  - mh_p_cbcl__rule__cond_002

  - mh_p_cbcl__rule__cond_003
  - mh_p_cbcl__rule__cond_004
  - mh_p_cbcl__rule_002
  - mh_p_cbcl__rule__cond_005
  - mh_p_cbcl__rule__cond_006
  - mh_p_cbcl__rule_003
  - mh_p_cbcl__rule__cond_007
  - mh_p_cbcl__rule__cond_008
  - mh_p_cbcl__rule__cond_009
  - mh_p_cbcl__rule_004
  - mh_p_cbcl__rule_005
  - mh_p_cbcl__aggr__opp_001
  - mh_p_cbcl__aggr__adhd_001
  - mh_p_cbcl__aggr__cond_001
  - mh_p_cbcl__aggr_001
  - mh_p_cbcl__aggr_002
  - mh_p_cbcl__aggr__cond_002
  - mh_p_cbcl__aggr__opp_002
  - mh_p_cbcl__aggr__opp_003
  - mh_p_cbcl__aggr__cond_003
  - mh_p_cbcl__aggr__cond_004
  - mh_p_cbcl__aggr_003
  - mh_p_cbcl__aggr__opp_004
  - mh_p_cbcl__aggr_004
  - mh_p_cbcl__aggr_005
  - mh_p_cbcl__aggr_006
  - mh_p_cbcl__aggr_007
  - mh_p_cbcl__aggr__opp_005
  - mh_p_cbcl__aggr__cond_005

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 35 items missing

Usage

```
compute_mh_p_cbcl__synd__ext_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__ext_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__ext_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__ext_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__ext_tscore", vars_mh_p_cbcl__synd__ext))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__int_sum

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Internalizing): Sum"

Description

Computes the summary score mh_p_cbcl__synd__int_sum Child Behavior Checklist [Parent] (Syndrome Scale - Internalizing): Sum

- *Summarized variables:*
  - mh_p_cbcl__anxdep__anx_007
  - mh_p_cbcl__anxdep__dep_001
  - mh_p_cbcl__anxdep__anx_001

  - mh_p_cbcl__anxdep__anx_002
  - mh_p_cbcl__anxdep__anx_003
  - mh_p_cbcl__anxdep_001
  - mh_p_cbcl__anxdep_002
  - mh_p_cbcl__anxdep__dep_002
  - mh_p_cbcl__anxdep__anx_004
  - mh_p_cbcl__anxdep__anx_005
  - mh_p_cbcl__anxdep__dep_003
  - mh_p_cbcl__anxdep__anx_006
  - mh_p_cbcl__anxdep__dep_004
  - mh_p_cbcl__wthdep__dep_001
  - mh_p_cbcl__wthdep__dep_002
  - mh_p_cbcl__wthdep__dep_003
  - mh_p_cbcl__wthdep_005
  - mh_p_cbcl__wthdep_001
  - mh_p_cbcl__wthdep_002
  - mh_p_cbcl__wthdep_003
  - mh_p_cbcl__wthdep_004
  - mh_p_cbcl__som__anx_001
  - mh_p_cbcl__som_001
  - mh_p_cbcl__som_002
  - mh_p_cbcl__som__dep_001
  - mh_p_cbcl__som__somat_001
  - mh_p_cbcl__som__somat_002
  - mh_p_cbcl__som__somat_003
  - mh_p_cbcl__som__somat_004
  - mh_p_cbcl__som__somat_005
  - mh_p_cbcl__som__somat_006
  - mh_p_cbcl__som__somat_007

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 32 items missing

Usage

```
compute_mh_p_cbcl__synd__int_sum(
  data,
  name = "mh_p_cbcl__synd__int_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__int_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__int_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__int_sum", vars_mh_p_cbcl__synd__int))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__int_tscore

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Internalizing): T-score"

Description

Computes the summary score mh_p_cbcl__synd__int_tscore Child Behavior Checklist [Parent] (Syndrome Scale - Internalizing): T-score

- *Summarized variables:*
  - mh_p_cbcl__anxdep__anx_007
  - mh_p_cbcl__anxdep__dep_001
  - mh_p_cbcl__anxdep__anx_001
  - mh_p_cbcl__anxdep__anx_002
  - mh_p_cbcl__anxdep__anx_003
  - mh_p_cbcl__anxdep_001

  - mh_p_cbcl__anxdep_002
  - mh_p_cbcl__anxdep__dep_002
  - mh_p_cbcl__anxdep__anx_004
  - mh_p_cbcl__anxdep__anx_005
  - mh_p_cbcl__anxdep__dep_003
  - mh_p_cbcl__anxdep__anx_006
  - mh_p_cbcl__anxdep__dep_004
  - mh_p_cbcl__wthdep__dep_001
  - mh_p_cbcl__wthdep__dep_002
  - mh_p_cbcl__wthdep__dep_003
  - mh_p_cbcl__wthdep_005
  - mh_p_cbcl__wthdep_001
  - mh_p_cbcl__wthdep_002
  - mh_p_cbcl__wthdep_003
  - mh_p_cbcl__wthdep_004
  - mh_p_cbcl__som__anx_001
  - mh_p_cbcl__som_001
  - mh_p_cbcl__som_002
  - mh_p_cbcl__som__dep_001
  - mh_p_cbcl__som__somat_001
  - mh_p_cbcl__som__somat_002
  - mh_p_cbcl__som__somat_003
  - mh_p_cbcl__som__somat_004
  - mh_p_cbcl__som__somat_005
  - mh_p_cbcl__som__somat_006
  - mh_p_cbcl__som__somat_007

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 32 items missing

Usage

```
compute_mh_p_cbcl__synd__int_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__int_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__int_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__int_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__int_tscore", vars_mh_p_cbcl__synd__int))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__othpr_sum

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Other problems): Sum"

Description

Computes the summary score mh_p_cbcl__synd__othpr_sum Child Behavior Checklist [Parent] (Syndrome Scale - Other problems): Sum

- *Summarized variables:*
  - mh_p_cbcl__othpr_001
  - mh_p_cbcl__othpr_002
  - mh_p_cbcl__othpr_009

  - mh_p_cbcl__othpr_010
  - mh_p_cbcl__othpr_011
  - mh_p_cbcl__othpr_012
  - mh_p_cbcl__othpr__cond_001
  - mh_p_cbcl__othpr__dep_001
  - mh_p_cbcl__othpr_003
  - mh_p_cbcl__othpr_004
  - mh_p_cbcl__othpr_005
  - mh_p_cbcl__othpr_006
  - mh_p_cbcl__othpr_007
  - mh_p_cbcl__othpr__dep_002
  - mh_p_cbcl__othpr__adhd_001
  - mh_p_cbcl__othpr_008
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 16 items missing

Usage

```
compute_mh_p_cbcl__synd__othpr_sum(
  data,
  name = "mh_p_cbcl__synd__othpr_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__othpr_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__othpr_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__othpr_sum", vars_mh_p_cbcl__synd__othpr))
  )

## End(Not run)
```

`compute_mh_p_cbcl__synd__rule_sum`

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): Sum"

Description

Computes the summary score `mh_p_cbcl__synd__rule_sum` Child Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): Sum

- *Summarized variables:*
  - `mh_p_cbcl__rule_001`
  - `mh_p_cbcl__rule__cond_010`
  - `mh_p_cbcl__rule_006`
  - `mh_p_cbcl__rule__cond_011`
  - `mh_p_cbcl__rule__cond_001`
  - `mh_p_cbcl__rule__cond_002`
  - `mh_p_cbcl__rule__cond_003`
  - `mh_p_cbcl__rule__cond_004`
  - `mh_p_cbcl__rule_002`
  - `mh_p_cbcl__rule__cond_005`
  - `mh_p_cbcl__rule__cond_006`
  - `mh_p_cbcl__rule_003`
  - `mh_p_cbcl__rule__cond_007`
  - `mh_p_cbcl__rule__cond_008`
  - `mh_p_cbcl__rule__cond_009`
  - `mh_p_cbcl__rule_004`
  - `mh_p_cbcl__rule_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 17 items missing

Usage

```
compute_mh_p_cbcl__synd__rule_sum(
  data,
  name = "mh_p_cbcl__synd__rule_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__rule_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__rule_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__rule_sum", vars_mh_p_cbcl__synd__rule))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__rule_tscore

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): T-score"

Description

Computes the summary score `mh_p_cbcl__synd__rule_tscore` Child Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): T-score

- *Summarized variables:*
  - `mh_p_cbcl__rule_001`
  - `mh_p_cbcl__rule__cond_010`
  - `mh_p_cbcl__rule_006`
  - `mh_p_cbcl__rule__cond_011`
  - `mh_p_cbcl__rule__cond_001`
  - `mh_p_cbcl__rule__cond_002`
  - `mh_p_cbcl__rule__cond_003`
  - `mh_p_cbcl__rule__cond_004`
  - `mh_p_cbcl__rule_002`
  - `mh_p_cbcl__rule__cond_005`
  - `mh_p_cbcl__rule__cond_006`
  - `mh_p_cbcl__rule_003`
  - `mh_p_cbcl__rule__cond_007`
  - `mh_p_cbcl__rule__cond_008`
  - `mh_p_cbcl__rule__cond_009`
  - `mh_p_cbcl__rule_004`
  - `mh_p_cbcl__rule_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 17 items missing

Usage

```
compute_mh_p_cbcl__synd__rule_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__rule_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.

name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__rule_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__rule_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__rule_tscore", vars_mh_p_cbcl__synd__rule))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__soc_sum

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Social): Sum"

Description

Computes the summary score mh_p_cbcl__synd__soc_sum Child Behavior Checklist [Parent] (Syndrome Scale -Social): Sum

- *Summarized variables:*
  - mh_p_cbcl__soc__anx_001
  - mh_p_cbcl__soc_001
  - mh_p_cbcl__soc_002
  - mh_p_cbcl__soc_003
  - mh_p_cbcl__soc_004
  - mh_p_cbcl__soc_005

  - mh_p_cbcl__soc_006
  - mh_p_cbcl__soc_007
  - mh_p_cbcl__soc_008
  - mh_p_cbcl__soc_009
  - mh_p_cbcl__soc_010
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 11 items missing

Usage

```
compute_mh_p_cbcl__synd__soc_sum(
  data,
  name = "mh_p_cbcl__synd__soc_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__soc_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__soc_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__soc_sum", vars_mh_p_cbcl__synd__soc))
  )

## End(Not run)
```

`compute_mh_p_cbcl__synd__soc_tscore` *Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Social): T-score"*

Description

Computes the summary score `mh_p_cbcl__synd__soc_tscore` Child Behavior Checklist [Parent] (Syndrome Scale -Social): T-score

- *Summarized variables:*
  - `mh_p_cbcl__soc__anx_001`
  - `mh_p_cbcl__soc_001`
  - `mh_p_cbcl__soc_002`
  - `mh_p_cbcl__soc_003`
  - `mh_p_cbcl__soc_004`
  - `mh_p_cbcl__soc_005`
  - `mh_p_cbcl__soc_006`
  - `mh_p_cbcl__soc_007`
  - `mh_p_cbcl__soc_008`
  - `mh_p_cbcl__soc_009`
  - `mh_p_cbcl__soc_010`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 11 items missing

Usage

```
compute_mh_p_cbcl__synd__soc_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__soc_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.

name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__soc_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__soc_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__soc_tscore", vars_mh_p_cbcl__synd__soc))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__som_sum

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): Sum"

Description

Computes the summary score mh_p_cbcl__synd__som_sum Child Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): Sum

- *Summarized variables:*
  - mh_p_cbcl__som__anx_001
  - mh_p_cbcl__som_001
  - mh_p_cbcl__som_002
  - mh_p_cbcl__som__dep_001
  - mh_p_cbcl__som__somat_001
  - mh_p_cbcl__som__somat_002

  - mh_p_cbcl__som__somat_003
  - mh_p_cbcl__som__somat_004
  - mh_p_cbcl__som__somat_005
  - mh_p_cbcl__som__somat_006
  - mh_p_cbcl__som__somat_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 11 items missing

Usage

```
compute_mh_p_cbcl__synd__som_sum(
  data,
  name = "mh_p_cbcl__synd__som_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__som_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__som_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__som_sum", vars_mh_p_cbcl__synd__som))
  )

## End(Not run)
```

`compute_mh_p_cbcl__synd__som_tscore`
Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): T-score"

Description

Computes the summary score `mh_p_cbcl__synd__som_tscore` Child Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): T-score

- *Summarized variables:*
  - `mh_p_cbcl__som__anx_001`
  - `mh_p_cbcl__som_001`
  - `mh_p_cbcl__som_002`
  - `mh_p_cbcl__som__dep_001`
  - `mh_p_cbcl__som__somat_001`
  - `mh_p_cbcl__som__somat_002`
  - `mh_p_cbcl__som__somat_003`
  - `mh_p_cbcl__som__somat_004`
  - `mh_p_cbcl__som__somat_005`
  - `mh_p_cbcl__som__somat_006`
  - `mh_p_cbcl__som__somat_007`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 11 items missing

Usage

```
compute_mh_p_cbcl__synd__som_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__som_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.

name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__som_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__som_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__som_tscore", vars_mh_p_cbcl__synd__som))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__tho_sum

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Thought problems): Sum"

Description

Computes the summary score mh_p_cbcl__synd__tho_sum Child Behavior Checklist [Parent] (Syndrome Scale - Thought problems): Sum

- *Summarized variables:*
  - mh_p_cbcl__tho_001
  - mh_p_cbcl__tho__dep_003
  - mh_p_cbcl__tho__dep_001
  - mh_p_cbcl__tho_002
  - mh_p_cbcl__tho_003
  - mh_p_cbcl__tho_004

  - mh_p_cbcl__tho_005
  - mh_p_cbcl__tho_006
  - mh_p_cbcl__tho_007
  - mh_p_cbcl__tho_008
  - mh_p_cbcl__tho__dep_002
  - mh_p_cbcl__tho_009
  - mh_p_cbcl__tho_010
  - mh_p_cbcl__tho_011
  - mh_p_cbcl__tho_012
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 15 items missing

Usage

```
compute_mh_p_cbcl__synd__tho_sum(
  data,
  name = "mh_p_cbcl__synd__tho_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__tho_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__tho_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__tho_sum", vars_mh_p_cbcl__synd__tho))
  )

## End(Not run)
```

`compute_mh_p_cbcl__synd__tho_tscore`
Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Thought problems): T-score"

Description

Computes the summary score `mh_p_cbcl__synd__tho_tscore` Child Behavior Checklist [Parent] (Syndrome Scale - Thought problems): T-score

- *Summarized variables:*
  - `mh_p_cbcl__tho_001`
  - `mh_p_cbcl__tho__dep_003`
  - `mh_p_cbcl__tho__dep_001`
  - `mh_p_cbcl__tho_002`
  - `mh_p_cbcl__tho_003`
  - `mh_p_cbcl__tho_004`
  - `mh_p_cbcl__tho_005`
  - `mh_p_cbcl__tho_006`
  - `mh_p_cbcl__tho_007`
  - `mh_p_cbcl__tho_008`
  - `mh_p_cbcl__tho__dep_002`
  - `mh_p_cbcl__tho_009`
  - `mh_p_cbcl__tho_010`
  - `mh_p_cbcl__tho_011`
  - `mh_p_cbcl__tho_012`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 15 items missing

Usage

```
compute_mh_p_cbcl__synd__tho_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__tho_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__tho_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__tho_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__tho_tscore", vars_mh_p_cbcl__synd__tho))
  )

## End(Not run)
```

`compute_mh_p_cbcl__synd__wthdep_sum`

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Withdrawn/Depressed): Sum"

Description

Computes the summary score `mh_p_cbcl__synd__wthdep_sum` Child Behavior Checklist [Parent] (Syndrome Scale - Withdrawn/Depressed): Sum

- *Summarized variables:*
  - `mh_p_cbcl__wthdep__dep_001`
  - `mh_p_cbcl__wthdep__dep_002`
  - `mh_p_cbcl__wthdep__dep_003`
  - `mh_p_cbcl__wthdep_005`
  - `mh_p_cbcl__wthdep_001`
  - `mh_p_cbcl__wthdep_002`
  - `mh_p_cbcl__wthdep_003`
  - `mh_p_cbcl__wthdep_004`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 8 items missing

Usage

```
compute_mh_p_cbcl__synd__wthdep_sum(
  data,
  name = "mh_p_cbcl__synd__wthdep_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_p_cbcl__synd__wthdep_nm()`

Examples

```
## Not run:
compute_mh_p_cbcl__synd__wthdep_sum(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__wthdep_sum", vars_mh_p_cbcl__synd__wthdep))
  )

## End(Not run)
```

---

compute_mh_p_cbcl__synd__wthdep_tscore

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Withdrawn/Depressed): T-score"

Description

Computes the summary score `mh_p_cbcl__synd__wthdep_tscore` Child Behavior Checklist [Parent] (Syndrome Scale - Withdrawn/Depressed): T-score

- *Summarized variables:*
  - `mh_p_cbcl__wthdep__dep_001`
  - `mh_p_cbcl__wthdep__dep_002`
  - `mh_p_cbcl__wthdep__dep_003`
  - `mh_p_cbcl__wthdep_005`
  - `mh_p_cbcl__wthdep_001`
  - `mh_p_cbcl__wthdep_002`
  - `mh_p_cbcl__wthdep_003`
  - `mh_p_cbcl__wthdep_004`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 8 items missing

Usage

```
compute_mh_p_cbcl__synd__wthdep_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl__synd__wthdep_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl__synd__wthdep_nm()

Examples

```
## Not run:
compute_mh_p_cbcl__synd__wthdep_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__wthdep_tscore", vars_mh_p_cbcl__synd__wthdep))
  )

## End(Not run)
```

compute_mh_p_cbcl_all *Compute all summary scores for mh_p_cbcl.*

Description

This function computes all summary scores for the mh_p_cbcl form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_cbcl_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_p_cbcl_all(data)

## End(Not run)
```

compute_mh_p_cbcl_sum *Compute "Child Behavior Checklist [Parent] (Syndrome Scale): Sum"*

Description

Computes the summary score mh_p_cbcl_sum Child Behavior Checklist [Parent] (Syndrome Scale): Sum

- *Summarized variables:*
  - mh_p_cbcl__attn__adhd_001
  - mh_p_cbcl__attn__adhd_002
  - mh_p_cbcl__attn__adhd_003
  - mh_p_cbcl__aggr__adhd_001
  - mh_p_cbcl__attn__adhd_004
  - mh_p_cbcl__attn__adhd_005
  - mh_p_cbcl__othpr__adhd_001
  - mh_p_cbcl__soc__anx_001
  - mh_p_cbcl__anxdep__anx_007

- mh_p_cbcl__anxdep__anx_001
- mh_p_cbcl__anxdep__anx_002
- mh_p_cbcl__anxdep__anx_003
- mh_p_cbcl__anxdep__anx_004
- mh_p_cbcl__som__anx_001
- mh_p_cbcl__anxdep__anx_005
- mh_p_cbcl__anxdep__anx_006
- mh_p_cbcl__rule__cond_010
- mh_p_cbcl__rule__cond_011
- mh_p_cbcl__othpr__cond_001
- mh_p_cbcl__aggr__cond_001
- mh_p_cbcl__aggr__cond_002
- mh_p_cbcl__rule__cond_001
- mh_p_cbcl__rule__cond_002
- mh_p_cbcl__aggr__cond_003
- mh_p_cbcl__rule__cond_003
- mh_p_cbcl__rule__cond_004
- mh_p_cbcl__aggr__cond_004
- mh_p_cbcl__rule__cond_005
- mh_p_cbcl__rule__cond_006
- mh_p_cbcl__rule__cond_007
- mh_p_cbcl__rule__cond_008
- mh_p_cbcl__rule__cond_009
- mh_p_cbcl__aggr__cond_005
- mh_p_cbcl__wthdep__dep_001
- mh_p_cbcl__tho__dep_003
- mh_p_cbcl__wthdep__dep_002
- mh_p_cbcl__wthdep__dep_003
- mh_p_cbcl__anxdep__dep_001
- mh_p_cbcl__tho__dep_001
- mh_p_cbcl__othpr__dep_001
- mh_p_cbcl__anxdep__dep_002
- mh_p_cbcl__anxdep__dep_003
- mh_p_cbcl__som__dep_001
- mh_p_cbcl__tho__dep_002
- mh_p_cbcl__othpr__dep_002
- mh_p_cbcl__anxdep__dep_004
- mh_p_cbcl__aggr__opp_001
- mh_p_cbcl__aggr__opp_002
- mh_p_cbcl__aggr__opp_003
- mh_p_cbcl__aggr__opp_004
- mh_p_cbcl__aggr__opp_005

- mh_p_cbcl__som__somat_001
- mh_p_cbcl__som__somat_002
- mh_p_cbcl__som__somat_003
- mh_p_cbcl__som__somat_004
- mh_p_cbcl__som__somat_005
- mh_p_cbcl__som__somat_006
- mh_p_cbcl__som__somat_007
- mh_p_cbcl__tho_001
- mh_p_cbcl__anxdep_001
- mh_p_cbcl__tho_007
- mh_p_cbcl__tho_010
- mh_p_cbcl__tho_011
- mh_p_cbcl__attn_002
- mh_p_cbcl__attn_003
- mh_p_cbcl__attn_005
- mh_p_cbcl__wthdep_005
- mh_p_cbcl__soc_004
- mh_p_cbcl__wthdep_003
- mh_p_cbcl__aggr_004
- mh_p_cbcl__aggr_001
- mh_p_cbcl__aggr_002
- mh_p_cbcl__aggr_003
- mh_p_cbcl__aggr_005
- mh_p_cbcl__aggr_006
- mh_p_cbcl__aggr_007
- mh_p_cbcl__anxdep_002
- mh_p_cbcl__attn_001
- mh_p_cbcl__attn_004
- mh_p_cbcl__rule_001
- mh_p_cbcl__rule_006
- mh_p_cbcl__rule_002
- mh_p_cbcl__rule_003
- mh_p_cbcl__rule_004
- mh_p_cbcl__rule_005
- mh_p_cbcl__wthdep_001
- mh_p_cbcl__wthdep_002
- mh_p_cbcl__wthdep_004
- mh_p_cbcl__som_001
- mh_p_cbcl__som_002
- mh_p_cbcl__othpr_001
- mh_p_cbcl__othpr_002
- mh_p_cbcl__othpr_009

  - mh_p_cbcl__othpr_010
  - mh_p_cbcl__othpr_011
  - mh_p_cbcl__othpr_012
  - mh_p_cbcl__othpr_003
  - mh_p_cbcl__othpr_004
  - mh_p_cbcl__othpr_005
  - mh_p_cbcl__othpr_006
  - mh_p_cbcl__othpr_007
  - mh_p_cbcl__othpr_008
  - mh_p_cbcl__soc_001
  - mh_p_cbcl__soc_002
  - mh_p_cbcl__soc_003
  - mh_p_cbcl__soc_005
  - mh_p_cbcl__soc_006
  - mh_p_cbcl__soc_007
  - mh_p_cbcl__soc_008
  - mh_p_cbcl__soc_009
  - mh_p_cbcl__soc_010
  - mh_p_cbcl__tho_002
  - mh_p_cbcl__tho_003
  - mh_p_cbcl__tho_004
  - mh_p_cbcl__tho_005
  - mh_p_cbcl__tho_006
  - mh_p_cbcl__tho_008
  - mh_p_cbcl__tho_009
  - mh_p_cbcl__tho_012

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 8 of 119 items missing

Usage

```
compute_mh_p_cbcl_sum(
  data,
  name = "mh_p_cbcl_sum",
  max_na = 8,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl_nm()

Examples

```
## Not run:
compute_mh_p_cbcl_sum(data) |>
  select(
    any_of(c("mh_p_cbcl_sum", vars_mh_p_cbcl))
  )

## End(Not run)
```

---

compute_mh_p_cbcl_tscore

Compute "Child Behavior Checklist [Parent] (Syndrome Scale): T-score"

Description

Computes the summary score mh_p_cbcl_tscore Child Behavior Checklist [Parent] (Syndrome Scale): T-score

- *Summarized variables:*
  - mh_p_cbcl__attn__adhd_001
  - mh_p_cbcl__attn__adhd_002
  - mh_p_cbcl__attn__adhd_003
  - mh_p_cbcl__aggr__adhd_001
  - mh_p_cbcl__attn__adhd_004
  - mh_p_cbcl__attn__adhd_005

- mh_p_cbcl__othpr__adhd_001
- mh_p_cbcl__soc__anx_001
- mh_p_cbcl__anxdep__anx_007
- mh_p_cbcl__anxdep__anx_001
- mh_p_cbcl__anxdep__anx_002
- mh_p_cbcl__anxdep__anx_003
- mh_p_cbcl__anxdep__anx_004
- mh_p_cbcl__som__anx_001
- mh_p_cbcl__anxdep__anx_005
- mh_p_cbcl__anxdep__anx_006
- mh_p_cbcl__rule__cond_010
- mh_p_cbcl__rule__cond_011
- mh_p_cbcl__othpr__cond_001
- mh_p_cbcl__aggr__cond_001
- mh_p_cbcl__aggr__cond_002
- mh_p_cbcl__rule__cond_001
- mh_p_cbcl__rule__cond_002
- mh_p_cbcl__aggr__cond_003
- mh_p_cbcl__rule__cond_003
- mh_p_cbcl__rule__cond_004
- mh_p_cbcl__aggr__cond_004
- mh_p_cbcl__rule__cond_005
- mh_p_cbcl__rule__cond_006
- mh_p_cbcl__rule__cond_007
- mh_p_cbcl__rule__cond_008
- mh_p_cbcl__rule__cond_009
- mh_p_cbcl__aggr__cond_005
- mh_p_cbcl__wthdep__dep_001
- mh_p_cbcl__tho__dep_003
- mh_p_cbcl__wthdep__dep_002
- mh_p_cbcl__wthdep__dep_003
- mh_p_cbcl__anxdep__dep_001
- mh_p_cbcl__tho__dep_001
- mh_p_cbcl__othpr__dep_001
- mh_p_cbcl__anxdep__dep_002
- mh_p_cbcl__anxdep__dep_003
- mh_p_cbcl__som__dep_001
- mh_p_cbcl__tho__dep_002
- mh_p_cbcl__othpr__dep_002
- mh_p_cbcl__anxdep__dep_004
- mh_p_cbcl__aggr__opp_001
- mh_p_cbcl__aggr__opp_002

- mh_p_cbcl__aggr__opp_003
- mh_p_cbcl__aggr__opp_004
- mh_p_cbcl__aggr__opp_005
- mh_p_cbcl__som__somat_001
- mh_p_cbcl__som__somat_002
- mh_p_cbcl__som__somat_003
- mh_p_cbcl__som__somat_004
- mh_p_cbcl__som__somat_005
- mh_p_cbcl__som__somat_006
- mh_p_cbcl__som__somat_007
- mh_p_cbcl__tho_001
- mh_p_cbcl__anxdep_001
- mh_p_cbcl__tho_007
- mh_p_cbcl__tho_010
- mh_p_cbcl__tho_011
- mh_p_cbcl__attn_002
- mh_p_cbcl__attn_003
- mh_p_cbcl__attn_005
- mh_p_cbcl__wthdep_005
- mh_p_cbcl__soc_004
- mh_p_cbcl__wthdep_003
- mh_p_cbcl__aggr_004
- mh_p_cbcl__aggr_001
- mh_p_cbcl__aggr_002
- mh_p_cbcl__aggr_003
- mh_p_cbcl__aggr_005
- mh_p_cbcl__aggr_006
- mh_p_cbcl__aggr_007
- mh_p_cbcl__anxdep_002
- mh_p_cbcl__attn_001
- mh_p_cbcl__attn_004
- mh_p_cbcl__rule_001
- mh_p_cbcl__rule_006
- mh_p_cbcl__rule_002
- mh_p_cbcl__rule_003
- mh_p_cbcl__rule_004
- mh_p_cbcl__rule_005
- mh_p_cbcl__wthdep_001
- mh_p_cbcl__wthdep_002
- mh_p_cbcl__wthdep_004
- mh_p_cbcl__som_001
- mh_p_cbcl__som_002

  - mh_p_cbcl__othpr_001
  - mh_p_cbcl__othpr_002
  - mh_p_cbcl__othpr_009
  - mh_p_cbcl__othpr_010
  - mh_p_cbcl__othpr_011
  - mh_p_cbcl__othpr_012
  - mh_p_cbcl__othpr_003
  - mh_p_cbcl__othpr_004
  - mh_p_cbcl__othpr_005
  - mh_p_cbcl__othpr_006
  - mh_p_cbcl__othpr_007
  - mh_p_cbcl__othpr_008
  - mh_p_cbcl__soc_001
  - mh_p_cbcl__soc_002
  - mh_p_cbcl__soc_003
  - mh_p_cbcl__soc_005
  - mh_p_cbcl__soc_006
  - mh_p_cbcl__soc_007
  - mh_p_cbcl__soc_008
  - mh_p_cbcl__soc_009
  - mh_p_cbcl__soc_010
  - mh_p_cbcl__tho_002
  - mh_p_cbcl__tho_003
  - mh_p_cbcl__tho_004
  - mh_p_cbcl__tho_005
  - mh_p_cbcl__tho_006
  - mh_p_cbcl__tho_008
  - mh_p_cbcl__tho_009
  - mh_p_cbcl__tho_012
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 8 of 119 items missing

Usage

```
compute_mh_p_cbcl_tscore(
  data,
  data_norm = NULL,
  name = "mh_p_cbcl_tscore",
  col_age = "mh_p_cbcl_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 8,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_cbcl_nm()

Examples

```
## Not run:
compute_mh_p_cbcl_tscore(data) |>
  select(
    any_of(c("mh_p_cbcl_tscore", vars_mh_p_cbcl))
  )

## End(Not run)
```

---

compute_mh_p_ders__attun_nm

Compute "Difficulties in Emotion Regulation Scale [Parent] (Attuned): Number missing"

Description

Computes the summary score mh_p_ders__attun_nm Difficulties in Emotion Regulation Scale [Parent] (Attuned): Number missing

- *Summarized variables:*
  - mh_p_ders__attun_001
  - mh_p_ders__attun_002
  - mh_p_ders__attun_003

  - mh_p_ders__attun_004
  - mh_p_ders__attun_005
  - mh_p_ders__attun_006

- *Excluded values:*
  - 999
  - 777

Usage

```
compute_mh_p_ders__attun_nm(
  data,
  name = "mh_p_ders__attun_nm",
  exclude = c("999", "777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_ders__attun_mean()

Examples

```
## Not run:
compute_mh_p_ders__attun_nm(data) |>
  select(
    any_of(c("mh_p_ders__attun_nm", vars_mh_p_ders__attun))
  )

## End(Not run)
```

`compute_mh_p_ders__catast_nm`

Compute "Difficulties in Emotion Regulation Scale [Parent] (Catastrophize): Number missing"

Description

Computes the summary score `mh_p_ders__catast_nm` Difficulties in Emotion Regulation Scale [Parent] (Catastrophize): Number missing

- *Summarized variables:*
  - `mh_p_ders__catast_001`
  - `mh_p_ders__catast_002`
  - `mh_p_ders__catast_003`
  - `mh_p_ders__catast_004`
  - `mh_p_ders__catast_005`
  - `mh_p_ders__catast_006`
  - `mh_p_ders__catast_007`
  - `mh_p_ders__catast_008`
  - `mh_p_ders__catast_009`
  - `mh_p_ders__catast_010`
  - `mh_p_ders__catast_011`
  - `mh_p_ders__catast_012`
- *Excluded values:*
  - 999
  - 777

Usage

```
compute_mh_p_ders__catast_nm(
  data,
  name = "mh_p_ders__catast_nm",
  exclude = c("999", "777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_ders__catast_mean()

Examples

```
## Not run:
compute_mh_p_ders__catast_nm(data) |>
  select(
    any_of(c("mh_p_ders__catast_nm", vars_mh_p_ders__catast))
  )

## End(Not run)
```

---

compute_mh_p_ders__distract_nm

Compute "Difficulties in Emotion Regulation Scale [Parent] (Distracted): Number missing"

Description

Computes the summary score mh_p_ders__distract_nm Difficulties in Emotion Regulation Scale [Parent] (Distracted): Number missing

- *Summarized variables:*
  - mh_p_ders__distract_001
  - mh_p_ders__distract_002
  - mh_p_ders__distract_003
  - mh_p_ders__distract_004
- *Excluded values:*
  - 999
  - 777

Usage

```
compute_mh_p_ders__distract_nm(
  data,
  name = "mh_p_ders__distract_nm",
  exclude = c("999", "777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_ders__distract_mean()

Examples

```
## Not run:
compute_mh_p_ders__distract_nm(data) |>
  select(
    any_of(c("mh_p_ders__distract_nm", vars_mh_p_ders__distract))
  )

## End(Not run)
```

---

compute_mh_p_ders__negscnd_nm

Compute "Difficulties in Emotion Regulation Scale [Parent] (Negative Secondary): Number missing"

Description

Computes the summary score mh_p_ders__negscnd_nm Difficulties in Emotion Regulation Scale [Parent] (Negative Secondary): Number missing

- *Summarized variables:*
  - mh_p_ders__negscnd_001
  - mh_p_ders__negscnd_002
  - mh_p_ders__negscnd_003
  - mh_p_ders__negscnd_004
  - mh_p_ders__negscnd_005
  - mh_p_ders__negscnd_006
  - mh_p_ders__negscnd_007
- *Excluded values:*
  - 999
  - 777

Usage

```
compute_mh_p_ders__negscnd_nm(
  data,
  name = "mh_p_ders__negscnd_nm",
  exclude = c("999", "777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_ders__negscnd_mean()

Examples

```
## Not run:
compute_mh_p_ders__negscnd_nm(data) |>
  select(
    any_of(c("mh_p_ders__negscnd_nm", vars_mh_p_ders__negscnd))
  )

## End(Not run)
```

---

compute_mh_p_ders_all *Compute all summary scores for mh_p_ders.*

Description

This function computes all summary scores for the mh_p_ders table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ders_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_p_ders_all(data)

## End(Not run)
```

---

compute_mh_p_eatq__actv_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Activation): Number missing"

Description

Computes the summary score mh_p_eatq__actv_nm Early Adolescent Temperament Questionnaire [Parent] (Activation): Number missing

- *Summarized variables:*
  - mh_p_eatq__actv_001
  - mh_p_eatq__actv_002
  - mh_p_eatq__actv_003
  - mh_p_eatq__actv_004
  - mh_p_eatq__actv_005
  - mh_p_eatq__actv_006
  - mh_p_eatq__actv_007
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__actv_nm(data, name = "mh_p_eatq__actv_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__actv_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__actv_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__actv_nm", vars_mh_p_eatq__actv))
)

## End(Not run)
```

---

compute_mh_p_eatq__affl_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Affiliation): Number missing"

Description

Computes the summary score `mh_p_eatq__affl_nm` Early Adolescent Temperament Questionnaire [Parent] (Affiliation): Number missing

- *Summarized variables:*
  - `mh_p_eatq__affl_001`
  - `mh_p_eatq__affl_002`
  - `mh_p_eatq__affl_003`
  - `mh_p_eatq__affl_004`
  - `mh_p_eatq__affl_005`
  - `mh_p_eatq__affl_006`
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__affl_nm(data, name = "mh_p_eatq__affl_nm", combine = TRUE)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE`, the summary score will be appended to the input data frame. If `FALSE`, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__affl_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__affl_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__affl_nm", vars_mh_p_eatq__affl))
)

## End(Not run)
```

---

compute_mh_p_eatq__aggr_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Aggression): Number missing"

Description

Computes the summary score mh_p_eatq__aggr_nm Early Adolescent Temperament Questionnaire [Parent] (Aggression): Number missing

- *Summarized variables:*
  - mh_p_eatq__aggr_001
  - mh_p_eatq__aggr_002
  - mh_p_eatq__aggr_003
  - mh_p_eatq__aggr_004
  - mh_p_eatq__aggr_005
  - mh_p_eatq__aggr_006
  - mh_p_eatq__aggr_007
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__aggr_nm(data, name = "mh_p_eatq__aggr_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__aggr_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__aggr_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__aggr_nm", vars_mh_p_eatq__aggr))
)

## End(Not run)
```

---

compute_mh_p_eatq__attn_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Attention): Number missing"

Description

Computes the summary score mh_p_eatq__attn_nm Early Adolescent Temperament Questionnaire [Parent] (Attention): Number missing

- *Summarized variables:*
  - mh_p_eatq__attn_001
  - mh_p_eatq__attn_002
  - mh_p_eatq__attn_003
  - mh_p_eatq__attn_004
  - mh_p_eatq__attn_005
  - mh_p_eatq__attn_006
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__attn_nm(data, name = "mh_p_eatq__attn_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__attn_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__attn_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__attn_nm", vars_mh_p_eatq__attn))
)

## End(Not run)
```

---

compute_mh_p_eatq__depm_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Depressive Mood): Number missing"

Description

Computes the summary score mh_p_eatq__depm_nm Early Adolescent Temperament Questionnaire [Parent] (Depressive Mood): Number missing

- *Summarized variables:*
  - mh_p_eatq__depm_001
  - mh_p_eatq__depm_002
  - mh_p_eatq__depm_003
  - mh_p_eatq__depm_004
  - mh_p_eatq__depm_005
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__depm_nm(data, name = "mh_p_eatq__depm_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__depm_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__depm_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__depm_nm", vars_mh_p_eatq__depm))
)

## End(Not run)
```

---

compute_mh_p_eatq__fear_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Fear): Number missing"

Description

Computes the summary score mh_p_eatq__fear_nm Early Adolescent Temperament Questionnaire [Parent] (Fear): Number missing

- *Summarized variables:*
  - mh_p_eatq__fear_001
  - mh_p_eatq__fear_002
  - mh_p_eatq__fear_003
  - mh_p_eatq__fear_004
  - mh_p_eatq__fear_005
  - mh_p_eatq__fear_006
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__fear_nm(data, name = "mh_p_eatq__fear_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__fear_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__fear_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__fear_nm", vars_mh_p_eatq__fear))
)

## End(Not run)
```

---

compute_mh_p_eatq__frust_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Frustration): Number missing"

Description

Computes the summary score mh_p_eatq__frust_nm Early Adolescent Temperament Questionnaire [Parent] (Frustration): Number missing

- *Summarized variables:*
  - mh_p_eatq__frust_001
  - mh_p_eatq__frust_002
  - mh_p_eatq__frust_003
  - mh_p_eatq__frust_004
  - mh_p_eatq__frust_005
  - mh_p_eatq__frust_006
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__frust_nm(data, name = "mh_p_eatq__frust_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__frust_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__frust_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__frust_nm", vars_mh_p_eatq__frust))
)

## End(Not run)
```

---

compute_mh_p_eatq__inhib_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Inhibition): Number missing"

Description

Computes the summary score mh_p_eatq__inhib_nm Early Adolescent Temperament Questionnaire [Parent] (Inhibition): Number missing

- *Summarized variables:*
  - mh_p_eatq__inhib_001
  - mh_p_eatq__inhib_002
  - mh_p_eatq__inhib_003
  - mh_p_eatq__inhib_004
  - mh_p_eatq__inhib_005
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__inhib_nm(data, name = "mh_p_eatq__inhib_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__inhib_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__inhib_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__inhib_nm", vars_mh_p_eatq__inhib))
)

## End(Not run)
```

---

compute_mh_p_eatq__shy_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Shyness): Number missing"

Description

Computes the summary score mh_p_eatq__shy_nm Early Adolescent Temperament Questionnaire [Parent] (Shyness): Number missing

- *Summarized variables:*
  - mh_p_eatq__shy_001
  - mh_p_eatq__shy_002
  - mh_p_eatq__shy_003
  - mh_p_eatq__shy_004
  - mh_p_eatq__shy_005
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__shy_nm(data, name = "mh_p_eatq__shy_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__shy_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__shy_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__shy_nm", vars_mh_p_eatq__shy))
)

## End(Not run)
```

---

compute_mh_p_eatq__ss__efcon_mean

Compute "Early Adolescent Temperament Questionnaire [Parent] (Super scale - Effortful control: Combines attention, inhibition, and activation scales): Mean"

Description

Computes the summary score mh_p_eatq__ss__efcon_mean Early Adolescent Temperament Questionnaire [Parent] (Super scale - Effortful control: Combines attention, inhibition, and activation scales): Mean

- *Summarized variables:*
  - mh_p_eatq__attn_mean
  - mh_p_eatq__inhib_mean
  - mh_p_eatq__actv_mean
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__ss__efcon_mean(
  data,
  name = "mh_p_eatq__ss__efcon_mean",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, append the new computed column to the end of original tibble? Default is TRUE.

Details

Effortful Control = Attention, Inhibitory Control, Activation Control

In the super scale calculation, no NA is allowed.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_mh_p_eatq__ss__efcon_mean(data) |>
  select(
    any_of(c(
      "mh_p_eatq__ss__efcon_mean",
    ))
  )

## End(Not run)
```

---

compute_mh_p_eatq__ss__efcon_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Super scale - Effortful control: Combines attention, inhibition, and activation scales): Number missing"

Description

Computes the summary score mh_p_eatq__ss__efcon_nm Early Adolescent Temperament Questionnaire [Parent] (Super scale - Effortful control: Combines attention, inhibition, and activation scales): Number missing

- *Summarized variables:*
  - mh_p_eatq__attn_001
  - mh_p_eatq__attn_002
  - mh_p_eatq__attn_003
  - mh_p_eatq__attn_004
  - mh_p_eatq__attn_005
  - mh_p_eatq__attn_006
  - mh_p_eatq__inhib_001
  - mh_p_eatq__inhib_002
  - mh_p_eatq__inhib_003
  - mh_p_eatq__inhib_004
  - mh_p_eatq__inhib_005
  - mh_p_eatq__actv_001
  - mh_p_eatq__actv_002
  - mh_p_eatq__actv_003
  - mh_p_eatq__actv_004
  - mh_p_eatq__actv_005
  - mh_p_eatq__actv_006
  - mh_p_eatq__actv_007
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__ss__efcon_nm(
  data,
  name = "mh_p_eatq__ss__efcon_nm",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__ss__efcon_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__ss__efcon_nm(data)

## End(Not run)
```

---

compute_mh_p_eatq__ss__negaff_mean

Compute "Early Adolescent Temperament Questionnaire [Parent] (Super scale - Negative Affect: Combines frustration, depressed mood, and aggression scales): Mean"

Description

Computes the summary score mh_p_eatq__ss__negaff_mean Early Adolescent Temperament Questionnaire [Parent] (Super scale - Negative Affect: Combines frustration, depressed mood, and aggression scales): Mean

- *Summarized variables:*
  - mh_p_eatq__frust_mean
  - mh_p_eatq__depm_mean
  - mh_p_eatq__aggr_mean
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__ss__negaff_mean(
  data,
  name = "mh_p_eatq__ss__negaff_mean",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, append the new computed column to the end of original tibble? Default is TRUE.

Details

Negative Affect = Frustration, Depressive Mood, Aggression

In the super scale calculation, no NA is allowed.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data |>
  compute_mh_p_eatq__ss__negaff_mean() |>
  select(
    any_of(c(
      "mh_p_eatq__ss__negaff_mean"
    ))
  )

## End(Not run)
```

---

compute_mh_p_eatq__ss__negaff_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Super scale - Negative Affect: Combines frustration, depressed mood, and aggression scales): Number missing"

Description

Computes the summary score `mh_p_eatq__ss__negaff_nm` Early Adolescent Temperament Questionnaire [Parent] (Super scale - Negative Affect: Combines frustration, depressed mood, and aggression scales): Number missing

- *Summarized variables:*
  - `mh_p_eatq__frust_001`
  - `mh_p_eatq__frust_002`
  - `mh_p_eatq__frust_003`
  - `mh_p_eatq__frust_004`
  - `mh_p_eatq__frust_005`
  - `mh_p_eatq__frust_006`
  - `mh_p_eatq__depm_001`
  - `mh_p_eatq__depm_002`
  - `mh_p_eatq__depm_003`
  - `mh_p_eatq__depm_004`
  - `mh_p_eatq__depm_005`

  - mh_p_eatq__aggr_001
  - mh_p_eatq__aggr_002
  - mh_p_eatq__aggr_003
  - mh_p_eatq__aggr_004
  - mh_p_eatq__aggr_005
  - mh_p_eatq__aggr_006
  - mh_p_eatq__aggr_007

- *Excluded values:* none

Usage

```
compute_mh_p_eatq__ss__negaff_nm(
  data,
  name = "mh_p_eatq__ss__negaff_nm",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__ss__negaff_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__ss__negaff_nm(data)

## End(Not run)
```

compute_mh_p_eatq__ss__surg_mean

Compute "Early Adolescent Temperament Questionnaire [Parent] (Super scale - Surgency: Combines surgency, fear (reverse coded), and shyness (reverse coded) scales): Mean [Validation: No more than 0 missing or declined]"

Description

Computes the summary score mh_p_eatq__ss__surg_mean Early Adolescent Temperament Questionnaire [Parent] (Super scale - Surgency: Combines surgency, fear (reverse coded), and shyness (reverse coded) scales): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_eatq__surg_mean
  - mh_p_eatq__fear_mean (revert)
  - mh_p_eatq__shy_mean (revert)
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__ss__surg_mean(
  data,
  name = "mh_p_eatq__ss__surg_mean",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, append the new computed column to the end of original tibble? Default is TRUE.

Details

Surgency = Surgency, Fear (reverse scored), Shyness (reverse scored)

In the super scale calculation, no NA is allowed.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_mh_p_eatq__ss__surg_mean(data) |>
  select(
    any_of(c(
      "mh_p_eatq__ss__surg_mean"
    ))
  )

## End(Not run)
```

`compute_mh_p_eatq__ss__surg_nm`

Compute "Early Adolescent Temperament Questionnaire [Parent] (Super scale - Surgency: Combines surgency, fear (reverse coded), and shyness (reverse coded) scales): Number missing"

Description

Computes the summary score `mh_p_eatq__ss__surg_nm` Early Adolescent Temperament Questionnaire [Parent] (Super scale - Surgency: Combines surgency, fear (reverse coded), and shyness (reverse coded) scales): Number missing

- *Summarized variables:*
  - `mh_p_eatq__surg_001`
  - `mh_p_eatq__surg_002`
  - `mh_p_eatq__surg_003`
  - `mh_p_eatq__surg_004`
  - `mh_p_eatq__surg_005`
  - `mh_p_eatq__surg_006`
  - `mh_p_eatq__surg_007`
  - `mh_p_eatq__surg_008`
  - `mh_p_eatq__surg_009`
  - `mh_p_eatq__fear_001`
  - `mh_p_eatq__fear_002`
  - `mh_p_eatq__fear_003`
  - `mh_p_eatq__fear_004`
  - `mh_p_eatq__fear_005`
  - `mh_p_eatq__fear_006`
  - `mh_p_eatq__shy_001`
  - `mh_p_eatq__shy_002`
  - `mh_p_eatq__shy_003`
  - `mh_p_eatq__shy_004`
  - `mh_p_eatq__shy_005`
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__ss__surg_nm(
  data,
  name = "mh_p_eatq__ss__surg_nm",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__ss__surg_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__ss__surg_nm(data)

## End(Not run)
```

---

compute_mh_p_eatq__surg_nm

Compute "Early Adolescent Temperament Questionnaire [Parent] (Surgency): Number missing"

Description

Computes the summary score mh_p_eatq__surg_nm Early Adolescent Temperament Questionnaire [Parent] (Surgency): Number missing

- *Summarized variables:*
  - mh_p_eatq__surg_001
  - mh_p_eatq__surg_002
  - mh_p_eatq__surg_003
  - mh_p_eatq__surg_004
  - mh_p_eatq__surg_005

  - mh_p_eatq__surg_006
  - mh_p_eatq__surg_007
  - mh_p_eatq__surg_008
  - mh_p_eatq__surg_009
- *Excluded values:* none

Usage

```
compute_mh_p_eatq__surg_nm(data, name = "mh_p_eatq__surg_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_p_eatq__surg_mean()

Examples

```
## Not run:
data <- compute_mh_p_eatq__surg_nm(data)
select(
  data,
  any_of(c("mh_p_eatq__surg_nm", vars_mh_p_eatq__surg))
)

## End(Not run)
```

---

compute_mh_p_eatq_all *Compute all the EATQ variables*

Description

This super function computes all scores in EATQ using all the **default** arguments.

Usage

```
compute_mh_p_eatq_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Details

Make sure the data is the full set of all variables from EATQ

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_p_eatq_all(data)

## End(Not run)
```

---

compute_mh_p_famhx_all

Compute all the mh_p_famhx *summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_mh_p_famhx_all(data)
```

Arguments

data	tbl. Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_p_famhx_all(data)

## End(Not run)
```

compute_mh_p_gbi_all *Compute all summary scores for mh_p_gbi.*

Description

This function computes all summary scores for the mh_p_gbi table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_gbi_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_p_gbi_all(data)

## End(Not run)
```

compute_mh_p_gbi_sum *Compute "Parent General Behavior Inventory [Parent]: Sum"*

Description

Computes the summary score mh_p_gbi_sum Parent General Behavior Inventory [Parent]: Sum

- *Summarized variables:*
  - mh_p_gbi_001
  - mh_p_gbi_002
  - mh_p_gbi_003
  - mh_p_gbi_004
  - mh_p_gbi_005
  - mh_p_gbi_006
  - mh_p_gbi_007
  - mh_p_gbi_008
  - mh_p_gbi_009
  - mh_p_gbi_010
- *Excluded values:* none
- *Validation criterion:* none of 10 items missing

Usage

```
compute_mh_p_gbi_sum(
  data,
  name = "mh_p_gbi_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_gbi_nm()

Examples

```
## Not run:
compute_mh_p_gbi_sum(data) |>
  select(
    any_of(c("mh_p_gbi_sum", vars_mh_p_gbi))
  )

## End(Not run)
```

---

compute_mh_p_ksads__adhd_all

Compute all summary scores for mh_p_ksads__adhd

Description

This function computes all summary scores for the mh_p_ksads__adhd table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__adhd_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__agor_all`
Compute all summary scores for mh_p_ksads__agor

Description

This function computes all summary scores for the mh_p_ksads__agor table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__agor_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__asd_all`
Compute all summary scores for mh_p_ksads__asd

Description

This function computes all summary scores for the mh_p_ksads__asd table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__asd_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

---

compute_mh_p_ksads__bpd_all

Compute all summary scores for mh_p_ksads__bpd

Description

This function computes all summary scores for the mh_p_ksads__bpd table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__bpd_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

---

compute_mh_p_ksads__cond_all

Compute all summary scores for mh_p_ksads__cond

Description

This function computes all summary scores for the mh_p_ksads__cond table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__cond_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__dep_all`

Compute all summary scores for mh_p_ksads__dep

Description

This function computes all summary scores for the mh_p_ksads__dep table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__dep_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__dmdd_all`

Compute all summary scores for mh_p_ksads__dep

Description

This function computes all summary scores for the mh_p_ksads__dep table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__dmdd_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_p_ksads__ed_all

Compute all summary scores for mh_p_ksads__ed

Description

This function computes all summary scores for the mh_p_ksads__ed table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__ed_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_p_ksads__gad_all

Compute all summary scores for mh_p_ksads__gad

Description

This function computes all summary scores for the mh_p_ksads__gad table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__gad_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__hom_all`

Compute all summary scores for mh_p_ksads__hom

Description

This function computes all summary scores for the mh_p_ksads__hom table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__hom_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__ocd_all`

Compute all summary scores for mh_p_ksads__ocd

Description

This function computes all summary scores for the mh_p_ksads__ocd table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__ocd_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_p_ksads__odd_all

Compute all summary scores for mh_p_ksads__odd

Description

This function computes all summary scores for the mh_p_ksads__odd table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__odd_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_p_ksads__panic_all

Compute all summary scores for mh_p_ksads__panic

Description

This function computes all summary scores for the mh_p_ksads__panic table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__panic_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__phobia_all`
Compute all summary scores for mh_p_ksads__phobia

Description

This function computes all summary scores for the mh_p_ksads__phobia table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__phobia_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__psych_all`
Compute all summary scores for mh_p_ksads__psych

Description

This function computes all summary scores for the mh_p_ksads__psych table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__psych_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_p_ksads__ptsd_all

Compute all summary scores for mh_p_ksads__ptsd

Description

This function computes all summary scores for the mh_p_ksads__ptsd table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__ptsd_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_p_ksads__sepanx_all

Compute all summary scores for mh_p_ksads__sepanx

Description

This function computes all summary scores for the mh_p_ksads__sepanx table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__sepanx_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__sleep_all`

Compute all summary scores for mh_p_ksads__sleep

Description

This function computes all summary scores for the mh_p_ksads__sleep table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__sleep_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ksads__socanx_all`

Compute all summary scores for mh_p_ksads__socanx

Description

This function computes all summary scores for the mh_p_ksads__socanx table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__socanx_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_p_ksads__suic_all

Compute all summary scores for mh_p_ksads__suic

Description

This function computes all summary scores for the mh_p_ksads__suic table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__suic_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_p_ksads__tic_all

Compute all summary scores for mh_p_ksads__tic

Description

This function computes all summary scores for the mh_p_ksads__tic table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ksads__tic_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_p_ple__exp__bad_count`
Compute "Life Events [Parent] (Experience Bad Events): Count"

Description

Computes the summary score `mh_p_ple__exp__bad_count` Life Events [Parent] (Experience Bad Events): Count

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__bad_count(
  data,
  name = "mh_p_ple__exp__bad_count",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__exp__bad_count__v01

Compute "Life Events [Parent] (Experience Bad Events): Count - Version 1 (Year 3)"

Description

Computes the summary score mh_p_ple__exp__bad_count__v01 Life Events [Parent] (Experience Bad Events): Count - Version 1 (Year 3)

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011

  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016
  - mh_p_ple__exp_017
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_020
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_025
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__bad_count__v01(
  data,
  name = "mh_p_ple__exp__bad_count__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__exp__bad_count__v02`
Compute "Life Events [Parent] (Experience Bad Events): Count - Version 2 (Year 4 and Year 5)"

Description

Computes the summary score `mh_p_ple__exp__bad_count__v02` Life Events [Parent] (Experience Bad Events): Count - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
  - `mh_p_ple__exp_026`
  - `mh_p_ple__exp_027`
  - `mh_p_ple__exp_028`

  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
  - mh_p_ple__exp_032

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__bad_count__v02(
  data,
  name = "mh_p_ple__exp__bad_count__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__exp__bad_count__v03

Compute "Life Events [Parent] (Experience Bad Events): Count - Version 3 (Year 6)"

Description

Computes the summary score `mh_p_ple__exp__bad_count__v03` Life Events [Parent] (Experience Bad Events): Count - Version 3 (Year 6)

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
  - `mh_p_ple__exp_026`
  - `mh_p_ple__exp_027`
  - `mh_p_ple__exp_028`
  - `mh_p_ple__exp_029`
  - `mh_p_ple__exp_030`
  - `mh_p_ple__exp_031`
  - `mh_p_ple__exp_032`
  - `mh_p_ple__exp_033`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__bad_count__v03(
  data,
  name = "mh_p_ple__exp__bad_count__v03",
  events = "ses-06A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__exp__bad_count__v04

Compute "Life Events [Parent] (Experience Bad Events): Count - Version 4 (Starting at Year 7)"

Description

Computes the summary score mh_p_ple__exp__bad_count__v04 Life Events [Parent] (Experience Bad Events): Count - Version 4 (Starting at Year 7)

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015

  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_032
  - mh_p_ple__exp_033
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__bad_count__v04(
  data,
  name = "mh_p_ple__exp__bad_count__v04",
  events = "ses-07A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__exp__good_count`
Compute "Life Events [Parent] (Experience Good Events): Count"

Description

Computes the summary score `mh_p_ple__exp__good_count` Life Events [Parent] (Experience Good Events): Count

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__good_count(
  data,
  name = "mh_p_ple__exp__good_count",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__exp__good_count__v01

Compute "Life Events [Parent] (Experience Good Events): Count - Version 1 (Year 3)"

Description

Computes the summary score mh_p_ple__exp__good_count__v01 Life Events [Parent] (Experience Good Events): Count - Version 1 (Year 3)

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011

  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016
  - mh_p_ple__exp_017
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_020
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_025
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__good_count__v01(
  data,
  name = "mh_p_ple__exp__good_count__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__exp__good_count__v02`
Compute "Life Events [Parent] (Experience Good Events): Count - Version 2 (Year 4 and Year 5)"

Description

Computes the summary score `mh_p_ple__exp__good_count__v02` Life Events [Parent] (Experience Good Events): Count - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
  - `mh_p_ple__exp_026`
  - `mh_p_ple__exp_027`
  - `mh_p_ple__exp_028`

  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
  - mh_p_ple__exp_032

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__good_count__v02(
  data,
  name = "mh_p_ple__exp__good_count__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__exp__good_count__v03

Compute "Life Events [Parent] (Experience Good Events): Count - Version 3 (Year 6)"

Description

Computes the summary score `mh_p_ple__exp__good_count__v03` Life Events [Parent] (Experience Good Events): Count - Version 3 (Year 6)

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
  - `mh_p_ple__exp_026`
  - `mh_p_ple__exp_027`
  - `mh_p_ple__exp_028`
  - `mh_p_ple__exp_029`
  - `mh_p_ple__exp_030`
  - `mh_p_ple__exp_031`
  - `mh_p_ple__exp_032`
  - `mh_p_ple__exp_033`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__good_count__v03(
  data,
  name = "mh_p_ple__exp__good_count__v03",
  events = "ses-06A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__exp__good_count__v04

Compute "Life Events [Parent] (Experience Good Events): Count - Version 4 (Starting at Year 7)"

Description

Computes the summary score mh_p_ple__exp__good_count__v04 Life Events [Parent] (Experience Good Events): Count - Version 4 (Starting at Year 7)

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015

  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_032
  - mh_p_ple__exp_033
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp__good_count__v04(
  data,
  name = "mh_p_ple__exp__good_count__v04",
  events = "ses-07A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

compute_mh_p_ple__exp_nm
Compute "Life Events [Parent] (Experience): Number missing"

Description

Computes the summary score mh_p_ple__exp_nm Life Events [Parent] (Experience): Number missing

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016
  - mh_p_ple__exp_017
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_020
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_025
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp_nm(data, name = "mh_p_ple__exp_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__exp_nm__v01

Compute "Life Events [Parent] (Experience): Number missing - Version 1 (Year 3)"

Description

Computes the summary score mh_p_ple__exp_nm__v01 Life Events [Parent] (Experience): Number missing - Version 1 (Year 3)

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016
  - mh_p_ple__exp_017
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_020
  - mh_p_ple__exp_021

  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_025
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp_nm__v01(
  data,
  name = "mh_p_ple__exp_nm__v01",
  events = "ses-03A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_mh_p_ple__exp_nm__v02 *Compute "Life Events [Parent] (Experience): Number missing - Version 2 (Year 4 and Year 5)"*

Description

Computes the summary score mh_p_ple__exp_nm__v02 Life Events [Parent] (Experience): Number missing - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016
  - mh_p_ple__exp_017
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_020
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_025
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031

  - mh_p_ple__exp_032
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp_nm__v02(
  data,
  name = "mh_p_ple__exp_nm__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__exp_nm__v03

Compute "Life Events [Parent] (Experience): Number missing - Version 3 (Year 6)"

Description

Computes the summary score mh_p_ple__exp_nm__v03 Life Events [Parent] (Experience): Number missing - Version 3 (Year 6)

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006

  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016
  - mh_p_ple__exp_017
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_020
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_025
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
  - mh_p_ple__exp_032
  - mh_p_ple__exp_033
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp_nm__v03(
  data,
  name = "mh_p_ple__exp_nm__v03",
  events = "ses-06A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__exp_nm__v04

Compute "Life Events [Parent] (Experience): Number missing - Version 4 (Starting at Year 7)"

Description

Computes the summary score mh_p_ple__exp_nm__v04 Life Events [Parent] (Experience): Number missing - Version 4 (Starting at Year 7)

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_032

  - mh_p_ple__exp_033
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__exp_nm__v04(
  data,
  name = "mh_p_ple__exp_nm__v04",
  events = "ses-07A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity__bad_mean

Compute "Life Events [Parent] (Severity of Bad Events): Mean [Validation: No more than 5 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__bad_mean Life Events [Parent] (Severity of Bad Events): Mean [Validation: No more than 5 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004

- mh_p_ple__exp_005
- mh_p_ple__exp_006
- mh_p_ple__exp_007
- mh_p_ple__exp_008
- mh_p_ple__exp_009
- mh_p_ple__exp_010
- mh_p_ple__exp_011
- mh_p_ple__exp_012
- mh_p_ple__exp_013
- mh_p_ple__exp_014
- mh_p_ple__exp_015
- mh_p_ple__exp_016
- mh_p_ple__exp_017
- mh_p_ple__exp_018
- mh_p_ple__exp_019
- mh_p_ple__exp_020
- mh_p_ple__exp_021
- mh_p_ple__exp_022
- mh_p_ple__exp_023
- mh_p_ple__exp_024
- mh_p_ple__exp_025
- mh_p_ple__severity_001
- mh_p_ple__severity_002
- mh_p_ple__severity_003
- mh_p_ple__severity_004
- mh_p_ple__severity_005
- mh_p_ple__severity_006
- mh_p_ple__severity_007
- mh_p_ple__severity_008
- mh_p_ple__severity_009
- mh_p_ple__severity_010
- mh_p_ple__severity_011
- mh_p_ple__severity_012
- mh_p_ple__severity_013
- mh_p_ple__severity_014
- mh_p_ple__severity_015
- mh_p_ple__severity_016
- mh_p_ple__severity_017
- mh_p_ple__severity_018
- mh_p_ple__severity_019
- mh_p_ple__severity_020
- mh_p_ple__severity_021

  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025

- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
compute_mh_p_ple__severity__bad_mean(
  data,
  name = "mh_p_ple__severity__bad_mean",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity__bad_mean__v01

Compute "Life Events [Parent] (Severity of Bad Events): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__bad_mean__v01 Life Events [Parent] (Severity of Bad Events): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016
  - mh_p_ple__exp_017
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_020
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_025
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005

  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031

- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
compute_mh_p_ple__severity__bad_mean__v01(
  data,
  name = "mh_p_ple__severity__bad_mean__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__severity__bad_mean__v02`

Compute "Life Events [Parent] (Severity of Bad Events): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity__bad_mean__v02` Life Events [Parent] (Severity of Bad Events): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`

- mh_p_ple__exp_017
- mh_p_ple__exp_018
- mh_p_ple__exp_019
- mh_p_ple__exp_020
- mh_p_ple__exp_021
- mh_p_ple__exp_022
- mh_p_ple__exp_023
- mh_p_ple__exp_024
- mh_p_ple__exp_025
- mh_p_ple__exp_026
- mh_p_ple__exp_027
- mh_p_ple__exp_028
- mh_p_ple__exp_029
- mh_p_ple__exp_030
- mh_p_ple__exp_031
- mh_p_ple__exp_032
- mh_p_ple__severity_001
- mh_p_ple__severity_002
- mh_p_ple__severity_003
- mh_p_ple__severity_004
- mh_p_ple__severity_005
- mh_p_ple__severity_006
- mh_p_ple__severity_007
- mh_p_ple__severity_008
- mh_p_ple__severity_009
- mh_p_ple__severity_010
- mh_p_ple__severity_011
- mh_p_ple__severity_012
- mh_p_ple__severity_013
- mh_p_ple__severity_014
- mh_p_ple__severity_015
- mh_p_ple__severity_016
- mh_p_ple__severity_017
- mh_p_ple__severity_018
- mh_p_ple__severity_019
- mh_p_ple__severity_020
- mh_p_ple__severity_021
- mh_p_ple__severity_022
- mh_p_ple__severity_023
- mh_p_ple__severity_024
- mh_p_ple__severity_025
- mh_p_ple__severity_026

  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 32 items missing

Usage

```
compute_mh_p_ple__severity__bad_mean__v02(
  data,
  name = "mh_p_ple__severity__bad_mean__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__severity__bad_mean__v03`

Compute "Life Events [Parent] (Severity of Bad Events): Mean - Version 3 (Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity__bad_mean__v03` Life Events [Parent] (Severity of Bad Events): Mean - Version 3 (Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
  - `mh_p_ple__exp_026`
  - `mh_p_ple__exp_027`
  - `mh_p_ple__exp_028`
  - `mh_p_ple__exp_029`

  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
  - mh_p_ple__exp_032
  - mh_p_ple__exp_033
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_p_ple__severity__bad_mean__v03(
  data,
  name = "mh_p_ple__severity__bad_mean__v03",
  events = "ses-06A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity__bad_mean__v04

Compute "Life Events [Parent] (Severity of Bad Events): Mean - Version 4 (Starting at Year 7) [Validation: No more than 4 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__bad_mean__v04 Life Events [Parent] (Severity of Bad Events): Mean - Version 4 (Starting at Year 7) [Validation: No more than 4 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013

  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_032
  - mh_p_ple__exp_033
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 4 of 20 items missing

Usage

```
compute_mh_p_ple__severity__bad_mean__v04(
  data,
  name = "mh_p_ple__severity__bad_mean__v04",
  events = "ses-07A",
  combine = TRUE,
  max_na = 4
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 4).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity__bad_sum

Compute "Life Events [Parent] (Severity of Bad Events): Sum [Validation: No more than 5 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__bad_sum Life Events [Parent] (Severity of Bad Events): Sum [Validation: No more than 5 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007

- mh_p_ple__exp_008
- mh_p_ple__exp_009
- mh_p_ple__exp_010
- mh_p_ple__exp_011
- mh_p_ple__exp_012
- mh_p_ple__exp_013
- mh_p_ple__exp_014
- mh_p_ple__exp_015
- mh_p_ple__exp_016
- mh_p_ple__exp_017
- mh_p_ple__exp_018
- mh_p_ple__exp_019
- mh_p_ple__exp_020
- mh_p_ple__exp_021
- mh_p_ple__exp_022
- mh_p_ple__exp_023
- mh_p_ple__exp_024
- mh_p_ple__exp_025
- mh_p_ple__severity_001
- mh_p_ple__severity_002
- mh_p_ple__severity_003
- mh_p_ple__severity_004
- mh_p_ple__severity_005
- mh_p_ple__severity_006
- mh_p_ple__severity_007
- mh_p_ple__severity_008
- mh_p_ple__severity_009
- mh_p_ple__severity_010
- mh_p_ple__severity_011
- mh_p_ple__severity_012
- mh_p_ple__severity_013
- mh_p_ple__severity_014
- mh_p_ple__severity_015
- mh_p_ple__severity_016
- mh_p_ple__severity_017
- mh_p_ple__severity_018
- mh_p_ple__severity_019
- mh_p_ple__severity_020
- mh_p_ple__severity_021
- mh_p_ple__severity_022
- mh_p_ple__severity_023
- mh_p_ple__severity_024

    - mh_p_ple__severity_025
  - *Excluded values:*
    - 444
    - 777
    - 999
  - *Validation criterion:* maximally 5 of 25 items missing

Usage

```
compute_mh_p_ple__severity__bad_sum(
  data,
  name = "mh_p_ple__severity__bad_sum",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity__bad_sum__v01

Compute "Life Events [Parent] (Severity of Bad Events): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__bad_sum__v01 Life Events [Parent] (Severity of Bad Events): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

  - *Summarized variables:*
    - mh_p_ple__exp_001
    - mh_p_ple__exp_002

- mh_p_ple__exp_003
- mh_p_ple__exp_004
- mh_p_ple__exp_005
- mh_p_ple__exp_006
- mh_p_ple__exp_007
- mh_p_ple__exp_008
- mh_p_ple__exp_009
- mh_p_ple__exp_010
- mh_p_ple__exp_011
- mh_p_ple__exp_012
- mh_p_ple__exp_013
- mh_p_ple__exp_014
- mh_p_ple__exp_015
- mh_p_ple__exp_016
- mh_p_ple__exp_017
- mh_p_ple__exp_018
- mh_p_ple__exp_019
- mh_p_ple__exp_020
- mh_p_ple__exp_021
- mh_p_ple__exp_022
- mh_p_ple__exp_023
- mh_p_ple__exp_024
- mh_p_ple__exp_025
- mh_p_ple__exp_026
- mh_p_ple__exp_027
- mh_p_ple__exp_028
- mh_p_ple__exp_029
- mh_p_ple__exp_030
- mh_p_ple__exp_031
- mh_p_ple__severity_001
- mh_p_ple__severity_002
- mh_p_ple__severity_003
- mh_p_ple__severity_004
- mh_p_ple__severity_005
- mh_p_ple__severity_006
- mh_p_ple__severity_007
- mh_p_ple__severity_008
- mh_p_ple__severity_009
- mh_p_ple__severity_010
- mh_p_ple__severity_011
- mh_p_ple__severity_012
- mh_p_ple__severity_013

  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
compute_mh_p_ple__severity__bad_sum__v01(
  data,
  name = "mh_p_ple__severity__bad_sum__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__severity__bad_sum__v02`
Compute "Life Events [Parent] (Severity of Bad Events): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity__bad_sum__v02` Life Events [Parent] (Severity of Bad Events): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
  - `mh_p_ple__exp_026`

  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
  - mh_p_ple__exp_032
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 32 items missing

Usage

```
compute_mh_p_ple__severity__bad_sum__v02(
  data,
  name = "mh_p_ple__severity__bad_sum__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity__bad_sum__v03

Compute "Life Events [Parent] (Severity of Bad Events): Sum - Version 3 (Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__bad_sum__v03 Life Events [Parent] (Severity of Bad Events): Sum - Version 3 (Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007

- mh_p_ple__exp_008
- mh_p_ple__exp_009
- mh_p_ple__exp_010
- mh_p_ple__exp_011
- mh_p_ple__exp_012
- mh_p_ple__exp_013
- mh_p_ple__exp_014
- mh_p_ple__exp_015
- mh_p_ple__exp_016
- mh_p_ple__exp_017
- mh_p_ple__exp_018
- mh_p_ple__exp_019
- mh_p_ple__exp_020
- mh_p_ple__exp_021
- mh_p_ple__exp_022
- mh_p_ple__exp_023
- mh_p_ple__exp_024
- mh_p_ple__exp_025
- mh_p_ple__exp_026
- mh_p_ple__exp_027
- mh_p_ple__exp_028
- mh_p_ple__exp_029
- mh_p_ple__exp_030
- mh_p_ple__exp_031
- mh_p_ple__exp_032
- mh_p_ple__exp_033
- mh_p_ple__severity_001
- mh_p_ple__severity_002
- mh_p_ple__severity_003
- mh_p_ple__severity_004
- mh_p_ple__severity_005
- mh_p_ple__severity_006
- mh_p_ple__severity_007
- mh_p_ple__severity_008
- mh_p_ple__severity_009
- mh_p_ple__severity_010
- mh_p_ple__severity_011
- mh_p_ple__severity_012
- mh_p_ple__severity_013
- mh_p_ple__severity_014
- mh_p_ple__severity_015
- mh_p_ple__severity_016

  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_p_ple__severity__bad_sum__v03(
  data,
  name = "mh_p_ple__severity__bad_sum__v03",
  events = "ses-06A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__severity__bad_sum__v04`
Compute "Life Events [Parent] (Severity of Bad Events): Sum - Version 4 (Starting at Year 7) [Validation: No more than 4 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity__bad_sum__v04` Life Events [Parent] (Severity of Bad Events): Sum - Version 4 (Starting at Year 7) [Validation: No more than 4 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_026`
  - `mh_p_ple__exp_027`
  - `mh_p_ple__exp_028`
  - `mh_p_ple__exp_032`
  - `mh_p_ple__exp_033`
  - `mh_p_ple__severity_001`
  - `mh_p_ple__severity_002`
  - `mh_p_ple__severity_007`
  - `mh_p_ple__severity_008`
  - `mh_p_ple__severity_011`
  - `mh_p_ple__severity_012`

  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 4 of 20 items missing

Usage

```
compute_mh_p_ple__severity__bad_sum__v04(
  data,
  name = "mh_p_ple__severity__bad_sum__v04",
  events = "ses-07A",
  combine = TRUE,
  max_na = 4
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 4).

Value

tbl. The input data frame with the summary score appended as a new column.

compute_mh_p_ple__severity__good_mean

Compute "Life Events [Parent] (Severity of Good Events): Mean [Validation: No more than 5 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__good_mean Life Events [Parent] (Severity of Good Events): Mean [Validation: No more than 5 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016
  - mh_p_ple__exp_017
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_020
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_025
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004

  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
compute_mh_p_ple__severity__good_mean(
  data,
  name = "mh_p_ple__severity__good_mean",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__severity__good_mean__v01`
Compute "Life Events [Parent] (Severity of Good Events): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity__good_mean__v01` Life Events [Parent] (Severity of Good Events): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
  - `mh_p_ple__exp_026`

  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_029
  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
compute_mh_p_ple__severity__good_mean__v01(
  data,
  name = "mh_p_ple__severity__good_mean__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity__good_mean__v02

Compute "Life Events [Parent] (Severity of Good Events): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__good_mean__v02 Life Events [Parent] (Severity of Good Events): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007

- mh_p_ple__exp_008
- mh_p_ple__exp_009
- mh_p_ple__exp_010
- mh_p_ple__exp_011
- mh_p_ple__exp_012
- mh_p_ple__exp_013
- mh_p_ple__exp_014
- mh_p_ple__exp_015
- mh_p_ple__exp_016
- mh_p_ple__exp_017
- mh_p_ple__exp_018
- mh_p_ple__exp_019
- mh_p_ple__exp_020
- mh_p_ple__exp_021
- mh_p_ple__exp_022
- mh_p_ple__exp_023
- mh_p_ple__exp_024
- mh_p_ple__exp_025
- mh_p_ple__exp_026
- mh_p_ple__exp_027
- mh_p_ple__exp_028
- mh_p_ple__exp_029
- mh_p_ple__exp_030
- mh_p_ple__exp_031
- mh_p_ple__exp_032
- mh_p_ple__severity_001
- mh_p_ple__severity_002
- mh_p_ple__severity_003
- mh_p_ple__severity_004
- mh_p_ple__severity_005
- mh_p_ple__severity_006
- mh_p_ple__severity_007
- mh_p_ple__severity_008
- mh_p_ple__severity_009
- mh_p_ple__severity_010
- mh_p_ple__severity_011
- mh_p_ple__severity_012
- mh_p_ple__severity_013
- mh_p_ple__severity_014
- mh_p_ple__severity_015
- mh_p_ple__severity_016
- mh_p_ple__severity_017

  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 32 items missing

Usage

```
compute_mh_p_ple__severity__good_mean__v02(
  data,
  name = "mh_p_ple__severity__good_mean__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__severity__good_mean__v03`
Compute "Life Events [Parent] (Severity of Good Events): Mean - Version 3 (Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity__good_mean__v03` Life Events [Parent] (Severity of Good Events): Mean - Version 3 (Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`
  - `mh_p_ple__exp_008`
  - `mh_p_ple__exp_009`
  - `mh_p_ple__exp_010`
  - `mh_p_ple__exp_011`
  - `mh_p_ple__exp_012`
  - `mh_p_ple__exp_013`
  - `mh_p_ple__exp_014`
  - `mh_p_ple__exp_015`
  - `mh_p_ple__exp_016`
  - `mh_p_ple__exp_017`
  - `mh_p_ple__exp_018`
  - `mh_p_ple__exp_019`
  - `mh_p_ple__exp_020`
  - `mh_p_ple__exp_021`
  - `mh_p_ple__exp_022`
  - `mh_p_ple__exp_023`
  - `mh_p_ple__exp_024`
  - `mh_p_ple__exp_025`
  - `mh_p_ple__exp_026`
  - `mh_p_ple__exp_027`
  - `mh_p_ple__exp_028`
  - `mh_p_ple__exp_029`

  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
  - mh_p_ple__exp_032
  - mh_p_ple__exp_033
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_p_ple__severity__good_mean__v03(
  data,
  name = "mh_p_ple__severity__good_mean__v03",
  events = "ses-06A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity__good_mean__v04

Compute "Life Events [Parent] (Severity of Good Events): Mean - Version 4 (Starting at Year 7) [Validation: No more than 4 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__good_mean__v04 Life Events [Parent] (Severity of Good Events): Mean - Version 4 (Starting at Year 7) [Validation: No more than 4 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013

  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_032
  - mh_p_ple__exp_033
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 4 of 20 items missing

Usage

```
compute_mh_p_ple__severity__good_mean__v04(
  data,
  name = "mh_p_ple__severity__good_mean__v04",
  events = "ses-07A",
  combine = TRUE,
  max_na = 4
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 4).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__severity__good_sum`

Compute "Life Events [Parent] (Severity of Good Events): Sum [Validation: No more than 5 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity__good_sum` Life Events [Parent] (Severity of Good Events): Sum [Validation: No more than 5 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__exp_001`
  - `mh_p_ple__exp_002`
  - `mh_p_ple__exp_003`
  - `mh_p_ple__exp_004`
  - `mh_p_ple__exp_005`
  - `mh_p_ple__exp_006`
  - `mh_p_ple__exp_007`

- mh_p_ple__exp_008
- mh_p_ple__exp_009
- mh_p_ple__exp_010
- mh_p_ple__exp_011
- mh_p_ple__exp_012
- mh_p_ple__exp_013
- mh_p_ple__exp_014
- mh_p_ple__exp_015
- mh_p_ple__exp_016
- mh_p_ple__exp_017
- mh_p_ple__exp_018
- mh_p_ple__exp_019
- mh_p_ple__exp_020
- mh_p_ple__exp_021
- mh_p_ple__exp_022
- mh_p_ple__exp_023
- mh_p_ple__exp_024
- mh_p_ple__exp_025
- mh_p_ple__severity_001
- mh_p_ple__severity_002
- mh_p_ple__severity_003
- mh_p_ple__severity_004
- mh_p_ple__severity_005
- mh_p_ple__severity_006
- mh_p_ple__severity_007
- mh_p_ple__severity_008
- mh_p_ple__severity_009
- mh_p_ple__severity_010
- mh_p_ple__severity_011
- mh_p_ple__severity_012
- mh_p_ple__severity_013
- mh_p_ple__severity_014
- mh_p_ple__severity_015
- mh_p_ple__severity_016
- mh_p_ple__severity_017
- mh_p_ple__severity_018
- mh_p_ple__severity_019
- mh_p_ple__severity_020
- mh_p_ple__severity_021
- mh_p_ple__severity_022
- mh_p_ple__severity_023
- mh_p_ple__severity_024

  - mh_p_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
compute_mh_p_ple__severity__good_sum(
  data,
  name = "mh_p_ple__severity__good_sum",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity_mean

Compute "Life Events [Parent] (Severity): Mean [Validation: No more than 5 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity_mean Life Events [Parent] (Severity): Mean [Validation: No more than 5 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004

  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
compute_mh_p_ple__severity_mean(
  data,
  name = "mh_p_ple__severity_mean",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__severity_mean__v01`

Compute "Life Events [Parent] (Severity): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity_mean__v01` Life Events [Parent] (Severity): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__severity_001`
  - `mh_p_ple__severity_002`
  - `mh_p_ple__severity_003`
  - `mh_p_ple__severity_004`
  - `mh_p_ple__severity_005`
  - `mh_p_ple__severity_006`
  - `mh_p_ple__severity_007`
  - `mh_p_ple__severity_008`
  - `mh_p_ple__severity_009`
  - `mh_p_ple__severity_010`
  - `mh_p_ple__severity_011`
  - `mh_p_ple__severity_012`
  - `mh_p_ple__severity_013`
  - `mh_p_ple__severity_014`
  - `mh_p_ple__severity_015`
  - `mh_p_ple__severity_016`
  - `mh_p_ple__severity_017`
  - `mh_p_ple__severity_018`
  - `mh_p_ple__severity_019`
  - `mh_p_ple__severity_020`
  - `mh_p_ple__severity_021`
  - `mh_p_ple__severity_022`
  - `mh_p_ple__severity_023`
  - `mh_p_ple__severity_024`
  - `mh_p_ple__severity_025`
  - `mh_p_ple__severity_026`

  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
compute_mh_p_ple__severity_mean__v01(
  data,
  name = "mh_p_ple__severity_mean__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity_mean__v02

Compute "Life Events [Parent] (Severity): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity_mean__v02` Life Events [Parent] (Severity): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__severity_001`
  - `mh_p_ple__severity_002`
  - `mh_p_ple__severity_003`
  - `mh_p_ple__severity_004`
  - `mh_p_ple__severity_005`
  - `mh_p_ple__severity_006`
  - `mh_p_ple__severity_007`
  - `mh_p_ple__severity_008`
  - `mh_p_ple__severity_009`
  - `mh_p_ple__severity_010`
  - `mh_p_ple__severity_011`
  - `mh_p_ple__severity_012`
  - `mh_p_ple__severity_013`
  - `mh_p_ple__severity_014`
  - `mh_p_ple__severity_015`
  - `mh_p_ple__severity_016`
  - `mh_p_ple__severity_017`
  - `mh_p_ple__severity_018`
  - `mh_p_ple__severity_019`
  - `mh_p_ple__severity_020`
  - `mh_p_ple__severity_021`
  - `mh_p_ple__severity_022`
  - `mh_p_ple__severity_023`
  - `mh_p_ple__severity_024`
  - `mh_p_ple__severity_025`
  - `mh_p_ple__severity_026`
  - `mh_p_ple__severity_027`
  - `mh_p_ple__severity_028`
  - `mh_p_ple__severity_029`
  - `mh_p_ple__severity_030`
  - `mh_p_ple__severity_031`
  - `mh_p_ple__severity_032`
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 32 items missing

Usage

```
compute_mh_p_ple__severity_mean__v02(
  data,
  name = "mh_p_ple__severity_mean__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity_mean__v03

Compute "Life Events [Parent] (Severity): Mean - Version 3 (Year 6) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity_mean__v03 Life Events [Parent] (Severity): Mean - Version 3 (Year 6) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007

  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_p_ple__severity_mean__v03(
  data,
  name = "mh_p_ple__severity_mean__v03",
  events = "ses-06A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity_mean__v04

Compute "Life Events [Parent] (Severity): Mean - Version 4 (Starting at Year 7) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity_mean__v04 Life Events [Parent] (Severity): Mean - Version 4 (Starting at Year 7) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_026

  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 4 of 20 items missing

Usage

```
compute_mh_p_ple__severity_mean__v04(
  data,
  name = "mh_p_ple__severity_mean__v04",
  events = "ses-07A",
  combine = TRUE,
  max_na = 4
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 4).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity_nm

Compute "Life Events [Parent] (Severity): Number missing"

Description

Computes the summary score `mh_p_ple__severity_nm` Life Events [Parent] (Severity): Number missing

- *Summarized variables:*
  - `mh_p_ple__severity_001`
  - `mh_p_ple__severity_002`
  - `mh_p_ple__severity_003`
  - `mh_p_ple__severity_004`
  - `mh_p_ple__severity_005`
  - `mh_p_ple__severity_006`
  - `mh_p_ple__severity_007`
  - `mh_p_ple__severity_008`
  - `mh_p_ple__severity_009`
  - `mh_p_ple__severity_010`
  - `mh_p_ple__severity_011`
  - `mh_p_ple__severity_012`
  - `mh_p_ple__severity_013`
  - `mh_p_ple__severity_014`
  - `mh_p_ple__severity_015`
  - `mh_p_ple__severity_016`
  - `mh_p_ple__severity_017`
  - `mh_p_ple__severity_018`
  - `mh_p_ple__severity_019`
  - `mh_p_ple__severity_020`
  - `mh_p_ple__severity_021`
  - `mh_p_ple__severity_022`
  - `mh_p_ple__severity_023`
  - `mh_p_ple__severity_024`
  - `mh_p_ple__severity_025`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__severity_nm(
  data,
  name = "mh_p_ple__severity_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity_nm__v01

Compute "Life Events [Parent] (Severity): Number missing - Version 1 (Year 3)"

Description

Computes the summary score mh_p_ple__severity_nm__v01 Life Events [Parent] (Severity): Number missing - Version 1 (Year 3)

- *Summarized variables:*
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021

  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__severity_nm__v01(
  data,
  name = "mh_p_ple__severity_nm__v01",
  events = "ses-03A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_p_ple__severity_nm__v02`
Compute "Life Events [Parent] (Severity): Number missing - Version 2 (Year 4 and Year 5)"

Description

Computes the summary score `mh_p_ple__severity_nm__v02` Life Events [Parent] (Severity): Number missing - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - `mh_p_ple__severity_001`
  - `mh_p_ple__severity_002`
  - `mh_p_ple__severity_003`
  - `mh_p_ple__severity_004`
  - `mh_p_ple__severity_005`
  - `mh_p_ple__severity_006`
  - `mh_p_ple__severity_007`
  - `mh_p_ple__severity_008`
  - `mh_p_ple__severity_009`
  - `mh_p_ple__severity_010`
  - `mh_p_ple__severity_011`
  - `mh_p_ple__severity_012`
  - `mh_p_ple__severity_013`
  - `mh_p_ple__severity_014`
  - `mh_p_ple__severity_015`
  - `mh_p_ple__severity_016`
  - `mh_p_ple__severity_017`
  - `mh_p_ple__severity_018`
  - `mh_p_ple__severity_019`
  - `mh_p_ple__severity_020`
  - `mh_p_ple__severity_021`
  - `mh_p_ple__severity_022`
  - `mh_p_ple__severity_023`
  - `mh_p_ple__severity_024`
  - `mh_p_ple__severity_025`
  - `mh_p_ple__severity_026`
  - `mh_p_ple__severity_027`
  - `mh_p_ple__severity_028`
  - `mh_p_ple__severity_029`
  - `mh_p_ple__severity_030`
  - `mh_p_ple__severity_031`

  - mh_p_ple__severity_032
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__severity_nm__v02(
  data,
  name = "mh_p_ple__severity_nm__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity_nm__v03

Compute "Life Events [Parent] (Severity): Number missing - Version 3 (Year 6)"

Description

Computes the summary score mh_p_ple__severity_nm__v03 Life Events [Parent] (Severity): Number missing - Version 3 (Year 6)

- *Summarized variables:*
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006

  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__severity_nm__v03(
  data,
  name = "mh_p_ple__severity_nm__v03",
  events = "ses-06A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple__severity_nm__v04

Compute "Life Events [Parent] (Severity): Number missing - Version 4 (Starting at Year 7)"

Description

Computes the summary score mh_p_ple__severity_nm__v04 Life Events [Parent] (Severity): Number missing - Version 4 (Starting at Year 7)

- *Summarized variables:*
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_032

  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple__severity_nm__v04(
  data,
  name = "mh_p_ple__severity_nm__v04",
  events = "ses-07A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple_all *Compute all summary scores for mh_p_ple*

Description

This function computes all summary scores for the mh_p_ple form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ple_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_p_ple_all(data)

## End(Not run)
```

`compute_mh_p_ple_nm` *Compute "Life Events [Parent] (Events): Number missing"*

Description

Computes the summary score `mh_p_ple_nm` Life Events [Parent] (Events): Number missing

- *Summarized variables:*
  - `mh_p_ple_001`
  - `mh_p_ple_002`
  - `mh_p_ple_003`
  - `mh_p_ple_004`
  - `mh_p_ple_005`
  - `mh_p_ple_006`
  - `mh_p_ple_007`
  - `mh_p_ple_008`
  - `mh_p_ple_009`
  - `mh_p_ple_010`
  - `mh_p_ple_011`
  - `mh_p_ple_012`
  - `mh_p_ple_013`
  - `mh_p_ple_014`
  - `mh_p_ple_015`
  - `mh_p_ple_016`
  - `mh_p_ple_017`
  - `mh_p_ple_018`
  - `mh_p_ple_019`
  - `mh_p_ple_020`
  - `mh_p_ple_021`
  - `mh_p_ple_022`
  - `mh_p_ple_023`
  - `mh_p_ple_024`
  - `mh_p_ple_025`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple_nm(data, name = "mh_p_ple_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple_nm__v01

Compute "Life Events [Parent] (Events): Number missing - Version 1 (Year 3)"

Description

Computes the summary score mh_p_ple_nm__v01 Life Events [Parent] (Events): Number missing - Version 1 (Year 3)

- *Summarized variables:*
  - mh_p_ple_001
  - mh_p_ple_002
  - mh_p_ple_003
  - mh_p_ple_004
  - mh_p_ple_005
  - mh_p_ple_006
  - mh_p_ple_007
  - mh_p_ple_008
  - mh_p_ple_009
  - mh_p_ple_010
  - mh_p_ple_011
  - mh_p_ple_012
  - mh_p_ple_013
  - mh_p_ple_014
  - mh_p_ple_015
  - mh_p_ple_016
  - mh_p_ple_017

  - mh_p_ple_018
  - mh_p_ple_019
  - mh_p_ple_020
  - mh_p_ple_021
  - mh_p_ple_022
  - mh_p_ple_023
  - mh_p_ple_024
  - mh_p_ple_025
  - mh_p_ple_026
  - mh_p_ple_027
  - mh_p_ple_028
  - mh_p_ple_029
  - mh_p_ple_030
  - mh_p_ple_031
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple_nm__v01(
  data,
  name = "mh_p_ple_nm__v01",
  events = "ses-03A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_mh_p_ple_nm__v02

Compute "Life Events [Parent] (Events): Number missing - Version 2 (Year 4 and Year 5)"

Description

Computes the summary score mh_p_ple_nm__v02 Life Events [Parent] (Events): Number missing - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - mh_p_ple_001
  - mh_p_ple_002
  - mh_p_ple_003
  - mh_p_ple_004
  - mh_p_ple_005
  - mh_p_ple_006
  - mh_p_ple_007
  - mh_p_ple_008
  - mh_p_ple_009
  - mh_p_ple_010
  - mh_p_ple_011
  - mh_p_ple_012
  - mh_p_ple_013
  - mh_p_ple_014
  - mh_p_ple_015
  - mh_p_ple_016
  - mh_p_ple_017
  - mh_p_ple_018
  - mh_p_ple_019
  - mh_p_ple_020
  - mh_p_ple_021
  - mh_p_ple_022
  - mh_p_ple_023
  - mh_p_ple_024
  - mh_p_ple_025
  - mh_p_ple_026
  - mh_p_ple_027
  - mh_p_ple_028
  - mh_p_ple_029
  - mh_p_ple_030
  - mh_p_ple_031

  - mh_p_ple_032
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple_nm__v02(
  data,
  name = "mh_p_ple_nm__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple_nm__v03

Compute "Life Events [Parent] (Events): Number missing - Version 3 (Year 6)"

Description

Computes the summary score mh_p_ple_nm__v03 Life Events [Parent] (Events): Number missing - Version 3 (Year 6)

- *Summarized variables:*
  - mh_p_ple_001
  - mh_p_ple_002
  - mh_p_ple_003
  - mh_p_ple_004
  - mh_p_ple_005
  - mh_p_ple_006

  - mh_p_ple_007
  - mh_p_ple_008
  - mh_p_ple_009
  - mh_p_ple_010
  - mh_p_ple_011
  - mh_p_ple_012
  - mh_p_ple_013
  - mh_p_ple_014
  - mh_p_ple_015
  - mh_p_ple_016
  - mh_p_ple_017
  - mh_p_ple_018
  - mh_p_ple_019
  - mh_p_ple_020
  - mh_p_ple_021
  - mh_p_ple_022
  - mh_p_ple_023
  - mh_p_ple_024
  - mh_p_ple_025
  - mh_p_ple_026
  - mh_p_ple_027
  - mh_p_ple_028
  - mh_p_ple_029
  - mh_p_ple_030
  - mh_p_ple_031
  - mh_p_ple_032
  - mh_p_ple_033

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple_nm__v03(
  data,
  name = "mh_p_ple_nm__v03",
  events = "ses-06A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ple_nm__v04

Compute "Life Events [Parent] (Events): Number missing - Version 4 (Starting at Year 7)"

Description

Computes the summary score mh_p_ple_nm__v04 Life Events [Parent] (Events): Number missing - Version 4 (Starting at Year 7)

- *Summarized variables:*
  - mh_p_ple_001
  - mh_p_ple_002
  - mh_p_ple_007
  - mh_p_ple_008
  - mh_p_ple_011
  - mh_p_ple_012
  - mh_p_ple_013
  - mh_p_ple_014
  - mh_p_ple_015
  - mh_p_ple_018
  - mh_p_ple_019
  - mh_p_ple_021
  - mh_p_ple_022
  - mh_p_ple_023
  - mh_p_ple_024
  - mh_p_ple_026
  - mh_p_ple_027
  - mh_p_ple_028
  - mh_p_ple_032

  - mh_p_ple_033
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_p_ple_nm__v04(
  data,
  name = "mh_p_ple_nm__v04",
  events = "ses-07A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_p_ssrs_all *Compute all summary scores for mh_p_ssrs.*

Description

This function computes all summary scores for the mh_p_ssrs table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_p_ssrs_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_p_ssrs_all(data)

## End(Not run)
```

`compute_mh_p_ssrs_sum` *Compute "Short Social Responsiveness Scale [Parent]: Sum"*

Description

Computes the summary score `mh_p_ssrs_sum` Short Social Responsiveness Scale [Parent]: Sum

- *Summarized variables:*
  - `mh_p_ssrs_001`
  - `mh_p_ssrs_002`
  - `mh_p_ssrs_003`
  - `mh_p_ssrs_004`
  - `mh_p_ssrs_005`
  - `mh_p_ssrs_006`
  - `mh_p_ssrs_007`
  - `mh_p_ssrs_008`
  - `mh_p_ssrs_009`
  - `mh_p_ssrs_010`
  - `mh_p_ssrs_011`
- *Excluded values:* none
- *Validation criterion:* none of 11 items missing

Usage

```
compute_mh_p_ssrs_sum(
  data,
  name = "mh_p_ssrs_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.

exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_p_ssrs_nm()

Examples

```
## Not run:
compute_mh_p_ssrs_sum(data) |>
  select(
    any_of(c("mh_p_ssrs_sum", vars_mh_p_ssrs))
  )

## End(Not run)
```

---

compute_mh_t_bpm__attn_sum

Compute "Brief Problem Monitor [Teacher] (Attention): Sum"

Description

Computes the summary score mh_t_bpm__attn_sum Brief Problem Monitor [Teacher] (Attention): Sum

- *Summarized variables:*
  - mh_t_bpm__attn_001
  - mh_t_bpm__attn_002
  - mh_t_bpm__attn_003
  - mh_t_bpm__attn_004
  - mh_t_bpm__attn_005
  - mh_t_bpm__attn_006
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_t_bpm__attn_sum(
  data,
  name = "mh_t_bpm__attn_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_t_bpm__attn_nm()

Examples

```
## Not run:
compute_mh_t_bpm__attn_sum(data) |>
  select(
    any_of(c("mh_t_bpm__attn_sum", vars_mh_t_bpm__attn))
  )

## End(Not run)
```

---

compute_mh_t_bpm__attn_tscore

Compute "Brief Problem Monitor [Teacher] (Attention): T-score"

Description

Computes the summary score `mh_t_bpm__attn_tscore` Brief Problem Monitor [Teacher] (Attention): T-score

- *Summarized variables:*
  - `mh_t_bpm__attn_001`
  - `mh_t_bpm__attn_002`
  - `mh_t_bpm__attn_003`
  - `mh_t_bpm__attn_004`
  - `mh_t_bpm__attn_005`
  - `mh_t_bpm__attn_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_t_bpm__attn_tscore(
  data,
  data_norm = NULL,
  name = "mh_t_bpm__attn_tscore",
  col_age = "mh_t_bpm_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.
`col_sex`	character, name of the sex column. see `ss_tscore()`.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

compute_mh_t_bpm__attn_nm()

Examples

```
## Not run:
compute_mh_t_bpm__attn_tscore(data) |>
  select(
    any_of(c("mh_t_bpm__attn_tscore", vars_mh_t_bpm__attn))
  )

## End(Not run)
```

---

compute_mh_t_bpm__ext_sum

Compute "Brief Problem Monitor [Teacher] (Externalizing): Sum"

Description

Computes the summary score `mh_t_bpm__ext_sum` Brief Problem Monitor [Teacher] (Externalizing): Sum

- *Summarized variables:*
  - `mh_t_bpm__ext_001`
  - `mh_t_bpm__ext_002`
  - `mh_t_bpm__ext_003`
  - `mh_t_bpm__ext_004`
  - `mh_t_bpm__ext_005`
  - `mh_t_bpm__ext_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_t_bpm__ext_sum(
  data,
  name = "mh_t_bpm__ext_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_t_bpm__ext_nm()

Examples

```
## Not run:
compute_mh_t_bpm__ext_sum(data) |>
  select(
    any_of(c("mh_t_bpm__ext_sum", vars_mh_t_bpm__ext))
  )

## End(Not run)
```

---

compute_mh_t_bpm__ext_tscore

Compute "Brief Problem Monitor [Teacher] (Externalizing): T-score"

Description

Computes the summary score mh_t_bpm__ext_tscore Brief Problem Monitor [Teacher] (Externalizing): T-score

- *Summarized variables:*
  - mh_t_bpm__ext_001
  - mh_t_bpm__ext_002
  - mh_t_bpm__ext_003
  - mh_t_bpm__ext_004
  - mh_t_bpm__ext_005
  - mh_t_bpm__ext_006
- *Excluded values:*

  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_t_bpm__ext_tscore(
  data,
  data_norm = NULL,
  name = "mh_t_bpm__ext_tscore",
  col_age = "mh_t_bpm_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_t_bpm__ext_nm()

Examples

```
## Not run:
compute_mh_t_bpm__ext_tscore(data) |>
  select(
    any_of(c("mh_t_bpm__ext_tscore", vars_mh_t_bpm__ext))
  )

## End(Not run)
```

`compute_mh_t_bpm__int_sum`
Compute "Brief Problem Monitor [Teacher] (Internalizing): Sum"

Description

Computes the summary score `mh_t_bpm__int_sum` Brief Problem Monitor [Teacher] (Internalizing): Sum

- *Summarized variables:*
  - `mh_t_bpm__int_001`
  - `mh_t_bpm__int_002`
  - `mh_t_bpm__int_003`
  - `mh_t_bpm__int_004`
  - `mh_t_bpm__int_005`
  - `mh_t_bpm__int_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_t_bpm__int_sum(
  data,
  name = "mh_t_bpm__int_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

compute_mh_t_bpm__int_nm()

Examples

```
## Not run:
compute_mh_t_bpm__int_sum(data) |>
  select(
    any_of(c("mh_t_bpm__int_sum", vars_mh_t_bpm__int))
  )

## End(Not run)
```

---

compute_mh_t_bpm__int_tscore

Compute "Brief Problem Monitor [Teacher] (Internalizing): T-score"

Description

Computes the summary score `mh_t_bpm__int_tscore` Brief Problem Monitor [Teacher] (Internalizing): T-score

- *Summarized variables:*
  - `mh_t_bpm__int_001`
  - `mh_t_bpm__int_002`
  - `mh_t_bpm__int_003`
  - `mh_t_bpm__int_004`
  - `mh_t_bpm__int_005`
  - `mh_t_bpm__int_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_t_bpm__int_tscore(
  data,
  data_norm = NULL,
  name = "mh_t_bpm__int_tscore",
  col_age = "mh_t_bpm_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_t_bpm__int_nm()

Examples

```
## Not run:
compute_mh_t_bpm__int_tscore(data) |>
  select(
    any_of(c("mh_t_bpm__int_tscore", vars_mh_t_bpm__int))
  )

## End(Not run)
```

---

compute_mh_t_bpm_all *Compute all summary scores for mh_t_bpm.*

Description

This function computes all summary scores for the mh_t_bpm form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_t_bpm_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_t_bpm_all(data)

## End(Not run)
```

`compute_mh_t_bpm_sum` *Compute "Brief Problem Monitor [Teacher]: Sum"*

Description

Computes the summary score `mh_t_bpm_sum` Brief Problem Monitor [Teacher]: Sum

- *Summarized variables:*
  - `mh_t_bpm__attn_001`
  - `mh_t_bpm__attn_002`
  - `mh_t_bpm__attn_003`
  - `mh_t_bpm__attn_004`
  - `mh_t_bpm__attn_005`
  - `mh_t_bpm__attn_006`
  - `mh_t_bpm__ext_001`
  - `mh_t_bpm__ext_002`
  - `mh_t_bpm__ext_003`
  - `mh_t_bpm__ext_004`
  - `mh_t_bpm__ext_005`
  - `mh_t_bpm__ext_006`
  - `mh_t_bpm__int_001`
  - `mh_t_bpm__int_002`
  - `mh_t_bpm__int_003`
  - `mh_t_bpm__int_004`
  - `mh_t_bpm__int_005`
  - `mh_t_bpm__int_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 18 items missing

Usage

```
compute_mh_t_bpm_sum(
  data,
  name = "mh_t_bpm_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_t_bpm_nm()

Examples

```
## Not run:
compute_mh_t_bpm_sum(data) |>
  select(
    any_of(c("mh_t_bpm_sum", vars_mh_t_bpm))
  )

## End(Not run)
```

---

compute_mh_t_bpm_tscore

Compute "Brief Problem Monitor [Teacher]: T-score"

Description

Computes the summary score `mh_t_bpm_tscore` Brief Problem Monitor [Teacher]: T-score

- *Summarized variables:*
  - `mh_t_bpm__attn_001`
  - `mh_t_bpm__attn_002`
  - `mh_t_bpm__attn_003`
  - `mh_t_bpm__attn_004`
  - `mh_t_bpm__attn_005`
  - `mh_t_bpm__attn_006`
  - `mh_t_bpm__ext_001`
  - `mh_t_bpm__ext_002`
  - `mh_t_bpm__ext_003`
  - `mh_t_bpm__ext_004`
  - `mh_t_bpm__ext_005`
  - `mh_t_bpm__ext_006`
  - `mh_t_bpm__int_001`
  - `mh_t_bpm__int_002`
  - `mh_t_bpm__int_003`
  - `mh_t_bpm__int_004`
  - `mh_t_bpm__int_005`
  - `mh_t_bpm__int_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 18 items missing

Usage

```
compute_mh_t_bpm_tscore(
  data,
  data_norm = NULL,
  name = "mh_t_bpm_tscore",
  col_age = "mh_t_bpm_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.

name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_t_bpm_nm()

Examples

```
## Not run:
compute_mh_t_bpm_tscore(data) |>
  select(
    any_of(c("mh_t_bpm_tscore", vars_mh_t_bpm))
  )

## End(Not run)
```

---

compute_mh_y_bisbas__bas__dr_sum

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Drive): Sum"

Description

Computes the summary score mh_y_bisbas__bas__dr_sum The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Drive): Sum

- *Summarized variables:*
  - mh_y_bisbas__bas__dr_001
  - mh_y_bisbas__bas__dr_002
  - mh_y_bisbas__bas__dr_003
  - mh_y_bisbas__bas__dr_004
- *Excluded values:* none
- *Validation criterion:* none of 4 items missing

Usage

```
compute_mh_y_bisbas__bas__dr_sum(
  data,
  name = "mh_y_bisbas__bas__dr_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bisbas__bas__dr_nm()

Examples

```
## Not run:
compute_mh_y_bisbas__bas__dr_sum(data) |>
  select(
    any_of(c("mh_y_bisbas__bas__dr_sum", vars_mh_y_bisbas__bas__dr))
  )

## End(Not run)
```

---

compute_mh_y_bisbas__bas__fs_sum

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Fun Seeking): Sum"

Description

Computes the summary score mh_y_bisbas__bas__fs_sum The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Fun Seeking): Sum

- *Summarized variables:*
  - mh_y_bisbas__bas__fs_001
  - mh_y_bisbas__bas__fs_002
  - mh_y_bisbas__bas__fs_003
  - mh_y_bisbas__bas__fs_004
- *Excluded values:* none
- *Validation criterion:* none of 4 items missing

Usage

```
compute_mh_y_bisbas__bas__fs_sum(
  data,
  name = "mh_y_bisbas__bas__fs_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bisbas__bas__fs_nm()

Examples

```
## Not run:
compute_mh_y_bisbas__bas__fs_sum(data) |>
  select(
    any_of(c("mh_y_bisbas__bas__fs_sum", vars_mh_y_bisbas__bas__fs))
```

```
  )

## End(Not run)
```

`compute_mh_y_bisbas__bas__rr_sum`
Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Reward Responsiveness): Sum"

Description

Computes the summary score `mh_y_bisbas__bas__rr_sum` The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Reward Responsiveness): Sum

- *Summarized variables:*
  - `mh_y_bisbas__bas__rr_001`
  - `mh_y_bisbas__bas__rr_002`
  - `mh_y_bisbas__bas__rr_003`
  - `mh_y_bisbas__bas__rr_004`
  - `mh_y_bisbas__bas__rr_005`
- *Excluded values:* none
- *Validation criterion:* none of 5 items missing

Usage

```
compute_mh_y_bisbas__bas__rr_sum(
  data,
  name = "mh_y_bisbas__bas__rr_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bisbas__bas__rr_nm()

Examples

```
## Not run:
compute_mh_y_bisbas__bas__rr_sum(data) |>
  select(
    any_of(c("mh_y_bisbas__bas__rr_sum", vars_mh_y_bisbas__bas__rr))
  )

## End(Not run)
```

---

compute_mh_y_bisbas__bas__rr_sum__v01

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] ((BAS Reward Responsiveness (modified)): Sum"

Description

Computes the summary score mh_y_bisbas__bas__rr_sum__v01 The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] ((BAS Reward Responsiveness (modified)): Sum

- *Summarized variables:*
  - mh_y_bisbas__bas__rr_001
  - mh_y_bisbas__bas__rr_002
  - mh_y_bisbas__bas__rr_004
  - mh_y_bisbas__bas__rr_005
- *Excluded values:* none
- *Validation criterion:* none of 4 items missing

Usage

```
compute_mh_y_bisbas__bas__rr_sum__v01(
  data,
  name = "mh_y_bisbas__bas__rr_sum__v01",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bisbas__bas__rr_nm__v01()

Examples

```
## Not run:
compute_mh_y_bisbas__bas__rr_sum__v01(data) |>
  select(
    any_of(c("mh_y_bisbas__bas__rr_sum__v01", vars_mh_y_bisbas__bas__rr__v01))
  )

## End(Not run)
```

---

compute_mh_y_bisbas__bis_sum

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BIS): Sum"

Description

Computes the summary score mh_y_bisbas__bis_sum The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BIS): Sum

- *Summarized variables:*
  - mh_y_bisbas__bis_001
  - mh_y_bisbas__bis_002
  - mh_y_bisbas__bis_003
  - mh_y_bisbas__bis_004
  - mh_y_bisbas__bis_005
  - mh_y_bisbas__bis_006
  - mh_y_bisbas__bis_007
- *Excluded values:* none
- *Validation criterion:* none of 7 items missing

Usage

```
compute_mh_y_bisbas__bis_sum(
  data,
  name = "mh_y_bisbas__bis_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bisbas__bis_nm()

Examples

```
## Not run:
compute_mh_y_bisbas__bis_sum(data) |>
  select(
    any_of(c("mh_y_bisbas__bis_sum", vars_mh_y_bisbas__bis))
  )

## End(Not run)
```

---

compute_mh_y_bisbas__bis_sum__v01

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BIS (modified)): Sum"

Description

Computes the summary score mh_y_bisbas__bis_sum__v01 The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BIS (modified)): Sum

- *Summarized variables:*
  - mh_y_bisbas__bis_002
  - mh_y_bisbas__bis_003
  - mh_y_bisbas__bis_004
  - mh_y_bisbas__bis_006
- *Excluded values:* none
- *Validation criterion:* none of 4 items missing

Usage

```
compute_mh_y_bisbas__bis_sum__v01(
  data,
  name = "mh_y_bisbas__bis_sum__v01",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bisbas__bis_nm__v01()

Examples

```
## Not run:
compute_mh_y_bisbas__bis_sum__v01(data) |>
  select(
    any_of(c("mh_y_bisbas__bis_sum__v01", vars_mh_y_bisbas__bis__v01))
```

```
  )

## End(Not run)
```

`compute_mh_y_bisbas_all`

Compute all summary scores for mh_y_bisbas.

Description

This function computes all summary scores for the mh_y_bisbas table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_bisbas_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_bisbas_all(data)

## End(Not run)
```

`compute_mh_y_bpm__attn_sum`

Compute "Brief Problem Monitor [Youth] (Attention): Sum"

Description

Computes the summary score `mh_y_bpm__attn_sum` Brief Problem Monitor [Youth] (Attention): Sum

- *Summarized variables:*
  - `mh_y_bpm__attn_001`
  - `mh_y_bpm__attn_002`
  - `mh_y_bpm__attn_003`
  - `mh_y_bpm__attn_004`

  - mh_y_bpm__attn_005
  - mh_y_bpm__attn_006
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_y_bpm__attn_sum(
  data,
  name = "mh_y_bpm__attn_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bpm__attn_nm()

Examples

```
## Not run:
compute_mh_y_bpm__attn_sum(data) |>
  select(
    any_of(c("mh_y_bpm__attn_sum", vars_mh_y_bpm__attn))
  )

## End(Not run)
```

`compute_mh_y_bpm__attn_tscore`
Compute "Brief Problem Monitor [Youth] (Attention): T-score"

Description

Computes the summary score `mh_y_bpm__attn_tscore` Brief Problem Monitor [Youth] (Attention): T-score

- *Summarized variables:*
  - `mh_y_bpm__attn_001`
  - `mh_y_bpm__attn_002`
  - `mh_y_bpm__attn_003`
  - `mh_y_bpm__attn_004`
  - `mh_y_bpm__attn_005`
  - `mh_y_bpm__attn_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_y_bpm__attn_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_bpm__attn_tscore",
  col_age = "mh_y_bpm_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.
`col_sex`	character, name of the sex column. see `ss_tscore()`.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.

exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bpm__attn_nm()

Examples

```
## Not run:
compute_mh_y_bpm__attn_tscore(data) |>
  select(
    any_of(c("mh_y_bpm__attn_tscore", vars_mh_y_bpm__attn))
  )

## End(Not run)
```

---

compute_mh_y_bpm__ext_sum

Compute "Brief Problem Monitor [Youth] (Externalizing): Sum"

Description

Computes the summary score mh_y_bpm__ext_sum Brief Problem Monitor [Youth] (Externalizing): Sum

- *Summarized variables:*
  - mh_y_bpm__ext_001
  - mh_y_bpm__ext_002
  - mh_y_bpm__ext_003
  - mh_y_bpm__ext_004
  - mh_y_bpm__ext_005
  - mh_y_bpm__ext_006
  - mh_y_bpm__ext_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_y_bpm__ext_sum(
  data,
  name = "mh_y_bpm__ext_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bpm__ext_nm()

Examples

```
## Not run:
compute_mh_y_bpm__ext_sum(data) |>
  select(
    any_of(c("mh_y_bpm__ext_sum", vars_mh_y_bpm__ext))
  )

## End(Not run)
```

---

compute_mh_y_bpm__ext_tscore

Compute "Brief Problem Monitor [Youth] (Externalizing): T-score"

Description

Computes the summary score `mh_y_bpm__ext_tscore` Brief Problem Monitor [Youth] (Externalizing): T-score

- *Summarized variables:*
  - `mh_y_bpm__ext_001`
  - `mh_y_bpm__ext_002`
  - `mh_y_bpm__ext_003`
  - `mh_y_bpm__ext_004`
  - `mh_y_bpm__ext_005`
  - `mh_y_bpm__ext_006`
  - `mh_y_bpm__ext_007`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_y_bpm__ext_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_bpm__ext_tscore",
  col_age = "mh_y_bpm_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.
`col_sex`	character, name of the sex column. see `ss_tscore()`.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_y_bpm__ext_nm()`

Examples

```
## Not run:
compute_mh_y_bpm__ext_tscore(data) |>
  select(
    any_of(c("mh_y_bpm__ext_tscore", vars_mh_y_bpm__ext))
  )

## End(Not run)
```

---

compute_mh_y_bpm__int_sum

Compute "Brief Problem Monitor [Youth] (Internalizing): Sum"

Description

Computes the summary score `mh_y_bpm__int_sum` Brief Problem Monitor [Youth] (Internalizing): Sum

- *Summarized variables:*
  - `mh_y_bpm__int_001`
  - `mh_y_bpm__int_002`
  - `mh_y_bpm__int_003`
  - `mh_y_bpm__int_004`
  - `mh_y_bpm__int_005`
  - `mh_y_bpm__int_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_y_bpm__int_sum(
  data,
  name = "mh_y_bpm__int_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bpm__int_nm()

Examples

```
## Not run:
compute_mh_y_bpm__int_sum(data) |>
  select(
    any_of(c("mh_y_bpm__int_sum", vars_mh_y_bpm__int))
  )

## End(Not run)
```

---

compute_mh_y_bpm__int_tscore

Compute "Brief Problem Monitor [Youth] (Internalizing): T-score"

Description

Computes the summary score mh_y_bpm__int_tscore Brief Problem Monitor [Youth] (Internalizing): T-score

- *Summarized variables:*
  - mh_y_bpm__int_001
  - mh_y_bpm__int_002
  - mh_y_bpm__int_003
  - mh_y_bpm__int_004
  - mh_y_bpm__int_005
  - mh_y_bpm__int_006
- *Excluded values:*

  - 777
  - 999
- *Validation criterion:* maximally 0 of 6 items missing

Usage

```
compute_mh_y_bpm__int_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_bpm__int_tscore",
  col_age = "mh_y_bpm_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bpm__int_nm()

Examples

```
## Not run:
compute_mh_y_bpm__int_tscore(data) |>
  select(
    any_of(c("mh_y_bpm__int_tscore", vars_mh_y_bpm__int))
  )

## End(Not run)
```

compute_mh_y_bpm_all *Compute all summary scores for mh_y_bpm.*

Description

This function computes all summary scores for the mh_y_bpm form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_bpm_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_bpm_all(data)

## End(Not run)
```

compute_mh_y_bpm_sum *Compute "Brief Problem Monitor [Youth]: Sum"*

Description

Computes the summary score mh_y_bpm_sum Brief Problem Monitor [Youth]: Sum

- *Summarized variables:*
  - mh_y_bpm__attn_001
  - mh_y_bpm__attn_002
  - mh_y_bpm__attn_003
  - mh_y_bpm__attn_004
  - mh_y_bpm__attn_005
  - mh_y_bpm__attn_006
  - mh_y_bpm__ext_001
  - mh_y_bpm__ext_002
  - mh_y_bpm__ext_003
  - mh_y_bpm__ext_004

  - mh_y_bpm__ext_005
  - mh_y_bpm__ext_006
  - mh_y_bpm__ext_007
  - mh_y_bpm__int_001
  - mh_y_bpm__int_002
  - mh_y_bpm__int_003
  - mh_y_bpm__int_004
  - mh_y_bpm__int_005
  - mh_y_bpm__int_006
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 19 items missing

Usage

```
compute_mh_y_bpm_sum(
  data,
  name = "mh_y_bpm_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bpm_nm()

Examples

```
## Not run:
compute_mh_y_bpm_sum(data) |>
  select(
    any_of(c("mh_y_bpm_sum", vars_mh_y_bpm))
  )

## End(Not run)
```

`compute_mh_y_bpm_tscore`

Compute "Brief Problem Monitor [Youth]: T-score"

Description

Computes the summary score `mh_y_bpm_tscore` Brief Problem Monitor [Youth]: T-score

- *Summarized variables:*
  - `mh_y_bpm__attn_001`
  - `mh_y_bpm__attn_002`
  - `mh_y_bpm__attn_003`
  - `mh_y_bpm__attn_004`
  - `mh_y_bpm__attn_005`
  - `mh_y_bpm__attn_006`
  - `mh_y_bpm__ext_001`
  - `mh_y_bpm__ext_002`
  - `mh_y_bpm__ext_003`
  - `mh_y_bpm__ext_004`
  - `mh_y_bpm__ext_005`
  - `mh_y_bpm__ext_006`
  - `mh_y_bpm__ext_007`
  - `mh_y_bpm__int_001`
  - `mh_y_bpm__int_002`
  - `mh_y_bpm__int_003`
  - `mh_y_bpm__int_004`
  - `mh_y_bpm__int_005`
  - `mh_y_bpm__int_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 19 items missing

Usage

```
compute_mh_y_bpm_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_bpm_tscore",
  col_age = "mh_y_bpm_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_bpm_nm()

Examples

```
## Not run:
compute_mh_y_bpm_tscore(data) |>
  select(
    any_of(c("mh_y_bpm_tscore", vars_mh_y_bpm))
  )

## End(Not run)
```

compute_mh_y_erq__reapp_nm *Compute "Emotion Regulation Questionnaire [Youth] (Reappraisal): Number missing"*

Description

Computes the summary score `mh_y_erq__reapp_nm` Emotion Regulation Questionnaire [Youth] (Reappraisal): Number missing

- *Summarized variables:*
  - `mh_y_erq__reapp_001`
  - `mh_y_erq__reapp_002`
  - `mh_y_erq__reapp_003`
- *Excluded values:*
  - 777

Usage

```
compute_mh_y_erq__reapp_nm(
  data,
  name = "mh_y_erq__reapp_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_y_erq__reapp_mean()`

Examples

```
## Not run:
compute_mh_y_erq__reapp_nm(data) |>
  select(
    any_of(c("mh_y_erq__reapp_nm", vars_mh_y_erq__reapp))
  )

## End(Not run)
```

`compute_mh_y_erq__suppr_nm` *Compute "Emotion Regulation Questionnaire [Youth] (Suppression): Number missing"*

Description

Computes the summary score `mh_y_erq__suppr_nm` Emotion Regulation Questionnaire [Youth] (Suppression): Number missing

- *Summarized variables:*
  - `mh_y_erq__suppr_001`
  - `mh_y_erq__suppr_002`
  - `mh_y_erq__suppr_003`
- *Excluded values:*
  - 777

Usage

```
compute_mh_y_erq__suppr_nm(
  data,
  name = "mh_y_erq__suppr_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_erq__suppr_mean()

Examples

```
## Not run:
compute_mh_y_erq__suppr_nm(data) |>
  select(
    any_of(c("mh_y_erq__suppr_nm", vars_mh_y_erq__suppr))
  )

## End(Not run)
```

---

compute_mh_y_erq_all *Compute all summary scores for mh_y_erq.*

Description

This function computes all summary scores for the mh_y_erq table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_erq_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_erq_all(data)

## End(Not run)
```

compute_mh_y_ksads__bpd_all

Compute all summary scores for mh_y_ksads__bpd

Description

This function computes all summary scores for the mh_y_ksads__bpd table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__bpd_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_y_ksads__cond_all

Compute all summary scores for mh_y_ksads__cond

Description

This function computes all summary scores for the mh_y_ksads__cond table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__cond_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_y_ksads__dep_all

Compute all summary scores for mh_y_ksads__dep

Description

This function computes all summary scores for the mh_y_ksads__dep table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__dep_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_y_ksads__dmdd_all

Compute all summary scores for mh_y_ksads__dep

Description

This function computes all summary scores for the mh_y_ksads__dep table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__dmdd_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_y_ksads__ed_all`

Compute all summary scores for mh_y_ksads__ed

Description

This function computes all summary scores for the mh_y_ksads__ed table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__ed_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_y_ksads__gad_all`

Compute all summary scores for mh_y_ksads__gad

Description

This function computes all summary scores for the mh_y_ksads__gad table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__gad_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_y_ksads__ocd_all` *Compute all summary scores for mh_y_ksads__ocd*

Description

This function computes all summary scores for the mh_y_ksads__ocd table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__ocd_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_y_ksads__panic_all` *Compute all summary scores for mh_y_ksads__panic*

Description

This function computes all summary scores for the mh_y_ksads__panic table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__panic_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_y_ksads__ptsd_all`

Compute all summary scores for mh_y_ksads__ptsd

Description

This function computes all summary scores for the mh_y_ksads__ptsd table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__ptsd_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

`compute_mh_y_ksads__sleep_all`

Compute all summary scores for mh_y_ksads__sleep

Description

This function computes all summary scores for the mh_y_ksads__sleep table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__sleep_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_y_ksads__socanx_all

Compute all summary scores for mh_y_ksads__socanx

Description

This function computes all summary scores for the mh_y_ksads__socanx table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__socanx_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_y_ksads__suic_all

Compute all summary scores for mh_y_ksads__suic

Description

This function computes all summary scores for the mh_y_ksads__suic table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ksads__suic_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_mh_y_pai_all *Compute all summary scores for mh_y_upps.*

Description

This function computes all summary scores for the mh_y_pai table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_pai_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_pai_all(data)

## End(Not run)
```

compute_mh_y_pai_sum *Compute "NIH Toolbox - Positive Affect Items [Youth] (NA): Sum [Validation: None missing or declined]"*

Description

Computes the summary score mh_y_pai_sum NIH Toolbox - Positive Affect Items [Youth] (NA): Sum [Validation: None missing or declined]

- *Summarized variables:*
  - mh_y_pai_001
  - mh_y_pai_002
  - mh_y_pai_003
  - mh_y_pai_004
  - mh_y_pai_005
  - mh_y_pai_006
  - mh_y_pai_007
  - mh_y_pai_008

  - mh_y_pai_009

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* none of 9 items missing

Usage

```
compute_mh_y_pai_sum(
  data,
  name = "mh_y_pai_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_pai_nm()

Examples

```
## Not run:
compute_mh_y_pai_sum(data) |>
  select(
    any_of(c("mh_y_pai_sum", vars_mh_y_pai))
  )

## End(Not run)
```

compute_mh_y_peq__overt__agg_sum
Compute "Peer Experiences Questionnaire [Youth] (Overt Aggression): Sum"

Description

Computes the summary score mh_y_peq__overt__agg_sum Peer Experiences Questionnaire [Youth] (Overt Aggression): Sum

- *Summarized variables:*
  - mh_y_peq__overt__agg_001
  - mh_y_peq__overt__agg_002
  - mh_y_peq__overt__agg_003
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
compute_mh_y_peq__overt__agg_sum(
  data,
  name = "mh_y_peq__overt__agg_sum",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_peq__overt__agg_nm()

Examples

```
## Not run:
compute_mh_y_peq__overt__agg_sum(data) |>
  select(
    any_of(c("mh_y_peq__overt__agg_sum", vars_mh_y_peq__overt__agg))
  )

## End(Not run)
```

---

compute_mh_y_peq__overt__vict_sum

Compute "Peer Experiences Questionnaire [Youth] (Overt Victimization): Sum"

Description

Computes the summary score `mh_y_peq__overt__vict_sum` Peer Experiences Questionnaire [Youth] (Overt Victimization): Sum

- *Summarized variables:*
  - `mh_y_peq__overt__vict_001`
  - `mh_y_peq__overt__vict_002`
  - `mh_y_peq__overt__vict_003`
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
compute_mh_y_peq__overt__vict_sum(
  data,
  name = "mh_y_peq__overt__vict_sum",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_y_peq__overt__vict_nm()`

Examples

```
## Not run:
compute_mh_y_peq__overt__vict_sum(data) |>
  select(
    any_of(c("mh_y_peq__overt__vict_sum", vars_mh_y_peq__overt__vict))
  )

## End(Not run)
```

`compute_mh_y_peq__rel__agg_sum` *Compute "Peer Experiences Questionnaire [Youth] (Relational Aggression): Sum"*

Description

Computes the summary score `mh_y_peq__rel__agg_sum` Peer Experiences Questionnaire [Youth] (Relational Aggression): Sum

- *Summarized variables:*
  - `mh_y_peq__rel__agg_001`
  - `mh_y_peq__rel__agg_002`
  - `mh_y_peq__rel__agg_003`
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
compute_mh_y_peq__rel__agg_sum(
  data,
  name = "mh_y_peq__rel__agg_sum",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_peq__rel__agg_nm()

Examples

```
## Not run:
compute_mh_y_peq__rel__agg_sum(data) |>
  select(
    any_of(c("mh_y_peq__rel__agg_sum", vars_mh_y_peq__rel__agg))
  )

## End(Not run)
```

---

compute_mh_y_peq__rel__vict_sum

Compute "Peer Experiences Questionnaire [Youth] (Relational Victimization): Sum"

Description

Computes the summary score mh_y_peq__rel__vict_sum Peer Experiences Questionnaire [Youth] (Relational Victimization): Sum

- *Summarized variables:*
  - mh_y_peq__rel__vict_001
  - mh_y_peq__rel__vict_002
  - mh_y_peq__rel__vict_003
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
compute_mh_y_peq__rel__vict_sum(
  data,
  name = "mh_y_peq__rel__vict_sum",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_peq__rel__vict_nm()

Examples

```
## Not run:
compute_mh_y_peq__rel__vict_sum(data) |>
  select(
    any_of(c("mh_y_peq__rel__vict_sum", vars_mh_y_peq__rel__vict))
  )

## End(Not run)
```

---

compute_mh_y_peq__rep__agg_sum

Compute "Peer Experiences Questionnaire [Youth] (Reputational Aggression): Sum"

Description

Computes the summary score mh_y_peq__rep__agg_sum Peer Experiences Questionnaire [Youth] (Reputational Aggression): Sum

- *Summarized variables:*
  - mh_y_peq__rep__agg_001
  - mh_y_peq__rep__agg_002
  - mh_y_peq__rep__agg_003
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
compute_mh_y_peq__rep__agg_sum(
  data,
  name = "mh_y_peq__rep__agg_sum",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_peq__rep__agg_nm()

Examples

```
## Not run:
compute_mh_y_peq__rep__agg_sum(data) |>
  select(
    any_of(c("mh_y_peq__rep__agg_sum", vars_mh_y_peq__rep__agg))
```

```
  )

## End(Not run)
```

`compute_mh_y_peq__rep__vict_sum` *Compute "Peer Experiences Questionnaire [Youth] (Reputational Victimization): Sum"*

Description

Computes the summary score `mh_y_peq__rep__vict_sum` Peer Experiences Questionnaire [Youth] (Reputational Victimization): Sum

- *Summarized variables:*
  - `mh_y_peq__rep__vict_001`
  - `mh_y_peq__rep__vict_002`
  - `mh_y_peq__rep__vict_003`
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
compute_mh_y_peq__rep__vict_sum(
  data,
  name = "mh_y_peq__rep__vict_sum",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

compute_mh_y_peq__rep__vict_nm()

Examples

```
## Not run:
compute_mh_y_peq__rep__vict_sum(data) |>
  select(
    any_of(c("mh_y_peq__rep__vict_sum", vars_mh_y_peq__rep__vict))
  )

## End(Not run)
```

---

compute_mh_y_peq_all *Compute all summary scores for mh_y_peq.*

Description

This function computes all summary scores for the mh_y_peq table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_peq_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_peq_all(data)

## End(Not run)
```

`compute_mh_y_ple__exp__bad_count`
Compute "Life Events [Youth] (Experience Bad Events): Count"

Description

Computes the summary score `mh_y_ple__exp__bad_count` Life Events [Youth] (Experience Bad Events): Count

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`
  - `mh_y_ple__exp_022`
  - `mh_y_ple__exp_023`
  - `mh_y_ple__exp_024`
  - `mh_y_ple__exp_025`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp__bad_count(
  data,
  name = "mh_y_ple__exp__bad_count",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__exp__bad_count__v01

Compute "Life Events [Youth] (Experience Bad Events): Count - Version 1 (Year 3)"

Description

Computes the summary score mh_y_ple__exp__bad_count__v01 Life Events [Youth] (Experience Bad Events): Count - Version 1 (Year 3)

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011

  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017
  - mh_y_ple__exp_018
  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021
  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__exp_026
  - mh_y_ple__exp_027
  - mh_y_ple__exp_028
  - mh_y_ple__exp_029
  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp__bad_count__v01(
  data,
  name = "mh_y_ple__exp__bad_count__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__exp__bad_count__v02`
Compute "Life Events [Youth] (Experience Bad Events): Count - Version 2 (Year 4 and Year 5)"

Description

Computes the summary score `mh_y_ple__exp__bad_count__v02` Life Events [Youth] (Experience Bad Events): Count - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`
  - `mh_y_ple__exp_022`
  - `mh_y_ple__exp_023`
  - `mh_y_ple__exp_024`
  - `mh_y_ple__exp_025`
  - `mh_y_ple__exp_026`
  - `mh_y_ple__exp_027`
  - `mh_y_ple__exp_028`

  - mh_y_ple__exp_029
  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
  - mh_y_ple__exp_032

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp__bad_count__v02(
  data,
  name = "mh_y_ple__exp__bad_count__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__exp__bad_count__v03

Compute "Life Events [Youth] (Experience Bad Events): Count - Version 3 (Starting at Year 6)"

Description

Computes the summary score `mh_y_ple__exp__bad_count__v03` Life Events [Youth] (Experience Bad Events): Count - Version 3 (Starting at Year 6)

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`
  - `mh_y_ple__exp_022`
  - `mh_y_ple__exp_023`
  - `mh_y_ple__exp_024`
  - `mh_y_ple__exp_025`
  - `mh_y_ple__exp_026`
  - `mh_y_ple__exp_027`
  - `mh_y_ple__exp_028`
  - `mh_y_ple__exp_029`
  - `mh_y_ple__exp_030`
  - `mh_y_ple__exp_031`
  - `mh_y_ple__exp_032`
  - `mh_y_ple__exp_033`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp__bad_count__v03(
  data,
  name = "mh_y_ple__exp__bad_count__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__exp__good_count

Compute "Life Events [Youth] (Experience Good Events): Count"

Description

Computes the summary score mh_y_ple__exp__good_count Life Events [Youth] (Experience Good Events): Count

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010

  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017
  - mh_y_ple__exp_018
  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021
  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp__good_count(
  data,
  name = "mh_y_ple__exp__good_count",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

compute_mh_y_ple__exp__good_count__v01

Compute "Life Events [Youth] (Experience Good Events): Count - Version 1 (Year 3)"

Description

Computes the summary score mh_y_ple__exp__good_count__v01 Life Events [Youth] (Experience Good Events): Count - Version 1 (Year 3)

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017
  - mh_y_ple__exp_018
  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021
  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__exp_026
  - mh_y_ple__exp_027
  - mh_y_ple__exp_028
  - mh_y_ple__exp_029
  - mh_y_ple__exp_030
  - mh_y_ple__exp_031

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp__good_count__v01(
  data,
  name = "mh_y_ple__exp__good_count__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__exp__good_count__v02

Compute "Life Events [Youth] (Experience Good Events): Count - Version 2 (Year 4 and Year 5)"

Description

Computes the summary score mh_y_ple__exp__good_count__v02 Life Events [Youth] (Experience Good Events): Count - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004

  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017
  - mh_y_ple__exp_018
  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021
  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__exp_026
  - mh_y_ple__exp_027
  - mh_y_ple__exp_028
  - mh_y_ple__exp_029
  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
  - mh_y_ple__exp_032
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp__good_count__v02(
  data,
  name = "mh_y_ple__exp__good_count__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__exp__good_count__v03

Compute "Life Events [Youth] (Experience Good Events): Count - Version 3 (Starting at Year 6)"

Description

Computes the summary score mh_y_ple__exp__good_count__v03 Life Events [Youth] (Experience Good Events): Count - Version 3 (Starting at Year 6)

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017

  - mh_y_ple__exp_018
  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021
  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__exp_026
  - mh_y_ple__exp_027
  - mh_y_ple__exp_028
  - mh_y_ple__exp_029
  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
  - mh_y_ple__exp_032
  - mh_y_ple__exp_033
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp__good_count__v03(
  data,
  name = "mh_y_ple__exp__good_count__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__exp_nm` *Compute "Life Events [Youth] (Experience): Number missing"*

Description

Computes the summary score `mh_y_ple__exp_nm` Life Events [Youth] (Experience): Number missing

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`
  - `mh_y_ple__exp_022`
  - `mh_y_ple__exp_023`
  - `mh_y_ple__exp_024`
  - `mh_y_ple__exp_025`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp_nm(data, name = "mh_y_ple__exp_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__exp_nm__v01

Compute "Life Events [Youth] (Experience): Number missing - Version 1 (Year 3)"

Description

Computes the summary score mh_y_ple__exp_nm__v01 Life Events [Youth] (Experience): Number missing - Version 1 (Year 3)

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017
  - mh_y_ple__exp_018
  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021

  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__exp_026
  - mh_y_ple__exp_027
  - mh_y_ple__exp_028
  - mh_y_ple__exp_029
  - mh_y_ple__exp_030
  - mh_y_ple__exp_031

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp_nm__v01(
  data,
  name = "mh_y_ple__exp_nm__v01",
  events = "ses-03A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__exp_nm__v02`
Compute "Life Events [Youth] (Experience): Number missing - Version 2 (Year 4 and Year 5)"

Description

Computes the summary score `mh_y_ple__exp_nm__v02` Life Events [Youth] (Experience): Number missing - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`
  - `mh_y_ple__exp_022`
  - `mh_y_ple__exp_023`
  - `mh_y_ple__exp_024`
  - `mh_y_ple__exp_025`
  - `mh_y_ple__exp_026`
  - `mh_y_ple__exp_027`
  - `mh_y_ple__exp_028`
  - `mh_y_ple__exp_029`
  - `mh_y_ple__exp_030`
  - `mh_y_ple__exp_031`

  - mh_y_ple__exp_032
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp_nm__v02(
  data,
  name = "mh_y_ple__exp_nm__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__exp_nm__v03

Compute "Life Events [Youth] (Experience): Number missing - Version 3 (Starting at Year 6)"

Description

Computes the summary score mh_y_ple__exp_nm__v03 Life Events [Youth] (Experience): Number missing - Version 3 (Starting at Year 6)

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006

  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017
  - mh_y_ple__exp_018
  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021
  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__exp_026
  - mh_y_ple__exp_027
  - mh_y_ple__exp_028
  - mh_y_ple__exp_029
  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
  - mh_y_ple__exp_032
  - mh_y_ple__exp_033

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__exp_nm__v03(
  data,
  name = "mh_y_ple__exp_nm__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity__bad_mean

Compute "Life Events [Youth] (Severity of Bad Events): Mean [Validation: No more than 5 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity__bad_mean Life Events [Youth] (Severity of Bad Events): Mean [Validation: No more than 5 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017
  - mh_y_ple__exp_018

  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021
  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
compute_mh_y_ple__severity__bad_mean(
  data,
  name = "mh_y_ple__severity__bad_mean",
```

```
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__severity__bad_mean__v01`

Compute "Life Events [Youth] (Severity of Bad Events): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_y_ple__severity__bad_mean__v01` Life Events [Youth] (Severity of Bad Events): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`

- mh_y_ple__exp_014
- mh_y_ple__exp_015
- mh_y_ple__exp_016
- mh_y_ple__exp_017
- mh_y_ple__exp_018
- mh_y_ple__exp_019
- mh_y_ple__exp_020
- mh_y_ple__exp_021
- mh_y_ple__exp_022
- mh_y_ple__exp_023
- mh_y_ple__exp_024
- mh_y_ple__exp_025
- mh_y_ple__exp_026
- mh_y_ple__exp_027
- mh_y_ple__exp_028
- mh_y_ple__exp_029
- mh_y_ple__exp_030
- mh_y_ple__exp_031
- mh_y_ple__severity_001
- mh_y_ple__severity_002
- mh_y_ple__severity_003
- mh_y_ple__severity_004
- mh_y_ple__severity_005
- mh_y_ple__severity_006
- mh_y_ple__severity_007
- mh_y_ple__severity_008
- mh_y_ple__severity_009
- mh_y_ple__severity_010
- mh_y_ple__severity_011
- mh_y_ple__severity_012
- mh_y_ple__severity_013
- mh_y_ple__severity_014
- mh_y_ple__severity_015
- mh_y_ple__severity_016
- mh_y_ple__severity_017
- mh_y_ple__severity_018
- mh_y_ple__severity_019
- mh_y_ple__severity_020
- mh_y_ple__severity_021
- mh_y_ple__severity_022
- mh_y_ple__severity_023
- mh_y_ple__severity_024

  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031

- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
compute_mh_y_ple__severity__bad_mean__v01(
  data,
  name = "mh_y_ple__severity__bad_mean__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__severity__bad_mean__v02`

Compute "Life Events [Youth] (Severity of Bad Events): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_y_ple__severity__bad_mean__v02` Life Events [Youth] (Severity of Bad Events): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`
  - `mh_y_ple__exp_022`
  - `mh_y_ple__exp_023`
  - `mh_y_ple__exp_024`
  - `mh_y_ple__exp_025`
  - `mh_y_ple__exp_026`
  - `mh_y_ple__exp_027`
  - `mh_y_ple__exp_028`
  - `mh_y_ple__exp_029`

  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
  - mh_y_ple__exp_032
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_y_ple__severity__bad_mean__v02(
  data,
  name = "mh_y_ple__severity__bad_mean__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity__bad_mean__v03

Compute "Life Events [Youth] (Severity of Bad Events): Mean - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity__bad_mean__v03 Life Events [Youth] (Severity of Bad Events): Mean - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007

- mh_y_ple__exp_008
- mh_y_ple__exp_009
- mh_y_ple__exp_010
- mh_y_ple__exp_011
- mh_y_ple__exp_012
- mh_y_ple__exp_013
- mh_y_ple__exp_014
- mh_y_ple__exp_015
- mh_y_ple__exp_016
- mh_y_ple__exp_017
- mh_y_ple__exp_018
- mh_y_ple__exp_019
- mh_y_ple__exp_020
- mh_y_ple__exp_021
- mh_y_ple__exp_022
- mh_y_ple__exp_023
- mh_y_ple__exp_024
- mh_y_ple__exp_025
- mh_y_ple__exp_026
- mh_y_ple__exp_027
- mh_y_ple__exp_028
- mh_y_ple__exp_029
- mh_y_ple__exp_030
- mh_y_ple__exp_031
- mh_y_ple__exp_032
- mh_y_ple__exp_033
- mh_y_ple__severity_001
- mh_y_ple__severity_002
- mh_y_ple__severity_003
- mh_y_ple__severity_004
- mh_y_ple__severity_005
- mh_y_ple__severity_006
- mh_y_ple__severity_007
- mh_y_ple__severity_008
- mh_y_ple__severity_009
- mh_y_ple__severity_010
- mh_y_ple__severity_011
- mh_y_ple__severity_012
- mh_y_ple__severity_013
- mh_y_ple__severity_014
- mh_y_ple__severity_015
- mh_y_ple__severity_016

  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_y_ple__severity__bad_mean__v03(
  data,
  name = "mh_y_ple__severity__bad_mean__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__severity__bad_sum`

Compute "Life Events [Youth] (Severity of Bad Events): Sum [Validation: No more than 5 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_y_ple__severity__bad_sum` Life Events [Youth] (Severity of Bad Events): Sum [Validation: No more than 5 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`
  - `mh_y_ple__exp_022`
  - `mh_y_ple__exp_023`
  - `mh_y_ple__exp_024`
  - `mh_y_ple__exp_025`
  - `mh_y_ple__severity_001`

  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
compute_mh_y_ple__severity__bad_sum(
  data,
  name = "mh_y_ple__severity__bad_sum",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).

combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__severity__bad_sum__v01`

Compute "Life Events [Youth] (Severity of Bad Events): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_y_ple__severity__bad_sum__v01` Life Events [Youth] (Severity of Bad Events): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`

  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__exp_026
  - mh_y_ple__exp_027
  - mh_y_ple__exp_028
  - mh_y_ple__exp_029
  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031

- *Excluded values:*

  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
compute_mh_y_ple__severity__bad_sum__v01(
  data,
  name = "mh_y_ple__severity__bad_sum__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity__bad_sum__v02

Compute "Life Events [Youth] (Severity of Bad Events): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity__bad_sum__v02 Life Events [Youth] (Severity of Bad Events): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002

- mh_y_ple__exp_003
- mh_y_ple__exp_004
- mh_y_ple__exp_005
- mh_y_ple__exp_006
- mh_y_ple__exp_007
- mh_y_ple__exp_008
- mh_y_ple__exp_009
- mh_y_ple__exp_010
- mh_y_ple__exp_011
- mh_y_ple__exp_012
- mh_y_ple__exp_013
- mh_y_ple__exp_014
- mh_y_ple__exp_015
- mh_y_ple__exp_016
- mh_y_ple__exp_017
- mh_y_ple__exp_018
- mh_y_ple__exp_019
- mh_y_ple__exp_020
- mh_y_ple__exp_021
- mh_y_ple__exp_022
- mh_y_ple__exp_023
- mh_y_ple__exp_024
- mh_y_ple__exp_025
- mh_y_ple__exp_026
- mh_y_ple__exp_027
- mh_y_ple__exp_028
- mh_y_ple__exp_029
- mh_y_ple__exp_030
- mh_y_ple__exp_031
- mh_y_ple__exp_032
- mh_y_ple__severity_001
- mh_y_ple__severity_002
- mh_y_ple__severity_003
- mh_y_ple__severity_004
- mh_y_ple__severity_005
- mh_y_ple__severity_006
- mh_y_ple__severity_007
- mh_y_ple__severity_008
- mh_y_ple__severity_009
- mh_y_ple__severity_010
- mh_y_ple__severity_011
- mh_y_ple__severity_012

  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_y_ple__severity__bad_sum__v02(
  data,
  name = "mh_y_ple__severity__bad_sum__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.

combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__severity__bad_sum__v03`

Compute "Life Events [Youth] (Severity of Bad Events): Sum - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_y_ple__severity__bad_sum__v03` Life Events [Youth] (Severity of Bad Events): Sum - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`

- mh_y_ple__exp_022
- mh_y_ple__exp_023
- mh_y_ple__exp_024
- mh_y_ple__exp_025
- mh_y_ple__exp_026
- mh_y_ple__exp_027
- mh_y_ple__exp_028
- mh_y_ple__exp_029
- mh_y_ple__exp_030
- mh_y_ple__exp_031
- mh_y_ple__exp_032
- mh_y_ple__exp_033
- mh_y_ple__severity_001
- mh_y_ple__severity_002
- mh_y_ple__severity_003
- mh_y_ple__severity_004
- mh_y_ple__severity_005
- mh_y_ple__severity_006
- mh_y_ple__severity_007
- mh_y_ple__severity_008
- mh_y_ple__severity_009
- mh_y_ple__severity_010
- mh_y_ple__severity_011
- mh_y_ple__severity_012
- mh_y_ple__severity_013
- mh_y_ple__severity_014
- mh_y_ple__severity_015
- mh_y_ple__severity_016
- mh_y_ple__severity_017
- mh_y_ple__severity_018
- mh_y_ple__severity_019
- mh_y_ple__severity_020
- mh_y_ple__severity_021
- mh_y_ple__severity_022
- mh_y_ple__severity_023
- mh_y_ple__severity_024
- mh_y_ple__severity_025
- mh_y_ple__severity_026
- mh_y_ple__severity_027
- mh_y_ple__severity_028
- mh_y_ple__severity_029
- mh_y_ple__severity_030

  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_033

- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_y_ple__severity__bad_sum__v03(
  data,
  name = "mh_y_ple__severity__bad_sum__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity__good_mean

Compute "Life Events [Youth] (Severity of Good Events): Mean [Validation: No more than 5 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_y_ple__severity__good_mean` Life Events [Youth] (Severity of Good Events): Mean [Validation: No more than 5 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`
  - `mh_y_ple__exp_022`
  - `mh_y_ple__exp_023`
  - `mh_y_ple__exp_024`
  - `mh_y_ple__exp_025`
  - `mh_y_ple__severity_001`
  - `mh_y_ple__severity_002`
  - `mh_y_ple__severity_003`
  - `mh_y_ple__severity_004`
  - `mh_y_ple__severity_005`
  - `mh_y_ple__severity_006`
  - `mh_y_ple__severity_007`
  - `mh_y_ple__severity_008`
  - `mh_y_ple__severity_009`
  - `mh_y_ple__severity_010`
  - `mh_y_ple__severity_011`

  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
compute_mh_y_ple__severity__good_mean(
  data,
  name = "mh_y_ple__severity__good_mean",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Value

tbl. The input data frame with the summary score appended as a new column.

compute_mh_y_ple__severity__good_mean__v01

Compute "Life Events [Youth] (Severity of Good Events): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity__good_mean__v01 Life Events [Youth] (Severity of Good Events): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017
  - mh_y_ple__exp_018
  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021
  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__exp_026
  - mh_y_ple__exp_027
  - mh_y_ple__exp_028
  - mh_y_ple__exp_029

  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
compute_mh_y_ple__severity__good_mean__v01(
  data,
  name = "mh_y_ple__severity__good_mean__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity__good_mean__v02

Compute "Life Events [Youth] (Severity of Good Events): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity__good_mean__v02 Life Events [Youth] (Severity of Good Events): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007

- mh_y_ple__exp_008
- mh_y_ple__exp_009
- mh_y_ple__exp_010
- mh_y_ple__exp_011
- mh_y_ple__exp_012
- mh_y_ple__exp_013
- mh_y_ple__exp_014
- mh_y_ple__exp_015
- mh_y_ple__exp_016
- mh_y_ple__exp_017
- mh_y_ple__exp_018
- mh_y_ple__exp_019
- mh_y_ple__exp_020
- mh_y_ple__exp_021
- mh_y_ple__exp_022
- mh_y_ple__exp_023
- mh_y_ple__exp_024
- mh_y_ple__exp_025
- mh_y_ple__exp_026
- mh_y_ple__exp_027
- mh_y_ple__exp_028
- mh_y_ple__exp_029
- mh_y_ple__exp_030
- mh_y_ple__exp_031
- mh_y_ple__exp_032
- mh_y_ple__severity_001
- mh_y_ple__severity_002
- mh_y_ple__severity_003
- mh_y_ple__severity_004
- mh_y_ple__severity_005
- mh_y_ple__severity_006
- mh_y_ple__severity_007
- mh_y_ple__severity_008
- mh_y_ple__severity_009
- mh_y_ple__severity_010
- mh_y_ple__severity_011
- mh_y_ple__severity_012
- mh_y_ple__severity_013
- mh_y_ple__severity_014
- mh_y_ple__severity_015
- mh_y_ple__severity_016
- mh_y_ple__severity_017

  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_y_ple__severity__good_mean__v02(
  data,
  name = "mh_y_ple__severity__good_mean__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__severity__good_mean__v03`

Compute "Life Events [Youth] (Severity of Good Events): Mean - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score `mh_y_ple__severity__good_mean__v03` Life Events [Youth] (Severity of Good Events): Mean - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - `mh_y_ple__exp_001`
  - `mh_y_ple__exp_002`
  - `mh_y_ple__exp_003`
  - `mh_y_ple__exp_004`
  - `mh_y_ple__exp_005`
  - `mh_y_ple__exp_006`
  - `mh_y_ple__exp_007`
  - `mh_y_ple__exp_008`
  - `mh_y_ple__exp_009`
  - `mh_y_ple__exp_010`
  - `mh_y_ple__exp_011`
  - `mh_y_ple__exp_012`
  - `mh_y_ple__exp_013`
  - `mh_y_ple__exp_014`
  - `mh_y_ple__exp_015`
  - `mh_y_ple__exp_016`
  - `mh_y_ple__exp_017`
  - `mh_y_ple__exp_018`
  - `mh_y_ple__exp_019`
  - `mh_y_ple__exp_020`
  - `mh_y_ple__exp_021`
  - `mh_y_ple__exp_022`
  - `mh_y_ple__exp_023`
  - `mh_y_ple__exp_024`
  - `mh_y_ple__exp_025`
  - `mh_y_ple__exp_026`
  - `mh_y_ple__exp_027`
  - `mh_y_ple__exp_028`
  - `mh_y_ple__exp_029`

  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
  - mh_y_ple__exp_032
  - mh_y_ple__exp_033
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_y_ple__severity__good_mean__v03(
  data,
  name = "mh_y_ple__severity__good_mean__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity_mean

Compute "Life Events [Youth] (Severity): Mean [Validation: No more than 5 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity_mean Life Events [Youth] (Severity): Mean [Validation: No more than 5 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009

  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
compute_mh_y_ple__severity_mean(
  data,
  name = "mh_y_ple__severity_mean",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__severity_mean__v01`

Compute "Life Events [Youth] (Severity): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score `mh_y_ple__severity_mean__v01` Life Events [Youth] (Severity): Mean - Version 1 (Year 3) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - `mh_y_ple__severity_001`
  - `mh_y_ple__severity_002`
  - `mh_y_ple__severity_003`
  - `mh_y_ple__severity_004`
  - `mh_y_ple__severity_005`
  - `mh_y_ple__severity_006`
  - `mh_y_ple__severity_007`
  - `mh_y_ple__severity_008`
  - `mh_y_ple__severity_009`
  - `mh_y_ple__severity_010`
  - `mh_y_ple__severity_011`
  - `mh_y_ple__severity_012`
  - `mh_y_ple__severity_013`
  - `mh_y_ple__severity_014`
  - `mh_y_ple__severity_015`
  - `mh_y_ple__severity_016`
  - `mh_y_ple__severity_017`
  - `mh_y_ple__severity_018`
  - `mh_y_ple__severity_019`
  - `mh_y_ple__severity_020`
  - `mh_y_ple__severity_021`
  - `mh_y_ple__severity_022`
  - `mh_y_ple__severity_023`
  - `mh_y_ple__severity_024`
  - `mh_y_ple__severity_025`
  - `mh_y_ple__severity_026`
  - `mh_y_ple__severity_027`
  - `mh_y_ple__severity_028`
  - `mh_y_ple__severity_029`

  - mh_y_ple__severity_030
  - mh_y_ple__severity_031

- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
compute_mh_y_ple__severity_mean__v01(
  data,
  name = "mh_y_ple__severity_mean__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__severity_mean__v02`

Compute "Life Events [Youth] (Severity): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity_mean__v02 Life Events [Youth] (Severity): Mean - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
compute_mh_y_ple__severity_mean__v02(
  data,
  name = "mh_y_ple__severity_mean__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity_mean__v03

Compute "Life Events [Youth] (Severity): Mean - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity_mean__v03 Life Events [Youth] (Severity): Mean - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007

  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_033
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 34 items missing

Usage

```
compute_mh_y_ple__severity_mean__v03(
  data,
  name = "mh_y_ple__severity_mean__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity_nm

Compute "Life Events [Youth] (Severity): Number missing"

Description

Computes the summary score mh_y_ple__severity_nm Life Events [Youth] (Severity): Number missing

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018

  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__severity_nm(
  data,
  name = "mh_y_ple__severity_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity_nm__v01

Compute "Life Events [Youth] (Severity): Number missing - Version 1 (Year 3)"

Description

Computes the summary score mh_y_ple__severity_nm__v01 Life Events [Youth] (Severity): Number missing - Version 1 (Year 3)

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002

  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__severity_nm__v01(
  data,
  name = "mh_y_ple__severity_nm__v01",
  events = "ses-03A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple__severity_nm__v02

Compute "Life Events [Youth] (Severity): Number missing - Version 2 (Year 4 and Year 5)"

Description

Computes the summary score mh_y_ple__severity_nm__v02 Life Events [Youth] (Severity): Number missing - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019

  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__severity_nm__v02(
  data,
  name = "mh_y_ple__severity_nm__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_mh_y_ple__severity_nm__v03`
Compute "Life Events [Youth] (Severity): Number missing - Version 3 (Starting at Year 6)"

Description

Computes the summary score `mh_y_ple__severity_nm__v03` Life Events [Youth] (Severity): Number missing - Version 3 (Starting at Year 6)

- *Summarized variables:*
  - `mh_y_ple__severity_001`
  - `mh_y_ple__severity_002`
  - `mh_y_ple__severity_003`
  - `mh_y_ple__severity_004`
  - `mh_y_ple__severity_005`
  - `mh_y_ple__severity_006`
  - `mh_y_ple__severity_007`
  - `mh_y_ple__severity_008`
  - `mh_y_ple__severity_009`
  - `mh_y_ple__severity_010`
  - `mh_y_ple__severity_011`
  - `mh_y_ple__severity_012`
  - `mh_y_ple__severity_013`
  - `mh_y_ple__severity_014`
  - `mh_y_ple__severity_015`
  - `mh_y_ple__severity_016`
  - `mh_y_ple__severity_017`
  - `mh_y_ple__severity_018`
  - `mh_y_ple__severity_019`
  - `mh_y_ple__severity_020`
  - `mh_y_ple__severity_021`
  - `mh_y_ple__severity_022`
  - `mh_y_ple__severity_023`
  - `mh_y_ple__severity_024`
  - `mh_y_ple__severity_025`
  - `mh_y_ple__severity_026`
  - `mh_y_ple__severity_027`
  - `mh_y_ple__severity_028`
  - `mh_y_ple__severity_029`
  - `mh_y_ple__severity_030`
  - `mh_y_ple__severity_031`

  - mh_y_ple__severity_032
  - mh_y_ple__severity_033
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple__severity_nm__v03(
  data,
  name = "mh_y_ple__severity_nm__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple_all *Compute all summary scores for mh_y_ple*

Description

This function computes all summary scores for the mh_y_ple form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ple_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_ple_all(data)

## End(Not run)
```

`compute_mh_y_ple_nm` *Compute "Life Events [Youth] (Events): Number missing"*

Description

Computes the summary score `mh_y_ple_nm` Life Events [Youth] (Events): Number missing

- *Summarized variables:*
  - `mh_y_ple_001`
  - `mh_y_ple_002`
  - `mh_y_ple_003`
  - `mh_y_ple_004`
  - `mh_y_ple_005`
  - `mh_y_ple_006`
  - `mh_y_ple_007`
  - `mh_y_ple_008`
  - `mh_y_ple_009`
  - `mh_y_ple_010`
  - `mh_y_ple_011`
  - `mh_y_ple_012`
  - `mh_y_ple_013`
  - `mh_y_ple_014`
  - `mh_y_ple_015`
  - `mh_y_ple_016`
  - `mh_y_ple_017`
  - `mh_y_ple_018`
  - `mh_y_ple_019`
  - `mh_y_ple_020`
  - `mh_y_ple_021`
  - `mh_y_ple_022`
  - `mh_y_ple_023`
  - `mh_y_ple_024`
  - `mh_y_ple_025`

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple_nm(data, name = "mh_y_ple_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple_nm__v01

Compute "Life Events [Youth] (Events): Number missing - Version 1 (Year 3)"

Description

Computes the summary score mh_y_ple_nm__v01 Life Events [Youth] (Events): Number missing - Version 1 (Year 3)

- *Summarized variables:*
  - mh_y_ple_001
  - mh_y_ple_002
  - mh_y_ple_003
  - mh_y_ple_004
  - mh_y_ple_005
  - mh_y_ple_006
  - mh_y_ple_007
  - mh_y_ple_008
  - mh_y_ple_009
  - mh_y_ple_010
  - mh_y_ple_011
  - mh_y_ple_012

  - mh_y_ple_013
  - mh_y_ple_014
  - mh_y_ple_015
  - mh_y_ple_016
  - mh_y_ple_017
  - mh_y_ple_018
  - mh_y_ple_019
  - mh_y_ple_020
  - mh_y_ple_021
  - mh_y_ple_022
  - mh_y_ple_023
  - mh_y_ple_024
  - mh_y_ple_025
  - mh_y_ple_026
  - mh_y_ple_027
  - mh_y_ple_028
  - mh_y_ple_029
  - mh_y_ple_030
  - mh_y_ple_031
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple_nm__v01(
  data,
  name = "mh_y_ple_nm__v01",
  events = "ses-03A",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_mh_y_ple_nm__v02

Compute "Life Events [Youth] (Events): Number missing - Version 2 (Year 4 and Year 5)"

Description

Computes the summary score mh_y_ple_nm__v02 Life Events [Youth] (Events): Number missing - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - mh_y_ple_001
  - mh_y_ple_002
  - mh_y_ple_003
  - mh_y_ple_004
  - mh_y_ple_005
  - mh_y_ple_006
  - mh_y_ple_007
  - mh_y_ple_008
  - mh_y_ple_009
  - mh_y_ple_010
  - mh_y_ple_011
  - mh_y_ple_012
  - mh_y_ple_013
  - mh_y_ple_014
  - mh_y_ple_015
  - mh_y_ple_016
  - mh_y_ple_017
  - mh_y_ple_018
  - mh_y_ple_019
  - mh_y_ple_020
  - mh_y_ple_021
  - mh_y_ple_022
  - mh_y_ple_023
  - mh_y_ple_024
  - mh_y_ple_025
  - mh_y_ple_026
  - mh_y_ple_027
  - mh_y_ple_028
  - mh_y_ple_029
  - mh_y_ple_030
  - mh_y_ple_031

  - mh_y_ple_032
  - mh_y_ple_034
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple_nm__v02(
  data,
  name = "mh_y_ple_nm__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_ple_nm__v03

Compute "Life Events [Youth] (Events): Number missing - Version 3 (Starting at Year 6)"

Description

Computes the summary score mh_y_ple_nm__v03 Life Events [Youth] (Events): Number missing - Version 3 (Starting at Year 6)

- *Summarized variables:*
  - mh_y_ple_001
  - mh_y_ple_002
  - mh_y_ple_003
  - mh_y_ple_004
  - mh_y_ple_005

  - mh_y_ple_006
  - mh_y_ple_007
  - mh_y_ple_008
  - mh_y_ple_009
  - mh_y_ple_010
  - mh_y_ple_011
  - mh_y_ple_012
  - mh_y_ple_013
  - mh_y_ple_014
  - mh_y_ple_015
  - mh_y_ple_016
  - mh_y_ple_017
  - mh_y_ple_018
  - mh_y_ple_019
  - mh_y_ple_020
  - mh_y_ple_021
  - mh_y_ple_022
  - mh_y_ple_023
  - mh_y_ple_024
  - mh_y_ple_025
  - mh_y_ple_026
  - mh_y_ple_027
  - mh_y_ple_028
  - mh_y_ple_029
  - mh_y_ple_030
  - mh_y_ple_031
  - mh_y_ple_032
  - mh_y_ple_033
  - mh_y_ple_034
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
compute_mh_y_ple_nm__v03(
  data,
  name = "mh_y_ple_nm__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_mh_y_pps__bother__no_count

Compute "Prodromal Psychosis Scale [Youth] (Bother "No" responses): Count"

Description

Computes the summary score mh_y_pps__bother__no_count Prodromal Psychosis Scale [Youth] (Bother

- *Summarized variables:*
  - mh_y_pps__bother_001
  - mh_y_pps__bother_002
  - mh_y_pps__bother_003
  - mh_y_pps__bother_004
  - mh_y_pps__bother_005
  - mh_y_pps__bother_006
  - mh_y_pps__bother_007
  - mh_y_pps__bother_008
  - mh_y_pps__bother_009
  - mh_y_pps__bother_010
  - mh_y_pps__bother_011
  - mh_y_pps__bother_012
  - mh_y_pps__bother_013
  - mh_y_pps__bother_014
  - mh_y_pps__bother_015
  - mh_y_pps__bother_016
  - mh_y_pps__bother_017
  - mh_y_pps__bother_018
  - mh_y_pps__bother_019

  - mh_y_pps__bother_020
  - mh_y_pps__bother_021
- *Excluded values:* none
- *Validation criterion:* 0 of 21 items missing

Usage

```
compute_mh_y_pps__bother__no_count(
  data,
  name = "mh_y_pps__bother__no_count",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Details

The bother count is depend on the mh_y_pps__bother_nm score. If the mh_y_pps__bother_nm score is greater than max_na, the bother count is set to NA.

There is also a sanity check for the gating question in PPS bother score. If the paired gating question is 0 or NA and the bother score is not missing, the paired bother score is set to NA before computing the count.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_y_pps__bother_nm()

Examples

```
## Not run:
compute_mh_y_pps__bother__no_count(data) |>
  select(
    any_of(c("mh_y_pps__bother__no_count", vars_mh_y_pps__bother))
  )

## End(Not run)
```

`compute_mh_y_pps__bother__yes_count` *Compute "Prodromal Psychosis Scale [Youth] (Bother "Yes" responses): Count"*

Description

Computes the summary score `mh_y_pps__bother__yes_count` Prodromal Psychosis Scale [Youth] (Bother

- *Summarized variables:*
  - `mh_y_pps__bother_001`
  - `mh_y_pps__bother_002`
  - `mh_y_pps__bother_003`
  - `mh_y_pps__bother_004`
  - `mh_y_pps__bother_005`
  - `mh_y_pps__bother_006`
  - `mh_y_pps__bother_007`
  - `mh_y_pps__bother_008`
  - `mh_y_pps__bother_009`
  - `mh_y_pps__bother_010`
  - `mh_y_pps__bother_011`
  - `mh_y_pps__bother_012`
  - `mh_y_pps__bother_013`
  - `mh_y_pps__bother_014`
  - `mh_y_pps__bother_015`
  - `mh_y_pps__bother_016`
  - `mh_y_pps__bother_017`
  - `mh_y_pps__bother_018`
  - `mh_y_pps__bother_019`
  - `mh_y_pps__bother_020`
  - `mh_y_pps__bother_021`
- *Excluded values:* none
- *Validation criterion:* 0 of 21 items missing

Usage

```
compute_mh_y_pps__bother__yes_count(
  data,
  name = "mh_y_pps__bother__yes_count",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Details

The bother count is depend on the mh_y_pps__bother_nm score. If the mh_y_pps__bother_nm score is greater than max_na, the bother count is set to NA.

There is also a sanity check for the gating question in PPS bother score. If the paired gating question is 0 or NA and the bother score is not missing, the paired bother score is set to NA before computing the count.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_y_pps__bother_nm()

Examples

```
## Not run:
compute_mh_y_pps__bother__yes_count(data) |>
  select(
    any_of(c("mh_y_pps__bother__yes_count", vars_mh_y_pps__bother))
  )

## End(Not run)
```

---

compute_mh_y_pps__dist__curr_score

Compute "Prodromal Psychosis Scale [Youth] (Current Distress Score)"

Description

Computes the summary score mh_y_pps__dist__curr_score Prodromal Psychosis Scale [Youth] (Current Distress Score)

For the current wave, if z-score of mh_y_pps__severity_score normalized across all current participants in the assessment wave is >= 1.96, set the value to "1"; else set the value to "0". If there is no score for the current assessment wave,set the value to NA (missing).

- *Summarized variables:*
  - mh_y_pps__severity_score (intermediate score)
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
compute_mh_y_pps__dist__curr_score(
  data,
  name = "mh_y_pps__dist__curr_score",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_pps__severity_score()

---

compute_mh_y_pps__dist__pers_score

Compute "Prodromal Psychosis Scale [Youth] (Persistent Distress Score)"

Description

Computes the summary score mh_y_pps__dist__pers_score Prodromal Psychosis Scale [Youth] (Persistent Distress Score)

For the last 3 consecutive waves (this wave, prior annual wave, and the wave before that), if 2 or more waves have a mh_y_pps__dist__curr_score of "1", then score is "1", else "0"; if more than 1 NA values in the last 3 waves, then score is NA.

The persistent flag is derived from a padded annual timeline per participant. Missing annual visits between observed sessions are treated as NA, so each observed session evaluates the current wave plus the two immediately preceding annual slots, even if data were not collected for one of those visits. The special case where both ses-00A and ses-01A meet the threshold (1) is also treated as persistent at ses-01A.

- *Summarized variables:*
  - mh_y_pps__dist__curr_score (intermediate score)
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
compute_mh_y_pps__dist__pers_score(
  data,
  name = "mh_y_pps__dist__pers_score",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_pps__dist__curr_score()

---

compute_mh_y_pps__severity_mean

Compute "Prodromal Psychosis Scale [Youth] (Severity Score): Mean"

Description

Computes the summary score mh_y_pps__severity_mean Prodromal Psychosis Scale [Youth] (Severity Score): Mean

- *Summarized variables:*
  - mh_y_pps_001
  - mh_y_pps_002
  - mh_y_pps_003
  - mh_y_pps_004
  - mh_y_pps_005

  - mh_y_pps_006
  - mh_y_pps_007
  - mh_y_pps_008
  - mh_y_pps_009
  - mh_y_pps_010
  - mh_y_pps_011
  - mh_y_pps_012
  - mh_y_pps_013
  - mh_y_pps_014
  - mh_y_pps_015
  - mh_y_pps_016
  - mh_y_pps_017
  - mh_y_pps_018
  - mh_y_pps_019
  - mh_y_pps_020
  - mh_y_pps_021
  - mh_y_pps__severity_001
  - mh_y_pps__severity_002
  - mh_y_pps__severity_003
  - mh_y_pps__severity_004
  - mh_y_pps__severity_005
  - mh_y_pps__severity_006
  - mh_y_pps__severity_007
  - mh_y_pps__severity_008
  - mh_y_pps__severity_009
  - mh_y_pps__severity_010
  - mh_y_pps__severity_011
  - mh_y_pps__severity_012
  - mh_y_pps__severity_013
  - mh_y_pps__severity_014
  - mh_y_pps__severity_015
  - mh_y_pps__severity_016
  - mh_y_pps__severity_017
  - mh_y_pps__severity_018
  - mh_y_pps__severity_019
  - mh_y_pps__severity_020
  - mh_y_pps__severity_021

- *Excluded values:* none
- *Validation criterion:* none of 21 items missing

Usage

```
compute_mh_y_pps__severity_mean(
  data,
  name = "mh_y_pps__severity_mean",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Details

The mean severity score is calculated by dividing the total severity score by the number of mh_y_pps__bother__yes_count. If any of the two values is missing, the mean severity score is set to NA.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_y_pps__bother__yes_count()

Examples

```
## Not run:
compute_mh_y_pps__severity_mean(data) |>
  select(
    any_of(c("mh_y_pps__severity_mean", vars_mh_y_pps__severity))
  )

## End(Not run)
```

`compute_mh_y_pps__severity_score`
Compute "Prodromal Psychosis Scale [Youth] (Severity Score)"

Description

Computes the summary score `mh_y_pps__severity_score` Prodromal Psychosis Scale [Youth] (Severity Score)

- *Summarized variables:*
  - `mh_y_pps__severity_001`
  - `mh_y_pps__severity_002`
  - `mh_y_pps__severity_003`
  - `mh_y_pps__severity_004`
  - `mh_y_pps__severity_005`
  - `mh_y_pps__severity_006`
  - `mh_y_pps__severity_007`
  - `mh_y_pps__severity_008`
  - `mh_y_pps__severity_009`
  - `mh_y_pps__severity_010`
  - `mh_y_pps__severity_011`
  - `mh_y_pps__severity_012`
  - `mh_y_pps__severity_013`
  - `mh_y_pps__severity_014`
  - `mh_y_pps__severity_015`
  - `mh_y_pps__severity_016`
  - `mh_y_pps__severity_017`
  - `mh_y_pps__severity_018`
  - `mh_y_pps__severity_019`
  - `mh_y_pps__severity_020`
  - `mh_y_pps__severity_021`
- *Excluded values:* none
- *Validation criterion:* none of 21 items missing

Usage

```
compute_mh_y_pps__severity_score(
  data,
  name = "mh_y_pps__severity_score",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Details

The severity score is calculated by summing the severity scores for each question and adding the number of mh_y_pps__bother__yes_count to the total.

However, if the mh_y_pps__severity_nm score is greater than max_na, the severity score is set to NA.

There is also a sanity check for the gating question of PPS base/bother score. If the paired base/bother question is 0 or NA and the severity score is not missing, the paired severity score is set to NA before computing the score.

Value

tbl. see combine.

See Also

compute_mh_y_pps__bother__yes_count()

Examples

```
## Not run:
compute_mh_y_pps__severity_score(data) |>
  select(
    any_of(c("mh_y_pps__severity_score", vars_mh_y_pps__severity))
  ) |>
  View()

## End(Not run)
```

---

compute_mh_y_pps_all *Compute all PPS scores*

Description

This super function computes all scores in PPS using all the **default** arguments.

Usage

```
compute_mh_y_pps_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Details

Make sure the data is the full set of all variables from PPS

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_pps_all(data)

## End(Not run)
```

---

compute_mh_y_pps_nm *Compute "Prodromal Psychosis Scale [Youth] (number of responses): Number missing "*

Description

Computes the summary score mh_y_pps_nm Prodromal Psychosis Scale [Youth] (number of responses): Number missing

- *Summarized variables:*
  - mh_y_pps_001
  - mh_y_pps_002
  - mh_y_pps_003
  - mh_y_pps_004
  - mh_y_pps_005
  - mh_y_pps_006
  - mh_y_pps_007
  - mh_y_pps_008
  - mh_y_pps_009
  - mh_y_pps_010
  - mh_y_pps_011
  - mh_y_pps_012
  - mh_y_pps_013

- mh_y_pps_014
- mh_y_pps_015
- mh_y_pps_016
- mh_y_pps_017
- mh_y_pps_018
- mh_y_pps_019
- mh_y_pps_020
- mh_y_pps_021

Usage

```
compute_mh_y_pps_nm(data, name = "mh_y_pps_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_mh_y_pps_count()

Examples

```
## Not run:
compute_mh_y_pps_nm(data) |>
  select(
    any_of(c("mh_y_pps_nm", vars_mh_y_pps_count))
  )

## End(Not run)
```

`compute_mh_y_ppsss__dist__curr_count` *Compute "Prodromal Psychosis Scale [Youth] (Current Distress Count)"*

Description

Computes the summary score `mh_y_ppsss__dist__curr_count` Prodromal Psychosis Scale [Youth] (Current Distress Count): Number of times criteria met.

This function creates a static variable from longitudinal data.

- *Summarized variables:*
  - mh_y_pps__dist__curr_score (intermediate score)
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
compute_mh_y_ppsss__dist__curr_count(
  data,
  name = "mh_y_ppsss__dist__curr_count"
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.

Value

a tibble of the `participant_id` column and the new static column

See Also

`compute_mh_y_pps__dist__curr_score()`

`compute_mh_y_ppsss__dist__curr_ever`
Compute "Static Prodromal Psychosis Scale [Youth] (Current Distress Ever)"

Description

Static Prodromal Psychosis Scale [Youth] (Current Distress Ever): Indicates if criteria ever met

This function creates a static variable from longitudinal data.

- *Summarized variables:*
  - mh_y_pps__dist__curr_score (intermediate score)
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
compute_mh_y_ppsss__dist__curr_ever(data, name = "mh_y_ppsss__dist__curr_ever")
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.

Value

a tibble of the `participant_id` column and the new static column

See Also

`compute_mh_y_pps__dist__curr_score()`

`compute_mh_y_ppsss__dist__curr_first`
Compute "Static Prodromal Psychosis Scale [Youth] (First Current Distress)"

Description

Static Prodromal Psychosis Scale [Youth] (First Current Distress): Session when criteria first met

This function creates a static variable from longitudinal data.

- *Summarized variables:*
  - mh_y_pps__dist__curr_score (intermediate score)
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
compute_mh_y_ppsss__dist__curr_first(
  data,
  name = "mh_y_ppsss__dist__curr_first"
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.

Value

a tibble of the participant_id column and the new static column

See Also

compute_mh_y_pps__dist__curr_score()

---

compute_mh_y_ppsss__dist__pers_count

Compute "Prodromal Psychosis Scale [Youth] (Persistent Distress Count)"

Description

Computes the summary score mh_y_ppsss__dist__pers_count Prodromal Psychosis Scale [Youth] (Persistent Distress Count): Number of times criteria met

This function creates a static variable from longitudinal data.

- *Summarized variables:*
  - mh_y_pps__dist__pers_score (intermediate score)
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
compute_mh_y_ppsss__dist__pers_count(
  data,
  name = "mh_y_ppsss__dist__pers_count"
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.

Value

a tibble of the participant_id column and the new static column

See Also

compute_mh_y_pps__dist__pers_score()

---

compute_mh_y_ppsss__dist__pers_ever

Compute "Static Prodromal Psychosis Scale [Youth] (Persistent Distress Ever)"

Description

Static Prodromal Psychosis Scale [Youth] (Persistent Distress Ever): Indicates if criteria ever met

- *Summarized variables:*
  - mh_y_pps__dist__pers_score (intermediate score)
- *Excluded values:* none
- *Validation criterion:* none

This function creates a static variable from longitudinal data.

Usage

```
compute_mh_y_ppsss__dist__pers_ever(data, name = "mh_y_ppsss__dist__pers_ever")
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.

Value

a tibble of the participant_id column and the new static column

See Also

compute_mh_y_pps__dist__pers_score()

`compute_mh_y_ppsss__dist__pers_first` *Compute "Prodromal Psychosis Scale [Youth] (First Persistent Distress)"*

Description

Static Prodromal Psychosis Scale [Youth] (First Persistent Distress): Session when criteria first met

- *Summarized variables:*
  - mh_y_pps__dist__pers_score (intermediate score)
- *Excluded values:* none
- *Validation criterion:* none

This function creates a static variable from longitudinal data.

Usage

```
compute_mh_y_ppsss__dist__pers_first(
  data,
  name = "mh_y_ppsss__dist__pers_first"
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.

Value

a tibble of the `participant_id` column and the new static column

See Also

`compute_mh_y_pps__dist__pers_score()`

compute_mh_y_ppsss_all *Compute all the mh_y_ppsss scores*

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_mh_y_ppsss_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

a tibble of the participant_id column and the new static columns

compute_mh_y_sup_all *Compute all summary scores for mh_y_sup.*

Description

This function computes all summary scores for the mh_y_sup table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_sup_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_sup_all(data)

## End(Not run)
```

`compute_mh_y_sup_sum` *Compute "7-Up Mania Inventory [Youth]: Sum"*

Description

Computes the summary score `mh_y_sup_sum` 7-Up Mania Inventory [Youth]: Sum

- *Summarized variables:*
  - `mh_y_sup_001`
  - `mh_y_sup_002`
  - `mh_y_sup_003`
  - `mh_y_sup_004`
  - `mh_y_sup_005`
  - `mh_y_sup_006`
  - `mh_y_sup_007`
- *Excluded values:* none
- *Validation criterion:* none of 7 items missing

Usage

```
compute_mh_y_sup_sum(
  data,
  name = "mh_y_sup_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

compute_mh_y_sup_nm()

Examples

```
## Not run:
compute_mh_y_sup_sum(data) |>
  select(
    any_of(c("mh_y_sup_sum", vars_mh_y_sup))
  )

## End(Not run)
```

---

compute_mh_y_upps__nurg_sum

Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Negative Urgency): Sum"

Description

Computes the summary score mh_y_upps__nurg_sum Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Negative Urgency): Sum

- *Summarized variables:*
  - mh_y_upps__nurg_001
  - mh_y_upps__nurg_002
  - mh_y_upps__nurg_003
  - mh_y_upps__nurg_004
- *Excluded values:* none
- *Validation criterion:* none of 4 items missing

Usage

```
compute_mh_y_upps__nurg_sum(
  data,
  name = "mh_y_upps__nurg_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_upps__nurg_nm()

Examples

```
## Not run:
compute_mh_y_upps__nurg_sum(data) |>
  select(
    any_of(c("mh_y_upps__nurg_sum", vars_mh_y_upps__nurg))
  )

## End(Not run)
```

---

compute_mh_y_upps__pers_sum

Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Lack of Perseverance (GSSF)): Sum"

Description

Computes the summary score mh_y_upps__pers_sum Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Lack of Perseverance (GSSF)): Sum

- *Summarized variables:*
  - mh_y_upps__pers_001
  - mh_y_upps__pers_002
  - mh_y_upps__pers_003
  - mh_y_upps__pers_004
- *Excluded values:* none
- *Validation criterion:* none of 4 items missing

Usage

```
compute_mh_y_upps__pers_sum(
  data,
  name = "mh_y_upps__pers_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_upps__pers_nm()

Examples

```
## Not run:
compute_mh_y_upps__pers_sum(data) |>
  select(
    any_of(c("mh_y_upps__pers_sum", vars_mh_y_upps__pers))
  )

## End(Not run)
```

---

compute_mh_y_upps__plan_sum

Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Lack of Planning): Sum"

Description

Computes the summary score mh_y_upps__plan_sum Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Lack of Planning): Sum

- *Summarized variables:*
  - mh_y_upps__plan_001
  - mh_y_upps__plan_002
  - mh_y_upps__plan_003
  - mh_y_upps__plan_004
- *Excluded values:* none
- *Validation criterion:* none of 4 items missing

Usage

```
compute_mh_y_upps__plan_sum(
  data,
  name = "mh_y_upps__plan_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_upps__plan_nm()

Examples

```
## Not run:
compute_mh_y_upps__plan_sum(data) |>
  select(
    any_of(c("mh_y_upps__plan_sum", vars_mh_y_upps__plan))
  )

## End(Not run)
```

`compute_mh_y_upps__purg_sum`

Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Positive Urgency): Sum"

Description

Computes the summary score `mh_y_upps__purg_sum` Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Positive Urgency): Sum

- *Summarized variables:*
  - `mh_y_upps__purg_001`
  - `mh_y_upps__purg_002`
  - `mh_y_upps__purg_003`
  - `mh_y_upps__purg_004`
- *Excluded values:* none
- *Validation criterion:* none of 4 items missing

Usage

```
compute_mh_y_upps__purg_sum(
  data,
  name = "mh_y_upps__purg_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.

exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_upps__purg_nm()

Examples

```
## Not run:
compute_mh_y_upps__purg_sum(data) |>
  select(
    any_of(c("mh_y_upps__purg_sum", vars_mh_y_upps__purg))
  )

## End(Not run)
```

---

compute_mh_y_upps__sens_sum

Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Sensation Seeking): Sum"

Description

Computes the summary score mh_y_upps__sens_sum Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Sensation Seeking): Sum

- *Summarized variables:*
  - mh_y_upps__sens_001
  - mh_y_upps__sens_002
  - mh_y_upps__sens_003
  - mh_y_upps__sens_004
- *Excluded values:* none
- *Validation criterion:* none of 4 items missing

Usage

```
compute_mh_y_upps__sens_sum(
  data,
  name = "mh_y_upps__sens_sum",
  max_na = 0,
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_upps__sens_nm()

Examples

```
## Not run:
compute_mh_y_upps__sens_sum(data) |>
  select(
    any_of(c("mh_y_upps__sens_sum", vars_mh_y_upps__sens))
  )

## End(Not run)
```

---

compute_mh_y_upps_all *Compute all summary scores for mh_y_upps.*

Description

This function computes all summary scores for the mh_y_upps table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_upps_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_upps_all(data)

## End(Not run)
```

---

compute_mh_y_ysr__dsm__adhd_sum

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - ADHD): Sum"

Description

Computes the summary score `mh_y_ysr__dsm__adhd_sum` Youth Self Report [Youth] (DSM-5 Oriented Scale - ADHD): Sum

- *Summarized variables:*
  - `mh_y_ysr__attn__adhd_001`
  - `mh_y_ysr__attn__adhd_002`
  - `mh_y_ysr__attn__adhd_003`
  - `mh_y_ysr__attn__adhd_004`
  - `mh_y_ysr__attn__adhd_005`
  - `mh_y_ysr__othpr__adhd_001`
  - `mh_y_ysr__aggr__adhd_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 7 items missing

Usage

```
compute_mh_y_ysr__dsm__adhd_sum(
  data,
  name = "mh_y_ysr__dsm__adhd_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__adhd_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__adhd_sum(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__adhd_sum", vars_mh_y_ysr__dsm__adhd))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__adhd_tscore

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - ADHD): T-score"

Description

Computes the summary score mh_y_ysr__dsm__adhd_tscore Youth Self Report [Youth] (DSM-5 Oriented Scale - ADHD): T-score

- *Summarized variables:*
  - mh_y_ysr__attn__adhd_001
  - mh_y_ysr__attn__adhd_002
  - mh_y_ysr__attn__adhd_003
  - mh_y_ysr__attn__adhd_004
  - mh_y_ysr__attn__adhd_005
  - mh_y_ysr__othpr__adhd_001
  - mh_y_ysr__aggr__adhd_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 7 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__dsm__adhd_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__dsm__adhd_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__adhd_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__adhd_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__adhd_tscore", vars_mh_y_ysr__dsm__adhd))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__anx_sum

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Anxiety problems): Sum"

Description

Computes the summary score mh_y_ysr__dsm__anx_sum Youth Self Report [Youth] (DSM-5 Oriented Scale - Anxiety problems): Sum

- *Summarized variables:*
  - mh_y_ysr__soc__anx_001
  - mh_y_ysr__anxdep__anx_001
  - mh_y_ysr__anxdep__anx_002
  - mh_y_ysr__anxdep__anx_003
  - mh_y_ysr__anxdep__anx_004
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__anxdep__anx_005
  - mh_y_ysr__anxdep__anx_006
  - mh_y_ysr__anxdep__anx_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
compute_mh_y_ysr__dsm__anx_sum(
  data,
  name = "mh_y_ysr__dsm__anx_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__anx_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__anx_sum(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__anx_sum", vars_mh_y_ysr__dsm__anx))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__anx_tscore

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Anxiety problems): T-score"

Description

Computes the summary score mh_y_ysr__dsm__anx_tscore Youth Self Report [Youth] (DSM-5 Oriented Scale - Anxiety problems): T-score

- *Summarized variables:*
  - mh_y_ysr__soc__anx_001
  - mh_y_ysr__anxdep__anx_001
  - mh_y_ysr__anxdep__anx_002
  - mh_y_ysr__anxdep__anx_003
  - mh_y_ysr__anxdep__anx_004
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__anxdep__anx_005
  - mh_y_ysr__anxdep__anx_006
  - mh_y_ysr__anxdep__anx_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__dsm__anx_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__dsm__anx_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__anx_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__anx_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__anx_tscore", vars_mh_y_ysr__dsm__anx))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__cond_sum

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Conduct problems): Sum"

Description

Computes the summary score mh_y_ysr__dsm__cond_sum Youth Self Report [Youth] (DSM-5 Oriented Scale - Conduct problems): Sum

- *Summarized variables:*
  - mh_y_ysr__aggr__cond_001
  - mh_y_ysr__aggr__cond_002
  - mh_y_ysr__rule__cond_001
  - mh_y_ysr__rule__cond_002
  - mh_y_ysr__aggr__cond_003
  - mh_y_ysr__rule__cond_003
  - mh_y_ysr__rule__cond_004
  - mh_y_ysr__aggr__cond_004
  - mh_y_ysr__rule__cond_005
  - mh_y_ysr__rule__cond_006
  - mh_y_ysr__rule__cond_007
  - mh_y_ysr__rule__cond_008
  - mh_y_ysr__rule__cond_009
  - mh_y_ysr__aggr__cond_005
  - mh_y_ysr__rule__cond_010
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
compute_mh_y_ysr__dsm__cond_sum(
  data,
  name = "mh_y_ysr__dsm__cond_sum",
  max_na = 3,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__cond_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__cond_sum(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__cond_sum", vars_mh_y_ysr__dsm__cond))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__cond_tscore

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Conduct problems): T-score"

Description

Computes the summary score `mh_y_ysr__dsm__cond_tscore` Youth Self Report [Youth] (DSM-5 Oriented Scale - Conduct problems): T-score

- *Summarized variables:*
  - `mh_y_ysr__aggr__cond_001`
  - `mh_y_ysr__aggr__cond_002`
  - `mh_y_ysr__rule__cond_001`
  - `mh_y_ysr__rule__cond_002`
  - `mh_y_ysr__aggr__cond_003`
  - `mh_y_ysr__rule__cond_003`
  - `mh_y_ysr__rule__cond_004`
  - `mh_y_ysr__aggr__cond_004`
  - `mh_y_ysr__rule__cond_005`
  - `mh_y_ysr__rule__cond_006`
  - `mh_y_ysr__rule__cond_007`
  - `mh_y_ysr__rule__cond_008`
  - `mh_y_ysr__rule__cond_009`
  - `mh_y_ysr__aggr__cond_005`
  - `mh_y_ysr__rule__cond_010`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 3 of 15 items missing or `mh_y_ysr__dsm__adhd_nm` <= 5

Usage

```
compute_mh_y_ysr__dsm__cond_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__dsm__cond_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 3,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.
`name`	character. Name of the summary score column.
`col_age`	character, name of the age column. see `ss_tscore()`.

col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__cond_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__cond_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__cond_tscore", vars_mh_y_ysr__dsm__cond))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__dep_sum

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Depressive problems): Sum"

Description

Computes the summary score mh_y_ysr__dsm__dep_sum Youth Self Report [Youth] (DSM-5 Oriented Scale - Depressive problems): Sum

- *Summarized variables:*
  - mh_y_ysr__wthdep__dep_001
  - mh_y_ysr__anxdep__dep_001
  - mh_y_ysr__othpr__dep_001
  - mh_y_ysr__anxdep__dep_002
  - mh_y_ysr__anxdep__dep_003
  - mh_y_ysr__som__dep_001
  - mh_y_ysr__tho__dep_002
  - mh_y_ysr__othpr__dep_002
  - mh_y_ysr__tho__dep_003

  - mh_y_ysr__wthdep__dep_002
  - mh_y_ysr__wthdep__dep_003
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 11 items missing

Usage

```
compute_mh_y_ysr__dsm__dep_sum(
  data,
  name = "mh_y_ysr__dsm__dep_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__dep_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__dep_sum(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__dep_sum", vars_mh_y_ysr__dsm__dep))
  )

## End(Not run)
```

`compute_mh_y_ysr__dsm__dep_tscore` *Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Depressive problems): T-score"*

Description

Computes the summary score `mh_y_ysr__dsm__dep_tscore` Youth Self Report [Youth] (DSM-5 Oriented Scale - Depressive problems): T-score

- *Summarized variables:*
  - `mh_y_ysr__wthdep__dep_001`
  - `mh_y_ysr__anxdep__dep_001`
  - `mh_y_ysr__othpr__dep_001`
  - `mh_y_ysr__anxdep__dep_002`
  - `mh_y_ysr__anxdep__dep_003`
  - `mh_y_ysr__som__dep_001`
  - `mh_y_ysr__tho__dep_002`
  - `mh_y_ysr__othpr__dep_002`
  - `mh_y_ysr__tho__dep_003`
  - `mh_y_ysr__wthdep__dep_002`
  - `mh_y_ysr__wthdep__dep_003`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 11 items missing or `mh_y_ysr__dsm__adhd_nm` <= 5

Usage

```
compute_mh_y_ysr__dsm__dep_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__dsm__dep_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.

name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__dep_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__dep_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__dep_tscore", vars_mh_y_ysr__dsm__dep))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__opp_sum

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Oppositional Defiant problems): Sum"

Description

Computes the summary score mh_y_ysr__dsm__opp_sum Youth Self Report [Youth] (DSM-5 Oriented Scale - Oppositional Defiant problems): Sum

- *Summarized variables:*
  - mh_y_ysr__aggr__opp_001
  - mh_y_ysr__aggr__opp_002
  - mh_y_ysr__aggr__opp_003
  - mh_y_ysr__aggr__opp_004
  - mh_y_ysr__aggr__opp_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
compute_mh_y_ysr__dsm__opp_sum(
  data,
  name = "mh_y_ysr__dsm__opp_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__opp_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__opp_sum(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__opp_sum", vars_mh_y_ysr__dsm__opp))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__opp_tscore

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Oppositional Defiant problems): T-score"

Description

Computes the summary score mh_y_ysr__dsm__opp_tscore Youth Self Report [Youth] (DSM-5 Oriented Scale - Oppositional Defiant problems): T-score

- *Summarized variables:*
  - mh_y_ysr__aggr__opp_001
  - mh_y_ysr__aggr__opp_002
  - mh_y_ysr__aggr__opp_003
  - mh_y_ysr__aggr__opp_004
  - mh_y_ysr__aggr__opp_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 5 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__dsm__opp_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__dsm__opp_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__opp_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__opp_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__opp_tscore", vars_mh_y_ysr__dsm__opp))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__somat_sum

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Somatic complaints): Sum"

Description

Computes the summary score mh_y_ysr__dsm__somat_sum Youth Self Report [Youth] (DSM-5 Oriented Scale - Somatic complaints): Sum

- *Summarized variables:*
  - mh_y_ysr__som__somat_001
  - mh_y_ysr__som__somat_002
  - mh_y_ysr__som__somat_003
  - mh_y_ysr__som__somat_004
  - mh_y_ysr__som__somat_005
  - mh_y_ysr__som__somat_006
  - mh_y_ysr__som__somat_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
compute_mh_y_ysr__dsm__somat_sum(
  data,
  name = "mh_y_ysr__dsm__somat_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__somat_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__somat_sum(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__somat_sum", vars_mh_y_ysr__dsm__somat))
  )

## End(Not run)
```

---

compute_mh_y_ysr__dsm__somat_tscore

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Somatic complaints): T-score"

Description

Computes the summary score mh_y_ysr__dsm__somat_tscore Youth Self Report [Youth] (DSM-5 Oriented Scale - Somatic complaints): T-score

- *Summarized variables:*
  - mh_y_ysr__som__somat_001
  - mh_y_ysr__som__somat_002
  - mh_y_ysr__som__somat_003
  - mh_y_ysr__som__somat_004
  - mh_y_ysr__som__somat_005
  - mh_y_ysr__som__somat_006

  - mh_y_ysr__som__somat_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 7 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__dsm__somat_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__dsm__somat_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__dsm__somat_nm()

Examples

```
## Not run:
compute_mh_y_ysr__dsm__somat_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__somat_tscore", vars_mh_y_ysr__dsm__somat))
```

```
  )

## End(Not run)
```

`compute_mh_y_ysr__pos_sum`
Compute "Youth Self Report [Youth] (Positive): Sum"

Description

Computes the summary score `mh_y_ysr__pos_sum` Youth Self Report [Youth] (Positive): Sum

- *Summarized variables:*
  - `mh_y_ysr__pos_001`
  - `mh_y_ysr__pos_002`
  - `mh_y_ysr__pos_003`
  - `mh_y_ysr__pos_004`
  - `mh_y_ysr__pos_005`
  - `mh_y_ysr__pos_006`
  - `mh_y_ysr__pos_007`
  - `mh_y_ysr__pos_008`
  - `mh_y_ysr__pos_009`
  - `mh_y_ysr__pos_010`
  - `mh_y_ysr__pos_011`
  - `mh_y_ysr__pos_012`
  - `mh_y_ysr__pos_013`
  - `mh_y_ysr__pos_014`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
compute_mh_y_ysr__pos_sum(
  data,
  name = "mh_y_ysr__pos_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__pos_nm()

Examples

```
## Not run:
compute_mh_y_ysr__pos_sum(data) |>
  select(
    any_of(c("mh_y_ysr__pos_sum", vars_mh_y_ysr__pos))
  )

## End(Not run)
```

---

compute_mh_y_ysr__pos_tscore

Compute "Youth Self Report [Youth] (Positive): T-score"

Description

Computes the summary score mh_y_ysr__pos_tscore Youth Self Report [Youth] (Positive): T-score

- *Summarized variables:*
  - mh_y_ysr__pos_001
  - mh_y_ysr__pos_002
  - mh_y_ysr__pos_003
  - mh_y_ysr__pos_004
  - mh_y_ysr__pos_005
  - mh_y_ysr__pos_006
  - mh_y_ysr__pos_007

  - mh_y_ysr__pos_008
  - mh_y_ysr__pos_009
  - mh_y_ysr__pos_010
  - mh_y_ysr__pos_011
  - mh_y_ysr__pos_012
  - mh_y_ysr__pos_013
  - mh_y_ysr__pos_014
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 14 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__pos_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__pos_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__pos_nm()

Examples

```
## Not run:
compute_mh_y_ysr__pos_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__pos_tscore", vars_mh_y_ysr__pos))
  )

## End(Not run)
```

`compute_mh_y_ysr__synd__aggr_sum`
Compute "Youth Self Report [Youth] (Syndrome Scale - Aggressive behavior): Sum"

Description

Computes the summary score `mh_y_ysr__synd__aggr_sum` Youth Self Report [Youth] (Syndrome Scale - Aggressive behavior): Sum

- *Summarized variables:*
  - `mh_y_ysr__aggr__opp_001`
  - `mh_y_ysr__aggr__cond_001`
  - `mh_y_ysr__aggr_001`
  - `mh_y_ysr__aggr_002`
  - `mh_y_ysr__aggr__cond_002`
  - `mh_y_ysr__aggr__opp_002`
  - `mh_y_ysr__aggr__opp_003`
  - `mh_y_ysr__aggr__cond_003`
  - `mh_y_ysr__aggr__cond_004`
  - `mh_y_ysr__aggr_003`
  - `mh_y_ysr__aggr__opp_004`
  - `mh_y_ysr__aggr_004`
  - `mh_y_ysr__aggr_005`
  - `mh_y_ysr__aggr_006`
  - `mh_y_ysr__aggr__opp_005`
  - `mh_y_ysr__aggr__cond_005`
  - `mh_y_ysr__aggr__adhd_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 3 of 17 items missing

Usage

```
compute_mh_y_ysr__synd__aggr_sum(
  data,
  name = "mh_y_ysr__synd__aggr_sum",
  max_na = 3,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__aggr_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__aggr_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__aggr_sum", vars_mh_y_ysr__synd__aggr))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__aggr_tscore

Compute "Youth Self Report [Youth] (Syndrome Scale - Aggressive): T-score"

Description

Computes the summary score `mh_y_ysr__synd__aggr_tscore` Youth Self Report [Youth] (Syndrome Scale - Aggressive): T-score

- *Summarized variables:*
  - `mh_y_ysr__aggr__opp_001`
  - `mh_y_ysr__aggr__cond_001`
  - `mh_y_ysr__aggr_001`
  - `mh_y_ysr__aggr_002`
  - `mh_y_ysr__aggr__cond_002`
  - `mh_y_ysr__aggr__opp_002`
  - `mh_y_ysr__aggr__opp_003`
  - `mh_y_ysr__aggr__cond_003`
  - `mh_y_ysr__aggr__cond_004`
  - `mh_y_ysr__aggr_003`
  - `mh_y_ysr__aggr__opp_004`
  - `mh_y_ysr__aggr_004`
  - `mh_y_ysr__aggr_005`
  - `mh_y_ysr__aggr_006`
  - `mh_y_ysr__aggr__opp_005`
  - `mh_y_ysr__aggr__cond_005`
  - `mh_y_ysr__aggr__adhd_001`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 3 of 17 items missing or `mh_y_ysr__dsm__adhd_nm` <= 5

Usage

```
compute_mh_y_ysr__synd__aggr_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__aggr_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 3,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`data_norm`	tbl. Data frame containing the norm (T-score) values. see `ss_tscore()`.

name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__aggr_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__aggr_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__aggr_tscore", vars_mh_y_ysr__synd__aggr))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__anxdep_sum

Compute "Youth Self Report [Youth] (Syndrome Scale - Anxious/Depressed): Sum"

Description

Computes the summary score mh_y_ysr__synd__anxdep_sum Youth Self Report [Youth] (Syndrome Scale - Anxious/Depressed): Sum

- *Summarized variables:*
  - mh_y_ysr__anxdep__dep_001
  - mh_y_ysr__anxdep__anx_001
  - mh_y_ysr__anxdep__anx_002
  - mh_y_ysr__anxdep__anx_003
  - mh_y_ysr__anxdep_001
  - mh_y_ysr__anxdep_002

  - mh_y_ysr__anxdep__dep_002
  - mh_y_ysr__anxdep__anx_004
  - mh_y_ysr__anxdep__anx_005
  - mh_y_ysr__anxdep__dep_003
  - mh_y_ysr__anxdep__anx_006
  - mh_y_ysr__anxdep__anx_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 12 items missing

Usage

```
compute_mh_y_ysr__synd__anxdep_sum(
  data,
  name = "mh_y_ysr__synd__anxdep_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__anxdep_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__anxdep_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__anxdep_sum", vars_mh_y_ysr__synd__anxdep))
  )
```

```
## End(Not run)
```

`compute_mh_y_ysr__synd__anxdep_tscore`
Compute "Youth Self Report [Youth] (Syndrome Scale - Anxious/Depressed): T-score"

Description

Computes the summary score `mh_y_ysr__synd__anxdep_tscore` Youth Self Report [Youth] (Syndrome Scale - Anxious/Depressed): T-score

- *Summarized variables:*
  - `mh_y_ysr__anxdep__dep_001`
  - `mh_y_ysr__anxdep__anx_001`
  - `mh_y_ysr__anxdep__anx_002`
  - `mh_y_ysr__anxdep__anx_003`
  - `mh_y_ysr__anxdep_001`
  - `mh_y_ysr__anxdep_002`
  - `mh_y_ysr__anxdep__dep_002`
  - `mh_y_ysr__anxdep__anx_004`
  - `mh_y_ysr__anxdep__anx_005`
  - `mh_y_ysr__anxdep__dep_003`
  - `mh_y_ysr__anxdep__anx_006`
  - `mh_y_ysr__anxdep__anx_007`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 12 items missing or `mh_y_ysr__dsm__adhd_nm` <= 5

Usage

```
compute_mh_y_ysr__synd__anxdep_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__anxdep_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__anxdep_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__anxdep_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__anxdep_tscore", vars_mh_y_ysr__synd__anxdep))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__attn_sum

Compute "Youth Self Report [Youth] (Syndrome Scale - Attention problems): Sum"

Description

Computes the summary score mh_y_ysr__synd__attn_sum Youth Self Report [Youth] (Syndrome Scale - Attention problems): Sum

- *Summarized variables:*
  - mh_y_ysr__attn_001
  - mh_y_ysr__attn__adhd_001
  - mh_y_ysr__attn__adhd_002

  - mh_y_ysr__attn__adhd_003
  - mh_y_ysr__attn_002
  - mh_y_ysr__attn_003
  - mh_y_ysr__attn__adhd_004
  - mh_y_ysr__attn_004
  - mh_y_ysr__attn__adhd_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
compute_mh_y_ysr__synd__attn_sum(
  data,
  name = "mh_y_ysr__synd__attn_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__attn_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__attn_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__attn_sum", vars_mh_y_ysr__synd__attn))
  )
```

```
## End(Not run)
```

`compute_mh_y_ysr__synd__attn_tscore`
Compute "Youth Self Report [Youth] (Syndrome Scale - Attention problems): T-score"

Description

Computes the summary score `mh_y_ysr__synd__attn_tscore` Youth Self Report [Youth] (Syndrome Scale - Attention problems): T-score

- *Summarized variables:*
  - `mh_y_ysr__attn_001`
  - `mh_y_ysr__attn__adhd_001`
  - `mh_y_ysr__attn__adhd_002`
  - `mh_y_ysr__attn__adhd_003`
  - `mh_y_ysr__attn_002`
  - `mh_y_ysr__attn_003`
  - `mh_y_ysr__attn__adhd_004`
  - `mh_y_ysr__attn_004`
  - `mh_y_ysr__attn__adhd_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing or `mh_y_ysr__dsm__adhd_nm` <= 5

Usage

```
compute_mh_y_ysr__synd__attn_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__attn_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__attn_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__attn_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__attn_tscore", vars_mh_y_ysr__synd__attn))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__ext_sum

Compute "Youth Self Report [Youth] (Syndrome Scale - External): Sum"

Description

Computes the summary score mh_y_ysr__synd__ext_sum Youth Self Report [Youth] (Syndrome Scale - External): Sum

- *Summarized variables:*
  - mh_y_ysr__rule_001
  - mh_y_ysr__rule__cond_001
  - mh_y_ysr__rule__cond_002

  - mh_y_ysr__rule__cond_003
  - mh_y_ysr__rule__cond_004
  - mh_y_ysr__rule_002
  - mh_y_ysr__rule__cond_005
  - mh_y_ysr__rule__cond_006
  - mh_y_ysr__rule__cond_007
  - mh_y_ysr__rule__cond_008
  - mh_y_ysr__rule__cond_009
  - mh_y_ysr__rule_003
  - mh_y_ysr__rule_004
  - mh_y_ysr__rule__cond_010
  - mh_y_ysr__rule_005
  - mh_y_ysr__aggr__opp_001
  - mh_y_ysr__aggr__cond_001
  - mh_y_ysr__aggr_001
  - mh_y_ysr__aggr_002
  - mh_y_ysr__aggr__cond_002
  - mh_y_ysr__aggr__opp_002
  - mh_y_ysr__aggr__opp_003
  - mh_y_ysr__aggr__cond_003
  - mh_y_ysr__aggr__cond_004
  - mh_y_ysr__aggr_003
  - mh_y_ysr__aggr__opp_004
  - mh_y_ysr__aggr_004
  - mh_y_ysr__aggr_005
  - mh_y_ysr__aggr_006
  - mh_y_ysr__aggr__opp_005
  - mh_y_ysr__aggr__cond_005
  - mh_y_ysr__aggr__adhd_001

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 6 of 32 items missing

Usage

```
compute_mh_y_ysr__synd__ext_sum(
  data,
  name = "mh_y_ysr__synd__ext_sum",
  max_na = 6,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__ext_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__ext_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__ext_sum", vars_mh_y_ysr__synd__ext))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__ext_tscore

Compute "Youth Self Report [Youth] (Syndrome Scale - External): T-score"

Description

Computes the summary score mh_y_ysr__synd__ext_tscore Youth Self Report [Youth] (Syndrome Scale - External): T-score

- *Summarized variables:*
  - mh_y_ysr__rule_001
  - mh_y_ysr__rule__cond_001
  - mh_y_ysr__rule__cond_002
  - mh_y_ysr__rule__cond_003
  - mh_y_ysr__rule__cond_004
  - mh_y_ysr__rule_002

  - mh_y_ysr__rule__cond_005
  - mh_y_ysr__rule__cond_006
  - mh_y_ysr__rule__cond_007
  - mh_y_ysr__rule__cond_008
  - mh_y_ysr__rule__cond_009
  - mh_y_ysr__rule_003
  - mh_y_ysr__rule_004
  - mh_y_ysr__rule__cond_010
  - mh_y_ysr__rule_005
  - mh_y_ysr__aggr__opp_001
  - mh_y_ysr__aggr__cond_001
  - mh_y_ysr__aggr_001
  - mh_y_ysr__aggr_002
  - mh_y_ysr__aggr__cond_002
  - mh_y_ysr__aggr__opp_002
  - mh_y_ysr__aggr__opp_003
  - mh_y_ysr__aggr__cond_003
  - mh_y_ysr__aggr__cond_004
  - mh_y_ysr__aggr_003
  - mh_y_ysr__aggr__opp_004
  - mh_y_ysr__aggr_004
  - mh_y_ysr__aggr_005
  - mh_y_ysr__aggr_006
  - mh_y_ysr__aggr__opp_005
  - mh_y_ysr__aggr__cond_005
  - mh_y_ysr__aggr__adhd_001

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 6 of 32 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__synd__ext_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__ext_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 6,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__ext_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__ext_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__ext_tscore", vars_mh_y_ysr__synd__ext))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__int_sum

Compute "Youth Self Report [Youth] (Syndrome Scale - Internaling): Sum"

Description

Computes the summary score mh_y_ysr__synd__int_sum Youth Self Report [Youth] (Syndrome Scale - Internaling): Sum

- *Summarized variables:*
  - mh_y_ysr__anxdep__dep_001
  - mh_y_ysr__anxdep__anx_001
  - mh_y_ysr__anxdep__anx_002

  - mh_y_ysr__anxdep__anx_003
  - mh_y_ysr__anxdep_001
  - mh_y_ysr__anxdep_002
  - mh_y_ysr__anxdep__dep_002
  - mh_y_ysr__anxdep__anx_004
  - mh_y_ysr__anxdep__anx_005
  - mh_y_ysr__anxdep__dep_003
  - mh_y_ysr__anxdep__anx_006
  - mh_y_ysr__anxdep__anx_007
  - mh_y_ysr__wthdep__dep_001
  - mh_y_ysr__wthdep_001
  - mh_y_ysr__wthdep_002
  - mh_y_ysr__wthdep_003
  - mh_y_ysr__wthdep_004
  - mh_y_ysr__wthdep__dep_002
  - mh_y_ysr__wthdep__dep_003
  - mh_y_ysr__wthdep_005
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__som_001
  - mh_y_ysr__som__dep_001
  - mh_y_ysr__som__somat_001
  - mh_y_ysr__som__somat_002
  - mh_y_ysr__som__somat_003
  - mh_y_ysr__som__somat_004
  - mh_y_ysr__som__somat_005
  - mh_y_ysr__som__somat_006
  - mh_y_ysr__som__somat_007

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 6 of 30 items missing

Usage

```
compute_mh_y_ysr__synd__int_sum(
  data,
  name = "mh_y_ysr__synd__int_sum",
  max_na = 6,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__int_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__int_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__int_sum", vars_mh_y_ysr__synd__int))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__int_tscore

Compute "Youth Self Report [Youth] (Syndrome Scale - Internaling): T-score"

Description

Computes the summary score mh_y_ysr__synd__int_tscore Youth Self Report [Youth] (Syndrome Scale - Internaling): T-score

- *Summarized variables:*
  - mh_y_ysr__anxdep__dep_001
  - mh_y_ysr__anxdep__anx_001
  - mh_y_ysr__anxdep__anx_002
  - mh_y_ysr__anxdep__anx_003
  - mh_y_ysr__anxdep_001
  - mh_y_ysr__anxdep_002

  - mh_y_ysr__anxdep__dep_002
  - mh_y_ysr__anxdep__anx_004
  - mh_y_ysr__anxdep__anx_005
  - mh_y_ysr__anxdep__dep_003
  - mh_y_ysr__anxdep__anx_006
  - mh_y_ysr__anxdep__anx_007
  - mh_y_ysr__wthdep__dep_001
  - mh_y_ysr__wthdep_001
  - mh_y_ysr__wthdep_002
  - mh_y_ysr__wthdep_003
  - mh_y_ysr__wthdep_004
  - mh_y_ysr__wthdep__dep_002
  - mh_y_ysr__wthdep__dep_003
  - mh_y_ysr__wthdep_005
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__som_001
  - mh_y_ysr__som__dep_001
  - mh_y_ysr__som__somat_001
  - mh_y_ysr__som__somat_002
  - mh_y_ysr__som__somat_003
  - mh_y_ysr__som__somat_004
  - mh_y_ysr__som__somat_005
  - mh_y_ysr__som__somat_006
  - mh_y_ysr__som__somat_007

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 6 of 30 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__synd__int_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__int_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 6,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__int_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__int_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__int_tscore", vars_mh_y_ysr__synd__int))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__othpr_sum

Compute "Youth Self Report [Youth] (Other problems): Sum"

Description

Computes the summary score mh_y_ysr__synd__othpr_sum Youth Self Report [Youth] (Other problems): Sum

- *Summarized variables:*
  - mh_y_ysr__othpr_001
  - mh_y_ysr__othpr__dep_001
  - mh_y_ysr__othpr_002
  - mh_y_ysr__othpr_003

  - mh_y_ysr__othpr_004
  - mh_y_ysr__othpr_005
  - mh_y_ysr__othpr_006
  - mh_y_ysr__othpr__dep_002
  - mh_y_ysr__othpr__adhd_001
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
compute_mh_y_ysr__synd__othpr_sum(
  data,
  name = "mh_y_ysr__synd__othpr_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__othpr_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__othpr_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__othpr_sum", vars_mh_y_ysr__synd__othpr))
  )

## End(Not run)
```

compute_mh_y_ysr__synd__rule_sum

Compute "Youth Self Report [Youth] (Syndrome Scale - Rule breaking behavior): Sum"

Description

Computes the summary score mh_y_ysr__synd__rule_sum Youth Self Report [Youth] (Syndrome Scale - Rule breaking behavior): Sum

- *Summarized variables:*
  - mh_y_ysr__rule_001
  - mh_y_ysr__rule__cond_001
  - mh_y_ysr__rule__cond_002
  - mh_y_ysr__rule__cond_003
  - mh_y_ysr__rule__cond_004
  - mh_y_ysr__rule_002
  - mh_y_ysr__rule__cond_005
  - mh_y_ysr__rule__cond_006
  - mh_y_ysr__rule__cond_007
  - mh_y_ysr__rule__cond_008
  - mh_y_ysr__rule__cond_009
  - mh_y_ysr__rule_003
  - mh_y_ysr__rule_004
  - mh_y_ysr__rule__cond_010
  - mh_y_ysr__rule_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
compute_mh_y_ysr__synd__rule_sum(
  data,
  name = "mh_y_ysr__synd__rule_sum",
  max_na = 3,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__rule_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__rule_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__rule_sum", vars_mh_y_ysr__synd__rule))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__rule_tscore

Compute "Youth Self Report [Youth] (Syndrome Scale - Rule breaking behavior): T-score"

Description

Computes the summary score mh_y_ysr__synd__rule_tscore Youth Self Report [Youth] (Syndrome Scale - Rule breaking behavior): T-score

- *Summarized variables:*
  - mh_y_ysr__rule_001
  - mh_y_ysr__rule__cond_001
  - mh_y_ysr__rule__cond_002
  - mh_y_ysr__rule__cond_003
  - mh_y_ysr__rule__cond_004
  - mh_y_ysr__rule_002

  - mh_y_ysr__rule__cond_005
  - mh_y_ysr__rule__cond_006
  - mh_y_ysr__rule__cond_007
  - mh_y_ysr__rule__cond_008
  - mh_y_ysr__rule__cond_009
  - mh_y_ysr__rule_003
  - mh_y_ysr__rule_004
  - mh_y_ysr__rule__cond_010
  - mh_y_ysr__rule_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 3 of 15 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__synd__rule_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__rule_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 3,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__rule_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__rule_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__rule_tscore", vars_mh_y_ysr__synd__rule))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__soc_sum

Compute "Youth Self Report [Youth] (Syndrome Scale -Social problems): Sum"

Description

Computes the summary score mh_y_ysr__synd__soc_sum Youth Self Report [Youth] (Syndrome Scale -Social problems): Sum

- *Summarized variables:*
  - mh_y_ysr__soc__anx_001
  - mh_y_ysr__soc_001
  - mh_y_ysr__soc_002
  - mh_y_ysr__soc_003
  - mh_y_ysr__soc_004
  - mh_y_ysr__soc_005
  - mh_y_ysr__soc_006
  - mh_y_ysr__soc_007
  - mh_y_ysr__soc_008
  - mh_y_ysr__soc_009
  - mh_y_ysr__soc_010
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 11 items missing

Usage

```
compute_mh_y_ysr__synd__soc_sum(
  data,
  name = "mh_y_ysr__synd__soc_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__soc_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__soc_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__soc_sum", vars_mh_y_ysr__synd__soc))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__soc_tscore

Compute "Youth Self Report [Youth] (Syndrome Scale -Social): T-score"

Description

Computes the summary score mh_y_ysr__synd__soc_tscore Youth Self Report [Youth] (Syndrome Scale -Social): T-score

- *Summarized variables:*
  - mh_y_ysr__soc__anx_001
  - mh_y_ysr__soc_001
  - mh_y_ysr__soc_002
  - mh_y_ysr__soc_003
  - mh_y_ysr__soc_004
  - mh_y_ysr__soc_005
  - mh_y_ysr__soc_006
  - mh_y_ysr__soc_007
  - mh_y_ysr__soc_008
  - mh_y_ysr__soc_009
  - mh_y_ysr__soc_010
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 11 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__synd__soc_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__soc_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.

combine — logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__soc_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__soc_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__soc_tscore", vars_mh_y_ysr__synd__soc))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__som_sum

Compute "Youth Self Report [Youth] (Syndrome Scale - Somatic complaints): Sum"

Description

Computes the summary score mh_y_ysr__synd__som_sum Youth Self Report [Youth] (Syndrome Scale - Somatic complaints): Sum

- *Summarized variables:*
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__som_001
  - mh_y_ysr__som__dep_001
  - mh_y_ysr__som__somat_001
  - mh_y_ysr__som__somat_002
  - mh_y_ysr__som__somat_003
  - mh_y_ysr__som__somat_004
  - mh_y_ysr__som__somat_005
  - mh_y_ysr__som__somat_006
  - mh_y_ysr__som__somat_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 10 items missing

Usage

```
compute_mh_y_ysr__synd__som_sum(
  data,
  name = "mh_y_ysr__synd__som_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__som_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__som_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__som_sum", vars_mh_y_ysr__synd__som))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__som_tscore

Compute "Youth Self Report [Youth] (Syndrome Scale - Somatic complaints): T-score"

Description

Computes the summary score mh_y_ysr__synd__som_tscore Youth Self Report [Youth] (Syndrome Scale - Somatic complaints): T-score

- *Summarized variables:*
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__som_001
  - mh_y_ysr__som__dep_001
  - mh_y_ysr__som__somat_001
  - mh_y_ysr__som__somat_002
  - mh_y_ysr__som__somat_003
  - mh_y_ysr__som__somat_004
  - mh_y_ysr__som__somat_005
  - mh_y_ysr__som__somat_006
  - mh_y_ysr__som__somat_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 10 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__synd__som_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__som_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see `combine`.

See Also

`compute_mh_y_ysr__synd__som_nm()`

Examples

```
## Not run:
compute_mh_y_ysr__synd__som_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__som_tscore", vars_mh_y_ysr__synd__som))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__tho_sum

Compute "Youth Self Report [Youth] (Syndrome Scale - Thought problems): Sum"

Description

Computes the summary score `mh_y_ysr__synd__tho_sum` Youth Self Report [Youth] (Syndrome Scale - Thought problems): Sum

- *Summarized variables:*
  - `mh_y_ysr__tho_001`
  - `mh_y_ysr__tho_002`
  - `mh_y_ysr__tho_003`
  - `mh_y_ysr__tho_004`
  - `mh_y_ysr__tho_005`
  - `mh_y_ysr__tho_006`
  - `mh_y_ysr__tho__dep_002`
  - `mh_y_ysr__tho_007`
  - `mh_y_ysr__tho_008`
  - `mh_y_ysr__tho_009`
  - `mh_y_ysr__tho__dep_003`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 11 items missing

Usage

```
compute_mh_y_ysr__synd__tho_sum(
  data,
  name = "mh_y_ysr__synd__tho_sum",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__tho_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__tho_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__tho_sum", vars_mh_y_ysr__synd__tho))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__tho_tscore

Compute "Youth Self Report [Youth] (Syndrome Scale - Thought problems): T-score"

Description

Computes the summary score mh_y_ysr__synd__tho_tscore Youth Self Report [Youth] (Syndrome Scale - Thought problems): T-score

- *Summarized variables:*
  - mh_y_ysr__tho_001
  - mh_y_ysr__tho_002
  - mh_y_ysr__tho_003
  - mh_y_ysr__tho_004
  - mh_y_ysr__tho_005
  - mh_y_ysr__tho_006
  - mh_y_ysr__tho__dep_002
  - mh_y_ysr__tho_007
  - mh_y_ysr__tho_008
  - mh_y_ysr__tho_009
  - mh_y_ysr__tho__dep_003
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 2 of 11 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__synd__tho_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__tho_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.

combine — logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__tho_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__tho_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__tho_tscore", vars_mh_y_ysr__synd__tho))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__wthdep_sum

Compute "Youth Self Report [Youth] (Syndrome Scale - Withdrawn/Depressed): Sum"

Description

Computes the summary score mh_y_ysr__synd__wthdep_sum Youth Self Report [Youth] (Syndrome Scale - Withdrawn/Depressed): Sum

- *Summarized variables:*
  - mh_y_ysr__wthdep__dep_001
  - mh_y_ysr__wthdep_001
  - mh_y_ysr__wthdep_002
  - mh_y_ysr__wthdep_003
  - mh_y_ysr__wthdep_004
  - mh_y_ysr__wthdep__dep_002
  - mh_y_ysr__wthdep__dep_003
  - mh_y_ysr__wthdep_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
compute_mh_y_ysr__synd__wthdep_sum(
  data,
  name = "mh_y_ysr__synd__wthdep_sum",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__wthdep_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__wthdep_sum(data) |>
  select(
    any_of(c("mh_y_ysr__synd__wthdep_sum", vars_mh_y_ysr__synd__wthdep))
  )

## End(Not run)
```

---

compute_mh_y_ysr__synd__wthdep_tscore

Compute "Youth Self Report [Youth] (Syndrome Scale - Withdrawn/Depressed): T-score"

Description

Computes the summary score mh_y_ysr__synd__wthdep_tscore Youth Self Report [Youth] (Syndrome Scale - Withdrawn/Depressed): T-score

- *Summarized variables:*
  - mh_y_ysr__wthdep__dep_001
  - mh_y_ysr__wthdep_001
  - mh_y_ysr__wthdep_002
  - mh_y_ysr__wthdep_003
  - mh_y_ysr__wthdep_004
  - mh_y_ysr__wthdep__dep_002
  - mh_y_ysr__wthdep__dep_003
  - mh_y_ysr__wthdep_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 8 items missing or mh_y_ysr__dsm__adhd_nm <= 5

Usage

```
compute_mh_y_ysr__synd__wthdep_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr__synd__wthdep_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr__synd__wthdep_nm()

Examples

```
## Not run:
compute_mh_y_ysr__synd__wthdep_tscore(data) |>
  select(
    any_of(c("mh_y_ysr__synd__wthdep_tscore", vars_mh_y_ysr__synd__wthdep))
  )

## End(Not run)
```

---

compute_mh_y_ysr_all *Compute all summary scores for mh_y_ysr.*

Description

This function computes all summary scores for the mh_y_ysr form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_mh_y_ysr_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_mh_y_ysr_all(data)

## End(Not run)
```

compute_mh_y_ysr_sum *Compute "Youth Self Report [Youth]: Sum"*

Description

Computes the summary score mh_y_ysr_sum Youth Self Report [Youth]: Sum

- *Summarized variables:*
  - mh_y_ysr__attn__adhd_001
  - mh_y_ysr__attn__adhd_002
  - mh_y_ysr__attn__adhd_003
  - mh_y_ysr__attn__adhd_004
  - mh_y_ysr__attn__adhd_005
  - mh_y_ysr__othpr__adhd_001
  - mh_y_ysr__aggr__adhd_001
  - mh_y_ysr__soc__anx_001
  - mh_y_ysr__anxdep__anx_001
  - mh_y_ysr__anxdep__anx_002
  - mh_y_ysr__anxdep__anx_003
  - mh_y_ysr__anxdep__anx_004
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__anxdep__anx_005
  - mh_y_ysr__anxdep__anx_006
  - mh_y_ysr__anxdep__anx_007
  - mh_y_ysr__aggr__cond_001
  - mh_y_ysr__aggr__cond_002
  - mh_y_ysr__rule__cond_001
  - mh_y_ysr__rule__cond_002
  - mh_y_ysr__aggr__cond_003
  - mh_y_ysr__rule__cond_003
  - mh_y_ysr__rule__cond_004
  - mh_y_ysr__aggr__cond_004
  - mh_y_ysr__rule__cond_005
  - mh_y_ysr__rule__cond_006
  - mh_y_ysr__rule__cond_007
  - mh_y_ysr__rule__cond_008
  - mh_y_ysr__rule__cond_009
  - mh_y_ysr__aggr__cond_005
  - mh_y_ysr__rule__cond_010
  - mh_y_ysr__wthdep__dep_001
  - mh_y_ysr__anxdep__dep_001

- mh_y_ysr__othpr__dep_001
- mh_y_ysr__anxdep__dep_002
- mh_y_ysr__anxdep__dep_003
- mh_y_ysr__som__dep_001
- mh_y_ysr__tho__dep_002
- mh_y_ysr__othpr__dep_002
- mh_y_ysr__tho__dep_003
- mh_y_ysr__wthdep__dep_002
- mh_y_ysr__wthdep__dep_003
- mh_y_ysr__aggr__opp_001
- mh_y_ysr__aggr__opp_002
- mh_y_ysr__aggr__opp_003
- mh_y_ysr__aggr__opp_004
- mh_y_ysr__aggr__opp_005
- mh_y_ysr__som__somat_001
- mh_y_ysr__som__somat_002
- mh_y_ysr__som__somat_003
- mh_y_ysr__som__somat_004
- mh_y_ysr__som__somat_005
- mh_y_ysr__som__somat_006
- mh_y_ysr__som__somat_007
- mh_y_ysr__aggr_001
- mh_y_ysr__aggr_002
- mh_y_ysr__aggr_003
- mh_y_ysr__aggr_004
- mh_y_ysr__aggr_005
- mh_y_ysr__aggr_006
- mh_y_ysr__anxdep_001
- mh_y_ysr__anxdep_002
- mh_y_ysr__attn_001
- mh_y_ysr__attn_002
- mh_y_ysr__attn_003
- mh_y_ysr__attn_004
- mh_y_ysr__rule_001
- mh_y_ysr__rule_002
- mh_y_ysr__rule_003
- mh_y_ysr__rule_004
- mh_y_ysr__rule_005
- mh_y_ysr__wthdep_001
- mh_y_ysr__wthdep_002
- mh_y_ysr__wthdep_003
- mh_y_ysr__wthdep_004

  - mh_y_ysr__wthdep_005
  - mh_y_ysr__som_001
  - mh_y_ysr__othpr_001
  - mh_y_ysr__othpr_002
  - mh_y_ysr__othpr_003
  - mh_y_ysr__othpr_004
  - mh_y_ysr__othpr_005
  - mh_y_ysr__othpr_006
  - mh_y_ysr__soc_001
  - mh_y_ysr__soc_002
  - mh_y_ysr__soc_003
  - mh_y_ysr__soc_004
  - mh_y_ysr__soc_005
  - mh_y_ysr__soc_006
  - mh_y_ysr__soc_007
  - mh_y_ysr__soc_008
  - mh_y_ysr__soc_009
  - mh_y_ysr__soc_010
  - mh_y_ysr__tho_001
  - mh_y_ysr__tho_002
  - mh_y_ysr__tho_003
  - mh_y_ysr__tho_004
  - mh_y_ysr__tho_005
  - mh_y_ysr__tho_006
  - mh_y_ysr__tho_007
  - mh_y_ysr__tho_008
  - mh_y_ysr__tho_009

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 5 of 102 items missing

Usage

```
compute_mh_y_ysr_sum(
  data,
  name = "mh_y_ysr_sum",
  max_na = 5,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr_nm()

Examples

```
## Not run:
compute_mh_y_ysr_sum(data) |>
  select(
    any_of(c("mh_y_ysr_sum", vars_mh_y_ysr))
  )

## End(Not run)
```

---

compute_mh_y_ysr_tscore

Compute "Youth Self Report [Youth]: T-score"

Description

Computes the summary score mh_y_ysr_tscore Youth Self Report [Youth]: T-score

- *Summarized variables:*
  - mh_y_ysr__attn__adhd_001
  - mh_y_ysr__attn__adhd_002
  - mh_y_ysr__attn__adhd_003
  - mh_y_ysr__attn__adhd_004
  - mh_y_ysr__attn__adhd_005
  - mh_y_ysr__othpr__adhd_001
  - mh_y_ysr__aggr__adhd_001
  - mh_y_ysr__soc__anx_001

- mh_y_ysr__anxdep__anx_001
- mh_y_ysr__anxdep__anx_002
- mh_y_ysr__anxdep__anx_003
- mh_y_ysr__anxdep__anx_004
- mh_y_ysr__som__anx_001
- mh_y_ysr__anxdep__anx_005
- mh_y_ysr__anxdep__anx_006
- mh_y_ysr__anxdep__anx_007
- mh_y_ysr__aggr__cond_001
- mh_y_ysr__aggr__cond_002
- mh_y_ysr__rule__cond_001
- mh_y_ysr__rule__cond_002
- mh_y_ysr__aggr__cond_003
- mh_y_ysr__rule__cond_003
- mh_y_ysr__rule__cond_004
- mh_y_ysr__aggr__cond_004
- mh_y_ysr__rule__cond_005
- mh_y_ysr__rule__cond_006
- mh_y_ysr__rule__cond_007
- mh_y_ysr__rule__cond_008
- mh_y_ysr__rule__cond_009
- mh_y_ysr__aggr__cond_005
- mh_y_ysr__rule__cond_010
- mh_y_ysr__wthdep__dep_001
- mh_y_ysr__anxdep__dep_001
- mh_y_ysr__othpr__dep_001
- mh_y_ysr__anxdep__dep_002
- mh_y_ysr__anxdep__dep_003
- mh_y_ysr__som__dep_001
- mh_y_ysr__tho__dep_002
- mh_y_ysr__othpr__dep_002
- mh_y_ysr__tho__dep_003
- mh_y_ysr__wthdep__dep_002
- mh_y_ysr__wthdep__dep_003
- mh_y_ysr__aggr__opp_001
- mh_y_ysr__aggr__opp_002
- mh_y_ysr__aggr__opp_003
- mh_y_ysr__aggr__opp_004
- mh_y_ysr__aggr__opp_005
- mh_y_ysr__som__somat_001
- mh_y_ysr__som__somat_002
- mh_y_ysr__som__somat_003

- mh_y_ysr__som__somat_004
- mh_y_ysr__som__somat_005
- mh_y_ysr__som__somat_006
- mh_y_ysr__som__somat_007
- mh_y_ysr__aggr_001
- mh_y_ysr__aggr_002
- mh_y_ysr__aggr_003
- mh_y_ysr__aggr_004
- mh_y_ysr__aggr_005
- mh_y_ysr__aggr_006
- mh_y_ysr__anxdep_001
- mh_y_ysr__anxdep_002
- mh_y_ysr__attn_001
- mh_y_ysr__attn_002
- mh_y_ysr__attn_003
- mh_y_ysr__attn_004
- mh_y_ysr__rule_001
- mh_y_ysr__rule_002
- mh_y_ysr__rule_003
- mh_y_ysr__rule_004
- mh_y_ysr__rule_005
- mh_y_ysr__wthdep_001
- mh_y_ysr__wthdep_002
- mh_y_ysr__wthdep_003
- mh_y_ysr__wthdep_004
- mh_y_ysr__wthdep_005
- mh_y_ysr__som_001
- mh_y_ysr__othpr_001
- mh_y_ysr__othpr_002
- mh_y_ysr__othpr_003
- mh_y_ysr__othpr_004
- mh_y_ysr__othpr_005
- mh_y_ysr__othpr_006
- mh_y_ysr__soc_001
- mh_y_ysr__soc_002
- mh_y_ysr__soc_003
- mh_y_ysr__soc_004
- mh_y_ysr__soc_005
- mh_y_ysr__soc_006
- mh_y_ysr__soc_007
- mh_y_ysr__soc_008
- mh_y_ysr__soc_009

  - mh_y_ysr__soc_010
  - mh_y_ysr__tho_001
  - mh_y_ysr__tho_002
  - mh_y_ysr__tho_003
  - mh_y_ysr__tho_004
  - mh_y_ysr__tho_005
  - mh_y_ysr__tho_006
  - mh_y_ysr__tho_007
  - mh_y_ysr__tho_008
  - mh_y_ysr__tho_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 5 of 102 items missing

Usage

```
compute_mh_y_ysr_tscore(
  data,
  data_norm = NULL,
  name = "mh_y_ysr_tscore",
  col_age = "mh_y_ysr_age",
  col_sex = "ab_g_stc__cohort_sex",
  max_na = 5,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the norm (T-score) values. see ss_tscore().
name	character. Name of the summary score column.
col_age	character, name of the age column. see ss_tscore().
col_sex	character, name of the sex column. see ss_tscore().
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. see combine.

See Also

compute_mh_y_ysr_nm()

Examples

```
## Not run:
compute_mh_y_ysr_tscore(data) |>
  select(
    any_of(c("mh_y_ysr_tscore", vars_mh_y_ysr))
  )

## End(Not run)
```

---

compute_nc_p_bdefs__sympt_count

Compute "Barkley Deficits in Executive Functioning Scale [Parent] (EF Symptom Count, number of answers of 3 or 4): Count"

Description

Computes the summary score nc_p_bdefs__sympt_count Barkley Deficits in Executive Functioning Scale [Parent] (EF Symptom Count, number of answers of 3 or 4): Count

- *Summarized variables:*
  - nc_p_bdefs_001
  - nc_p_bdefs_002
  - nc_p_bdefs_003
  - nc_p_bdefs_004
  - nc_p_bdefs_005
  - nc_p_bdefs_006
  - nc_p_bdefs_007
  - nc_p_bdefs_008
  - nc_p_bdefs_009
  - nc_p_bdefs_010
  - nc_p_bdefs_011
  - nc_p_bdefs_012
  - nc_p_bdefs_013
  - nc_p_bdefs_014
  - nc_p_bdefs_015
  - nc_p_bdefs_016
  - nc_p_bdefs_017
  - nc_p_bdefs_018
  - nc_p_bdefs_019
  - nc_p_bdefs_020

Usage

```
compute_nc_p_bdefs__sympt_count(
  data,
  name = "nc_p_bdefs__sympt_count",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_nc_p_bdefs_sum()

Examples

```
## Not run:
compute_nc_p_bdefs__sympt_count(data) |>
  select(
    data,
    all_of(c("nc_p_bdefs__sympt_count", vars_nc_p_bdefs))
  )

## End(Not run)
```

---

compute_nc_p_bdefs_all

Compute all the BDEFS summary scores

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_nc_p_bdefs_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_nc_p_bdefs_all(data)

## End(Not run)
```

---

compute_nc_p_bdefs_nm *Compute "Barkley Deficits in Executive Functioning Scale [Parent] (EF Summary Score): Number missing"*

Description

Computes the summary score nc_p_bdefs_nm Barkley Deficits in Executive Functioning Scale [Parent] (EF Summary Score): Number missing

- *Summarized variables:*
  - nc_p_bdefs_001
  - nc_p_bdefs_002
  - nc_p_bdefs_003
  - nc_p_bdefs_004
  - nc_p_bdefs_005
  - nc_p_bdefs_006
  - nc_p_bdefs_007
  - nc_p_bdefs_008
  - nc_p_bdefs_009
  - nc_p_bdefs_010
  - nc_p_bdefs_011
  - nc_p_bdefs_012
  - nc_p_bdefs_013
  - nc_p_bdefs_014
  - nc_p_bdefs_015
  - nc_p_bdefs_016
  - nc_p_bdefs_017

- nc_p_bdefs_018
- nc_p_bdefs_019
- nc_p_bdefs_020

Usage

```
compute_nc_p_bdefs_nm(data, name = "nc_p_bdefs_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_nc_p_bdefs_sum()

Examples

```
## Not run:
compute_nc_p_bdefs_nm(data) |>
  select(
    data,
    all_of(c("nc_p_bdefs_nm", vars_nc_p_bdefs))
  )

## End(Not run)
```

---

compute_nc_y_ehis_all *Compute all the EHIS summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_nc_y_ehis_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_nc_y_ehis_all(data)

## End(Not run)
```

---

compute_nc_y_ehis_nm *Compute "Edinburgh Handedness Inventory [Youth]: Number missing"*

Description

Computes the summary score nc_y_ehis_nm Edinburgh Handedness Inventory [Youth]: Number missing

- *Summarized variables:*
  - nc_y_ehis_001
  - nc_y_ehis_002
  - nc_y_ehis_003
  - nc_y_ehis_004

Usage

```
compute_nc_y_ehis_nm(data, name = "nc_y_ehis_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_nc_y_ehis_score()

Examples

```
## Not run:
compute_nc_y_ehis_nm(data) |>
  select(
    data,
    all_of(c("nc_y_ehis_nm", vars_nc_y_ehis))
  )

## End(Not run)
```

---

compute_nt_p_yst__pmum_nm

Compute "Youth Screen Time [Parent] (Problematic Media Use): Number missing"

Description

Computes the summary score `nt_p_yst__pmum_nm` Youth Screen Time [Parent] (Problematic Media Use): Number missing

- *Summarized variables:*
  - `nt_p_yst__pmum_001`
  - `nt_p_yst__pmum_002`
  - `nt_p_yst__pmum_003`
  - `nt_p_yst__pmum_004`
  - `nt_p_yst__pmum_005`
  - `nt_p_yst__pmum_006`
  - `nt_p_yst__pmum_007`
  - `nt_p_yst__pmum_008`
  - `nt_p_yst__pmum_009`
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_nt_p_yst__pmum_nm(data, name = "nt_p_yst__pmum_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_nt_p_yst__screen__wkdy_nm

Compute "Youth Screen Time [Parent] (Weekday): Number missing"

Description

Computes the summary score `nt_p_yst__screen__wkdy_nm` Youth Screen Time [Parent] (Weekday): Number missing

- *Summarized variables:*
  - `nt_p_yst__wkdy__hr_001`
  - `nt_p_yst__wkdy__min_001`
  - `nt_p_yst__wkdy__min_001__v01`
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_nt_p_yst__screen__wkdy_nm(
  data,
  name = "nt_p_yst__screen__wkdy_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_nt_p_yst__screen__wknd_nm`
Compute "Youth Screen Time [Parent] (Weekend): Number missing"

Description

Computes the summary score `nt_p_yst__screen__wknd_nm` Youth Screen Time [Parent] (Weekend): Number missing

- *Summarized variables:*
  - `nt_p_yst__wknd__hr_001`
  - `nt_p_yst__wknd__min_001`
  - `nt_p_yst__wknd__min_001__v01`
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_nt_p_yst__screen__wknd_nm(
  data,
  name = "nt_p_yst__screen__wknd_nm",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_nt_p_yst_all *Compute all summary scores for nt_p_yst.*

Description

This function computes all summary scores for the nt_p_yst form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_nt_p_yst_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_nt_p_yst_all(data)

## End(Not run)
```

compute_nt_y_stq__screen__wkdy_nm *Compute "Screen Time [Youth] (Weekday): Number missing"*

Description

Computes the summary score `nt_y_stq__screen__wkdy_nm` Screen Time [Youth] (Weekday): Number missing

- *Summarized variables:*
  - `nt_y_stq__screen__wkdy_001`
  - `nt_y_stq__screen__wkdy_002`
  - `nt_y_stq__screen__wkdy_003`
  - `nt_y_stq__screen__wkdy_004`
  - `nt_y_stq__screen__wkdy_005`
  - `nt_y_stq__screen__wkdy_006`
  - `nt_y_stq__screen__wkdy__hr_001`
  - `nt_y_stq__screen__wkdy__min_001`

  - nt_y_stq__screen__wkdy__hr_001__v01
  - nt_y_stq__screen__wkdy__min_001__v01
  - nt_y_stq__screen__wkdy__hr_002
  - nt_y_stq__screen__wkdy__min_002
  - nt_y_stq__screen__wkdy__hr_003
  - nt_y_stq__screen__wkdy__min_003
  - nt_y_stq__screen__wkdy__hr_004
  - nt_y_stq__screen__wkdy__min_004
  - nt_y_stq__screen__wkdy__hr_005
  - nt_y_stq__screen__wkdy__min_005
  - nt_y_stq__screen__wkdy__hr_006
  - nt_y_stq__screen__wkdy__min_006
  - nt_y_stq__screen__wkdy__hr_007
  - nt_y_stq__screen__wkdy__min_007
  - nt_y_stq__screen__wkdy__hr_008
  - nt_y_stq__screen__wkdy__min_008
  - nt_y_stq__screen__wkdy__hr_009
  - nt_y_stq__screen__wkdy__min_009

- *Excluded values:*
  - 777
  - 999

Usage

```
compute_nt_y_stq__screen__wkdy_nm(
  data,
  name = "nt_y_stq__screen__wkdy_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_nt_y_stq__screen__wknd_nm
Compute "Screen Time [Youth] (Weekend): Number missing"

Description

Computes the summary score nt_y_stq__screen__wknd_nm Screen Time [Youth] (Weekend): Number missing

- *Summarized variables:*
  - nt_y_stq__screen__wknd_001
  - nt_y_stq__screen__wknd_002
  - nt_y_stq__screen__wknd_003
  - nt_y_stq__screen__wknd_004
  - nt_y_stq__screen__wknd_005
  - nt_y_stq__screen__wknd_006
  - nt_y_stq__screen__wknd__hr_001
  - nt_y_stq__screen__wknd__min_001
  - nt_y_stq__screen__wknd__hr_001__v01
  - nt_y_stq__screen__wknd__min_001__v01
  - nt_y_stq__screen__wknd__hr_002
  - nt_y_stq__screen__wknd__min_002
  - nt_y_stq__screen__wknd__hr_003
  - nt_y_stq__screen__wknd__min_003
  - nt_y_stq__screen__wknd__hr_004
  - nt_y_stq__screen__wknd__min_004
  - nt_y_stq__screen__wknd__hr_005
  - nt_y_stq__screen__wknd__min_005
  - nt_y_stq__screen__wknd__hr_006
  - nt_y_stq__screen__wknd__min_006
  - nt_y_stq__screen__wknd__hr_007
  - nt_y_stq__screen__wknd__min_007
  - nt_y_stq__screen__wknd__hr_008
  - nt_y_stq__screen__wknd__min_008
  - nt_y_stq__screen__wknd__hr_009
  - nt_y_stq__screen__wknd__min_009
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_nt_y_stq__screen__wknd_nm(
  data,
  name = "nt_y_stq__screen__wknd_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_nt_y_stq_all *Compute all summary scores for nt_y_stq*

Description

This function computes all summary scores for the nt_y_stq form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_nt_y_stq_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_nt_y_stq_all(data)

## End(Not run)
```

compute_ph_meds_catg_all
Compute all medication categories [Parent] [Youth]

Description

This function computes all medication category mapping summary scores based on the provided configuration in `rx_config` by mapping medication RxCUI codes to their respective categories that are stored in `ABCDscores::rx_map`.

It processes each row in `rx_config`. One row corresponds to one medication category mapping score. For each row, it first checks `col_summary1`. If `col_summary1` has data, that value is used. If `col_summary1` is `NA`, it falls back to `col_summary2`.

It then applies `col_add` filtering only when both conditions are met:

- the corresponding flag (`use_col_add1` or `use_col_add2`) is `TRUE`, and
- `col_add` is provided (not `NA`).

When filtering is applied, only rows with `col_add == "1"` are retained; otherwise, the selected RxCUI is set to `NA`.

After source selection and optional filtering, it maps the retained RxCUI codes to their respective categories using the appropriate mapping data frame from `ABCDscores::rx_map` based on the `catg` specified in `rx_config`. The resulting category values are then stored in a new column named as specified in the `name` column of `rx_config`.

- *Summarized variables:* see `rx_config` for the list of variables.

Usage

```
compute_ph_meds_catg_all(
  data,
  rx_config = ABCDscores::rx_config,
  combine = TRUE
)

compute_ph_p_meds_catg_all(
  data,
  rx_config = ABCDscores::rx_config,
  combine = TRUE
)

compute_ph_y_meds_catg_all(
  data,
  rx_config = ABCDscores::rx_config,
  combine = TRUE
)
```

```
compute_ph_p_dhx_catg_all(
  data,
  rx_config = ABCDscores::rx_config,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
rx_config	tbl, Configuration tibble specifying the medication category mappings to compute. Default is ABCDscores::rx_config.
combine	logical, If TRUE, the computed summary scores are appended to the original data frame. If FALSE, only the summary scores are returned. Default is TRUE.

Details

Disclaimer:

"This product uses publicly available data from the U.S. National Library of Medicine (NLM), National Institutes of Health, Department of Health and Human Services; NLM is not responsible for the product and does not endorse or recommend this or any other product."

Functions for specific tables:

- compute_ph_meds_catg_all(): Computes all medication category mappings across all tables.
- compute_ph_p_meds_catg_all(): Computes all medication category mappings for the ph_p_meds table.
- compute_ph_y_meds_catg_all(): Computes all medication category mappings for the ph_y_meds table.
- compute_ph_p_dhx_catg_all(): Computes all medication category mappings for the ph_p_dhx table.

Value

tbl. see combine parameter.

References

The medical estimated use values and categories are generated from: Lopez, D. A., Overholtzer, L. N., Rhee, K. E., Buchbinder, N., Ruiz-Orozco, G. E., Steinhilber, S., Tognoli, M., Lopez-Flores, A., & Nagel, B. J. (2025). Classifying and visualizing medication use in the Adolescent Brain Cognitive Development (ABCD) Study. *medRxiv*.

See Also

rx_map

compute_ph_meds_estuse_flags_all
Compute all medication estimated use flags [Parent] [Youth]

Description

This function computes all medication estimated use flag summary scores based on the provided configuration in `rx_config_estuse_flags` and the computed medication categories from `rx_config`.

It first calls `compute_ph_meds_catg_all()` to obtain the medication category mappings of all `estuse` categories. Then, for each row in `rx_config_estuse_flags`, it checks if any of the corresponding medication category mapping scores (from both OTC and RX medications) match the specified `idx` category index. If a match is found, it assigns a value of "1" to indicate estimated use; otherwise, it assigns "0". The resulting estimated use flags are stored in new columns named as specified in the `name` column of `rx_config_estuse_flags`.

- *Summarized variables:* see `rx_config` for the list of variables.

Usage

```
compute_ph_meds_estuse_flags_all(
  data,
  rx_config_estuse_flags = ABCDscores::rx_config_estuse_flags,
  rx_config = ABCDscores::rx_config,
  combine = TRUE
)

compute_ph_p_meds_estuse_flags_all(
  data,
  rx_config_estuse_flags = ABCDscores::rx_config_estuse_flags,
  rx_config = ABCDscores::rx_config,
  combine = TRUE
)

compute_ph_y_meds_estuse_flags_all(
  data,
  rx_config_estuse_flags = ABCDscores::rx_config_estuse_flags,
  rx_config = ABCDscores::rx_config,
  combine = TRUE
)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`rx_config_estuse_flags`	tbl, Configuration tibble specifying the estimated use flag mappings to compute. Default is `ABCDscores::rx_config_estuse_flags`.

rx_config	tbl, Configuration tibble specifying the medication category mappings to compute. Default is ABCDscores::rx_config.
combine	logical, If TRUE, the computed summary scores are appended to the original data frame. If FALSE, only the summary scores are returned. Default is TRUE.

Details

Disclaimer:
"This product uses publicly available data from the U.S. National Library of Medicine (NLM), National Institutes of Health, Department of Health and Human Services; NLM is not responsible for the product and does not endorse or recommend this or any other product."

Functions for specific tables:

- compute_ph_meds_estuse_flags_all(): Computes all medication estimated use flags across all tables.
- compute_ph_p_meds_estuse_flags_all(): Computes all medication estimated use flags for the ph_p_meds table.
- compute_ph_y_meds_estuse_flags_all(): Computes all medication estimated use flags for the ph_y_meds table.

Value

tbl. see combine parameter.

References

The medical estimated use values and categories are generated from: Lopez, D. A., Overholtzer, L. N., Rhee, K. E., Buchbinder, N., Ruiz-Orozco, G. E., Steinhilber, S., Tognoli, M., Lopez-Flores, A., & Nagel, B. J. (2025). Classifying and visualizing medication use in the Adolescent Brain Cognitive Development (ABCD) Study. *medRxiv*.

See Also

compute_ph_meds_catg_all(), rx_map

---

compute_ph_p_anthr__fath_height__cm

Compute "Anthropometrics [Parent] (Height): Father's height (cm)"

Description

Computes the summary score ph_p_anthr__fath_height__cm Anthropometrics [Parent] (Height): Father's height (cm)

- *Summarized variables:*
  - ph_p_anthr__height__fath_001
  - ph_p_anthr__height__fath_001__01
- *Excluded values:* None
- *Validation criterion:* None

Usage

```
compute_ph_p_anthr__fath_height__cm(
  data,
  name = "ph_p_anthr__fath_height__cm",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

See Also

compute_ph_p_anthr__fath_height__in()

Examples

```
## Not run:
compute_ph_p_anthr__fath_height__cm(data) |>
  select(
    all_of(c("ph_p_anthr__fath_height__cm", vars_ph_p_anthr__height))
  )

## End(Not run)
```

---

compute_ph_p_anthr__moth_height__cm

Compute "Anthropometrics [Parent] (Height): Mother's height (cm)"

Description

Computes the summary score ph_p_anthr__moth_height__cm Anthropometrics [Parent] (Height): Mother's height (cm)

- *Summarized variables:*
  - ph_p_anthr__height__moth_001
  - ph_p_anthr__height__moth_001__01
- *Excluded values:* None
- *Validation criterion:* None

Usage

```
compute_ph_p_anthr__moth_height__cm(
  data,
  name = "ph_p_anthr__moth_height__cm",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

See Also

compute_ph_p_anthr__fath_height__in()

Examples

```
## Not run:
compute_ph_p_anthr__moth_height__cm(data) |>
  select(
    all_of(c("ph_p_anthr__moth_height__cm", vars_ph_p_anthr__height))
  )

## End(Not run)
```

---

compute_ph_p_anthr__moth_height__in

Compute "Anthropometrics [Parent] (Height): Mother's height (in)"

Description

Computes the summary score ph_p_anthr__moth_height__in Anthropometrics [Parent] (Height): Mother's height (in)

- *Summarized variables:*
  - ph_p_anthr__height__moth_001
  - ph_p_anthr__height__moth_001__01
- *Excluded values:* None
- *Validation criterion:* None

Usage

```
compute_ph_p_anthr__moth_height__in(
  data,
  name = "ph_p_anthr__moth_height__in",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

See Also

compute_ph_p_anthr__fath_height__in()

Examples

```
## Not run:
compute_ph_p_anthr__moth_height__in(data) |>
  select(
    all_of(c("ph_p_anthr__moth_height__in", vars_ph_p_anthr__height))
  )

## End(Not run)
```

---

compute_ph_p_anthr_all

Compute all the ph_p_anthr *summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_ph_p_anthr_all(data)
```

Arguments

data	tbl. Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ph_p_anthr_all(data)

## End(Not run)
```

`compute_ph_p_cna_all` *Compute all the* `ph_p_cna` *summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_ph_p_cna_all(data)
```

Arguments

`data`	tbl. Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ph_p_cna(data)

## End(Not run)
```

`compute_ph_p_cna_nm` *Compute "Child Nutrition Assessment [Parent]: Sum [Validation: No more than 0 missing or declined]"*

Description

Computes the summary score `ph_p_cna_sum` Child Nutrition Assessment [Parent]: Sum [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `ph_p_cna_001`
  - `ph_p_cna_002`
  - `ph_p_cna_003`
  - `ph_p_cna_004`
  - `ph_p_cna_005`
  - `ph_p_cna_006`
  - `ph_p_cna_007`
  - `ph_p_cna_008`
  - `ph_p_cna_009`
  - `ph_p_cna_010`
  - `ph_p_cna_011`
  - `ph_p_cna_012`
  - `ph_p_cna_013`
  - `ph_p_cna_014`
- *Excluded values:*
  - 999
  - 777

Usage

```
compute_ph_p_cna_nm(
  data,
  name = "ph_p_cna_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`exclude`	character, Values to be excluded from the summary score.
`combine`	logical, If `TRUE`, the summary score will be appended to the input data frame. If `FALSE`, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_p_cna_nm(data) |>
  select(
    all_of(c("ph_p_cna_nm", vars_ph_p_cna))
  )

## End(Not run)
```

---

compute_ph_p_otbi__loc__30m_nm

Compute "Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness - Over 30 minutes): Number missing"

Description

Computes the summary score `ph_p_otbi__loc__30m_nm` Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness - Over 30 minutes): Number missing

- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_otbi__loc__30m_nm(
  data,
  name = "ph_p_otbi__loc__30m_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_otbi__loc__30m_count()

---

compute_ph_p_otbi__loc__tbiage_nm

Compute "Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): Age of first injury with LOC - Number missing"

Description

Computes the summary score ph_p_otbi__loc__tbiage_nm Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): Age of first injury with LOC - Number missing

- *Excluded values:*
  - 777
  - 999
- *Notes:*
  - The output is set to NA when no head or neck injury/impact is reported

Usage

```
compute_ph_p_otbi__loc__tbiage_nm(
  data,
  name = "ph_p_otbi__loc__tbiage_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_otbi__loc_tbiage()

`compute_ph_p_otbi__loc_nm`

Compute "Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): Number missing"

Description

Computes the summary score `ph_p_otbi__loc_nm` Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): Number missing

- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_otbi__loc_nm(
  data,
  name = "ph_p_otbi__loc_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_ph_p_otbi__loc_count()`

`compute_ph_p_otbi__rpt_nm`

Compute "Ohio State Traumatic Brain Injury Screen [Parent] (Repeated injuries): Number missing"

Description

Computes the summary score `ph_p_otbi__rpt_nm` Ohio State Traumatic Brain Injury Screen [Parent] (Repeated injuries): Number missing

- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_otbi__rpt_nm(
  data,
  name = "ph_p_otbi__rpt_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_ph_p_otbi__rpt_count()`

compute_ph_p_otbi_all *Compute all the ph_p_otbi scores*

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_ph_p_otbi_all(data)
```

Arguments

data	tbl. Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ph_p_otbi_all(data)

## End(Not run)
```

compute_ph_p_pds__f__categ_nm *Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Female): Approximate tanner stages - Number missing"*

Description

Computes the summary score ph_p_pds__f__categ_nm Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Female): Approximate tanner stages - Number missing

- *Summarized variables:*
  - ph_p_pds_002
  - ph_p_pds__f_001
  - ph_p_pds__f_002
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_pds__f__categ_nm(
  data,
  name = "ph_p_pds__f__categ_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_pds__f_categ()

---

compute_ph_p_pds__f_nm

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Female): Number missing"

Description

Computes the summary score ph_p_pds__f_nm Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Female): Number missing

- *Summarized variables:*
  - ph_p_pds_001
  - ph_p_pds_002
  - ph_p_pds_003
  - ph_p_pds__f_001
  - ph_p_pds__f_002
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_pds__f_nm(
  data,
  name = "ph_p_pds__f_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_pds__f_mean()

---

compute_ph_p_pds__m__categ_nm

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Male): Approximate tanner stages - Number missing"

Description

Computes the summary score ph_p_pds__m__categ_nm Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Male): Approximate tanner stages - Number missing

- *Summarized variables:*
  - ph_p_pds_002
  - ph_p_pds__m_001
  - ph_p_pds__m_002
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_pds__m__categ_nm(
  data,
  name = "ph_p_pds__m__categ_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_pds__m_categ()

---

compute_ph_p_pds__m_nm

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Male): Number missing"

Description

Computes the summary score ph_p_pds__m_nm Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Male): Number missing

- *Summarized variables:*
  - ph_p_pds_001
  - ph_p_pds_002
  - ph_p_pds_003
  - ph_p_pds__m_001
  - ph_p_pds__m_002
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_pds__m_nm(
  data,
  name = "ph_p_pds__m_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_pds__m_mean()

---

compute_ph_p_pds_all *Compute all the* ph_p_pds *summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_ph_p_pds_all(data)
```

Arguments

data	tbl. Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ph_p_pds_all(data)

## End(Not run)
```

`compute_ph_p_sds__da_nm` *Compute "Sleep Disturbance Scale [Parent] (Disorder of arousal): Number missing"*

Description

Computes the summary score `ph_p_sds__da_nm` Sleep Disturbance Scale [Parent] (Disorder of arousal): Number missing

- *Summarized variables:*
  - `ph_p_sds__da_001`
  - `ph_p_sds__da_002`
  - `ph_p_sds__da_003`
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_sds__da_nm(
  data,
  name = "ph_p_sds__da_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`exclude`	character, Values to be excluded from the summary score.
`combine`	logical, If `TRUE`, the summary score will be appended to the input data frame. If `FALSE`, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_sds__da_sum()

---

compute_ph_p_sds__dims_nm

Compute "Sleep Disturbance Scale [Parent] (Disorders of initiating and maintaining sleep): Number missing"

Description

Computes the summary score ph_p_sds__dims_nm Sleep Disturbance Scale [Parent] (Disorders of initiating and maintaining sleep): Number missing

- *Summarized variables:*
  - ph_p_sds__dims_001
  - ph_p_sds__dims_002
  - ph_p_sds__dims_003
  - ph_p_sds__dims_004
  - ph_p_sds__dims_005
  - ph_p_sds__dims_006
  - ph_p_sds__dims_007
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_sds__dims_nm(
  data,
  name = "ph_p_sds__dims_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_sds__dims_sum()

---

compute_ph_p_sds__does_nm

Compute "Sleep Disturbance Scale [Parent] (Disorders of excessive somnolence): Number missing"

Description

Computes the summary score ph_p_sds__does_nm Sleep Disturbance Scale [Parent] (Disorders of excessive somnolence) - Number missing

- *Summarized variables:*
  - ph_p_sds__does_001
  - ph_p_sds__does_002
  - ph_p_sds__does_003
  - ph_p_sds__does_004
  - ph_p_sds__does_005
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_sds__does_nm(
  data,
  name = "ph_p_sds__does_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_sds__does_sum()

---

compute_ph_p_sds__hyphy_nm

Compute "Sleep Disturbance Scale [Parent] (Sleep hyperhydrosis): Number missing"

Description

Computes the summary score ph_p_sds__hyphy_nm Sleep Disturbance Scale [Parent] (Sleep hyperhydrosis): Number missing

- *Summarized variables:*
  - ph_p_sds__hyphy_001
  - ph_p_sds__hyphy_002
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_sds__hyphy_nm(
  data,
  name = "ph_p_sds__hyphy_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_sds__hyphy_sum()

---

compute_ph_p_sds__sbd_nm

Compute "Sleep Disturbance Scale [Parent] (Sleep breathing disorders): Number missing"

Description

Computes the summary score ph_p_sds__sbd_nm Sleep Disturbance Scale [Parent] (Sleep breathing disorders): Number missing

- *Summarized variables:*
  - ph_p_sds__sbd_001
  - ph_p_sds__sbd_002
  - ph_p_sds__sbd_003
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_sds__sbd_nm(
  data,
  name = "ph_p_sds__sbd_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_sds__sbd_sum()

`compute_ph_p_sds__swtd_nm`

Compute "Sleep Disturbance Scale [Parent] (Sleep-wake transition disorders): Number missing"

Description

Computes the summary score `ph_p_sds__swtd_nm` Sleep Disturbance Scale [Parent] (Sleep-wake transition disorders): Number missing

- *Summarized variables:*
  - `ph_p_sds__swtd_001`
  - `ph_p_sds__swtd_002`
  - `ph_p_sds__swtd_003`
  - `ph_p_sds__swtd_004`
  - `ph_p_sds__swtd_005`
  - `ph_p_sds__swtd_006`
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_sds__swtd_nm(
  data,
  name = "ph_p_sds__swtd_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`exclude`	character, Values to be excluded from the summary score.
`combine`	logical, If `TRUE`, the summary score will be appended to the input data frame. If `FALSE`, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_ph_p_sds__swtd_sum()`

compute_ph_p_sds_all *Compute all the* ph_p_sds *summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_ph_p_sds_all(data)
```

Arguments

data	tbl. Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ph_p_sds_all(data)

## End(Not run)
```

compute_ph_p_sds_nm *Compute "Sleep Disturbance Scale [Parent]: Number missing"*

Description

Computes the summary score ph_p_sds_nm Sleep Disturbance Scale [Parent]: Number missing

- *Summarized variables:*
  - ph_p_sds__dims_001
  - ph_p_sds__dims_002
  - ph_p_sds__dims_003
  - ph_p_sds__dims_004
  - ph_p_sds__dims_005
  - ph_p_sds__swtd_001
  - ph_p_sds__swtd_002
  - ph_p_sds__swtd_003
  - ph_p_sds__hyphy_001
  - ph_p_sds__dims_006

  - ph_p_sds__dims_007
  - ph_p_sds__swtd_004
  - ph_p_sds__sbd_001
  - ph_p_sds__sbd_002
  - ph_p_sds__sbd_003
  - ph_p_sds__hyphy_002
  - ph_p_sds__da_001
  - ph_p_sds__swtd_005
  - ph_p_sds__swtd_006
  - ph_p_sds__da_002
  - ph_p_sds__da_003
  - ph_p_sds__does_001
  - ph_p_sds__does_002
  - ph_p_sds__does_003
  - ph_p_sds__does_004
  - ph_p_sds__does_005
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_p_sds_nm(
  data,
  name = "ph_p_sds_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_sds_sum()

compute_ph_y_anthr__height_nm
Compute "Anthropometrics [Youth] (Height): Number missing"

Description

Computes the summary score ph_y_anthr__height_nm Anthropometrics [Youth] (Height): Number missing

- *Summarized variables:*
  - ph_y_anthr__height__r01_001
  - ph_y_anthr__height__r02_001
  - ph_y_anthr__height__r03_001
- *Excluded values:* none

Usage

```
compute_ph_y_anthr__height_nm(
  data,
  name = "ph_y_anthr__height_nm",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_y_anthr__height_mean()

Examples

```
## Not run:
compute_ph_y_anthr__height_nm(data) |>
  select(
    all_of(c("ph_y_anthr__height_nm", vars_ph_y_anthr__height))
  )

## End(Not run)
```

`compute_ph_y_anthr__weight_nm`
Compute "Anthropometrics [Youth] (Weight): Number missing"

Description

Computes the summary score `ph_y_anthr__weight_nm` Anthropometrics [Youth] (Weight): Number missing

- *Summarized variables:*
  - `ph_y_anthr__weight__r01_001`
  - `ph_y_anthr__weight__r02_001`
  - `ph_y_anthr__weight__r03_001`
- *Excluded values:* none

Usage

```
compute_ph_y_anthr__weight_nm(
  data,
  name = "ph_y_anthr__weight_nm",
  combine = TRUE
)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE`, the summary score will be appended to the input data frame. If `FALSE`, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_ph_y_anthr__weight_mean()`

Examples

```
## Not run:
compute_ph_y_anthr__weight_nm(data) |>
  select(
    all_of(c("ph_y_anthr__weight_nm", vars_ph_y_anthr__weight))
  )

## End(Not run)
```

compute_ph_y_anthr_all

Compute all the youth anthropometric measurements.

Description

This is a high-level function that computes all summary scores in this table. Make sure the `data` contains all the necessary columns.

Usage

```
compute_ph_y_anthr_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ph_y_anthr_all(data)

## End(Not run)
```

compute_ph_y_bp__dia_nm

Compute "Blood Pressure [Youth] (Diastolic): Number missing"

Description

Computes the summary score `ph_y_bp__dia_nm` Blood Pressure [Youth] (Diastolic): Number missing

- *Summarized variables:*
  - `ph_y_bp__dia__r01_001`
  - `ph_y_bp__dia__r01_002`
  - `ph_y_bp__dia__r01_003`
  - `ph_y_bp__dia__r02_001`
  - `ph_y_bp__dia__r02_002`
  - `ph_y_bp__dia__r03_001`
  - `ph_y_bp__dia__r03_002`

- *Excluded values:* none

Calculation:

There are at most 3 possible rounds of measurements, and the calculation is as follows:

- if round 3 is available, use it, otherwise use round 2, otherwise use round 1
- for round 3 and 2, there are at most 2 measurements
- for round 1, there are at most 3 measurements:
  - participants with 3 measurements, and 0 missing, nm = 0
  - participants with 2 measurements, and 1 missing, nm = 1 - 1 = 0
  - participants with 1 measurement, and 2 missing, nm = 2 - 1 = 1
  - participants with 0 measurements, and 3 missing, nm = 3 - 1 = 2

Usage

```
compute_ph_y_bp__dia_nm(data, name = "ph_y_bp__dia_nm", combine = TRUE)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE`, the summary score will be appended to the input data frame. If `FALSE`, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_ph_y_bp__dia_mean()`

Examples

```
## Not run:
compute_ph_y_bp__dia_nm(data) |>
  select(
    all_of(c("ph_y_bp__dia_nm", vars_ph_y_bp__dia))
  )

## End(Not run)
```

compute_ph_y_bp__hrate_nm
Compute "Blood Pressure [Youth] (Heart rate): Number missing"

Description

Computes the summary score ph_y_bp__hrate_nm Blood Pressure [Youth] (Heart rate): Number missing

- *Summarized variables:*
  - ph_y_bp__hrate__r01_001
  - ph_y_bp__hrate__r01_002
  - ph_y_bp__hrate__r01_003
  - ph_y_bp__hrate__r02_001
  - ph_y_bp__hrate__r02_002
  - ph_y_bp__hrate__r03_001
  - ph_y_bp__hrate__r03_002
- *Excluded values:* none

Calculation:

There are at most 3 possible rounds of measurements, and the calculation is as follows:

- if round 3 is available, use it, otherwise use round 2, otherwise use round 1
- for round 3 and 2, there are at most 2 measurements
- for round 1, there are at most 3 measurements:
  - participants with 3 measurements, and 0 missing, nm = 0
  - participants with 2 measurements, and 1 missing, nm = 1 - 1 = 0
  - participants with 1 measurement, and 2 missing, nm = 2 - 1 = 1
  - participants with 0 measurements, and 3 missing, nm = 3 - 1 = 2

Usage

```
compute_ph_y_bp__hrate_nm(data, name = "ph_y_bp__hrate_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_y_bp__hrate_mean()

Examples

```
## Not run:
compute_ph_y_bp__hrate_nm(data) |>
  select(
    all_of(c("ph_y_bp__hrate_nm", vars_ph_y_bp__hrate))
  )

## End(Not run)
```

---

compute_ph_y_bp__sys_nm

Compute "Blood Pressure [Youth] (Systolic): Number missing"

Description

Computes the summary score ph_y_bp__sys_nm Blood Pressure [Youth] (Systolic): Number missing

- *Summarized variables:*
  - ph_y_bp__sys__r01_001
  - ph_y_bp__sys__r01_002
  - ph_y_bp__sys__r01_003
  - ph_y_bp__sys__r02_001
  - ph_y_bp__sys__r02_002
  - ph_y_bp__sys__r03_001
  - ph_y_bp__sys__r03_002
- *Excluded values:* none

Calculation:

There are at most 3 possible rounds of measurements, and the calculation is as follows:

- if round 3 is available, use it, otherwise use round 2, otherwise use round 1
- for round 3 and 2, there are at most 2 measurements
- for round 1, there are at most 3 measurements:
  - participants with 3 measurements, and 0 missing, nm = 0
  - participants with 2 measurements, and 1 missing, nm = 1 - 1 = 0
  - participants with 1 measurement, and 2 missing, nm = 2 - 1 = 1
  - participants with 0 measurements, and 3 missing, nm = 3 - 1 = 2

Usage

```
compute_ph_y_bp__sys_nm(data, name = "ph_y_bp__sys_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_y_bp__sys_mean()

Examples

```
## Not run:
compute_ph_y_bp__sys_nm(data) |>
  select(
    all_of(c("ph_y_bp__sys_nm", vars_ph_y_bp__sys))
  )

## End(Not run)
```

---

compute_ph_y_bp_all *Compute all the youth blood pressure measurements.*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_ph_y_bp_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ph_y_bp_all(data)

## End(Not run)
```

`compute_ph_y_mctq__fd__bed__end__24h_t`
Compute "Munich Chronotype Questionnaire [Youth] (Free Day - In bed end): Time [24 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__fd__bed__end__24h_t` Munich Chronotype Questionnaire [Youth] (Free Day - In bed end): Time [24 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__fd__sleep__end__24h_t` (intermediate score)
  - `ph_y_mctq__fd__sleep_inertia` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__bed__end__24h_t(
  data,
  name = "ph_y_mctq__fd__bed__end__24h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd__bed__end__24h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd__bed__end__24h_t"
    ))
  )

## End(Not run)
```

`compute_ph_y_mctq__fd__bed__end__36h_t`

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - In bed end): Time [36 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__fd__bed__end__36h_t` Munich Chronotype Questionnaire [Youth] (Free Day - In bed end): Time [36 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__fd__sleep__end__36h_t` (intermediate score)
  - `ph_y_mctq__fd__sleep_inertia` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__bed__end__36h_t(
  data,
  name = "ph_y_mctq__fd__bed__end__36h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd__bed__end__36h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd__bed__end__36h_t"
    ))
  )

## End(Not run)
```

`compute_ph_y_mctq__fd__bed__start__24h_t`

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - In bed start): Time [24 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__fd__bed__start__24h_t` Munich Chronotype Questionnaire [Youth] (Free Day - In bed start): Time [24 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__fd_001__02`
  - `ph_y_mctq__fd_001__01a`
  - `ph_y_mctq__fd_001__01b`
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__bed__start__24h_t(
  data,
  name = "ph_y_mctq__fd__bed__start__24h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__fd__bed__start__24h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__fd_001__02",
    "ph_y_mctq__fd_001__01a",
    "ph_y_mctq__fd_001__01b",
    "ph_y_mctq__fd__bed__start__24h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__fd__bed__start__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - In bed start): Time [36 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__fd__bed__start__36h_t` Munich Chronotype Questionnaire [Youth] (Free Day - In bed start): Time [36 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__fd_001__02`
  - `ph_y_mctq__fd_001__01a`
  - `ph_y_mctq__fd_001__01b`
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__bed__start__36h_t(
  data,
  name = "ph_y_mctq__fd__bed__start__36h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__fd__bed__start__36h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__fd_001__02",
    "ph_y_mctq__fd_001__01a",
    "ph_y_mctq__fd_001__01b",
    "ph_y_mctq__fd__bed__start__36h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__fd__bed_sum

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - In bed): Sum"

Description

Computes the summary score `ph_y_mctq__fd__bed_sum` Munich Chronotype Questionnaire [Youth] (Free Day - In bed): Sum

- *Summarized variables:*
  - `ph_y_mctq__fd__bed__end__36h_t` (intermediate score)
  - `ph_y_mctq__fd__bed__start__36h_t` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__bed_sum(
  data,
  name = "ph_y_mctq__fd__bed_sum",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd__bed_sum(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd__bed_sum"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep__end__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep end): Time [24 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__fd__sleep__end__24h_t` Munich Chronotype Questionnaire [Youth] (Free Day - Sleep end): Time [24 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__fd_005__02`
  - `ph_y_mctq__fd_005__01a`
  - `ph_y_mctq__fd_005__01b`
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep__end__24h_t(
  data,
  name = "ph_y_mctq__fd__sleep__end__24h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__fd__sleep__end__24h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__fd_005__02",
    "ph_y_mctq__fd_005__01a",
    "ph_y_mctq__fd_005__01b",
    "ph_y_mctq__fd__sleep__end__24h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep__end__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep end): Time [36 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__fd__sleep__end__36h_t` Munich Chronotype Questionnaire [Youth] (Free Day - Sleep end): Time [36 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__fd_005__02`
  - `ph_y_mctq__fd_005__01a`
  - `ph_y_mctq__fd_005__01b`
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep__end__36h_t(
  data,
  name = "ph_y_mctq__fd__sleep__end__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__fd__sleep__end__36h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__fd_005__02",
    "ph_y_mctq__fd_005__01a",
    "ph_y_mctq__fd_005__01b",
    "ph_y_mctq__fd__sleep__end__36h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep__mid__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep mid): Time [24 hour adjusted]"

Description

Computes the summary score ph_y_mctq__fd__sleep__mid__24h_t Munich Chronotype Questionnaire [Youth] (Free Day - Sleep mid): Time [24 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__fd__sleep__onset__24h_t (intermediate score)
  - ph_y_mctq__fd__sleep_dur (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep__mid__24h_t(
  data,
  name = "ph_y_mctq__fd__sleep__mid__24h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd__sleep__mid__24h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd__sleep__mid__24h_t"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep__mid__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep mid): Time [36 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__fd__sleep__mid__36h_t` Munich Chronotype Questionnaire [Youth] (Free Day - Sleep mid): Time [36 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__fd__sleep__onset__36h_t` (intermediate score)
  - `ph_y_mctq__fd__sleep_period` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep__mid__36h_t(
  data,
  name = "ph_y_mctq__fd__sleep__mid__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd__sleep__mid__36h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd__sleep__mid__36h_t"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep__onset__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep onset): Time [24 hour adjusted]"

Description

Computes the summary score ph_y_mctq__fd__sleep__onset__24h_t Munich Chronotype Questionnaire [Youth] (Free Day - Sleep onset): Time [24 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__fd__sleep__start__24h_t (intermediate score)
  - ph_y_mctq__fd__sleep_latent (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep__onset__24h_t(
  data,
  name = "ph_y_mctq__fd__sleep__onset__24h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd__sleep__onset__24h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd__sleep__onset__24h_t"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep__onset__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep onset): Time [36 hour adjusted]"

Description

Computes the summary score ph_y_mctq__fd__sleep__onset__36h_t Munich Chronotype Questionnaire [Youth] (Free Day - Sleep onset): Time [36 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__fd__sleep__start__36h_t(intermediate score)
  - ph_y_mctq__fd__sleep_latent (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep__onset__36h_t(
  data,
  name = "ph_y_mctq__fd__sleep__onset__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd__sleep__onset__36h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd__sleep__onset__36h_t"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep__start__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep start): Time [24 hour adjusted]"

Description

Computes the summary score ph_y_mctq__fd__sleep__start__24h_t Munich Chronotype Questionnaire [Youth] (Free Day - Sleep start): Time [24 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__fd_002__02
  - ph_y_mctq__fd_002__01a
  - ph_y_mctq__fd_002__01b
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep__start__24h_t(
  data,
  name = "ph_y_mctq__fd__sleep__start__24h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__fd__sleep__start__24h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__fd_002__02",
    "ph_y_mctq__fd_002__01a",
    "ph_y_mctq__fd_002__01b",
    "ph_y_mctq__fd__sleep__start__24h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep__start__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep start): Time [36 hour adjusted]"

Description

Computes the summary score ph_y_mctq__fd__sleep__start__36h_t Munich Chronotype Questionnaire [Youth] (Free Day - Sleep start): Time [36 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__fd_002__02
  - ph_y_mctq__fd_002__01a
  - ph_y_mctq__fd_002__01b
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep__start__36h_t(
  data,
  name = "ph_y_mctq__fd__sleep__start__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__fd__sleep__start__36h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__fd_002__02",
    "ph_y_mctq__fd_002__01a",
    "ph_y_mctq__fd_002__01b",
    "ph_y_mctq__fd__sleep__start__36h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep__waso_sum

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep wakenings after sleep onset): Sum"

Description

Computes the summary score ph_y_mctq__fd__sleep__waso_sum Munich Chronotype Questionnaire [Youth] (Free Day - Sleep wakenings after sleep onset): Sum

- *Summarized variables:*
  - ph_y_mctq__fd_004
  - ph_y_mctq__fd_004__01
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep__waso_sum(
  data,
  name = "ph_y_mctq__fd__sleep__waso_sum",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__fd__sleep__waso_sum(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__fd_004",
    "ph_y_mctq__fd_004__01",
    "ph_y_mctq__fd__sleep__waso_sum"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep_dur

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep): Duration"

Description

Computes the summary score `ph_y_mctq__fd__sleep_dur` Munich Chronotype Questionnaire [Youth] (Free Day - Sleep): Duration

- *Summarized variables:*
  - `ph_y_mctq__fd__sleep__end__36h_t` (intermediate score)
  - `ph_y_mctq__fd__sleep__onset__36h_t` (intermediate score)
  - `ph_y_mctq__fd__sleep__waso_sum` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep_dur(
  data,
  name = "ph_y_mctq__fd__sleep_dur",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd__sleep_dur(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd__sleep_dur"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep_inertia

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep): Inertia"

Description

Computes the summary score ph_y_mctq__fd__sleep_inertia Munich Chronotype Questionnaire [Youth] (Free Day - Sleep): Inertia

- *Summarized variables:*
  - ph_y_mctq__fd_006
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep_inertia(
  data,
  name = "ph_y_mctq__fd__sleep_inertia",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__fd__sleep_inertia(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__fd_006",
    "ph_y_mctq__fd__sleep_inertia"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep_latent

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep): Latency"

Description

Computes the summary score ph_y_mctq__fd__sleep_latent Munich Chronotype Questionnaire [Youth] (Free Day - Sleep): Latency

- *Summarized variables:*
  - ph_y_mctq__fd_003
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep_latent(
  data,
  name = "ph_y_mctq__fd__sleep_latent",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__fd__sleep_latent(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__fd_003",
    "ph_y_mctq__fd__sleep_latent"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__fd__sleep_period

Compute "Munich Chronotype Questionnaire [Youth] (Free Day - Sleep): Period"

Description

Computes the summary score `ph_y_mctq__fd__sleep_period` Munich Chronotype Questionnaire [Youth] (Free Day - Sleep): Period

- *Summarized variables:*
  - `ph_y_mctq__fd__sleep__end__36h_t` (intermediate score)
  - `ph_y_mctq__fd__sleep__onset__36h_t` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd__sleep_period(
  data,
  name = "ph_y_mctq__fd__sleep_period",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd__sleep_period(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd__sleep_period"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__fd_count

Compute "Munich Chronotype Questionnaire [Youth] (Free Day): Count"

Description

Computes the summary score ph_y_mctq__fd_count Munich Chronotype Questionnaire [Youth] (Free Day): Count

- *Summarized variables:*
  - ph_y_mctq__sd_count (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__fd_count(data, name = "ph_y_mctq__fd_count", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__fd_count(data) |>
  select(
    any_of(c(
      "ph_y_mctq__fd_count"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__raw__36h_chrono

Compute "Munich Chronotype Questionnaire [Youth] (Raw: Chronotype): Time [36 hour adjusted]"

Description

Computes the summary score ph_y_mctq__raw__36h_chrono Munich Chronotype Questionnaire [Youth] (Raw: Chronotype): Time [36 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__fd__sleep_dur (intermediate score)
  - ph_y_mctq__sd__sleep_dur (intermediate score)
  - ph_y_mctq__fd__sleep__mid__36h_t (intermediate score)
  - ph_y_mctq__fd__sleep__onset__36h_t (intermediate score)
  - ph_y_mctq__sleep_dur (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__raw__36h_chrono(
  data,
  name = "ph_y_mctq__raw__36h_chrono",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__raw__36h_chrono(data) |>
  select(
    any_of(c(
      "ph_y_mctq__raw__36h_chrono"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__school__leave__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Schedule leave): Time [24 hour adjusted]"

Description

Computes the summary score ph_y_mctq__school__leave__24h_t Munich Chronotype Questionnaire [Youth] (School Schedule leave): Time [24 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__school_003__02
  - ph_y_mctq__school_003__01a
  - ph_y_mctq__school_003__01b
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__school__leave__24h_t(
  data,
  name = "ph_y_mctq__school__leave__24h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__school__leave__24h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__school_003__02",
    "ph_y_mctq__school_003__01a",
    "ph_y_mctq__school_003__01b",
    "ph_y_mctq__school__leave__24h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__school__leave__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Schedule leave): Time [36 hour adjusted]"

Description

Computes the summary score ph_y_mctq__school__leave__36h_t Munich Chronotype Questionnaire [Youth] (School Schedule leave): Time [36 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__school_003__02
  - ph_y_mctq__school_003__01a
  - ph_y_mctq__school_003__01b
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__school__leave__36h_t(
  data,
  name = "ph_y_mctq__school__leave__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__school__leave__36h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__school_003__02",
    "ph_y_mctq__school_003__01a",
    "ph_y_mctq__school_003__01b",
    "ph_y_mctq__school__leave__36h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__school__start__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Schedule start): Time [24 hour adjusted]"

Description

Computes the summary score ph_y_mctq__school__start__24h_t Munich Chronotype Questionnaire [Youth] (School Schedule start): Time [24 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__school_002__02

  - ph_y_mctq__school_002__01a
  - ph_y_mctq__school_002__01b

- *Excluded values:* none

Usage

```
compute_ph_y_mctq__school__start__24h_t(
  data,
  name = "ph_y_mctq__school__start__24h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__school__start__24h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__school_002__02",
    "ph_y_mctq__school_002__01a",
    "ph_y_mctq__school_002__01b",
    "ph_y_mctq__school__start__24h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__school__start__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Schedule start): Time [36 hour adjusted]"

Description

Computes the summary score ph_y_mctq__school__start__36h_t Munich Chronotype Questionnaire [Youth] (School Schedule start): Time [36 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__school_002__02
  - ph_y_mctq__school_002__01a
  - ph_y_mctq__school_002__01b
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__school__start__36h_t(
  data,
  name = "ph_y_mctq__school__start__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__school__start__36h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__school_002__02",
    "ph_y_mctq__school_002__01a",
    "ph_y_mctq__school_002__01b",
    "ph_y_mctq__school__start__36h_t"
  ))
)

## End(Not run)
```

`compute_ph_y_mctq__sd__bed__end__24h_t`

Compute "Munich Chronotype Questionnaire [Youth] (School Day - In bed end): Time [24 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__sd__bed__end__24h_t` Munich Chronotype Questionnaire [Youth] (School Day - In bed end): Time [24 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__sd__sleep__end__24h_t` (intermediate score)
  - `ph_y_mctq__sd__sleep_inertia` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__bed__end__24h_t(
  data,
  name = "ph_y_mctq__sd__bed__end__24h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sd__bed__end__24h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sd__bed__end__24h_t"
    ))
  )

## End(Not run)
```

`compute_ph_y_mctq__sd__bed__end__36h_t`

Compute "Munich Chronotype Questionnaire [Youth] (School Day - In bed end): Time [36 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__sd__bed__end__36h_t` Munich Chronotype Questionnaire [Youth] (School Day - In bed end): Time [36 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__sd__sleep__end__36h_t` (intermediate score)
  - `ph_y_mctq__sd__sleep_inertia` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__bed__end__36h_t(
  data,
  name = "ph_y_mctq__sd__bed__end__36h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sd__bed__end__36h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sd__bed__end__36h_t"
    ))
  )

## End(Not run)
```

`compute_ph_y_mctq__sd__bed__start__24h_t`
Compute "Munich Chronotype Questionnaire [Youth] (School Day - In bed start): Time [24 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__sd__bed__start__24h_t` Munich Chronotype Questionnaire [Youth] (School Day - In bed start): Time [24 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__sd_001__02`
  - `ph_y_mctq__sd_001__01a`
  - `ph_y_mctq__sd_001__01b`
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__bed__start__24h_t(
  data,
  name = "ph_y_mctq__sd__bed__start__24h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd__bed__start__24h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__sd_001__02",
    "ph_y_mctq__sd_001__01a",
    "ph_y_mctq__sd_001__01b",
    "ph_y_mctq__sd__bed__start__24h_t"
```

```
  ))
)

## End(Not run)
```

`compute_ph_y_mctq__sd__bed__start__36h_t` *Compute "Munich Chronotype Questionnaire [Youth] (School Day - In bed start): Time [36 hour adjusted]"*

Description

Computes the summary score `ph_y_mctq__sd__bed__start__36h_t` Munich Chronotype Questionnaire [Youth] (School Day - In bed start): Time [36 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__sd_001__02`
  - `ph_y_mctq__sd_001__01a`
  - `ph_y_mctq__sd_001__01b`
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__bed__start__36h_t(
  data,
  name = "ph_y_mctq__sd__bed__start__36h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd__bed__start__36h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__sd_001__02",
    "ph_y_mctq__sd_001__01a",
    "ph_y_mctq__sd_001__01b",
    "ph_y_mctq__sd__bed__start__36h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__sd__bed_sum

Compute "Munich Chronotype Questionnaire [Youth] (School Day - In bed): Sum"

Description

Computes the summary score `ph_y_mctq__sd__bed_sum` Munich Chronotype Questionnaire [Youth] (School Day - In bed): Sum

- *Summarized variables:*
  - `ph_y_mctq__sd__bed__end__36h_t` (intermediate score)
  - `ph_y_mctq__sd__bed__start__36h_t` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__bed_sum(
  data,
  name = "ph_y_mctq__sd__bed_sum",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sd__bed_sum(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sd__bed_sum"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep__end__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep end): Time [24 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__sd__sleep__end__24h_t` Munich Chronotype Questionnaire [Youth] (School Day - Sleep end): Time [24 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__sd_005__02`
  - `ph_y_mctq__sd_005__01a`
  - `ph_y_mctq__sd_005__01b`
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep__end__24h_t(
  data,
  name = "ph_y_mctq__sd__sleep__end__24h_t",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd__sleep__end__24h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__sd_005__02",
    "ph_y_mctq__sd_005__01a",
    "ph_y_mctq__sd_005__01b",
    "ph_y_mctq__sd__sleep__end__24h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep__end__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep end): Time [36 hour adjusted]"

Description

Computes the summary score `ph_y_mctq__sd__sleep__end__36h_t` Munich Chronotype Questionnaire [Youth] (School Day - Sleep end): Time [36 hour adjusted]

- *Summarized variables:*
  - `ph_y_mctq__sd_005__02`
  - `ph_y_mctq__sd_005__01a`
  - `ph_y_mctq__sd_005__01b`
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep__end__36h_t(
  data,
  name = "ph_y_mctq__sd__sleep__end__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd__sleep__end__36h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__sd_005__02",
    "ph_y_mctq__sd_005__01a",
    "ph_y_mctq__sd_005__01b",
    "ph_y_mctq__sd__sleep__end__36h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep__mid__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep mid): Time [24 hour adjusted]"

Description

Computes the summary score ph_y_mctq__sd__sleep__mid__24h_t Munich Chronotype Questionnaire [Youth] (School Day - Sleep mid): Time [24 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__sd__sleep__onset__24h_t (intermediate score)
  - ph_y_mctq__sd__sleep_dur (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep__mid__24h_t(
  data,
  name = "ph_y_mctq__sd__sleep__mid__24h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sd__sleep__mid__24h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sd__sleep__mid__24h_t"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep__mid__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep mid): Time [36 hour adjusted]"

Description

Computes the summary score ph_y_mctq__sd__sleep__mid__36h_t Munich Chronotype Questionnaire [Youth] (School Day - Sleep mid): Time [36 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__sd__sleep__onset__36h_t (intermediate score)
  - ph_y_mctq__sd__sleep_period (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep__mid__36h_t(
  data,
  name = "ph_y_mctq__sd__sleep__mid__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sd__sleep__mid__36h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sd__sleep__mid__36h_t"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep__onset__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep onset): Time [24 hour adjusted]"

Description

Computes the summary score ph_y_mctq__sd__sleep__onset__24h_t Munich Chronotype Questionnaire [Youth] (School Day - Sleep onset): Time [24 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__sd__sleep__start__24h_t (intermediate score)
  - ph_y_mctq__sd__sleep_latent (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep__onset__24h_t(
  data,
  name = "ph_y_mctq__sd__sleep__onset__24h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sd__sleep__onset__24h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sd__sleep__onset__24h_t"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep__onset__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep onset): Time [36 hour adjusted]"

Description

Computes the summary score ph_y_mctq__sd__sleep__onset__36h_t Munich Chronotype Questionnaire [Youth] (School Day - Sleep onset): Time [36 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__sd__sleep__start__36h_t (intermediate score)
  - ph_y_mctq__sd__sleep_latent (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep__onset__36h_t(
  data,
  name = "ph_y_mctq__sd__sleep__onset__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sd__sleep__onset__36h_t(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sd__sleep__onset__36h_t"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep__start__24h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep start): Time [24 hour adjusted]"

Description

Computes the summary score ph_y_mctq__sd__sleep__start__24h_t Munich Chronotype Questionnaire [Youth] (School Day - Sleep start): Time [24 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__sd_002__02
  - ph_y_mctq__sd_002__01a
  - ph_y_mctq__sd_002__01b
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep__start__24h_t(
  data,
  name = "ph_y_mctq__sd__sleep__start__24h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd__sleep__start__24h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__sd_002__02",
    "ph_y_mctq__sd_002__01a",
    "ph_y_mctq__sd_002__01b",
    "ph_y_mctq__sd__sleep__start__24h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep__start__36h_t

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep start): Time [36 hour adjusted]"

Description

Computes the summary score ph_y_mctq__sd__sleep__start__36h_t Munich Chronotype Questionnaire [Youth] (School Day - Sleep start): Time [36 hour adjusted]

- *Summarized variables:*
  - ph_y_mctq__sd_002__02
  - ph_y_mctq__sd_002__01a
  - ph_y_mctq__sd_002__01b
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep__start__36h_t(
  data,
  name = "ph_y_mctq__sd__sleep__start__36h_t",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd__sleep__start__36h_t(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__sd_002__02",
    "ph_y_mctq__sd_002__01a",
    "ph_y_mctq__sd_002__01b",
    "ph_y_mctq__sd__sleep__start__36h_t"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep__waso_sum

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep wakenings after sleep onset): Sum"

Description

Computes the summary score ph_y_mctq__sd__sleep__waso_sum Munich Chronotype Questionnaire [Youth] (School Day - Sleep wakenings after sleep onset): Sum

- *Summarized variables:*
  - ph_y_mctq__sd_004
  - ph_y_mctq__sd_004__01
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep__waso_sum(
  data,
  name = "ph_y_mctq__sd__sleep__waso_sum",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd__sleep__waso_sum(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__sd_004",
    "ph_y_mctq__sd_004__01",
    "ph_y_mctq__sd__sleep__waso_sum"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep_dur

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep): Duration"

Description

Computes the summary score `ph_y_mctq__sd__sleep_dur` Munich Chronotype Questionnaire [Youth] (School Day - Sleep): Duration

- *Summarized variables:*
  - `ph_y_mctq__sd__sleep__end__36h_t` (intermediate score)
  - `ph_y_mctq__sd__sleep__onset__36h_t` (intermediate score)
  - `ph_y_mctq__sd__sleep__waso_sum` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep_dur(
  data,
  name = "ph_y_mctq__sd__sleep_dur",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sd__sleep_dur(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sd__sleep_dur"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep_inertia

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep): Inertia"

Description

Computes the summary score ph_y_mctq__sd__sleep_inertia Munich Chronotype Questionnaire [Youth] (School Day - Sleep): Inertia

- *Summarized variables:*
  - ph_y_mctq__sd_006
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep_inertia(
  data,
  name = "ph_y_mctq__sd__sleep_inertia",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd__sleep_inertia(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__sd_006",
    "ph_y_mctq__sd__sleep_inertia"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep_latent

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep): Latency"

Description

Computes the summary score `ph_y_mctq__sd__sleep_latent` Munich Chronotype Questionnaire [Youth] (School Day - Sleep): Latency

- *Summarized variables:*
  - `ph_y_mctq__sd_003`
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep_latent(
  data,
  name = "ph_y_mctq__sd__sleep_latent",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd__sleep_latent(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__sd_003",
    "ph_y_mctq__sd__sleep_latent"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__sd__sleep_period

Compute "Munich Chronotype Questionnaire [Youth] (School Day - Sleep): Period"

Description

Computes the summary score ph_y_mctq__sd__sleep_period Munich Chronotype Questionnaire [Youth] (School Day - Sleep): Period

- *Summarized variables:*
  - ph_y_mctq__sd__sleep__end__36h_t (intermediate score)
  - ph_y_mctq__sd__sleep__onset__36h_t (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd__sleep_period(
  data,
  name = "ph_y_mctq__sd__sleep_period",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sd__sleep_period(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sd__sleep_period"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq__sd_count

Compute "Munich Chronotype Questionnaire [Youth] (School Day): Count"

Description

Computes the summary score ph_y_mctq__sd_count Munich Chronotype Questionnaire [Youth] (School Day): Count

- *Summarized variables:*
  - ph_y_mctq__school_001
  - ph_y_mctq__school_001__01
  - ph_y_mctq__school_001__v01 (>= 7.0.0)
  - ph_y_mctq__school_001__01__v1 (>= 7.0.0)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sd_count(data, name = "ph_y_mctq__sd_count", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Details

In data release before 7.0 and 7.0.0 of the ABCDscores package, the variables ph_y_mctq__school_001__v01 and ph_y_mctq__school_001__01__v1 were not available. In this case, the function will create these variables internally and fill them with NA values. After 7.0.0, these variables are expected to be present.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_ph_y_mctq__sd_count(data)
select(
  data,
  any_of(c(
    "ph_y_mctq__school_001",
    "ph_y_mctq__school_001__01",
    "ph_y_mctq__school_001__v01",
    "ph_y_mctq__school_001__01__v1",
    "ph_y_mctq__sd_count"
  ))
)

## End(Not run)
```

---

compute_ph_y_mctq__sleep_dur

Compute "Munich Chronotype Questionnaire [Youth] (Sleep): Duration"

Description

Computes the summary score ph_y_mctq__sleep_dur Munich Chronotype Questionnaire [Youth] (Sleep): Duration

- *Summarized variables:*
  - ph_y_mctq__sd_count (intermediate score)
  - ph_y_mctq__sd__sleep_dur (intermediate score)
  - ph_y_mctq__fd__sleep_dur (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sleep_dur(
  data,
  name = "ph_y_mctq__sleep_dur",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sleep_dur(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sleep_dur"
    ))
  )

## End(Not run)
```

`compute_ph_y_mctq__sleep_loss`
Compute "Munich Chronotype Questionnaire [Youth] (Sleep): Loss"

Description

Computes the summary score `ph_y_mctq__sleep_loss` Munich Chronotype Questionnaire [Youth] (Sleep): Loss

- *Summarized variables:*
  - `ph_y_mctq__fd__sleep_period` (intermediate score)
  - `ph_y_mctq__sd__sleep_period` (intermediate score)
  - `ph_y_mctq__sd_count` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sleep_loss(
  data,
  name = "ph_y_mctq__sleep_loss",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sleep_loss(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sleep_loss"
    ))
  )

## End(Not run)
```

compute_ph_y_mctq__sleep_period *Compute "Munich Chronotype Questionnaire [Youth] (Sleep): Period"*

Description

Computes the summary score ph_y_mctq__sleep_period Munich Chronotype Questionnaire [Youth] (Sleep): Period

- *Summarized variables:*
  - ph_y_mctq__sd_count (intermediate score)
  - ph_y_mctq__sd__sleep_period (intermediate score)
  - ph_y_mctq__fd__sleep_period (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__sleep_period(
  data,
  name = "ph_y_mctq__sleep_period",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__sleep_period(data) |>
  select(
    any_of(c(
      "ph_y_mctq__sleep_period"
    ))
  )

## End(Not run)
```

`compute_ph_y_mctq__socjl_absl` *Compute "Munich Chronotype Questionnaire [Youth] (Social Jetlag: Absolute): Time"*

Description

Computes the summary score `ph_y_mctq__socjl_absl` Munich Chronotype Questionnaire [Youth] (Social Jetlag: Absolute): Time

- *Summarized variables:*
  - `ph_y_mctq__fd__sleep__mid__36h_t` (intermediate score)
  - `ph_y_mctq__sd__sleep__mid__36h_t` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__socjl_absl(
  data,
  name = "ph_y_mctq__socjl_absl",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__socjl_absl(data) |>
  select(
    any_of(c(
      "ph_y_mctq__socjl_absl"
    ))
  )

## End(Not run)
```

compute_ph_y_mctq__socjl_rel *Compute "Munich Chronotype Questionnaire [Youth] (Social Jetlag: Relative): Time"*

Description

Computes the summary score `ph_y_mctq__socjl_rel` Munich Chronotype Questionnaire [Youth] (Social Jetlag: Relative): Time

- *Summarized variables:*
  - `ph_y_mctq__fd__sleep__mid__36h_t` (intermediate score)
  - `ph_y_mctq__sd__sleep__mid__36h_t` (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq__socjl_rel(
  data,
  name = "ph_y_mctq__socjl_rel",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq__socjl_rel(data) |>
  select(
    any_of(c(
      "ph_y_mctq__socjl_rel"
    ))
  )

## End(Not run)
```

compute_ph_y_mctq_all *Compute all the MCTQ variables*

Description

Compute all the MCTQ variables

Usage

```
compute_ph_y_mctq_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Details

Make sure the data is the full set of all variables from MCTQ.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ph_y_mctq_all(data)

## End(Not run)
```

compute_ph_y_mctq_chrono *Compute "Munich Chronotype Questionnaire [Youth] (Chronotype): Time"*

Description

Computes the summary score ph_y_mctq_chrono Munich Chronotype Questionnaire [Youth] (Chronotype): Time

- *Summarized variables:*
  - ph_y_mctq__fd_007
  - ph_y_mctq__fd__sleep_period (intermediate score)
  - ph_y_mctq__sd__sleep_period (intermediate score)
  - ph_y_mctq__fd__sleep__mid__36h_t (intermediate score)
  - ph_y_mctq__fd__sleep__onset__36h_t (intermediate score)
  - ph_y_mctq__sleep_period (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq_chrono(data, name = "ph_y_mctq_chrono", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq_chrono(data) |>
  select(
    any_of(c(
      "ph_y_mctq_chrono"
    ))
  )

## End(Not run)
```

---

compute_ph_y_mctq_outlier

Compute "Munich Chronotype Questionnaire [Youth]: Outlier"

Description

Computes the summary score ph_y_mctq_outlier Munich Chronotype Questionnaire [Youth]: Outlier

- *Summarized variables:*
  - ph_y_mctq__sd__sleep__onset__36h_t (intermediate score)
  - ph_y_mctq__fd__sleep__onset__36h_t (intermediate score)
  - ph_y_mctq__sd__sleep__mid__36h_t (intermediate score)
  - ph_y_mctq__fd__sleep__mid__36h_t (intermediate score)
  - ph_y_mctq__sd__sleep_dur (intermediate score)
  - ph_y_mctq__fd__sleep_dur (intermediate score)
- *Excluded values:* none

Usage

```
compute_ph_y_mctq_outlier(data, name = "ph_y_mctq_outlier", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_mctq_outlier(data) |>
  select(
    any_of(c(
      "ph_y_mctq_outlier"
    ))
  )

## End(Not run)
```

---

compute_ph_y_pds__f__categ_nm

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Female): Approximate tanner stages - Number missing"

Description

Computes the summary score ph_y_pds__f__categ_nm Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Female): Approximate tanner stages - Number missing

- *Summarized variables:*
  - ph_y_pds_002
  - ph_y_pds__f_001
  - ph_y_pds__f_002
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_y_pds__f__categ_nm(
  data,
  name = "ph_y_pds__f__categ_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_y_pds__f_categ()

---

compute_ph_y_pds__f_nm

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Female): Number missing"

Description

Computes the summary score ph_y_pds__f_nm Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Female): Number missing

- *Summarized variables:*
  - ph_y_pds_001
  - ph_y_pds_002
  - ph_y_pds_003
  - ph_y_pds__f_001
  - ph_y_pds__f_002
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_y_pds__f_nm(
  data,
  name = "ph_y_pds__f_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_y_pds__f_mean()

---

compute_ph_y_pds__m__categ_nm

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Male): Approximate tanner stages - Number missing"

Description

Computes the summary score ph_y_pds__m__categ_nm Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Male): Approximate tanner stages - Number missing

- *Summarized variables:*
  - ph_y_pds_002
  - ph_y_pds__m_001
  - ph_y_pds__m_002
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_y_pds__m__categ_nm(
  data,
  name = "ph_y_pds__m__categ_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_y_pds__m_categ()

---

compute_ph_y_pds__m_nm

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Male): Number missing"

Description

Computes the summary score ph_y_pds__m_nm Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Male): Number missing

- *Summarized variables:*
  - ph_y_pds_001
  - ph_y_pds_002
  - ph_y_pds_003
  - ph_y_pds__m_001
  - ph_y_pds__m_002
- *Excluded values:*
  - 777
  - 999

Usage

```
compute_ph_y_pds__m_nm(
  data,
  name = "ph_y_pds__m_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_y_pds__m_mean()

---

compute_ph_y_pds_all *Compute all the* ph_y_pds *summary scores*

Description

This is a high-level function that computes all summary scores in this table. Make sure the data contains all the necessary columns.

Usage

```
compute_ph_y_pds_all(data)
```

Arguments

data	tbl. Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_ph_y_pds_all(data)

## End(Not run)
```

`compute_ss_use_onset_age` *Compute annual session substance use age of onset for a participant*

Description

For each participant returns the age of onset for the requested substance(s). The function:

- determines the session of first use (via `compute_ss_use_onset_event()`) and extracts the reported age at that visit;
- for substance(s) that have detailed first-use age items, also extracts the earliest reported age of first use across the relevant substance-specific onset items; and
- returns the age of first use if available, otherwise returns the age reported at the visit. If neither value is available the result is `NA`.

Usage

```
compute_ss_use_onset_age(data, name, substance, algo = NULL)
```

Arguments

`data`	tibble. A dataframe produced by `prepare_data_sdsu()`.
`name`	character(1). Name of the output score column to validate.
`substance`	character (vector). The substance(s) to compute the score for. Must be one or several of the following values: • `"Alcohol (Sipping)"` • `"Nicotine (Puffing)"` • `"Marijuana (Puffing)"` • `"Alcohol"` • `"Nicotine"` • `"Marijuana"` • `"Cocaine or Crack Cocaine"` • `"Methamphetamine, Meth, or Crystal Meth"` • `"Ketamine or Special K"` • `"Heroin, Opium, Junk, Smack, or Dope"` • `"Cathinones such as Bath Salts, Drone, or Meph"` • `"Ecstasy, Molly, or MDMA"` • `"GHB, Liquid G, or Georgia Homeboy"`

- "Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Anabolic Steroids"
- "Inhalants"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Salvia"
- "Prescription Stimulants"
- "Prescription Opioids"
- "'Fake' Marijuana or Synthetics"
- "Other substances"
- "Nicotine Vaping Products"
- "Tobacco Cigarette"
- "Cigars, Little Cigars, or Cigarillos"
- "Tobacco in a Pipe"
- "Hookah with Tobacco"
- "Nicotine Replacements"
- "Smokeless Tobacco, Chew, or Snus"
- "Flavored Vaping Products"
- "Smoking Marijuana Flower"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Marijuana Concentrates"
- "Concentrated Marijuana Tinctures"
- "Blunts or Combined Tobacco and Marijuana in Joints"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "CBD (Non-Medical Use)"
- "Alcohol (Including low-level use)"
- "Nicotine (Including low-level use)"
- "Marijuana (Including low-level use)"
- "Substance use (Not including alcohol, nicotine, and cannabis)"
- "Substance use"
- "Substance use (Including low-level use)"

`algo` character. Mapping algorithm to apply to mid-year sessions. Allowed values:

- "next_existing_fy": assign a mid year to the next existing full year. If a participant ends with mid-year visits, those terminal mid-year records are dropped.
- "next_potential_fy": assign a mid year to the next existing full year when present, otherwise assign to the next forecasted full year (that may never materialize).

- "next_immediate_fy": assign a mid year to the next full year regardless of whether that full year record exists or not.
- "remove_my": drop mid-year events and keep only full-year events. If NULL (default) no mapping is performed and data is returned unchanged.

Value

A tibble with columns participant_id and a character column named by name containing the age of onset or NA if there was no use.

See Also

map_mid_years()

Examples

```
## Not run:
deap_data |>
  prepare_data_sdsu() |>
  compute_ss_use_onset_age(
    name = "su_alc_onset_age",
    substance = "Alcohol"
  )

## End(Not run)
```

---

compute_ss_use_onset_event

Compute substance use onset session for each participant

Description

For each participant returns the session (character session_id) of first use for the requested substance(s). The function:

- maps or removes mid-year sessions according to algo (see map_mid_years()) by default no.
- for each participant selects the earliest session where any use was observed.

Usage

```
compute_ss_use_onset_event(data, name, substance, algo = NULL)
```

Arguments

data	tibble. A dataframe produced by prepare_data_sdsu().
name	character(1). Name of the output score column to validate.
substance	character (vector). The substance(s) to compute the score for. Must be one or several of the following values:

- "Alcohol (Sipping)"
- "Nicotine (Puffing)"
- "Marijuana (Puffing)"
- "Alcohol"
- "Nicotine"
- "Marijuana"
- "Cocaine or Crack Cocaine"
- "Methamphetamine, Meth, or Crystal Meth"
- "Ketamine or Special K"
- "Heroin, Opium, Junk, Smack, or Dope"
- "Cathinones such as Bath Salts, Drone, or Meph"
- "Ecstasy, Molly, or MDMA"
- "GHB, Liquid G, or Georgia Homeboy"
- "Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Anabolic Steroids"
- "Inhalants"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Salvia"
- "Prescription Stimulants"
- "Prescription Opioids"
- "'Fake' Marijuana or Synthetics"
- "Other substances"
- "Nicotine Vaping Products"
- "Tobacco Cigarette"
- "Cigars, Little Cigars, or Cigarillos"
- "Tobacco in a Pipe"
- "Hookah with Tobacco"
- "Nicotine Replacements"
- "Smokeless Tobacco, Chew, or Snus"
- "Flavored Vaping Products"
- "Smoking Marijuana Flower"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Marijuana Concentrates"
- "Concentrated Marijuana Tinctures"
- "Blunts or Combined Tobacco and Marijuana in Joints"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "CBD (Non-Medical Use)"

- "Alcohol (Including low-level use)"
- "Nicotine (Including low-level use)"
- "Marijuana (Including low-level use)"
- "Substance use (Not including alcohol, nicotine, and cannabis)"
- "Substance use"
- "Substance use (Including low-level use)"

algo character. Mapping algorithm to apply to mid-year sessions. Allowed values:

- "next_existing_fy": assign a mid year to the next existing full year. If a participant ends with mid-year visits, those terminal mid-year records are dropped.
- "next_potential_fy": assign a mid year to the next existing full year when present, otherwise assign to the next forecasted full year (that may never materialize).
- "next_immediate_fy": assign a mid year to the next full year regardless of whether that full year record exists or not.
- "remove_my": drop mid-year events and keep only full-year events. If NULL (default) no mapping is performed and data is returned unchanged.

Value

A tibble with columns participant_id and a character column named by name containing the session of onset or NA if there was no use.

See Also

map_mid_years()

Examples

```
## Not run:
deap_data |>
  prepare_data_sdsu() |>
  compute_ss_use_onset_event(
    name = "su_alc_onset_event",
    substance = "Alcohol"
  )

## End(Not run)
```

---

compute_ss_use_yn *Compute substance use Y/N for a participant*

Description

For each participant computes a binary (1/0) indicator indicating any use of (one of) the given substance(s) at a session (or cumulatively up to and including that session when cumulative = TRUE). Parameter algo is set to "next_existing_fy".

Usage

```
compute_ss_use_yn(
  data,
  name,
  substance,
  algo = "next_existing_fy",
  cumulative = FALSE
)
```

Arguments

data	tibble. A dataframe produced by prepare_data_sdsu().
name	character(1). Name of the output score column to validate.
substance	character (vector). The substance(s) to compute the score for. Must be one or several of the following values:

- "Alcohol (Sipping)"
- "Nicotine (Puffing)"
- "Marijuana (Puffing)"
- "Alcohol"
- "Nicotine"
- "Marijuana"
- "Cocaine or Crack Cocaine"
- "Methamphetamine, Meth, or Crystal Meth"
- "Ketamine or Special K"
- "Heroin, Opium, Junk, Smack, or Dope"
- "Cathinones such as Bath Salts, Drone, or Meph"
- "Ecstasy, Molly, or MDMA"
- "GHB, Liquid G, or Georgia Homeboy"
- "Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Anabolic Steroids"
- "Inhalants"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Salvia"
- "Prescription Stimulants"
- "Prescription Opioids"
- "'Fake' Marijuana or Synthetics"
- "Other substances"
- "Nicotine Vaping Products"
- "Tobacco Cigarette"
- "Cigars, Little Cigars, or Cigarillos"

- "Tobacco in a Pipe"
- "Hookah with Tobacco"
- "Nicotine Replacements"
- "Smokeless Tobacco, Chew, or Snus"
- "Flavored Vaping Products"
- "Smoking Marijuana Flower"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Marijuana Concentrates"
- "Concentrated Marijuana Tinctures"
- "Blunts or Combined Tobacco and Marijuana in Joints"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "CBD (Non-Medical Use)"
- "Alcohol (Including low-level use)"
- "Nicotine (Including low-level use)"
- "Marijuana (Including low-level use)"
- "Substance use (Not including alcohol, nicotine, and cannabis)"
- "Substance use"
- "Substance use (Including low-level use)"

`algo` character. Mapping algorithm to apply to mid-year sessions. Allowed values:

- "next_existing_fy": assign a mid year to the next existing full year. If a participant ends with mid-year visits, those terminal mid-year records are dropped.
- "next_potential_fy": assign a mid year to the next existing full year when present, otherwise assign to the next forecasted full year (that may never materialize).
- "next_immediate_fy": assign a mid year to the next full year regardless of whether that full year record exists or not.
- "remove_my": drop mid-year events and keep only full-year events. If NULL (default) no mapping is performed and data is returned unchanged.

`cumulative` logical(1). If FALSE (default), returns use at each session. If TRUE, returns 1 from the first session where use was observed onward (i.e. ever used up to and including that session).

Value

A tibble with columns participant_id, session_id and a numeric column named by name containing 1 (use) or 0 (no use).

See Also

map_mid_years()

Examples

```
## Not run:
deap_data |>
  prepare_data_sdsu() |>
  compute_ss_use_yn(
    name = "su_y_alc_use_yn",
    substance = "Alcohol"
  )

## End(Not run)
```

---

compute_su_p_ksads__aud_all

Compute all summary scores for su_p_ksads__aud

Description

This function computes all summary scores for the su_p_ksads__aud table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_su_p_ksads__aud_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

---

compute_su_p_ksads__dud_all

Compute all summary scores for su_p_ksads__dud

Description

This function computes all summary scores for the su_p_ksads__dud table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_su_p_ksads__dud_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

---

compute_su_y_alcexp__neg_nm

Compute "Alcohol Expectancies (AEQ-AB) [Youth] (Strength of negative expectancies): Number missing"

Description

Computes the summary score su_y_alcexp__neg_nm Alcohol Expectancies (AEQ-AB) [Youth] (Strength of negative expectancies): Number missing

- *Summarized variables:*
  - su_y_alcexp__neg_001
  - su_y_alcexp__neg_002
  - su_y_alcexp__neg_003
- *Excluded values:* none

Usage

```
compute_su_y_alcexp__neg_nm(data, name = "su_y_alcexp__neg_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_alcexp__neg_prsum()

`compute_su_y_alcexp__pos_nm`

Compute "Alcohol Expectancies (AEQ-AB) [Youth] (Strength of positive expectancies): Number missing"

Description

Computes the summary score `su_y_alcexp__pos_nm` Alcohol Expectancies (AEQ-AB) [Youth] (Strength of positive expectancies): Number missing

- *Summarized variables:*
  - `su_y_alcexp__pos_001`
  - `su_y_alcexp__pos_002`
  - `su_y_alcexp__pos_003`
- *Excluded values:* none

Usage

```
compute_su_y_alcexp__pos_nm(data, name = "su_y_alcexp__pos_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE` (default), the summary score will be appended to the input data frame. If `FALSE`, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_su_y_alcexp__pos_prsum()`

compute_su_y_alcexp_all

Compute all the su_y_alcexp scores

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_su_y_alcexp_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_alcexp_all(data)

## End(Not run)
```

compute_su_y_alchss_all

Compute all Alcohol Hangover Symptoms Scale (HSS) Youth summary scores

Description

compute all summary scores of Alcohol Hangover Symptoms Scale (HSS) Youth

Usage

```
compute_su_y_alchss_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_su_y_alchss_all(data)

## End(Not run)
```

---

compute_su_y_alchss_count
Compute "Alcohol Hangover Symptoms Scale (HSS) [Youth]: Count"

Description

Computes the summary score `su_y_alchss_count` Alcohol Hangover Symptoms Scale (HSS) [Youth]: Count

- *Summarized variables:*
  - `su_y_alchss_001`
  - `su_y_alchss_002`
  - `su_y_alchss_003`
  - `su_y_alchss_004`
  - `su_y_alchss_005`
  - `su_y_alchss_006`
  - `su_y_alchss_007`
  - `su_y_alchss_008`
  - `su_y_alchss_009`
  - `su_y_alchss_010`
  - `su_y_alchss_011`
  - `su_y_alchss_012`
  - `su_y_alchss_013`
  - `su_y_alchss_014`
  - `su_y_alchss_001__l`
  - `su_y_alchss_002__l`
  - `su_y_alchss_003__l`
  - `su_y_alchss_004__l`
  - `su_y_alchss_005__l`
  - `su_y_alchss_006__l`
  - `su_y_alchss_007__l`
  - `su_y_alchss_008__l`
  - `su_y_alchss_009__l`
  - `su_y_alchss_010__l`
  - `su_y_alchss_011__l`
  - `su_y_alchss_012__l`

  - su_y_alchss_013__l
  - su_y_alchss_014__l

- *Excluded values:* none
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
compute_su_y_alchss_count(
  data,
  name = "su_y_alchss_count",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_alchss_sum()

Examples

```
## Not run:
compute_su_y_alchss_count(data) |> View()

## End(Not run)
```

---

compute_su_y_alchss_nm

Compute "Alcohol Hangover Symptoms Scale (HSS) [Youth]: Number missing"

Description

Computes the summary score su_y_alchss_nm Alcohol Hangover Symptoms Scale (HSS) [Youth]: Number missing

- *Summarized variables:*
  - su_y_alchss_001
  - su_y_alchss_002
  - su_y_alchss_003
  - su_y_alchss_004
  - su_y_alchss_005
  - su_y_alchss_006
  - su_y_alchss_007
  - su_y_alchss_008
  - su_y_alchss_009
  - su_y_alchss_010
  - su_y_alchss_011
  - su_y_alchss_012
  - su_y_alchss_013
  - su_y_alchss_014
  - su_y_alchss_001__l
  - su_y_alchss_002__l
  - su_y_alchss_003__l
  - su_y_alchss_004__l
  - su_y_alchss_005__l
  - su_y_alchss_006__l
  - su_y_alchss_007__l
  - su_y_alchss_008__l
  - su_y_alchss_009__l
  - su_y_alchss_010__l
  - su_y_alchss_011__l
  - su_y_alchss_012__l
  - su_y_alchss_013__l
  - su_y_alchss_014__l
- *Excluded values:* none

Usage

```
compute_su_y_alchss_nm(data, name = "su_y_alchss_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_alchss_sum()

Examples

```
## Not run:
compute_su_y_alchss_nm(data)

## End(Not run)
```

`compute_su_y_alcprob_all`

Compute all the su_y_alcprob scores

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_su_y_alcprob_all(data)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_alcprob_all(data)

## End(Not run)
```

compute_su_y_alcprob_nm *Compute "Alcohol Problem Index (RAPI) [Youth]: Number missing"*

Description

Computes the summary score su_y_alcprob_nm Alcohol Problem Index (RAPI) [Youth]: Number missing

- *Summarized variables:*
  - ab_p_demo__race_001___0
  - ab_p_demo__race_001___10
  - ab_p_demo__race_001___11
  - ab_p_demo__race_001___12
  - ab_p_demo__race_001___13
  - ab_p_demo__race_001___14
  - ab_p_demo__race_001___15
  - ab_p_demo__race_001___16
  - ab_p_demo__race_001___17
  - ab_p_demo__race_001___18
  - ab_p_demo__race_001___19
  - ab_p_demo__race_001___20
  - ab_p_demo__race_001___21
  - ab_p_demo__race_001___22
  - ab_p_demo__race_001___23
  - ab_p_demo__race_001___24
  - ab_p_demo__race_001___25
  - ab_p_demo__race_001___777
  - ab_p_demo__race_001___999
  - ab_p_demo__race_001__v01___999
  - ab_p_demo__race_001__v01___10
  - ab_p_demo__race_001__v01___11
  - ab_p_demo__race_001__v01___12
  - ab_p_demo__race_001__v01___20
  - ab_p_demo__race_001__v01___21
  - ab_p_demo__race_001__v01___22
  - ab_p_demo__race_001__v01___23
  - ab_p_demo__race_001__v01___13
  - ab_p_demo__race_001__v01___14
  - ab_p_demo__race_001__v01___15
  - ab_p_demo__race_001__v01___17
  - ab_p_demo__race_001__v01___18

  - ab_p_demo__race_001__v01___19
  - ab_p_demo__race_001__v01___16
  - ab_p_demo__race_001__v01___24
  - ab_p_demo__race_001__v01___777
- *Excluded values:* none

Usage

```
compute_su_y_alcprob_nm(data, name = "su_y_alcprob_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_alcprob_prsum()

---

compute_su_y_alcsre__6mo_count

Compute "Alcohol Subject Response and Effects [Youth] (Last 6 months): Count [Validation: None missing or declined]"

Description

Computes the summary score su_y_alcsre__6mo_count Alcohol Subject Response and Effects [Youth] (Last 6 months): Count [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_alcsre__6mo_001
  - su_y_alcsre__6mo_002
  - su_y_alcsre__6mo_003
  - su_y_alcsre__6mo_004
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
compute_su_y_alcsre__6mo_count(
  data,
  name = "su_y_alcsre__6mo_count",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_su_y_alcsre__6mo_nm

Compute "Alcohol Subject Response and Effects [Youth] (Last 6 months): Number missing"

Description

Computes the summary score su_y_alcsre__6mo_nm Alcohol Subject Response and Effects [Youth] (Last 6 months): Number missing

- *Summarized variables:*
  - su_y_alcsre__6mo_001
  - su_y_alcsre__6mo_002
  - su_y_alcsre__6mo_003
  - su_y_alcsre__6mo_004
- *Excluded values:* none

Usage

```
compute_su_y_alcsre__6mo_nm(data, name = "su_y_alcsre__6mo_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_su_y_alcsre__first5_count

Compute "Alcohol Subject Response and Effects [Youth] (First 5 times ever drank): Count [Validation: None missing or declined]"

Description

Computes the summary score su_y_alcsre__first5_count Alcohol Subject Response and Effects [Youth] (First 5 times ever drank): Count [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_alcsre__first5_001
  - su_y_alcsre__first5_002
  - su_y_alcsre__first5_003
  - su_y_alcsre__first5_004
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
compute_su_y_alcsre__first5_count(
  data,
  name = "su_y_alcsre__first5_count",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Value

tbl. The input data frame with the summary score appended as a new column.

`compute_su_y_alcsre__first5_nm`

Compute "Alcohol Subject Response and Effects [Youth] (First 5 times ever drank): Number missing"

Description

Computes the summary score `su_y_alcsre__first5_nm` Alcohol Subject Response and Effects [Youth] (First 5 times ever drank): Number missing

- *Summarized variables:*
  - `su_y_alcsre__first5_001`
  - `su_y_alcsre__first5_002`
  - `su_y_alcsre__first5_003`
  - `su_y_alcsre__first5_004`
- *Excluded values:* none

Usage

```
compute_su_y_alcsre__first5_nm(
  data,
  name = "su_y_alcsre__first5_nm",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_su_y_alcsre__hvy_count

Compute "Alcohol Subject Response and Effects [Youth] (Heaviest drinking period): Count [Validation: None missing or declined]"

Description

Computes the summary score su_y_alcsre__hvy_count Alcohol Subject Response and Effects [Youth] (Heaviest drinking period): Count [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_alcsre__hvy_001
  - su_y_alcsre__hvy_002
  - su_y_alcsre__hvy_003
  - su_y_alcsre__hvy_004
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
compute_su_y_alcsre__hvy_count(
  data,
  name = "su_y_alcsre__hvy_count",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Value

tbl. The input data frame with the summary score appended as a new column.

compute_su_y_alcsre__hvy_nm

Compute "Alcohol Subject Response and Effects [Youth] (Heaviest drinking period): Number missing"

Description

Computes the summary score `su_y_alcsre__hvy_nm` Alcohol Subject Response and Effects [Youth] (Heaviest drinking period): Number missing

- *Summarized variables:*
  - `su_y_alcsre__hvy_001`
  - `su_y_alcsre__hvy_002`
  - `su_y_alcsre__hvy_003`
  - `su_y_alcsre__hvy_004`
- *Excluded values:* none

Usage

```
compute_su_y_alcsre__hvy_nm(data, name = "su_y_alcsre__hvy_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_su_y_alcsre_all

Compute all summary scores for su_y_alcsre.

Description

This function computes all summary scores for the su_y_alcsre form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_su_y_alcsre_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_alcsre_all(data)

## End(Not run)
```

---

compute_su_y_cigexp__neg_nm

Compute "Cigarette Expectancies (ASCQ) [Youth] (Strength of negative expectancies): Number missing"

Description

Computes the summary score su_y_cigexp__neg_nm Cigarette Expectancies (ASCQ) [Youth] (Strength of negative expectancies): Number missing

- *Summarized variables:*
  - su_y_cigexp__neg_001
  - su_y_cigexp__neg_002
- *Excluded values:* none

Usage

```
compute_su_y_cigexp__neg_nm(data, name = "su_y_cigexp__neg_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_cigexp__neg_prsum()

`compute_su_y_cigexp__neg_prsum__v01`

Compute "Cigarette Expectancies (ASCQ) [Youth] (Strength of negative expectancies): Prorated sum (v01)"

Description

Computes the summary score `su_y_cigexp__neg_prsum__v01` Cigarette Expectancies (ASCQ) [Youth] (Strength of negative expectancies): Prorated sum (v01)

Note: all 0s are changed to 1s prior to calculating pro-rated sum

- *Summarized variables:*
  - `su_y_cigexp__neg_001`
  - `su_y_cigexp__neg_002`
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
compute_su_y_cigexp__neg_prsum__v01(
  data,
  name = "su_y_cigexp__neg_prsum__v01",
  combine = TRUE,
  max_na = 0
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE` (default), the summary score will be appended to the input data frame. If `FALSE`, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_su_y_cigexp__neg_prsum()`

`compute_su_y_cigexp__pos_nm` *Compute "Cigarette Expectancies (ASCQ) [Youth] (Strength of positive expectancies): Number missing"*

Description

Computes the summary score `su_y_cigexp__pos_nm` Cigarette Expectancies (ASCQ) [Youth] (Strength of positive expectancies): Number missing

- *Summarized variables:*
  - `su_y_cigexp__pos_001`
  - `su_y_cigexp__pos_002`
  - `su_y_cigexp__pos_003`
  - `su_y_cigexp__pos_004`
- *Excluded values:* none

Usage

```
compute_su_y_cigexp__pos_nm(data, name = "su_y_cigexp__pos_nm", combine = TRUE)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE` (default), the summary score will be appended to the input data frame. If `FALSE`, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

`compute_su_y_cigexp__pos_prsum()`

`compute_su_y_cigexp__pos_prsum__v01`

Compute "Cigarette Expectancies (ASCQ) [Youth] (Strength of positive expectancies): Prorated sum (v01)"

Description

Computes the summary score `su_y_cigexp__pos_prsum__v01` Cigarette Expectancies (ASCQ) [Youth] (Strength of positive expectancies): Prorated sum (v01) [Validation: No more than 2 missing or declined]

Note: all 0s are changed to 1s prior to calculating pro-rated sum

- *Summarized variables:*
  - `su_y_cigexp__pos_001`
  - `su_y_cigexp__pos_002`
  - `su_y_cigexp__pos_003`
  - `su_y_cigexp__pos_004`
- *Excluded values:* none
- *Validation criterion:* maximally 2 of 4 items missing
- *Notes:*
  - Values in all input variables were recoded:
    - "0" –> "1"

Usage

```
compute_su_y_cigexp__pos_prsum__v01(
  data,
  name = "su_y_cigexp__pos_prsum__v01",
  combine = TRUE,
  max_na = 2
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE` (default), the summary score will be appended to the input data frame. If `FALSE`, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_cigexp__pos_prsum()

---

compute_su_y_cigexp_all

Compute all the su_y_cigexp scores

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_su_y_cigexp_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_cigexp_all(data)

## End(Not run)
```

---

compute_su_y_drgprob_all

Compute all the su_y_drgprob scores

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_su_y_drgprob_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_drgprob_all(data)

## End(Not run)
```

---

compute_su_y_drgprob_nm

Compute "Drug Problem Index (DAPI) [Youth]: Number missing"

Description

Computes the summary score su_y_drgprob_nm Drug Problem Index (DAPI) [Youth]: Number missing

- *Summarized variables:*
  - su_y_drgprob_001
  - su_y_drgprob_002
  - su_y_drgprob_003
  - su_y_drgprob_004
  - su_y_drgprob_005
  - su_y_drgprob_006
  - su_y_drgprob_007
  - su_y_drgprob_008
  - su_y_drgprob_009
  - su_y_drgprob_010
  - su_y_drgprob_012
  - su_y_drgprob_013
  - su_y_drgprob_014
  - su_y_drgprob_015
  - su_y_drgprob_016
  - su_y_drgprob_017
  - su_y_drgprob_018
- *Excluded values:* none

Usage

```
compute_su_y_drgprob_nm(data, name = "su_y_drgprob_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_drgprob_prsum()

---

compute_su_y_ksads__aud_all

Compute all summary scores for su_y_ksads__aud

Description

This function computes all summary scores for the su_y_ksads__aud table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_su_y_ksads__aud_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_su_y_ksads__dud_all

Compute all summary scores for su_y_ksads__dud

Description

This function computes all summary scores for the su_y_ksads__dud table. Make sure to have all necessary columns in the data frame.

Usage

```
compute_su_y_ksads__dud_all(data)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

compute_su_y_mjexp__neg_nm

Compute "Marijuana Expectancies (MEEQ-B) [Youth] (Strength of negative expectancies): Number missing"

Description

Computes the summary score `su_y_mjexp__neg_nm` Marijuana Expectancies (MEEQ-B) [Youth] (Strength of negative expectancies): Number missing

- *Summarized variables:*
  - `su_y_mjexp__neg_001`
  - `su_y_mjexp__neg_002`
  - `su_y_mjexp__neg_003`
- *Excluded values:* none

Usage

```
compute_su_y_mjexp__neg_nm(data, name = "su_y_mjexp__neg_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_mjexp__neg_prsum()

---

compute_su_y_mjexp__pos_nm

Compute "Marijuana Expectancies (MEEQ-B) [Youth] (Strength of positive expectancies): Number missing"

Description

Computes the summary score su_y_mjexp__pos_nm Marijuana Expectancies (MEEQ-B) [Youth] (Strength of positive expectancies): Number missing

- *Summarized variables:*
  - su_y_mjexp__pos_001
  - su_y_mjexp__pos_002
  - su_y_mjexp__pos_003
- *Excluded values:* none

Usage

```
compute_su_y_mjexp__pos_nm(data, name = "su_y_mjexp__pos_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_mjexp__pos_prsum()

---

compute_su_y_mjexp_all

Compute all the su_y_mjexp scores

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_su_y_mjexp_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_mjexp_all(data)

## End(Not run)
```

---

compute_su_y_mjprob_all

Compute all the su_y_mjprob scores

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_su_y_mjprob_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_mjprob_all(data)

## End(Not run)
```

---

compute_su_y_mjprob_nm

Compute "Marijuana Problem Index (MAPI) [Youth]: Number missing"

Description

Computes the summary score su_y_mjprob_nm Marijuana Problem Index (MAPI) [Youth]: Number missing

- *Summarized variables:*
  - su_y_mjprob_001
  - su_y_mjprob_002
  - su_y_mjprob_003
  - su_y_mjprob_004
  - su_y_mjprob_005
  - su_y_mjprob_006
  - su_y_mjprob_007
  - su_y_mjprob_008
  - su_y_mjprob_009
  - su_y_mjprob_010
  - su_y_mjprob_011
  - su_y_mjprob_012
  - su_y_mjprob_016
  - su_y_mjprob_017
  - su_y_mjprob_018
- *Excluded values:* none

Usage

```
compute_su_y_mjprob_nm(data, name = "su_y_mjprob_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_mjprob_prsum()

---

compute_su_y_mjsre__neg_nm

Compute "Marijuana Subjective Response and Effects [Youth] (Negative): Number missing"

Description

Computes the summary score su_y_mjsre__neg_nm Marijuana Subjective Response and Effects [Youth] (Negative): Number missing

- *Summarized variables:*
  - su_y_mjsre__neg_001
  - su_y_mjsre__neg_002
  - su_y_mjsre__neg_003
  - su_y_mjsre__neg_004
  - su_y_mjsre__neg_005
  - su_y_mjsre__neg_006
  - su_y_mjsre__neg_007
  - su_y_mjsre__neg_008
- *Excluded values:* none

Usage

```
compute_su_y_mjsre__neg_nm(data, name = "su_y_mjsre__neg_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_su_y_mjsre__pos_nm

Compute "Marijuana Subjective Response and Effects [Youth] (Positive): Number missing"

Description

Computes the summary score su_y_mjsre__pos_nm Marijuana Subjective Response and Effects [Youth] (Positive): Number missing

- *Summarized variables:*
  - su_y_mjsre__pos_001
  - su_y_mjsre__pos_002
  - su_y_mjsre__pos_003
- *Excluded values:* none

Usage

```
compute_su_y_mjsre__pos_nm(data, name = "su_y_mjsre__pos_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_su_y_mjsre_all

Compute all summary scores for su_y_mjsre.

Description

This function computes all summary scores for the su_y_mjsre form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_su_y_mjsre_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_mjsre_all(data)

## End(Not run)
```

compute_su_y_mjsre_nm

Compute "Marijuana Subjective Response and Effects [Youth] (NA): Number missing"

Description

Computes the summary score `su_y_mjsre_nm` Marijuana Subjective Response and Effects [Youth] (NA): Number missing

- *Summarized variables:*
  - `su_y_mjsre__pos_001`
  - `su_y_mjsre__pos_002`
  - `su_y_mjsre__pos_003`
  - `su_y_mjsre__neg_001`
  - `su_y_mjsre__neg_002`
  - `su_y_mjsre__neg_003`
  - `su_y_mjsre__neg_004`

  - su_y_mjsre__neg_005
  - su_y_mjsre__neg_006
  - su_y_mjsre__neg_007
  - su_y_mjsre__neg_008
- *Excluded values:* none

Usage

```
compute_su_y_mjsre_nm(data, name = "su_y_mjsre_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_su_y_nicsre__chew_nm

Compute "Nicotine Subjective Response and Effects [Youth] (Positive and negative effects of first smokeless tobacco or chew use): Number missing"

Description

Computes the summary score su_y_nicsre__chew_nm Nicotine Subjective Response and Effects [Youth] (Positive and negative effects of first smokeless tobacco or chew use): Number missing

- *Summarized variables:*
  - su_y_nicsre__chew__pos_001
  - su_y_nicsre__chew__neg_001
- *Excluded values:* none

Usage

```
compute_su_y_nicsre__chew_nm(
  data,
  name = "su_y_nicsre__chew_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

---

compute_su_y_nicsre__cig_nm

Compute "Nicotine Subjective Response and Effects [Youth] (Positive and negative effects of first cigarette use): Number missing"

Description

Computes the summary score su_y_nicsre__cig_nm Nicotine Subjective Response and Effects [Youth] (Positive and negative effects of first cigarette use): Number missing

- *Summarized variables:*
  - su_y_nicsre__cig__pos_001
  - su_y_nicsre__cig__neg_001
- *Excluded values:* none

Usage

```
compute_su_y_nicsre__cig_nm(data, name = "su_y_nicsre__cig_nm", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_su_y_nicsre__vape_nm

Compute "Nicotine Subjective Response and Effects [Youth] (Positive and negative effects of first vape use): Number missing"

Description

Computes the summary score su_y_nicsre__vape_nm Nicotine Subjective Response and Effects [Youth] (Positive and negative effects of first vape use): Number missing

- *Summarized variables:*
  - su_y_nicsre__vape__pos_001
  - su_y_nicsre__vape__pos_001__v01
  - su_y_nicsre__vape__neg_001
  - su_y_nicsre__vape__neg_001__v01
- *Excluded values:* none

Usage

```
compute_su_y_nicsre__vape_nm(
  data,
  name = "su_y_nicsre__vape_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Value

tbl. The input data frame with the summary score appended as a new column.

compute_su_y_nicsre_all

Compute all summary scores for su_y_nicsre.

Description

This function computes all summary scores for the su_y_nicsre form. Make sure to have all necessary columns in the data frame.

Usage

```
compute_su_y_nicsre_all(data)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_nicsre_all(data)

## End(Not run)
```

compute_su_y_nicvapeexp__neg_nm

Compute "ENDS Expectancies [Youth] (Strength of negative expectancies): Number missing"

Description

Computes the summary score `su_y_nicvapeexp__neg_nm` ENDS Expectancies [Youth] (Strength of negative expectancies): Number missing

- *Summarized variables:*
  - `su_y_nicvapeexp__neg_001`
  - `su_y_nicvapeexp__neg_002`
  - `su_y_nicvapeexp__neg_003`
  - `su_y_nicvapeexp__neg_004`
- *Excluded values:* none

Usage

```
compute_su_y_nicvapeexp__neg_nm(
  data,
  name = "su_y_nicvapeexp__neg_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_nicvapeexp__neg_prsum()

---

compute_su_y_nicvapeexp__pos_nm

Compute "ENDS Expectancies [Youth] (Strength of positive expectancies): Number missing"

Description

Computes the summary score su_y_nicvapeexp__pos_nm ENDS Expectancies [Youth] (Strength of positive expectancies): Number missing

- *Summarized variables:*
  - su_y_nicvapeexp__pos_001
  - su_y_nicvapeexp__pos_002
  - su_y_nicvapeexp__pos_003
  - su_y_nicvapeexp__pos_004
- *Excluded values:* none

Usage

```
compute_su_y_nicvapeexp__pos_nm(
  data,
  name = "su_y_nicvapeexp__pos_nm",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_su_y_nicvapeexp__pos_prsum()

---

compute_su_y_nicvapeexp_all

Compute all the su_y_nicvapeexp scores

Description

A single function to compute all scores in the above domain using **default** arguments.

Usage

```
compute_su_y_nicvapeexp_all(data)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.

Value

tbl. The input data frame with the summary scores appended as new columns.

Examples

```
## Not run:
compute_su_y_nicvapeexp_all(data)

## End(Not run)
```

`compute_su_y_sui__last__day_count` *Count days since last use of a given substance*

Description

Computes the number of days since the last use of a given substance as of the day of the substance use interview. Returns `NA` for the participants with no reported use of the provided substance.

Usage

```
compute_su_y_sui__last__day_count(data, name, substance, combine = TRUE)
```

Arguments

`data`	tibble. A data frame containing the data.
`name`	character. The name of the output column for the computed score.
`substance`	character (vector). The substance to compute the score for. Must be one of the following values: • `"alc"` • `"alc__sip"` • `"rxstim"` • `"cath"` • `"cbd"` • `"coc"` • `"dxm"` • `"ghb"` • `"hall"` • `"inh"` • `"ket"` • `"meth"` • `"mdma"` • `"mj__blunt"` • `"mj__conc"` • `"mj__conc__smoke"` • `"mj__conc__vape"` • `"mj__drink"` • `"mj__edbl"` • `"mj__smoke"` • `"mj__vape"` • `"mj__synth"` • `"mj__tinc"`

- "nic__chew"
- "nic__cigar"
- "nic__cig"
- "nic__hookah"
- "nic__pipe"
- "nic__rplc"
- "nic__vape"
- "opi"
- "othdrg"
- "qc"
- "roid"
- "rxopi"
- "salv"
- "shroom"
- "rxsed"
- "vape"
- "vape__flav"

combine logical. Whether to combine the summary score column with the input data frame (Default: 'TRUE').

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_su_y_sui__last__day_count(
  data = data_sui,
  name = "su_y_sui__alc__last__day_count",
  substance = "alc"
)

## End(Not run)
```

---

compute_su_y_sui__reg_useage

Compute age of regular use for a given substance

Description

Computes the age (in years) of regular use of a given substance. Returns NA for the participants with no regular use of the provided substance reported.

Usage

```
compute_su_y_sui__reg_useage(data, name, substance, combine = TRUE)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
substance	character (vector). The substance to compute the score for. Must be one of the following values:

- "alc"
- "alc__sip"
- "rxstim"
- "cath"
- "cbd"
- "coc"
- "dxm"
- "ghb"
- "hall"
- "inh"
- "ket"
- "meth"
- "mdma"
- "mj__blunt"
- "mj__conc"
- "mj__conc__smoke"
- "mj__conc__vape"
- "mj__drink"
- "mj__edbl"
- "mj__smoke"
- "mj__vape"
- "mj__synth"
- "mj__tinc"
- "nic__chew"
- "nic__cigar"
- "nic__cig"
- "nic__hookah"
- "nic__pipe"
- "nic__rplc"
- "nic__vape"
- "opi"
- "othdrg"
- "qc"

- "roid"
- "rxopi"
- "salv"
- "shroom"
- "rxsed"
- "vape"
- "vape__flav"

combine logical. Whether to combine the summary score column with the input data frame (Default: 'TRUE').

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_su_y_sui__reg_useage(
  data = data_sui,
  name = "su_y_sui__alc__reg_useage",
  substance = "alc"
)

## End(Not run)
```

---

compute_tlfb_dt *Compute TLFB first or last date of substance use*

Description

Computes either the first or last date of use for a given (set of) substance(s). Optionally, allows to filter by period (detailed and/or estimated); only considering a specified number of days before the TLFB interview; only considering days with co-use of (a)other substance(s); and/or only binge use.

Usage

```
compute_tlfb_dt(
  data,
  name,
  substance = NULL,
  period = NULL,
  days = NULL,
  co_use = NULL,
  binge = NULL,
  position
)
```

Arguments

data	tibble. A data frame containing the TLFB raw data.
name	character. The name of the output column for the computed score.
substance	character (vector). The substance(s) to compute the score for. Must be one or several of the following values:

- "'Fake' Marijuana or Synthetics"
- "Alcohol"
- "Anabolic Steroids"
- "Any Other Drug They Used to Get High"
- "Blunts or Combined Tobacco and Marijuana in Joints"
- "CBD (Non-Medical Use)"
- "Cathinones such as Bath Salts, Drone, or Meph"
- "Cigars, Little Cigars, or Cigarillos"
- "Cocaine or Crack Cocaine"
- "Concentrated Marijuana Tinctures"
- "Ecstasy, Molly, or MDMA"
- "Electronic Nicotine or Vaping Products"
- "GHB, Liquid G, or Georgia Homeboy"
- "Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"
- "Heroin, Opium, Junk, Smack, or Dope"
- "Hookah with Tobacco"
- "Inhalants"
- "Ketamine or Special K"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Methamphetamine, Meth, or Crystal Meth"
- "Nicotine Replacements"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "Prescription Pain Relievers or Opioids"
- "Prescription Stimulants"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Salvia"
- "Smokeless Tobacco, Chew, or Snus"
- "Smoking Marijuana Flower"
- "Smoking Marijuana Oils or Concentrates"
- "Tobacco Cigarette"
- "Tobacco in a Pipe"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "Marijuana (all forms)"

- "Nicotine (all forms)"

(Default: NULL, i.e., all substances are considered.)

period — character (vector). The period for which the score is computed for. Must be one of "detailed" (last year before date of TLFB interview) or "estimated" (more than one year before date of TLFB). (Default: NULL, i.e., all periods are considered). Cannot be used in combination with days.

days — integer. Number of days before the TLFB interview to consider. (Default: NULL, i.e., all days are considered). Cannot be used in combination with period.

co_use — character (vector). Co-use substance(s). Must be one or several of the possible values for substance listed above. Only days where the specified substance(s) was/were used together with (one of) the co-use substance(s) are considered. (Default: NULL, i.e., co-use is not considered). co_use cannot be specified without substance and can only contain substance(s) that are not specified in substance.

binge — (named list of) numeric. Binge threshold(s) for the substance(s). If only one value is provided, it is used, independent of the sex of the participant. If a list is provided, it must contain two named elements: "F" (female) and "M" (male) with the respective sex-specific binge thresholds. Only days where the the quantity of the substance(s) exceeds the specified threshold(s) are considered. (Default: NULL, i.e., binge behavior is not considered).

position — character. The position of the substance use event. Must be one of "first" or "last".

Value

A tibble with the computed score for each participant/event.

See Also

compute_tlfb_abst()

Examples

```
## Not run:
compute_tlfb_dt(
  data = data_tlfb,
  name = "su_y_tlfb__alc__first__cum_dt",
  substance = "Alcohol",
  position = "first"
)

## End(Not run)
```

`compute_tlfb_maxdose` *Compute TLFB maximum dose*

Description

Computes the maximum dose over all use days for a given (set of) substance(s). Optionally, allows to filter by period (detailed and/or estimated); only considering a specified number of days before the TLFB interview; only considering specific day types (weekends or week days); only considering days with co-use of (a)other substance(s); and/or only binge use.

Usage

```
compute_tlfb_maxdose(
  data,
  name,
  substance = NULL,
  period = NULL,
  days = NULL,
  wknd = NULL,
  co_use = NULL,
  binge = NULL
)
```

Arguments

`data`	tibble. A data frame containing the TLFB raw data.
`name`	character. The name of the output column for the computed score.
`substance`	character (vector). The substance(s) to compute the score for. Must be one or several of the following values: • `"'Fake' Marijuana or Synthetics"` • `"Alcohol"` • `"Anabolic Steroids"` • `"Any Other Drug They Used to Get High"` • `"Blunts or Combined Tobacco and Marijuana in Joints"` • `"CBD (Non-Medical Use)"` • `"Cathinones such as Bath Salts, Drone, or Meph"` • `"Cigars, Little Cigars, or Cigarillos"` • `"Cocaine or Crack Cocaine"` • `"Concentrated Marijuana Tinctures"` • `"Ecstasy, Molly, or MDMA"` • `"Electronic Nicotine or Vaping Products"` • `"GHB, Liquid G, or Georgia Homeboy"` • `"Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"`

- "Heroin, Opium, Junk, Smack, or Dope"
- "Hookah with Tobacco"
- "Inhalants"
- "Ketamine or Special K"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Methamphetamine, Meth, or Crystal Meth"
- "Nicotine Replacements"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "Prescription Pain Relievers or Opioids"
- "Prescription Stimulants"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Salvia"
- "Smokeless Tobacco, Chew, or Snus"
- "Smoking Marijuana Flower"
- "Smoking Marijuana Oils or Concentrates"
- "Tobacco Cigarette"
- "Tobacco in a Pipe"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "Marijuana (all forms)"
- "Nicotine (all forms)"

(Default: NULL, i.e., all substances are considered.)

period — character (vector). The period for which the score is computed for. Must be one of "detailed" (last year before date of TLFB interview) or "estimated" (more than one year before date of TLFB). (Default: NULL, i.e., all periods are considered). Cannot be used in combination with days.

days — integer. Number of days before the TLFB interview to consider. (Default: NULL, i.e., all days are considered). Cannot be used in combination with period.

wknd — logical. Whether the score should be computed for weekends only (TRUE) or for week days only (FALSE). (Default: NULL, i.e., all days are considered).

co_use — character (vector). Co-use substance(s). Must be one or several of the possible values for substance listed above. Only days where the specified substance(s) was/were used together with (one of) the co-use substance(s) are considered. (Default: NULL, i.e., co-use is not considered). co_use cannot be specified without substance and can only contain substance(s) that are not specified in substance.

binge — (named list of) numeric. Binge threshold(s) for the substance(s). If only one value is provided, it is used, independent of the sex of the participant. If a list is provided, it must contain two named elements: "F" (female) and "M" (male) with the respective sex-specific binge thresholds. Only days where the the quantity of the substance(s) exceeds the specified threshold(s) are considered. (Default: NULL, i.e., binge behavior is not considered).

Value

A tibble with the computed score for each participant/event.

Examples

```
## Not run:
compute_tlfb_maxdose(
  data = data_tlfb,
  name = "su_y_tlfb__alc__3mo_maxdose",
  substance = "Alcohol",
  days = 90
)

## End(Not run)
```

---

compute_tlfb_mean *Compute TLFB mean quantity*

Description

Computes the mean quantity per use day for a given (set of) substance(s). Optionally, allows to filter by period (detailed and/or estimated); only considering a specified number of days before the TLFB interview; only considering specific day types (weekends or week days); only considering days with co-use of (a)other substance(s); and/or only binge use.

Usage

```
compute_tlfb_mean(
  data,
  name,
  substance = NULL,
  period = NULL,
  days = NULL,
  wknd = NULL,
  co_use = NULL,
  binge = NULL
)
```

Arguments

data	tibble. A data frame containing the TLFB raw data.
name	character. The name of the output column for the computed score.
substance	character (vector). The substance(s) to compute the score for. Must be one or several of the following values: • "'Fake' Marijuana or Synthetics" • "Alcohol"

- "Anabolic Steroids"
- "Any Other Drug They Used to Get High"
- "Blunts or Combined Tobacco and Marijuana in Joints"
- "CBD (Non-Medical Use)"
- "Cathinones such as Bath Salts, Drone, or Meph"
- "Cigars, Little Cigars, or Cigarillos"
- "Cocaine or Crack Cocaine"
- "Concentrated Marijuana Tinctures"
- "Ecstasy, Molly, or MDMA"
- "Electronic Nicotine or Vaping Products"
- "GHB, Liquid G, or Georgia Homeboy"
- "Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"
- "Heroin, Opium, Junk, Smack, or Dope"
- "Hookah with Tobacco"
- "Inhalants"
- "Ketamine or Special K"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Methamphetamine, Meth, or Crystal Meth"
- "Nicotine Replacements"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "Prescription Pain Relievers or Opioids"
- "Prescription Stimulants"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Salvia"
- "Smokeless Tobacco, Chew, or Snus"
- "Smoking Marijuana Flower"
- "Smoking Marijuana Oils or Concentrates"
- "Tobacco Cigarette"
- "Tobacco in a Pipe"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "Marijuana (all forms)"
- "Nicotine (all forms)"

(Default: NULL, i.e., all substances are considered.)

`period` character (vector). The period for which the score is computed for. Must be one of "detailed" (last year before date of TLFB interview) or "estimated" (more than one year before date of TLFB). (Default: NULL, i.e., all periods are considered). Cannot be used in combination with days.

`days` integer. Number of days before the TLFB interview to consider. (Default: NULL, i.e., all days are considered). Cannot be used in combination with period.

wknd	logical. Whether the score should be computed for weekends only (TRUE) or for week days only (FALSE). (Default: NULL, i.e., all days are considered).
co_use	character (vector). Co-use substance(s). Must be one or several of the possible values for substance listed above. Only days where the specified substance(s) was/were used together with (one of) the co-use substance(s) are considered. (Default: NULL, i.e., co-use is not considered). co_use cannot be specified without substance and can only contain substance(s) that are not specified in substance.
binge	(named list of) numeric. Binge threshold(s) for the substance(s). If only one value is provided, it is used, independent of the sex of the participant. If a list is provided, it must contain two named elements: "F" (female) and "M" (male) with the respective sex-specific binge thresholds. Only days where the the quantity of the substance(s) exceeds the specified threshold(s) are considered. (Default: NULL, i.e., binge behavior is not considered).

Value

A tibble with the computed score for each participant/event.

Examples

```
## Not run:
compute_tlfb_mean(
  data = data_tlfb,
  name = "su_y_tlfb__alc__1mo_mean",
  substance = "Alcohol",
  days = 30
)

## End(Not run)
```

---

compute_tlfb_totdose *Compute TLFB total dose*

Description

Computes the total dose over all use day for a given (set of) substance(s). Optionally, allows to filter by period (detailed and/or estimated); only considering a specified number of days before the TLFB interview; only considering specific day types (weekends or week days); only considering days with co-use of (a)other substance(s); and/or only binge use.

Usage

```
compute_tlfb_totdose(
  data,
  name,
  substance = NULL,
```

```
  period = NULL,
  days = NULL,
  wknd = NULL,
  co_use = NULL,
  binge = NULL
)
```

Arguments

data	tibble. A data frame containing the TLFB raw data.
name	character. The name of the output column for the computed score.
substance	character (vector). The substance(s) to compute the score for. Must be one or several of the following values:

- "'Fake' Marijuana or Synthetics"
- "Alcohol"
- "Anabolic Steroids"
- "Any Other Drug They Used to Get High"
- "Blunts or Combined Tobacco and Marijuana in Joints"
- "CBD (Non-Medical Use)"
- "Cathinones such as Bath Salts, Drone, or Meph"
- "Cigars, Little Cigars, or Cigarillos"
- "Cocaine or Crack Cocaine"
- "Concentrated Marijuana Tinctures"
- "Ecstasy, Molly, or MDMA"
- "Electronic Nicotine or Vaping Products"
- "GHB, Liquid G, or Georgia Homeboy"
- "Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"
- "Heroin, Opium, Junk, Smack, or Dope"
- "Hookah with Tobacco"
- "Inhalants"
- "Ketamine or Special K"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Methamphetamine, Meth, or Crystal Meth"
- "Nicotine Replacements"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "Prescription Pain Relievers or Opioids"
- "Prescription Stimulants"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Salvia"
- "Smokeless Tobacco, Chew, or Snus"

- "Smoking Marijuana Flower"
- "Smoking Marijuana Oils or Concentrates"
- "Tobacco Cigarette"
- "Tobacco in a Pipe"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "Marijuana (all forms)"
- "Nicotine (all forms)"

(Default: NULL, i.e., all substances are considered.)

period — character (vector). The period for which the score is computed for. Must be one of "detailed" (last year before date of TLFB interview) or "estimated" (more than one year before date of TLFB). (Default: NULL, i.e., all periods are considered). Cannot be used in combination with days.

days — integer. Number of days before the TLFB interview to consider. (Default: NULL, i.e., all days are considered). Cannot be used in combination with period.

wknd — logical. Whether the score should be computed for weekends only (TRUE) or for week days only (FALSE). (Default: NULL, i.e., all days are considered).

co_use — character (vector). Co-use substance(s). Must be one or several of the possible values for substance listed above. Only days where the specified substance(s) was/were used together with (one of) the co-use substance(s) are considered. (Default: NULL, i.e., co-use is not considered). co_use cannot be specified without substance and can only contain substance(s) that are not specified in substance.

binge — (named list of) numeric. Binge threshold(s) for the substance(s). If only one value is provided, it is used, independent of the sex of the participant. If a list is provided, it must contain two named elements: "F" (female) and "M" (male) with the respective sex-specific binge thresholds. Only days where the the quantity of the substance(s) exceeds the specified threshold(s) are considered. (Default: NULL, i.e., binge behavior is not considered).

Value

A tibble with the computed score for each participant/event.

Examples

```
## Not run:
compute_tlfb_totdose(
  data = data_tlfb,
  name = "su_y_tlfb__alc__binge_totdose",
  substance = "Alcohol",
  binge = list("F" = 4, "M" = 5)
)

## End(Not run)
```

compute_tlfb_totdose_sum

Compute TLFB lifetime total dose

Description

Computes the lifetime total dose over all use day for a given (set of) substance(s). Optionally, allows to filter by period (detailed and/or estimated); only considering a specified number of days before the TLFB interview; only considering specific day types (weekends or week days); only considering days with co-use of (a)other substance(s); and/or only binge use.

Usage

```
compute_tlfb_totdose_sum(
  data,
  name,
  substance = NULL,
  period = NULL,
  days = NULL,
  wknd = NULL,
  co_use = NULL,
  binge = NULL
)
```

Arguments

data	tibble. A data frame containing the TLFB raw data.
name	character. The name of the output column for the computed score.
substance	character (vector). The substance(s) to compute the score for. Must be one or several of the following values:

- "'Fake' Marijuana or Synthetics"
- "Alcohol"
- "Anabolic Steroids"
- "Any Other Drug They Used to Get High"
- "Blunts or Combined Tobacco and Marijuana in Joints"
- "CBD (Non-Medical Use)"
- "Cathinones such as Bath Salts, Drone, or Meph"
- "Cigars, Little Cigars, or Cigarillos"
- "Cocaine or Crack Cocaine"
- "Concentrated Marijuana Tinctures"
- "Ecstasy, Molly, or MDMA"
- "Electronic Nicotine or Vaping Products"
- "GHB, Liquid G, or Georgia Homeboy"

- "Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"
- "Heroin, Opium, Junk, Smack, or Dope"
- "Hookah with Tobacco"
- "Inhalants"
- "Ketamine or Special K"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Methamphetamine, Meth, or Crystal Meth"
- "Nicotine Replacements"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "Prescription Pain Relievers or Opioids"
- "Prescription Stimulants"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Salvia"
- "Smokeless Tobacco, Chew, or Snus"
- "Smoking Marijuana Flower"
- "Smoking Marijuana Oils or Concentrates"
- "Tobacco Cigarette"
- "Tobacco in a Pipe"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "Marijuana (all forms)"
- "Nicotine (all forms)"

(Default: NULL, i.e., all substances are considered.)

period — character (vector). The period for which the score is computed for. Must be one of "detailed" (last year before date of TLFB interview) or "estimated" (more than one year before date of TLFB). (Default: NULL, i.e., all periods are considered). Cannot be used in combination with days.

days — integer. Number of days before the TLFB interview to consider. (Default: NULL, i.e., all days are considered). Cannot be used in combination with period.

wknd — logical. Whether the score should be computed for weekends only (TRUE) or for week days only (FALSE). (Default: NULL, i.e., all days are considered).

co_use — character (vector). Co-use substance(s). Must be one or several of the possible values for substance listed above. Only days where the specified substance(s) was/were used together with (one of) the co-use substance(s) are considered. (Default: NULL, i.e., co-use is not considered). co_use cannot be specified without substance and can only contain substance(s) that are not specified in substance.

binge — (named list of) numeric. Binge threshold(s) for the substance(s). If only one value is provided, it is used, independent of the sex of the participant. If a list is provided, it must contain two named elements: "F" (female) and "M" (male)

with the respective sex-specific binge thresholds. Only days where the the quantity of the substance(s) exceeds the specified threshold(s) are considered. (Default: NULL, i.e., binge behavior is not considered).

Value

A tibble with the computed score for each participant/event.

Examples

```
## Not run:
compute_tlfb_totdose_sum(
  data = data_tlfb,
  name = "su_y_tlfb__alc__totdose_sum",
  substance = "Alcohol"
)

## End(Not run)
```

---

compute_tlfb_ud *Compute TLFB use days*

Description

Computes the number of use days for a given (set of) substance(s). Optionally, allows to filter by period (detailed and/or estimated); only considering a specified number of days before the TLFB interview; only considering specific day types (weekends or week days); only considering days with co-use of (a)other substance(s); and/or only binge use.

Usage

```
compute_tlfb_ud(
  data,
  name,
  substance = NULL,
  period = NULL,
  days = NULL,
  wknd = NULL,
  co_use = NULL,
  binge = NULL
)
```

Arguments

data	tibble. A data frame containing the TLFB raw data.
name	character. The name of the output column for the computed score.
substance	character (vector). The substance(s) to compute the score for. Must be one or several of the following values:

- "'Fake' Marijuana or Synthetics"
- "Alcohol"
- "Anabolic Steroids"
- "Any Other Drug They Used to Get High"
- "Blunts or Combined Tobacco and Marijuana in Joints"
- "CBD (Non-Medical Use)"
- "Cathinones such as Bath Salts, Drone, or Meph"
- "Cigars, Little Cigars, or Cigarillos"
- "Cocaine or Crack Cocaine"
- "Concentrated Marijuana Tinctures"
- "Ecstasy, Molly, or MDMA"
- "Electronic Nicotine or Vaping Products"
- "GHB, Liquid G, or Georgia Homeboy"
- "Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"
- "Heroin, Opium, Junk, Smack, or Dope"
- "Hookah with Tobacco"
- "Inhalants"
- "Ketamine or Special K"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Methamphetamine, Meth, or Crystal Meth"
- "Nicotine Replacements"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "Prescription Pain Relievers or Opioids"
- "Prescription Stimulants"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Salvia"
- "Smokeless Tobacco, Chew, or Snus"
- "Smoking Marijuana Flower"
- "Smoking Marijuana Oils or Concentrates"
- "Tobacco Cigarette"
- "Tobacco in a Pipe"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "Marijuana (all forms)"
- "Nicotine (all forms)"

(Default: NULL, i.e., all substances are considered.)

period — character (vector). The period for which the score is computed for. Must be one of "detailed" (last year before date of TLFB interview) or "estimated" (more than one year before date of TLFB). (Default: NULL, i.e., all periods are considered). Cannot be used in combination with days.

days	integer. Number of days before the TLFB interview to consider. (Default: NULL, i.e., all days are considered). Cannot be used in combination with period.
wknd	logical. Whether the score should be computed for weekends only (TRUE) or for week days only (FALSE). (Default: NULL, i.e., all days are considered).
co_use	character (vector). Co-use substance(s). Must be one or several of the possible values for substance listed above. Only days where the specified substance(s) was/were used together with (one of) the co-use substance(s) are considered. (Default: NULL, i.e., co-use is not considered). co_use cannot be specified without substance and can only contain substance(s) that are not specified in substance.
binge	(named list of) numeric. Binge threshold(s) for the substance(s). If only one value is provided, it is used, independent of the sex of the participant. If a list is provided, it must contain two named elements: "F" (female) and "M" (male) with the respective sex-specific binge thresholds. Only days where the the quantity of the substance(s) exceeds the specified threshold(s) are considered. (Default: NULL, i.e., binge behavior is not considered).

Value

A tibble with the computed score for each participant/event.

Examples

```
## Not run:
compute_tlfb_ud(
  data = data_tlfb,
  name = "su_y_tlfb__alc__1mo__wknd_ud",
  substance = "Alcohol",
  days = 30,
  wknd = TRUE
)

## End(Not run)
```

---

convert_time_mctq *Convert MCTQ time data to 24h or 36 format*

Description

Utility function to convert MCTQ survey responses to 24h or 36h format times.

Usage

```
convert_time_mctq(data, name, col_hrs_a, col_hrs_b, col_minute, scale = "24h")
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. The name of the new column with the summary score.
col_hrs_a	character. The name of the column with the first time. 1, 4 AM | 2, 5 AM | 3, 6 AM | 4, 7 AM | 5, 8 AM | 6, 9 AM | 7, 10 AM | 8, 11 AM | 9, 12 PM | 10, 1 PM | 11, 2 PM | 12, 3 PM | 13, 4 PM
col_hrs_b	character. The name of the column with the second time. 1, 5 PM | 2, 6 PM | 3, 7 PM | 4, 8 PM | 5, 9 PM | 6, 10 PM | 7, 11 PM | 8, 12 AM | 9, 1 AM | 10, 2 AM | 11, 3 AM
col_minute	character. The name of the column with the minutes. If the column value is NA, the minute is set to 0. 1, 0 minutes | 2, 5 minutes | 3, 10 minutes | 4, 15 minutes | 5, 20 minutes | 6, 25 minutes | 7, 30 minutes | 8, 35 minutes | 9, 40 minutes | 10, 45 minutes | 11, 50 minutes | 12, 55 minutes
scale	character. The scale of the time format. Default is "24h". The other option is "36h".

Details

Expect values 0 <= value < 24 for 24h format. Expect values 12 <= value < 36 for 36h format.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
col_hrs_a <- "ph_y_mctq__fd_001__01a"
col_hrs_b <- "ph_y_mctq__fd_001__01b"
col_minute <- "ph_y_mctq__fd_001__02"
name <- "ph_y_mctq__fd__bed__start__24h_t"
data <- dplyr::tibble(
  ph_y_mctq__fd_001__01a = c(NA, NA, NA, NA, NA, 1, 7, 3, NA),
  ph_y_mctq__fd_001__01b = c(6, 7, 8, 8, 10, NA, NA, NA, NA),
  ph_y_mctq__fd_001__02 = c(1, 1, 1, 7, 7, 1, 4, 1, NA)
)
convert_time_mctq(data, name, col_hrs_a, col_hrs_b, col_minute)
name <- "ph_y_mctq__fd__bed__start__36h_t"
convert_time_mctq(data, name, col_hrs_a, col_hrs_b, col_minute, "36h")
```

`create_session_num` *Creates a new column by converting session_id column into a numeric*

Description

Creates a new column which contains the parsed numeric value for the visit. Annual visits are set to integers, where 0 = baseline, 1 = year 1, and so on. Mid-years are defined as 0.5 increments of the prior annual visits, e.g., 0.5 = between baseline and year 1, 1.5 = between year 1 and 2, and so on.

Usage

```
create_session_num(data, name = "session_num")
```

Arguments

`data`	tbl. Data frame containing the `session_id` column.
`name`	character of length 1. The name of the newly created and appended column. Default: `session_num`

Value

tbl. The input data frame with the `name` column added.

Examples

```
# Example data
dat <- tibble::tibble(
  participant_id = c("A123", "A123", "A123", "A123"),
  session_id = c("ses-00S", "ses-00A", "ses-00M", "ses-01A"),
  a = c(1, 2, 3, 4),
  b = c(10, 11, 12, NA)
)

# Create a new column (default: `session_num`) with numeric session
create_session_num(
  dat
)

# Create a new column called `num` that contains the session numbers
create_session_num(
  dat,
  name = "num"
)
```

filter_tlfb *Filter TLFB data*

Description

This function filters the TLFB (Timeline Followback) data based on specified substance(s); period (estimated vs. detailed); number of days before the TLFB interview; weekend-only usage; co-use of other substances; and/or binge use.

Usage

```
filter_tlfb(
  data,
  substance = NULL,
  period = NULL,
  days = NULL,
  wknd = NULL,
  co_use = NULL,
  binge = NULL
)
```

Arguments

data	tibble. A data frame containing the TLFB raw data.
substance	character (vector). The substance(s) to compute the score for. Must be one or several of the following values:

- "'Fake' Marijuana or Synthetics"
- "Alcohol"
- "Anabolic Steroids"
- "Any Other Drug They Used to Get High"
- "Blunts or Combined Tobacco and Marijuana in Joints"
- "CBD (Non-Medical Use)"
- "Cathinones such as Bath Salts, Drone, or Meph"
- "Cigars, Little Cigars, or Cigarillos"
- "Cocaine or Crack Cocaine"
- "Concentrated Marijuana Tinctures"
- "Ecstasy, Molly, or MDMA"
- "Electronic Nicotine or Vaping Products"
- "GHB, Liquid G, or Georgia Homeboy"
- "Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"
- "Heroin, Opium, Junk, Smack, or Dope"
- "Hookah with Tobacco"
- "Inhalants"

- "Ketamine or Special K"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Methamphetamine, Meth, or Crystal Meth"
- "Nicotine Replacements"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "Prescription Pain Relievers or Opioids"
- "Prescription Stimulants"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Salvia"
- "Smokeless Tobacco, Chew, or Snus"
- "Smoking Marijuana Flower"
- "Smoking Marijuana Oils or Concentrates"
- "Tobacco Cigarette"
- "Tobacco in a Pipe"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "Marijuana (all forms)"
- "Nicotine (all forms)"

(Default: NULL, i.e., all substances are considered.)

`period` character (vector). The period for which the score is computed for. Must be one of "detailed" (last year before date of TLFB interview) or "estimated" (more than one year before date of TLFB). (Default: NULL, i.e., all periods are considered). Cannot be used in combination with days.

`days` integer. Number of days before the TLFB interview to consider. (Default: NULL, i.e., all days are considered). Cannot be used in combination with period.

`wknd` logical. Whether the score should be computed for weekends only (TRUE) or for week days only (FALSE). (Default: NULL, i.e., all days are considered).

`co_use` character (vector). Co-use substance(s). Must be one or several of the possible values for substance listed above. Only days where the specified substance(s) was/were used together with (one of) the co-use substance(s) are considered. (Default: NULL, i.e., co-use is not considered). co_use cannot be specified without substance and can only contain substance(s) that are not specified in substance.

`binge` (named list of) numeric. Binge threshold(s) for the substance(s). If only one value is provided, it is used, independent of the sex of the participant. If a list is provided, it must contain two named elements: "F" (female) and "M" (male) with the respective sex-specific binge thresholds. Only days where the the quantity of the substance(s) exceeds the specified threshold(s) are considered. (Default: NULL, i.e., binge behavior is not considered).

Value

A filtered data frame based on the specified criteria.

Examples

```
## Not run:
filtered_data <- filter_tlfb(
  data,
  substance = "Alcohol",
  wknd_only = TRUE,
  period = "estimated",
  days = 30
)

## End(Not run)
```

`get_tscore_tbl` *Get T-score table from list of tscores (Internal)*

Description

This function retrieves the tscore table from a list of tscores based on the function name. The function should be used internally.

Usage

```
get_tscore_tbl(list_tscore, func_name)
```

Arguments

`list_tscore`	list. List of tscores. see details.
`func_name`	character. The name of the function.

Details

The `list_tscore` should be a list of prepared tscore tables. The list has two layers of structure: the first layer is the name of form, and the second layer is the keyword of the tscore table.

```
list
|- form_1
|  |- keyword_1
|  |- keyword_2
|  |- ...
|- form_2
|  |- keyword_1
|  |- keyword_2
|  |- ...
|- ...
```

This object is prepared by the DSM team and for internal users, please ask the DSM team for the `rds` file.

Forms and keywords:

Forms and keywords are based on the function names. A function should contain both the form and keyword in its name, with only one exception being the overall score of a form, which does not have a keyword. The function name should be in the format of `compute_form_xx__keyword_tscore` or `compute_form_xx_tscore`. The function name will be split by _ and the unique keywords will be used to search for the tscore table.

Value

tbl. The tscore table. If there is no match or more than one match, an error will be thrown.

Examples

```
## Not run:
list_tscore <- readRDS("aseba_tscore.rds")
get_tscore_tbl(list_tscore, "compute_mh_p_abcl__afs__frnd_tscore")

## End(Not run)
```

---

make_static *Create static variable, one per participant, using longitudinal responses*

Description

Update an existing field to include longitudinal responses. Use data for each `id` from the first available `event` and set that value for all `event` rows.

Usage

```
make_static(
  data,
  id = "participant_id",
  event = "session_id",
  exclude = NULL,
  var_in,
  var_out
)
```

Arguments

`data`	Dataframe with fields specified in `id`, `event`, and `var`.
`id`	character of length 1. Name of field that contains the IDs for which we need to assess the longitudinal data.
`event`	character of length 1. Name of field that contains the (longitudinal) event IDs.
`exclude`	character (vector). The value(s) to be excluded (Default: NULL; all values are used).

var_in	character of length 1. Name of the field that contains the longitudinal values or responses.
var_out	character of length 1. Name of the new field that contains one static value per id computed from the longitudinal values or responses in var_in.

Value

Dataframe with two columns: id and var_out

Examples

```
data <- tibble::tribble(
  ~"id", ~"event", ~"values",
  "A", 1, NA,
  "A", 2, 2,
  "A", 3, 3,
  "B", 1, NA,
  "B", 2, NA,
  "B", 3, 1
)

make_static(
  data,
  var_in = "values",
  var_out = "static_nothing_excluded",
  id = "id",
  event = "event"
)

make_static(
  data,
  var_in = "values",
  var_out = "static_excluding_1and2",
  exclude = c("1", "2"),
  id = "id",
  event = "event"
)
```

---

md_bullet *Markdown bullet point list*

Description

Creates a bullet point list in markdown format. Copy of gluedown::md_bullet() but with the added ability to specify an indent to create nested lists and the option to use code font.

Usage

```
md_bullet(
  x,
  indent = 0,
  code = FALSE,
  italic = FALSE,
  marker = c("*", "-", "+")
)
```

Arguments

x	character (vector). Text to convert into a bullet point list.
indent	numeric, positive whole number. Number of spaces to indent the bullet point list by (Default: 0).
code	logical. If the text will be formatted as code (Default: TRUE).
italic	logical. If the text will be formatted as italic (Default: FALSE).
marker	character. The bullet list marker to use (Default: "*").

Value

glue vector. A bullet point list in markdown format.

Examples

```
md_bullet(c("First item", "Second item", "Third item"), code = TRUE)

md_bullet(c("First item", "Second item", "Third item"), indent = 2)
```

---

recode_levels *Recode levels*

Description

Recodes specified levels of a character/factor variable, e.g., to apply reverse coding before summary score computation.

Usage

```
recode_levels(data, vars, recode, temp = FALSE)
```

Arguments

data	tbl. Data frame containing the columns to be recoded.
vars	character (vector). The name(s) of the column(s) to be recoded.
recode	named character vector. The levels to be recoded, with the name being the original value and the value being the value to recode to.
temp	logical. If TRUE creates a new column to save the recoded values. The new columns will be named as temp_{vars}.

Value

tbl. The input data frame with the recoded variable(s).

Examples

```
data <- tibble::tibble(
  var_a = c("1", "2", "3", "4", "5", NA, "999", "777"),
  var_b = c("5", "4", "3", "2", "1", "777", NA, "999")
)

# recode individual variables
data |>
  recode_levels(
    vars = "var_a",
    recode = c("999" = "0", "777" = "0")
  ) |>
  recode_levels(
    vars = "var_b",
    recode = c("999" = "6", "777" = "7")
  )

# apply the same recoding to several variables
data |>
  recode_levels(
    vars = c(
      "var_a",
      "var_b"
    ),
    recode = c(
      "1" = "5",
      "2" = "4",
      "4" = "2",
      "5" = "1"
    )
  )
```

---

ss_count *Compute the number or count of matching conditions*

Description

Computes the number of conditions (provided as a character vectorcond), involving the input variables `vars`, that were found to be `TRUE`. Options available to exclude certain values from the input variables (provided as a character vector `exclude`).

Usage

```
ss_count(
  data,
```

```
  name,
  vars,
  vars_temp = NULL,
  exclude = NULL,
  combine = FALSE,
  allow_missingness = TRUE,
  cond
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. The name of the summary score.
vars	character vector. The name(s) of the column(s) to be summarized.
vars_temp	character vector. The name(s) of temporary column(s) used to compute the summary score. Note, these columns are not checked for missingness. See allow_missingness.
exclude	character (vector). The value(s) to be excluded (Default: NULL; all values are used).
combine	logical. Whether to combine the summary score column with the input data frame (Default: FALSE).
allow_missingness	logical. Default set to TRUE. If TRUE, summary score is set to NA only when ALL the in-going fields have missingness. If FALSE, summary score is set to NA when ANY of the in-going fields have missingness. NOTE: exclude operation is performed prior to checking for missingness.
cond	character vector. Each specified condition, involving the values of specific input fields, gets tested for 1 (TRUE) or 0 (FALSE). If a condition is specified as "field_name", the numeric value in the field is counted and could be greater than 1. Whereas other conditions when met can get a value of 1 or 0. The summary score is a sum over all the values obtained from testing each condition specified in cond.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
dat <- tibble::tibble(
  id   = c("1", "2", "3", "4", "5", "6", "7", "8"),
  a_1  = c(1, 1, NA, 1, 1, 1, 1, 1),
  a_2  = c(1, NA, NA, 1, 1, NA, 1, 1),
  b_1  = c(1, 1, NA, NA, 1, 1, 1, 1),
  b_2  = c(1, 1, NA, 1, 1, NA, 1, 1),
  c    = c(NA, 1, NA, 1, 777, 0, 1, 0)
)
```

```
# define conditions to assess
conditions <- c(
  "a_1 == 1 & a_2 == 1",
  "b_1 == 1 & b_2 == 1",
  "c"
)

# count number of matched conditions
ss_count(
  data    = dat,
  name    = "ss",
  vars    = c("a_1", "a_2", "b_1", "b_2", "c"),
  cond    = conditions,
  combine = TRUE
)

ss_count(
  data    = dat,
  name    = "ss",
  vars    = c("a_1", "a_2", "b_1", "b_2", "c"),
  cond    = conditions,
  exclude = c("777"),
  combine = TRUE
)

conditions <- paste(
  c(
    "a_1 == 1 & a_2 == 1",
    "b_1 == 1 & b_2 == 1",
    "c >= 1"
  ),
  collapse = "&"
)

ss_count(
  data    = dat,
  name    = "ss",
  vars    = c("a_1", "a_2", "b_1", "b_2", "c"),
  cond    = conditions,
  exclude = c("777"),
  combine = TRUE
)

ss_count(
  data = dat,
  name = "ss",
  vars = c("a_1", "a_2", "b_1", "b_2", "c"),
  cond = conditions,
  exclude = c("777"),
  allow_missingness = FALSE,
  combine = TRUE
)
```

ss_count_cond *Compute the number or count of matching conditions*

Description

Computes the number of conditions (provided as a character vectorcond), involving the input variables vars, that were found to be TRUE. Options available to exclude certain values from the input variables (provided as a character vector exclude).

Usage

```
ss_count_cond(data, name, vars, exclude = NULL, combine = FALSE, cond, max_na)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. The name of the summary score.
vars	character vector. The names of the columns to be summarized.
exclude	character (vector). The value(s) to be excluded (Default: NULL; all values are used).
combine	logical. Whether to combine the summary score column with the input data frame (Default: FALSE).
cond	character vector. Each specified condition, involving the values of specific input fields, gets tested for 1 (TRUE) or 0 (FALSE). If a condition is specified as "field_name", the numeric value in the field is counted and could be greater than 1. Whereas other conditions when met can get a value of 1 or 0. The summary score is a sum over all the values obtained from testing each condition specified in cond.
max_na	numeric, positive whole number. Number of missing items allowed.

Value

tbl. The input data frame with the summary score appended as a new column.

ss_max *Compute max across columns*

Description

Computes the max of a set of variables, with the option to exclude certain values (for non-responses like "Don't know"/"Decline to answer") and to set a maximum number of missing values.

Usage

```
ss_max(
  data,
  name,
  vars,
  max_na = NULL,
  exclude = NULL,
  events = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. The name of the summary score.
vars	character vector. The names of the columns to be summarized.
max_na	numeric, positive whole number. Number of missing items allowed (Default: NULL; no restriction on missing values).
exclude	character (vector). The value(s) to be excluded (Default: NULL; all values are used).
events	character (vector). Only compute the summary score for the specified events (Default: NULL; computed for all events).
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
data <- tibble::tribble(
  ~id,    ~session_id, ~A, ~B,  ~C, ~D,
  "id1",  "1",         1,  5,   2,  NA,
  "id1",  "2",         2,  4,   NA, NA,
  "id1",  "3",         3,  3,   3,  3,
  "id1",  "4",         4,  2,   4,  2,
  "id1",  "5",         5,  1,   5,  3
)

ss_max(
  data,
  name = "summary",
  vars = c("A", "B", "C", "D")
)

ss_max(
  data,
```

```
  name = "summary",
  vars = c("A", "B", "C", "D"),
  max_na = 1,
  exclude = c("1")
)

ss_max(
  data,
  name = "summary",
  vars = c("A", "B", "C", "D"),
  max_na = 1,
  exclude = c("1"),
  events = c("4")
)
```

`ss_mean` *Compute mean*

Description

Computes the mean of a set of variables, with the option to exclude certain values (for non-responses like "Don't know"/"Decline to answer") and to set a maximum number of missing values.

Usage

```
ss_mean(
  data,
  name,
  vars,
  max_na = NULL,
  exclude = NULL,
  events = NULL,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. The name of the summary score.
`vars`	character vector. The names of the columns to be summarized.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: NULL; no restriction on missing values).
`exclude`	character (vector). The value(s) to be excluded (Default: NULL; all values are used).
`events`	character (vector). Only compute the summary score for the specified events (Default: NULL; computed for all events).
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
data <- tibble::tribble(
  ~session_id, ~a, ~b,  ~c,  ~d,  ~e,
  "ses-00A",   1,  1,   1,   1,   NA,
  "ses-01A",   2,  777, 2,   2,   2,
  "ses-02A",   3,  3,   999, 3,   3,
  "ses-02A",   4,  4,   4,   777, NA,
  "ses-03A",   5,  NA,  777, 999, 5,
  "ses-03A",   NA, NA,  NA,  NA,  NA,
  "ses-04A",   1,  NA,  NA,  NA,  NA
)

data |>
  ss_mean(
    name = "mean",
    vars = c("a", "b", "c", "d", "e"),
    max_na = 1,
    exclude = c("777", "999")
  )

data |>
  ss_mean(
    name = "mean",
    vars = c("a", "b", "c", "d", "e"),
    max_na = 1,
    exclude = c("777", "999"),
    combine = FALSE
  )

data |>
  ss_mean(
    name = "mean",
    vars = c("a", "b", "c", "d", "e"),
    max_na = NULL,
    exclude = NULL,
    events = c("ses-00A", "ses-01A"),
  )
```

---

ss_mean_pos *Compute mean of positive values*

Description

Computes the mean of strictly positive values for a set of variables, with the option to exclude certain values (for non-responses like "Don't know"/"Decline to answer") and to set a maximum number of missing values.

Usage

```
ss_mean_pos(
  data,
  name,
  vars,
  max_na = NULL,
  exclude = NULL,
  events = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. The name of the summary score.
vars	character vector. The names of the columns to be summarized.
max_na	numeric, positive whole number. Number of missing items allowed (Default: NULL; no restriction on missing values).
exclude	character (vector). The value(s) to be excluded (Default: NULL; all values are used).
events	character (vector). Only compute the summary score for the specified events (Default: NULL; computed for all events).
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
data <- tibble::tribble(
  ~session_id, ~a, ~b, ~c, ~d, ~e,
  "ses-00A", -1, 1, 1, 1, NA,
  "ses-01A", 2, 777, 2, 2, 2,
  "ses-02A", 3, 3, 999, 3, 3,
  "ses-02A", 4, 4, 4, 777, NA,
  "ses-03A", 5, NA, 777, 999, 5,
  "ses-03A", NA, NA, NA, NA, NA,
  "ses-04A", 1, NA, NA, NA, NA
)

data |>
  ss_mean_pos(
    name = "mean",
    vars = c("a", "b", "c", "d", "e"),
    max_na = 1,
    exclude = c("777", "999")
```

```
  )

data |>
  ss_mean_pos(
    name = "mean",
    vars = c("a", "b", "c", "d", "e"),
    max_na = 1,
    exclude = c("777", "999"),
    combine = FALSE
  )

data |>
  ss_mean_pos(
    name = "mean",
    vars = c("a", "b", "c", "d", "e"),
    max_na = NULL,
    exclude = NULL,
    events = c("ses-00A", "ses-01A"),
  )
```

---

ss_nm *Compute number missing*

Description

Computes the number of missing items among a set of variables, with the option to exclude certain values (for non-responses like "Don't know" / "Decline to answer"). If all items are NA, the summary score will not be computed (assuming that the questionnaire was not filled out at all).

Usage

```
ss_nm(data, name, vars, exclude = NULL, events = NULL, combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. The name of the summary score.
vars	character vector. The names of the columns to be summarized.
exclude	character (vector). The value(s) to be excluded (Default: NULL; all values are used).
events	character (vector). Only compute the summary score for the specified events (Default: NULL; computed for all events).
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
data <- tibble::tribble(
  ~session_id, ~a, ~b,  ~c,  ~d,  ~e,
  "ses-00A",   1,  1,   1,   1,   NA,
  "ses-01A",   2,  777, 2,   2,   2,
  "ses-02A",   3,  3,   999, 3,   3,
  "ses-02A",   4,  4,   4,   777, NA,
  "ses-03A",   5,  NA,  777, 999, 5,
  "ses-03A",   NA, NA,  NA,  NA,  NA,
  "ses-04A",   1,  NA,  NA,  NA,  NA
)

data |>
  ss_nm(
    name    = "nm",
    vars    = c("a", "b", "c", "d", "e"),
    exclude = c("777", "999")
  )

data |>
  ss_nm(
    name    = "nm",
    vars    = c("a", "b", "c", "d", "e"),
    exclude = c("777", "999"),
    event   = c("ses-00A", "ses-01A")
  )
```

`ss_prsum` *Compute pro-rated sum*

Description

Computes the pro-rated sum of a set of variables, with the option to exclude certain values (for non-responses like "Don't know"/"Decline to answer") and to set a maximum number of missing values. Also include a second field

Usage

```
ss_prsum(
  data,
  name,
  vars,
  max_na = NULL,
  exclude = NULL,
  events = NULL,
  as_integer = TRUE,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. The name of the summary score.
vars	character vector. The names of the columns to be summarized.
max_na	numeric, positive whole number. Number of missing items allowed (Default: NULL; no restriction on missing values).
exclude	character (vector). The value(s) to be excluded (Default: NULL; all values are used).
events	character (vector). Only compute the summary score for the specified events (Default: NULL; computed for all events).
as_integer	logical. Whether to coerce the summary score to an integer, default is TRUE. If FALSE, the summary score will be a double.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
data <- tibble::tibble(
  participant_id = c("A", "A", "A", "B", "A", "B", "A"),
 session_id    = c("ses-00A", "ses-01A", "ses-02A", "ses-02A", "ses-03A", "0ses-3A", "ses-04A"),
  a              = c(1, 2, 3, 4, 5, NA, 1),
  b              = c(1, 777, 3, 4, NA, NA, NA),
  c              = c(1, 2, 999, 4, 777, NA, NA),
  d              = c(1, 2, 3, 777, 999, NA, NA),
  e              = c(NA, 2, 3, NA, 5, NA, NA)
)

data |>
  ss_prsum(
    name = "score_prorated_sum",
    vars = c("a", "b", "c", "d", "e"),
    max_na = 1,
    exclude = c("777", "999")
  )

data |>
  ss_prsum(
    name = "score_prorated_sum",
    vars = c("a", "b", "c", "d", "e"),
    max_na = 1,
    exclude = c("777", "999"),
    combine = FALSE
  )

data |>
```

```
ss_prsum(
  name = "score_prorated_sum",
  vars = c("a", "b", "c", "d", "e"),
  max_na = NULL,
  exclude = NULL,
  events = c("ses-00A", "ses-01A"),
)
```

`ss_sum` *Compute sum*

Description

Computes the sum of a set of variables, with the option to exclude certain values (for non-responses like "Don't know"/"Decline to answer") and to set a maximum number of missing values.

Usage

```
ss_sum(
  data,
  name,
  vars,
  max_na = NULL,
  exclude = NULL,
  events = NULL,
  as_integer = TRUE,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. The name of the summary score.
`vars`	character vector. The names of the columns to be summarized.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: NULL; no restriction on missing values).
`exclude`	character (vector). The value(s) to be excluded (Default: NULL; all values are used).
`events`	character (vector). Only compute the summary score for the specified events (Default: NULL; computed for all events).
`as_integer`	logical. Whether to coerce the summary score to an integer, default is `TRUE`. If `FALSE`, the summary score will be a double.
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
data <- tibble::tribble(
  ~session_id, ~a, ~b,  ~c,  ~d,  ~e,
  "ses-00A",   1,  1,   1,   1,   NA,
  "ses-01A",   2,  777, 2,   2,   2,
  "ses-02A",   3,  3,   999, 3,   3,
  "ses-02A",   4,  4,   4,   777, NA,
  "ses-03A",   5,  NA,  777, 999, 5,
  "ses-03A",   NA, NA,  NA,  NA,  NA,
  "ses-04A",   1,  NA,  NA,  NA,  NA
)

data |>
  ss_sum(
    name = "mean",
    vars = c("a", "b", "c", "d", "e"),
    max_na = 1,
    exclude = c("777", "999")
  )

data |>
  ss_sum(
    name = "mean",
    vars = c("a", "b", "c", "d", "e"),
    max_na = 1,
    exclude = c("777", "999"),
    combine = FALSE
  )

data |>
  ss_sum(
    name = "mean",
    vars = c("a", "b", "c", "d", "e"),
    max_na = NULL,
    exclude = NULL,
    events = c("ses-00A", "ses-01A"),
  )
```

---

ss_tscore *Compute T-score*

Description

This function computes the T-score based on the given columns, and the provided T-score table.

Usage

```
ss_tscore(
  data,
  data_norm = NULL,
  vars,
  name = "tscore",
  max_na = NULL,
  exclude = NULL,
  col_age = "age",
  col_sex = "sex",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
data_norm	tbl. Data frame containing the T-score table. See details.
vars	character vector. The names of the columns to be summarized.
name	character. The column name of the T-score.
max_na	numeric, positive whole number. Number of missing items allowed (Default: NULL; no restriction on missing values).
exclude	character (vector). The value(s) to be excluded (Default: NULL; all values are used).
col_age	character. The name of the age column.
col_sex	character The name of sex column.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Details

T-score table:

The data_norm should be a data frame containing the T-score table. The default value NULL is only used for internal usage (see below). For normal usage, the data_norm should be provided.

The table should have the following columns:

- sex: character or factor both ok. The biological sex of the participant. The values should be either "1" (male) or "2" (female).
- age_min: numeric. The minimum age of the participant.
- age_max: numeric. The maximum age of the participant.
- scale_r: numeric. The raw score of the scale.
- scale_t: numeric. The T-score of the scale.

For example

A tibble: n x 5

sex	age_min	age_max	scale_r	scale_t

<chr>	<dbl>	<dbl>	<dbl>	<dbl>
1	18	35	50	1
1	18	35	50.5	2
1	18	35	51	3
1	18	35	51.5	4
...				

out-range values:

- If the age of the participant is out of the range of the T-score table, the function will return NA.
- If the raw score is out of the range of the T-score table, the function will return NA.
- If any of the sex column is not "1" or "2", the function will return NA.
- If any of the required columns has NA, that row will return NA.

Internal usage:

When used in DSM internally, the data_norm can be omitted. Instead, the function will try to find the T-score table from the list_tscore option, and tries to find the tscore list based on object name provided in the list_tscore option. Once the object is found, the function will automatically extract the T-score table based on the function name.

- The list_tscore object should present in the global environment.
- See get_tscore_tbl() for more details on how to construct the list_tscore.

For example

```
my_tscore <<- readRDS("aseba_tscore.rds")
options(list_tscore = "my_tscore")
compute_mh_x_yyyy_zz_tscore(data)
```

Value

tbl. The input data frame with the T-score appended as a new column if combine is TRUE, otherwise only the T-score column.

Examples

```
data_norm <- tibble::tibble(
  sex = c("1", "1", "1", "1", "1"),
  age_min = 18,
  age_max = 35,
  scale_r = 0:4,
  scale_t = 20:24
)
data <- tibble::tibble(
  var1 = c(0, 1, NA, 1, 2),
  var2 = c(1, 2, 1, 2, 5),
  age = c(18, 20, 25, 99, 35),
  sex = c("1", "1", "1", "1", "1")
)
ss_tscore(
```

```
  data = data,
  data_norm = data_norm,
  max_na = 0,
  vars = c("var1", "var2")
)
```

`sui_substances` *Compute age of onset use for a given substance*

Description

Computes the age (in years) of onset use of a given substance. Returns `NA` for the participants with no onset use of the provided substance reported.

Usage

```
sui_substances

compute_su_y_sui__onset_useage(data, name, substance, combine = TRUE)
```

Arguments

`data`	tibble. A data frame containing the data.
`name`	character. The name of the output column for the computed score.
`substance`	character (vector). The substance to compute the score for. Must be one of the following values: • `"alc"` • `"alc__sip"` • `"rxstim"` • `"cath"` • `"cbd"` • `"coc"` • `"dxm"` • `"ghb"` • `"hall"` • `"inh"` • `"ket"` • `"meth"` • `"mdma"` • `"mj__blunt"` • `"mj__conc"` • `"mj__conc__smoke"` • `"mj__conc__vape"` • `"mj__drink"`

- "mj__edbl"
- "mj__smoke"
- "mj__vape"
- "mj__synth"
- "mj__tinc"
- "nic__chew"
- "nic__cigar"
- "nic__cig"
- "nic__hookah"
- "nic__pipe"
- "nic__rplc"
- "nic__vape"
- "opi"
- "othdrg"
- "qc"
- "roid"
- "rxopi"
- "salv"
- "shroom"
- "rxsed"
- "vape"
- "vape__flav"

combine logical. Whether to combine the summary score column with the input data frame (Default: 'TRUE').

Format

sui_substances is a character vector of substances keywords.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_su_y_sui__onset_useage(
  data = data_sui,
  name = "su_y_sui__alc__onset_useage",
  substance = "alc"
)

## End(Not run)
```

`tlfb_substances` *Compute TLFB length of abstinence*

Description

Computes the length of abstinence in days for a given (set of) substance(s). Optionally, allows to filter by period (detailed and/or estimated); only considering a specified number of days before the TLFB interview; and/or only binge use.

Usage

```
tlfb_substances

compute_tlfb_abst(
  data,
  name,
  substance = NULL,
  period = NULL,
  days = NULL,
  binge = NULL
)
```

Arguments

`data`	tibble. A data frame containing the TLFB raw data.
`name`	character. The name of the output column for the computed score.
`substance`	character (vector). The substance(s) to compute the score for. Must be one or several of the following values: • `"'Fake' Marijuana or Synthetics"` • `"Alcohol"` • `"Anabolic Steroids"` • `"Any Other Drug They Used to Get High"` • `"Blunts or Combined Tobacco and Marijuana in Joints"` • `"CBD (Non-Medical Use)"` • `"Cathinones such as Bath Salts, Drone, or Meph"` • `"Cigars, Little Cigars, or Cigarillos"` • `"Cocaine or Crack Cocaine"` • `"Concentrated Marijuana Tinctures"` • `"Ecstasy, Molly, or MDMA"` • `"Electronic Nicotine or Vaping Products"` • `"GHB, Liquid G, or Georgia Homeboy"` • `"Hallucinogen Drugs including LSD, PCP, Peyote, Mescaline, DMT, AMT, or Foxy"` • `"Heroin, Opium, Junk, Smack, or Dope"`

- "Hookah with Tobacco"
- "Inhalants"
- "Ketamine or Special K"
- "Marijuana Edibles"
- "Marijuana Infused Alcohol Drinks"
- "Methamphetamine, Meth, or Crystal Meth"
- "Nicotine Replacements"
- "OTC Cough or Cold Medicine, DXM, 'Lean', or 'Purple Drank'"
- "Prescription Anxiolytics, Tranquilizers, or Sedatives"
- "Prescription Pain Relievers or Opioids"
- "Prescription Stimulants"
- "Psilocybin, Magic Mushrooms, or Shrooms"
- "Salvia"
- "Smokeless Tobacco, Chew, or Snus"
- "Smoking Marijuana Flower"
- "Smoking Marijuana Oils or Concentrates"
- "Tobacco Cigarette"
- "Tobacco in a Pipe"
- "Vaped Marijuana Flower"
- "Vaped Marijuana Oils or Concentrates"
- "Marijuana (all forms)"
- "Nicotine (all forms)"

(Default: NULL, i.e., all substances are considered.)

period — character (vector). The period for which the score is computed for. Must be one of "detailed" (last year before date of TLFB interview) or "estimated" (more than one year before date of TLFB). (Default: NULL, i.e., all periods are considered). Cannot be used in combination with days.

days — integer. Number of days before the TLFB interview to consider. (Default: NULL, i.e., all days are considered). Cannot be used in combination with period.

binge — (named list of) numeric. Binge threshold(s) for the substance(s). If only one value is provided, it is used, independent of the sex of the participant. If a list is provided, it must contain two named elements: "F" (female) and "M" (male) with the respective sex-specific binge thresholds. Only days where the the quantity of the substance(s) exceeds the specified threshold(s) are considered. (Default: NULL, i.e., binge behavior is not considered).

Format

tlfb_substances is a character vector of all substances that can be reported in the TLFB.

Value

A tibble with the computed score for each participant/event.

Examples

```
## Not run:
compute_tlfb_abst(
  data = data_tlfb,
  name = "su_y_tlfb__alc__cum_abst",
  substance = "Alcohol"
)

## End(Not run)
```

---

vars_ab_g_dyn__cohort_edu__cgs

Compute "Cohort description: Highest education across caregivers"

Description

Computes the summary score ab_g_dyn__cohort_edu__cgs Cohort description: Highest education across caregivers

- *Summarized variables:*
  - ab_p_demo__edu__slf_001
  - ab_p_demo__edu__slf_001__v01
  - ab_p_demo__edu__slf_001__v02
  - ab_p_demo__edu__prtnr_001
  - ab_p_demo__edu__prtnr_001__v01
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_ab_g_dyn__cohort_edu__cgs

compute_ab_g_dyn__cohort_edu__cgs(
  data,
  name = "ab_g_dyn__cohort_edu__cgs",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.

exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Format

a character vector of all column names used to compute summary score of ab_g_dyn__cohort_edu__cgs.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ab_g_dyn__cohort_income__hhold__6lvl

Compute "Cohort description: Household income - 6 levels"

Description

Computes the summary score ab_g_dyn__cohort_income__hhold__6lvl Cohort description: Household income - 6 levels

- *Summarized variables:*
  - ab_p_demo__income__hhold_001
  - ab_p_demo__income__hhold_001__v01

Usage

```
vars_ab_g_dyn__cohort_income__hhold__6lvl

compute_ab_g_dyn__cohort_income__hhold__6lvl(
  data,
  name = "ab_g_dyn__cohort_income__hhold__6lvl",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Format

a character vector of all column names used to compute summary score of ab_g_dyn__cohort_income__hhold__6lvl.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ab_g_dyn__cohort_prtnrshp__employ

Compute "Cohort description: Caregivers' partnership and employment status"

Description

Computes the summary score ab_g_dyn__cohort_prtnrshp__employ Cohort description: Caregivers' partnership and employment status

- *Summarized variables:*
  - ab_p_demo__marital__slf_001
  - ab_p_demo__prtnr_001
  - ab_p_demo__empl__slf_001
  - ab_p_demo__empl__prtnr_001
  - ab_p_demo__empl__prtnr_001__v01
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_ab_g_dyn__cohort_prtnrshp__employ

compute_ab_g_dyn__cohort_prtnrshp__employ(
  data,
  name = "ab_g_dyn__cohort_prtnrshp__employ",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Format

a character vector of all column names used to compute summary score of ab_g_dyn__cohort_prtnrshp__employ.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ab_g_stc__cohort_ethn

Compute "Cohort description: Ethnicity (Hispanic or not Hispanic) [Based on baseline response; missingness filled in from longitudinal responses]"

Description

Computes the summary score ab_g_stc__cohort_ethn Cohort description: Ethnicity (Hispanic or not Hispanic) [Based on baseline response; missingness filled in from longitudinal responses]

- *Summarized variables:*
  - ab_p_demo__ethn_001
  - ab_p_demo__ethn_001__v01
- *Excluded values:*
  - 777
  - 999
- *Notes:*
  - Values in ab_p_demo__ethn_001__v01 were recoded:
    - "0" –> "2",
    - "2" –> "1"
    - "3" –> "1"
    - "4" –> "1"
  - Values in ab_p_demo__ethn_001 were recoded:
    - "0" –> "2"

Usage

```
vars_ab_g_stc__cohort_ethn

compute_ab_g_stc__cohort_ethn(
  data,
  name = "ab_g_stc__cohort_ethn",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Format

a character vector of all column names used to compute summary score of ab_g_stc__cohort_ethn.

Value

tbl. The input data frame with the summary score appended as a new column (default). If combine == FALSE, a data frame with two columns: participant ID and summary score.

---

vars_ab_g_stc__cohort_ethnrace__leg

Compute "Cohort description: Ethno-racial identity (Legacy ABCD variable reporting 6 levels; Hispanic ethnicity report outweighs any racial endorements) [Based on baseline response; missingness filled in from longitudinal responses]"

Description

Computes the summary score ab_g_stc__cohort_ethnrace__leg Cohort description: Ethno-racial identity (Legacy ABCD variable reporting 6 levels; Hispanic ethnicity report outweighs any racial endorements) [Based on baseline response; missingness filled in from longitudinal responses]

- *Summarized variables:*
  - ab_p_demo__ethn_001
  - ab_p_demo__ethn_001__v01
  - ab_p_demo__race_001___0
  - ab_p_demo__race_001___10
  - ab_p_demo__race_001___11
  - ab_p_demo__race_001___12
  - ab_p_demo__race_001___13
  - ab_p_demo__race_001___14
  - ab_p_demo__race_001___15
  - ab_p_demo__race_001___16
  - ab_p_demo__race_001___17
  - ab_p_demo__race_001___18

- ab_p_demo__race_001___19
- ab_p_demo__race_001___20
- ab_p_demo__race_001___21
- ab_p_demo__race_001___22
- ab_p_demo__race_001___23
- ab_p_demo__race_001___24
- ab_p_demo__race_001___25
- ab_p_demo__race_001___777
- ab_p_demo__race_001___999
- ab_p_demo__race_001__v01___999
- ab_p_demo__race_001__v01___10
- ab_p_demo__race_001__v01___11
- ab_p_demo__race_001__v01___12
- ab_p_demo__race_001__v01___20
- ab_p_demo__race_001__v01___21
- ab_p_demo__race_001__v01___22
- ab_p_demo__race_001__v01___23
- ab_p_demo__race_001__v01___13
- ab_p_demo__race_001__v01___14
- ab_p_demo__race_001__v01___15
- ab_p_demo__race_001__v01___17
- ab_p_demo__race_001__v01___18
- ab_p_demo__race_001__v01___19
- ab_p_demo__race_001__v01___16
- ab_p_demo__race_001__v01___24
- ab_p_demo__race_001__v01___777

Usage

```
vars_ab_g_stc__cohort_ethnrace__leg

compute_ab_g_stc__cohort_ethnrace__leg(
  data,
  name = "ab_g_stc__cohort_ethnrace__leg",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Format

a character vector of all column names used to compute summary score of ab_g_stc__cohort_ethnrace__leg.

Value

tbl. The input data frame with the summary score appended as a new column (default). If combine == FALSE, a data frame with two columns: participant ID and summary score.

---

vars_ab_g_stc__cohort_ethnrace__mblack

Compute "Cohort description: Ethno-racial identity (8 level aggregation providing information on Black identity for multiracial endoreements) [Based on baseline response; missingness filled in from longitudinal responses]"

Description

Computes the summary score ab_g_stc__cohort_ethnrace__mblack Cohort description: Ethno-racial identity (8 level aggregation providing information on Black identity for multiracial endoreements) [Based on baseline response; missingness filled in from longitudinal responses]

- *Summarized variables:*
  - ab_p_demo__ethn_001
  - ab_p_demo__ethn_001__v01
  - ab_p_demo__race_001___0
  - ab_p_demo__race_001___10
  - ab_p_demo__race_001___11
  - ab_p_demo__race_001___12
  - ab_p_demo__race_001___13
  - ab_p_demo__race_001___14
  - ab_p_demo__race_001___15
  - ab_p_demo__race_001___16
  - ab_p_demo__race_001___17
  - ab_p_demo__race_001___18
  - ab_p_demo__race_001___19
  - ab_p_demo__race_001___20
  - ab_p_demo__race_001___21
  - ab_p_demo__race_001___22
  - ab_p_demo__race_001___23
  - ab_p_demo__race_001___24
  - ab_p_demo__race_001___25
  - ab_p_demo__race_001___777
  - ab_p_demo__race_001___999

- ab_p_demo__race_001__v01___999
- ab_p_demo__race_001__v01___10
- ab_p_demo__race_001__v01___11
- ab_p_demo__race_001__v01___12
- ab_p_demo__race_001__v01___20
- ab_p_demo__race_001__v01___21
- ab_p_demo__race_001__v01___22
- ab_p_demo__race_001__v01___23
- ab_p_demo__race_001__v01___13
- ab_p_demo__race_001__v01___14
- ab_p_demo__race_001__v01___15
- ab_p_demo__race_001__v01___17
- ab_p_demo__race_001__v01___18
- ab_p_demo__race_001__v01___19
- ab_p_demo__race_001__v01___16
- ab_p_demo__race_001__v01___24
- ab_p_demo__race_001__v01___777

Usage

```
vars_ab_g_stc__cohort_ethnrace__mblack

compute_ab_g_stc__cohort_ethnrace__mblack(
  data,
  name = "ab_g_stc__cohort_ethnrace__mblack",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Format

a character vector of all column names used to compute summary score of ab_g_stc__cohort_ethnrace__mblack.

Value

tbl. The input data frame with the summary score appended as a new column (default). If combine == FALSE, a data frame with two columns: participant ID and summary score.

vars_ab_g_stc__cohort_ethnrace__meim

Compute "Cohort description: Ethno-racial identity (15 level classification from fc_p_meim_001) [Based on baseline response; missingness filled in from longitudinal responses]"

Description

Computes the summary score ab_g_stc__cohort_ethnrace__meim Cohort description: Ethno-racial identity (15 level classification from fc_p_meim_001) [Based on baseline response; missingness filled in from longitudinal responses]

- *Summarized variables:*
  - fc_p_meim_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_ab_g_stc__cohort_ethnrace__meim

compute_ab_g_stc__cohort_ethnrace__meim(
  data,
  name = "ab_g_stc__cohort_ethnrace__meim",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Format

a character vector of all column names used to compute summary score of ab_g_stc__cohort_ethnrace__meim.

Value

tbl. The input data frame with the summary score appended as a new column (default). If combine == FALSE, a data frame with two columns: participant ID and summary score.

vars_ab_g_stc__cohort_ethnrace__mhisp

Compute "Cohort description: Ethno-racial identity (8 level aggregation providing information on ethnicity for multiracial endoremements) [Based on baseline response; missingness filled in from longitudinal responses]"

Description

Computes the summary score ab_g_stc__cohort_ethnrace__mhisp Cohort description: Ethno-racial identity (8 level aggregation providing information on ethnicity for multiracial endoremements) [Based on baseline response; missingness filled in from longitudinal responses]

- *Summarized variables:*
  - ab_p_demo__ethn_001
  - ab_p_demo__ethn_001__v01
  - ab_p_demo__race_001___0
  - ab_p_demo__race_001___10
  - ab_p_demo__race_001___11
  - ab_p_demo__race_001___12
  - ab_p_demo__race_001___13
  - ab_p_demo__race_001___14
  - ab_p_demo__race_001___15
  - ab_p_demo__race_001___16
  - ab_p_demo__race_001___17
  - ab_p_demo__race_001___18
  - ab_p_demo__race_001___19
  - ab_p_demo__race_001___20
  - ab_p_demo__race_001___21
  - ab_p_demo__race_001___22
  - ab_p_demo__race_001___23
  - ab_p_demo__race_001___24
  - ab_p_demo__race_001___25
  - ab_p_demo__race_001___777
  - ab_p_demo__race_001___999
  - ab_p_demo__race_001__v01___999
  - ab_p_demo__race_001__v01___10
  - ab_p_demo__race_001__v01___11
  - ab_p_demo__race_001__v01___12
  - ab_p_demo__race_001__v01___20
  - ab_p_demo__race_001__v01___21
  - ab_p_demo__race_001__v01___22

- ab_p_demo__race_001__v01___23
- ab_p_demo__race_001__v01___13
- ab_p_demo__race_001__v01___14
- ab_p_demo__race_001__v01___15
- ab_p_demo__race_001__v01___17
- ab_p_demo__race_001__v01___18
- ab_p_demo__race_001__v01___19
- ab_p_demo__race_001__v01___16
- ab_p_demo__race_001__v01___24
- ab_p_demo__race_001__v01___777

Usage

```
vars_ab_g_stc__cohort_ethnrace__mhisp

compute_ab_g_stc__cohort_ethnrace__mhisp(
  data,
  name = "ab_g_stc__cohort_ethnrace__mhisp",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Format

a character vector of all column names used to compute summary score of ab_g_stc__cohort_ethnrace__mhisp.

Value

tbl. The input data frame with the summary score appended as a new column (default). If combine == FALSE, a data frame with two columns: participant ID and summary score.

vars_ab_g_stc__cohort_race__nih

Compute "Cohort description: Race (NIH classification reporting 7 levels) [Based on baseline response; missingness filled in from longitudinal responses]"

Description

Computes the summary score ab_g_stc__cohort_race__nih Cohort description: Race (NIH classification reporting 7 levels) [Based on baseline response; missingness filled in from longitudinal responses]

- *Summarized variables:*
  - ab_p_demo__race_001___0
  - ab_p_demo__race_001___10
  - ab_p_demo__race_001___11
  - ab_p_demo__race_001___12
  - ab_p_demo__race_001___13
  - ab_p_demo__race_001___14
  - ab_p_demo__race_001___15
  - ab_p_demo__race_001___16
  - ab_p_demo__race_001___17
  - ab_p_demo__race_001___18
  - ab_p_demo__race_001___19
  - ab_p_demo__race_001___20
  - ab_p_demo__race_001___21
  - ab_p_demo__race_001___22
  - ab_p_demo__race_001___23
  - ab_p_demo__race_001___24
  - ab_p_demo__race_001___25
  - ab_p_demo__race_001___777
  - ab_p_demo__race_001___999
  - ab_p_demo__race_001__v01___999
  - ab_p_demo__race_001__v01___10
  - ab_p_demo__race_001__v01___11
  - ab_p_demo__race_001__v01___12
  - ab_p_demo__race_001__v01___20
  - ab_p_demo__race_001__v01___21
  - ab_p_demo__race_001__v01___22
  - ab_p_demo__race_001__v01___23
  - ab_p_demo__race_001__v01___13
  - ab_p_demo__race_001__v01___14

- ab_p_demo__race_001__v01___15
- ab_p_demo__race_001__v01___17
- ab_p_demo__race_001__v01___18
- ab_p_demo__race_001__v01___19
- ab_p_demo__race_001__v01___16
- ab_p_demo__race_001__v01___24
- ab_p_demo__race_001__v01___777

Usage

```
vars_ab_g_stc__cohort_race__nih

compute_ab_g_stc__cohort_race__nih(
  data,
  name = "ab_g_stc__cohort_race__nih",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: FALSE)

Format

a tibble of all column names, baseline and longitudinal, used to compute summary score of ab_g_stc__cohort_race__nih.

Value

tbl. The input data frame with the summary score appended as a new column (default). If combine == FALSE, a data frame with two columns: participant ID and summary score.

---

vars_ab_p_demo__ntvam *Compute "Demographics [Parent] (Native American Acculturation): Mean"*

Description

Computes the summary score ab_p_demo__ntvam_mean (Demographics [Parent] (Native American Acculturation): Mean)

- *Summarized variables:*
  - ab_p_demo__ntvam_005
  - ab_p_demo__ntvam_006
  - ab_p_demo__ntvam_007
- *Excluded values:*
  - 999
- *Validation criterion:* maximally 0 of 3 items missing

Usage

```
vars_ab_p_demo__ntvam

compute_ab_p_demo__ntvam_mean(
  data,
  name = "ab_p_demo__ntvam_mean",
  max_na = 0,
  exclude = c("999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_ab_p_demo__ntvam is a character vector of all column names used to compute summary score of ab_p_demo__ntvam.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_fc_p_fes__cohes *Compute "Family Environment Scale [Parent] (Cohesion): Mean"*

Description

Computes the summary score `fc_p_fes__cohes_mean` (Family Environment Scale [Parent] (Cohesion): Mean)

- *Summarized variables:*
  - `fc_p_fes__cohes_001`
  - `fc_p_fes__cohes_002`
  - `fc_p_fes__cohes_003`
  - `fc_p_fes__cohes_004`
  - `fc_p_fes__cohes_005`
  - `fc_p_fes__cohes_006`
  - `fc_p_fes__cohes_007`
  - `fc_p_fes__cohes_008`
  - `fc_p_fes__cohes_009`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
vars_fc_p_fes__cohes

compute_fc_p_fes__cohes_mean(
  data,
  name = "fc_p_fes__cohes_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_p_fes__cohes is a character vector of all column names used to compute summary score of `fc_p_fes__cohes`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_p_fes__confl` *Compute "Family Environment Scale [Parent] (Conflict): Mean"*

Description

Computes the summary score `fc_p_fes__confl_mean` (Family Environment Scale [Parent] (Conflict): Mean)

- *Summarized variables:*
  - `fc_p_fes__confl_001`
  - `fc_p_fes__confl_002`
  - `fc_p_fes__confl_003`
  - `fc_p_fes__confl_004`
  - `fc_p_fes__confl_005`
  - `fc_p_fes__confl_006`
  - `fc_p_fes__confl_007`
  - `fc_p_fes__confl_008`
  - `fc_p_fes__confl_009`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
vars_fc_p_fes__confl

compute_fc_p_fes__confl_mean(
  data,
  name = "fc_p_fes__confl_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_fes__confl is a character vector of all column names used to compute summary score of fc_p_fes__confl.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_fes__expr *Compute "Family Environment Scale [Parent] (Expression): Mean"*

Description

Computes the summary score fc_p_fes__expr_mean (Family Environment Scale [Parent] (Expression): Mean)

- *Summarized variables:*
  - fc_p_fes__expr_001
  - fc_p_fes__expr_002
  - fc_p_fes__expr_003
  - fc_p_fes__expr_004
  - fc_p_fes__expr_005
  - fc_p_fes__expr_006
  - fc_p_fes__expr_007
  - fc_p_fes__expr_008
  - fc_p_fes__expr_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
vars_fc_p_fes__expr

compute_fc_p_fes__expr_mean(
  data,
  name = "fc_p_fes__expr_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_fes__expr is a character vector of all column names used to compute summary score of fc_p_fes__expr.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_fes__intelcult

Compute "Family Environment Scale [Parent] (Intellectual and cultural): Mean"

Description

Computes the summary score fc_p_fes__intelcult_mean (Family Environment Scale [Parent] (Intellectual and cultural): Mean)

- *Summarized variables:*
  - fc_p_fes__intelcult_001
  - fc_p_fes__intelcult_002
  - fc_p_fes__intelcult_003
  - fc_p_fes__intelcult_004

  - fc_p_fes__intelcult_005
  - fc_p_fes__intelcult_006
  - fc_p_fes__intelcult_007
  - fc_p_fes__intelcult_008
  - fc_p_fes__intelcult_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
vars_fc_p_fes__intelcult

compute_fc_p_fes__intelcult_mean(
  data,
  name = "fc_p_fes__intelcult_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_fes__intelcult is a character vector of all column names used to compute summary score of fc_p_fes__intelcult.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_fc_p_fes__org *Compute "Family Environment Scale [Parent] (Organization): Mean"*

Description

Computes the summary score fc_p_fes__org_mean (Family Environment Scale [Parent] (Organization): Mean)

- *Summarized variables:*
  - fc_p_fes__org_001
  - fc_p_fes__org_002
  - fc_p_fes__org_003
  - fc_p_fes__org_004
  - fc_p_fes__org_005
  - fc_p_fes__org_006
  - fc_p_fes__org_007
  - fc_p_fes__org_008
  - fc_p_fes__org_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
vars_fc_p_fes__org

compute_fc_p_fes__org_mean(
  data,
  name = "fc_p_fes__org_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_fes__org is a character vector of all column names used to compute summary score of `fc_p_fes__org`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_p_fes__rec` *Compute "Family Environment Scale [Parent] (Activity and recreational): Mean"*

Description

Computes the summary score `fc_p_fes__rec_mean` (Family Environment Scale [Parent] (Activity and recreational): Mean)

- *Summarized variables:*
  - `fc_p_fes__rec_001`
  - `fc_p_fes__rec_002`
  - `fc_p_fes__rec_003`
  - `fc_p_fes__rec_004`
  - `fc_p_fes__rec_005`
  - `fc_p_fes__rec_006`
  - `fc_p_fes__rec_007`
  - `fc_p_fes__rec_008`
  - `fc_p_fes__rec_009`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
vars_fc_p_fes__rec

compute_fc_p_fes__rec_mean(
  data,
  name = "fc_p_fes__rec_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_fes__rec is a character vector of all column names used to compute summary score of fc_p_fes__rec.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_meim *Compute "The Multigroup Ethnic Identity Measure-Revised [Parent]: Mean"*

Description

Computes the summary score fc_p_meim_mean (The Multigroup Ethnic Identity Measure-Revised [Parent]: Mean)

- *Summarized variables:*
  - fc_p_meim__commattach_001
  - fc_p_meim__commattach_002
  - fc_p_meim__commattach_003
  - fc_p_meim__explor_001
  - fc_p_meim__explor_002
  - fc_p_meim__explor_003
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_fc_p_meim

compute_fc_p_meim_mean(
  data,
  name = "fc_p_meim_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_meim is a character vector of all column names used to compute summary score of fc_p_meim.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_meim__commattach

Compute "The Multigroup Ethnic Identity Measure-Revised [Parent] (Commitment and attachment): Mean"

Description

Computes the summary score fc_p_meim__commattach_mean (The Multigroup Ethnic Identity Measure-Revised [Parent] (Commitment and attachment): Mean)

- *Summarized variables:*
  - fc_p_meim__commattach_001
  - fc_p_meim__commattach_002
  - fc_p_meim__commattach_003
- *Excluded values:* none
- *Validation criterion:* none of 3 items missing

Usage

```
vars_fc_p_meim__commattach

compute_fc_p_meim__commattach_mean(
  data,
  name = "fc_p_meim__commattach_mean",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_meim__commattach is a character vector of all column names used to compute summary score of fc_p_meim__commattach.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_meim__explor

Compute "The Multigroup Ethnic Identity Measure-Revised [Parent] (Exploration): Mean"

Description

Computes the summary score fc_p_meim__explor_mean (The Multigroup Ethnic Identity Measure-Revised [Parent] (Exploration): Mean)

- *Summarized variables:*
  - fc_p_meim__explor_001
  - fc_p_meim__explor_002
  - fc_p_meim__explor_003
- *Excluded values:* none
- *Validation criterion:* none of 3 items missing

Usage

```
vars_fc_p_meim__explor

compute_fc_p_meim__explor_mean(
  data,
  name = "fc_p_meim__explor_mean",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_meim__explor is a character vector of all column names used to compute summary score of fc_p_meim__explor.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_nce *Compute "Neighborhood Collective Efficacy [Parent]: Mean"*

Description

Computes the summary score fc_p_nce_mean (Neighborhood Collective Efficacy [Parent]: Mean)

- *Summarized variables:*
  - fc_p_nce__cc_001
  - fc_p_nce__cc_002
  - fc_p_nce__cc_003
  - fc_p_nce__cc_004
  - fc_p_nce__cc_005
  - fc_p_nce__isc_001
  - fc_p_nce__isc_002
  - fc_p_nce__isc_003
  - fc_p_nce__isc_004
  - fc_p_nce__isc_005
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 2 of 10 items missing
- *Notes:*
  - The following variables are reverse coded before computing the summary score:
    - fc_p_nce__cc_003
    - fc_p_nce__cc_004
  - The value "99" (Don't know) is recoded to "3" (Neither... nor...)

Usage

```
vars_fc_p_nce

compute_fc_p_nce_mean(data, name = "fc_p_nce_mean", max_na = 2, combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 2).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_nce is a character vector of all column names used to compute summary score of fc_p_nce.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_nce__cc *Compute "Neighborhood Collective Efficacy [Parent] (Community cohesion): Mean"*

Description

Computes the summary score fc_p_nce__cc_mean (Neighborhood Collective Efficacy [Parent] (Community cohesion): Mean)

- *Summarized variables:*
  - fc_p_nce__cc_001
  - fc_p_nce__cc_002
  - fc_p_nce__cc_003
  - fc_p_nce__cc_004
  - fc_p_nce__cc_005
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 5 items missing
- *Notes:*
  - The following variables are reverse coded before computing the summary score:
    - fc_p_nce__cc_003
    - fc_p_nce__cc_004
  - The value "99" (Don't know) is recoded to "3" (Neither... nor...)

Usage

```
vars_fc_p_nce__cc

compute_fc_p_nce__cc_mean(
  data,
  name = "fc_p_nce__cc_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_nce__cc is a character vector of all column names used to compute summary score of fc_p_nce__cc.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_nce__isc *Compute "Neighborhood Collective Efficacy [Parent] (Informal social control): Mean"*

Description

Computes the summary score fc_p_nce__isc_mean (Neighborhood Collective Efficacy [Parent] (Informal social control): Mean)

- *Summarized variables:*
  - fc_p_nce__isc_001
  - fc_p_nce__isc_002
  - fc_p_nce__isc_003
  - fc_p_nce__isc_004
  - fc_p_nce__isc_005
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 5 items missing
- *Note:* The value "99" (Don't know) is recoded to "3" (Neither... nor...)

Usage

```
vars_fc_p_nce__isc

compute_fc_p_nce__isc_mean(
  data,
  name = "fc_p_nce__isc_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_nce__isc is a character vector of all column names used to compute summary score of fc_p_nce__isc.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_nsc__ns *Compute "Neighborhood Safety & Crime [Parent] (Neighborhood safety): Mean"*

Description

Computes the summary score fc_p_nsc__ns_mean (Neighborhood Safety & Crime [Parent] (Neighborhood safety): Mean)

- *Summarized variables:*
  - fc_p_nsc__ns_001
  - fc_p_nsc__ns_002
  - fc_p_nsc__ns_003
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* none of 3 items missing

Usage

```
vars_fc_p_nsc__ns

compute_fc_p_nsc__ns_mean(
  data,
  name = "fc_p_nsc__ns_mean",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_nsc__ns is a character vector of all column names used to compute summary score of fc_p_nsc__ns.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_pk__knowl *Compute "Parental Knowledge Scale [Parent]: Mean"*

Description

Computes the summary score fc_p_pk__knowl_mean (Parental Knowledge Scale [Parent]: Mean)

- *Summarized variables:*
  - fc_p_pk__knowl_001
  - fc_p_pk__knowl_002
  - fc_p_pk__knowl_003
  - fc_p_pk__knowl_004
  - fc_p_pk__knowl_005
  - fc_p_pk__knowl_006
  - fc_p_pk__knowl_007
  - fc_p_pk__knowl_008
  - fc_p_pk__knowl_009

- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 9 items missing
- *Notes:* All items are reverse coded before computing the summary score.

Usage

```
vars_fc_p_pk__knowl

compute_fc_p_pk__knowl_mean(
  data,
  name = "fc_p_pk__knowl_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_pk__knowl is a character vector of all column names used to compute summary score of fc_p_pk__knowl.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_psb *Compute "Prosocial Behavior [Parent]: Mean"*

Description

Computes the summary score fc_p_psb_mean (Prosocial Behavior [Parent]: Mean)

- *Summarized variables:*
  - fc_p_psb_001
  - fc_p_psb_002
  - fc_p_psb_003

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* none of 3 items missing

Usage

```
vars_fc_p_psb

compute_fc_p_psb_mean(
  data,
  name = "fc_p_psb_mean",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 0).
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_p_psb is a character vector of all column names used to compute summary score of `fc_p_psb`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_p_vs__famil` *Compute "Values Scale [Parent] (Familism): Mean (Subscales: supp, ref, obl)"*

Description

Computes the summary score `fc_p_vs__famil_mean` (Values Scale [Parent] (Familism): Mean (Subscales: supp, ref, obl))

- *Summarized variables:*
  - `fc_p_vs__supp_001`
  - `fc_p_vs__supp_002`
  - `fc_p_vs__supp_003`
  - `fc_p_vs__supp_004`
  - `fc_p_vs__supp_005`
  - `fc_p_vs__supp_006`
  - `fc_p_vs__ref_001`
  - `fc_p_vs__ref_002`
  - `fc_p_vs__ref_003`
  - `fc_p_vs__ref_004`
  - `fc_p_vs__ref_005`
  - `fc_p_vs__obl_001`
  - `fc_p_vs__obl_002`
  - `fc_p_vs__obl_003`
  - `fc_p_vs__obl_004`
  - `fc_p_vs__obl_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:*
  - maximally 3 of 16 items missing
  - all sub-scales can be calculated

Usage

```
vars_fc_p_vs__famil

compute_fc_p_vs__famil_mean(
  data,
  name = "fc_p_vs__famil_mean",
  max_na = 3,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.

max_na	numeric vector of positive whole number. Number of missing items allowed (Default: 3).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

a character vector of all column names used to compute summary score of fc_p_vs__famil_mean and fc_p_vs__famil_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_vs__famil__v01

Compute "Values Scale [Parent] (Familism): Mean - Version 1 (Subscales: supp, ref)"

Description

Computes the summary score fc_p_vs__famil_mean__v01 (Values Scale [Parent] (Familism): Mean - Version 1 (Subscales: supp, ref))

- *Summarized variables:*
  - fc_p_vs__supp_001
  - fc_p_vs__supp_002
  - fc_p_vs__supp_003
  - fc_p_vs__supp_004
  - fc_p_vs__supp_005
  - fc_p_vs__supp_006
  - fc_p_vs__ref_001
  - fc_p_vs__ref_002
  - fc_p_vs__ref_003
  - fc_p_vs__ref_004
  - fc_p_vs__ref_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:*
  - maximally 2 of 11 items missing
  - all sub-scales can be calculated

Usage

```
vars_fc_p_vs__famil__v01

compute_fc_p_vs__famil_mean__v01(
  data,
  name = "fc_p_vs__famil_mean__v01",
  max_na = 2,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric vector of positive whole number. Number of missing items allowed (Default: 2).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

a character vector of all column names used to compute summary score of fc_p_vs__famil_mean__v01 and fc_p_vs__famil_nm__v01.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_p_vs__famil_mean()

---

vars_fc_p_vs__indselfrel

Compute "Values Scale [Parent] (Independence and self-reliance): Mean"

Description

Computes the summary score fc_p_vs__indselfrel_mean (Values Scale [Parent] (Independence and self-reliance): Mean)

- *Summarized variables:*
  - fc_p_vs__indselfrel_001

  - fc_p_vs__indselfrel_002
  - fc_p_vs__indselfrel_003
  - fc_p_vs__indselfrel_004
  - fc_p_vs__indselfrel_005

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_p_vs__indselfrel

compute_fc_p_vs__indselfrel_mean(
  data,
  name = "fc_p_vs__indselfrel_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_vs__indselfrel is a character vector of all column names used to compute summary score of fc_p_vs__indselfrel.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_fc_p_vs__obl *Compute "Values Scale [Parent] (Family obligation): Mean"*

Description

Computes the summary score `fc_p_vs__obl_mean` (Values Scale [Parent] (Family obligation): Mean)

- *Summarized variables:*
  - `fc_p_vs__obl_001`
  - `fc_p_vs__obl_002`
  - `fc_p_vs__obl_003`
  - `fc_p_vs__obl_004`
  - `fc_p_vs__obl_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_p_vs__obl

compute_fc_p_vs__obl_mean(
  data,
  name = "fc_p_vs__obl_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_p_vs__obl is a character vector of all column names used to compute summary score of `fc_p_vs__obl`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_p_vs__ref` *Compute "Values Scale [Parent] (Family as referent): Mean"*

Description

Computes the summary score `fc_p_vs__ref_mean` (Values Scale [Parent] (Family as referent): Mean)

- *Summarized variables:*
  - `fc_p_vs__ref_001`
  - `fc_p_vs__ref_002`
  - `fc_p_vs__ref_003`
  - `fc_p_vs__ref_004`
  - `fc_p_vs__ref_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_p_vs__ref

compute_fc_p_vs__ref_mean(
  data,
  name = "fc_p_vs__ref_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_p_vs__ref is a character vector of all column names used to compute summary score of `fc_p_vs__ref`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_p_vs__relig` *Compute "Values Scale [Parent] (Religion): Mean"*

Description

Computes the summary score `fc_p_vs__relig_mean` (Values Scale [Parent] (Religion): Mean)

- *Summarized variables:*
  - `fc_p_vs__relig_001`
  - `fc_p_vs__relig_002`
  - `fc_p_vs__relig_003`
  - `fc_p_vs__relig_004`
  - `fc_p_vs__relig_005`
  - `fc_p_vs__relig_006`
  - `fc_p_vs__relig_007`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_fc_p_vs__relig

compute_fc_p_vs__relig_mean(
  data,
  name = "fc_p_vs__relig_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_p_vs__relig is a character vector of all column names used to compute summary score of fc_p_vs__relig.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_p_vs__supp *Compute "Values Scale [Parent] (Family support): Mean"*

Description

Computes the summary score fc_p_vs__supp_mean (Values Scale [Parent] (Family support): Mean)

- *Summarized variables:*
  - fc_p_vs__supp_001
  - fc_p_vs__supp_002
  - fc_p_vs__supp_003
  - fc_p_vs__supp_004
  - fc_p_vs__supp_005
  - fc_p_vs__supp_006
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_fc_p_vs__supp

compute_fc_p_vs__supp_mean(
  data,
  name = "fc_p_vs__supp_mean",
  max_na = 1,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

a character vector of all column names used to compute summary score of fc_p_vs__supp.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_as__safe *Compute "Activity Space [Youth] (Safety): Mean"*

Description

Computes the summary score fc_y_as__safe_mean (Activity Space [Youth] (Safety): Mean)

- *Summarized variables:*
  - fc_y_as__safe_001a
  - fc_y_as__safe_001b
  - fc_y_as__safe_001c
- *Excluded values:* none
- *Validation criterion:* none of 3 items missing

Usage

```
vars_fc_y_as__safe

compute_fc_y_as__safe_mean(
  data,
  name = "fc_y_as__safe_mean",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_as__safe is a character vector of all column names used to compute summary score of fc_y_as__safe.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_crpbi__cg1 *Compute "Children's Report of Parental Behavioral Inventory [Youth] (Caregiver A): Mean"*

Description

Computes the summary score fc_y_crpbi__cg1_mean (Children's Report of Parental Behavioral Inventory [Youth] (Caregiver A): Mean)

- *Summarized variables:*
  - fc_y_crpbi__cg1_002
  - fc_y_crpbi__cg1_003
  - fc_y_crpbi__cg1_004
  - fc_y_crpbi__cg1_005
  - fc_y_crpbi__cg1_006
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_y_crpbi__cg1

compute_fc_y_crpbi__cg1_mean(
  data,
  name = "fc_y_crpbi__cg1_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_crpbi__cg1 is a character vector of all column names used to compute summary score of fc_y_crpbi__cg1.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_crpbi__cg2 *Compute "Children's Report of Parental Behavioral Inventory [Youth] (Caregiver B): Mean"*

Description

Computes the summary score fc_y_crpbi__cg2_mean (Children's Report of Parental Behavioral Inventory [Youth] (Caregiver B): Mean)

- *Summarized variables:*
  - fc_y_crpbi__cg2_002
  - fc_y_crpbi__cg2_003
  - fc_y_crpbi__cg2_004
  - fc_y_crpbi__cg2_005
  - fc_y_crpbi__cg2_006
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_y_crpbi__cg2

compute_fc_y_crpbi__cg2_mean(
  data,
  name = "fc_y_crpbi__cg2_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_crpbi__cg2 is a character vector of all column names used to compute summary score of fc_y_crpbi__cg2.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_eut__ethn *Compute "Experiences with Unfair Treatment [Youth] (Ethnicity): Mean"*

Description

Computes the summary score fc_y_eut__ethn_mean (Experiences with Unfair Treatment [Youth] (Ethnicity): Mean)

- *Summarized variables:*
  - fc_y_eut__ethn_001a
  - fc_y_eut__ethn_001b
  - fc_y_eut__ethn_001c/fc_y_eut__ethn_001c__v01
  - fc_y_eut__ethn_001d (only from event "ses-06A" onwards)
  - fc_y_eut__ethn_002
  - fc_y_eut__ethn_003a/fc_y_eut__ethn_003a__v01
  - fc_y_eut__ethn_003b/fc_y_eut__ethn_003b__v01

  - fc_y_eut__ethn_003c/fc_y_eut__ethn_003c__v01
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:*
  - before event ses-06A: none of 7 items missing
  - starting at event ses-06A: maximally 1 of 8 items missing

Usage

```
vars_fc_y_eut__ethn

compute_fc_y_eut__ethn_mean(data, name = "fc_y_eut__ethn_mean", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_eut__ethn is a character vector of all column names used to compute summary score of fc_y_eut__ethn.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_fes__cohes *Compute "Family Environment Scale [Youth] (Cohesion): Mean"*

Description

Computes the summary score fc_y_fes__cohes_mean (Family Environment Scale [Youth] (Cohesion): Mean)

- *Summarized variables:*
  - fc_y_fes__cohes_001
  - fc_y_fes__cohes_002
  - fc_y_fes__cohes_003
  - fc_y_fes__cohes_004
  - fc_y_fes__cohes_005

  - fc_y_fes__cohes_006
  - fc_y_fes__cohes_007
  - fc_y_fes__cohes_008
  - fc_y_fes__cohes_009

- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
vars_fc_y_fes__cohes

compute_fc_y_fes__cohes_mean(
  data,
  name = "fc_y_fes__cohes_mean",
  max_na = 1,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_fes__cohes is a character vector of all column names used to compute summary score of fc_y_fes__cohes.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_y_fes__confl` *Compute "Family Environment Scale [Youth] (Conflict): Mean"*

Description

Computes the summary score `fc_y_fes__confl_mean` (Family Environment Scale [Youth] (Conflict): Mean)

- *Summarized variables:*
  - `fc_y_fes__confl_001`
  - `fc_y_fes__confl_002`
  - `fc_y_fes__confl_003`
  - `fc_y_fes__confl_004`
  - `fc_y_fes__confl_005`
  - `fc_y_fes__confl_006`
  - `fc_y_fes__confl_007`
  - `fc_y_fes__confl_008`
  - `fc_y_fes__confl_009`
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
vars_fc_y_fes__confl

compute_fc_y_fes__confl_mean(
  data,
  name = "fc_y_fes__confl_mean",
  max_na = 1,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_y_fes__confl is a character vector of all column names used to compute summary score of `fc_y_fes__confl`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_y_lone` *Compute "UCLA Loneliness Scale [Youth]: Mean"*

Description

Computes the summary score `fc_y_lone_mean` (UCLA Loneliness Scale [Youth]: Mean)

- *Summarized variables:*
  - `fc_y_lone_001`
  - `fc_y_lone_002`
  - `fc_y_lone_003`
  - `fc_y_lone_004`
  - `fc_y_lone_005`
  - `fc_y_lone_006`
  - `fc_y_lone_007`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_fc_y_lone

compute_fc_y_lone_mean(
  data,
  name = "fc_y_lone_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_y_lone is a character vector of all column names used to compute summary score of `fc_y_lone`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_y_meim` *Compute "The Multigroup Ethnic Identity Measure-Revised [Youth]: Mean"*

Description

Computes the summary score `fc_y_meim_mean` (The Multigroup Ethnic Identity Measure-Revised [Youth]: Mean)

- *Summarized variables:*
  - `fc_y_meim__commattach_001`
  - `fc_y_meim__commattach_002`
  - `fc_y_meim__commattach_003`
  - `fc_y_meim__explor_001`
  - `fc_y_meim__explor_002`
  - `fc_y_meim__explor_003`
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_fc_y_meim

compute_fc_y_meim_mean(
  data,
  name = "fc_y_meim_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_y_meim is a character vector of all column names used to compute summary score of `fc_y_meim`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_y_meim__commattach`

Compute "The Multigroup Ethnic Identity Measure-Revised [Youth] (Commitment and attachment): Mean"

Description

Computes the summary score `fc_y_meim__commattach_mean` (The Multigroup Ethnic Identity Measure-Revised [Youth] (Commitment and attachment): Mean)

- *Summarized variables:*
  - `fc_y_meim__commattach_001`
  - `fc_y_meim__commattach_002`
  - `fc_y_meim__commattach_003`
- *Excluded values:* none
- *Validation criterion:* none of 3 items missing

Usage

```
vars_fc_y_meim__commattach

compute_fc_y_meim__commattach_mean(
  data,
  name = "fc_y_meim__commattach_mean",
  max_na = 0,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 0).
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_y_meim__commattach is a character vector of all column names used to compute summary score of `fc_y_meim__commattach`.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_meim__explor

Compute "The Multigroup Ethnic Identity Measure-Revised [Youth] (Exploration): Mean"

Description

Computes the summary score `fc_y_meim__explor_mean` (The Multigroup Ethnic Identity Measure-Revised [Youth] (Exploration): Mean)

- *Summarized variables:*
  - `fc_y_meim__explor_001`
  - `fc_y_meim__explor_002`
  - `fc_y_meim__explor_003`
- *Excluded values:* none
- *Validation criterion:* none of 3 items missing

Usage

```
vars_fc_y_meim__explor

compute_fc_y_meim__explor_mean(
  data,
  name = "fc_y_meim__explor_mean",
  max_na = 0,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 0).
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_y_meim__explor is a character vector of all column names used to compute summary score of `fc_y_meim__explor`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_y_mnbs` *Compute "Multidimensional Neglectful Behavior Scale [Youth]: Mean"*

Description

Computes the summary score `fc_y_mnbs_mean` (Multidimensional Neglectful Behavior Scale [Youth]: Mean)

- *Summarized variables:*
  - `fc_y_mnbs__edusupp_001`
  - `fc_y_mnbs__edusupp_002`
  - `fc_y_mnbs__edusupp_003`
  - `fc_y_mnbs__superv_001`
  - `fc_y_mnbs__superv_002`
  - `fc_y_mnbs__superv_003`
  - `fc_y_mnbs__superv_004`
  - `fc_y_mnbs__superv_005`
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_fc_y_mnbs

compute_fc_y_mnbs_mean(
  data,
  name = "fc_y_mnbs_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_mnbs is a character vector of all column names used to compute summary score of fc_y_mnbs.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_mnbs__edusupp

Compute "Multidimensional Neglectful Behavior Scale [Youth] (Education support): Mean"

Description

Computes the summary score fc_y_mnbs__edusupp_mean (Multidimensional Neglectful Behavior Scale [Youth] (Education support): Mean)

- *Summarized variables:*
  - fc_y_mnbs__edusupp_001
  - fc_y_mnbs__edusupp_002
  - fc_y_mnbs__edusupp_003
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
vars_fc_y_mnbs__edusupp

compute_fc_y_mnbs__edusupp_mean(
  data,
  name = "fc_y_mnbs__edusupp_mean",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_mnbs__edusupp is a character vector of all column names used to compute summary score of fc_y_mnbs__edusupp.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_mnbs__superv

Compute "Multidimensional Neglectful Behavior Scale [Youth] (Supervision): Mean"

Description

Computes the summary score fc_y_mnbs__superv_mean (Multidimensional Neglectful Behavior Scale [Youth] (Supervision): Mean)

- *Summarized variables:*
  - fc_y_mnbs__superv_001
  - fc_y_mnbs__superv_002
  - fc_y_mnbs__superv_003
  - fc_y_mnbs__superv_004
  - fc_y_mnbs__superv_005
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_y_mnbs__superv

compute_fc_y_mnbs__superv_mean(
  data,
  name = "fc_y_mnbs__superv_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_mnbs__superv is a character vector of all column names used to compute summary score of fc_y_mnbs__superv.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_naa *Compute "Native American Acculturation [Youth]: Mean"*

Description

Computes the summary score fc_y_naa_mean (Native American Acculturation [Youth]: Mean)

- *Summarized variables:*
  - fc_y_naa_001
  - fc_y_naa_002
  - fc_y_naa_003
- *Excluded values:*
  - 999
- *Validation criterion:* maximally 0 of 3 items missing

Usage

```
vars_fc_y_naa

compute_fc_y_naa_mean(
  data,
  name = "fc_y_naa_mean",
  max_na = 0,
  exclude = c("999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_naa is a character vector of all column names used to compute summary score of fc_y_naa.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_pm *Compute "Parental Monitoring [Youth]: Mean"*

Description

Computes the summary score fc_y_pm_mean (Parental Monitoring [Youth]: Mean)

- *Summarized variables:*
  - fc_y_pm_001
  - fc_y_pm_002
  - fc_y_pm_003
  - fc_y_pm_004
  - fc_y_pm_005
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_y_pm

compute_fc_y_pm_mean(data, name = "fc_y_pm_mean", max_na = 1, combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_pm is a character vector of all column names used to compute summary score of `fc_y_pm`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_y_pnh` *Compute "Peer Network Health [Youth]: Sum"*

Description

Computes the summary score `fc_y_pnh_sum` (Peer Network Health [Youth]: Sum)

- *Summarized variables:*
  - `fc_y_pnh_001`
  - `fc_y_pnh_002`
  - `fc_y_pnh_002__01`
  - `fc_y_pnh_003`
  - `fc_y_pnh_003__01`
- *Excluded values:*
  - 777
- *Validation criterion:* none of 5 items missing
- *Notes:*
  - `fc_y_pnh_001` is scored: No = 0; Yes = 3
  - `fc_y_pnh_002`/`fc_y_pnh_003` are scored: No = 0; Yes = 2
  - `fc_y_pnh_002__01`/`fc_y_pnh_003__01` are scored with their original values (1 through 10)

Usage

```
vars_fc_y_pnh

compute_fc_y_pnh_sum(
  data,
  name = "fc_y_pnh_sum",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_pnh is a character vector of all column names used to compute summary score of fc_y_pnh.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_psb *Compute "Prosocial Behavior [Youth]: Mean"*

Description

Computes the summary score fc_y_psb_mean (Prosocial Behavior [Youth]: Mean)

- *Summarized variables:*
  - fc_y_psb_001
  - fc_y_psb_002
  - fc_y_psb_003
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
vars_fc_y_psb

compute_fc_y_psb_mean(
  data,
  name = "fc_y_psb_mean",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_psb is a character vector of all column names used to compute summary score of fc_y_psb.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_rpi *Compute "Resistance to Peer Influence [Youth]: Mean"*

Description

Computes the summary score fc_y_rpi_mean (Resistance to Peer Influence [Youth]: Mean)

- *Summarized variables:*
  - fc_y_rpi_001
  - fc_y_rpi_002
  - fc_y_rpi_003
  - fc_y_rpi_004
  - fc_y_rpi_005
  - fc_y_rpi_006
  - fc_y_rpi_007
  - fc_y_rpi_008
  - fc_y_rpi_009
  - fc_y_rpi_010
- *Excluded values:* none
- *Validation criterion:* maximally 3 of 10 items missing
- *Note:* The following variables are reverse coded before computing the summary score:
  - fc_y_rpi_002
  - fc_y_rpi_006
  - fc_y_rpi_010

Usage

```
vars_fc_y_rpi

compute_fc_y_rpi_mean(data, name = "fc_y_rpi_mean", max_na = 3, combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 3).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_rpi is a character vector of all column names used to compute summary score of fc_y_rpi.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_srpf__dis *Compute "School Risk & Protective Factors [Youth] (School disengagement): Mean"*

Description

Computes the summary score fc_y_srpf__dis_mean (School Risk & Protective Factors [Youth] (School disengagement): Mean)

- *Summarized variables:*
  - fc_y_srpf__dis_001
  - fc_y_srpf__dis_002
- *Excluded values:*
  - 777
- *Validation criterion:* none of 2 items missing

Usage

```
vars_fc_y_srpf__dis

compute_fc_y_srpf__dis_mean(
  data,
  name = "fc_y_srpf__dis_mean",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_srpf__dis is a character vector of all column names used to compute summary score of fc_y_srpf__dis.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_srpf__env *Compute "School Risk & Protective Factors [Youth] (School environment): Mean"*

Description

Computes the summary score fc_y_srpf__env_mean (School Risk & Protective Factors [Youth] (School environment): Mean)

- *Summarized variables:*
  - fc_y_srpf__env_001
  - fc_y_srpf__env_002
  - fc_y_srpf__env_003
  - fc_y_srpf__env_004
  - fc_y_srpf__env_005

  - fc_y_srpf__env_006

- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_fc_y_srpf__env

compute_fc_y_srpf__env_mean(
  data,
  name = "fc_y_srpf__env_mean",
  max_na = 1,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_srpf__env is a character vector of all column names used to compute summary score of fc_y_srpf__env.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_srpf__involv

Compute "School Risk & Protective Factors [Youth] (School involvement): Mean"

Description

Computes the summary score `fc_y_srpf__involv_mean` (School Risk & Protective Factors [Youth] (School involvement): Mean)

- *Summarized variables:*
  - `fc_y_srpf__involv_001`
  - `fc_y_srpf__involv_002`
  - `fc_y_srpf__involv_003`
  - `fc_y_srpf__involv_004`
- *Excluded values:*
  - 777
- *Validation criterion:* none of 4 items missing

Usage

```
vars_fc_y_srpf__involv

compute_fc_y_srpf__involv_mean(
  data,
  name = "fc_y_srpf__involv_mean",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 0).
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_y_srpf__involv is a character vector of all column names used to compute summary score of `fc_y_srpf__involv`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_y_vs__famil` *Compute "Values Scale [Youth] (Familism): Mean (Subscales: supp, ref, obl)"*

Description

Computes the summary score `fc_y_vs__famil_mean` (Values Scale [Youth] (Familism): Mean (Subscales: supp, ref, obl))

- *Summarized variables:*
  - `fc_y_vs__supp_001`
  - `fc_y_vs__supp_002`
  - `fc_y_vs__supp_003`
  - `fc_y_vs__supp_004`
  - `fc_y_vs__supp_005`
  - `fc_y_vs__supp_006`
  - `fc_y_vs__ref_001`
  - `fc_y_vs__ref_002`
  - `fc_y_vs__ref_003`
  - `fc_y_vs__ref_004`
  - `fc_y_vs__ref_005`
  - `fc_y_vs__obl_001`
  - `fc_y_vs__obl_002`
  - `fc_y_vs__obl_003`
  - `fc_y_vs__obl_004`
  - `fc_y_vs__obl_005`
- *Excluded values:*
  - 777
- *Validation criterion:*
  - maximally 3 of 16 items missing
  - all sub-scales can be calculated

Usage

```
vars_fc_y_vs__famil

compute_fc_y_vs__famil_mean(
  data,
  name = "fc_y_vs__famil_mean",
  max_na = 3,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric vector of positive whole number. Number of missing items allowed (Default: 3).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

a character vector of all column names used to compute summary score of fc_y_vs__famil_mean and fc_y_vs__famil_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_vs__famil__v01

Compute "Values Scale [Youth] (Familism): Mean - Version 1 (Subscales: supp, ref)"

Description

Computes the summary score fc_y_vs__famil_mean__v01 (Values Scale [Youth] (Familism): Mean - Version 1 (Subscales: supp, ref))

- *Summarized variables:*
  - fc_y_vs__supp_001
  - fc_y_vs__supp_002
  - fc_y_vs__supp_003
  - fc_y_vs__supp_004
  - fc_y_vs__supp_005
  - fc_y_vs__supp_006
  - fc_y_vs__ref_001
  - fc_y_vs__ref_002
  - fc_y_vs__ref_003
  - fc_y_vs__ref_004
  - fc_y_vs__ref_005
- *Excluded values:*
  - 777
- *Validation criterion:*
  - maximally 2 of 11 items missing
  - all sub-scales can be calculated

Usage

```
vars_fc_y_vs__famil__v01

compute_fc_y_vs__famil_mean__v01(
  data,
  name = "fc_y_vs__famil_mean__v01",
  max_na = 2,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric vector of positive whole number. Number of missing items allowed (Default: 2).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

a character vector of all column names used to compute summary score of fc_y_vs__famil_mean__v01 and fc_y_vs__famil_nm__v01.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_fc_y_vs__famil_mean()

---

vars_fc_y_vs__indselfrel

Compute "Values Scale [Youth] (Independence and self-reliance): Mean"

Description

Computes the summary score fc_y_vs__indselfrel_mean (Values Scale [Youth] (Independence and self-reliance): Mean)

- *Summarized variables:*
  - fc_y_vs__indselfrel_001

  - fc_y_vs__indselfrel_002
  - fc_y_vs__indselfrel_003
  - fc_y_vs__indselfrel_004
  - fc_y_vs__indselfrel_005

- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_y_vs__indselfrel

compute_fc_y_vs__indselfrel_mean(
  data,
  name = "fc_y_vs__indselfrel_mean",
  max_na = 1,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_vs__indselfrel is a character vector of all column names used to compute summary score of fc_y_vs__indselfrel.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_fc_y_vs__obl *Compute "Values Scale [Youth] (Family obligation): Mean"*

Description

Computes the summary score fc_y_vs__obl_mean (Values Scale [Youth] (Family obligation): Mean)

- *Summarized variables:*
  - fc_y_vs__obl_001
  - fc_y_vs__obl_002
  - fc_y_vs__obl_003
  - fc_y_vs__obl_004
  - fc_y_vs__obl_005
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_y_vs__obl

compute_fc_y_vs__obl_mean(
  data,
  name = "fc_y_vs__obl_mean",
  max_na = 1,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_vs__obl is a character vector of all column names used to compute summary score of fc_y_vs__obl.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_y_vs__ref` *Compute "Values Scale [Youth] (Family as referent): Mean"*

Description

Computes the summary score `fc_y_vs__ref_mean` (Values Scale [Youth] (Family as referent): Mean)

- *Summarized variables:*
  - `fc_y_vs__ref_001`
  - `fc_y_vs__ref_002`
  - `fc_y_vs__ref_003`
  - `fc_y_vs__ref_004`
  - `fc_y_vs__ref_005`
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_fc_y_vs__ref

compute_fc_y_vs__ref_mean(
  data,
  name = "fc_y_vs__ref_mean",
  max_na = 1,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score. Default is the name in the description.
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE`, the summary score is appended to the input data frame. If `FALSE`, the summary score is returned as a separate data frame. Default is `TRUE`.

Format

vars_fc_y_vs__ref is a character vector of all column names used to compute summary score of `fc_y_vs__ref`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_fc_y_vs__relig` *Compute "Values Scale [Youth] (Religion): Mean"*

Description

Computes the summary score `fc_y_vs__relig_mean` (Values Scale [Youth] (Religion): Mean)

- *Summarized variables:*
  - `fc_y_vs__relig_001`
  - `fc_y_vs__relig_002`
  - `fc_y_vs__relig_003`
  - `fc_y_vs__relig_004`
  - `fc_y_vs__relig_005`
  - `fc_y_vs__relig_006`
  - `fc_y_vs__relig_007`
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_fc_y_vs__relig

compute_fc_y_vs__relig_mean(
  data,
  name = "fc_y_vs__relig_mean",
  max_na = 1,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_vs__relig is a character vector of all column names used to compute summary score of fc_y_vs__relig.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_vs__supp *Compute "Values Scale [Youth] (Family support): Mean"*

Description

Computes the summary score fc_y_vs__supp_mean (Values Scale [Youth] (Family support): Mean)

- *Summarized variables:*
  - fc_y_vs__supp_001
  - fc_y_vs__supp_002
  - fc_y_vs__supp_003
  - fc_y_vs__supp_004
  - fc_y_vs__supp_005
  - fc_y_vs__supp_006
- *Excluded values:*
  - 777
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_fc_y_vs__supp

compute_fc_y_vs__supp_mean(
  data,
  name = "fc_y_vs__supp_mean",
  max_na = 1,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_vs__supp is a character vector of all column names used to compute summary score of fc_y_vs__supp.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_fc_y_wpss *Compute "Wills Problem Solving Scale [Youth]: Mean"*

Description

Computes the summary score fc_y_wpss_mean (Wills Problem Solving Scale [Youth]: Mean)

- *Summarized variables:*
  - fc_y_wpss_001
  - fc_y_wpss_002
  - fc_y_wpss_003
  - fc_y_wpss_004
  - fc_y_wpss_005
  - fc_y_wpss_006
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_fc_y_wpss

compute_fc_y_wpss_mean(
  data,
  name = "fc_y_wpss_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score. Default is the name in the description.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the summary score is appended to the input data frame. If FALSE, the summary score is returned as a separate data frame. Default is TRUE.

Format

vars_fc_y_wpss is a character vector of all column names used to compute summary score of fc_y_wpss.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_abcl *Compute "Adult Behavior Checklist [Parent]: Number missing"*

Description

Computes the summary score mh_p_abcl_nm Adult Behavior Checklist [Parent]: Number missing

- *Summarized variables:*
  - mh_p_abcl__rule_001
  - mh_p_abcl__attn__adhd_002
  - mh_p_abcl__tho_001
  - mh_p_abcl__othpr__adhd_001
  - mh_p_abcl__anxdep__dep_001
  - mh_p_abcl__aggr__antsoc_003
  - mh_p_abcl__tho__dep_001
  - mh_p_abcl__othpr__antsoc_001
  - mh_p_abcl__tho_002
  - mh_p_abcl__aggr_001
  - mh_p_abcl__aggr__antsoc_006
  - mh_p_abcl__tho_003
  - mh_p_abcl__tho_004
  - mh_p_abcl__tho_006
  - mh_p_abcl__rule_002
  - mh_p_abcl__tho__dep_002
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__aggr__antsoc_008

- mh_p_abcl__anxdep__dep_004
- mh_p_abcl__aggr__adhd_001
- mh_p_abcl__attn__adhd_001
- mh_p_abcl__attn__adhd_003
- mh_p_abcl__attn__adhd_004
- mh_p_abcl__attn__adhd_005
- mh_p_abcl__attn__adhd_006
- mh_p_abcl__attn__adhd_007
- mh_p_abcl__othpr__adhd_002
- mh_p_abcl__othpr__adhd_003
- mh_p_abcl__othpr__adhd_004
- mh_p_abcl__rule__adhd_001
- mh_p_abcl__aggr__antsoc_001
- mh_p_abcl__aggr__antsoc_002
- mh_p_abcl__aggr__antsoc_004
- mh_p_abcl__aggr__antsoc_005
- mh_p_abcl__aggr__antsoc_007
- mh_p_abcl__attn__antsoc_001
- mh_p_abcl__othpr__antsoc_002
- mh_p_abcl__rule__antsoc_001
- mh_p_abcl__rule__antsoc_002
- mh_p_abcl__rule__antsoc_003
- mh_p_abcl__rule__antsoc_004
- mh_p_abcl__rule__antsoc_005
- mh_p_abcl__rule__antsoc_006
- mh_p_abcl__rule__antsoc_008
- mh_p_abcl__rule__antsoc_009
- mh_p_abcl__anxdep__anx_001
- mh_p_abcl__anxdep__anx_002
- mh_p_abcl__anxdep__anx_003
- mh_p_abcl__othpr__anx_001
- mh_p_abcl__othpr__anx_002
- mh_p_abcl__othpr__anx_003
- mh_p_abcl__anxdep__avoid_001
- mh_p_abcl__anxdep__avoid_002
- mh_p_abcl__othpr__avoid_001
- mh_p_abcl__wthdr__avoid_001
- mh_p_abcl__wthdr__avoid_002
- mh_p_abcl__wthdr__avoid_003
- mh_p_abcl__wthdr__avoid_004
- mh_p_abcl__anxdep__dep_002
- mh_p_abcl__anxdep__dep_003

- mh_p_abcl__anxdep__dep_005
- mh_p_abcl__attn__dep_001
- mh_p_abcl__attn__dep_002
- mh_p_abcl__attn__dep_003
- mh_p_abcl__othpr__dep_001
- mh_p_abcl__othpr__dep_002
- mh_p_abcl__othpr__dep_003
- mh_p_abcl__som__dep_001
- mh_p_abcl__wthdr__dep_001
- mh_p_abcl__som__somat_001
- mh_p_abcl__som__somat_002
- mh_p_abcl__som__somat_003
- mh_p_abcl__som__somat_004
- mh_p_abcl__som__somat_005
- mh_p_abcl__som__somat_006
- mh_p_abcl__som__somat_007
- mh_p_abcl__aggr_002
- mh_p_abcl__aggr_003
- mh_p_abcl__aggr_004
- mh_p_abcl__aggr_005
- mh_p_abcl__aggr_006
- mh_p_abcl__aggr_007
- mh_p_abcl__anxdep_001
- mh_p_abcl__anxdep_002
- mh_p_abcl__anxdep_003
- mh_p_abcl__anxdep_004
- mh_p_abcl__attn_001
- mh_p_abcl__attn_002
- mh_p_abcl__attn_003
- mh_p_abcl__attn_004
- mh_p_abcl__attn_005
- mh_p_abcl__attn_006
- mh_p_abcl__rule_003
- mh_p_abcl__intru_001
- mh_p_abcl__intru_002
- mh_p_abcl__intru_003
- mh_p_abcl__intru_004
- mh_p_abcl__intru_005
- mh_p_abcl__intru_006
- mh_p_abcl__wthdr_001
- mh_p_abcl__wthdr_002
- mh_p_abcl__wthdr_003

  - mh_p_abcl__wthdr_004
  - mh_p_abcl__som_001
  - mh_p_abcl__othpr_001
  - mh_p_abcl__othpr_002
  - mh_p_abcl__othpr_003
  - mh_p_abcl__othpr_004
  - mh_p_abcl__othpr_005
  - mh_p_abcl__othpr_006
  - mh_p_abcl__othpr_007
  - mh_p_abcl__othpr_008
  - mh_p_abcl__othpr_009
  - mh_p_abcl__othpr_010
  - mh_p_abcl__othpr_011
  - mh_p_abcl__othpr_012
  - mh_p_abcl__tho_005
  - mh_p_abcl__tho_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl

compute_mh_p_abcl_nm(
  data,
  name = "mh_p_abcl_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl is vector of all column names used to compute summary score of mh_p_abcl scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl_nm(data) |>
  select(
    any_of(c("mh_p_abcl_nm", vars_mh_p_abcl))
  )

## End(Not run)
```

---

vars_mh_p_abcl__afs__frnd *Compute "Adult Behavior Checklist [Parent] (Adaptive Functioning Scale - Friends): Number missing"*

Description

Computes the summary score mh_p_abcl__afs__frnd_nm Adult Behavior Checklist [Parent] (Adaptive Functioning Scale - Friends): Number missing

- *Summarized variables:*
  - mh_p_abcl__frnd_001
  - mh_p_abcl__frnd_002
  - mh_p_abcl__frnd_003
  - mh_p_abcl__frnd_004
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__afs__frnd

compute_mh_p_abcl__afs__frnd_nm(
  data,
  name = "mh_p_abcl__afs__frnd_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__afs__frnd is vector of all column names used to compute summary score of mh_p_abcl__afs__frnd scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__afs__frnd_nm(data) |>
  select(
    any_of(c("mh_p_abcl__afs__frnd_nm", vars_mh_p_abcl__afs__frnd))
  )

## End(Not run)
```

---

vars_mh_p_abcl__cg2 *Compute "Adult Behavior Checklist [Parent] Sex Assignment"*

Description

Computes the summary score mh_p_abcl__cg2_sex Adult Behavior Checklist [Parent] Sex Assignment

- *Summarized variables:*
  - mh_p_abcl__cg2_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__cg2

compute_mh_p_abcl__cg2_sex(data, name = "mh_p_abcl__cg2_sex", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__cg2 is vector of all column names used to compute summary score of mh_p_abcl__cg2 scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__cg2_sex(data) |>
  select(
    any_of(c("mh_p_abcl__cg2_sex", vars_mh_p_abcl__cg2))
  )

## End(Not run)
```

---

vars_mh_p_abcl__critic

Compute "Adult Behavior Checklist [Parent] (Critical items): Number missing"

Description

Computes the summary score mh_p_abcl__critic_nm Adult Behavior Checklist [Parent] (Critical items): Number missing

- *Summarized variables:*
  - mh_p_abcl__rule_001
  - mh_p_abcl__attn__adhd_002
  - mh_p_abcl__tho_001
  - mh_p_abcl__othpr__adhd_001
  - mh_p_abcl__anxdep__dep_001
  - mh_p_abcl__aggr__antsoc_003
  - mh_p_abcl__tho__dep_001
  - mh_p_abcl__othpr__antsoc_001

- mh_p_abcl__tho_002
- mh_p_abcl__aggr_001
- mh_p_abcl__aggr__antsoc_006
- mh_p_abcl__tho_003
- mh_p_abcl__tho_004
- mh_p_abcl__tho_006
- mh_p_abcl__rule_002
- mh_p_abcl__tho__dep_002
- mh_p_abcl__rule__antsoc_007
- mh_p_abcl__aggr__antsoc_008
- mh_p_abcl__anxdep__dep_004

Usage

```
vars_mh_p_abcl__critic

compute_mh_p_abcl__critic_nm(
  data,
  name = "mh_p_abcl__critic_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__critic is vector of all column names used to compute summary score of mh_p_abcl__critic scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__critic_nm(data) |>
  select(
    any_of(c("mh_p_abcl__critic_nm", vars_mh_p_abcl__critic))
```

```
  )

## End(Not run)
```

`vars_mh_p_abcl__dsm__adhd`

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): Number missing"

Description

Computes the summary score `mh_p_abcl__dsm__adhd_nm` Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): Number missing

- *Summarized variables:*
  - `mh_p_abcl__aggr__adhd_001`
  - `mh_p_abcl__attn__adhd_001`
  - `mh_p_abcl__attn__adhd_002`
  - `mh_p_abcl__attn__adhd_003`
  - `mh_p_abcl__attn__adhd_004`
  - `mh_p_abcl__attn__adhd_005`
  - `mh_p_abcl__attn__adhd_006`
  - `mh_p_abcl__attn__adhd_007`
  - `mh_p_abcl__othpr__adhd_001`
  - `mh_p_abcl__othpr__adhd_002`
  - `mh_p_abcl__othpr__adhd_003`
  - `mh_p_abcl__othpr__adhd_004`
  - `mh_p_abcl__rule__adhd_001`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__dsm__adhd

compute_mh_p_abcl__dsm__adhd_nm(
  data,
  name = "mh_p_abcl__dsm__adhd_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__dsm__adhd is vector of all column names used to compute summary score of mh_p_abcl__dsm__adhd scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__dsm__adhd_nm(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__adhd_nm", vars_mh_p_abcl__dsm__adhd))
  )

## End(Not run)
```

---

vars_mh_p_abcl__dsm__antsoc

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): Number missing"

Description

Computes the summary score mh_p_abcl__dsm__antsoc_nm Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): Number missing

- *Summarized variables:*
  - mh_p_abcl__aggr__antsoc_001
  - mh_p_abcl__aggr__antsoc_002
  - mh_p_abcl__aggr__antsoc_003
  - mh_p_abcl__aggr__antsoc_004
  - mh_p_abcl__aggr__antsoc_005
  - mh_p_abcl__aggr__antsoc_006
  - mh_p_abcl__aggr__antsoc_007

  - mh_p_abcl__aggr__antsoc_008
  - mh_p_abcl__attn__antsoc_001
  - mh_p_abcl__othpr__antsoc_001
  - mh_p_abcl__othpr__antsoc_002
  - mh_p_abcl__rule__antsoc_001
  - mh_p_abcl__rule__antsoc_002
  - mh_p_abcl__rule__antsoc_003
  - mh_p_abcl__rule__antsoc_004
  - mh_p_abcl__rule__antsoc_005
  - mh_p_abcl__rule__antsoc_006
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__rule__antsoc_008
  - mh_p_abcl__rule__antsoc_009
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__dsm__antsoc

compute_mh_p_abcl__dsm__antsoc_nm(
  data,
  name = "mh_p_abcl__dsm__antsoc_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__dsm__antsoc is vector of all column names used to compute summary score of mh_p_abcl__dsm__antsoc scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__dsm__antsoc_nm(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__antsoc_nm", vars_mh_p_abcl__dsm__antsoc))
  )

## End(Not run)
```

`vars_mh_p_abcl__dsm__anx`

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety problems): Number missing"

Description

Computes the summary score `mh_p_abcl__dsm__anx_nm` Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety problems): Number missing

- *Summarized variables:*
  - `mh_p_abcl__anxdep__anx_001`
  - `mh_p_abcl__anxdep__anx_002`
  - `mh_p_abcl__anxdep__anx_003`
  - `mh_p_abcl__othpr__anx_001`
  - `mh_p_abcl__othpr__anx_002`
  - `mh_p_abcl__othpr__anx_003`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__dsm__anx

compute_mh_p_abcl__dsm__anx_nm(
  data,
  name = "mh_p_abcl__dsm__anx_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__dsm__anx is vector of all column names used to compute summary score of mh_p_abcl__dsm__anx scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__dsm__anx_nm(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__anx_nm", vars_mh_p_abcl__dsm__anx))
  )

## End(Not run)
```

---

vars_mh_p_abcl__dsm__avoid

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): Number missing"

Description

Computes the summary score mh_p_abcl__dsm__avoid_nm Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): Number missing

- *Summarized variables:*
  - mh_p_abcl__anxdep__avoid_001
  - mh_p_abcl__anxdep__avoid_002
  - mh_p_abcl__othpr__avoid_001
  - mh_p_abcl__wthdr__avoid_001
  - mh_p_abcl__wthdr__avoid_002
  - mh_p_abcl__wthdr__avoid_003
  - mh_p_abcl__wthdr__avoid_004
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__dsm__avoid

compute_mh_p_abcl__dsm__avoid_nm(
  data,
  name = "mh_p_abcl__dsm__avoid_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__dsm__avoid is vector of all column names used to compute summary score of mh_p_abcl__dsm__avoid scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__dsm__avoid_nm(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__avoid_nm", vars_mh_p_abcl__dsm__avoid))
  )

## End(Not run)
```

---

vars_mh_p_abcl__dsm__dep

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): Number missing"

Description

Computes the summary score mh_p_abcl__dsm__dep_nm Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): Number missing

- *Summarized variables:*
  - mh_p_abcl__anxdep__dep_001
  - mh_p_abcl__anxdep__dep_002
  - mh_p_abcl__anxdep__dep_003
  - mh_p_abcl__anxdep__dep_004
  - mh_p_abcl__anxdep__dep_005
  - mh_p_abcl__attn__dep_001
  - mh_p_abcl__attn__dep_002
  - mh_p_abcl__attn__dep_003
  - mh_p_abcl__othpr__dep_001
  - mh_p_abcl__othpr__dep_002
  - mh_p_abcl__othpr__dep_003
  - mh_p_abcl__som__dep_001
  - mh_p_abcl__tho__dep_001
  - mh_p_abcl__tho__dep_002
  - mh_p_abcl__wthdr__dep_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__dsm__dep

compute_mh_p_abcl__dsm__dep_nm(
  data,
  name = "mh_p_abcl__dsm__dep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__dsm__dep is vector of all column names used to compute summary score of mh_p_abcl__dsm__dep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__dsm__dep_nm(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__dep_nm", vars_mh_p_abcl__dsm__dep))
  )

## End(Not run)
```

---

vars_mh_p_abcl__dsm__somat

Compute "Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): Number missing"

Description

Computes the summary score mh_p_abcl__dsm__somat_nm Adult Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): Number missing

- *Summarized variables:*
  - mh_p_abcl__som__somat_001
  - mh_p_abcl__som__somat_002
  - mh_p_abcl__som__somat_003
  - mh_p_abcl__som__somat_004
  - mh_p_abcl__som__somat_005
  - mh_p_abcl__som__somat_006
  - mh_p_abcl__som__somat_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__dsm__somat

compute_mh_p_abcl__dsm__somat_nm(
  data,
  name = "mh_p_abcl__dsm__somat_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__dsm__somat is vector of all column names used to compute summary score of mh_p_abcl__dsm__somat scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__dsm__somat_nm(data) |>
  select(
    any_of(c("mh_p_abcl__dsm__somat_nm", vars_mh_p_abcl__dsm__somat))
  )

## End(Not run)
```

---

vars_mh_p_abcl__su *Compute "Adult Behavior Checklist [Parent] (Substance use): Number missing"*

Description

Computes the summary score mh_p_abcl__su_nm Adult Behavior Checklist [Parent] (Substance use): Number missing

- *Summarized variables:*
  - mh_p_abcl__drg_001
  - mh_p_abcl__drunk_001
  - mh_p_abcl__nic_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__su

compute_mh_p_abcl__su_nm(
  data,
  name = "mh_p_abcl__su_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__su is vector of all column names used to compute summary score of mh_p_abcl__su scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__su_nm(data) |>
  select(
    any_of(c("mh_p_abcl__su_nm", vars_mh_p_abcl__su))
```

```
  )

## End(Not run)
```

`vars_mh_p_abcl__su__drg` *Compute "Adult Behavior Checklist [Parent] (Days drug use): Number missing"*

Description

Computes the summary score `mh_p_abcl__su__drg_nm` Adult Behavior Checklist [Parent] (Days drug use): Number missing

- *Summarized variables:*
  - `mh_p_abcl__drg_001`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__su__drg

compute_mh_p_abcl__su__drg_nm(
  data,
  name = "mh_p_abcl__su__drg_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

`vars_mh_p_abcl__su__drg` is vector of all column names used to compute summary score of `mh_p_abcl__su__drg` scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__su__drg_nm(data) |>
  select(
    any_of(c("mh_p_abcl__su__drg_nm", vars_mh_p_abcl__su__drg))
  )

## End(Not run)
```

---

vars_mh_p_abcl__su__drunk

Compute "Adult Behavior Checklist [Parent] (Days Drunk): Number missing"

Description

Computes the summary score mh_p_abcl__su__drunk_nm Adult Behavior Checklist [Parent] (Days Drunk): Number missing

- *Summarized variables:*
  - mh_p_abcl__drunk_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__su__drunk

compute_mh_p_abcl__su__drunk_nm(
  data,
  name = "mh_p_abcl__su__drunk_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__su__drunk is vector of all column names used to compute summary score of mh_p_abcl__su__drunk scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__su__drunk_nm(data) |>
  select(
    any_of(c("mh_p_abcl__su__drunk_nm", vars_mh_p_abcl__su__drunk))
  )

## End(Not run)
```

---

vars_mh_p_abcl__su__nic

Compute "Adult Behavior Checklist [Parent] (Tobacco per day): Number missing"

Description

Computes the summary score mh_p_abcl__su__nic_nm Adult Behavior Checklist [Parent] (Tobacco per day): Number missing

- *Summarized variables:*
  - mh_p_abcl__nic_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__su__nic

compute_mh_p_abcl__su__nic_nm(
  data,
  name = "mh_p_abcl__su__nic_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__su__nic is vector of all column names used to compute summary score of mh_p_abcl__su__nic scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__su__nic_nm(data) |>
  select(
    any_of(c("mh_p_abcl__su__nic_nm", vars_mh_p_abcl__su__nic))
  )

## End(Not run)
```

---

vars_mh_p_abcl__synd__aggr

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): Number missing"

Description

Computes the summary score mh_p_abcl__synd__aggr_nm Adult Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): Number missing

- *Summarized variables:*
  - mh_p_abcl__aggr_001
  - mh_p_abcl__aggr_002
  - mh_p_abcl__aggr_003
  - mh_p_abcl__aggr_004
  - mh_p_abcl__aggr_005
  - mh_p_abcl__aggr_006
  - mh_p_abcl__aggr_007

  - mh_p_abcl__aggr__adhd_001
  - mh_p_abcl__aggr__antsoc_001
  - mh_p_abcl__aggr__antsoc_002
  - mh_p_abcl__aggr__antsoc_003
  - mh_p_abcl__aggr__antsoc_004
  - mh_p_abcl__aggr__antsoc_005
  - mh_p_abcl__aggr__antsoc_006
  - mh_p_abcl__aggr__antsoc_007
  - mh_p_abcl__aggr__antsoc_008
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__aggr

compute_mh_p_abcl__synd__aggr_nm(
  data,
  name = "mh_p_abcl__synd__aggr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__aggr is vector of all column names used to compute summary score of mh_p_abcl__synd__aggr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__aggr_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__aggr_nm", vars_mh_p_abcl__synd__aggr))
  )

## End(Not run)
```

---

vars_mh_p_abcl__synd__anxdep

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): Number missing"

Description

Computes the summary score mh_p_abcl__synd__anxdep_nm Adult Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): Number missing

- *Summarized variables:*
  - mh_p_abcl__anxdep_001
  - mh_p_abcl__anxdep_002
  - mh_p_abcl__anxdep_003
  - mh_p_abcl__anxdep_004
  - mh_p_abcl__anxdep__anx_001
  - mh_p_abcl__anxdep__anx_002
  - mh_p_abcl__anxdep__anx_003
  - mh_p_abcl__anxdep__avoid_001
  - mh_p_abcl__anxdep__avoid_002
  - mh_p_abcl__anxdep__dep_001
  - mh_p_abcl__anxdep__dep_002
  - mh_p_abcl__anxdep__dep_003
  - mh_p_abcl__anxdep__dep_004
  - mh_p_abcl__anxdep__dep_005
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__anxdep

compute_mh_p_abcl__synd__anxdep_nm(
  data,
```

```
  name = "mh_p_abcl__synd__anxdep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__anxdep is vector of all column names used to compute summary score of mh_p_abcl__synd__anxdep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__anxdep_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__anxdep_nm", vars_mh_p_abcl__synd__anxdep))
  )

## End(Not run)
```

---

vars_mh_p_abcl__synd__attn

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Attention problems): Number missing"

Description

Computes the summary score mh_p_abcl__synd__attn_nm Adult Behavior Checklist [Parent] (Syndrome Scale - Attention problems): Number missing

- *Summarized variables:*
  - mh_p_abcl__attn_001
  - mh_p_abcl__attn_002
  - mh_p_abcl__attn_003

  - mh_p_abcl__attn_004
  - mh_p_abcl__attn_005
  - mh_p_abcl__attn_006
  - mh_p_abcl__attn__adhd_001
  - mh_p_abcl__attn__adhd_002
  - mh_p_abcl__attn__adhd_003
  - mh_p_abcl__attn__adhd_004
  - mh_p_abcl__attn__adhd_005
  - mh_p_abcl__attn__adhd_006
  - mh_p_abcl__attn__adhd_007
  - mh_p_abcl__attn__antsoc_001
  - mh_p_abcl__attn__dep_001
  - mh_p_abcl__attn__dep_002
  - mh_p_abcl__attn__dep_003
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__attn

compute_mh_p_abcl__synd__attn_nm(
  data,
  name = "mh_p_abcl__synd__attn_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__attn is vector of all column names used to compute summary score of mh_p_abcl__synd__attn scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__attn_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__attn_nm", vars_mh_p_abcl__synd__attn))
  )

## End(Not run)
```

---

vars_mh_p_abcl__synd__ext

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - External): Number missing"

Description

Computes the summary score `mh_p_abcl__synd__ext_nm` Adult Behavior Checklist [Parent] (Syndrome Scale - External): Number missing

- *Summarized variables:*
  - `mh_p_abcl__aggr_001`
  - `mh_p_abcl__aggr_002`
  - `mh_p_abcl__aggr_003`
  - `mh_p_abcl__aggr_004`
  - `mh_p_abcl__aggr_005`
  - `mh_p_abcl__aggr_006`
  - `mh_p_abcl__aggr_007`
  - `mh_p_abcl__aggr__adhd_001`
  - `mh_p_abcl__aggr__antsoc_001`
  - `mh_p_abcl__aggr__antsoc_002`
  - `mh_p_abcl__aggr__antsoc_003`
  - `mh_p_abcl__aggr__antsoc_004`
  - `mh_p_abcl__aggr__antsoc_005`
  - `mh_p_abcl__aggr__antsoc_006`
  - `mh_p_abcl__aggr__antsoc_007`
  - `mh_p_abcl__aggr__antsoc_008`
  - `mh_p_abcl__rule_001`
  - `mh_p_abcl__rule_002`
  - `mh_p_abcl__rule_003`
  - `mh_p_abcl__rule__adhd_001`
  - `mh_p_abcl__rule__antsoc_001`
  - `mh_p_abcl__rule__antsoc_002`
  - `mh_p_abcl__rule__antsoc_003`

  - mh_p_abcl__rule__antsoc_004
  - mh_p_abcl__rule__antsoc_005
  - mh_p_abcl__rule__antsoc_006
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__rule__antsoc_008
  - mh_p_abcl__rule__antsoc_009
  - mh_p_abcl__intru_001
  - mh_p_abcl__intru_002
  - mh_p_abcl__intru_003
  - mh_p_abcl__intru_004
  - mh_p_abcl__intru_005
  - mh_p_abcl__intru_006
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__ext

compute_mh_p_abcl__synd__ext_nm(
  data,
  name = "mh_p_abcl__synd__ext_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__ext is vector of all column names used to compute summary score of mh_p_abcl__synd__ext scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__ext_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__ext_nm", vars_mh_p_abcl__synd__ext))
  )

## End(Not run)
```

`vars_mh_p_abcl__synd__int`

Compute "Adult Behavior Checklist [Parent] (Internalizing): Number missing"

Description

Computes the summary score `mh_p_abcl__synd__int_nm` Adult Behavior Checklist [Parent] (Internalizing): Number missing

- *Summarized variables:*
  - `mh_p_abcl__anxdep_001`
  - `mh_p_abcl__anxdep_002`
  - `mh_p_abcl__anxdep_003`
  - `mh_p_abcl__anxdep_004`
  - `mh_p_abcl__anxdep__anx_001`
  - `mh_p_abcl__anxdep__anx_002`
  - `mh_p_abcl__anxdep__anx_003`
  - `mh_p_abcl__anxdep__avoid_001`
  - `mh_p_abcl__anxdep__avoid_002`
  - `mh_p_abcl__anxdep__dep_001`
  - `mh_p_abcl__anxdep__dep_002`
  - `mh_p_abcl__anxdep__dep_003`
  - `mh_p_abcl__anxdep__dep_004`
  - `mh_p_abcl__anxdep__dep_005`
  - `mh_p_abcl__wthdr_001`
  - `mh_p_abcl__wthdr_002`
  - `mh_p_abcl__wthdr_003`
  - `mh_p_abcl__wthdr_004`
  - `mh_p_abcl__wthdr__avoid_001`
  - `mh_p_abcl__wthdr__avoid_002`
  - `mh_p_abcl__wthdr__avoid_003`
  - `mh_p_abcl__wthdr__avoid_004`
  - `mh_p_abcl__wthdr__dep_001`

  - mh_p_abcl__som_001
  - mh_p_abcl__som__dep_001
  - mh_p_abcl__som__somat_001
  - mh_p_abcl__som__somat_002
  - mh_p_abcl__som__somat_003
  - mh_p_abcl__som__somat_004
  - mh_p_abcl__som__somat_005
  - mh_p_abcl__som__somat_006
  - mh_p_abcl__som__somat_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__int

compute_mh_p_abcl__synd__int_nm(
  data,
  name = "mh_p_abcl__synd__int_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__int is vector of all column names used to compute summary score of mh_p_abcl__synd__int scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__int_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__int_nm", vars_mh_p_abcl__synd__int))
  )

## End(Not run)
```

`vars_mh_p_abcl__synd__intru`

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Intrusive): Number missing"

Description

Computes the summary score `mh_p_abcl__synd__intru_nm` Adult Behavior Checklist [Parent] (Syndrome Scale - Intrusive): Number missing

- *Summarized variables:*
  - `mh_p_abcl__intru_001`
  - `mh_p_abcl__intru_002`
  - `mh_p_abcl__intru_003`
  - `mh_p_abcl__intru_004`
  - `mh_p_abcl__intru_005`
  - `mh_p_abcl__intru_006`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__intru

compute_mh_p_abcl__synd__intru_nm(
  data,
  name = "mh_p_abcl__synd__intru_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__intru is vector of all column names used to compute summary score of mh_p_abcl__synd__intru scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__intru_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__intru_nm", vars_mh_p_abcl__synd__intru))
  )

## End(Not run)
```

---

vars_mh_p_abcl__synd__othpr

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Other problems): Number missing"

Description

Computes the summary score mh_p_abcl__synd__othpr_nm Adult Behavior Checklist [Parent] (Syndrome Scale - Other problems): Number missing

- *Summarized variables:*
  - mh_p_abcl__othpr_001
  - mh_p_abcl__othpr_002
  - mh_p_abcl__othpr_003
  - mh_p_abcl__othpr_004
  - mh_p_abcl__othpr_005
  - mh_p_abcl__othpr_006
  - mh_p_abcl__othpr_007

  - mh_p_abcl__othpr_008
  - mh_p_abcl__othpr_009
  - mh_p_abcl__othpr_010
  - mh_p_abcl__othpr_011
  - mh_p_abcl__othpr_012
  - mh_p_abcl__othpr__adhd_001
  - mh_p_abcl__othpr__adhd_002
  - mh_p_abcl__othpr__adhd_003
  - mh_p_abcl__othpr__adhd_004
  - mh_p_abcl__othpr__antsoc_001
  - mh_p_abcl__othpr__antsoc_002
  - mh_p_abcl__othpr__anx_001
  - mh_p_abcl__othpr__anx_002
  - mh_p_abcl__othpr__anx_003
  - mh_p_abcl__othpr__avoid_001
  - mh_p_abcl__othpr__dep_001
  - mh_p_abcl__othpr__dep_002
  - mh_p_abcl__othpr__dep_003
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__othpr

compute_mh_p_abcl__synd__othpr_nm(
  data,
  name = "mh_p_abcl__synd__othpr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__othpr is vector of all column names used to compute summary score of mh_p_abcl__synd__othpr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__othpr_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__othpr_nm", vars_mh_p_abcl__synd__othpr))
  )

## End(Not run)
```

---

vars_mh_p_abcl__synd__rule

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): Number missing"

Description

Computes the summary score mh_p_abcl__synd__rule_nm Adult Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): Number missing

- *Summarized variables:*
  - mh_p_abcl__rule_001
  - mh_p_abcl__rule_002
  - mh_p_abcl__rule_003
  - mh_p_abcl__rule__adhd_001
  - mh_p_abcl__rule__antsoc_001
  - mh_p_abcl__rule__antsoc_002
  - mh_p_abcl__rule__antsoc_003
  - mh_p_abcl__rule__antsoc_004
  - mh_p_abcl__rule__antsoc_005
  - mh_p_abcl__rule__antsoc_006
  - mh_p_abcl__rule__antsoc_007
  - mh_p_abcl__rule__antsoc_008
  - mh_p_abcl__rule__antsoc_009
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__rule

compute_mh_p_abcl__synd__rule_nm(
  data,
  name = "mh_p_abcl__synd__rule_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__rule is vector of all column names used to compute summary score of mh_p_abcl__synd__rule scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__rule_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__rule_nm", vars_mh_p_abcl__synd__rule))
  )

## End(Not run)
```

---

vars_mh_p_abcl__synd__som

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): Number missing"

Description

Computes the summary score mh_p_abcl__synd__som_nm Adult Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): Number missing

- *Summarized variables:*
  - mh_p_abcl__som_001
  - mh_p_abcl__som__dep_001
  - mh_p_abcl__som__somat_001
  - mh_p_abcl__som__somat_002
  - mh_p_abcl__som__somat_003
  - mh_p_abcl__som__somat_004
  - mh_p_abcl__som__somat_005
  - mh_p_abcl__som__somat_006
  - mh_p_abcl__som__somat_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__som

compute_mh_p_abcl__synd__som_nm(
  data,
  name = "mh_p_abcl__synd__som_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__som is vector of all column names used to compute summary score of mh_p_abcl__synd__som scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__som_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__som_nm", vars_mh_p_abcl__synd__som))
  )

## End(Not run)
```

`vars_mh_p_abcl__synd__tho`

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Thought problems): Number missing"

Description

Computes the summary score `mh_p_abcl__synd__tho_nm` Adult Behavior Checklist [Parent] (Syndrome Scale - Thought problems): Number missing

- *Summarized variables:*
  - `mh_p_abcl__tho_001`
  - `mh_p_abcl__tho_002`
  - `mh_p_abcl__tho_003`
  - `mh_p_abcl__tho_004`
  - `mh_p_abcl__tho_005`
  - `mh_p_abcl__tho_006`
  - `mh_p_abcl__tho_007`
  - `mh_p_abcl__tho__dep_001`
  - `mh_p_abcl__tho__dep_002`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__tho

compute_mh_p_abcl__synd__tho_nm(
  data,
  name = "mh_p_abcl__synd__tho_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__tho is vector of all column names used to compute summary score of mh_p_abcl__synd__tho scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__tho_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__tho_nm", vars_mh_p_abcl__synd__tho))
  )

## End(Not run)
```

---

vars_mh_p_abcl__synd__wthdr

Compute "Adult Behavior Checklist [Parent] (Syndrome Scale - Withdrawn): Number missing"

Description

Computes the summary score mh_p_abcl__synd__wthdr_nm Adult Behavior Checklist [Parent] (Syndrome Scale - Withdrawn): Number missing

- *Summarized variables:*
  - mh_p_abcl__wthdr_001
  - mh_p_abcl__wthdr_002
  - mh_p_abcl__wthdr_003
  - mh_p_abcl__wthdr_004
  - mh_p_abcl__wthdr__avoid_001
  - mh_p_abcl__wthdr__avoid_002
  - mh_p_abcl__wthdr__avoid_003

  - mh_p_abcl__wthdr__avoid_004
  - mh_p_abcl__wthdr__dep_001

- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_abcl__synd__wthdr

compute_mh_p_abcl__synd__wthdr_nm(
  data,
  name = "mh_p_abcl__synd__wthdr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_abcl__synd__wthdr is vector of all column names used to compute summary score of mh_p_abcl__synd__wthdr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_abcl__synd__wthdr_nm(data) |>
  select(
    any_of(c("mh_p_abcl__synd__wthdr_nm", vars_mh_p_abcl__synd__wthdr))
  )

## End(Not run)
```

vars_mh_p_asr *Compute "Adult Self Report [Parent]: Number missing"*

Description

Computes the summary score mh_p_asr_nm Adult Self Report [Parent]: Number missing

- *Summarized variables:*
  - mh_p_asr__aggr_001
  - mh_p_asr__aggr__antsoc_003
  - mh_p_asr__aggr__antsoc_006
  - mh_p_asr__aggr__antsoc_008
  - mh_p_asr__anxdep__dep_001
  - mh_p_asr__anxdep__dep_004
  - mh_p_asr__anxdep__dep_005
  - mh_p_asr__attn__inatt_002
  - mh_p_asr__othpr__hypimp_001
  - mh_p_asr__othpr__antsoc_001
  - mh_p_asr__rule_001
  - mh_p_asr__rule_003
  - mh_p_asr__rule__antsoc_007
  - mh_p_asr__tho_001
  - mh_p_asr__tho_002
  - mh_p_asr__tho_005
  - mh_p_asr__tho_006
  - mh_p_asr__tho_007
  - mh_p_asr__tho__dep_001
  - mh_p_asr__aggr__hypimp_001
  - mh_p_asr__othpr__hypimp_002
  - mh_p_asr__othpr__hypimp_003
  - mh_p_asr__rule__hypimp_001
  - mh_p_asr__tho__hypimp_001
  - mh_p_asr__attn__inatt_001
  - mh_p_asr__attn__inatt_003
  - mh_p_asr__attn__inatt_004
  - mh_p_asr__attn__inatt_005
  - mh_p_asr__attn__inatt_006
  - mh_p_asr__attn__inatt_007
  - mh_p_asr__aggr__antsoc_001
  - mh_p_asr__aggr__antsoc_002
  - mh_p_asr__aggr__antsoc_004

- mh_p_asr__aggr__antsoc_005
- mh_p_asr__aggr__antsoc_007
- mh_p_asr__attn__antsoc_001
- mh_p_asr__othpr__antsoc_002
- mh_p_asr__rule__antsoc_001
- mh_p_asr__rule__antsoc_002
- mh_p_asr__rule__antsoc_003
- mh_p_asr__rule__antsoc_004
- mh_p_asr__rule__antsoc_005
- mh_p_asr__rule__antsoc_006
- mh_p_asr__rule__antsoc_008
- mh_p_asr__rule__antsoc_009
- mh_p_asr__anxdep__anx_001
- mh_p_asr__anxdep__anx_002
- mh_p_asr__anxdep__anx_003
- mh_p_asr__anxdep__anx_004
- mh_p_asr__othpr__anx_001
- mh_p_asr__othpr__anx_002
- mh_p_asr__anxdep__avoid_001
- mh_p_asr__anxdep__avoid_002
- mh_p_asr__othpr__avoid_001
- mh_p_asr__wthdr__avoid_001
- mh_p_asr__wthdr__avoid_002
- mh_p_asr__wthdr__avoid_003
- mh_p_asr__wthdr__avoid_004
- mh_p_asr__anxdep__dep_002
- mh_p_asr__anxdep__dep_003
- mh_p_asr__anxdep__dep_006
- mh_p_asr__attn__dep_001
- mh_p_asr__attn__dep_002
- mh_p_asr__othpr__dep_001
- mh_p_asr__othpr__dep_002
- mh_p_asr__som__dep_001
- mh_p_asr__som__dep_002
- mh_p_asr__wthdr__dep_001
- mh_p_asr__som__somat_001
- mh_p_asr__som__somat_002
- mh_p_asr__som__somat_003
- mh_p_asr__som__somat_004
- mh_p_asr__som__somat_005
- mh_p_asr__som__somat_006
- mh_p_asr__som__somat_007

- mh_p_asr__som__somat_008
- mh_p_asr__som__somat_009
- mh_p_asr__aggr_002
- mh_p_asr__aggr_003
- mh_p_asr__aggr_004
- mh_p_asr__aggr_005
- mh_p_asr__aggr_006
- mh_p_asr__anxdep_001
- mh_p_asr__anxdep_002
- mh_p_asr__anxdep_003
- mh_p_asr__anxdep_004
- mh_p_asr__anxdep_005
- mh_p_asr__anxdep_006
- mh_p_asr__attn_001
- mh_p_asr__attn_002
- mh_p_asr__attn_003
- mh_p_asr__attn_004
- mh_p_asr__attn_005
- mh_p_asr__intru_001
- mh_p_asr__intru_002
- mh_p_asr__intru_003
- mh_p_asr__intru_004
- mh_p_asr__intru_005
- mh_p_asr__intru_006
- mh_p_asr__rule_002
- mh_p_asr__rule_004
- mh_p_asr__som_001
- mh_p_asr__wthdr_001
- mh_p_asr__wthdr_002
- mh_p_asr__wthdr_003
- mh_p_asr__wthdr_004
- mh_p_asr__othpr_001
- mh_p_asr__othpr_002
- mh_p_asr__othpr_003
- mh_p_asr__othpr_004
- mh_p_asr__othpr_005
- mh_p_asr__othpr_006
- mh_p_asr__othpr_007
- mh_p_asr__othpr_008
- mh_p_asr__othpr_009
- mh_p_asr__othpr_010
- mh_p_asr__othpr_011

  - mh_p_asr__tho_003
  - mh_p_asr__tho_004
  - mh_p_asr__tho_008
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr

compute_mh_p_asr_nm(
  data,
  name = "mh_p_asr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr is vector of all column names used to compute summary score of mh_p_asr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr_nm(data) |>
  select(
    any_of(c("mh_p_asr_nm", vars_mh_p_asr))
  )

## End(Not run)
```

vars_mh_p_asr__afs__strng *Compute "Adult Self Report [Parent] (Adaptive Functioning Scale - Personal strength): Number missing"*

Description

Computes the summary score mh_p_asr__afs__strng_nm Adult Self Report [Parent] (Adaptive Functioning Scale - Personal strength): Number missing

- *Summarized variables:*
  - mh_p_asr__strng_001
  - mh_p_asr__strng_002
  - mh_p_asr__strng_003
  - mh_p_asr__strng_004
  - mh_p_asr__strng_005
  - mh_p_asr__strng_006
  - mh_p_asr__strng_007
  - mh_p_asr__strng_008
  - mh_p_asr__strng_009
  - mh_p_asr__strng_010
  - mh_p_asr__strng_011
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__afs__strng

compute_mh_p_asr__afs__strng_nm(
  data,
  name = "mh_p_asr__afs__strng_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__afs__strng is vector of all column names used to compute summary score of mh_p_asr__afs__strng scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__afs__strng_nm(data) |>
  select(
    any_of(c("mh_p_asr__afs__strng_nm", vars_mh_p_asr__afs__strng))
  )

## End(Not run)
```

---

vars_mh_p_asr__critic *Compute "Adult Self Report [Parent] (Critical Items): Number missing"*

Description

Computes the summary score mh_p_asr__critic_nm Adult Self Report [Parent] (Critical Items): Number missing

- *Summarized variables:*
  - mh_p_asr__aggr_001
  - mh_p_asr__aggr__antsoc_003
  - mh_p_asr__aggr__antsoc_006
  - mh_p_asr__aggr__antsoc_008
  - mh_p_asr__anxdep__dep_001
  - mh_p_asr__anxdep__dep_004
  - mh_p_asr__anxdep__dep_005
  - mh_p_asr__attn__inatt_002
  - mh_p_asr__othpr__hypimp_001
  - mh_p_asr__othpr__antsoc_001
  - mh_p_asr__rule_001
  - mh_p_asr__rule_003
  - mh_p_asr__rule__antsoc_007
  - mh_p_asr__tho_001
  - mh_p_asr__tho_002
  - mh_p_asr__tho_005
  - mh_p_asr__tho_006

  - mh_p_asr__tho_007
  - mh_p_asr__tho__dep_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__critic

compute_mh_p_asr__critic_nm(
  data,
  name = "mh_p_asr__critic_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__critic is vector of all column names used to compute summary score of mh_p_asr__critic scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__critic_nm(data) |>
  select(
    any_of(c("mh_p_asr__critic_nm", vars_mh_p_asr__critic))
  )

## End(Not run)
```

vars_mh_p_asr__dsm__adhd *Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD): Number missing"*

Description

Computes the summary score `mh_p_asr__dsm__adhd_nm` Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD): Number missing

- *Summarized variables:*
  - `mh_p_asr__attn__inatt_001`
  - `mh_p_asr__attn__inatt_002`
  - `mh_p_asr__attn__inatt_003`
  - `mh_p_asr__attn__inatt_004`
  - `mh_p_asr__attn__inatt_005`
  - `mh_p_asr__attn__inatt_006`
  - `mh_p_asr__attn__inatt_007`
  - `mh_p_asr__aggr__hypimp_001`
  - `mh_p_asr__othpr__hypimp_001`
  - `mh_p_asr__othpr__hypimp_002`
  - `mh_p_asr__othpr__hypimp_003`
  - `mh_p_asr__rule__hypimp_001`
  - `mh_p_asr__tho__hypimp_001`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__dsm__adhd

compute_mh_p_asr__dsm__adhd_nm(
  data,
  name = "mh_p_asr__dsm__adhd_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score.

combine logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__dsm__adhd is vector of all column names used to compute summary score of mh_p_asr__dsm__adhd scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__dsm__adhd_nm(data) |>
  select(
    any_of(c("mh_p_asr__dsm__adhd_nm", vars_mh_p_asr__dsm__adhd))
  )

## End(Not run)
```

---

vars_mh_p_asr__dsm__adhd__hypimp

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD Hyperactivity-Impulsivity): Number missing"

Description

Computes the summary score mh_p_asr__dsm__adhd__hypimp_nm Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD Hyperactivity-Impulsivity): Number missing

- *Summarized variables:*
  - mh_p_asr__aggr__hypimp_001
  - mh_p_asr__othpr__hypimp_001
  - mh_p_asr__othpr__hypimp_002
  - mh_p_asr__othpr__hypimp_003
  - mh_p_asr__rule__hypimp_001
  - mh_p_asr__tho__hypimp_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__dsm__adhd__hypimp

compute_mh_p_asr__dsm__adhd__hypimp_nm(
  data,
  name = "mh_p_asr__dsm__adhd__hypimp_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__dsm__adhd__hypimp is vector of all column names used to compute summary score of mh_p_asr__dsm__adhd__hypimp scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__dsm__adhd__hypimp_nm(data) |>
  select(
    any_of(c("mh_p_asr__dsm__adhd__hypimp_nm", vars_mh_p_asr__dsm__adhd__hypimp))
  )

## End(Not run)
```

---

vars_mh_p_asr__dsm__adhd__inatt

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD Inattention): Number missing"

Description

Computes the summary score mh_p_asr__dsm__adhd__inatt_nm Adult Self Report [Parent] (DSM-5 Oriented Scale - ADHD Inattention): Number missing

- *Summarized variables:*
  - mh_p_asr__attn__inatt_001
  - mh_p_asr__attn__inatt_002
  - mh_p_asr__attn__inatt_003
  - mh_p_asr__attn__inatt_004
  - mh_p_asr__attn__inatt_005
  - mh_p_asr__attn__inatt_006
  - mh_p_asr__attn__inatt_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__dsm__adhd__inatt

compute_mh_p_asr__dsm__adhd__inatt_nm(
  data,
  name = "mh_p_asr__dsm__adhd__inatt_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__dsm__adhd__inatt is vector of all column names used to compute summary score of mh_p_asr__dsm__adhd__inatt scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__dsm__adhd__inatt_nm(data) |>
  select(
    any_of(c("mh_p_asr__dsm__adhd__inatt_nm", vars_mh_p_asr__dsm__adhd__inatt))
  )

## End(Not run)
```

`vars_mh_p_asr__dsm__antsoc`

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): Number missing"

Description

Computes the summary score `mh_p_asr__dsm__antsoc_nm` Adult Self Report [Parent] (DSM-5 Oriented Scale - Antisocial personality problems): Number missing

- *Summarized variables:*
  - `mh_p_asr__aggr__antsoc_001`
  - `mh_p_asr__aggr__antsoc_002`
  - `mh_p_asr__aggr__antsoc_003`
  - `mh_p_asr__aggr__antsoc_004`
  - `mh_p_asr__aggr__antsoc_005`
  - `mh_p_asr__aggr__antsoc_006`
  - `mh_p_asr__aggr__antsoc_007`
  - `mh_p_asr__aggr__antsoc_008`
  - `mh_p_asr__attn__antsoc_001`
  - `mh_p_asr__othpr__antsoc_001`
  - `mh_p_asr__othpr__antsoc_002`
  - `mh_p_asr__rule__antsoc_001`
  - `mh_p_asr__rule__antsoc_002`
  - `mh_p_asr__rule__antsoc_003`
  - `mh_p_asr__rule__antsoc_004`
  - `mh_p_asr__rule__antsoc_005`
  - `mh_p_asr__rule__antsoc_006`
  - `mh_p_asr__rule__antsoc_007`
  - `mh_p_asr__rule__antsoc_008`
  - `mh_p_asr__rule__antsoc_009`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__dsm__antsoc

compute_mh_p_asr__dsm__antsoc_nm(
  data,
  name = "mh_p_asr__dsm__antsoc_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__dsm__antsoc is vector of all column names used to compute summary score of mh_p_asr__dsm__antsoc scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__dsm__antsoc_nm(data) |>
  select(
    any_of(c("mh_p_asr__dsm__antsoc_nm", vars_mh_p_asr__dsm__antsoc))
  )

## End(Not run)
```

---

vars_mh_p_asr__dsm__anx

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Anxiety problems): Number missing"

Description

Computes the summary score mh_p_asr__dsm__anx_nm Adult Self Report [Parent] (DSM-5 Oriented Scale - Anxiety problems): Number missing

- *Summarized variables:*
  - mh_p_asr__anxdep__anx_001
  - mh_p_asr__anxdep__anx_002
  - mh_p_asr__anxdep__anx_003
  - mh_p_asr__anxdep__anx_004
  - mh_p_asr__othpr__anx_001
  - mh_p_asr__othpr__anx_002
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__dsm__anx

compute_mh_p_asr__dsm__anx_nm(
  data,
  name = "mh_p_asr__dsm__anx_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__dsm__anx is vector of all column names used to compute summary score of mh_p_asr__dsm__anx scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__dsm__anx_nm(data) |>
  select(
    any_of(c("mh_p_asr__dsm__anx_nm", vars_mh_p_asr__dsm__anx))
  )

## End(Not run)
```

`vars_mh_p_asr__dsm__avoid`

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): Number missing"

Description

Computes the summary score `mh_p_asr__dsm__avoid_nm` Adult Self Report [Parent] (DSM-5 Oriented Scale - Avoidant personality problems): Number missing

- *Summarized variables:*
  - `mh_p_asr__anxdep__avoid_001`
  - `mh_p_asr__anxdep__avoid_002`
  - `mh_p_asr__othpr__avoid_001`
  - `mh_p_asr__wthdr__avoid_001`
  - `mh_p_asr__wthdr__avoid_002`
  - `mh_p_asr__wthdr__avoid_003`
  - `mh_p_asr__wthdr__avoid_004`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__dsm__avoid

compute_mh_p_asr__dsm__avoid_nm(
  data,
  name = "mh_p_asr__dsm__avoid_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__dsm__avoid is vector of all column names used to compute summary score of mh_p_asr__dsm__avoid scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__dsm__avoid_nm(data) |>
  select(
    any_of(c("mh_p_asr__dsm__avoid_nm", vars_mh_p_asr__dsm__avoid))
  )

## End(Not run)
```

---

vars_mh_p_asr__dsm__dep

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Depresssive problems): Number missing"

Description

Computes the summary score mh_p_asr__dsm__dep_nm Adult Self Report [Parent] (DSM-5 Oriented Scale - Depresssive problems): Number missing

- *Summarized variables:*
  - mh_p_asr__anxdep__dep_001
  - mh_p_asr__anxdep__dep_002
  - mh_p_asr__anxdep__dep_003
  - mh_p_asr__anxdep__dep_004
  - mh_p_asr__anxdep__dep_005
  - mh_p_asr__anxdep__dep_006
  - mh_p_asr__attn__dep_001

  - mh_p_asr__attn__dep_002
  - mh_p_asr__othpr__dep_001
  - mh_p_asr__othpr__dep_002
  - mh_p_asr__som__dep_001
  - mh_p_asr__som__dep_002
  - mh_p_asr__tho__dep_001
  - mh_p_asr__wthdr__dep_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__dsm__dep

compute_mh_p_asr__dsm__dep_nm(
  data,
  name = "mh_p_asr__dsm__dep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__dsm__dep is vector of all column names used to compute summary score of mh_p_asr__dsm__dep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__dsm__dep_nm(data) |>
  select(
    any_of(c("mh_p_asr__dsm__dep_nm", vars_mh_p_asr__dsm__dep))
  )

## End(Not run)
```

vars_mh_p_asr__dsm__somat

Compute "Adult Self Report [Parent] (DSM-5 Oriented Scale - Somatic complaints): Number missing"

Description

Computes the summary score `mh_p_asr__dsm__somat_nm` Adult Self Report [Parent] (DSM-5 Oriented Scale - Somatic complaints): Number missing

- *Summarized variables:*
  - `mh_p_asr__som__somat_001`
  - `mh_p_asr__som__somat_002`
  - `mh_p_asr__som__somat_003`
  - `mh_p_asr__som__somat_004`
  - `mh_p_asr__som__somat_005`
  - `mh_p_asr__som__somat_006`
  - `mh_p_asr__som__somat_007`
  - `mh_p_asr__som__somat_008`
  - `mh_p_asr__som__somat_009`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__dsm__somat

compute_mh_p_asr__dsm__somat_nm(
  data,
  name = "mh_p_asr__dsm__somat_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__dsm__somat is vector of all column names used to compute summary score of mh_p_asr__dsm__somat scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__dsm__somat_nm(data) |>
  select(
    any_of(c("mh_p_asr__dsm__somat_nm", vars_mh_p_asr__dsm__somat))
  )

## End(Not run)
```

---

vars_mh_p_asr__synd__aggr

Compute "Adult Self Report [Parent] (Syndrome Scale - Aggressive Behavior): Number missing"

Description

Computes the summary score mh_p_asr__synd__aggr_nm Adult Self Report [Parent] (Syndrome Scale - Aggressive Behavior): Number missing

- *Summarized variables:*
  - mh_p_asr__aggr_001
  - mh_p_asr__aggr_002
  - mh_p_asr__aggr_003
  - mh_p_asr__aggr_004
  - mh_p_asr__aggr_005
  - mh_p_asr__aggr_006
  - mh_p_asr__aggr__hypimp_001
  - mh_p_asr__aggr__antsoc_001
  - mh_p_asr__aggr__antsoc_002
  - mh_p_asr__aggr__antsoc_003
  - mh_p_asr__aggr__antsoc_004
  - mh_p_asr__aggr__antsoc_005
  - mh_p_asr__aggr__antsoc_006
  - mh_p_asr__aggr__antsoc_007
  - mh_p_asr__aggr__antsoc_008
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__aggr

compute_mh_p_asr__synd__aggr_nm(
  data,
  name = "mh_p_asr__synd__aggr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__aggr is vector of all column names used to compute summary score of mh_p_asr__synd__aggr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__aggr_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__aggr_nm", vars_mh_p_asr__synd__aggr))
  )

## End(Not run)
```

---

vars_mh_p_asr__synd__anxdep

Compute "Adult Self Report [Parent] (Syndrome Scale - Anxious/Depressed): Number missing"

Description

Computes the summary score mh_p_asr__synd__anxdep_nm Adult Self Report [Parent] (Syndrome Scale - Anxious/Depressed): Number missing

- *Summarized variables:*
  - mh_p_asr__anxdep_001
  - mh_p_asr__anxdep_002
  - mh_p_asr__anxdep_003
  - mh_p_asr__anxdep_004
  - mh_p_asr__anxdep_005
  - mh_p_asr__anxdep_006
  - mh_p_asr__anxdep__anx_001
  - mh_p_asr__anxdep__anx_002
  - mh_p_asr__anxdep__anx_003
  - mh_p_asr__anxdep__anx_004
  - mh_p_asr__anxdep__avoid_001
  - mh_p_asr__anxdep__avoid_002
  - mh_p_asr__anxdep__dep_001
  - mh_p_asr__anxdep__dep_002
  - mh_p_asr__anxdep__dep_003
  - mh_p_asr__anxdep__dep_004
  - mh_p_asr__anxdep__dep_005
  - mh_p_asr__anxdep__dep_006
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__anxdep

compute_mh_p_asr__synd__anxdep_nm(
  data,
  name = "mh_p_asr__synd__anxdep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__anxdep is vector of all column names used to compute summary score of mh_p_asr__synd__anxdep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__anxdep_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__anxdep_nm", vars_mh_p_asr__synd__anxdep))
  )

## End(Not run)
```

---

vars_mh_p_asr__synd__attn

Compute "Adult Self Report [Parent] (Syndrome Scale - Attention problems): Number missing"

Description

Computes the summary score mh_p_asr__synd__attn_nm Adult Self Report [Parent] (Syndrome Scale - Attention problems): Number missing

- *Summarized variables:*
  - mh_p_asr__attn_001
  - mh_p_asr__attn_002
  - mh_p_asr__attn_003
  - mh_p_asr__attn_004
  - mh_p_asr__attn_005
  - mh_p_asr__attn__inatt_001
  - mh_p_asr__attn__inatt_002
  - mh_p_asr__attn__inatt_003
  - mh_p_asr__attn__inatt_004
  - mh_p_asr__attn__inatt_005
  - mh_p_asr__attn__inatt_006
  - mh_p_asr__attn__inatt_007
  - mh_p_asr__attn__antsoc_001
  - mh_p_asr__attn__dep_001
  - mh_p_asr__attn__dep_002
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__attn

compute_mh_p_asr__synd__attn_nm(
  data,
  name = "mh_p_asr__synd__attn_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__attn is vector of all column names used to compute summary score of mh_p_asr__synd__attn scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__attn_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__attn_nm", vars_mh_p_asr__synd__attn))
  )

## End(Not run)
```

---

vars_mh_p_asr__synd__ext

Compute "Adult Self Report [Parent] (Syndrome Scale - Externalizing): Number missing"

Description

Computes the summary score `mh_p_asr__synd__ext_nm` Adult Self Report [Parent] (Syndrome Scale - Externalizing): Number missing

- *Summarized variables:*
  - `mh_p_asr__intru_001`
  - `mh_p_asr__intru_002`
  - `mh_p_asr__intru_003`
  - `mh_p_asr__intru_004`
  - `mh_p_asr__intru_005`
  - `mh_p_asr__intru_006`
  - `mh_p_asr__rule_001`
  - `mh_p_asr__rule_002`
  - `mh_p_asr__rule_003`
  - `mh_p_asr__rule_004`
  - `mh_p_asr__rule__hypimp_001`
  - `mh_p_asr__rule__antsoc_001`
  - `mh_p_asr__rule__antsoc_002`
  - `mh_p_asr__rule__antsoc_003`
  - `mh_p_asr__rule__antsoc_004`
  - `mh_p_asr__rule__antsoc_005`
  - `mh_p_asr__rule__antsoc_006`
  - `mh_p_asr__rule__antsoc_007`
  - `mh_p_asr__rule__antsoc_008`
  - `mh_p_asr__rule__antsoc_009`
  - `mh_p_asr__aggr_001`
  - `mh_p_asr__aggr_002`
  - `mh_p_asr__aggr_003`
  - `mh_p_asr__aggr_004`
  - `mh_p_asr__aggr_005`
  - `mh_p_asr__aggr_006`
  - `mh_p_asr__aggr__hypimp_001`
  - `mh_p_asr__aggr__antsoc_001`
  - `mh_p_asr__aggr__antsoc_002`
  - `mh_p_asr__aggr__antsoc_003`
  - `mh_p_asr__aggr__antsoc_004`
  - `mh_p_asr__aggr__antsoc_005`
  - `mh_p_asr__aggr__antsoc_006`
  - `mh_p_asr__aggr__antsoc_007`
  - `mh_p_asr__aggr__antsoc_008`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__ext

compute_mh_p_asr__synd__ext_nm(
  data,
  name = "mh_p_asr__synd__ext_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__ext is vector of all column names used to compute summary score of mh_p_asr__synd__ext scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__ext_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__ext_nm", vars_mh_p_asr__synd__ext))
  )

## End(Not run)
```

---

vars_mh_p_asr__synd__int

Compute "Adult Self Report [Parent] (Syndrome Scale - Internalizing): Number missing"

Description

Computes the summary score mh_p_asr__synd__int_nm Adult Self Report [Parent] (Syndrome Scale - Internalizing): Number missing

- *Summarized variables:*
  - mh_p_asr__anxdep_001
  - mh_p_asr__anxdep_002
  - mh_p_asr__anxdep_003
  - mh_p_asr__anxdep_004
  - mh_p_asr__anxdep_005
  - mh_p_asr__anxdep_006
  - mh_p_asr__anxdep__anx_001
  - mh_p_asr__anxdep__anx_002
  - mh_p_asr__anxdep__anx_003
  - mh_p_asr__anxdep__anx_004
  - mh_p_asr__anxdep__avoid_001
  - mh_p_asr__anxdep__avoid_002
  - mh_p_asr__anxdep__dep_001
  - mh_p_asr__anxdep__dep_002
  - mh_p_asr__anxdep__dep_003
  - mh_p_asr__anxdep__dep_004
  - mh_p_asr__anxdep__dep_005
  - mh_p_asr__anxdep__dep_006
  - mh_p_asr__som_001
  - mh_p_asr__som__dep_001
  - mh_p_asr__som__dep_002
  - mh_p_asr__som__somat_001
  - mh_p_asr__som__somat_002
  - mh_p_asr__som__somat_003
  - mh_p_asr__som__somat_004
  - mh_p_asr__som__somat_005
  - mh_p_asr__som__somat_006
  - mh_p_asr__som__somat_007
  - mh_p_asr__som__somat_008
  - mh_p_asr__som__somat_009
  - mh_p_asr__wthdr_001
  - mh_p_asr__wthdr_002
  - mh_p_asr__wthdr_003
  - mh_p_asr__wthdr_004
  - mh_p_asr__wthdr__avoid_001
  - mh_p_asr__wthdr__avoid_002
  - mh_p_asr__wthdr__avoid_003

  - mh_p_asr__wthdr__avoid_004
  - mh_p_asr__wthdr__dep_001

- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__int

compute_mh_p_asr__synd__int_nm(
  data,
  name = "mh_p_asr__synd__int_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__int is vector of all column names used to compute summary score of mh_p_asr__synd__int scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__int_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__int_nm", vars_mh_p_asr__synd__int))
  )

## End(Not run)
```

vars_mh_p_asr__synd__intru

Compute "Adult Self Report [Parent] (Syndrome Scale - Intrusive): Number missing"

Description

Computes the summary score mh_p_asr__synd__intru_nm Adult Self Report [Parent] (Syndrome Scale - Intrusive): Number missing

- *Summarized variables:*
  - mh_p_asr__intru_001
  - mh_p_asr__intru_002
  - mh_p_asr__intru_003
  - mh_p_asr__intru_004
  - mh_p_asr__intru_005
  - mh_p_asr__intru_006
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__intru

compute_mh_p_asr__synd__intru_nm(
  data,
  name = "mh_p_asr__synd__intru_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__intru is vector of all column names used to compute summary score of mh_p_asr__synd__intru scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__intru_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__intru_nm", vars_mh_p_asr__synd__intru))
  )

## End(Not run)
```

---

vars_mh_p_asr__synd__othpr

Compute "Adult Self Report [Parent] (Syndrome Scale - Other problems): Number missing"

Description

Computes the summary score mh_p_asr__synd__othpr_nm Adult Self Report [Parent] (Syndrome Scale - Other problems): Number missing

- *Summarized variables:*
  - mh_p_asr__othpr_001
  - mh_p_asr__othpr_002
  - mh_p_asr__othpr_003
  - mh_p_asr__othpr_004
  - mh_p_asr__othpr_005
  - mh_p_asr__othpr_006
  - mh_p_asr__othpr_007
  - mh_p_asr__othpr_008
  - mh_p_asr__othpr_009
  - mh_p_asr__othpr_010
  - mh_p_asr__othpr_011
  - mh_p_asr__othpr__hypimp_001
  - mh_p_asr__othpr__hypimp_002
  - mh_p_asr__othpr__hypimp_003
  - mh_p_asr__othpr__antsoc_001
  - mh_p_asr__othpr__antsoc_002
  - mh_p_asr__othpr__anx_001
  - mh_p_asr__othpr__anx_002
  - mh_p_asr__othpr__avoid_001
  - mh_p_asr__othpr__dep_001

  - mh_p_asr__othpr__dep_002

- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__othpr

compute_mh_p_asr__synd__othpr_nm(
  data,
  name = "mh_p_asr__synd__othpr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__othpr is vector of all column names used to compute summary score of mh_p_asr__synd__othpr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__othpr_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__othpr_nm", vars_mh_p_asr__synd__othpr))
  )

## End(Not run)
```

vars_mh_p_asr__synd__rule

Compute "Adult Self Report [Parent] (Syndrome Scale - Rule breaking behavior): Number missing"

Description

Computes the summary score mh_p_asr__synd__rule_nm Adult Self Report [Parent] (Syndrome Scale - Rule breaking behavior): Number missing

- *Summarized variables:*
  - mh_p_asr__rule_001
  - mh_p_asr__rule_002
  - mh_p_asr__rule_003
  - mh_p_asr__rule_004
  - mh_p_asr__rule__hypimp_001
  - mh_p_asr__rule__antsoc_001
  - mh_p_asr__rule__antsoc_002
  - mh_p_asr__rule__antsoc_003
  - mh_p_asr__rule__antsoc_004
  - mh_p_asr__rule__antsoc_005
  - mh_p_asr__rule__antsoc_006
  - mh_p_asr__rule__antsoc_007
  - mh_p_asr__rule__antsoc_008
  - mh_p_asr__rule__antsoc_009
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__rule

compute_mh_p_asr__synd__rule_nm(
  data,
  name = "mh_p_asr__synd__rule_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__rule is vector of all column names used to compute summary score of mh_p_asr__synd__rule scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__rule_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__rule_nm", vars_mh_p_asr__synd__rule))
  )

## End(Not run)
```

---

vars_mh_p_asr__synd__som

Compute "Adult Self Report [Parent] (Syndrome Scale - Somatic complaints): Number missing"

Description

Computes the summary score mh_p_asr__synd__som_nm Adult Self Report [Parent] (Syndrome Scale - Somatic complaints): Number missing

- *Summarized variables:*
  - mh_p_asr__som_001
  - mh_p_asr__som__dep_001
  - mh_p_asr__som__dep_002
  - mh_p_asr__som__somat_001
  - mh_p_asr__som__somat_002
  - mh_p_asr__som__somat_003
  - mh_p_asr__som__somat_004

  - mh_p_asr__som__somat_005
  - mh_p_asr__som__somat_006
  - mh_p_asr__som__somat_007
  - mh_p_asr__som__somat_008
  - mh_p_asr__som__somat_009
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__som

compute_mh_p_asr__synd__som_nm(
  data,
  name = "mh_p_asr__synd__som_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__som is vector of all column names used to compute summary score of mh_p_asr__synd__som scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__som_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__som_nm", vars_mh_p_asr__synd__som))
  )

## End(Not run)
```

vars_mh_p_asr__synd__tho

Compute "Adult Self Report [Parent] (Syndrome Scale - Thought problems): Number missing"

Description

Computes the summary score `mh_p_asr__synd__tho_nm` Adult Self Report [Parent] (Syndrome Scale - Thought problems): Number missing

- *Summarized variables:*
  - `mh_p_asr__tho_001`
  - `mh_p_asr__tho_002`
  - `mh_p_asr__tho_003`
  - `mh_p_asr__tho_004`
  - `mh_p_asr__tho_005`
  - `mh_p_asr__tho_006`
  - `mh_p_asr__tho_007`
  - `mh_p_asr__tho_008`
  - `mh_p_asr__tho__hypimp_001`
  - `mh_p_asr__tho__dep_001`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__tho

compute_mh_p_asr__synd__tho_nm(
  data,
  name = "mh_p_asr__synd__tho_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__tho is vector of all column names used to compute summary score of mh_p_asr__synd__tho scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__tho_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__tho_nm", vars_mh_p_asr__synd__tho))
  )

## End(Not run)
```

---

vars_mh_p_asr__synd__wthdr

Compute "Adult Self Report [Parent] (Syndrome Scale - Withdrawn): Number missing"

Description

Computes the summary score mh_p_asr__synd__wthdr_nm Adult Self Report [Parent] (Syndrome Scale - Withdrawn): Number missing

- *Summarized variables:*
  - mh_p_asr__wthdr_001
  - mh_p_asr__wthdr_002
  - mh_p_asr__wthdr_003
  - mh_p_asr__wthdr_004
  - mh_p_asr__wthdr__avoid_001
  - mh_p_asr__wthdr__avoid_002
  - mh_p_asr__wthdr__avoid_003
  - mh_p_asr__wthdr__avoid_004
  - mh_p_asr__wthdr__dep_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_asr__synd__wthdr

compute_mh_p_asr__synd__wthdr_nm(
  data,
  name = "mh_p_asr__synd__wthdr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_asr__synd__wthdr is vector of all column names used to compute summary score of mh_p_asr__synd__wthdr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_asr__synd__wthdr_nm(data) |>
  select(
    any_of(c("mh_p_asr__synd__wthdr_nm", vars_mh_p_asr__synd__wthdr))
  )

## End(Not run)
```

---

vars_mh_p_cbcl *Compute "Child Behavior Checklist [Parent] (Syndrome Scale): Number missing"*

Description

Computes the summary score `mh_p_cbcl_nm` Child Behavior Checklist [Parent] (Syndrome Scale): Number missing

- *Summarized variables:*
  - `mh_p_cbcl__attn__adhd_001`
  - `mh_p_cbcl__attn__adhd_002`
  - `mh_p_cbcl__attn__adhd_003`
  - `mh_p_cbcl__aggr__adhd_001`
  - `mh_p_cbcl__attn__adhd_004`
  - `mh_p_cbcl__attn__adhd_005`
  - `mh_p_cbcl__othpr__adhd_001`
  - `mh_p_cbcl__soc__anx_001`
  - `mh_p_cbcl__anxdep__anx_007`
  - `mh_p_cbcl__anxdep__anx_001`
  - `mh_p_cbcl__anxdep__anx_002`
  - `mh_p_cbcl__anxdep__anx_003`
  - `mh_p_cbcl__anxdep__anx_004`
  - `mh_p_cbcl__som__anx_001`
  - `mh_p_cbcl__anxdep__anx_005`
  - `mh_p_cbcl__anxdep__anx_006`
  - `mh_p_cbcl__rule__cond_010`
  - `mh_p_cbcl__rule__cond_011`
  - `mh_p_cbcl__othpr__cond_001`
  - `mh_p_cbcl__aggr__cond_001`
  - `mh_p_cbcl__aggr__cond_002`
  - `mh_p_cbcl__rule__cond_001`
  - `mh_p_cbcl__rule__cond_002`
  - `mh_p_cbcl__aggr__cond_003`
  - `mh_p_cbcl__rule__cond_003`
  - `mh_p_cbcl__rule__cond_004`
  - `mh_p_cbcl__aggr__cond_004`
  - `mh_p_cbcl__rule__cond_005`
  - `mh_p_cbcl__rule__cond_006`
  - `mh_p_cbcl__rule__cond_007`
  - `mh_p_cbcl__rule__cond_008`
  - `mh_p_cbcl__rule__cond_009`
  - `mh_p_cbcl__aggr__cond_005`
  - `mh_p_cbcl__wthdep__dep_001`
  - `mh_p_cbcl__tho__dep_003`
  - `mh_p_cbcl__wthdep__dep_002`
  - `mh_p_cbcl__wthdep__dep_003`

- mh_p_cbcl__anxdep__dep_001
- mh_p_cbcl__tho__dep_001
- mh_p_cbcl__othpr__dep_001
- mh_p_cbcl__anxdep__dep_002
- mh_p_cbcl__anxdep__dep_003
- mh_p_cbcl__som__dep_001
- mh_p_cbcl__tho__dep_002
- mh_p_cbcl__othpr__dep_002
- mh_p_cbcl__anxdep__dep_004
- mh_p_cbcl__aggr__opp_001
- mh_p_cbcl__aggr__opp_002
- mh_p_cbcl__aggr__opp_003
- mh_p_cbcl__aggr__opp_004
- mh_p_cbcl__aggr__opp_005
- mh_p_cbcl__som__somat_001
- mh_p_cbcl__som__somat_002
- mh_p_cbcl__som__somat_003
- mh_p_cbcl__som__somat_004
- mh_p_cbcl__som__somat_005
- mh_p_cbcl__som__somat_006
- mh_p_cbcl__som__somat_007
- mh_p_cbcl__tho_001
- mh_p_cbcl__anxdep_001
- mh_p_cbcl__tho_007
- mh_p_cbcl__tho_010
- mh_p_cbcl__tho_011
- mh_p_cbcl__attn_002
- mh_p_cbcl__attn_003
- mh_p_cbcl__attn_005
- mh_p_cbcl__wthdep_005
- mh_p_cbcl__soc_004
- mh_p_cbcl__wthdep_003
- mh_p_cbcl__aggr_004
- mh_p_cbcl__aggr_001
- mh_p_cbcl__aggr_002
- mh_p_cbcl__aggr_003
- mh_p_cbcl__aggr_005
- mh_p_cbcl__aggr_006
- mh_p_cbcl__aggr_007
- mh_p_cbcl__anxdep_002
- mh_p_cbcl__attn_001
- mh_p_cbcl__attn_004

  - mh_p_cbcl__rule_001
  - mh_p_cbcl__rule_006
  - mh_p_cbcl__rule_002
  - mh_p_cbcl__rule_003
  - mh_p_cbcl__rule_004
  - mh_p_cbcl__rule_005
  - mh_p_cbcl__wthdep_001
  - mh_p_cbcl__wthdep_002
  - mh_p_cbcl__wthdep_004
  - mh_p_cbcl__som_001
  - mh_p_cbcl__som_002
  - mh_p_cbcl__othpr_001
  - mh_p_cbcl__othpr_002
  - mh_p_cbcl__othpr_009
  - mh_p_cbcl__othpr_010
  - mh_p_cbcl__othpr_011
  - mh_p_cbcl__othpr_012
  - mh_p_cbcl__othpr_003
  - mh_p_cbcl__othpr_004
  - mh_p_cbcl__othpr_005
  - mh_p_cbcl__othpr_006
  - mh_p_cbcl__othpr_007
  - mh_p_cbcl__othpr_008
  - mh_p_cbcl__soc_001
  - mh_p_cbcl__soc_002
  - mh_p_cbcl__soc_003
  - mh_p_cbcl__soc_005
  - mh_p_cbcl__soc_006
  - mh_p_cbcl__soc_007
  - mh_p_cbcl__soc_008
  - mh_p_cbcl__soc_009
  - mh_p_cbcl__soc_010
  - mh_p_cbcl__tho_002
  - mh_p_cbcl__tho_003
  - mh_p_cbcl__tho_004
  - mh_p_cbcl__tho_005
  - mh_p_cbcl__tho_006
  - mh_p_cbcl__tho_008
  - mh_p_cbcl__tho_009
  - mh_p_cbcl__tho_012
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl

compute_mh_p_cbcl_nm(
  data,
  name = "mh_p_cbcl_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl is vector of all column names used to compute summary score of mh_p_cbcl scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl_nm(data) |>
  select(
    any_of(c("mh_p_cbcl_nm", vars_mh_p_cbcl))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__dsm__adhd

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): Number missing"

Description

Computes the summary score mh_p_cbcl__dsm__adhd_nm Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - ADHD): Number missing

- *Summarized variables:*
  - mh_p_cbcl__attn__adhd_001
  - mh_p_cbcl__attn__adhd_002
  - mh_p_cbcl__attn__adhd_003
  - mh_p_cbcl__aggr__adhd_001
  - mh_p_cbcl__attn__adhd_004
  - mh_p_cbcl__attn__adhd_005
  - mh_p_cbcl__othpr__adhd_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__dsm__adhd

compute_mh_p_cbcl__dsm__adhd_nm(
  data,
  name = "mh_p_cbcl__dsm__adhd_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__dsm__adhd is vector of all column names used to compute summary score of mh_p_cbcl__dsm__adhd scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__adhd_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__adhd_nm", vars_mh_p_cbcl__dsm__adhd))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__dsm__anx

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety): Number missing"

Description

Computes the summary score `mh_p_cbcl__dsm__anx_nm` Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Anxiety): Number missing

- *Summarized variables:*
  - `mh_p_cbcl__soc__anx_001`
  - `mh_p_cbcl__anxdep__anx_007`
  - `mh_p_cbcl__anxdep__anx_001`
  - `mh_p_cbcl__anxdep__anx_002`
  - `mh_p_cbcl__anxdep__anx_003`
  - `mh_p_cbcl__anxdep__anx_004`
  - `mh_p_cbcl__som__anx_001`
  - `mh_p_cbcl__anxdep__anx_005`
  - `mh_p_cbcl__anxdep__anx_006`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__dsm__anx

compute_mh_p_cbcl__dsm__anx_nm(
  data,
  name = "mh_p_cbcl__dsm__anx_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__dsm__anx is vector of all column names used to compute summary score of mh_p_cbcl__dsm__anx scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__anx_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__anx_nm", vars_mh_p_cbcl__dsm__anx))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__dsm__cond

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Conduct problems): Number missing"

Description

Computes the summary score mh_p_cbcl__dsm__cond_nm Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Conduct problems): Number missing

- *Summarized variables:*
  - mh_p_cbcl__rule__cond_010
  - mh_p_cbcl__rule__cond_011
  - mh_p_cbcl__othpr__cond_001
  - mh_p_cbcl__aggr__cond_001
  - mh_p_cbcl__aggr__cond_002
  - mh_p_cbcl__rule__cond_001
  - mh_p_cbcl__rule__cond_002

  - mh_p_cbcl__aggr__cond_003
  - mh_p_cbcl__rule__cond_003
  - mh_p_cbcl__rule__cond_004
  - mh_p_cbcl__aggr__cond_004
  - mh_p_cbcl__rule__cond_005
  - mh_p_cbcl__rule__cond_006
  - mh_p_cbcl__rule__cond_007
  - mh_p_cbcl__rule__cond_008
  - mh_p_cbcl__rule__cond_009
  - mh_p_cbcl__aggr__cond_005
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__dsm__cond

compute_mh_p_cbcl__dsm__cond_nm(
  data,
  name = "mh_p_cbcl__dsm__cond_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__dsm__cond is vector of all column names used to compute summary score of mh_p_cbcl__dsm__cond scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__cond_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__cond_nm", vars_mh_p_cbcl__dsm__cond))
  )

## End(Not run)
```

`vars_mh_p_cbcl__dsm__dep`

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): Number missing"

Description

Computes the summary score `mh_p_cbcl__dsm__dep_nm` Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Depressive problems): Number missing

- *Summarized variables:*
  - `mh_p_cbcl__wthdep__dep_001`
  - `mh_p_cbcl__tho__dep_003`
  - `mh_p_cbcl__wthdep__dep_002`
  - `mh_p_cbcl__wthdep__dep_003`
  - `mh_p_cbcl__anxdep__dep_001`
  - `mh_p_cbcl__tho__dep_001`
  - `mh_p_cbcl__othpr__dep_001`
  - `mh_p_cbcl__anxdep__dep_002`
  - `mh_p_cbcl__anxdep__dep_003`
  - `mh_p_cbcl__som__dep_001`
  - `mh_p_cbcl__tho__dep_002`
  - `mh_p_cbcl__othpr__dep_002`
  - `mh_p_cbcl__anxdep__dep_004`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__dsm__dep

compute_mh_p_cbcl__dsm__dep_nm(
  data,
  name = "mh_p_cbcl__dsm__dep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__dsm__dep is vector of all column names used to compute summary score of mh_p_cbcl__dsm__dep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__dep_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__dep_nm", vars_mh_p_cbcl__dsm__dep))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__dsm__opp

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Oppositional Defiant problems): Number missing"

Description

Computes the summary score mh_p_cbcl__dsm__opp_nm Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Oppositional Defiant problems): Number missing

- *Summarized variables:*
  - mh_p_cbcl__aggr__opp_001
  - mh_p_cbcl__aggr__opp_002
  - mh_p_cbcl__aggr__opp_003
  - mh_p_cbcl__aggr__opp_004
  - mh_p_cbcl__aggr__opp_005
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__dsm__opp

compute_mh_p_cbcl__dsm__opp_nm(
  data,
  name = "mh_p_cbcl__dsm__opp_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__dsm__opp is vector of all column names used to compute summary score of mh_p_cbcl__dsm__opp scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__opp_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__opp_nm", vars_mh_p_cbcl__dsm__opp))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__dsm__somat

Compute "Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): Number missing"

Description

Computes the summary score mh_p_cbcl__dsm__somat_nm Child Behavior Checklist [Parent] (DSM-5 Oriented Scale - Somatic complaints): Number missing

- *Summarized variables:*
  - mh_p_cbcl__som__somat_001
  - mh_p_cbcl__som__somat_002
  - mh_p_cbcl__som__somat_003
  - mh_p_cbcl__som__somat_004
  - mh_p_cbcl__som__somat_005
  - mh_p_cbcl__som__somat_006
  - mh_p_cbcl__som__somat_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__dsm__somat

compute_mh_p_cbcl__dsm__somat_nm(
  data,
  name = "mh_p_cbcl__dsm__somat_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__dsm__somat is vector of all column names used to compute summary score of mh_p_cbcl__dsm__somat scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__dsm__somat_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__dsm__somat_nm", vars_mh_p_cbcl__dsm__somat))
  )

## End(Not run)
```

`vars_mh_p_cbcl__ocd` *Compute "Child Behavior Checklist [Parent] (Obsessive-Compulsive Problems): Number missing"*

Description

Computes the summary score `mh_p_cbcl__ocd_nm` Child Behavior Checklist [Parent] (Obsessive-Compulsive Problems): Number missing

- *Summarized variables:*
  - `mh_p_cbcl__tho_001`
  - `mh_p_cbcl__anxdep__anx_007`
  - `mh_p_cbcl__anxdep__anx_003`
  - `mh_p_cbcl__anxdep_001`
  - `mh_p_cbcl__anxdep__dep_003`
  - `mh_p_cbcl__tho_007`
  - `mh_p_cbcl__tho_010`
  - `mh_p_cbcl__tho_011`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__ocd

compute_mh_p_cbcl__ocd_nm(
  data,
  name = "mh_p_cbcl__ocd_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__ocd is vector of all column names used to compute summary score of mh_p_cbcl__ocd scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__ocd_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__ocd_nm", vars_mh_p_cbcl__ocd))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__sct *Compute "Child Behavior Checklist [Parent] (Sluggish Cognitive Tempo): Number missing"*

Description

Computes the summary score mh_p_cbcl__sct_nm Child Behavior Checklist [Parent] (Sluggish Cognitive Tempo): Number missing

- *Summarized variables:*
  - mh_p_cbcl__wthdep__dep_002
  - mh_p_cbcl__attn_002
  - mh_p_cbcl__attn_003
  - mh_p_cbcl__attn_005
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__sct

compute_mh_p_cbcl__sct_nm(
  data,
  name = "mh_p_cbcl__sct_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__sct is vector of all column names used to compute summary score of mh_p_cbcl__sct scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__sct_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__sct_nm", vars_mh_p_cbcl__sct))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__strs *Compute "Child Behavior Checklist [Parent] (Stress): Number missing"*

Description

Computes the summary score mh_p_cbcl__strs_nm Child Behavior Checklist [Parent] (Stress): Number missing

- *Summarized variables:*
  - mh_p_cbcl__aggr__opp_001
  - mh_p_cbcl__attn__adhd_002
  - mh_p_cbcl__tho_001
  - mh_p_cbcl__wthdep__dep_002
  - mh_p_cbcl__soc__anx_001
  - mh_p_cbcl__wthdep_005
  - mh_p_cbcl__anxdep__anx_003
  - mh_p_cbcl__soc_004
  - mh_p_cbcl__anxdep__anx_004
  - mh_p_cbcl__som__anx_001
  - mh_p_cbcl__anxdep__anx_005
  - mh_p_cbcl__anxdep__dep_003
  - mh_p_cbcl__wthdep_003
  - mh_p_cbcl__aggr_004
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__strs

compute_mh_p_cbcl__strs_nm(
  data,
  name = "mh_p_cbcl__strs_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

`vars_mh_p_cbcl__strs` is vector of all column names used to compute summary score of `mh_p_cbcl__strs` scores.

Value

tbl. see `combine`.

Examples

```
## Not run:
compute_mh_p_cbcl__strs_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__strs_nm", vars_mh_p_cbcl__strs))
  )

## End(Not run)
```

`vars_mh_p_cbcl__synd__aggr` *Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): Number missing"*

Description

Computes the summary score `mh_p_cbcl__synd__aggr_nm` Child Behavior Checklist [Parent] (Syndrome Scale - Aggressive behavior): Number missing

- *Summarized variables:*
  - `mh_p_cbcl__aggr__opp_001`
  - `mh_p_cbcl__aggr__adhd_001`
  - `mh_p_cbcl__aggr__cond_001`
  - `mh_p_cbcl__aggr_001`
  - `mh_p_cbcl__aggr_002`
  - `mh_p_cbcl__aggr__cond_002`
  - `mh_p_cbcl__aggr__opp_002`
  - `mh_p_cbcl__aggr__opp_003`
  - `mh_p_cbcl__aggr__cond_003`
  - `mh_p_cbcl__aggr__cond_004`
  - `mh_p_cbcl__aggr_003`
  - `mh_p_cbcl__aggr__opp_004`
  - `mh_p_cbcl__aggr_004`
  - `mh_p_cbcl__aggr_005`
  - `mh_p_cbcl__aggr_006`
  - `mh_p_cbcl__aggr_007`

  - mh_p_cbcl__aggr__opp_005
  - mh_p_cbcl__aggr__cond_005
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__aggr

compute_mh_p_cbcl__synd__aggr_nm(
  data,
  name = "mh_p_cbcl__synd__aggr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__aggr is vector of all column names used to compute summary score of mh_p_cbcl__synd__aggr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__aggr_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__aggr_nm", vars_mh_p_cbcl__synd__aggr))
  )

## End(Not run)
```

vars_mh_p_cbcl__synd__anxdep

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): Number missing"

Description

Computes the summary score mh_p_cbcl__synd__anxdep_nm Child Behavior Checklist [Parent] (Syndrome Scale - Anxious/Depressed): Number missing

- *Summarized variables:*
  - mh_p_cbcl__anxdep__anx_007
  - mh_p_cbcl__anxdep__dep_001
  - mh_p_cbcl__anxdep__anx_001
  - mh_p_cbcl__anxdep__anx_002
  - mh_p_cbcl__anxdep__anx_003
  - mh_p_cbcl__anxdep_001
  - mh_p_cbcl__anxdep_002
  - mh_p_cbcl__anxdep__dep_002
  - mh_p_cbcl__anxdep__anx_004
  - mh_p_cbcl__anxdep__anx_005
  - mh_p_cbcl__anxdep__dep_003
  - mh_p_cbcl__anxdep__anx_006
  - mh_p_cbcl__anxdep__dep_004
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__anxdep

compute_mh_p_cbcl__synd__anxdep_nm(
  data,
  name = "mh_p_cbcl__synd__anxdep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.

combine logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__anxdep is vector of all column names used to compute summary score of mh_p_cbcl__synd__anxdep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__anxdep_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__anxdep_nm", vars_mh_p_cbcl__synd__anxdep))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__synd__attn

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Attention problems): Number missing"

Description

Computes the summary score mh_p_cbcl__synd__attn_nm Child Behavior Checklist [Parent] (Syndrome Scale - Attention problems): Number missing

- *Summarized variables:*
  - mh_p_cbcl__attn_001
  - mh_p_cbcl__attn__adhd_001
  - mh_p_cbcl__attn__adhd_002
  - mh_p_cbcl__attn__adhd_003
  - mh_p_cbcl__attn_002
  - mh_p_cbcl__attn_003
  - mh_p_cbcl__attn__adhd_004
  - mh_p_cbcl__attn_004
  - mh_p_cbcl__attn__adhd_005
  - mh_p_cbcl__attn_005
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__attn

compute_mh_p_cbcl__synd__attn_nm(
  data,
  name = "mh_p_cbcl__synd__attn_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__attn is vector of all column names used to compute summary score of mh_p_cbcl__synd__attn scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__attn_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__attn_nm", vars_mh_p_cbcl__synd__attn))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__synd__ext

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Externalizing): Number missing"

Description

Computes the summary score `mh_p_cbcl__synd__ext_nm` Child Behavior Checklist [Parent] (Syndrome Scale - Externalizing): Number missing

- *Summarized variables:*
  - `mh_p_cbcl__rule_001`
  - `mh_p_cbcl__rule__cond_010`
  - `mh_p_cbcl__rule_006`
  - `mh_p_cbcl__rule__cond_011`
  - `mh_p_cbcl__rule__cond_001`
  - `mh_p_cbcl__rule__cond_002`
  - `mh_p_cbcl__rule__cond_003`
  - `mh_p_cbcl__rule__cond_004`
  - `mh_p_cbcl__rule_002`
  - `mh_p_cbcl__rule__cond_005`
  - `mh_p_cbcl__rule__cond_006`
  - `mh_p_cbcl__rule_003`
  - `mh_p_cbcl__rule__cond_007`
  - `mh_p_cbcl__rule__cond_008`
  - `mh_p_cbcl__rule__cond_009`
  - `mh_p_cbcl__rule_004`
  - `mh_p_cbcl__rule_005`
  - `mh_p_cbcl__aggr__opp_001`
  - `mh_p_cbcl__aggr__adhd_001`
  - `mh_p_cbcl__aggr__cond_001`
  - `mh_p_cbcl__aggr_001`
  - `mh_p_cbcl__aggr_002`
  - `mh_p_cbcl__aggr__cond_002`
  - `mh_p_cbcl__aggr__opp_002`
  - `mh_p_cbcl__aggr__opp_003`
  - `mh_p_cbcl__aggr__cond_003`
  - `mh_p_cbcl__aggr__cond_004`
  - `mh_p_cbcl__aggr_003`
  - `mh_p_cbcl__aggr__opp_004`
  - `mh_p_cbcl__aggr_004`
  - `mh_p_cbcl__aggr_005`
  - `mh_p_cbcl__aggr_006`
  - `mh_p_cbcl__aggr_007`
  - `mh_p_cbcl__aggr__opp_005`
  - `mh_p_cbcl__aggr__cond_005`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__ext

compute_mh_p_cbcl__synd__ext_nm(
  data,
  name = "mh_p_cbcl__synd__ext_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__ext is vector of all column names used to compute summary score of mh_p_cbcl__synd__ext scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__ext_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__ext_nm", vars_mh_p_cbcl__synd__ext))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__synd__int

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Internalizing): Number missing"

Description

Computes the summary score `mh_p_cbcl__synd__int_nm` Child Behavior Checklist [Parent] (Syndrome Scale - Internalizing): Number missing

- *Summarized variables:*
  - `mh_p_cbcl__anxdep__anx_007`
  - `mh_p_cbcl__anxdep__dep_001`
  - `mh_p_cbcl__anxdep__anx_001`
  - `mh_p_cbcl__anxdep__anx_002`
  - `mh_p_cbcl__anxdep__anx_003`
  - `mh_p_cbcl__anxdep_001`
  - `mh_p_cbcl__anxdep_002`
  - `mh_p_cbcl__anxdep__dep_002`
  - `mh_p_cbcl__anxdep__anx_004`
  - `mh_p_cbcl__anxdep__anx_005`
  - `mh_p_cbcl__anxdep__dep_003`
  - `mh_p_cbcl__anxdep__anx_006`
  - `mh_p_cbcl__anxdep__dep_004`
  - `mh_p_cbcl__wthdep__dep_001`
  - `mh_p_cbcl__wthdep__dep_002`
  - `mh_p_cbcl__wthdep__dep_003`
  - `mh_p_cbcl__wthdep_005`
  - `mh_p_cbcl__wthdep_001`
  - `mh_p_cbcl__wthdep_002`
  - `mh_p_cbcl__wthdep_003`
  - `mh_p_cbcl__wthdep_004`
  - `mh_p_cbcl__som__anx_001`
  - `mh_p_cbcl__som_001`
  - `mh_p_cbcl__som_002`
  - `mh_p_cbcl__som__dep_001`
  - `mh_p_cbcl__som__somat_001`
  - `mh_p_cbcl__som__somat_002`
  - `mh_p_cbcl__som__somat_003`
  - `mh_p_cbcl__som__somat_004`
  - `mh_p_cbcl__som__somat_005`
  - `mh_p_cbcl__som__somat_006`
  - `mh_p_cbcl__som__somat_007`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__int

compute_mh_p_cbcl__synd__int_nm(
  data,
  name = "mh_p_cbcl__synd__int_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__int is vector of all column names used to compute summary score of mh_p_cbcl__synd__int scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__int_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__int_nm", vars_mh_p_cbcl__synd__int))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__synd__othpr

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Other problems): Number missing"

Description

Computes the summary score mh_p_cbcl__synd__othpr_nm Child Behavior Checklist [Parent] (Syndrome Scale - Other problems): Number missing

- *Summarized variables:*
  - mh_p_cbcl__othpr_001
  - mh_p_cbcl__othpr_002
  - mh_p_cbcl__othpr_009
  - mh_p_cbcl__othpr_010
  - mh_p_cbcl__othpr_011
  - mh_p_cbcl__othpr_012
  - mh_p_cbcl__othpr__cond_001
  - mh_p_cbcl__othpr__dep_001
  - mh_p_cbcl__othpr_003
  - mh_p_cbcl__othpr_004
  - mh_p_cbcl__othpr_005
  - mh_p_cbcl__othpr_006
  - mh_p_cbcl__othpr_007
  - mh_p_cbcl__othpr__dep_002
  - mh_p_cbcl__othpr__adhd_001
  - mh_p_cbcl__othpr_008
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__othpr

compute_mh_p_cbcl__synd__othpr_nm(
  data,
  name = "mh_p_cbcl__synd__othpr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__othpr is vector of all column names used to compute summary score of mh_p_cbcl__synd__othpr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__othpr_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__othpr_nm", vars_mh_p_cbcl__synd__othpr))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__synd__rule

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): Number missing"

Description

Computes the summary score mh_p_cbcl__synd__rule_nm Child Behavior Checklist [Parent] (Syndrome Scale - Rule breaking behavior): Number missing

- *Summarized variables:*
  - mh_p_cbcl__rule_001
  - mh_p_cbcl__rule__cond_010
  - mh_p_cbcl__rule_006
  - mh_p_cbcl__rule__cond_011
  - mh_p_cbcl__rule__cond_001
  - mh_p_cbcl__rule__cond_002
  - mh_p_cbcl__rule__cond_003
  - mh_p_cbcl__rule__cond_004
  - mh_p_cbcl__rule_002
  - mh_p_cbcl__rule__cond_005
  - mh_p_cbcl__rule__cond_006
  - mh_p_cbcl__rule_003
  - mh_p_cbcl__rule__cond_007
  - mh_p_cbcl__rule__cond_008
  - mh_p_cbcl__rule__cond_009
  - mh_p_cbcl__rule_004

    - mh_p_cbcl__rule_005
  - *Excluded values:*
    - 777
    - 999

Usage

```
vars_mh_p_cbcl__synd__rule

compute_mh_p_cbcl__synd__rule_nm(
  data,
  name = "mh_p_cbcl__synd__rule_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__rule is vector of all column names used to compute summary score of mh_p_cbcl__synd__rule scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__rule_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__rule_nm", vars_mh_p_cbcl__synd__rule))
  )

## End(Not run)
```

vars_mh_p_cbcl__synd__soc

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Social): Number missing"

Description

Computes the summary score mh_p_cbcl__synd__soc_nm Child Behavior Checklist [Parent] (Syndrome Scale -Social): Number missing

- *Summarized variables:*
  - mh_p_cbcl__soc__anx_001
  - mh_p_cbcl__soc_001
  - mh_p_cbcl__soc_002
  - mh_p_cbcl__soc_003
  - mh_p_cbcl__soc_004
  - mh_p_cbcl__soc_005
  - mh_p_cbcl__soc_006
  - mh_p_cbcl__soc_007
  - mh_p_cbcl__soc_008
  - mh_p_cbcl__soc_009
  - mh_p_cbcl__soc_010
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__soc

compute_mh_p_cbcl__synd__soc_nm(
  data,
  name = "mh_p_cbcl__synd__soc_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__soc is vector of all column names used to compute summary score of mh_p_cbcl__synd__soc scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__soc_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__soc_nm", vars_mh_p_cbcl__synd__soc))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__synd__som

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): Number missing"

Description

Computes the summary score mh_p_cbcl__synd__som_nm Child Behavior Checklist [Parent] (Syndrome Scale - Somatic complaints): Number missing

- *Summarized variables:*
  - mh_p_cbcl__som__anx_001
  - mh_p_cbcl__som_001
  - mh_p_cbcl__som_002
  - mh_p_cbcl__som__dep_001
  - mh_p_cbcl__som__somat_001
  - mh_p_cbcl__som__somat_002
  - mh_p_cbcl__som__somat_003
  - mh_p_cbcl__som__somat_004
  - mh_p_cbcl__som__somat_005
  - mh_p_cbcl__som__somat_006
  - mh_p_cbcl__som__somat_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__som

compute_mh_p_cbcl__synd__som_nm(
  data,
  name = "mh_p_cbcl__synd__som_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__som is vector of all column names used to compute summary score of mh_p_cbcl__synd__som scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__som_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__som_nm", vars_mh_p_cbcl__synd__som))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__synd__tho

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Thought problems): Number missing"

Description

Computes the summary score mh_p_cbcl__synd__tho_nm Child Behavior Checklist [Parent] (Syndrome Scale - Thought problems): Number missing

- *Summarized variables:*
  - mh_p_cbcl__tho_001
  - mh_p_cbcl__tho__dep_003
  - mh_p_cbcl__tho__dep_001
  - mh_p_cbcl__tho_002
  - mh_p_cbcl__tho_003
  - mh_p_cbcl__tho_004
  - mh_p_cbcl__tho_005
  - mh_p_cbcl__tho_006
  - mh_p_cbcl__tho_007
  - mh_p_cbcl__tho_008
  - mh_p_cbcl__tho__dep_002
  - mh_p_cbcl__tho_009
  - mh_p_cbcl__tho_010
  - mh_p_cbcl__tho_011
  - mh_p_cbcl__tho_012
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__tho

compute_mh_p_cbcl__synd__tho_nm(
  data,
  name = "mh_p_cbcl__synd__tho_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__tho is vector of all column names used to compute summary score of mh_p_cbcl__synd__tho scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__tho_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__tho_nm", vars_mh_p_cbcl__synd__tho))
  )

## End(Not run)
```

---

vars_mh_p_cbcl__synd__wthdep

Compute "Child Behavior Checklist [Parent] (Syndrome Scale - Withdrawn/Depressed): Number missing"

Description

Computes the summary score mh_p_cbcl__synd__wthdep_nm Child Behavior Checklist [Parent] (Syndrome Scale - Withdrawn/Depressed): Number missing

- *Summarized variables:*
  - mh_p_cbcl__wthdep__dep_001
  - mh_p_cbcl__wthdep__dep_002
  - mh_p_cbcl__wthdep__dep_003
  - mh_p_cbcl__wthdep_005
  - mh_p_cbcl__wthdep_001
  - mh_p_cbcl__wthdep_002
  - mh_p_cbcl__wthdep_003
  - mh_p_cbcl__wthdep_004
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_p_cbcl__synd__wthdep

compute_mh_p_cbcl__synd__wthdep_nm(
  data,
  name = "mh_p_cbcl__synd__wthdep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_cbcl__synd__wthdep is vector of all column names used to compute summary score of mh_p_cbcl__synd__wthdep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_cbcl__synd__wthdep_nm(data) |>
  select(
    any_of(c("mh_p_cbcl__synd__wthdep_nm", vars_mh_p_cbcl__synd__wthdep))
  )

## End(Not run)
```

---

vars_mh_p_ders__attun *Compute "Difficulties in Emotion Regulation Scale [Parent] (Attuned): Mean"*

Description

Computes the summary score mh_p_ders__attun_mean Difficulties in Emotion Regulation Scale [Parent] (Attuned): Mean

- *Summarized variables:*
  - mh_p_ders__attun_001
  - mh_p_ders__attun_002
  - mh_p_ders__attun_003
  - mh_p_ders__attun_004
  - mh_p_ders__attun_005
  - mh_p_ders__attun_006
- *Excluded values:*
  - 999
  - 777
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_mh_p_ders__attun

compute_mh_p_ders__attun_mean(
  data,
  name = "mh_p_ders__attun_mean",
  max_na = 1,
  exclude = c("999", "777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ders__attun is vector of all column names used to compute summary score of mh_p_ders__attun scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_ders__attun_mean(data) |>
  select(
    any_of(c("mh_p_ders__attun_mean", vars_mh_p_ders__attun))
  )

## End(Not run)
```

---

vars_mh_p_ders__catast

Compute "Difficulties in Emotion Regulation Scale [Parent] (Catastrophize): Mean"

Description

Computes the summary score `mh_p_ders__catast_mean` Difficulties in Emotion Regulation Scale [Parent] (Catastrophize): Mean

- *Summarized variables:*
  - `mh_p_ders__catast_001`
  - `mh_p_ders__catast_002`
  - `mh_p_ders__catast_003`
  - `mh_p_ders__catast_004`
  - `mh_p_ders__catast_005`
  - `mh_p_ders__catast_006`
  - `mh_p_ders__catast_007`
  - `mh_p_ders__catast_008`
  - `mh_p_ders__catast_009`
  - `mh_p_ders__catast_010`
  - `mh_p_ders__catast_011`
  - `mh_p_ders__catast_012`
- *Excluded values:*
  - 999
  - 777
- *Validation criterion:* maximally 2 of 12 items missing

Usage

```
vars_mh_p_ders__catast

compute_mh_p_ders__catast_mean(
  data,
  name = "mh_p_ders__catast_mean",
```

```
  max_na = 2,
  exclude = c("999", "777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ders__catast is vector of all column names used to compute summary score of mh_p_ders__catast scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_ders__catast_mean(data) |>
  select(
    any_of(c("mh_p_ders__catast_mean", vars_mh_p_ders__catast))
  )

## End(Not run)
```

---

vars_mh_p_ders__distract

Compute "Difficulties in Emotion Regulation Scale [Parent] (Distracted): Mean"

Description

Computes the summary score mh_p_ders__distract_mean Difficulties in Emotion Regulation Scale [Parent] (Distracted): Mean

- *Summarized variables:*
  - mh_p_ders__distract_001

  - mh_p_ders__distract_002
  - mh_p_ders__distract_003
  - mh_p_ders__distract_004
- *Excluded values:*
  - 999
  - 777
- *Validation criterion:* none of 4 items missing

Usage

```
vars_mh_p_ders__distract

compute_mh_p_ders__distract_mean(
  data,
  name = "mh_p_ders__distract_mean",
  max_na = 0,
  exclude = c("999", "777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ders__distract is vector of all column names used to compute summary score of mh_p_ders__distract scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_ders__distract_mean(data) |>
  select(
    any_of(c("mh_p_ders__distract_mean", vars_mh_p_ders__distract))
  )

## End(Not run)
```

vars_mh_p_ders__negscnd

Compute "Difficulties in Emotion Regulation Scale [Parent] (Negative Secondary): Mean"

Description

Computes the summary score mh_p_ders__negscnd_mean Difficulties in Emotion Regulation Scale [Parent] (Negative Secondary): Mean

- *Summarized variables:*
  - mh_p_ders__negscnd_001
  - mh_p_ders__negscnd_002
  - mh_p_ders__negscnd_003
  - mh_p_ders__negscnd_004
  - mh_p_ders__negscnd_005
  - mh_p_ders__negscnd_006
  - mh_p_ders__negscnd_007
- *Excluded values:*
  - 999
  - 777
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_mh_p_ders__negscnd

compute_mh_p_ders__negscnd_mean(
  data,
  name = "mh_p_ders__negscnd_mean",
  max_na = 1,
  exclude = c("999", "777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ders__negscnd is vector of all column names used to compute summary score of mh_p_ders__negscnd scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_ders__negscnd_mean(data) |>
  select(
    any_of(c("mh_p_ders__negscnd_mean", vars_mh_p_ders__negscnd))
  )

## End(Not run)
```

---

vars_mh_p_eatq__actv *Compute "Early Adolescent Temperament Questionnaire [Parent] (Activation): Mean "*

Description

Computes the summary score mh_p_eatq__actv_mean Early Adolescent Temperament Questionnaire [Parent] (Activation): Mean

- *Summarized variables:*
  - mh_p_eatq__actv_001
  - mh_p_eatq__actv_002
  - mh_p_eatq__actv_003
  - mh_p_eatq__actv_004
  - mh_p_eatq__actv_005
  - mh_p_eatq__actv_006
  - mh_p_eatq__actv_007
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_mh_p_eatq__actv

compute_mh_p_eatq__actv_mean(
  data,
  name = "mh_p_eatq__actv_mean",
  max_na = 1,
```

```
  combine = TRUE,
  revert = FALSE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.
revert	logical, If TRUE, the summary score will be reverse scored.

Format

vars_mh_p_eatq__actv is a character vector of all column names used to compute summary score of mh_p_eatq__actv_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__actv_mean(data)
select(
  data,
  any_of(c("mh_p_eatq__actv_mean", vars_mh_p_eatq__actv))
)

## End(Not run)
```

---

vars_mh_p_eatq__affl *Compute "Early Adolescent Temperament Questionnaire [Parent] (Affiliation): Mean"*

Description

Computes the summary score mh_p_eatq__affl_mean Early Adolescent Temperament Questionnaire [Parent] (Affiliation): Mean

- *Summarized variables:*
  - mh_p_eatq__affl_001

  - mh_p_eatq__affl_002
  - mh_p_eatq__affl_003
  - mh_p_eatq__affl_004
  - mh_p_eatq__affl_005
  - mh_p_eatq__affl_006
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_mh_p_eatq__affl

compute_mh_p_eatq__affl_mean(
  data,
  name = "mh_p_eatq__affl_mean",
  max_na = 1,
  combine = TRUE,
  revert = FALSE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.
revert	logical, If TRUE, the summary score will be reverse scored.

Format

vars_mh_p_eatq__affl is a character vector of all column names used to compute summary score of mh_p_eatq__affl_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__affl_mean(data)
select(
  data,
  any_of(c("mh_p_eatq__affl_mean", vars_mh_p_eatq__affl))
)
```

```
## End(Not run)
```

`vars_mh_p_eatq__aggr` *Compute "Early Adolescent Temperament Questionnaire [Parent] (Aggression): Mean"*

Description

Computes the summary score `mh_p_eatq__aggr_mean` Early Adolescent Temperament Questionnaire [Parent] (Aggression): Mean

- *Summarized variables:*
  - `mh_p_eatq__aggr_001`
  - `mh_p_eatq__aggr_002`
  - `mh_p_eatq__aggr_003`
  - `mh_p_eatq__aggr_004`
  - `mh_p_eatq__aggr_005`
  - `mh_p_eatq__aggr_006`
  - `mh_p_eatq__aggr_007`
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_mh_p_eatq__aggr

compute_mh_p_eatq__aggr_mean(
  data,
  name = "mh_p_eatq__aggr_mean",
  max_na = 1,
  combine = TRUE,
  revert = FALSE
)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`max_na`	integer, Maximum number of missing values allowed in the summary score. `NULL` means no limit.
`combine`	logical, If `TRUE`, the summary score will be appended to the input data frame. If `FALSE`, the summary score will be returned as a separate data frame.
`revert`	logical, If `TRUE`, the summary score will be reverse scored.

Format

vars_mh_p_eatq__aggr is a character vector of all column names used to compute summary score of mh_p_eatq__aggr_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__aggr_mean(data)
select(
  data,
  any_of(c("mh_p_eatq__aggr_mean", vars_mh_p_eatq__aggr))
)

## End(Not run)
```

---

vars_mh_p_eatq__attn *Compute "Early Adolescent Temperament Questionnaire [Parent] (Attention): Mean"*

Description

Computes the summary score mh_p_eatq__attn_mean Early Adolescent Temperament Questionnaire [Parent] (Attention): Mean

- *Summarized variables:*
  - mh_p_eatq__attn_001
  - mh_p_eatq__attn_002
  - mh_p_eatq__attn_003
  - mh_p_eatq__attn_004
  - mh_p_eatq__attn_005
  - mh_p_eatq__attn_006
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_mh_p_eatq__attn

compute_mh_p_eatq__attn_mean(
  data,
  name = "mh_p_eatq__attn_mean",
```

```
  max_na = 1,
  combine = TRUE,
  revert = FALSE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.
revert	logical, If TRUE, the summary score will be reverse scored.

Format

vars_mh_p_eatq__attn is a character vector of all column names used to compute summary score of mh_p_eatq__attn_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__attn_mean(data)
select(
  data,
  any_of(c("mh_p_eatq__attn_mean", vars_mh_p_eatq__attn))
)

## End(Not run)
```

---

vars_mh_p_eatq__depm *Compute "Early Adolescent Temperament Questionnaire [Parent] (Depressive Mood): Mean"*

Description

Computes the summary score mh_p_eatq__depm_mean Early Adolescent Temperament Questionnaire [Parent] (Depressive Mood): Mean

- *Summarized variables:*
  - mh_p_eatq__depm_001
  - mh_p_eatq__depm_002
  - mh_p_eatq__depm_003
  - mh_p_eatq__depm_004
  - mh_p_eatq__depm_005
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_mh_p_eatq__depm

compute_mh_p_eatq__depm_mean(
  data,
  name = "mh_p_eatq__depm_mean",
  max_na = 1,
  combine = TRUE,
  revert = FALSE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.
revert	logical, If TRUE, the summary score will be reverse scored.

Format

vars_mh_p_eatq__depm is a character vector of all column names used to compute summary score of mh_p_eatq__depm_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__depm_mean(data)
select(
  data,
  any_of(c("mh_p_eatq__depm_mean", vars_mh_p_eatq__depm))
)

## End(Not run)
```

`vars_mh_p_eatq__fear` *Compute "Early Adolescent Temperament Questionnaire [Parent] (Fear): Mean"*

Description

Computes the summary score `mh_p_eatq__fear_mean` Early Adolescent Temperament Questionnaire [Parent] (Fear): Mean

- *Summarized variables:*
  - `mh_p_eatq__fear_001`
  - `mh_p_eatq__fear_002`
  - `mh_p_eatq__fear_003`
  - `mh_p_eatq__fear_004`
  - `mh_p_eatq__fear_005`
  - `mh_p_eatq__fear_006`
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_mh_p_eatq__fear

compute_mh_p_eatq__fear_mean(
  data,
  name = "mh_p_eatq__fear_mean",
  max_na = 1,
  combine = TRUE,
  revert = FALSE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.
revert	logical, If TRUE, the summary score will be reverse scored.

Format

vars_mh_p_eatq__fear is a character vector of all column names used to compute summary score of mh_p_eatq__fear_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__fear_mean(data)
select(
  data,
  any_of(c(
    "mh_p_eatq__fear_mean",
    vars_mh_p_eatq__fear
  ))
)

## End(Not run)
```

---

vars_mh_p_eatq__frust *Compute "Early Adolescent Temperament Questionnaire [Parent] (Frustration): Mean"*

Description

Computes the summary score mh_p_eatq__frust_mean Early Adolescent Temperament Questionnaire [Parent] (Frustration): Mean

- *Summarized variables:*
  - mh_p_eatq__frust_001
  - mh_p_eatq__frust_002

  - mh_p_eatq__frust_003
  - mh_p_eatq__frust_004
  - mh_p_eatq__frust_005
  - mh_p_eatq__frust_006
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 6 items missing

Usage

```
vars_mh_p_eatq__frust

compute_mh_p_eatq__frust_mean(
  data,
  name = "mh_p_eatq__frust_mean",
  max_na = 1,
  combine = TRUE,
  revert = FALSE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.
revert	logical, If TRUE, the summary score will be reverse scored.

Format

vars_mh_p_eatq__frust is a character vector of all column names used to compute summary score of mh_p_eatq__frust_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__frust_mean(data)
select(
  data,
  any_of(c("mh_p_eatq__frust_mean", vars_mh_p_eatq__frust))
)
```

```
## End(Not run)
```

---

vars_mh_p_eatq__inhib *Compute "Early Adolescent Temperament Questionnaire [Parent] (Inhibition): Mean"*

Description

Computes the summary score mh_p_eatq__inhib_mean Early Adolescent Temperament Questionnaire [Parent] (Inhibition): Mean

- *Summarized variables:*
  - mh_p_eatq__inhib_001
  - mh_p_eatq__inhib_002
  - mh_p_eatq__inhib_003
  - mh_p_eatq__inhib_004
  - mh_p_eatq__inhib_005
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_mh_p_eatq__inhib

compute_mh_p_eatq__inhib_mean(
  data,
  name = "mh_p_eatq__inhib_mean",
  max_na = 1,
  combine = TRUE,
  revert = FALSE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.
revert	logical, If TRUE, the summary score will be reverse scored.

Format

vars_mh_p_eatq__inhib is a character vector of all column names used to compute summary score of mh_p_eatq__inhib_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__inhib_mean(data)
select(
  data,
  any_of(c("mh_p_eatq__inhib_mean", vars_mh_p_eatq__inhib))
)

## End(Not run)
```

---

vars_mh_p_eatq__shy *Compute "Early Adolescent Temperament Questionnaire [Parent] (Shyness): Mean"*

Description

Computes the summary score mh_p_eatq__shy_mean Early Adolescent Temperament Questionnaire [Parent] (Shyness): Mean

- *Summarized variables:*
  - mh_p_eatq__shy_001
  - mh_p_eatq__shy_002
  - mh_p_eatq__shy_003
  - mh_p_eatq__shy_004
  - mh_p_eatq__shy_005
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 5 items missing

Usage

```
vars_mh_p_eatq__shy

compute_mh_p_eatq__shy_mean(
  data,
  name = "mh_p_eatq__shy_mean",
  max_na = 1,
  combine = TRUE,
  revert = FALSE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.
revert	logical, If TRUE, the summary score will be reverse scored.

Format

vars_mh_p_eatq__shy is a character vector of all column names used to compute summary score of mh_p_eatq__shy_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__shy_mean(data)
select(
  data,
  any_of(c(
    "mh_p_eatq__shy_mean",
    vars_mh_p_eatq__shy
  ))
)

## End(Not run)
```

---

vars_mh_p_eatq__surg *Compute "Early Adolescent Temperament Questionnaire [Parent] (Surgency): Mean [Validation: No more than 1 missing or declined]"*

Description

Computes the summary score mh_p_eatq__surg_mean Early Adolescent Temperament Questionnaire [Parent] (Surgency): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_p_eatq__surg_001
  - mh_p_eatq__surg_002

  - mh_p_eatq__surg_003
  - mh_p_eatq__surg_004
  - mh_p_eatq__surg_005
  - mh_p_eatq__surg_006
  - mh_p_eatq__surg_007
  - mh_p_eatq__surg_008
  - mh_p_eatq__surg_009

- *Excluded values:* none
- *Validation criterion:* maximally 1 of 9 items missing

Usage

```
vars_mh_p_eatq__surg

compute_mh_p_eatq__surg_mean(
  data,
  name = "mh_p_eatq__surg_mean",
  max_na = 1,
  combine = TRUE,
  revert = FALSE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.
revert	logical, If TRUE, the summary score will be reverse scored.

Format

vars_mh_p_eatq__surg is a character vector of all column names used to compute summary score of mh_p_eatq__surg_mean.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
data <- compute_mh_p_eatq__surg_mean(data)
select(
  data,
  any_of(c("mh_p_eatq__surg_mean", vars_mh_p_eatq__surg))
)

## End(Not run)
```

`vars_mh_p_famhx__alc__moth__fath_indicator`
Compute "Family History [Parent] (Alcohol) Endorsed: Either parent"

Description

Computes the summary score `mh_p_famhx__alc__moth__fath_indicator` (Family History [Parent] (Alcohol) Endorsed: Either parent)

- *Notes:*
  - Following values are recoded as NA prior to any computation
    - 777
    - 888
    - 999
  - Following logic is applied to compute the score:
    - father endorsed `yes` OR mother endorsed `yes` = `1`
    - father endorsed `no` AND mother endorsed `no` = `0`
    - all other cases set to `NA`

Usage

```
vars_mh_p_famhx__alc__moth__fath_indicator

compute_mh_p_famhx__alc__moth__fath_indicator(
  data,
  name = "mh_p_famhx__alc__moth__fath_indicator",
  combine = TRUE
)
```

Arguments

`data`	tibble. A data frame containing the data.
`name`	character. The name of the output column for the computed score.
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: `TRUE`).

Format

a character vector of base name of the check boxes used to compute mh_p_famhx__alc__moth__fath_indicator.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__alc__moth__fath_score

Compute "Family History [Parent] (Alcohol) Endorsed: Parents overall"

Description

Computes the summary score mh_p_famhx__alc__moth__fath_score (Family History [Parent] (Alcohol) Endorsed: Parents overall)

- *Notes:*
  - Following values are recoded as NA prior to any computation
    - 777
    - 888
    - 999
  - Following logic is applied to compute the score:
    - father endorsed no AND mother endorsed no = 0
    - father endorsed yes AND mother endorsed no = 1
    - father endorsed no AND mother endorsed yes = 2
    - father endorsed yes AND mother endorsed yes = 3
    - father endorsed NA AND mother endorsed yes = 4
    - father endorsed yes AND mother endorsed NA = 5
    - all other cases set to NA

Usage

```
vars_mh_p_famhx__alc__moth__fath_score

compute_mh_p_famhx__alc__moth__fath_score(
  data,
  name = "mh_p_famhx__alc__moth__fath_score",
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of base name of the check boxes used to compute `mh_p_famhx__alc__moth__fath_score`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_p_famhx__dep__moth__fath_indicator`
Compute "Family History [Parent] (Depression) Endorsed: Either parent"

Description

Computes the summary score `mh_p_famhx__dep__moth__fath_indicator` (Family History [Parent] (Depression) Endorsed: Either parent)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed `yes` OR mother endorsed `yes` = `1`
    - father endorsed `no` AND mother endorsed `no` = `0`
    - all other cases set to `NA`

Usage

```
vars_mh_p_famhx__dep__moth__fath_indicator

compute_mh_p_famhx__dep__moth__fath_indicator(
  data,
  name = "mh_p_famhx__dep__moth__fath_indicator",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

`data`	tibble. A data frame containing the data.
`name`	character. The name of the output column for the computed score.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: `TRUE`).

Format

a character vector of fields used to compute `mh_p_famhx__dep__moth__fath_indicator`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_p_famhx__dep__moth__fath_score`
Compute "Family History [Parent] (Depression) Endorsed: Parents overall"

Description

Computes the summary score `mh_p_famhx__dep__moth__fath_score` (Family History [Parent] (Depression) Endorsed: Parents overall)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    * father endorsed `no` AND mother endorsed `no` = `0`
    * father endorsed `yes` AND mother endorsed `no` = `1`
    * father endorsed `no` AND mother endorsed `yes` = `2`
    * father endorsed `yes` AND mother endorsed `yes` = `3`
    * father endorsed `NA` AND mother endorsed `yes` = `4`
    * father endorsed `yes` AND mother endorsed `NA` = `5`
    * all other cases set to `NA`

Usage

```
vars_mh_p_famhx__dep__moth__fath_score

compute_mh_p_famhx__dep__moth__fath_score(
  data,
  name = "mh_p_famhx__dep__moth__fath_score",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of base name of the check boxes used to compute mh_p_famhx__dep__moth__fath_score.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__doc__moth__fath_indicator

Compute "Family History [Parent] (Doctor Visit)) Endorsed: Either parent"

Description

Computes the summary score mh_p_famhx__doc__moth__fath_indicator (Family History [Parent] (Doctor Visit)) Endorsed: Either parent)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed yes OR mother endorsed yes = 1
    - father endorsed no AND mother endorsed no = 0
    - all other cases set to NA

Usage

```
vars_mh_p_famhx__doc__moth__fath_indicator

compute_mh_p_famhx__doc__moth__fath_indicator(
  data,
  name = "mh_p_famhx__doc__moth__fath_indicator",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of fields used to compute mh_p_famhx__doc__moth__fath_indicator.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__doc__moth__fath_score

Compute "Family History [Parent] (Doctor Visit) Endorsed: Parents overall"

Description

Computes the summary score mh_p_famhx__doc__moth__fath_score (Family History [Parent] (Doctor Visit) Endorsed: Parents overall)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed no AND mother endorsed no = 0
    - father endorsed yes AND mother endorsed no = 1
    - father endorsed no AND mother endorsed yes = 2
    - father endorsed yes AND mother endorsed yes = 3
    - father endorsed NA AND mother endorsed yes = 4
    - father endorsed yes AND mother endorsed NA = 5
    - all other cases set to NA

Usage

```
vars_mh_p_famhx__doc__moth__fath_score

compute_mh_p_famhx__doc__moth__fath_score(
  data,
  name = "mh_p_famhx__doc__moth__fath_score",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of base name of the check boxes used to compute mh_p_famhx__doc__moth__fath_score.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__drg__moth__fath_indicator

Compute "Family History [Parent] (Drug Use) Endorsed: Either parent"

Description

Computes the summary score mh_p_famhx__drg__moth__fath_indicator (Family History [Parent] (Drug Use) Endorsed: Either parent)

- *Notes:*
  - Following values are recoded as NA prior to any computation
    - 777
    - 888
    - 999
  - Following logic is applied to compute the score:
    - father endorsed yes OR mother endorsed yes = 1
    - father endorsed no AND mother endorsed no = 0
    - all other cases set to NA

Usage

```
vars_mh_p_famhx__drg__moth__fath_indicator

compute_mh_p_famhx__drg__moth__fath_indicator(
  data,
  name = "mh_p_famhx__drg__moth__fath_indicator",
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of base name of the check boxes used to compute mh_p_famhx__drg__moth__fath_indicator.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__drg__moth__fath_score

Compute "Family History [Parent] (Drug Use) Endorsed: Parents overall"

Description

Computes the summary score mh_p_famhx__drg__moth__fath_score (Family History [Parent] (Drug Use) Endorsed: Parents overall)

- *Notes:*
  - Following values are recoded as NA prior to any computation
    - 777
    - 888
    - 999
  - Following logic is applied to compute the score:
    - father endorsed no AND mother endorsed no = 0
    - father endorsed yes AND mother endorsed no = 1
    - father endorsed no AND mother endorsed yes = 2
    - father endorsed yes AND mother endorsed yes = 3
    - father endorsed NA AND mother endorsed yes = 4
    - father endorsed yes AND mother endorsed NA = 5
    - all other cases set to NA

Usage

```
vars_mh_p_famhx__drg__moth__fath_score

compute_mh_p_famhx__drg__moth__fath_score(
  data,
  name = "mh_p_famhx__drg__moth__fath_score",
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of base name of the check boxes used to compute mh_p_famhx__drg__moth__fath_score.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__halluc__moth__fath_indicator

Compute "Family History [Parent] (Hallucinations) Endorsed: Either parent"

Description

Computes the summary score mh_p_famhx__halluc__moth__fath_indicator (Family History [Parent] (Hallucinations) Endorsed: Either parent)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed yes OR mother endorsed yes = 1
    - father endorsed no AND mother endorsed no = 0
    - all other cases set to NA

Usage

```
vars_mh_p_famhx__halluc__moth__fath_indicator

compute_mh_p_famhx__halluc__moth__fath_indicator(
  data,
  name = "mh_p_famhx__halluc__moth__fath_indicator",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of fields used to compute mh_p_famhx__halluc__moth__fath_indicator.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__halluc__moth__fath_score

Compute "Family History [Parent] (Hallucinations) Endorsed: Parents overall"

Description

Computes the summary score mh_p_famhx__halluc__moth__fath_score (Family History [Parent] (Hallucinations) Endorsed: Parents overall)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed no AND mother endorsed no = 0
    - father endorsed yes AND mother endorsed no = 1
    - father endorsed no AND mother endorsed yes = 2

- father endorsed yes AND mother endorsed yes = 3
- father endorsed NA AND mother endorsed yes = 4
- father endorsed yes AND mother endorsed NA = 5
- all other cases set to NA

Usage

```
vars_mh_p_famhx__halluc__moth__fath_score

compute_mh_p_famhx__halluc__moth__fath_score(
  data,
  name = "mh_p_famhx__halluc__moth__fath_score",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of base name of the check boxes used to compute mh_p_famhx__halluc__moth__fath_score.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__hosp__moth__fath_indicator

Compute "Family History [Parent] (Hospitalized)) Endorsed: Either parent"

Description

Computes the summary score mh_p_famhx__hosp__moth__fath_indicator (Family History [Parent] (Hospitalized)) Endorsed: Either parent)

- *Excluded values:*
  - 777
  - 888
  - 999

- *Notes:*
  - Following logic is applied to compute the score:
    * father endorsed `yes` OR mother endorsed `yes` = `1`
    * father endorsed `no` AND mother endorsed `no` = `0`
    * all other cases set to `NA`

Usage

```
vars_mh_p_famhx__hosp__moth__fath_indicator

compute_mh_p_famhx__hosp__moth__fath_indicator(
  data,
  name = "mh_p_famhx__hosp__moth__fath_indicator",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

`data`	tibble. A data frame containing the data.
`name`	character. The name of the output column for the computed score.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: `TRUE`).

Format

a character vector of fields used to compute `mh_p_famhx__hosp__moth__fath_indicator`.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__hosp__moth__fath_score

Compute "Family History [Parent] (Hospitalized) Endorsed: Parents overall"

Description

Computes the summary score `mh_p_famhx__hosp__moth__fath_score` (Family History [Parent] (Hospitalized) Endorsed: Parents overall)

- *Excluded values:*
  - 777
  - 888

  - 999

- *Notes:*
  - Following logic is applied to compute the score:
    * father endorsed `no` AND mother endorsed `no` = `0`
    * father endorsed `yes` AND mother endorsed `no` = `1`
    * father endorsed `no` AND mother endorsed `yes` = `2`
    * father endorsed `yes` AND mother endorsed `yes` = `3`
    * father endorsed `NA` AND mother endorsed `yes` = `4`
    * father endorsed `yes` AND mother endorsed `NA` = `5`
    * all other cases set to `NA`

Usage

```
vars_mh_p_famhx__hosp__moth__fath_score

compute_mh_p_famhx__hosp__moth__fath_score(
  data,
  name = "mh_p_famhx__hosp__moth__fath_score",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

`data`	tibble. A data frame containing the data.
`name`	character. The name of the output column for the computed score.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: `TRUE`).

Format

a character vector of base name of the check boxes used to compute `mh_p_famhx__hosp__moth__fath_score`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_p_famhx__mania__moth__fath_indicator`
Compute "Family History [Parent] (Mania) Endorsed: Either parent"

Description

Computes the summary score `mh_p_famhx__mania__moth__fath_indicator` (Family History [Parent] (Mania) Endorsed: Either parent)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed `yes` OR mother endorsed `yes` = `1`
    - father endorsed `no` AND mother endorsed `no` = `0`
    - all other cases set to `NA`

Usage

```
vars_mh_p_famhx__mania__moth__fath_indicator

compute_mh_p_famhx__mania__moth__fath_indicator(
  data,
  name = "mh_p_famhx__mania__moth__fath_indicator",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

`data`	tibble. A data frame containing the data.
`name`	character. The name of the output column for the computed score.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: `TRUE`).

Format

a character vector of fields used to compute `mh_p_famhx__mania__moth__fath_indicator`.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_mh_p_famhx__mania__moth__fath_score
Compute "Family History [Parent] (Mania) Endorsed: Parents overall"

Description

Computes the summary score `mh_p_famhx__mania__moth__fath_score` (Family History [Parent] (Mania) Endorsed: Parents overall)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed `no` AND mother endorsed `no` = `0`
    - father endorsed `yes` AND mother endorsed `no` = `1`
    - father endorsed `no` AND mother endorsed `yes` = `2`
    - father endorsed `yes` AND mother endorsed `yes` = `3`
    - father endorsed `NA` AND mother endorsed `yes` = `4`
    - father endorsed `yes` AND mother endorsed `NA` = `5`
    - all other cases set to `NA`

Usage

```
vars_mh_p_famhx__mania__moth__fath_score

compute_mh_p_famhx__mania__moth__fath_score(
  data,
  name = "mh_p_famhx__mania__moth__fath_score",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

`data`	tibble. A data frame containing the data.
`name`	character. The name of the output column for the computed score.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: `TRUE`).

Format

a character vector of base name of the check boxes used to compute `mh_p_famhx__mania__moth__fath_score`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_p_famhx__nerve__moth__fath_indicator`
Compute "Family History [Parent] (Nerves/Nervous Breakdown) Endorsed: Either parent"

Description

Computes the summary score `mh_p_famhx__nerve__moth__fath_indicator` (Family History [Parent] (Nerves/Nervous Breakdown) Endorsed: Either parent)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed `yes` OR mother endorsed `yes` = `1`
    - father endorsed `no` AND mother endorsed `no` = `0`
    - all other cases set to `NA`

Usage

```
vars_mh_p_famhx__nerve__moth__fath_indicator

compute_mh_p_famhx__nerve__moth__fath_indicator(
  data,
  name = "mh_p_famhx__nerve__moth__fath_indicator",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

`data`	tibble. A data frame containing the data.
`name`	character. The name of the output column for the computed score.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. Whether to combine the summary score column with the input data frame (Default: `TRUE`).

Format

a character vector of fields used to compute `mh_p_famhx__nerve__moth__fath_indicator`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_p_famhx__nerve__moth__fath_score`
Compute "Family History [Parent] (Nerves/Nervous Breakdown) Endorsed: Parents overall"

Description

Computes the summary score `mh_p_famhx__nerve__moth__fath_score` (Family History [Parent] (Nerves/Nervous Breakdown) Endorsed: Parents overall)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed `no` AND mother endorsed `no` = `0`
    - father endorsed `yes` AND mother endorsed `no` = `1`
    - father endorsed `no` AND mother endorsed `yes` = `2`
    - father endorsed `yes` AND mother endorsed `yes` = `3`
    - father endorsed `NA` AND mother endorsed `yes` = `4`
    - father endorsed `yes` AND mother endorsed `NA` = `5`
    - all other cases set to `NA`

Usage

```
vars_mh_p_famhx__nerve__moth__fath_score

compute_mh_p_famhx__nerve__moth__fath_score(
  data,
  name = "mh_p_famhx__nerve__moth__fath_score",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of base name of the check boxes used to compute mh_p_famhx__nerve__moth__fath_score.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__suic__moth__fath_indicator

Compute "Family History [Parent] (Suicide)) Endorsed: Either parent"

Description

Computes the summary score mh_p_famhx__suic__moth__fath_indicator (Family History [Parent] (Suicide)) Endorsed: Either parent)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed yes OR mother endorsed yes = 1
    - father endorsed no AND mother endorsed no = 0
    - all other cases set to NA

Usage

```
vars_mh_p_famhx__suic__moth__fath_indicator

compute_mh_p_famhx__suic__moth__fath_indicator(
  data,
  name = "mh_p_famhx__suic__moth__fath_indicator",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of fields used to compute mh_p_famhx__suic__moth__fath_indicator.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__suic__moth__fath_score

Compute "Family History [Parent] (Suicide) Endorsed: Parents overall"

Description

Computes the summary score mh_p_famhx__suic__moth__fath_score (Family History [Parent] (Suicide) Endorsed: Parents overall)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed no AND mother endorsed no = 0
    - father endorsed yes AND mother endorsed no = 1
    - father endorsed no AND mother endorsed yes = 2
    - father endorsed yes AND mother endorsed yes = 3
    - father endorsed NA AND mother endorsed yes = 4
    - father endorsed yes AND mother endorsed NA = 5
    - all other cases set to NA

Usage

```
vars_mh_p_famhx__suic__moth__fath_score

compute_mh_p_famhx__suic__moth__fath_score(
  data,
  name = "mh_p_famhx__suic__moth__fath_score",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of base name of the check boxes used to compute mh_p_famhx__suic__moth__fath_score.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__troub__moth__fath_indicator

Compute "Family History [Parent] (Trouble/Problems) Endorsed: Either parent"

Description

Computes the summary score mh_p_famhx__troub__moth__fath_indicator (Family History [Parent] (Trouble/Problems) Endorsed: Either parent)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed yes OR mother endorsed yes = 1
    - father endorsed no AND mother endorsed no = 0
    - all other cases set to NA

Usage

```
vars_mh_p_famhx__troub__moth__fath_indicator

compute_mh_p_famhx__troub__moth__fath_indicator(
  data,
  name = "mh_p_famhx__troub__moth__fath_indicator",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of fields used to compute mh_p_famhx__troub__moth__fath_indicator.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_famhx__troub__moth__fath_score

Compute "Family History [Parent] (Trouble/Problems) Endorsed: Parents overall"

Description

Computes the summary score mh_p_famhx__troub__moth__fath_score (Family History [Parent] (Trouble/Problems) Endorsed: Parents overall)

- *Excluded values:*
  - 777
  - 888
  - 999
- *Notes:*
  - Following logic is applied to compute the score:
    - father endorsed no AND mother endorsed no = 0
    - father endorsed yes AND mother endorsed no = 1
    - father endorsed no AND mother endorsed yes = 2

- father endorsed yes AND mother endorsed yes = 3
- father endorsed NA AND mother endorsed yes = 4
- father endorsed yes AND mother endorsed NA = 5
- all other cases set to NA

Usage

```
vars_mh_p_famhx__troub__moth__fath_score

compute_mh_p_famhx__troub__moth__fath_score(
  data,
  name = "mh_p_famhx__troub__moth__fath_score",
  exclude = c("777", "888", "999"),
  combine = TRUE
)
```

Arguments

data	tibble. A data frame containing the data.
name	character. The name of the output column for the computed score.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. Whether to combine the summary score column with the input data frame (Default: TRUE).

Format

a character vector of base name of the check boxes used to compute mh_p_famhx__troub__moth__fath_score.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_gbi *Compute "Parent General Behavior Inventory [Parent]: Number missing"*

Description

Computes the summary score mh_p_gbi_nm Parent General Behavior Inventory [Parent]: Number missing

- *Summarized variables:*
  - mh_p_gbi_001
  - mh_p_gbi_002
  - mh_p_gbi_003
  - mh_p_gbi_004

  - mh_p_gbi_005
  - mh_p_gbi_006
  - mh_p_gbi_007
  - mh_p_gbi_008
  - mh_p_gbi_009
  - mh_p_gbi_010

- *Excluded values:* none

Usage

```
vars_mh_p_gbi

compute_mh_p_gbi_nm(data, name = "mh_p_gbi_nm", exclude = NULL, combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_gbi is vector of all column names used to compute summary score of mh_p_gbi scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_gbi_nm(data) |>
  select(
    any_of(c("mh_p_gbi_nm", vars_mh_p_gbi))
  )

## End(Not run)
```

vars_mh_p_ksads__adhd__past__sx *Compute "KSADS - Attention-Deficit/Hyperactivity Disorder [Parent] (Symptom - Past): Mean"*

Description

Computes the summary score mh_p_ksads__adhd__past__sx_mean KSADS - Attention-Deficit/Hyperactivity Disorder [Parent] (Symptom - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__adhd__avoid__task__past_sx
  - mh_p_ksads__adhd__blurt__past_sx
  - mh_p_ksads__adhd__distract__1schlyr__past_sx
  - mh_p_ksads__adhd__fidget__past_sx
  - mh_p_ksads__adhd__flwinstr__past_sx
  - mh_p_ksads__adhd__forget__past_sx
  - mh_p_ksads__adhd__hypractv__past_sx
  - mh_p_ksads__adhd__impuls__past_sx
  - mh_p_ksads__adhd__interrupt__past_sx
  - mh_p_ksads__adhd__loses__past_sx
  - mh_p_ksads__adhd__mistake__past_sx
  - mh_p_ksads__adhd__motor__past_sx
  - mh_p_ksads__adhd__notlisten__past_sx
  - mh_p_ksads__adhd__orgtask__past_sx
  - mh_p_ksads__adhd__quiet__past_sx
  - mh_p_ksads__adhd__seat__1schlyr__past_sx
  - mh_p_ksads__adhd__sustattn__1schlyr__past_sx
  - mh_p_ksads__adhd__talkexcess__past_sx
  - mh_p_ksads__adhd__wait__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 19 items missing

Usage

```
vars_mh_p_ksads__adhd__past__sx

compute_mh_p_ksads__adhd__past__sx_mean(
  data,
  name = "mh_p_ksads__adhd__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__adhd__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__adhd__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__adhd__pres__sx

Compute "KSADS - Attention-Deficit/Hyperactivity Disorder [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__adhd__pres__sx_mean KSADS - Attention-Deficit/Hyperactivity Disorder [Parent] (Symptom - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__adhd__avoid__task__pres_sx
  - mh_p_ksads__adhd__blurt__pres_sx
  - mh_p_ksads__adhd__distract__grdschl__pres_sx
  - mh_p_ksads__adhd__fidget__pres_sx

  - mh_p_ksads__adhd__flwinstr__pres_sx
  - mh_p_ksads__adhd__forget__pres_sx
  - mh_p_ksads__adhd__hypractv__pres_sx
  - mh_p_ksads__adhd__impuls__pres_sx
  - mh_p_ksads__adhd__interrupt__pres_sx
  - mh_p_ksads__adhd__loses__pres_sx
  - mh_p_ksads__adhd__mistake__pres_sx
  - mh_p_ksads__adhd__motor__pres_sx
  - mh_p_ksads__adhd__notlisten__pres_sx
  - mh_p_ksads__adhd__orgtask__pres_sx
  - mh_p_ksads__adhd__quiet__pres_sx
  - mh_p_ksads__adhd__seat__grdschl__pres_sx
  - mh_p_ksads__adhd__sustattn__grdschl__pres_sx
  - mh_p_ksads__adhd__talkexcess__pres_sx
  - mh_p_ksads__adhd__wait__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 19 items missing

Usage

```
vars_mh_p_ksads__adhd__pres__sx

compute_mh_p_ksads__adhd__pres__sx_mean(
  data,
  name = "mh_p_ksads__adhd__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__adhd__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__adhd__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__agor__past__sx

Compute "KSADS - Agoraphobia [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__agor__past__sx_mean KSADS - Agoraphobia [Parent] (Symptom - Past): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__agor__avoid__past_sx
  - mh_p_ksads__agor__multi__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_mh_p_ksads__agor__past__sx

compute_mh_p_ksads__agor__past__sx_mean(
  data,
  name = "mh_p_ksads__agor__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__agor__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__agor__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__agor__pres__sx

Compute "KSADS - Agoraphobia [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__agor__pres__sx_mean KSADS - Agoraphobia [Parent] (Symptom - Present): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__agor__avoid__pres_sx
  - mh_p_ksads__agor__multi__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_mh_p_ksads__agor__pres__sx

compute_mh_p_ksads__agor__pres__sx_mean(
  data,
  name = "mh_p_ksads__agor__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__agor__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__agor__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_p_ksads__asd__past__sx
Compute "KSADS - Autism Spectrum Disorders [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__asd__past__sx_mean KSADS - Autism Spectrum Disorders [Parent] (Symptom - Past): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__asd__hyporeact__past_sx
  - mh_p_ksads__asd__hyprreact__past_sx
  - mh_p_ksads__asd__pooreyecont__past_sx
  - mh_p_ksads__asd__relatsh__past_sx
  - mh_p_ksads__asd__restrctintrst__past_sx
  - mh_p_ksads__asd__routine__past_sx
  - mh_p_ksads__asd__socemotrcp__past_sx
  - mh_p_ksads__asd__unusmvmnt__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_p_ksads__asd__past__sx

compute_mh_p_ksads__asd__past__sx_mean(
  data,
  name = "mh_p_ksads__asd__past__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__asd__past__sx is a character vector of all column names used to compute summary score of `mh_p_ksads__asd__past__sx_mean`

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

---

vars_mh_p_ksads__asd__pres__sx

Compute "KSADS - Autism Spectrum Disorders [Parent] (Symptom - Present): Mean"

Description

Computes the summary score `mh_p_ksads__asd__pres__sx_mean` KSADS - Autism Spectrum Disorders [Parent] (Symptom - Present): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__asd__hyporeact__pres_sx`
  - `mh_p_ksads__asd__hyprreact__pres_sx`
  - `mh_p_ksads__asd__pooreyecont__pres_sx`
  - `mh_p_ksads__asd__relatsh__pres_sx`
  - `mh_p_ksads__asd__restrctintrst__pres_sx`
  - `mh_p_ksads__asd__routine__pres_sx`
  - `mh_p_ksads__asd__socemotrcp__pres_sx`
  - `mh_p_ksads__asd__unusmvmnt__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_p_ksads__asd__pres__sx

compute_mh_p_ksads__asd__pres__sx_mean(
  data,
  name = "mh_p_ksads__asd__pres__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__asd__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__asd__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_p_ksads__bpd__past__sx
Compute "KSADS - Bipolar Disorders [Parent] (Symptom - Past): Mean "

Description

Computes the summary score mh_p_ksads__bpd__past__sx_mean KSADS - Bipolar Disorders [Parent] (Symptom - Past): Mean [validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__bpd__distract__incr__past_sx
  - mh_p_ksads__bpd__distract__past_sx
  - mh_p_ksads__bpd__enrg__incr__past_sx
  - mh_p_ksads__bpd__flgtid__past_sx
  - mh_p_ksads__bpd__goaldir__incr__past_sx
  - mh_p_ksads__bpd__grndios__past_sx
  - mh_p_ksads__bpd__hyprsex__past_sx
  - mh_p_ksads__bpd__irrit__expl__past_sx
  - mh_p_ksads__bpd__irrit__manic__past_sx
  - mh_p_ksads__bpd__mood__elv__past_sx
  - mh_p_ksads__bpd__mood__euph__past_sx
  - mh_p_ksads__bpd__prspch__past_sx
  - mh_p_ksads__bpd__psymot__agit__past_sx
  - mh_p_ksads__bpd__ractho__past_sx
  - mh_p_ksads__bpd__riskactv__past_sx
  - mh_p_ksads__bpd__slpdecr__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 16 items missing

Usage

```
vars_mh_p_ksads__bpd__past__sx

compute_mh_p_ksads__bpd__past__sx_mean(
  data,
  name = "mh_p_ksads__bpd__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__bpd__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__bpd__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__bpd__pres__sx

Compute "KSADS - Bipolar Disorders [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__bpd__pres__sx_mean KSADS - Bipolar Disorders [Parent] (Symptom - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__bpd__distract__incr__pres_sx
  - mh_p_ksads__bpd__distract__pres_sx
  - mh_p_ksads__bpd__enrg__incr__pres_sx
  - mh_p_ksads__bpd__flgtid__pres_sx

  - mh_p_ksads__bpd__goaldir__incr__pres_sx
  - mh_p_ksads__bpd__grndios__pres_sx
  - mh_p_ksads__bpd__hyprsex__pres_sx
  - mh_p_ksads__bpd__irrit__expl__pres_sx
  - mh_p_ksads__bpd__irrit__manic__pres_sx
  - mh_p_ksads__bpd__mood__elv__pres_sx
  - mh_p_ksads__bpd__mood__euph__pres_sx
  - mh_p_ksads__bpd__prspch__pres_sx
  - mh_p_ksads__bpd__psymot__agit__pres_sx
  - mh_p_ksads__bpd__ractho__pres_sx
  - mh_p_ksads__bpd__riskactv__pres_sx
  - mh_p_ksads__bpd__slpdecr__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 16 items missing

Usage

```
vars_mh_p_ksads__bpd__pres__sx

compute_mh_p_ksads__bpd__pres__sx_mean(
  data,
  name = "mh_p_ksads__bpd__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__bpd__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__bpd__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

`vars_mh_p_ksads__cond__past__sx` *Compute "KSADS - Conduct Disorder [Parent] (Symptom - Past): Mean "*

Description

Computes the summary score `mh_p_ksads__cond__past__sx_mean` KSADS - Conduct Disorder [Parent] (Symptom - Past): Mean [validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__cond__breakin__past_sx`
  - `mh_p_ksads__cond__bully__past_sx`
  - `mh_p_ksads__cond__fight__past_sx`
  - `mh_p_ksads__cond__fire__past_sx`
  - `mh_p_ksads__cond__lies__past_sx`
  - `mh_p_ksads__cond__outlate__past_sx`
  - `mh_p_ksads__cond__physcruel__anml__past_sx`
  - `mh_p_ksads__cond__physcruel__ppl__past_sx`
  - `mh_p_ksads__cond__rob__past_sx`
  - `mh_p_ksads__cond__runaway__past_sx`
  - `mh_p_ksads__cond__steal__past_sx`
  - `mh_p_ksads__cond__truant__past_sx`
  - `mh_p_ksads__cond__vandal__past_sx`
  - `mh_p_ksads__cond__weapon__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_mh_p_ksads__cond__past__sx

compute_mh_p_ksads__cond__past__sx_mean(
  data,
  name = "mh_p_ksads__cond__past__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__cond__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__cond__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_p_ksads__cond__pres__sx
Compute "KSADS - Conduct Disorder [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__cond__pres__sx_mean KSADS - Conduct Disorder [Parent] (Symptom - Present): Mean [validation: No more than 2 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__cond__breakin__pres_sx
  - mh_p_ksads__cond__bully__pres_sx
  - mh_p_ksads__cond__fight__pres_sx
  - mh_p_ksads__cond__fire__pres_sx
  - mh_p_ksads__cond__lies__pres_sx
  - mh_p_ksads__cond__outlate__pres_sx
  - mh_p_ksads__cond__physcruel__anml__pres_sx
  - mh_p_ksads__cond__physcruel__ppl__pres_sx
  - mh_p_ksads__cond__rob__pres_sx
  - mh_p_ksads__cond__runaway__pres_sx
  - mh_p_ksads__cond__steal__pres_sx
  - mh_p_ksads__cond__truant__pres_sx
  - mh_p_ksads__cond__vandal__pres_sx
  - mh_p_ksads__cond__weapon__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_mh_p_ksads__cond__pres__sx

compute_mh_p_ksads__cond__pres__sx_mean(
  data,
  name = "mh_p_ksads__cond__pres__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__cond__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__cond__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__dep__past__sx

Compute "KSADS - Depressive Disorders [Parent] (Symptom - Past): Mean "

Description

Computes the summary score mh_p_ksads__dep__past__sx_mean KSADS - Depressive Disorders [Parent] (Symptom - Past): Mean [validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__dep__anhed__past_sx
  - mh_p_ksads__dep__appdecr__past_sx
  - mh_p_ksads__dep__conc__past_sx
  - mh_p_ksads__dep__fatig__past_sx

  - mh_p_ksads__dep__glt__past_sx
  - mh_p_ksads__dep__hplss__past_sx
  - mh_p_ksads__dep__hyprsom__past_sx
  - mh_p_ksads__dep__incapp__past_sx
  - mh_p_ksads__dep__indec__past_sx
  - mh_p_ksads__dep__insom__past_sx
  - mh_p_ksads__dep__irrit__past_sx
  - mh_p_ksads__dep__mood__past_sx
  - mh_p_ksads__dep__psymot__agit__past_sx
  - mh_p_ksads__dep__psymot__rtrd__past_sx
  - mh_p_ksads__dep__slfestmdecr__past_sx
  - mh_p_ksads__dep__wghtgain__past_sx
  - mh_p_ksads__dep__wghtloss__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 17 items missing

Usage

```
vars_mh_p_ksads__dep__past__sx

compute_mh_p_ksads__dep__past__sx_mean(
  data,
  name = "mh_p_ksads__dep__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__dep__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__dep__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__dep__pres__sx *Compute "KSADS - Depressive Disorders [Parent] (Symptom - Present): Mean"*

Description

Computes the summary score mh_p_ksads__dep__pres__sx_mean KSADS - Depressive Disorders [Parent] (Symptom - Present): Mean [validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__dep__anhed__pres_sx
  - mh_p_ksads__dep__appdecr__pres_sx
  - mh_p_ksads__dep__conc__pres_sx
  - mh_p_ksads__dep__fatig__pres_sx
  - mh_p_ksads__dep__glt__pres_sx
  - mh_p_ksads__dep__hplss__pres_sx
  - mh_p_ksads__dep__hyprsom__pres_sx
  - mh_p_ksads__dep__incapp__pres_sx
  - mh_p_ksads__dep__indec__pres_sx
  - mh_p_ksads__dep__irrit__pres_sx
  - mh_p_ksads__dep__mood__pres_sx
  - mh_p_ksads__dep__psymot__agit__pres_sx
  - mh_p_ksads__dep__psymot__rtrd__pres_sx
  - mh_p_ksads__dep__slfestmdecr__pres_sx
  - mh_p_ksads__dep__wghtgain__pres_sx
  - mh_p_ksads__dep__wghtloss__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 17 items missing

Usage

```
vars_mh_p_ksads__dep__pres__sx

compute_mh_p_ksads__dep__pres__sx_mean(
  data,
  name = "mh_p_ksads__dep__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__dep__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__dep__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_p_ksads__dmdd__sx

Compute "KSADS - Disruptive Mood Dysregulation Disorder [Parent] (Symptom): Mean"

Description

Computes the summary score mh_p_ksads__dmdd__sx_mean KSADS - Disruptive Mood Dysregulation Disorder [Parent] (Symptom): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__dmdd__outbrst__3perwk_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
vars_mh_p_ksads__dmdd__sx

compute_mh_p_ksads__dmdd__sx_mean(
  data,
  name = "mh_p_ksads__dmdd__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__dmdd__sx is a character vector of all column names used to compute summary score of mh_p_ksads__dmdd__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__ed__past__sx

Compute "KSADS - Eating Disorders [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__ed__past__sx_mean KSADS - Eating Disorders [Parent] (Symptom - Past): Mean [validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__ed__binge__distrs__past_sx
  - mh_p_ksads__ed__binge__past_sx
  - mh_p_ksads__ed__compbehav__past_sx
  - mh_p_ksads__ed__emac__past_sx
  - mh_p_ksads__ed__fear__obese__past_sx
  - mh_p_ksads__ed__slfwrth__past_sx
  - mh_p_ksads__ed__wghtcntrl__oth__past_sx
  - mh_p_ksads__ed__wghtcntrl__vom__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_p_ksads__ed__past__sx

compute_mh_p_ksads__ed__past__sx_mean(
  data,
  name = "mh_p_ksads__ed__past__sx_mean",
```

```
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__ed__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__ed__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__ed__pres__sx

Compute "KSADS - Eating Disorders [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__ed__pres__sx_mean KSADS - Eating Disorders [Parent] (Symptom - Present): Mean [validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__ed__binge__distrs__pres_sx
  - mh_p_ksads__ed__binge__pres_sx
  - mh_p_ksads__ed__compbehav__pres_sx
  - mh_p_ksads__ed__emac__pres_sx
  - mh_p_ksads__ed__fear__obese__pres_sx
  - mh_p_ksads__ed__slfwrth__pres_sx
  - mh_p_ksads__ed__wghtcntrl__oth__pres_sx
  - mh_p_ksads__ed__wghtcntrl__vom__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_p_ksads__ed__pres__sx

compute_mh_p_ksads__ed__pres__sx_mean(
  data,
  name = "mh_p_ksads__ed__pres__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__ed__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__ed__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__gad__past__sx

Compute "KSADS - Generalized Anxiety Disorder [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__gad__past__sx_mean KSADS - Generalized Anxiety Disorder [Parent] (Symptom - Past): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__gad__worry__6mo__past_sx
  - mh_p_ksads__gad__worry__diffctrl__past_sx
  - mh_p_ksads__gad__worry__excess__past_sx
  - mh_p_ksads__gad__worry__multi__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_mh_p_ksads__gad__past__sx

compute_mh_p_ksads__gad__past__sx_mean(
  data,
  name = "mh_p_ksads__gad__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__gad__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__gad__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__gad__pres__sx

Compute "KSADS - Generalized Anxiety Disorder [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__gad__pres__sx_mean KSADS - Generalized Anxiety Disorder [Parent] (Symptom - Present): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__gad__worry__6mo__pres_sx
  - mh_p_ksads__gad__worry__diffctrl__pres_sx
  - mh_p_ksads__gad__worry__excess__pres_sx
  - mh_p_ksads__gad__worry__multi__pres_sx

- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_mh_p_ksads__gad__pres__sx

compute_mh_p_ksads__gad__pres__sx_mean(
  data,
  name = "mh_p_ksads__gad__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__gad__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__gad__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_p_ksads__hom__past__sx
Compute "KSADS - Homicidality [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__hom__past__sx_mean KSADS - Homicidality [Parent] (Symptom - Past): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__hom__idea__past_sx
  - mh_p_ksads__hom__plan__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_mh_p_ksads__hom__past__sx

compute_mh_p_ksads__hom__past__sx_mean(
  data,
  name = "mh_p_ksads__hom__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__hom__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__hom__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

`vars_mh_p_ksads__hom__pres__sx` *Compute "KSADS - Homicidality [Parent] (Symptom - Present): Mean"*

Description

Computes the summary score `mh_p_ksads__hom__pres__sx_mean` KSADS - Homicidality [Parent] (Symptom - Present): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__hom__idea__pres_sx`
  - `mh_p_ksads__hom__plan__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_mh_p_ksads__hom__pres__sx

compute_mh_p_ksads__hom__pres__sx_mean(
  data,
  name = "mh_p_ksads__hom__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__hom__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__hom__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__ocd__past__sx

Compute "KSADS - Obsessive Compulsive Disorder [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__ocd__past__sx_mean KSADS - Obsessive Compulsive Disorder [Parent] (Symptom - Past): Mean [validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__ocd__compuls__past_sx
  - mh_p_ksads__ocd__compuls__prvntanx__past_sx
  - mh_p_ksads__ocd__compuls__tcnsm__past_sx
  - mh_p_ksads__ocd__obsess__intru__past_sx

  - mh_p_ksads__ocd__obsess__past_sx
  - mh_p_ksads__ocd__obsess__tcnsm__past_sx
  - mh_p_ksads__ocd__suprstho__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_mh_p_ksads__ocd__past__sx

compute_mh_p_ksads__ocd__past__sx_mean(
  data,
  name = "mh_p_ksads__ocd__past__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__ocd__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__ocd__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see `combine`.

`vars_mh_p_ksads__ocd__pres__sx`

Compute "KSADS - Obsessive Compulsive Disorder [Parent] (Symptom - Present): Mean"

Description

Computes the summary score `mh_p_ksads__ocd__pres__sx_mean` KSADS - Obsessive Compulsive Disorder [Parent] (Symptom - Present): Mean [validation: No more than 1 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__ocd__compuls__pres_sx`
  - `mh_p_ksads__ocd__compuls__prvntanx__pres_sx`
  - `mh_p_ksads__ocd__compuls__tcnsm__pres_sx`
  - `mh_p_ksads__ocd__obsess__intru__pres_sx`
  - `mh_p_ksads__ocd__obsess__pres_sx`
  - `mh_p_ksads__ocd__obsess__tcnsm__pres_sx`
  - `mh_p_ksads__ocd__suprstho__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_mh_p_ksads__ocd__pres__sx

compute_mh_p_ksads__ocd__pres__sx_mean(
  data,
  name = "mh_p_ksads__ocd__pres__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__ocd__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__ocd__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__odd__past__sx

Compute "KSADS - Oppositional Defiant Disorder [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__odd__past__sx_mean KSADS - Oppositional Defiant Disorder [Parent] (Symptom - Past): Mean [validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__odd__angry__past_sx
  - mh_p_ksads__odd__argue__past_sx
  - mh_p_ksads__odd__blame__past_sx
  - mh_p_ksads__odd__delibannoy__past_sx
  - mh_p_ksads__odd__disobey__past_sx
  - mh_p_ksads__odd__temper__past_sx
  - mh_p_ksads__odd__touchy__past_sx
  - mh_p_ksads__odd__vindict__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_p_ksads__odd__past__sx

compute_mh_p_ksads__odd__past__sx_mean(
  data,
  name = "mh_p_ksads__odd__past__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__odd__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__odd__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_p_ksads__odd__pres__sx

Compute "KSADS - Oppositional Defiant Disorder [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__odd__pres__sx_mean KSADS - Oppositional Defiant Disorder [Parent] (Symptom - Present): Mean [validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__odd__angry__pres_sx
  - mh_p_ksads__odd__argue__pres_sx
  - mh_p_ksads__odd__blame__pres_sx
  - mh_p_ksads__odd__delibannoy__pres_sx
  - mh_p_ksads__odd__disobey__pres_sx
  - mh_p_ksads__odd__temper__pres_sx
  - mh_p_ksads__odd__touchy__pres_sx
  - mh_p_ksads__odd__vindict__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_p_ksads__odd__pres__sx

compute_mh_p_ksads__odd__pres__sx_mean(
  data,
  name = "mh_p_ksads__odd__pres__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__odd__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__odd__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__panic__past__sx

Compute "KSADS - Panic Disorder [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__panic__past__sx_mean KSADS - Panic Disorder [Parent] (Symptom - Past): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__panic__attack__maladp__past_sx
  - mh_p_ksads__panic__attack__past_sx
  - mh_p_ksads__panic__sympt__past_sx
  - mh_p_ksads__panic__worry__attack__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_mh_p_ksads__panic__past__sx

compute_mh_p_ksads__panic__past__sx_mean(
  data,
  name = "mh_p_ksads__panic__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__panic__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__panic__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__panic__pres__sx

Compute "KSADS - Panic Disorder [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__panic__pres__sx_mean KSADS - Panic Disorder [Parent] (Symptom - Present): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__panic__attack__maladp__pres_sx
  - mh_p_ksads__panic__attack__pres_sx
  - mh_p_ksads__panic__sympt__pres_sx
  - mh_p_ksads__panic__worry__attack__pres_sx

- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_mh_p_ksads__panic__pres__sx

compute_mh_p_ksads__panic__pres__sx_mean(
  data,
  name = "mh_p_ksads__panic__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__panic__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__panic__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_p_ksads__phobia__past__sx *Compute "KSADS - Specific Phobia [Parent] (Symptom - Past): Mean"*

Description

Computes the summary score `mh_p_ksads__phobia__past__sx_mean` KSADS - Specific Phobia [Parent] (Symptom - Past): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__phobia__avoid__past_sx`
  - `mh_p_ksads__phobia__fear__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_mh_p_ksads__phobia__past__sx

compute_mh_p_ksads__phobia__past__sx_mean(
  data,
  name = "mh_p_ksads__phobia__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__phobia__past__sx is a character vector of all column names used to compute summary score of `mh_p_ksads__phobia__past__sx_mean`

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

`vars_mh_p_ksads__phobia__pres__sx`
Compute "KSADS - Specific Phobia [Parent] (Symptom - Present): Mean"

Description

Computes the summary score `mh_p_ksads__phobia__pres__sx_mean` KSADS - Specific Phobia [Parent] (Symptom - Present): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__phobia__avoid__pres_sx`
  - `mh_p_ksads__phobia__fear__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_mh_p_ksads__phobia__pres__sx

compute_mh_p_ksads__phobia__pres__sx_mean(
  data,
  name = "mh_p_ksads__phobia__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__phobia__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__phobia__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__psych__past__sx

Compute "KSADS - Psychosis [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__psych__past__sx_mean KSADS - Psychosis [Parent] (Symptom - Past): Mean [validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__psych__delus__oth__past_sx
  - mh_p_ksads__psych__delus__persec__past_sx
  - mh_p_ksads__psych__delus__past_sx
  - mh_p_ksads__psych__halluc__adt__past_sx
  - mh_p_ksads__psych__halluc__clust__past_sx

  - mh_p_ksads__psych__halluc__oth__past_sx
  - mh_p_ksads__psych__halluc__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_mh_p_ksads__psych__past__sx

compute_mh_p_ksads__psych__past__sx_mean(
  data,
  name = "mh_p_ksads__psych__past__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__psych__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__psych__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

`vars_mh_p_ksads__psych__pres__sx`
Compute "KSADS - Psychosis [Parent] (Symptom - Present): Mean"

Description

Computes the summary score `mh_p_ksads__psych__pres__sx_mean` KSADS - Psychosis [Parent] (Symptom - Present): Mean [validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__psych__delus__oth__2wk__pres_sx`
  - `mh_p_ksads__psych__delus__persec__2wk__pres_sx`
  - `mh_p_ksads__psych__delus__pres_sx`
  - `mh_p_ksads__psych__disorg__behav__pres_sx`
  - `mh_p_ksads__psych__disorg__speech__pres_sx`
  - `mh_p_ksads__psych__halluc__adt__pres_sx`
  - `mh_p_ksads__psych__halluc__clust__pres_sx`
  - `mh_p_ksads__psych__halluc__oth__altw__pres_sx`
  - `mh_p_ksads__psych__halluc__oth__ap__pres_sx`
  - `mh_p_ksads__psych__halluc__oth__pres_sx`
  - `mh_p_ksads__psych__halluc__pres_sx`
  - `mh_p_ksads__psych__neg__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 12 items missing

Usage

```
vars_mh_p_ksads__psych__pres__sx

compute_mh_p_ksads__psych__pres__sx_mean(
  data,
  name = "mh_p_ksads__psych__pres__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.

exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__psych__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__psych__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__ptsd__past__sx

Compute "KSADS - Post-Traumatic Stress Disorder [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__ptsd__past__sx_mean KSADS - Post-Traumatic Stress Disorder [Parent] (Symptom - Past): Mean [validation: No more than 4 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__ptsd__anhed__past_sx
  - mh_p_ksads__ptsd__avoid__extrmnd__past_sx
  - mh_p_ksads__ptsd__avoid__trmatho__past_sx
  - mh_p_ksads__ptsd__concprob__past_sx
  - mh_p_ksads__ptsd__depersnl__past_sx
  - mh_p_ksads__ptsd__derealztn__past_sx
  - mh_p_ksads__ptsd__detach__past_sx
  - mh_p_ksads__ptsd__distortcog__cause__past_sx
  - mh_p_ksads__ptsd__distortcog__consq__past_sx

  - mh_p_ksads__ptsd__emot__neg__past_sx
  - mh_p_ksads__ptsd__emot__nopos__past_sx
  - mh_p_ksads__ptsd__extrmnd__distrs__past_sx
  - mh_p_ksads__ptsd__flshbck__past_sx
  - mh_p_ksads__ptsd__hyprvigl__past_sx
  - mh_p_ksads__ptsd__intrmnd__distrs__past_sx
  - mh_p_ksads__ptsd__irrit__past_sx
  - mh_p_ksads__ptsd__memloss__past_sx
  - mh_p_ksads__ptsd__negblf__past_sx
  - mh_p_ksads__ptsd__nghtmr__past_sx
  - mh_p_ksads__ptsd__physreact__past_sx
  - mh_p_ksads__ptsd__rckls__past_sx
  - mh_p_ksads__ptsd__sleepdistb__past_sx
  - mh_p_ksads__ptsd__startle__past_sx
  - mh_p_ksads__ptsd__trmatho__intru__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 4 of 24 items missing

Usage

```
vars_mh_p_ksads__ptsd__past__sx

compute_mh_p_ksads__ptsd__past__sx_mean(
  data,
  name = "mh_p_ksads__ptsd__past__sx_mean",
  max_na = 4,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__ptsd__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__ptsd__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__ptsd__pres__sx

Compute "KSADS - Post-Traumatic Stress Disorder [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__ptsd__pres__sx_mean KSADS - Post-Traumatic Stress Disorder [Parent] (Symptom - Present): Mean [validation: No more than 4 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__ptsd__anhed__pres_sx
  - mh_p_ksads__ptsd__avoid__extrmnd__pres_sx
  - mh_p_ksads__ptsd__avoid__trmatho__pres_sx
  - mh_p_ksads__ptsd__concprob__pres_sx
  - mh_p_ksads__ptsd__depersnl__pres_sx
  - mh_p_ksads__ptsd__derealztn__pres_sx
  - mh_p_ksads__ptsd__detach__pres_sx
  - mh_p_ksads__ptsd__distortcog__cause__pres_sx
  - mh_p_ksads__ptsd__distortcog__consq__pres_sx
  - mh_p_ksads__ptsd__emot__neg__pres_sx
  - mh_p_ksads__ptsd__emot__nopos__pres_sx
  - mh_p_ksads__ptsd__extrmnd__distrs__pres_sx
  - mh_p_ksads__ptsd__flshbck__pres_sx
  - mh_p_ksads__ptsd__hyprvigl__pres_sx
  - mh_p_ksads__ptsd__intrmnd__distrs__pres_sx
  - mh_p_ksads__ptsd__irrit__pres_sx
  - mh_p_ksads__ptsd__memloss__pres_sx
  - mh_p_ksads__ptsd__negblf__pres_sx

  - mh_p_ksads__ptsd__nghtmr__pres_sx
  - mh_p_ksads__ptsd__physreact__pres_sx
  - mh_p_ksads__ptsd__rckls__pres_sx
  - mh_p_ksads__ptsd__sleepdistb__pres_sx
  - mh_p_ksads__ptsd__startle__pres_sx
  - mh_p_ksads__ptsd__trmatho__intru__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 4 of 24 items missing

Usage

```
vars_mh_p_ksads__ptsd__pres__sx

compute_mh_p_ksads__ptsd__pres__sx_mean(
  data,
  name = "mh_p_ksads__ptsd__pres__sx_mean",
  max_na = 4,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__ptsd__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__ptsd__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see `combine`.

`vars_mh_p_ksads__sepanx__past__sx`

Compute "KSADS - Separation Anxiety [Parent] (Symptom - Past): Mean"

Description

Computes the summary score `mh_p_ksads__sepanx__past__sx_mean` KSADS - Separation Anxiety [Parent] (Symptom - Past): Mean [validation: No more than 1 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__sepanx__evnt__fear__past_sx`
  - `mh_p_ksads__sepanx__fig__harm__past_sx`
  - `mh_p_ksads__sepanx__nghtmr__past_sx`
  - `mh_p_ksads__sepanx__nofig__fear__past_sx`
  - `mh_p_ksads__sepanx__nofig__physympt__past_sx`
  - `mh_p_ksads__sepanx__noschl__past_sx`
  - `mh_p_ksads__sepanx__nosleep__past_sx`
  - `mh_p_ksads__sepanx__sep__distrs__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_p_ksads__sepanx__past__sx

compute_mh_p_ksads__sepanx__past__sx_mean(
  data,
  name = "mh_p_ksads__sepanx__past__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.

exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__sepanx__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__sepanx__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__sepanx__pres__sx

Compute "KSADS - Separation Anxiety [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__sepanx__pres__sx_mean KSADS - Separation Anxiety [Parent] (Symptom - Present): Mean [validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__sepanx__evnt__fear__pres_sx
  - mh_p_ksads__sepanx__fig__harm__pres_sx
  - mh_p_ksads__sepanx__nghtmr__pres_sx
  - mh_p_ksads__sepanx__nofig__fear__pres_sx
  - mh_p_ksads__sepanx__nofig__physympt__pres_sx
  - mh_p_ksads__sepanx__noschl__pres_sx
  - mh_p_ksads__sepanx__nosleep__pres_sx
  - mh_p_ksads__sepanx__sep__distrs__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_p_ksads__sepanx__pres__sx

compute_mh_p_ksads__sepanx__pres__sx_mean(
  data,
  name = "mh_p_ksads__sepanx__pres__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__sepanx__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__sepanx__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

`vars_mh_p_ksads__sleep__past__sx`
Compute "KSADS - Sleep Problems [Parent] (Symptom - Past): Mean"

Description

Computes the summary score `mh_p_ksads__sleep__past__sx_mean` KSADS - Sleep Problems [Parent] (Symptom - Past): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__sleep__insom__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
vars_mh_p_ksads__sleep__past__sx

compute_mh_p_ksads__sleep__past__sx_mean(
  data,
  name = "mh_p_ksads__sleep__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__sleep__past__sx is a character vector of all column names used to compute summary score of `mh_p_ksads__sleep__past__sx_mean`

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

`vars_mh_p_ksads__sleep__pres__sx` *Compute "KSADS - Sleep Problems [Parent] (Symptom - Present): Mean"*

Description

Computes the summary score `mh_p_ksads__sleep__pres__sx_mean` KSADS - Sleep Problems [Parent] (Symptom - Present): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__sleep__insom__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
vars_mh_p_ksads__sleep__pres__sx

compute_mh_p_ksads__sleep__pres__sx_mean(
  data,
  name = "mh_p_ksads__sleep__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__sleep__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__sleep__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__socanx__past__sx

Compute "KSADS - Social Anxiety Disorder [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__socanx__past__sx_mean KSADS - Social Anxiety Disorder [Parent] (Symptom - Past): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__socanx__anx__past_sx
  - mh_p_ksads__socanx__avoid__past_sx
  - mh_p_ksads__socanx__fear__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 3 items missing

Usage

```
vars_mh_p_ksads__socanx__past__sx

compute_mh_p_ksads__socanx__past__sx_mean(
  data,
  name = "mh_p_ksads__socanx__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__socanx__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__socanx__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_p_ksads__socanx__pres__sx
Compute "KSADS - Social Anxiety Disorder [Parent] (Symptom - Present): Mean"

Description

Computes the summary score mh_p_ksads__socanx__pres__sx_mean KSADS - Social Anxiety Disorder [Parent] (Symptom - Present): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__socanx__anx__pres_sx
  - mh_p_ksads__socanx__avoid__pres_sx
  - mh_p_ksads__socanx__fear__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 3 items missing

Usage

```
vars_mh_p_ksads__socanx__pres__sx

compute_mh_p_ksads__socanx__pres__sx_mean(
  data,
  name = "mh_p_ksads__socanx__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__socanx__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__socanx__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

`vars_mh_p_ksads__suic__past__sx`
Compute "KSADS - Suicidality [Parent] (Symptom - Past): Mean"

Description

Computes the summary score `mh_p_ksads__suic__past__sx_mean` KSADS - Suicidality [Parent] (Symptom - Past): Mean [validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__suic__slfinj__past_sx`
  - `mh_p_ksads__suic__slfinj__nointnt__past_sx`
  - `mh_p_ksads__suic__slfinj__intnt__past_sx`
  - `mh_p_ksads__suic__slfinj__psbldie__past_sx`
  - `mh_p_ksads__suic__idea__past_sx`
  - `mh_p_ksads__suic__intnt__past_sx`
  - `mh_p_ksads__suic__mthd__past_sx`
  - `mh_p_ksads__suic__plan__past_sx`
  - `mh_p_ksads__suic__prep__past_sx`
  - `mh_p_ksads__suic__attmpt__past_sx`
  - `mh_p_ksads__suic__attmpt__intrpt__past_sx`
  - `mh_p_ksads__suic__attmpt__psbldie__past_sx`
  - `mh_p_ksads__suic__wishdead__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 13 items missing

Usage

```
vars_mh_p_ksads__suic__past__sx

compute_mh_p_ksads__suic__past__sx_mean(
  data,
  name = "mh_p_ksads__suic__past__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__suic__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__suic__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

`vars_mh_p_ksads__suic__pres__sx`
Compute "KSADS - Suicidality [Parent] (Symptom - Present): Mean"

Description

Computes the summary score `mh_p_ksads__suic__pres__sx_mean` KSADS - Suicidality [Parent] (Symptom - Present): Mean [validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__suic__slfinj__pres_sx`
  - `mh_p_ksads__suic__slfinj__nointnt__pres_sx`
  - `mh_p_ksads__suic__slfinj__intnt__pres_sx`
  - `mh_p_ksads__suic__slfinj__psbldie__pres_sx`
  - `mh_p_ksads__suic__idea__pres_sx`
  - `mh_p_ksads__suic__intnt__pres_sx`
  - `mh_p_ksads__suic__mthd__pres_sx`
  - `mh_p_ksads__suic__plan__pres_sx`
  - `mh_p_ksads__suic__prep__pres_sx`
  - `mh_p_ksads__suic__attmpt__pres_sx`
  - `mh_p_ksads__suic__attmpt__intrpt__pres_sx`
  - `mh_p_ksads__suic__attmpt__psbldie__pres_sx`
  - `mh_p_ksads__suic__wishdead__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 13 items missing

Usage

```
vars_mh_p_ksads__suic__pres__sx

compute_mh_p_ksads__suic__pres__sx_mean(
  data,
  name = "mh_p_ksads__suic__pres__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__suic__pres__sx is a character vector of all column names used to compute summary score of mh_p_ksads__suic__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ksads__tic__past__sx

Compute "KSADS - Tic Disorders [Parent] (Symptom - Past): Mean"

Description

Computes the summary score mh_p_ksads__tic__past__sx_mean KSADS - Tic Disorders [Parent] (Symptom - Past): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_p_ksads__tic__mtr__past_sx
  - mh_p_ksads__tic__phnc__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_mh_p_ksads__tic__past__sx

compute_mh_p_ksads__tic__past__sx_mean(
  data,
  name = "mh_p_ksads__tic__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__tic__past__sx is a character vector of all column names used to compute summary score of mh_p_ksads__tic__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_p_ksads__tic__pres__sx *Compute "KSADS - Tic Disorders [Parent] (Symptom - Present): Mean"*

Description

Computes the summary score `mh_p_ksads__tic__pres__sx_mean` KSADS - Tic Disorders [Parent] (Symptom - Present): Mean [validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_p_ksads__tic__mtr__pres_sx`
  - `mh_p_ksads__tic__phnc__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_mh_p_ksads__tic__pres__sx

compute_mh_p_ksads__tic__pres__sx_mean(
  data,
  name = "mh_p_ksads__tic__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ksads__tic__pres__sx is a character vector of all column names used to compute summary score of `mh_p_ksads__tic__pres__sx_mean`

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_p_ple *Compute "Life Events [Parent] (Events): Count"*

Description

Computes the summary score mh_p_ple_count Life Events [Parent] (Events): Count

- *Summarized variables:*
  - mh_p_ple_001
  - mh_p_ple_002
  - mh_p_ple_003
  - mh_p_ple_004
  - mh_p_ple_005
  - mh_p_ple_006
  - mh_p_ple_007
  - mh_p_ple_008
  - mh_p_ple_009
  - mh_p_ple_010
  - mh_p_ple_011
  - mh_p_ple_012
  - mh_p_ple_013
  - mh_p_ple_014
  - mh_p_ple_015
  - mh_p_ple_016
  - mh_p_ple_017
  - mh_p_ple_018
  - mh_p_ple_019
  - mh_p_ple_020
  - mh_p_ple_021

  - mh_p_ple_022
  - mh_p_ple_023
  - mh_p_ple_024
  - mh_p_ple_025
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
vars_mh_p_ple

vars_mh_p_ple__exp

compute_mh_p_ple_count(
  data,
  name = "mh_p_ple_count",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Format

vars_mh_p_ple is a character vector of all column names used to compute summary score of mh_p_ple.

vars_mh_p_ple__exp is a character vector of all column names used to compute summary score of mh_p_ple__exp.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_mh_p_ple__exp__v01

Compute "Life Events [Parent] (Severity of Good Events): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__good_sum__v01 Life Events [Parent] (Severity of Good Events): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016
  - mh_p_ple__exp_017
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_020
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_025
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_029

  - mh_p_ple__exp_030
  - mh_p_ple__exp_031
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
vars_mh_p_ple__exp__v01

compute_mh_p_ple__severity__good_sum__v01(
  data,
  name = "mh_p_ple__severity__good_sum__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_p_ple__exp__v01 is a character vector of all column names used to compute summary score of mh_p_ple__exp.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_ple__exp__v02

Compute "Life Events [Parent] (Severity of Good Events): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__good_sum__v02 Life Events [Parent] (Severity of Good Events): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001

- mh_p_ple__exp_002
- mh_p_ple__exp_003
- mh_p_ple__exp_004
- mh_p_ple__exp_005
- mh_p_ple__exp_006
- mh_p_ple__exp_007
- mh_p_ple__exp_008
- mh_p_ple__exp_009
- mh_p_ple__exp_010
- mh_p_ple__exp_011
- mh_p_ple__exp_012
- mh_p_ple__exp_013
- mh_p_ple__exp_014
- mh_p_ple__exp_015
- mh_p_ple__exp_016
- mh_p_ple__exp_017
- mh_p_ple__exp_018
- mh_p_ple__exp_019
- mh_p_ple__exp_020
- mh_p_ple__exp_021
- mh_p_ple__exp_022
- mh_p_ple__exp_023
- mh_p_ple__exp_024
- mh_p_ple__exp_025
- mh_p_ple__exp_026
- mh_p_ple__exp_027
- mh_p_ple__exp_028
- mh_p_ple__exp_029
- mh_p_ple__exp_030
- mh_p_ple__exp_031
- mh_p_ple__exp_032
- mh_p_ple__severity_001
- mh_p_ple__severity_002
- mh_p_ple__severity_003
- mh_p_ple__severity_004
- mh_p_ple__severity_005
- mh_p_ple__severity_006
- mh_p_ple__severity_007
- mh_p_ple__severity_008
- mh_p_ple__severity_009
- mh_p_ple__severity_010
- mh_p_ple__severity_011

  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017
  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 32 items missing

Usage

```
vars_mh_p_ple__exp__v02

compute_mh_p_ple__severity__good_sum__v02(
  data,
  name = "mh_p_ple__severity__good_sum__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).

events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_p_ple__exp__v02 is a character vector of all column names used to compute summary score of mh_p_ple__exp.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_ple__exp__v03

Compute "Life Events [Parent] (Severity of Good Events): Sum - Version 3 (Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__good_sum__v03 Life Events [Parent] (Severity of Good Events): Sum - Version 3 (Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_003
  - mh_p_ple__exp_004
  - mh_p_ple__exp_005
  - mh_p_ple__exp_006
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_009
  - mh_p_ple__exp_010
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_016

- mh_p_ple__exp_017
- mh_p_ple__exp_018
- mh_p_ple__exp_019
- mh_p_ple__exp_020
- mh_p_ple__exp_021
- mh_p_ple__exp_022
- mh_p_ple__exp_023
- mh_p_ple__exp_024
- mh_p_ple__exp_025
- mh_p_ple__exp_026
- mh_p_ple__exp_027
- mh_p_ple__exp_028
- mh_p_ple__exp_029
- mh_p_ple__exp_030
- mh_p_ple__exp_031
- mh_p_ple__exp_032
- mh_p_ple__exp_033
- mh_p_ple__severity_001
- mh_p_ple__severity_002
- mh_p_ple__severity_003
- mh_p_ple__severity_004
- mh_p_ple__severity_005
- mh_p_ple__severity_006
- mh_p_ple__severity_007
- mh_p_ple__severity_008
- mh_p_ple__severity_009
- mh_p_ple__severity_010
- mh_p_ple__severity_011
- mh_p_ple__severity_012
- mh_p_ple__severity_013
- mh_p_ple__severity_014
- mh_p_ple__severity_015
- mh_p_ple__severity_016
- mh_p_ple__severity_017
- mh_p_ple__severity_018
- mh_p_ple__severity_019
- mh_p_ple__severity_020
- mh_p_ple__severity_021
- mh_p_ple__severity_022
- mh_p_ple__severity_023
- mh_p_ple__severity_024
- mh_p_ple__severity_025

  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
vars_mh_p_ple__exp__v03

compute_mh_p_ple__severity__good_sum__v03(
  data,
  name = "mh_p_ple__severity__good_sum__v03",
  events = "ses-06A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_p_ple__exp__v03 is a character vector of all column names used to compute summary score of mh_p_ple__exp.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_mh_p_ple__exp__v04

Compute "Life Events [Parent] (Severity of Good Events): Sum - Version 4 (Starting at Year 7) [Validation: No more than 4 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity__good_sum__v04 Life Events [Parent] (Severity of Good Events): Sum - Version 4 (Starting at Year 7) [Validation: No more than 4 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__exp_001
  - mh_p_ple__exp_002
  - mh_p_ple__exp_007
  - mh_p_ple__exp_008
  - mh_p_ple__exp_011
  - mh_p_ple__exp_012
  - mh_p_ple__exp_013
  - mh_p_ple__exp_014
  - mh_p_ple__exp_015
  - mh_p_ple__exp_018
  - mh_p_ple__exp_019
  - mh_p_ple__exp_021
  - mh_p_ple__exp_022
  - mh_p_ple__exp_023
  - mh_p_ple__exp_024
  - mh_p_ple__exp_026
  - mh_p_ple__exp_027
  - mh_p_ple__exp_028
  - mh_p_ple__exp_032
  - mh_p_ple__exp_033
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015

  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 4 of 20 items missing

Usage

```
vars_mh_p_ple__exp__v04

compute_mh_p_ple__severity__good_sum__v04(
  data,
  name = "mh_p_ple__severity__good_sum__v04",
  events = "ses-07A",
  combine = TRUE,
  max_na = 4
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 4).

Format

vars_mh_p_ple__exp__v04 is a character vector of all column names used to compute summary score of mh_p_ple__exp.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_p_ple__severity`

Compute "Life Events [Parent] (Severity): Sum [Validation: No more than 5 events missing and no severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity_sum` Life Events [Parent] (Severity): Sum [Validation: No more than 5 events missing and no severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__severity_001`
  - `mh_p_ple__severity_002`
  - `mh_p_ple__severity_003`
  - `mh_p_ple__severity_004`
  - `mh_p_ple__severity_005`
  - `mh_p_ple__severity_006`
  - `mh_p_ple__severity_007`
  - `mh_p_ple__severity_008`
  - `mh_p_ple__severity_009`
  - `mh_p_ple__severity_010`
  - `mh_p_ple__severity_011`
  - `mh_p_ple__severity_012`
  - `mh_p_ple__severity_013`
  - `mh_p_ple__severity_014`
  - `mh_p_ple__severity_015`
  - `mh_p_ple__severity_016`
  - `mh_p_ple__severity_017`
  - `mh_p_ple__severity_018`
  - `mh_p_ple__severity_019`
  - `mh_p_ple__severity_020`
  - `mh_p_ple__severity_021`
  - `mh_p_ple__severity_022`
  - `mh_p_ple__severity_023`
  - `mh_p_ple__severity_024`
  - `mh_p_ple__severity_025`
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
vars_mh_p_ple__severity

compute_mh_p_ple__severity_sum(
  data,
  name = "mh_p_ple__severity_sum",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Format

vars_mh_p_ple__severity is a character vector of all column names used to compute summary score of mh_p_ple__severity.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_ple__severity__v01

Compute "Life Events [Parent] (Severity): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity_sum__v01 Life Events [Parent] (Severity): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003

    - mh_p_ple__severity_004
    - mh_p_ple__severity_005
    - mh_p_ple__severity_006
    - mh_p_ple__severity_007
    - mh_p_ple__severity_008
    - mh_p_ple__severity_009
    - mh_p_ple__severity_010
    - mh_p_ple__severity_011
    - mh_p_ple__severity_012
    - mh_p_ple__severity_013
    - mh_p_ple__severity_014
    - mh_p_ple__severity_015
    - mh_p_ple__severity_016
    - mh_p_ple__severity_017
    - mh_p_ple__severity_018
    - mh_p_ple__severity_019
    - mh_p_ple__severity_020
    - mh_p_ple__severity_021
    - mh_p_ple__severity_022
    - mh_p_ple__severity_023
    - mh_p_ple__severity_024
    - mh_p_ple__severity_025
    - mh_p_ple__severity_026
    - mh_p_ple__severity_027
    - mh_p_ple__severity_028
    - mh_p_ple__severity_029
    - mh_p_ple__severity_030
    - mh_p_ple__severity_031
  - *Excluded values:*
    - 444
    - 777
    - 999
  - *Validation criterion:* maximally 6 of 31 items missing

Usage

```
vars_mh_p_ple__severity__v01

compute_mh_p_ple__severity_sum__v01(
  data,
  name = "mh_p_ple__severity_sum__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_p_ple__severity__v01 is a character vector of all column names used to compute summary score of mh_p_ple__severity.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_ple__severity__v02

Compute "Life Events [Parent] (Severity): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity_sum__v02 Life Events [Parent] (Severity): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012

    - mh_p_ple__severity_013
    - mh_p_ple__severity_014
    - mh_p_ple__severity_015
    - mh_p_ple__severity_016
    - mh_p_ple__severity_017
    - mh_p_ple__severity_018
    - mh_p_ple__severity_019
    - mh_p_ple__severity_020
    - mh_p_ple__severity_021
    - mh_p_ple__severity_022
    - mh_p_ple__severity_023
    - mh_p_ple__severity_024
    - mh_p_ple__severity_025
    - mh_p_ple__severity_026
    - mh_p_ple__severity_027
    - mh_p_ple__severity_028
    - mh_p_ple__severity_029
    - mh_p_ple__severity_030
    - mh_p_ple__severity_031
    - mh_p_ple__severity_032
  - *Excluded values:*
    - 444
    - 777
    - 999
  - *Validation criterion:* maximally 6 of 32 items missing

Usage

```
vars_mh_p_ple__severity__v02

compute_mh_p_ple__severity_sum__v02(
  data,
  name = "mh_p_ple__severity_sum__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.

combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_p_ple__severity__v02 is a character vector of all column names used to compute summary score of mh_p_ple__severity.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_ple__severity__v03

Compute "Life Events [Parent] (Severity): Sum - Version 3 (Year 6) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_p_ple__severity_sum__v03 Life Events [Parent] (Severity): Sum - Version 3 (Year 6) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_p_ple__severity_001
  - mh_p_ple__severity_002
  - mh_p_ple__severity_003
  - mh_p_ple__severity_004
  - mh_p_ple__severity_005
  - mh_p_ple__severity_006
  - mh_p_ple__severity_007
  - mh_p_ple__severity_008
  - mh_p_ple__severity_009
  - mh_p_ple__severity_010
  - mh_p_ple__severity_011
  - mh_p_ple__severity_012
  - mh_p_ple__severity_013
  - mh_p_ple__severity_014
  - mh_p_ple__severity_015
  - mh_p_ple__severity_016
  - mh_p_ple__severity_017

  - mh_p_ple__severity_018
  - mh_p_ple__severity_019
  - mh_p_ple__severity_020
  - mh_p_ple__severity_021
  - mh_p_ple__severity_022
  - mh_p_ple__severity_023
  - mh_p_ple__severity_024
  - mh_p_ple__severity_025
  - mh_p_ple__severity_026
  - mh_p_ple__severity_027
  - mh_p_ple__severity_028
  - mh_p_ple__severity_029
  - mh_p_ple__severity_030
  - mh_p_ple__severity_031
  - mh_p_ple__severity_032
  - mh_p_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
vars_mh_p_ple__severity__v03

compute_mh_p_ple__severity_sum__v03(
  data,
  name = "mh_p_ple__severity_sum__v03",
  events = "ses-06A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_p_ple__severity__v03 is a character vector of all column names used to compute summary score of `mh_p_ple__severity`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_p_ple__severity__v04`

Compute "Life Events [Parent] (Severity): Sum - Version 4 (Starting at Year 7) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score `mh_p_ple__severity_sum__v04` Life Events [Parent] (Severity): Sum - Version 4 (Starting at Year 7) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - `mh_p_ple__severity_001`
  - `mh_p_ple__severity_002`
  - `mh_p_ple__severity_007`
  - `mh_p_ple__severity_008`
  - `mh_p_ple__severity_011`
  - `mh_p_ple__severity_012`
  - `mh_p_ple__severity_013`
  - `mh_p_ple__severity_014`
  - `mh_p_ple__severity_015`
  - `mh_p_ple__severity_018`
  - `mh_p_ple__severity_019`
  - `mh_p_ple__severity_021`
  - `mh_p_ple__severity_022`
  - `mh_p_ple__severity_023`
  - `mh_p_ple__severity_024`
  - `mh_p_ple__severity_026`
  - `mh_p_ple__severity_027`
  - `mh_p_ple__severity_028`
  - `mh_p_ple__severity_032`
  - `mh_p_ple__severity_033`
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 4 of 20 items missing

Usage

```
vars_mh_p_ple__severity__v04

compute_mh_p_ple__severity_sum__v04(
  data,
  name = "mh_p_ple__severity_sum__v04",
  events = "ses-07A",
  combine = TRUE,
  max_na = 4
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 4).

Format

vars_mh_p_ple__severity__v04 is a character vector of all column names used to compute summary score of `mh_p_ple__severity`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_p_ple__v01` *Compute "Life Events [Parent] (Events): Count - Version 1 (Year 3)"*

Description

Computes the summary score `mh_p_ple_count__v01` Life Events [Parent] (Events): Count - Version 1 (Year 3)

- *Summarized variables:*
  - `mh_p_ple_001`
  - `mh_p_ple_002`
  - `mh_p_ple_003`
  - `mh_p_ple_004`
  - `mh_p_ple_005`

  - mh_p_ple_006
  - mh_p_ple_007
  - mh_p_ple_008
  - mh_p_ple_009
  - mh_p_ple_010
  - mh_p_ple_011
  - mh_p_ple_012
  - mh_p_ple_013
  - mh_p_ple_014
  - mh_p_ple_015
  - mh_p_ple_016
  - mh_p_ple_017
  - mh_p_ple_018
  - mh_p_ple_019
  - mh_p_ple_020
  - mh_p_ple_021
  - mh_p_ple_022
  - mh_p_ple_023
  - mh_p_ple_024
  - mh_p_ple_025
  - mh_p_ple_026
  - mh_p_ple_027
  - mh_p_ple_028
  - mh_p_ple_029
  - mh_p_ple_030
  - mh_p_ple_031
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
vars_mh_p_ple__v01

compute_mh_p_ple_count__v01(
  data,
  name = "mh_p_ple_count__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Format

vars_mh_p_ple__v01 is a character vector of all column names used to compute summary score of mh_p_ple.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_ple__v02 *Compute "Life Events [Parent] (Events): Count - Version 2 (Year 4 and Year 5)"*

Description

Computes the summary score mh_p_ple_count__v02 Life Events [Parent] (Events): Count - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - mh_p_ple_001
  - mh_p_ple_002
  - mh_p_ple_003
  - mh_p_ple_004
  - mh_p_ple_005
  - mh_p_ple_006
  - mh_p_ple_007
  - mh_p_ple_008
  - mh_p_ple_009
  - mh_p_ple_010
  - mh_p_ple_011
  - mh_p_ple_012
  - mh_p_ple_013
  - mh_p_ple_014

  - mh_p_ple_015
  - mh_p_ple_016
  - mh_p_ple_017
  - mh_p_ple_018
  - mh_p_ple_019
  - mh_p_ple_020
  - mh_p_ple_021
  - mh_p_ple_022
  - mh_p_ple_023
  - mh_p_ple_024
  - mh_p_ple_025
  - mh_p_ple_026
  - mh_p_ple_027
  - mh_p_ple_028
  - mh_p_ple_029
  - mh_p_ple_030
  - mh_p_ple_031
  - mh_p_ple_032
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
vars_mh_p_ple__v02

compute_mh_p_ple_count__v02(
  data,
  name = "mh_p_ple_count__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Format

vars_mh_p_ple__v02 is a character vector of all column names used to compute summary score of `mh_p_ple`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_p_ple__v03` *Compute "Life Events [Parent] (Events): Count - Version 3 (Year 6)"*

Description

Computes the summary score `mh_p_ple_count__v03` Life Events [Parent] (Events): Count - Version 3 (Year 6)

- *Summarized variables:*
  - `mh_p_ple_001`
  - `mh_p_ple_002`
  - `mh_p_ple_003`
  - `mh_p_ple_004`
  - `mh_p_ple_005`
  - `mh_p_ple_006`
  - `mh_p_ple_007`
  - `mh_p_ple_008`
  - `mh_p_ple_009`
  - `mh_p_ple_010`
  - `mh_p_ple_011`
  - `mh_p_ple_012`
  - `mh_p_ple_013`
  - `mh_p_ple_014`
  - `mh_p_ple_015`
  - `mh_p_ple_016`
  - `mh_p_ple_017`
  - `mh_p_ple_018`
  - `mh_p_ple_019`
  - `mh_p_ple_020`
  - `mh_p_ple_021`
  - `mh_p_ple_022`
  - `mh_p_ple_023`
  - `mh_p_ple_024`
  - `mh_p_ple_025`
  - `mh_p_ple_026`

  - mh_p_ple_027
  - mh_p_ple_028
  - mh_p_ple_029
  - mh_p_ple_030
  - mh_p_ple_031
  - mh_p_ple_032
  - mh_p_ple_033
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
vars_mh_p_ple__v03

compute_mh_p_ple_count__v03(
  data,
  name = "mh_p_ple_count__v03",
  events = "ses-06A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Format

vars_mh_p_ple__v03 is a character vector of all column names used to compute summary score of mh_p_ple.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_mh_p_ple__v04 *Compute "Life Events [Parent] (Events): Count - Version 4 (Starting at Year 7)"*

Description

Computes the summary score mh_p_ple_count__v04 Life Events [Parent] (Events): Count - Version 4 (Starting at Year 7)

- *Summarized variables:*
  - mh_p_ple_001
  - mh_p_ple_002
  - mh_p_ple_007
  - mh_p_ple_008
  - mh_p_ple_011
  - mh_p_ple_012
  - mh_p_ple_013
  - mh_p_ple_014
  - mh_p_ple_015
  - mh_p_ple_018
  - mh_p_ple_019
  - mh_p_ple_021
  - mh_p_ple_022
  - mh_p_ple_023
  - mh_p_ple_024
  - mh_p_ple_026
  - mh_p_ple_027
  - mh_p_ple_028
  - mh_p_ple_032
  - mh_p_ple_033
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
vars_mh_p_ple__v04

compute_mh_p_ple_count__v04(
  data,
  name = "mh_p_ple_count__v04",
  events = "ses-07A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Format

vars_mh_p_ple__v04 is a character vector of all column names used to compute summary score of mh_p_ple.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_p_ssrs *Compute "Short Social Responsiveness Scale [Parent]: Number missing"*

Description

Computes the summary score mh_p_ssrs_nm Short Social Responsiveness Scale [Parent]: Number missing

- *Summarized variables:*
  - mh_p_ssrs_001
  - mh_p_ssrs_002
  - mh_p_ssrs_003
  - mh_p_ssrs_004
  - mh_p_ssrs_005
  - mh_p_ssrs_006
  - mh_p_ssrs_007
  - mh_p_ssrs_008
  - mh_p_ssrs_009
  - mh_p_ssrs_010
  - mh_p_ssrs_011
- *Excluded values:* none

Usage

```
vars_mh_p_ssrs

compute_mh_p_ssrs_nm(
  data,
  name = "mh_p_ssrs_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_p_ssrs is vector of all column names used to compute summary score of mh_p_ssrs scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_p_ssrs_nm(data) |>
  select(
    any_of(c("mh_p_ssrs_nm", vars_mh_p_ssrs))
  )

## End(Not run)
```

---

vars_mh_t_bpm *Compute "Brief Problem Monitor [Teacher]: Number missing"*

Description

Computes the summary score `mh_t_bpm_nm` Brief Problem Monitor [Teacher]: Number missing

- *Summarized variables:*
  - `mh_t_bpm__attn_001`
  - `mh_t_bpm__attn_002`
  - `mh_t_bpm__attn_003`
  - `mh_t_bpm__attn_004`
  - `mh_t_bpm__attn_005`
  - `mh_t_bpm__attn_006`
  - `mh_t_bpm__ext_001`
  - `mh_t_bpm__ext_002`
  - `mh_t_bpm__ext_003`
  - `mh_t_bpm__ext_004`
  - `mh_t_bpm__ext_005`
  - `mh_t_bpm__ext_006`
  - `mh_t_bpm__int_001`
  - `mh_t_bpm__int_002`
  - `mh_t_bpm__int_003`
  - `mh_t_bpm__int_004`
  - `mh_t_bpm__int_005`
  - `mh_t_bpm__int_006`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_t_bpm

compute_mh_t_bpm_nm(
  data,
  name = "mh_t_bpm_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_t_bpm is vector of all column names used to compute summary score of mh_t_bpm scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_t_bpm_nm(data) |>
  select(
    any_of(c("mh_t_bpm_nm", vars_mh_t_bpm))
  )

## End(Not run)
```

---

vars_mh_t_bpm__attn *Compute "Brief Problem Monitor [Teacher] (Attention): Number missing"*

Description

Computes the summary score mh_t_bpm__attn_nm Brief Problem Monitor [Teacher] (Attention): Number missing

- *Summarized variables:*
  - mh_t_bpm__attn_001
  - mh_t_bpm__attn_002
  - mh_t_bpm__attn_003
  - mh_t_bpm__attn_004
  - mh_t_bpm__attn_005
  - mh_t_bpm__attn_006
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_t_bpm__attn

compute_mh_t_bpm__attn_nm(
  data,
  name = "mh_t_bpm__attn_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_t_bpm__attn is vector of all column names used to compute summary score of mh_t_bpm__attn scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_t_bpm__attn_nm(data) |>
  select(
    any_of(c("mh_t_bpm__attn_nm", vars_mh_t_bpm__attn))
  )

## End(Not run)
```

---

vars_mh_t_bpm__ext *Compute "Brief Problem Monitor [Teacher] (Externalizing): Number missing"*

Description

Computes the summary score mh_t_bpm__ext_nm Brief Problem Monitor [Teacher] (Externalizing): Number missing

- *Summarized variables:*
  - mh_t_bpm__ext_001
  - mh_t_bpm__ext_002
  - mh_t_bpm__ext_003
  - mh_t_bpm__ext_004
  - mh_t_bpm__ext_005
  - mh_t_bpm__ext_006
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_t_bpm__ext

compute_mh_t_bpm__ext_nm(
  data,
  name = "mh_t_bpm__ext_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_t_bpm__ext is vector of all column names used to compute summary score of mh_t_bpm__ext scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_t_bpm__ext_nm(data) |>
  select(
    any_of(c("mh_t_bpm__ext_nm", vars_mh_t_bpm__ext))
  )

## End(Not run)
```

---

vars_mh_t_bpm__int *Compute "Brief Problem Monitor [Teacher] (Internalizing): Number missing"*

Description

Computes the summary score mh_t_bpm__int_nm Brief Problem Monitor [Teacher] (Internalizing): Number missing

- *Summarized variables:*
  - mh_t_bpm__int_001
  - mh_t_bpm__int_002
  - mh_t_bpm__int_003
  - mh_t_bpm__int_004
  - mh_t_bpm__int_005
  - mh_t_bpm__int_006
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_t_bpm__int

compute_mh_t_bpm__int_nm(
  data,
  name = "mh_t_bpm__int_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_t_bpm__int is vector of all column names used to compute summary score of mh_t_bpm__int scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_t_bpm__int_nm(data) |>
  select(
    any_of(c("mh_t_bpm__int_nm", vars_mh_t_bpm__int))
  )

## End(Not run)
```

---

vars_mh_y_bisbas__bas__dr

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Drive): Number missing"

Description

Computes the summary score `mh_y_bisbas__bas__dr_nm` The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Drive): Number missing

- *Summarized variables:*
  - `mh_y_bisbas__bas__dr_001`
  - `mh_y_bisbas__bas__dr_002`
  - `mh_y_bisbas__bas__dr_003`
  - `mh_y_bisbas__bas__dr_004`
- *Excluded values:* none

Usage

```
vars_mh_y_bisbas__bas__dr

compute_mh_y_bisbas__bas__dr_nm(
  data,
  name = "mh_y_bisbas__bas__dr_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_bisbas__bas__dr is vector of all column names used to compute summary score of mh_y_bisbas__bas__dr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bisbas__bas__dr_nm(data) |>
  select(
    any_of(c("mh_y_bisbas__bas__dr_nm", vars_mh_y_bisbas__bas__dr))
  )

## End(Not run)
```

---

vars_mh_y_bisbas__bas__fs

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Fun Seeking): Number missing"

Description

Computes the summary score mh_y_bisbas__bas__fs_nm The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Fun Seeking): Number missing

- *Summarized variables:*
  - mh_y_bisbas__bas__fs_001
  - mh_y_bisbas__bas__fs_002
  - mh_y_bisbas__bas__fs_003
  - mh_y_bisbas__bas__fs_004
- *Excluded values:* none

Usage

```
vars_mh_y_bisbas__bas__fs

compute_mh_y_bisbas__bas__fs_nm(
  data,
  name = "mh_y_bisbas__bas__fs_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_bisbas__bas__fs is vector of all column names used to compute summary score of mh_y_bisbas__bas__fs scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bisbas__bas__fs_nm(data) |>
  select(
    any_of(c("mh_y_bisbas__bas__fs_nm", vars_mh_y_bisbas__bas__fs))
  )

## End(Not run)
```

---

vars_mh_y_bisbas__bas__rr

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Reward Responsiveness): Number missing"

Description

Computes the summary score mh_y_bisbas__bas__rr_nm The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BAS Reward Responsiveness): Number missing

- *Summarized variables:*
  - mh_y_bisbas__bas__rr_001
  - mh_y_bisbas__bas__rr_002
  - mh_y_bisbas__bas__rr_003
  - mh_y_bisbas__bas__rr_004
  - mh_y_bisbas__bas__rr_005
- *Excluded values:* none

Usage

```
vars_mh_y_bisbas__bas__rr

compute_mh_y_bisbas__bas__rr_nm(
  data,
  name = "mh_y_bisbas__bas__rr_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_bisbas__bas__rr is vector of all column names used to compute summary score of mh_y_bisbas__bas__rr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bisbas__bas__rr_nm(data) |>
  select(
    any_of(c("mh_y_bisbas__bas__rr_nm", vars_mh_y_bisbas__bas__rr))
  )

## End(Not run)
```

---

vars_mh_y_bisbas__bas__rr__v01

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] ((BAS Reward Responsiveness (modified)): Number missing"

Description

Computes the summary score mh_y_bisbas__bas__rr_nm__v01 The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] ((BAS Reward Responsiveness (modified)): Number missing

- *Summarized variables:*
  - mh_y_bisbas__bas__rr_001
  - mh_y_bisbas__bas__rr_002
  - mh_y_bisbas__bas__rr_004
  - mh_y_bisbas__bas__rr_005
- *Excluded values:* none

Usage

```
vars_mh_y_bisbas__bas__rr__v01

compute_mh_y_bisbas__bas__rr_nm__v01(
  data,
  name = "mh_y_bisbas__bas__rr_nm__v01",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_bisbas__bas__rr__v01 is vector of all column names used to compute summary score of mh_y_bisbas__bas__rr__v01 scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bisbas__bas__rr_nm__v01(data) |>
  select(
    any_of(c("mh_y_bisbas__bas__rr_nm__v01", vars_mh_y_bisbas__bas__rr__v01))
  )
```

```
## End(Not run)
```

`vars_mh_y_bisbas__bis` *Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BIS): Number missing"*

Description

Computes the summary score `mh_y_bisbas__bis_nm` The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BIS): Number missing

- *Summarized variables:*
  - `mh_y_bisbas__bis_001`
  - `mh_y_bisbas__bis_002`
  - `mh_y_bisbas__bis_003`
  - `mh_y_bisbas__bis_004`
  - `mh_y_bisbas__bis_005`
  - `mh_y_bisbas__bis_006`
  - `mh_y_bisbas__bis_007`
- *Excluded values:* none

Usage

```
vars_mh_y_bisbas__bis

compute_mh_y_bisbas__bis_nm(
  data,
  name = "mh_y_bisbas__bis_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

`vars_mh_y_bisbas__bis` is vector of all column names used to compute summary score of `mh_y_bisbas__bis` scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bisbas__bis_nm(data) |>
  select(
    any_of(c("mh_y_bisbas__bis_nm", vars_mh_y_bisbas__bis))
  )

## End(Not run)
```

---

vars_mh_y_bisbas__bis__v01

Compute "The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BIS (modified)): Number missing"

Description

Computes the summary score mh_y_bisbas__bis_nm__v01 The Behavioral Inhibition System/Behavioral Activation System Scales [Youth] (BIS (modified)): Number missing

- *Summarized variables:*
  - mh_y_bisbas__bis_002
  - mh_y_bisbas__bis_003
  - mh_y_bisbas__bis_004
  - mh_y_bisbas__bis_006
- *Excluded values:* none

Usage

```
vars_mh_y_bisbas__bis__v01

compute_mh_y_bisbas__bis_nm__v01(
  data,
  name = "mh_y_bisbas__bis_nm__v01",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.

combine logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_bisbas__bis__v01 is vector of all column names used to compute summary score of mh_y_bisbas__bis__v01 scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bisbas__bis_nm__v01(data) |>
  select(
    any_of(c("mh_y_bisbas__bis_nm__v01", vars_mh_y_bisbas__bis__v01))
  )

## End(Not run)
```

---

vars_mh_y_bpm *Compute "Brief Problem Monitor [Youth]: Number missing"*

Description

Computes the summary score mh_y_bpm_nm Brief Problem Monitor [Youth]: Number missing

- *Summarized variables:*
  - mh_y_bpm__attn_001
  - mh_y_bpm__attn_002
  - mh_y_bpm__attn_003
  - mh_y_bpm__attn_004
  - mh_y_bpm__attn_005
  - mh_y_bpm__attn_006
  - mh_y_bpm__ext_001
  - mh_y_bpm__ext_002
  - mh_y_bpm__ext_003
  - mh_y_bpm__ext_004
  - mh_y_bpm__ext_005
  - mh_y_bpm__ext_006
  - mh_y_bpm__ext_007
  - mh_y_bpm__int_001
  - mh_y_bpm__int_002

  - mh_y_bpm__int_003
  - mh_y_bpm__int_004
  - mh_y_bpm__int_005
  - mh_y_bpm__int_006
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_bpm

compute_mh_y_bpm_nm(
  data,
  name = "mh_y_bpm_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_bpm is vector of all column names used to compute summary score of mh_y_bpm scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bpm_nm(data) |>
  select(
    any_of(c("mh_y_bpm_nm", vars_mh_y_bpm))
  )

## End(Not run)
```

vars_mh_y_bpm__attn *Compute "Brief Problem Monitor [Youth] (Attention): Number missing"*

Description

Computes the summary score mh_y_bpm__attn_nm Brief Problem Monitor [Youth] (Attention): Number missing

- *Summarized variables:*
  - mh_y_bpm__attn_001
  - mh_y_bpm__attn_002
  - mh_y_bpm__attn_003
  - mh_y_bpm__attn_004
  - mh_y_bpm__attn_005
  - mh_y_bpm__attn_006
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_bpm__attn

compute_mh_y_bpm__attn_nm(
  data,
  name = "mh_y_bpm__attn_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_bpm__attn is vector of all column names used to compute summary score of mh_y_bpm__attn scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bpm__attn_nm(data) |>
  select(
    any_of(c("mh_y_bpm__attn_nm", vars_mh_y_bpm__attn))
  )

## End(Not run)
```

---

vars_mh_y_bpm__ext *Compute "Brief Problem Monitor [Youth] (Externalizing): Number missing"*

Description

Computes the summary score mh_y_bpm__ext_nm Brief Problem Monitor [Youth] (Externalizing): Number missing

- *Summarized variables:*
  - mh_y_bpm__ext_001
  - mh_y_bpm__ext_002
  - mh_y_bpm__ext_003
  - mh_y_bpm__ext_004
  - mh_y_bpm__ext_005
  - mh_y_bpm__ext_006
  - mh_y_bpm__ext_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_bpm__ext

compute_mh_y_bpm__ext_nm(
  data,
  name = "mh_y_bpm__ext_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_bpm__ext is vector of all column names used to compute summary score of mh_y_bpm__ext scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bpm__ext_nm(data) |>
  select(
    any_of(c("mh_y_bpm__ext_nm", vars_mh_y_bpm__ext))
  )

## End(Not run)
```

---

vars_mh_y_bpm__int *Compute "Brief Problem Monitor [Youth] (Internalizing): Number missing"*

Description

Computes the summary score mh_y_bpm__int_nm Brief Problem Monitor [Youth] (Internalizing): Number missing

- *Summarized variables:*
  - mh_y_bpm__int_001
  - mh_y_bpm__int_002
  - mh_y_bpm__int_003
  - mh_y_bpm__int_004
  - mh_y_bpm__int_005
  - mh_y_bpm__int_006
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_bpm__int

compute_mh_y_bpm__int_nm(
  data,
  name = "mh_y_bpm__int_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_bpm__int is vector of all column names used to compute summary score of mh_y_bpm__int scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_bpm__int_nm(data) |>
  select(
    any_of(c("mh_y_bpm__int_nm", vars_mh_y_bpm__int))
  )

## End(Not run)
```

---

vars_mh_y_erq__reapp *Compute "Emotion Regulation Questionnaire [Youth] (Reappraisal): Mean"*

Description

Computes the summary score mh_y_erq__reapp_mean Emotion Regulation Questionnaire [Youth] (Reappraisal): Mean

- *Summarized variables:*
  - mh_y_erq__reapp_001
  - mh_y_erq__reapp_002
  - mh_y_erq__reapp_003
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
vars_mh_y_erq__reapp

compute_mh_y_erq__reapp_mean(
  data,
  name = "mh_y_erq__reapp_mean",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_erq__reapp is vector of all column names used to compute summary score of mh_y_erq__reapp scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_erq__reapp_mean(data) |>
  select(
    any_of(c("mh_y_erq__reapp_mean", vars_mh_y_erq__reapp))
  )

## End(Not run)
```

`vars_mh_y_erq__suppr` *Compute "Emotion Regulation Questionnaire [Youth] (Suppression): Mean"*

Description

Computes the summary score `mh_y_erq__suppr_mean` Emotion Regulation Questionnaire [Youth] (Suppression): Mean

- *Summarized variables:*
  - `mh_y_erq__suppr_001`
  - `mh_y_erq__suppr_002`
  - `mh_y_erq__suppr_003`
- *Excluded values:*
  - 777
- *Validation criterion:* none of 3 items missing

Usage

```
vars_mh_y_erq__suppr

compute_mh_y_erq__suppr_mean(
  data,
  name = "mh_y_erq__suppr_mean",
  max_na = 0,
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_erq__suppr is vector of all column names used to compute summary score of mh_y_erq__suppr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_erq__suppr_mean(data) |>
  select(
    any_of(c("mh_y_erq__suppr_mean", vars_mh_y_erq__suppr))
  )

## End(Not run)
```

---

vars_mh_y_ksads__bpd__past__sx

Compute "KSADS - Bipolar Disorders [Youth] (Symptom - Past): Mean "

Description

Computes the summary score mh_y_ksads__bpd__past__sx_mean KSADS - Bipolar Disorders [Youth] (Symptom - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__bpd__distract__incr__past_sx
  - mh_y_ksads__bpd__distract__past_sx
  - mh_y_ksads__bpd__enrg__incr__past_sx
  - mh_y_ksads__bpd__flgtid__past_sx
  - mh_y_ksads__bpd__goaldir__incr__past_sx
  - mh_y_ksads__bpd__grndios__past_sx
  - mh_y_ksads__bpd__hyprsex__past_sx
  - mh_y_ksads__bpd__irrit__expl__past_sx
  - mh_y_ksads__bpd__irrit__manic__past_sx
  - mh_y_ksads__bpd__mood__elv__past_sx
  - mh_y_ksads__bpd__mood__euph__past_sx
  - mh_y_ksads__bpd__prspch__past_sx
  - mh_y_ksads__bpd__psymot__agit__past_sx
  - mh_y_ksads__bpd__ractho__past_sx
  - mh_y_ksads__bpd__riskactv__past_sx
  - mh_y_ksads__bpd__slpdecr__past_sx

- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 16 items missing

Usage

```
vars_mh_y_ksads__bpd__past__sx

compute_mh_y_ksads__bpd__past__sx_mean(
  data,
  name = "mh_y_ksads__bpd__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__bpd__past__sx is a character vector of all column names used to compute summary score of mh_y_ksads__bpd__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_y_ksads__bpd__pres__sx
Compute "KSADS - Bipolar Disorders [Youth] (Symptom - Present): Mean"

Description

Computes the summary score mh_y_ksads__bpd__pres__sx_mean KSADS - Bipolar Disorders [Youth] (Symptom - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__bpd__distract__incr__pres_sx
  - mh_y_ksads__bpd__distract__pres_sx
  - mh_y_ksads__bpd__enrg__incr__pres_sx
  - mh_y_ksads__bpd__flgtid__pres_sx
  - mh_y_ksads__bpd__goaldir__incr__pres_sx
  - mh_y_ksads__bpd__grndios__pres_sx
  - mh_y_ksads__bpd__hyprsex__pres_sx
  - mh_y_ksads__bpd__irrit__expl__pres_sx
  - mh_y_ksads__bpd__irrit__manic__pres_sx
  - mh_y_ksads__bpd__mood__elv__pres_sx
  - mh_y_ksads__bpd__mood__euph__pres_sx
  - mh_y_ksads__bpd__prspch__pres_sx
  - mh_y_ksads__bpd__psymot__agit__pres_sx
  - mh_y_ksads__bpd__ractho__pres_sx
  - mh_y_ksads__bpd__riskactv__pres_sx
  - mh_y_ksads__bpd__slpdecr__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 16 items missing

Usage

```
vars_mh_y_ksads__bpd__pres__sx

compute_mh_y_ksads__bpd__pres__sx_mean(
  data,
  name = "mh_y_ksads__bpd__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__bpd__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__bpd__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_ksads__cond__past__sx

Compute "KSADS - Conduct Disorder [Youth] (Symptom - Past): Mean "

Description

Computes the summary score mh_y_ksads__cond__past__sx_mean KSADS - Conduct Disorder [Youth] (Symptom - Past): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__cond__breakin__past_sx
  - mh_y_ksads__cond__bully__past_sx
  - mh_y_ksads__cond__fight__past_sx
  - mh_y_ksads__cond__fire__past_sx

  - mh_y_ksads__cond__lies__past_sx
  - mh_y_ksads__cond__outlate__past_sx
  - mh_y_ksads__cond__physcruel__anml__past_sx
  - mh_y_ksads__cond__physcruel__ppl__past_sx
  - mh_y_ksads__cond__rob__past_sx
  - mh_y_ksads__cond__runaway__past_sx
  - mh_y_ksads__cond__steal__past_sx
  - mh_y_ksads__cond__truant__past_sx
  - mh_y_ksads__cond__vandal__past_sx
  - mh_y_ksads__cond__weapon__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_mh_y_ksads__cond__past__sx

compute_mh_y_ksads__cond__past__sx_mean(
  data,
  name = "mh_y_ksads__cond__past__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__cond__past__sx is a character vector of all column names used to compute summary score of mh_y_ksads__cond__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

`vars_mh_y_ksads__cond__pres__sx`
Compute "KSADS - Conduct Disorder [Youth] (Symptom - Present): Mean"

Description

Computes the summary score `mh_y_ksads__cond__pres__sx_mean` KSADS - Conduct Disorder [Youth] (Symptom - Present): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `mh_y_ksads__cond__breakin__pres_sx`
  - `mh_y_ksads__cond__bully__pres_sx`
  - `mh_y_ksads__cond__fight__pres_sx`
  - `mh_y_ksads__cond__fire__pres_sx`
  - `mh_y_ksads__cond__lies__pres_sx`
  - `mh_y_ksads__cond__outlate__pres_sx`
  - `mh_y_ksads__cond__physcruel__anml__pres_sx`
  - `mh_y_ksads__cond__physcruel__ppl__pres_sx`
  - `mh_y_ksads__cond__rob__pres_sx`
  - `mh_y_ksads__cond__runaway__pres_sx`
  - `mh_y_ksads__cond__steal__pres_sx`
  - `mh_y_ksads__cond__truant__pres_sx`
  - `mh_y_ksads__cond__vandal__pres_sx`
  - `mh_y_ksads__cond__weapon__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_mh_y_ksads__cond__pres__sx

compute_mh_y_ksads__cond__pres__sx_mean(
  data,
  name = "mh_y_ksads__cond__pres__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__cond__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__cond__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_y_ksads__dep__past__sx *Compute "KSADS - Depressive Disorders [Youth] (Symptom - Past): Mean "*

Description

Computes the summary score mh_y_ksads__dep__past__sx_mean KSADS - Depressive Disorders [Youth] (Symptom - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__dep__anhed__past_sx
  - mh_y_ksads__dep__appdecr__past_sx
  - mh_y_ksads__dep__conc__past_sx
  - mh_y_ksads__dep__fatig__past_sx
  - mh_y_ksads__dep__glt__past_sx
  - mh_y_ksads__dep__hplss__past_sx
  - mh_y_ksads__dep__hyprsom__past_sx
  - mh_y_ksads__dep__incapp__past_sx
  - mh_y_ksads__dep__indec__past_sx
  - mh_y_ksads__dep__insom__past_sx
  - mh_y_ksads__dep__irrit__past_sx
  - mh_y_ksads__dep__mood__past_sx
  - mh_y_ksads__dep__psymot__agit__past_sx
  - mh_y_ksads__dep__psymot__rtrd__past_sx
  - mh_y_ksads__dep__slfestmdecr__past_sx
  - mh_y_ksads__dep__wghtgain__past_sx
  - mh_y_ksads__dep__wghtloss__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 17 items missing

Usage

```
vars_mh_y_ksads__dep__past__sx

compute_mh_y_ksads__dep__past__sx_mean(
  data,
  name = "mh_y_ksads__dep__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__dep__past__sx is a character vector of all column names used to compute summary score of mh_y_ksads__dep__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_ksads__dep__pres__sx

Compute "KSADS - Depressive Disorders [Youth] (Symptom - Present): Mean"

Description

Computes the summary score mh_y_ksads__dep__pres__sx_mean KSADS - Depressive Disorders [Youth] (Symptom - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__dep__anhed__pres_sx
  - mh_y_ksads__dep__appdecr__pres_sx
  - mh_y_ksads__dep__conc__pres_sx
  - mh_y_ksads__dep__fatig__pres_sx

  - mh_y_ksads__dep__glt__pres_sx
  - mh_y_ksads__dep__hplss__pres_sx
  - mh_y_ksads__dep__hyprsom__pres_sx
  - mh_y_ksads__dep__incapp__pres_sx
  - mh_y_ksads__dep__indec__pres_sx
  - mh_y_ksads__dep__irrit__pres_sx
  - mh_y_ksads__dep__mood__pres_sx
  - mh_y_ksads__dep__psymot__agit__pres_sx
  - mh_y_ksads__dep__psymot__rtrd__pres_sx
  - mh_y_ksads__dep__slfestmdecr__pres_sx
  - mh_y_ksads__dep__wghtgain__pres_sx
  - mh_y_ksads__dep__wghtloss__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 17 items missing

Usage

```
vars_mh_y_ksads__dep__pres__sx

compute_mh_y_ksads__dep__pres__sx_mean(
  data,
  name = "mh_y_ksads__dep__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__dep__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__dep__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_ksads__dmdd__sx

Compute "KSADS - Disruptive Mood Dysregulation Disorder [Youth] (Symptom): Mean"

Description

Computes the summary score mh_y_ksads__dmdd__sx_mean KSADS - Disruptive Mood Dysregulation Disorder [Youth] (Symptom): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__dmdd__outbrst__3perwk_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
vars_mh_y_ksads__dmdd__sx

compute_mh_y_ksads__dmdd__sx_mean(
  data,
  name = "mh_y_ksads__dmdd__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__dmdd__sx is a character vector of all column names used to compute summary score of mh_y_ksads__dmdd__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_ksads__ed__past__sx

Compute "KSADS - Eating Disorders [Youth] (Symptom - Past): Mean"

Description

Computes the summary score mh_y_ksads__ed__past__sx_mean KSADS - Eating Disorders [Youth] (Symptom - Past): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__ed__binge__distrs__past_sx
  - mh_y_ksads__ed__binge__past_sx
  - mh_y_ksads__ed__compbehav__past_sx
  - mh_y_ksads__ed__emac__past_sx

  - mh_y_ksads__ed__fear__obese__past_sx
  - mh_y_ksads__ed__slfwrth__past_sx
  - mh_y_ksads__ed__wghtcntrl__oth__past_sx
  - mh_y_ksads__ed__wghtcntrl__vom__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_y_ksads__ed__past__sx

compute_mh_y_ksads__ed__past__sx_mean(
  data,
  name = "mh_y_ksads__ed__past__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__ed__past__sx is a character vector of all column names used to compute summary score of mh_y_ksads__ed__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see `combine`.

`vars_mh_y_ksads__ed__pres__sx`

Compute "KSADS - Eating Disorders [Youth] (Symptom - Present): Mean"

Description

Computes the summary score `mh_y_ksads__ed__pres__sx_mean` KSADS - Eating Disorders [Youth] (Symptom - Present): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - `mh_y_ksads__ed__binge__distrs__pres_sx`
  - `mh_y_ksads__ed__binge__pres_sx`
  - `mh_y_ksads__ed__compbehav__pres_sx`
  - `mh_y_ksads__ed__emac__pres_sx`
  - `mh_y_ksads__ed__fear__obese__pres_sx`
  - `mh_y_ksads__ed__slfwrth__pres_sx`
  - `mh_y_ksads__ed__wghtcntrl__oth__pres_sx`
  - `mh_y_ksads__ed__wghtcntrl__vom__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 8 items missing

Usage

```
vars_mh_y_ksads__ed__pres__sx

compute_mh_y_ksads__ed__pres__sx_mean(
  data,
  name = "mh_y_ksads__ed__pres__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.

exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__ed__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__ed__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_ksads__gad__past__sx

Compute "KSADS - Generalized Anxiety Disorder [Youth] (Symptom - Past): Mean"

Description

Computes the summary score mh_y_ksads__gad__past__sx_mean KSADS - Generalized Anxiety Disorder [Youth] (Symptom - Past): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__gad__worry__6mo__past_sx
  - mh_y_ksads__gad__worry__diffctrl__past_sx
  - mh_y_ksads__gad__worry__excess__past_sx
  - mh_y_ksads__gad__worry__multi__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_mh_y_ksads__gad__past__sx

compute_mh_y_ksads__gad__past__sx_mean(
  data,
  name = "mh_y_ksads__gad__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__gad__past__sx is a character vector of all column names used to compute summary score of mh_y_ksads__gad__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_y_ksads__gad__pres__sx

Compute "KSADS - Generalized Anxiety Disorder [Youth] (Symptom - Present): Mean"

Description

Computes the summary score mh_y_ksads__gad__pres__sx_mean KSADS - Generalized Anxiety Disorder [Youth] (Symptom - Present): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__gad__worry__6mo__pres_sx
  - mh_y_ksads__gad__worry__diffctrl__pres_sx
  - mh_y_ksads__gad__worry__excess__pres_sx
  - mh_y_ksads__gad__worry__multi__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_mh_y_ksads__gad__pres__sx

compute_mh_y_ksads__gad__pres__sx_mean(
  data,
  name = "mh_y_ksads__gad__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__gad__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__gad__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_ksads__ocd__past__sx

Compute "KSADS - Obsessive Compulsive Disorder [Youth] (Symptom - Past): Mean"

Description

Computes the summary score mh_y_ksads__ocd__past__sx_mean KSADS - Obsessive Compulsive Disorder [Youth] (Symptom - Past): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__ocd__compuls__past_sx
  - mh_y_ksads__ocd__compuls__prvntanx__past_sx
  - mh_y_ksads__ocd__compuls__tcnsm__past_sx
  - mh_y_ksads__ocd__obsess__intru__past_sx
  - mh_y_ksads__ocd__obsess__past_sx
  - mh_y_ksads__ocd__obsess__tcnsm__past_sx
  - mh_y_ksads__ocd__suprstho__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_mh_y_ksads__ocd__past__sx

compute_mh_y_ksads__ocd__past__sx_mean(
  data,
  name = "mh_y_ksads__ocd__past__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__ocd__past__sx is a character vector of all column names used to compute summary score of mh_y_ksads__ocd__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_ksads__ocd__pres__sx

Compute "KSADS - Obsessive Compulsive Disorder [Youth] (Symptom - Present): Mean"

Description

Computes the summary score mh_y_ksads__ocd__pres__sx_mean KSADS - Obsessive Compulsive Disorder [Youth] (Symptom - Present): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__ocd__compuls__pres_sx
  - mh_y_ksads__ocd__compuls__prvntanx__pres_sx
  - mh_y_ksads__ocd__compuls__tcnsm__pres_sx
  - mh_y_ksads__ocd__obsess__intru__pres_sx

  - mh_y_ksads__ocd__obsess__pres_sx
  - mh_y_ksads__ocd__obsess__tcnsm__pres_sx
  - mh_y_ksads__ocd__suprstho__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 1 of 7 items missing

Usage

```
vars_mh_y_ksads__ocd__pres__sx

compute_mh_y_ksads__ocd__pres__sx_mean(
  data,
  name = "mh_y_ksads__ocd__pres__sx_mean",
  max_na = 1,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__ocd__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__ocd__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see `combine`.

`vars_mh_y_ksads__panic__past__sx`

Compute "KSADS - Panic Disorder [Youth] (Symptom - Past): Mean"

Description

Computes the summary score `mh_y_ksads__panic__past__sx_mean` KSADS - Panic Disorder [Youth] (Symptom - Past): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_y_ksads__panic__attack__maladp__past_sx`
  - `mh_y_ksads__panic__attack__past_sx`
  - `mh_y_ksads__panic__sympt__past_sx`
  - `mh_y_ksads__panic__worry__attack__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_mh_y_ksads__panic__past__sx

compute_mh_y_ksads__panic__past__sx_mean(
  data,
  name = "mh_y_ksads__panic__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__panic__past__sx is a character vector of all column names used to compute summary score of `mh_y_ksads__panic__past__sx_mean`

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

---

vars_mh_y_ksads__panic__pres__sx

Compute "KSADS - Panic Disorder [Youth] (Symptom - Present): Mean"

Description

Computes the summary score `mh_y_ksads__panic__pres__sx_mean` KSADS - Panic Disorder [Youth] (Symptom - Present): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_y_ksads__panic__attack__maladp__pres_sx`
  - `mh_y_ksads__panic__attack__pres_sx`
  - `mh_y_ksads__panic__sympt__pres_sx`
  - `mh_y_ksads__panic__worry__attack__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_mh_y_ksads__panic__pres__sx

compute_mh_y_ksads__panic__pres__sx_mean(
  data,
  name = "mh_y_ksads__panic__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__panic__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__panic__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_ksads__ptsd__past__sx
Compute "KSADS - Post-Traumatic Stress Disorder [Youth] (Symptom - Past): Mean"

Description

Computes the summary score mh_y_ksads__ptsd__past__sx_mean KSADS - Post-Traumatic Stress Disorder [Youth] (Symptom - Past): Mean [Validation: No more than 4 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__ptsd__anhed__past_sx
  - mh_y_ksads__ptsd__avoid__extrmnd__past_sx
  - mh_y_ksads__ptsd__avoid__trmatho__past_sx
  - mh_y_ksads__ptsd__concprob__past_sx
  - mh_y_ksads__ptsd__depersnl__past_sx
  - mh_y_ksads__ptsd__derealztn__past_sx
  - mh_y_ksads__ptsd__detach__past_sx
  - mh_y_ksads__ptsd__distortcog__cause__past_sx
  - mh_y_ksads__ptsd__distortcog__consq__past_sx
  - mh_y_ksads__ptsd__emot__neg__past_sx
  - mh_y_ksads__ptsd__emot__nopos__past_sx
  - mh_y_ksads__ptsd__extrmnd__distrs__past_sx
  - mh_y_ksads__ptsd__flshbck__past_sx
  - mh_y_ksads__ptsd__hyprvigl__past_sx
  - mh_y_ksads__ptsd__intrmnd__distrs__past_sx
  - mh_y_ksads__ptsd__irrit__past_sx
  - mh_y_ksads__ptsd__memloss__past_sx
  - mh_y_ksads__ptsd__negblf__past_sx
  - mh_y_ksads__ptsd__nghtmr__past_sx
  - mh_y_ksads__ptsd__physreact__past_sx
  - mh_y_ksads__ptsd__rckls__past_sx
  - mh_y_ksads__ptsd__sleepdistb__past_sx
  - mh_y_ksads__ptsd__startle__past_sx
  - mh_y_ksads__ptsd__trmatho__intru__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 4 of 24 items missing

Usage

```
vars_mh_y_ksads__ptsd__past__sx

compute_mh_y_ksads__ptsd__past__sx_mean(
  data,
  name = "mh_y_ksads__ptsd__past__sx_mean",
  max_na = 4,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__ptsd__past__sx is a character vector of all column names used to compute summary score of mh_y_ksads__ptsd__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

`vars_mh_y_ksads__ptsd__pres__sx`
Compute "KSADS - Post-Traumatic Stress Disorder [Youth] (Symptom - Present): Mean"

Description

Computes the summary score `mh_y_ksads__ptsd__pres__sx_mean` KSADS - Post-Traumatic Stress Disorder [Youth] (Symptom - Present): Mean [Validation: No more than 4 missing or declined]

- *Summarized variables:*
  - `mh_y_ksads__ptsd__anhed__pres_sx`
  - `mh_y_ksads__ptsd__avoid__extrmnd__pres_sx`
  - `mh_y_ksads__ptsd__avoid__trmatho__pres_sx`
  - `mh_y_ksads__ptsd__concprob__pres_sx`
  - `mh_y_ksads__ptsd__depersnl__pres_sx`
  - `mh_y_ksads__ptsd__derealztn__pres_sx`
  - `mh_y_ksads__ptsd__detach__pres_sx`
  - `mh_y_ksads__ptsd__distortcog__cause__pres_sx`
  - `mh_y_ksads__ptsd__distortcog__consq__pres_sx`
  - `mh_y_ksads__ptsd__emot__neg__pres_sx`
  - `mh_y_ksads__ptsd__emot__nopos__pres_sx`
  - `mh_y_ksads__ptsd__extrmnd__distrs__pres_sx`
  - `mh_y_ksads__ptsd__flshbck__pres_sx`
  - `mh_y_ksads__ptsd__hyprvigl__pres_sx`
  - `mh_y_ksads__ptsd__intrmnd__distrs__pres_sx`
  - `mh_y_ksads__ptsd__irrit__pres_sx`
  - `mh_y_ksads__ptsd__memloss__pres_sx`
  - `mh_y_ksads__ptsd__negblf__pres_sx`
  - `mh_y_ksads__ptsd__nghtmr__pres_sx`
  - `mh_y_ksads__ptsd__physreact__pres_sx`
  - `mh_y_ksads__ptsd__rckls__pres_sx`
  - `mh_y_ksads__ptsd__sleepdistb__pres_sx`
  - `mh_y_ksads__ptsd__startle__pres_sx`
  - `mh_y_ksads__ptsd__trmatho__intru__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 4 of 24 items missing

Usage

```
vars_mh_y_ksads__ptsd__pres__sx

compute_mh_y_ksads__ptsd__pres__sx_mean(
  data,
  name = "mh_y_ksads__ptsd__pres__sx_mean",
  max_na = 4,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__ptsd__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__ptsd__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

`vars_mh_y_ksads__sleep__past__sx`
Compute "KSADS - Sleep Problems [Youth] (Symptom - Past): Mean"

Description

Computes the summary score `mh_y_ksads__sleep__past__sx_mean` KSADS - Sleep Problems [Youth] (Symptom - Past): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_y_ksads__sleep__insom__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
vars_mh_y_ksads__sleep__past__sx

compute_mh_y_ksads__sleep__past__sx_mean(
  data,
  name = "mh_y_ksads__sleep__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__sleep__past__sx is a character vector of all column names used to compute summary score of `mh_y_ksads__sleep__past__sx_mean`

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

---

vars_mh_y_ksads__sleep__pres__sx

Compute "KSADS - Sleep Problems [Youth] (Symptom - Present): Mean"

Description

Computes the summary score `mh_y_ksads__sleep__pres__sx_mean` KSADS - Sleep Problems [Youth] (Symptom - Present): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_y_ksads__sleep__insom__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 1 items missing

Usage

```
vars_mh_y_ksads__sleep__pres__sx

compute_mh_y_ksads__sleep__pres__sx_mean(
  data,
  name = "mh_y_ksads__sleep__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__sleep__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__sleep__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_ksads__socanx__past__sx

Compute "KSADS - Social Anxiety Disorder [Youth] (Symptom - Past): Mean"

Description

Computes the summary score mh_y_ksads__socanx__past__sx_mean KSADS - Social Anxiety Disorder [Youth] (Symptom - Past): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__socanx__anx__past_sx
  - mh_y_ksads__socanx__avoid__past_sx
  - mh_y_ksads__socanx__fear__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 3 items missing

Usage

```
vars_mh_y_ksads__socanx__past__sx

compute_mh_y_ksads__socanx__past__sx_mean(
  data,
  name = "mh_y_ksads__socanx__past__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__socanx__past__sx is a character vector of all column names used to compute summary score of mh_y_ksads__socanx__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_y_ksads__socanx__pres__sx *Compute "KSADS - Social Anxiety Disorder [Youth] (Symptom - Present): Mean"*

Description

Computes the summary score `mh_y_ksads__socanx__pres__sx_mean` KSADS - Social Anxiety Disorder [Youth] (Symptom - Present): Mean [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `mh_y_ksads__socanx__anx__pres_sx`
  - `mh_y_ksads__socanx__avoid__pres_sx`
  - `mh_y_ksads__socanx__fear__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 0 of 3 items missing

Usage

```
vars_mh_y_ksads__socanx__pres__sx

compute_mh_y_ksads__socanx__pres__sx_mean(
  data,
  name = "mh_y_ksads__socanx__pres__sx_mean",
  max_na = 0,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__socanx__pres__sx is a character vector of all column names used to compute summary score of `mh_y_ksads__socanx__pres__sx_mean`

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

`vars_mh_y_ksads__suic__past__sx`

Compute "KSADS - Suicidality [Youth] (Symptom - Past): Mean"

Description

Computes the summary score `mh_y_ksads__suic__past__sx_mean` KSADS - Suicidality [Youth] (Symptom - Past): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `mh_y_ksads__suic__slfinj__past_sx`
  - `mh_y_ksads__suic__slfinj__nointnt__past_sx`
  - `mh_y_ksads__suic__slfinj__intnt__past_sx`
  - `mh_y_ksads__suic__slfinj__psbldie__past_sx`
  - `mh_y_ksads__suic__idea__past_sx`
  - `mh_y_ksads__suic__intnt__past_sx`
  - `mh_y_ksads__suic__mthd__past_sx`
  - `mh_y_ksads__suic__plan__past_sx`
  - `mh_y_ksads__suic__prep__past_sx`
  - `mh_y_ksads__suic__attmpt__past_sx`
  - `mh_y_ksads__suic__attmpt__intrpt__past_sx`
  - `mh_y_ksads__suic__attmpt__psbldie__past_sx`
  - `mh_y_ksads__suic__wishdead__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 13 items missing

Usage

```
vars_mh_y_ksads__suic__past__sx

compute_mh_y_ksads__suic__past__sx_mean(
  data,
  name = "mh_y_ksads__suic__past__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__suic__past__sx is a character vector of all column names used to compute summary score of mh_y_ksads__suic__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_mh_y_ksads__suic__pres__sx
Compute "KSADS - Suicidality [Youth] (Symptom - Present): Mean"

Description

Computes the summary score mh_y_ksads__suic__pres__sx_mean KSADS - Suicidality [Youth] (Symptom - Present): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - mh_y_ksads__suic__slfinj__pres_sx
  - mh_y_ksads__suic__slfinj__nointnt__pres_sx
  - mh_y_ksads__suic__slfinj__intnt__pres_sx
  - mh_y_ksads__suic__slfinj__psbldie__pres_sx
  - mh_y_ksads__suic__idea__pres_sx
  - mh_y_ksads__suic__intnt__pres_sx
  - mh_y_ksads__suic__mthd__pres_sx
  - mh_y_ksads__suic__plan__pres_sx
  - mh_y_ksads__suic__prep__pres_sx
  - mh_y_ksads__suic__attmpt__pres_sx
  - mh_y_ksads__suic__attmpt__intrpt__pres_sx
  - mh_y_ksads__suic__attmpt__psbldie__pres_sx
  - mh_y_ksads__suic__wishdead__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 13 items missing

Usage

```
vars_mh_y_ksads__suic__pres__sx

compute_mh_y_ksads__suic__pres__sx_mean(
  data,
  name = "mh_y_ksads__suic__pres__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.

max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ksads__suic__pres__sx is a character vector of all column names used to compute summary score of mh_y_ksads__suic__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_mh_y_pai *Compute "NIH Toolbox - Positive Affect Items [Youth] (NA): Number missing"*

Description

Computes the summary score mh_y_pai_nm NIH Toolbox - Positive Affect Items [Youth] (NA): Number missing

- *Summarized variables:*
  - mh_y_pai_001
  - mh_y_pai_002
  - mh_y_pai_003
  - mh_y_pai_004
  - mh_y_pai_005
  - mh_y_pai_006
  - mh_y_pai_007
  - mh_y_pai_008

  - mh_y_pai_009
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_pai

compute_mh_y_pai_nm(
  data,
  name = "mh_y_pai_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_pai is vector of all column names used to compute summary score of compute_mh_y_pai scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_pai_nm(data) |>
  select(
    any_of(c("mh_y_pai_nm", vars_mh_y_pai))
  )

## End(Not run)
```

vars_mh_y_peq__overt__agg

Compute "Peer Experiences Questionnaire [Youth] (Overt Aggression): Number missing"

Description

Computes the summary score mh_y_peq__overt__agg_nm Peer Experiences Questionnaire [Youth] (Overt Aggression): Number missing

- *Summarized variables:*
  - mh_y_peq__overt__agg_001
  - mh_y_peq__overt__agg_002
  - mh_y_peq__overt__agg_003
- *Excluded values:*
  - 777

Usage

```
vars_mh_y_peq__overt__agg

compute_mh_y_peq__overt__agg_nm(
  data,
  name = "mh_y_peq__overt__agg_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_peq__overt__agg is vector of all column names used to compute summary score of mh_y_peq__overt__agg scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_peq__overt__agg_nm(data) |>
  select(
    any_of(c("mh_y_peq__overt__agg_nm", vars_mh_y_peq__overt__agg))
  )

## End(Not run)
```

---

vars_mh_y_peq__overt__vict

Compute "Peer Experiences Questionnaire [Youth] (Overt Victimization): Number missing"

Description

Computes the summary score `mh_y_peq__overt__vict_nm` Peer Experiences Questionnaire [Youth] (Overt Victimization): Number missing

- *Summarized variables:*
  - `mh_y_peq__overt__vict_001`
  - `mh_y_peq__overt__vict_002`
  - `mh_y_peq__overt__vict_003`
- *Excluded values:*
  - 777

Usage

```
vars_mh_y_peq__overt__vict

compute_mh_y_peq__overt__vict_nm(
  data,
  name = "mh_y_peq__overt__vict_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_peq__overt__vict is vector of all column names used to compute summary score of mh_y_peq__overt__vict scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_peq__overt__vict_nm(data) |>
  select(
    any_of(c("mh_y_peq__overt__vict_nm", vars_mh_y_peq__overt__vict))
  )

## End(Not run)
```

---

vars_mh_y_peq__rel__agg

Compute "Peer Experiences Questionnaire [Youth] (Relational Aggression): Number missing"

Description

Computes the summary score mh_y_peq__rel__agg_nm Peer Experiences Questionnaire [Youth] (Relational Aggression): Number missing

- *Summarized variables:*
  - mh_y_peq__rel__agg_001
  - mh_y_peq__rel__agg_002
  - mh_y_peq__rel__agg_003
- *Excluded values:*
  - 777

Usage

```
vars_mh_y_peq__rel__agg

compute_mh_y_peq__rel__agg_nm(
  data,
  name = "mh_y_peq__rel__agg_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_peq__rel__agg is vector of all column names used to compute summary score of mh_y_peq__rel__agg scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_peq__rel__agg_nm(data) |>
  select(
    any_of(c("mh_y_peq__rel__agg_nm", vars_mh_y_peq__rel__agg))
  )

## End(Not run)
```

---

vars_mh_y_peq__rel__vict

Compute "Peer Experiences Questionnaire [Youth] (Relational Victimization): Number missing"

Description

Computes the summary score mh_y_peq__rel__vict_nm Peer Experiences Questionnaire [Youth] (Relational Victimization): Number missing

- *Summarized variables:*
  - mh_y_peq__rel__vict_001
  - mh_y_peq__rel__vict_002
  - mh_y_peq__rel__vict_003
- *Excluded values:*
  - 777

Usage

```
vars_mh_y_peq__rel__vict

compute_mh_y_peq__rel__vict_nm(
  data,
  name = "mh_y_peq__rel__vict_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_peq__rel__vict is vector of all column names used to compute summary score of mh_y_peq__rel__vict scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_peq__rel__vict_nm(data) |>
  select(
    any_of(c("mh_y_peq__rel__vict_nm", vars_mh_y_peq__rel__vict))
  )

## End(Not run)
```

---

vars_mh_y_peq__rep__agg

Compute "Peer Experiences Questionnaire [Youth] (Reputational Aggression): Number missing"

Description

Computes the summary score mh_y_peq__rep__agg_nm Peer Experiences Questionnaire [Youth] (Reputational Aggression): Number missing

- *Summarized variables:*
  - mh_y_peq__rep__agg_001
  - mh_y_peq__rep__agg_002
  - mh_y_peq__rep__agg_003
- *Excluded values:*
  - 777

Usage

```
vars_mh_y_peq__rep__agg

compute_mh_y_peq__rep__agg_nm(
  data,
  name = "mh_y_peq__rep__agg_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_peq__rep__agg is vector of all column names used to compute summary score of mh_y_peq__rep__agg scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_peq__rep__agg_nm(data) |>
  select(
    any_of(c("mh_y_peq__rep__agg_nm", vars_mh_y_peq__rep__agg))
  )

## End(Not run)
```

vars_mh_y_peq__rep__vict

Compute "Peer Experiences Questionnaire [Youth] (Reputational Victimization): Number missing"

Description

Computes the summary score mh_y_peq__rep__vict_nm Peer Experiences Questionnaire [Youth] (Reputational Victimization): Number missing

- *Summarized variables:*
  - mh_y_peq__rep__vict_001
  - mh_y_peq__rep__vict_002
  - mh_y_peq__rep__vict_003
- *Excluded values:*
  - 777

Usage

```
vars_mh_y_peq__rep__vict

compute_mh_y_peq__rep__vict_nm(
  data,
  name = "mh_y_peq__rep__vict_nm",
  exclude = c("777"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_peq__rep__vict is vector of all column names used to compute summary score of mh_y_peq__rep__vict scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_peq__rep__vict_nm(data) |>
  select(
    any_of(c("mh_y_peq__rep__vict_nm", vars_mh_y_peq__rep__vict))
  )

## End(Not run)
```

`vars_mh_y_ple` *Compute "Life Events [Youth] (Events): Count"*

Description

Computes the summary score `mh_y_ple_count` Life Events [Youth] (Events): Count

- *Summarized variables:*
  - `mh_y_ple_001`
  - `mh_y_ple_002`
  - `mh_y_ple_003`
  - `mh_y_ple_004`
  - `mh_y_ple_005`
  - `mh_y_ple_006`
  - `mh_y_ple_007`
  - `mh_y_ple_008`
  - `mh_y_ple_009`
  - `mh_y_ple_010`
  - `mh_y_ple_011`
  - `mh_y_ple_012`
  - `mh_y_ple_013`
  - `mh_y_ple_014`
  - `mh_y_ple_015`
  - `mh_y_ple_016`
  - `mh_y_ple_017`
  - `mh_y_ple_018`
  - `mh_y_ple_019`
  - `mh_y_ple_020`
  - `mh_y_ple_021`
  - `mh_y_ple_022`
  - `mh_y_ple_023`
  - `mh_y_ple_024`
  - `mh_y_ple_025`
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
vars_mh_y_ple

compute_mh_y_ple_count(
  data,
  name = "mh_y_ple_count",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Format

vars_mh_y_ple is a character vector of all column names used to compute summary score of mh_y_ple.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_y_ple__exp *Compute "Life Events [Youth] (Severity of Good Events): Sum [Validation: No more than 5 events missing and no experience/severity items missing or declined]"*

Description

Computes the summary score mh_y_ple__severity__good_sum Life Events [Youth] (Severity of Good Events): Sum [Validation: No more than 5 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004

- mh_y_ple__exp_005
- mh_y_ple__exp_006
- mh_y_ple__exp_007
- mh_y_ple__exp_008
- mh_y_ple__exp_009
- mh_y_ple__exp_010
- mh_y_ple__exp_011
- mh_y_ple__exp_012
- mh_y_ple__exp_013
- mh_y_ple__exp_014
- mh_y_ple__exp_015
- mh_y_ple__exp_016
- mh_y_ple__exp_017
- mh_y_ple__exp_018
- mh_y_ple__exp_019
- mh_y_ple__exp_020
- mh_y_ple__exp_021
- mh_y_ple__exp_022
- mh_y_ple__exp_023
- mh_y_ple__exp_024
- mh_y_ple__exp_025
- mh_y_ple__severity_001
- mh_y_ple__severity_002
- mh_y_ple__severity_003
- mh_y_ple__severity_004
- mh_y_ple__severity_005
- mh_y_ple__severity_006
- mh_y_ple__severity_007
- mh_y_ple__severity_008
- mh_y_ple__severity_009
- mh_y_ple__severity_010
- mh_y_ple__severity_011
- mh_y_ple__severity_012
- mh_y_ple__severity_013
- mh_y_ple__severity_014
- mh_y_ple__severity_015
- mh_y_ple__severity_016
- mh_y_ple__severity_017
- mh_y_ple__severity_018
- mh_y_ple__severity_019
- mh_y_ple__severity_020
- mh_y_ple__severity_021

  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
vars_mh_y_ple__exp

compute_mh_y_ple__severity__good_sum(
  data,
  name = "mh_y_ple__severity__good_sum",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Format

vars_mh_y_ple__exp is a character vector of all column names used to compute summary score of mh_y_ple__exp.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_mh_y_ple__exp__v01

Compute "Life Events [Youth] (Severity of Good Events): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity__good_sum__v01 Life Events [Youth] (Severity of Good Events): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016
  - mh_y_ple__exp_017
  - mh_y_ple__exp_018
  - mh_y_ple__exp_019
  - mh_y_ple__exp_020
  - mh_y_ple__exp_021
  - mh_y_ple__exp_022
  - mh_y_ple__exp_023
  - mh_y_ple__exp_024
  - mh_y_ple__exp_025
  - mh_y_ple__exp_026
  - mh_y_ple__exp_027
  - mh_y_ple__exp_028
  - mh_y_ple__exp_029

  - mh_y_ple__exp_030
  - mh_y_ple__exp_031
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
vars_mh_y_ple__exp__v01

compute_mh_y_ple__severity__good_sum__v01(
  data,
  name = "mh_y_ple__severity__good_sum__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_y_ple__exp__v01 is a character vector of all column names used to compute summary score of mh_y_ple__exp.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_y_ple__exp__v02

Compute "Life Events [Youth] (Severity of Good Events): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity__good_sum__v02 Life Events [Youth] (Severity of Good Events): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__exp_001

- mh_y_ple__exp_002
- mh_y_ple__exp_003
- mh_y_ple__exp_004
- mh_y_ple__exp_005
- mh_y_ple__exp_006
- mh_y_ple__exp_007
- mh_y_ple__exp_008
- mh_y_ple__exp_009
- mh_y_ple__exp_010
- mh_y_ple__exp_011
- mh_y_ple__exp_012
- mh_y_ple__exp_013
- mh_y_ple__exp_014
- mh_y_ple__exp_015
- mh_y_ple__exp_016
- mh_y_ple__exp_017
- mh_y_ple__exp_018
- mh_y_ple__exp_019
- mh_y_ple__exp_020
- mh_y_ple__exp_021
- mh_y_ple__exp_022
- mh_y_ple__exp_023
- mh_y_ple__exp_024
- mh_y_ple__exp_025
- mh_y_ple__exp_026
- mh_y_ple__exp_027
- mh_y_ple__exp_028
- mh_y_ple__exp_029
- mh_y_ple__exp_030
- mh_y_ple__exp_031
- mh_y_ple__exp_032
- mh_y_ple__severity_001
- mh_y_ple__severity_002
- mh_y_ple__severity_003
- mh_y_ple__severity_004
- mh_y_ple__severity_005
- mh_y_ple__severity_006
- mh_y_ple__severity_007
- mh_y_ple__severity_008
- mh_y_ple__severity_009
- mh_y_ple__severity_010
- mh_y_ple__severity_011

  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
vars_mh_y_ple__exp__v02

compute_mh_y_ple__severity__good_sum__v02(
  data,
  name = "mh_y_ple__severity__good_sum__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).

events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_y_ple__exp__v02 is a character vector of all column names used to compute summary score of mh_y_ple__exp.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_y_ple__exp__v03

Compute "Life Events [Youth] (Severity of Good Events): Sum - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity__good_sum__v03 Life Events [Youth] (Severity of Good Events): Sum - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no experience/severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__exp_001
  - mh_y_ple__exp_002
  - mh_y_ple__exp_003
  - mh_y_ple__exp_004
  - mh_y_ple__exp_005
  - mh_y_ple__exp_006
  - mh_y_ple__exp_007
  - mh_y_ple__exp_008
  - mh_y_ple__exp_009
  - mh_y_ple__exp_010
  - mh_y_ple__exp_011
  - mh_y_ple__exp_012
  - mh_y_ple__exp_013
  - mh_y_ple__exp_014
  - mh_y_ple__exp_015
  - mh_y_ple__exp_016

- mh_y_ple__exp_017
- mh_y_ple__exp_018
- mh_y_ple__exp_019
- mh_y_ple__exp_020
- mh_y_ple__exp_021
- mh_y_ple__exp_022
- mh_y_ple__exp_023
- mh_y_ple__exp_024
- mh_y_ple__exp_025
- mh_y_ple__exp_026
- mh_y_ple__exp_027
- mh_y_ple__exp_028
- mh_y_ple__exp_029
- mh_y_ple__exp_030
- mh_y_ple__exp_031
- mh_y_ple__exp_032
- mh_y_ple__exp_033
- mh_y_ple__severity_001
- mh_y_ple__severity_002
- mh_y_ple__severity_003
- mh_y_ple__severity_004
- mh_y_ple__severity_005
- mh_y_ple__severity_006
- mh_y_ple__severity_007
- mh_y_ple__severity_008
- mh_y_ple__severity_009
- mh_y_ple__severity_010
- mh_y_ple__severity_011
- mh_y_ple__severity_012
- mh_y_ple__severity_013
- mh_y_ple__severity_014
- mh_y_ple__severity_015
- mh_y_ple__severity_016
- mh_y_ple__severity_017
- mh_y_ple__severity_018
- mh_y_ple__severity_019
- mh_y_ple__severity_020
- mh_y_ple__severity_021
- mh_y_ple__severity_022
- mh_y_ple__severity_023
- mh_y_ple__severity_024
- mh_y_ple__severity_025

  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_033
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
vars_mh_y_ple__exp__v03

compute_mh_y_ple__severity__good_sum__v03(
  data,
  name = "mh_y_ple__severity__good_sum__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_y_ple__exp__v03 is a character vector of all column names used to compute summary score of mh_y_ple__exp.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_mh_y_ple__severity

Compute "Life Events [Youth] (Severity): Sum [Validation: No more than 5 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity_sum Life Events [Youth] (Severity): Sum [Validation: No more than 5 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 5 of 25 items missing

Usage

```
vars_mh_y_ple__severity

compute_mh_y_ple__severity_sum(
  data,
  name = "mh_y_ple__severity_sum",
  combine = TRUE,
  max_na = 5
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 5).

Format

vars_mh_y_ple__severity is a character vector of all column names used to compute summary score of mh_y_ple__severity.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_y_ple__severity__v01

Compute "Life Events [Youth] (Severity): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity_sum__v01 Life Events [Youth] (Severity): Sum - Version 1 (Year 3) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003

  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 31 items missing

Usage

```
vars_mh_y_ple__severity__v01

compute_mh_y_ple__severity_sum__v01(
  data,
  name = "mh_y_ple__severity_sum__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_y_ple__severity__v01 is a character vector of all column names used to compute summary score of mh_y_ple__severity.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_y_ple__severity__v02

Compute "Life Events [Youth] (Severity): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity_sum__v02 Life Events [Youth] (Severity): Sum - Version 2 (Year 4 and Year 5) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012

  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016
  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 33 items missing

Usage

```
vars_mh_y_ple__severity__v02

compute_mh_y_ple__severity_sum__v02(
  data,
  name = "mh_y_ple__severity_sum__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).

events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_y_ple__severity__v02 is a character vector of all column names used to compute summary score of mh_y_ple__severity.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_mh_y_ple__severity__v03

Compute "Life Events [Youth] (Severity): Sum - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no severity items missing or declined]"

Description

Computes the summary score mh_y_ple__severity_sum__v03 Life Events [Youth] (Severity): Sum - Version 3 (Starting at Year 6) [Validation: No more than 6 events missing and no severity items missing or declined]

- *Summarized variables:*
  - mh_y_ple__severity_001
  - mh_y_ple__severity_002
  - mh_y_ple__severity_003
  - mh_y_ple__severity_004
  - mh_y_ple__severity_005
  - mh_y_ple__severity_006
  - mh_y_ple__severity_007
  - mh_y_ple__severity_008
  - mh_y_ple__severity_009
  - mh_y_ple__severity_010
  - mh_y_ple__severity_011
  - mh_y_ple__severity_012
  - mh_y_ple__severity_013
  - mh_y_ple__severity_014
  - mh_y_ple__severity_015
  - mh_y_ple__severity_016

  - mh_y_ple__severity_017
  - mh_y_ple__severity_018
  - mh_y_ple__severity_019
  - mh_y_ple__severity_020
  - mh_y_ple__severity_021
  - mh_y_ple__severity_022
  - mh_y_ple__severity_023
  - mh_y_ple__severity_024
  - mh_y_ple__severity_025
  - mh_y_ple__severity_026
  - mh_y_ple__severity_027
  - mh_y_ple__severity_028
  - mh_y_ple__severity_029
  - mh_y_ple__severity_030
  - mh_y_ple__severity_031
  - mh_y_ple__severity_032
  - mh_y_ple__severity_033
  - mh_y_ple__severity_034
- *Excluded values:*
  - 444
  - 777
  - 999
- *Validation criterion:* maximally 6 of 34 items missing

Usage

```
vars_mh_y_ple__severity__v03

compute_mh_y_ple__severity_sum__v03(
  data,
  name = "mh_y_ple__severity_sum__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE,
  max_na = 6
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 6).

Format

vars_mh_y_ple__severity__v03 is a character vector of all column names used to compute summary score of `mh_y_ple__severity`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_y_ple__v01` *Compute "Life Events [Youth] (Events): Count - Version 1 (Year 3)"*

Description

Computes the summary score `mh_y_ple_count__v01` Life Events [Youth] (Events): Count - Version 1 (Year 3)

- *Summarized variables:*
  - `mh_y_ple_001`
  - `mh_y_ple_002`
  - `mh_y_ple_003`
  - `mh_y_ple_004`
  - `mh_y_ple_005`
  - `mh_y_ple_006`
  - `mh_y_ple_007`
  - `mh_y_ple_008`
  - `mh_y_ple_009`
  - `mh_y_ple_010`
  - `mh_y_ple_011`
  - `mh_y_ple_012`
  - `mh_y_ple_013`
  - `mh_y_ple_014`
  - `mh_y_ple_015`
  - `mh_y_ple_016`
  - `mh_y_ple_017`
  - `mh_y_ple_018`
  - `mh_y_ple_019`
  - `mh_y_ple_020`
  - `mh_y_ple_021`
  - `mh_y_ple_022`
  - `mh_y_ple_023`
  - `mh_y_ple_024`
  - `mh_y_ple_025`
  - `mh_y_ple_026`

  - mh_y_ple_027
  - mh_y_ple_028
  - mh_y_ple_029
  - mh_y_ple_030
  - mh_y_ple_031
- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
vars_mh_y_ple__v01

compute_mh_y_ple_count__v01(
  data,
  name = "mh_y_ple_count__v01",
  events = "ses-03A",
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Format

vars_mh_y_ple__v01 is a character vector of all column names used to compute summary score of mh_y_ple.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_mh_y_ple__v02` *Compute "Life Events [Youth] (Events): Count - Version 2 (Year 4 and Year 5)"*

Description

Computes the summary score `mh_y_ple_count__v02` Life Events [Youth] (Events): Count - Version 2 (Year 4 and Year 5)

- *Summarized variables:*
  - `mh_y_ple_001`
  - `mh_y_ple_002`
  - `mh_y_ple_003`
  - `mh_y_ple_004`
  - `mh_y_ple_005`
  - `mh_y_ple_006`
  - `mh_y_ple_007`
  - `mh_y_ple_008`
  - `mh_y_ple_009`
  - `mh_y_ple_010`
  - `mh_y_ple_011`
  - `mh_y_ple_012`
  - `mh_y_ple_013`
  - `mh_y_ple_014`
  - `mh_y_ple_015`
  - `mh_y_ple_016`
  - `mh_y_ple_017`
  - `mh_y_ple_018`
  - `mh_y_ple_019`
  - `mh_y_ple_020`
  - `mh_y_ple_021`
  - `mh_y_ple_022`
  - `mh_y_ple_023`
  - `mh_y_ple_024`
  - `mh_y_ple_025`
  - `mh_y_ple_026`
  - `mh_y_ple_027`
  - `mh_y_ple_028`
  - `mh_y_ple_029`
  - `mh_y_ple_030`
  - `mh_y_ple_031`
  - `mh_y_ple_032`

    - mh_y_ple_034

- *Excluded values:*
    - 444
    - 777
    - 999

Usage

```
vars_mh_y_ple__v02

compute_mh_y_ple_count__v02(
  data,
  name = "mh_y_ple_count__v02",
  events = c("ses-04A", "ses-05A"),
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Format

vars_mh_y_ple__v02 is a character vector of all column names used to compute summary score of mh_y_ple.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_mh_y_ple__v03 *Compute "Life Events [Youth] (Events): Count - Version 3 (Starting at Year 6)"*

Description

Computes the summary score mh_y_ple_count__v03 Life Events [Youth] (Events): Count - Version 3 (Starting at Year 6)

- *Summarized variables:*
  - mh_y_ple_001
  - mh_y_ple_002
  - mh_y_ple_003
  - mh_y_ple_004
  - mh_y_ple_005
  - mh_y_ple_006
  - mh_y_ple_007
  - mh_y_ple_008
  - mh_y_ple_009
  - mh_y_ple_010
  - mh_y_ple_011
  - mh_y_ple_012
  - mh_y_ple_013
  - mh_y_ple_014
  - mh_y_ple_015
  - mh_y_ple_016
  - mh_y_ple_017
  - mh_y_ple_018
  - mh_y_ple_019
  - mh_y_ple_020
  - mh_y_ple_021
  - mh_y_ple_022
  - mh_y_ple_023
  - mh_y_ple_024
  - mh_y_ple_025
  - mh_y_ple_026
  - mh_y_ple_027
  - mh_y_ple_028
  - mh_y_ple_029
  - mh_y_ple_030
  - mh_y_ple_031
  - mh_y_ple_032

  - mh_y_ple_033
  - mh_y_ple_034

- *Excluded values:*
  - 444
  - 777
  - 999

Usage

```
vars_mh_y_ple__v03

compute_mh_y_ple_count__v03(
  data,
  name = "mh_y_ple_count__v03",
  events = c("ses-06A", "ses-07A"),
  combine = TRUE,
  max_na = NULL
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
events	character vector. Event (session ID) to be used.
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit (Default: NULL).

Format

vars_mh_y_ple__v03 is a character vector of all column names used to compute summary score of mh_y_ple.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_mh_y_pps__bother *Compute "Prodromal Psychosis Scale [Youth] (Bother responses): Number missing"*

Description

Computes the summary score mh_y_pps__bother_nm Prodromal Psychosis Scale [Youth] (Bother responses): Number missing

- *Summarized variables:*
  - mh_y_pps__bother_001
  - mh_y_pps__bother_002
  - mh_y_pps__bother_003
  - mh_y_pps__bother_004
  - mh_y_pps__bother_005
  - mh_y_pps__bother_006
  - mh_y_pps__bother_007
  - mh_y_pps__bother_008
  - mh_y_pps__bother_009
  - mh_y_pps__bother_010
  - mh_y_pps__bother_011
  - mh_y_pps__bother_012
  - mh_y_pps__bother_013
  - mh_y_pps__bother_014
  - mh_y_pps__bother_015
  - mh_y_pps__bother_016
  - mh_y_pps__bother_017
  - mh_y_pps__bother_018
  - mh_y_pps__bother_019
  - mh_y_pps__bother_020
  - mh_y_pps__bother_021

Usage

```
vars_mh_y_pps__bother

compute_mh_y_pps__bother_nm(data, name = "mh_y_pps__bother_nm", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_mh_y_pps__bother is a character vector of all column names used to compute summary of `mh_y_pps__bother` scores.

Details

The number of missing values in the `mh_y_pps__bother` score is calculated by subtracting the number of valid pairs from the total PPS count for each subject (mh_y_pps_count - bother_pair_good_sum).

A good pair is defined as a pair where the `mh_y_pps_count` is 1 and the `mh_y_pps__bother` is not missing.

See Also

`compute_mh_y_pps_count()`

Examples

```
## Not run:
compute_mh_y_pps__bother_nm(data) |>
  select(
    any_of(c("mh_y_pps__bother_nm", vars_mh_y_pps__bother))
  )

## End(Not run)
```

---

vars_mh_y_pps__severity

Compute "Prodromal Psychosis Scale [Youth] (Severity Score): Number missing"

Description

Computes the summary score `mh_y_pps__severity_nm` Prodromal Psychosis Scale [Youth] (Severity Score): Number missing

- *Summarized variables:*
  - `mh_y_pps__severity_001`
  - `mh_y_pps__severity_002`
  - `mh_y_pps__severity_003`
  - `mh_y_pps__severity_004`
  - `mh_y_pps__severity_005`
  - `mh_y_pps__severity_006`
  - `mh_y_pps__severity_007`
  - `mh_y_pps__severity_008`
  - `mh_y_pps__severity_009`
  - `mh_y_pps__severity_010`

  - mh_y_pps__severity_011
  - mh_y_pps__severity_012
  - mh_y_pps__severity_013
  - mh_y_pps__severity_014
  - mh_y_pps__severity_015
  - mh_y_pps__severity_016
  - mh_y_pps__severity_017
  - mh_y_pps__severity_018
  - mh_y_pps__severity_019
  - mh_y_pps__severity_020
  - mh_y_pps__severity_021
- *Excluded values:* none

Usage

```
vars_mh_y_pps__severity

compute_mh_y_pps__severity_nm(
  data,
  name = "mh_y_pps__severity_nm",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_mh_y_pps__severity is a character vector of all column names used to compute summary of mh_y_pps__severity scores.

Details

The number of missing values in the mh_y_pps__severity score is calculated by subtracting the number of valid pairs from the total **bother** count for each subject (mh_y_pps__bother_yes_count - severity_pair_good_sum).

A good pair is defined as a pair where the mh_y_pps__bother__yes_count is 1 and the mh_y_pps__severity is not missing.

See Also

compute_mh_y_pps__bother__yes_count()

Examples

```
## Not run:
compute_mh_y_pps__severity_nm(data) |>
  select(
    any_of(c("mh_y_pps__severity_nm", vars_mh_y_pps__severity))
  )

## End(Not run)
```

`vars_mh_y_pps_count` *Compute "Prodromal Psychosis Scale [Youth] (number of "Yes" responses): Count "*

Description

Computes the summary score `mh_y_pps_count` Prodromal Psychosis Scale [Youth] (number of

- *Summarized variables:*
  - `mh_y_pps_001`
  - `mh_y_pps_002`
  - `mh_y_pps_003`
  - `mh_y_pps_004`
  - `mh_y_pps_005`
  - `mh_y_pps_006`
  - `mh_y_pps_007`
  - `mh_y_pps_008`
  - `mh_y_pps_009`
  - `mh_y_pps_010`
  - `mh_y_pps_011`
  - `mh_y_pps_012`
  - `mh_y_pps_013`
  - `mh_y_pps_014`
  - `mh_y_pps_015`
  - `mh_y_pps_016`
  - `mh_y_pps_017`
  - `mh_y_pps_018`
  - `mh_y_pps_019`
  - `mh_y_pps_020`
  - `mh_y_pps_021`
- *Excluded values:* none
- *Validation criterion:* maximally 4 of 21 items missing

Usage

```
vars_mh_y_pps_count

compute_mh_y_pps_count(
  data,
  name = "mh_y_pps_count",
  max_na = 4,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_mh_y_pps_count is a character vector of all column names used to compute summary score of mh_y_pps_count and mh_y_pps_nm

Details

The mh_y_pps_count is calculated by summing the number of 1s in each question. If the number of missing values is greater than max_na, the summary score is set to NA. By default, max_na is set to 4 (20%).

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_mh_y_pps_count(data) |>
  select(
    any_of(c("mh_y_pps_count", vars_mh_y_pps_count))
  )

## End(Not run)
```

vars_mh_y_sup *Compute "7-Up Mania Inventory [Youth]: Number missing"*

Description

Computes the summary score mh_y_sup_nm 7-Up Mania Inventory [Youth]: Number missing

- *Summarized variables:*
  - mh_y_sup_001
  - mh_y_sup_002
  - mh_y_sup_003
  - mh_y_sup_004
  - mh_y_sup_005
  - mh_y_sup_006
  - mh_y_sup_007
- *Excluded values:* none

Usage

```
vars_mh_y_sup

compute_mh_y_sup_nm(data, name = "mh_y_sup_nm", exclude = NULL, combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_sup is vector of all column names used to compute summary score of mh_y_sup scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_sup_nm(data) |>
  select(
    any_of(c("mh_y_sup_nm", vars_mh_y_sup))
  )

## End(Not run)
```

`vars_mh_y_upps__nurg` *Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Negative Urgency): Number missing"*

Description

Computes the summary score `mh_y_upps__nurg_nm` Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Negative Urgency): Number missing

- *Summarized variables:*
  - `mh_y_upps__nurg_001`
  - `mh_y_upps__nurg_002`
  - `mh_y_upps__nurg_003`
  - `mh_y_upps__nurg_004`
- *Excluded values:* none

Usage

```
vars_mh_y_upps__nurg

compute_mh_y_upps__nurg_nm(
  data,
  name = "mh_y_upps__nurg_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_upps__nurg is vector of all column names used to compute summary score of mh_y_upps__nurg scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_upps__nurg_nm(data) |>
  select(
    any_of(c("mh_y_upps__nurg_nm", vars_mh_y_upps__nurg))
  )

## End(Not run)
```

---

vars_mh_y_upps__pers *Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Lack of Perseverance (GSSF)): Number missing"*

Description

Computes the summary score mh_y_upps__pers_nm Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Lack of Perseverance (GSSF)): Number missing

- *Summarized variables:*
  - mh_y_upps__pers_001
  - mh_y_upps__pers_002
  - mh_y_upps__pers_003
  - mh_y_upps__pers_004
- *Excluded values:* none

Usage

```
vars_mh_y_upps__pers

compute_mh_y_upps__pers_nm(
  data,
  name = "mh_y_upps__pers_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_upps__pers is vector of all column names used to compute summary score of mh_y_upps__pers scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_upps__pers_nm(data) |>
  select(
    any_of(c("mh_y_upps__pers_nm", vars_mh_y_upps__pers))
  )

## End(Not run)
```

---

vars_mh_y_upps__plan *Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Lack of Planning): Number missing"*

Description

Computes the summary score mh_y_upps__plan_nm Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Lack of Planning): Number missing

- *Summarized variables:*
  - mh_y_upps__plan_001
  - mh_y_upps__plan_002
  - mh_y_upps__plan_003
  - mh_y_upps__plan_004
- *Excluded values:* none

Usage

```
vars_mh_y_upps__plan

compute_mh_y_upps__plan_nm(
  data,
  name = "mh_y_upps__plan_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_upps__plan is vector of all column names used to compute summary score of mh_y_upps__plan scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_upps__plan_nm(data) |>
  select(
    any_of(c("mh_y_upps__plan_nm", vars_mh_y_upps__plan))
  )

## End(Not run)
```

---

vars_mh_y_upps__purg *Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Positive Urgency): Number missing"*

Description

Computes the summary score mh_y_upps__purg_nm Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Positive Urgency): Number missing

- *Summarized variables:*
  - mh_y_upps__purg_001
  - mh_y_upps__purg_002
  - mh_y_upps__purg_003
  - mh_y_upps__purg_004
- *Excluded values:* none

Usage

```
vars_mh_y_upps__purg

compute_mh_y_upps__purg_nm(
  data,
  name = "mh_y_upps__purg_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_upps__purg is vector of all column names used to compute summary score of mh_y_upps__purg scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_upps__purg_nm(data) |>
  select(
    any_of(c("mh_y_upps__purg_nm", vars_mh_y_upps__purg))
  )
```

```
## End(Not run)
```

`vars_mh_y_upps__sens` *Compute "Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Sensation Seeking): Number missing"*

Description

Computes the summary score `mh_y_upps__sens_nm` Urgency, Premeditation, Perseverance, Sensation Seeking, Positive Urgency, Impulsive Behavior Scale (Short Version) [Youth] (Sensation Seeking): Number missing

- *Summarized variables:*
  - `mh_y_upps__sens_001`
  - `mh_y_upps__sens_002`
  - `mh_y_upps__sens_003`
  - `mh_y_upps__sens_004`
- *Excluded values:* none

Usage

```
vars_mh_y_upps__sens

compute_mh_y_upps__sens_nm(
  data,
  name = "mh_y_upps__sens_nm",
  exclude = NULL,
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

`vars_mh_y_upps__sens` is vector of all column names used to compute summary score of `mh_y_upps__sens` scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_upps__sens_nm(data) |>
  select(
    any_of(c("mh_y_upps__sens_nm", vars_mh_y_upps__sens))
  )

## End(Not run)
```

---

vars_mh_y_ysr *Compute "Youth Self Report [Youth]: Number missing"*

Description

Computes the summary score mh_y_ysr_nm Youth Self Report [Youth]: Number missing

- *Summarized variables:*
  - mh_y_ysr__attn__adhd_001
  - mh_y_ysr__attn__adhd_002
  - mh_y_ysr__attn__adhd_003
  - mh_y_ysr__attn__adhd_004
  - mh_y_ysr__attn__adhd_005
  - mh_y_ysr__othpr__adhd_001
  - mh_y_ysr__aggr__adhd_001
  - mh_y_ysr__soc__anx_001
  - mh_y_ysr__anxdep__anx_001
  - mh_y_ysr__anxdep__anx_002
  - mh_y_ysr__anxdep__anx_003
  - mh_y_ysr__anxdep__anx_004
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__anxdep__anx_005
  - mh_y_ysr__anxdep__anx_006
  - mh_y_ysr__anxdep__anx_007
  - mh_y_ysr__aggr__cond_001
  - mh_y_ysr__aggr__cond_002
  - mh_y_ysr__rule__cond_001
  - mh_y_ysr__rule__cond_002
  - mh_y_ysr__aggr__cond_003
  - mh_y_ysr__rule__cond_003
  - mh_y_ysr__rule__cond_004

- mh_y_ysr__aggr__cond_004
- mh_y_ysr__rule__cond_005
- mh_y_ysr__rule__cond_006
- mh_y_ysr__rule__cond_007
- mh_y_ysr__rule__cond_008
- mh_y_ysr__rule__cond_009
- mh_y_ysr__aggr__cond_005
- mh_y_ysr__rule__cond_010
- mh_y_ysr__wthdep__dep_001
- mh_y_ysr__anxdep__dep_001
- mh_y_ysr__othpr__dep_001
- mh_y_ysr__anxdep__dep_002
- mh_y_ysr__anxdep__dep_003
- mh_y_ysr__som__dep_001
- mh_y_ysr__tho__dep_002
- mh_y_ysr__othpr__dep_002
- mh_y_ysr__tho__dep_003
- mh_y_ysr__wthdep__dep_002
- mh_y_ysr__wthdep__dep_003
- mh_y_ysr__aggr__opp_001
- mh_y_ysr__aggr__opp_002
- mh_y_ysr__aggr__opp_003
- mh_y_ysr__aggr__opp_004
- mh_y_ysr__aggr__opp_005
- mh_y_ysr__som__somat_001
- mh_y_ysr__som__somat_002
- mh_y_ysr__som__somat_003
- mh_y_ysr__som__somat_004
- mh_y_ysr__som__somat_005
- mh_y_ysr__som__somat_006
- mh_y_ysr__som__somat_007
- mh_y_ysr__aggr_001
- mh_y_ysr__aggr_002
- mh_y_ysr__aggr_003
- mh_y_ysr__aggr_004
- mh_y_ysr__aggr_005
- mh_y_ysr__aggr_006
- mh_y_ysr__anxdep_001
- mh_y_ysr__anxdep_002
- mh_y_ysr__attn_001
- mh_y_ysr__attn_002
- mh_y_ysr__attn_003

  - mh_y_ysr__attn_004
  - mh_y_ysr__rule_001
  - mh_y_ysr__rule_002
  - mh_y_ysr__rule_003
  - mh_y_ysr__rule_004
  - mh_y_ysr__rule_005
  - mh_y_ysr__wthdep_001
  - mh_y_ysr__wthdep_002
  - mh_y_ysr__wthdep_003
  - mh_y_ysr__wthdep_004
  - mh_y_ysr__wthdep_005
  - mh_y_ysr__som_001
  - mh_y_ysr__othpr_001
  - mh_y_ysr__othpr_002
  - mh_y_ysr__othpr_003
  - mh_y_ysr__othpr_004
  - mh_y_ysr__othpr_005
  - mh_y_ysr__othpr_006
  - mh_y_ysr__soc_001
  - mh_y_ysr__soc_002
  - mh_y_ysr__soc_003
  - mh_y_ysr__soc_004
  - mh_y_ysr__soc_005
  - mh_y_ysr__soc_006
  - mh_y_ysr__soc_007
  - mh_y_ysr__soc_008
  - mh_y_ysr__soc_009
  - mh_y_ysr__soc_010
  - mh_y_ysr__tho_001
  - mh_y_ysr__tho_002
  - mh_y_ysr__tho_003
  - mh_y_ysr__tho_004
  - mh_y_ysr__tho_005
  - mh_y_ysr__tho_006
  - mh_y_ysr__tho_007
  - mh_y_ysr__tho_008
  - mh_y_ysr__tho_009
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr

compute_mh_y_ysr_nm(
  data,
  name = "mh_y_ysr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr is vector of all column names used to compute summary score of mh_y_ysr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr_nm(data) |>
  select(
    any_of(c("mh_y_ysr_nm", vars_mh_y_ysr))
  )

## End(Not run)
```

---

vars_mh_y_ysr__dsm__adhd

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - ADHD): Number missing"

Description

Computes the summary score mh_y_ysr__dsm__adhd_nm Youth Self Report [Youth] (DSM-5 Oriented Scale - ADHD): Number missing

- *Summarized variables:*
  - mh_y_ysr__attn__adhd_001
  - mh_y_ysr__attn__adhd_002
  - mh_y_ysr__attn__adhd_003
  - mh_y_ysr__attn__adhd_004
  - mh_y_ysr__attn__adhd_005
  - mh_y_ysr__othpr__adhd_001
  - mh_y_ysr__aggr__adhd_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__dsm__adhd

compute_mh_y_ysr__dsm__adhd_nm(
  data,
  name = "mh_y_ysr__dsm__adhd_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__dsm__adhd is vector of all column names used to compute summary score of mh_y_ysr__dsm__adhd scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__dsm__adhd_nm(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__adhd_nm", vars_mh_y_ysr__dsm__adhd))
  )

## End(Not run)
```

---

vars_mh_y_ysr__dsm__anx

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Anxiety problems): Number missing"

Description

Computes the summary score `mh_y_ysr__dsm__anx_nm` Youth Self Report [Youth] (DSM-5 Oriented Scale - Anxiety problems): Number missing

- *Summarized variables:*
  - `mh_y_ysr__soc__anx_001`
  - `mh_y_ysr__anxdep__anx_001`
  - `mh_y_ysr__anxdep__anx_002`
  - `mh_y_ysr__anxdep__anx_003`
  - `mh_y_ysr__anxdep__anx_004`
  - `mh_y_ysr__som__anx_001`
  - `mh_y_ysr__anxdep__anx_005`
  - `mh_y_ysr__anxdep__anx_006`
  - `mh_y_ysr__anxdep__anx_007`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__dsm__anx

compute_mh_y_ysr__dsm__anx_nm(
  data,
  name = "mh_y_ysr__dsm__anx_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__dsm__anx is vector of all column names used to compute summary score of mh_y_ysr__dsm__anx scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__dsm__anx_nm(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__anx_nm", vars_mh_y_ysr__dsm__anx))
  )

## End(Not run)
```

---

vars_mh_y_ysr__dsm__cond

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Conduct problems): Number missing"

Description

Computes the summary score mh_y_ysr__dsm__cond_nm Youth Self Report [Youth] (DSM-5 Oriented Scale - Conduct problems): Number missing

- *Summarized variables:*
  - mh_y_ysr__aggr__cond_001
  - mh_y_ysr__aggr__cond_002
  - mh_y_ysr__rule__cond_001
  - mh_y_ysr__rule__cond_002
  - mh_y_ysr__aggr__cond_003
  - mh_y_ysr__rule__cond_003
  - mh_y_ysr__rule__cond_004

  - mh_y_ysr__aggr__cond_004
  - mh_y_ysr__rule__cond_005
  - mh_y_ysr__rule__cond_006
  - mh_y_ysr__rule__cond_007
  - mh_y_ysr__rule__cond_008
  - mh_y_ysr__rule__cond_009
  - mh_y_ysr__aggr__cond_005
  - mh_y_ysr__rule__cond_010
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__dsm__cond

compute_mh_y_ysr__dsm__cond_nm(
  data,
  name = "mh_y_ysr__dsm__cond_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__dsm__cond is vector of all column names used to compute summary score of mh_y_ysr__dsm__cond scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__dsm__cond_nm(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__cond_nm", vars_mh_y_ysr__dsm__cond))
```

```
  )

## End(Not run)
```

---

vars_mh_y_ysr__dsm__dep

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Depressive problems): Number missing"

Description

Computes the summary score mh_y_ysr__dsm__dep_nm Youth Self Report [Youth] (DSM-5 Oriented Scale - Depressive problems): Number missing

- *Summarized variables:*
  - mh_y_ysr__wthdep__dep_001
  - mh_y_ysr__anxdep__dep_001
  - mh_y_ysr__othpr__dep_001
  - mh_y_ysr__anxdep__dep_002
  - mh_y_ysr__anxdep__dep_003
  - mh_y_ysr__som__dep_001
  - mh_y_ysr__tho__dep_002
  - mh_y_ysr__othpr__dep_002
  - mh_y_ysr__tho__dep_003
  - mh_y_ysr__wthdep__dep_002
  - mh_y_ysr__wthdep__dep_003
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__dsm__dep

compute_mh_y_ysr__dsm__dep_nm(
  data,
  name = "mh_y_ysr__dsm__dep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__dsm__dep is vector of all column names used to compute summary score of mh_y_ysr__dsm__dep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__dsm__dep_nm(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__dep_nm", vars_mh_y_ysr__dsm__dep))
  )

## End(Not run)
```

---

vars_mh_y_ysr__dsm__opp

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Oppositional Defiant problems): Number missing"

Description

Computes the summary score mh_y_ysr__dsm__opp_nm Youth Self Report [Youth] (DSM-5 Oriented Scale - Oppositional Defiant problems): Number missing

- *Summarized variables:*
  - mh_y_ysr__aggr__opp_001
  - mh_y_ysr__aggr__opp_002
  - mh_y_ysr__aggr__opp_003
  - mh_y_ysr__aggr__opp_004
  - mh_y_ysr__aggr__opp_005
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__dsm__opp

compute_mh_y_ysr__dsm__opp_nm(
  data,
  name = "mh_y_ysr__dsm__opp_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__dsm__opp is vector of all column names used to compute summary score of mh_y_ysr__dsm__opp scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__dsm__opp_nm(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__opp_nm", vars_mh_y_ysr__dsm__opp))
  )

## End(Not run)
```

---

vars_mh_y_ysr__dsm__somat

Compute "Youth Self Report [Youth] (DSM-5 Oriented Scale - Somatic complaints): Number missing"

Description

Computes the summary score mh_y_ysr__dsm__somat_nm Youth Self Report [Youth] (DSM-5 Oriented Scale - Somatic complaints): Number missing

- *Summarized variables:*
  - mh_y_ysr__som__somat_001
  - mh_y_ysr__som__somat_002
  - mh_y_ysr__som__somat_003
  - mh_y_ysr__som__somat_004
  - mh_y_ysr__som__somat_005
  - mh_y_ysr__som__somat_006
  - mh_y_ysr__som__somat_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__dsm__somat

compute_mh_y_ysr__dsm__somat_nm(
  data,
  name = "mh_y_ysr__dsm__somat_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__dsm__somat is vector of all column names used to compute summary score of mh_y_ysr__dsm__somat scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__dsm__somat_nm(data) |>
  select(
    any_of(c("mh_y_ysr__dsm__somat_nm", vars_mh_y_ysr__dsm__somat))
  )

## End(Not run)
```

`vars_mh_y_ysr__pos` *Compute "Youth Self Report [Youth] (Positive): Number missing"*

Description

Computes the summary score `mh_y_ysr__pos_nm` Youth Self Report [Youth] (Positive): Number missing

- *Summarized variables:*
  - `mh_y_ysr__pos_001`
  - `mh_y_ysr__pos_002`
  - `mh_y_ysr__pos_003`
  - `mh_y_ysr__pos_004`
  - `mh_y_ysr__pos_005`
  - `mh_y_ysr__pos_006`
  - `mh_y_ysr__pos_007`
  - `mh_y_ysr__pos_008`
  - `mh_y_ysr__pos_009`
  - `mh_y_ysr__pos_010`
  - `mh_y_ysr__pos_011`
  - `mh_y_ysr__pos_012`
  - `mh_y_ysr__pos_013`
  - `mh_y_ysr__pos_014`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__pos

compute_mh_y_ysr__pos_nm(
  data,
  name = "mh_y_ysr__pos_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__pos is vector of all column names used to compute summary score of mh_y_ysr__pos scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__pos_nm(data) |>
  select(
    any_of(c("mh_y_ysr__pos_nm", vars_mh_y_ysr__pos))
  )

## End(Not run)
```

---

vars_mh_y_ysr__synd__aggr

Compute "Youth Self Report [Youth] (Syndrome Scale - Aggressive behavior): Number missing"

Description

Computes the summary score mh_y_ysr__synd__aggr_nm Youth Self Report [Youth] (Syndrome Scale - Aggressive behavior): Number missing

- *Summarized variables:*
  - mh_y_ysr__aggr__opp_001
  - mh_y_ysr__aggr__cond_001
  - mh_y_ysr__aggr_001
  - mh_y_ysr__aggr_002
  - mh_y_ysr__aggr__cond_002
  - mh_y_ysr__aggr__opp_002
  - mh_y_ysr__aggr__opp_003

  - mh_y_ysr__aggr__cond_003
  - mh_y_ysr__aggr__cond_004
  - mh_y_ysr__aggr_003
  - mh_y_ysr__aggr__opp_004
  - mh_y_ysr__aggr_004
  - mh_y_ysr__aggr_005
  - mh_y_ysr__aggr_006
  - mh_y_ysr__aggr__opp_005
  - mh_y_ysr__aggr__cond_005
  - mh_y_ysr__aggr__adhd_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__aggr

compute_mh_y_ysr__synd__aggr_nm(
  data,
  name = "mh_y_ysr__synd__aggr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__aggr is vector of all column names used to compute summary score of mh_y_ysr__synd__aggr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__aggr_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__aggr_nm", vars_mh_y_ysr__synd__aggr))
  )

## End(Not run)
```

`vars_mh_y_ysr__synd__anxdep`

Compute "Youth Self Report [Youth] (Syndrome Scale - Anxious/Depressed): Number missing"

Description

Computes the summary score `mh_y_ysr__synd__anxdep_nm` Youth Self Report [Youth] (Syndrome Scale - Anxious/Depressed): Number missing

- *Summarized variables:*
  - `mh_y_ysr__anxdep__dep_001`
  - `mh_y_ysr__anxdep__anx_001`
  - `mh_y_ysr__anxdep__anx_002`
  - `mh_y_ysr__anxdep__anx_003`
  - `mh_y_ysr__anxdep_001`
  - `mh_y_ysr__anxdep_002`
  - `mh_y_ysr__anxdep__dep_002`
  - `mh_y_ysr__anxdep__anx_004`
  - `mh_y_ysr__anxdep__anx_005`
  - `mh_y_ysr__anxdep__dep_003`
  - `mh_y_ysr__anxdep__anx_006`
  - `mh_y_ysr__anxdep__anx_007`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__anxdep

compute_mh_y_ysr__synd__anxdep_nm(
  data,
  name = "mh_y_ysr__synd__anxdep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__anxdep is vector of all column names used to compute summary score of mh_y_ysr__synd__anxdep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__anxdep_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__anxdep_nm", vars_mh_y_ysr__synd__anxdep))
  )

## End(Not run)
```

---

vars_mh_y_ysr__synd__attn

Compute "Youth Self Report [Youth] (Syndrome Scale - Attention problems): Number missing"

Description

Computes the summary score mh_y_ysr__synd__attn_nm Youth Self Report [Youth] (Syndrome Scale - Attention problems): Number missing

- *Summarized variables:*
  - mh_y_ysr__attn_001
  - mh_y_ysr__attn__adhd_001
  - mh_y_ysr__attn__adhd_002
  - mh_y_ysr__attn__adhd_003
  - mh_y_ysr__attn_002
  - mh_y_ysr__attn_003
  - mh_y_ysr__attn__adhd_004

  - mh_y_ysr__attn_004
  - mh_y_ysr__attn__adhd_005
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__attn

compute_mh_y_ysr__synd__attn_nm(
  data,
  name = "mh_y_ysr__synd__attn_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__attn is vector of all column names used to compute summary score of mh_y_ysr__synd__attn scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__attn_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__attn_nm", vars_mh_y_ysr__synd__attn))
  )

## End(Not run)
```

vars_mh_y_ysr__synd__ext

Compute "Youth Self Report [Youth] (Syndrome Scale - External): Number missing"

Description

Computes the summary score mh_y_ysr__synd__ext_nm Youth Self Report [Youth] (Syndrome Scale - External): Number missing

- *Summarized variables:*
  - mh_y_ysr__rule_001
  - mh_y_ysr__rule__cond_001
  - mh_y_ysr__rule__cond_002
  - mh_y_ysr__rule__cond_003
  - mh_y_ysr__rule__cond_004
  - mh_y_ysr__rule_002
  - mh_y_ysr__rule__cond_005
  - mh_y_ysr__rule__cond_006
  - mh_y_ysr__rule__cond_007
  - mh_y_ysr__rule__cond_008
  - mh_y_ysr__rule__cond_009
  - mh_y_ysr__rule_003
  - mh_y_ysr__rule_004
  - mh_y_ysr__rule__cond_010
  - mh_y_ysr__rule_005
  - mh_y_ysr__aggr__opp_001
  - mh_y_ysr__aggr__cond_001
  - mh_y_ysr__aggr_001
  - mh_y_ysr__aggr_002
  - mh_y_ysr__aggr__cond_002
  - mh_y_ysr__aggr__opp_002
  - mh_y_ysr__aggr__opp_003
  - mh_y_ysr__aggr__cond_003
  - mh_y_ysr__aggr__cond_004
  - mh_y_ysr__aggr_003
  - mh_y_ysr__aggr__opp_004
  - mh_y_ysr__aggr_004
  - mh_y_ysr__aggr_005
  - mh_y_ysr__aggr_006
  - mh_y_ysr__aggr__opp_005
  - mh_y_ysr__aggr__cond_005

  - mh_y_ysr__aggr__adhd_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__ext

compute_mh_y_ysr__synd__ext_nm(
  data,
  name = "mh_y_ysr__synd__ext_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__ext is vector of all column names used to compute summary score of mh_y_ysr__synd__ext scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__ext_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__ext_nm", vars_mh_y_ysr__synd__ext))
  )

## End(Not run)
```

vars_mh_y_ysr__synd__int

Compute "Youth Self Report [Youth] (Syndrome Scale - Internaling): Number missing"

Description

Computes the summary score mh_y_ysr__synd__int_nm Youth Self Report [Youth] (Syndrome Scale - Internaling): Number missing

- *Summarized variables:*
  - mh_y_ysr__anxdep__dep_001
  - mh_y_ysr__anxdep__anx_001
  - mh_y_ysr__anxdep__anx_002
  - mh_y_ysr__anxdep__anx_003
  - mh_y_ysr__anxdep_001
  - mh_y_ysr__anxdep_002
  - mh_y_ysr__anxdep__dep_002
  - mh_y_ysr__anxdep__anx_004
  - mh_y_ysr__anxdep__anx_005
  - mh_y_ysr__anxdep__dep_003
  - mh_y_ysr__anxdep__anx_006
  - mh_y_ysr__anxdep__anx_007
  - mh_y_ysr__wthdep__dep_001
  - mh_y_ysr__wthdep_001
  - mh_y_ysr__wthdep_002
  - mh_y_ysr__wthdep_003
  - mh_y_ysr__wthdep_004
  - mh_y_ysr__wthdep__dep_002
  - mh_y_ysr__wthdep__dep_003
  - mh_y_ysr__wthdep_005
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__som_001
  - mh_y_ysr__som__dep_001
  - mh_y_ysr__som__somat_001
  - mh_y_ysr__som__somat_002
  - mh_y_ysr__som__somat_003
  - mh_y_ysr__som__somat_004
  - mh_y_ysr__som__somat_005
  - mh_y_ysr__som__somat_006
  - mh_y_ysr__som__somat_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__int

compute_mh_y_ysr__synd__int_nm(
  data,
  name = "mh_y_ysr__synd__int_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__int is vector of all column names used to compute summary score of mh_y_ysr__synd__int scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__int_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__int_nm", vars_mh_y_ysr__synd__int))
  )

## End(Not run)
```

---

vars_mh_y_ysr__synd__othpr

Compute "Youth Self Report [Youth] (Other problems): Number missing"

Description

Computes the summary score mh_y_ysr__synd__othpr_nm Youth Self Report [Youth] (Other problems): Number missing

- *Summarized variables:*
  - mh_y_ysr__othpr_001
  - mh_y_ysr__othpr__dep_001
  - mh_y_ysr__othpr_002
  - mh_y_ysr__othpr_003
  - mh_y_ysr__othpr_004
  - mh_y_ysr__othpr_005
  - mh_y_ysr__othpr_006
  - mh_y_ysr__othpr__dep_002
  - mh_y_ysr__othpr__adhd_001
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__othpr

compute_mh_y_ysr__synd__othpr_nm(
  data,
  name = "mh_y_ysr__synd__othpr_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__othpr is vector of all column names used to compute summary score of mh_y_ysr__synd__othpr scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__othpr_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__othpr_nm", vars_mh_y_ysr__synd__othpr))
  )

## End(Not run)
```

`vars_mh_y_ysr__synd__rule`

Compute "Youth Self Report [Youth] (Syndrome Scale - Rule breaking behavior): Number missing"

Description

Computes the summary score `mh_y_ysr__synd__rule_nm` Youth Self Report [Youth] (Syndrome Scale - Rule breaking behavior): Number missing

- *Summarized variables:*
  - `mh_y_ysr__rule_001`
  - `mh_y_ysr__rule__cond_001`
  - `mh_y_ysr__rule__cond_002`
  - `mh_y_ysr__rule__cond_003`
  - `mh_y_ysr__rule__cond_004`
  - `mh_y_ysr__rule_002`
  - `mh_y_ysr__rule__cond_005`
  - `mh_y_ysr__rule__cond_006`
  - `mh_y_ysr__rule__cond_007`
  - `mh_y_ysr__rule__cond_008`
  - `mh_y_ysr__rule__cond_009`
  - `mh_y_ysr__rule_003`
  - `mh_y_ysr__rule_004`
  - `mh_y_ysr__rule__cond_010`
  - `mh_y_ysr__rule_005`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__rule

compute_mh_y_ysr__synd__rule_nm(
  data,
  name = "mh_y_ysr__synd__rule_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__rule is vector of all column names used to compute summary score of mh_y_ysr__synd__rule scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__rule_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__rule_nm", vars_mh_y_ysr__synd__rule))
  )

## End(Not run)
```

---

vars_mh_y_ysr__synd__soc

Compute "Youth Self Report [Youth] (Syndrome Scale -Social problems): Number missing"

Description

Computes the summary score mh_y_ysr__synd__soc_nm Youth Self Report [Youth] (Syndrome Scale -Social problems): Number missing

- *Summarized variables:*
  - mh_y_ysr__soc__anx_001
  - mh_y_ysr__soc_001
  - mh_y_ysr__soc_002
  - mh_y_ysr__soc_003
  - mh_y_ysr__soc_004
  - mh_y_ysr__soc_005
  - mh_y_ysr__soc_006
  - mh_y_ysr__soc_007
  - mh_y_ysr__soc_008
  - mh_y_ysr__soc_009
  - mh_y_ysr__soc_010
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__soc

compute_mh_y_ysr__synd__soc_nm(
  data,
  name = "mh_y_ysr__synd__soc_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__soc is vector of all column names used to compute summary score of mh_y_ysr__synd__soc scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__soc_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__soc_nm", vars_mh_y_ysr__synd__soc))
  )

## End(Not run)
```

---

vars_mh_y_ysr__synd__som

Compute "Youth Self Report [Youth] (Syndrome Scale - Somatic complaints): Number missing"

Description

Computes the summary score mh_y_ysr__synd__som_nm Youth Self Report [Youth] (Syndrome Scale - Somatic complaints): Number missing

- *Summarized variables:*
  - mh_y_ysr__som__anx_001
  - mh_y_ysr__som_001
  - mh_y_ysr__som__dep_001
  - mh_y_ysr__som__somat_001
  - mh_y_ysr__som__somat_002
  - mh_y_ysr__som__somat_003
  - mh_y_ysr__som__somat_004
  - mh_y_ysr__som__somat_005
  - mh_y_ysr__som__somat_006
  - mh_y_ysr__som__somat_007
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__som

compute_mh_y_ysr__synd__som_nm(
  data,
  name = "mh_y_ysr__synd__som_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__som is vector of all column names used to compute summary score of mh_y_ysr__synd__som scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__som_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__som_nm", vars_mh_y_ysr__synd__som))
  )

## End(Not run)
```

---

vars_mh_y_ysr__synd__tho

Compute "Youth Self Report [Youth] (Syndrome Scale - Thought problems): Number missing"

Description

Computes the summary score mh_y_ysr__synd__tho_nm Youth Self Report [Youth] (Syndrome Scale - Thought problems): Number missing

- *Summarized variables:*
  - mh_y_ysr__tho_001
  - mh_y_ysr__tho_002
  - mh_y_ysr__tho_003
  - mh_y_ysr__tho_004
  - mh_y_ysr__tho_005
  - mh_y_ysr__tho_006
  - mh_y_ysr__tho__dep_002

  - mh_y_ysr__tho_007
  - mh_y_ysr__tho_008
  - mh_y_ysr__tho_009
  - mh_y_ysr__tho__dep_003
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__tho

compute_mh_y_ysr__synd__tho_nm(
  data,
  name = "mh_y_ysr__synd__tho_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__tho is vector of all column names used to compute summary score of mh_y_ysr__synd__tho scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__tho_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__tho_nm", vars_mh_y_ysr__synd__tho))
  )

## End(Not run)
```

vars_mh_y_ysr__synd__wthdep *Compute "Youth Self Report [Youth] (Syndrome Scale - Withdrawn/Depressed): Number missing"*

Description

Computes the summary score mh_y_ysr__synd__wthdep_nm Youth Self Report [Youth] (Syndrome Scale - Withdrawn/Depressed): Number missing

- *Summarized variables:*
  - mh_y_ysr__wthdep__dep_001
  - mh_y_ysr__wthdep_001
  - mh_y_ysr__wthdep_002
  - mh_y_ysr__wthdep_003
  - mh_y_ysr__wthdep_004
  - mh_y_ysr__wthdep__dep_002
  - mh_y_ysr__wthdep__dep_003
  - mh_y_ysr__wthdep_005
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_mh_y_ysr__synd__wthdep

compute_mh_y_ysr__synd__wthdep_nm(
  data,
  name = "mh_y_ysr__synd__wthdep_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_mh_y_ysr__synd__wthdep is vector of all column names used to compute summary score of mh_y_ysr__synd__wthdep scores.

Value

tbl. see combine.

Examples

```
## Not run:
compute_mh_y_ysr__synd__wthdep_nm(data) |>
  select(
    any_of(c("mh_y_ysr__synd__wthdep_nm", vars_mh_y_ysr__synd__wthdep))
  )

## End(Not run)
```

---

vars_nc_p_bdefs *Compute "Barkley Deficits in Executive Functioning Scale [Parent] (EF Summary Score): Sum"*

Description

Computes the summary score nc_p_bdefs_sum Barkley Deficits in Executive Functioning Scale [Parent] (EF Summary Score): Sum

- *Summarized variables:*
  - nc_p_bdefs_001
  - nc_p_bdefs_002
  - nc_p_bdefs_003
  - nc_p_bdefs_004
  - nc_p_bdefs_005
  - nc_p_bdefs_006
  - nc_p_bdefs_007
  - nc_p_bdefs_008
  - nc_p_bdefs_009
  - nc_p_bdefs_010
  - nc_p_bdefs_011
  - nc_p_bdefs_012
  - nc_p_bdefs_013
  - nc_p_bdefs_014
  - nc_p_bdefs_015
  - nc_p_bdefs_016
  - nc_p_bdefs_017

- nc_p_bdefs_018
- nc_p_bdefs_019
- nc_p_bdefs_020

Usage

```
vars_nc_p_bdefs

compute_nc_p_bdefs_sum(
  data,
  name = "nc_p_bdefs_sum",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_nc_p_bdefs is a character vector of all column names used to compute summary scores of nc_p_bdefs.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_nc_p_bdefs_sum(data) |>
  select(
    data,
    all_of(c("nc_p_bdefs_sum", vars_nc_p_bdefs))
  )

## End(Not run)
```

vars_nc_y_ehis *Compute "Edinburgh Handedness Inventory [Youth] (Handedness score rating)"*

Description

Computes the summary score nc_y_ehis_score Edinburgh Handedness Inventory [Youth] (Handedness score rating)

- *Summarized variables:*
  - nc_y_ehis_001
  - nc_y_ehis_002
  - nc_y_ehis_003
  - nc_y_ehis_004

Usage

```
vars_nc_y_ehis

compute_nc_y_ehis_score(
  data,
  name = "nc_y_ehis_score",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_nc_y_ehis is a character vector of all column names used to compute summary scores of nc_y_ehis.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_nc_y_ehis_score(data) |>
  select(
    data,
    all_of(c("nc_y_ehis_score", vars_nc_y_ehis))
  )

## End(Not run)
```

`vars_nt_p_yst__pmum` *Compute "Youth Screen Time [Parent] (Problematic Media Use): Mean [Validation: No more than 1 missing or declined]"*

Description

Computes the summary score `nt_p_yst__pmum_mean` Youth Screen Time [Parent] (Problematic Media Use): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - `nt_p_yst__pmum_001`
  - `nt_p_yst__pmum_002`
  - `nt_p_yst__pmum_003`
  - `nt_p_yst__pmum_004`
  - `nt_p_yst__pmum_005`
  - `nt_p_yst__pmum_006`
  - `nt_p_yst__pmum_007`
  - `nt_p_yst__pmum_008`
  - `nt_p_yst__pmum_009`
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_nt_p_yst__pmum

compute_nt_p_yst__pmum_mean(
  data,
  name = "nt_p_yst__pmum_mean",
  max_na = 1,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_nt_p_yst__pmum is a character vector of all column names used to compute summary score of `nt_p_yst__pmum_mean`.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_nt_p_yst__screen__wkdy

Compute "Youth Screen Time [Parent] (Weekday): Sum"

Description

Computes the summary score `nt_p_yst__screen__wkdy_sum` Youth Screen Time [Parent] (Weekday): Sum

- *Summarized variables:*
  - `nt_p_yst__wkdy__hr_001`
  - `nt_p_yst__wkdy__min_001`
  - `nt_p_yst__wkdy__min_001__v01`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 1 item missing

Usage

```
vars_nt_p_yst__screen__wkdy

compute_nt_p_yst__screen__wkdy_sum(
  data,
  name = "nt_p_yst__screen__wkdy_sum",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_nt_p_yst__screen__wkdy is a character vector of all column names used to compute summary score of `nt_p_yst__screen__wkdy`.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_nt_p_yst__screen__wknd

Compute "Youth Screen Time [Parent] (Weekend): Sum"

Description

Computes the summary score `nt_p_yst__screen__wknd_sum` Youth Screen Time [Parent] (Weekend): Sum

- *Summarized variables:*
  - `nt_p_yst__wknd__hr_001`
  - `nt_p_yst__wknd__min_001`
  - `nt_p_yst__wknd__min_001__v01`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 of 1 item missing

Usage

```
vars_nt_p_yst__screen__wknd

compute_nt_p_yst__screen__wknd_sum(
  data,
  name = "nt_p_yst__screen__wknd_sum",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_nt_p_yst__screen__wknd is a character vector of all column names used to compute summary score of nt_p_yst__screen__wknd.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_nt_y_stq__screen__wkdy

Compute "Screen Time [Youth] (Weekday): Sum"

Description

Computes the summary score nt_y_stq__screen__wkdy_sum Screen Time [Youth] (Weekday): Sum

- *Summarized variables:*
  - nt_y_stq__screen__wkdy_001
  - nt_y_stq__screen__wkdy_002
  - nt_y_stq__screen__wkdy_003
  - nt_y_stq__screen__wkdy_004
  - nt_y_stq__screen__wkdy_005
  - nt_y_stq__screen__wkdy_006
  - nt_y_stq__screen__wkdy__hr_001
  - nt_y_stq__screen__wkdy__min_001
  - nt_y_stq__screen__wkdy__hr_001__v01
  - nt_y_stq__screen__wkdy__min_001__v01
  - nt_y_stq__screen__wkdy__hr_002
  - nt_y_stq__screen__wkdy__min_002
  - nt_y_stq__screen__wkdy__hr_003
  - nt_y_stq__screen__wkdy__min_003
  - nt_y_stq__screen__wkdy__hr_004

  - nt_y_stq__screen__wkdy__min_004
  - nt_y_stq__screen__wkdy__hr_005
  - nt_y_stq__screen__wkdy__min_005
  - nt_y_stq__screen__wkdy__hr_006
  - nt_y_stq__screen__wkdy__min_006
  - nt_y_stq__screen__wkdy__hr_007
  - nt_y_stq__screen__wkdy__min_007
  - nt_y_stq__screen__wkdy__hr_008
  - nt_y_stq__screen__wkdy__min_008
  - nt_y_stq__screen__wkdy__hr_009
  - nt_y_stq__screen__wkdy__min_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* none missing

Usage

```
vars_nt_y_stq__screen__wkdy

compute_nt_y_stq__screen__wkdy_sum(
  data,
  name = "nt_y_stq__screen__wkdy_sum",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_nt_y_stq__screen__wkdy is a character vector of all column names used to compute summary score of nt_y_stq__screen__wkdy.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_nt_y_stq__screen__wknd *Compute "Screen Time [Youth] (Weekend): Sum"*

Description

Computes the summary score nt_y_stq__screen__wknd_sum Screen Time [Youth] (Weekend): Sum

- *Summarized variables:*
  - nt_y_stq__screen__wknd_001
  - nt_y_stq__screen__wknd_002
  - nt_y_stq__screen__wknd_003
  - nt_y_stq__screen__wknd_004
  - nt_y_stq__screen__wknd_005
  - nt_y_stq__screen__wknd_006
  - nt_y_stq__screen__wknd__hr_001
  - nt_y_stq__screen__wknd__min_001
  - nt_y_stq__screen__wknd__hr_001__v01
  - nt_y_stq__screen__wknd__min_001__v01
  - nt_y_stq__screen__wknd__hr_002
  - nt_y_stq__screen__wknd__min_002
  - nt_y_stq__screen__wknd__hr_003
  - nt_y_stq__screen__wknd__min_003
  - nt_y_stq__screen__wknd__hr_004
  - nt_y_stq__screen__wknd__min_004
  - nt_y_stq__screen__wknd__hr_005
  - nt_y_stq__screen__wknd__min_005
  - nt_y_stq__screen__wknd__hr_006
  - nt_y_stq__screen__wknd__min_006
  - nt_y_stq__screen__wknd__hr_007
  - nt_y_stq__screen__wknd__min_007
  - nt_y_stq__screen__wknd__hr_008
  - nt_y_stq__screen__wknd__min_008
  - nt_y_stq__screen__wknd__hr_009
  - nt_y_stq__screen__wknd__min_009
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* none missing

Usage

```
vars_nt_y_stq__screen__wknd

compute_nt_y_stq__screen__wknd_sum(
  data,
  name = "nt_y_stq__screen__wknd_sum",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_nt_y_stq__screen__wknd is a character vector of all column names used to compute summary score of `nt_y_stq__screen__wknd`.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_p_anthr__height

Compute "Anthropometrics [Parent] (Height): Father's height (in)"

Description

Computes the summary score `ph_p_anthr__fath_height__in` Anthropometrics [Parent] (Height): Father's height (in)

- *Summarized variables:*
  - `ph_p_anthr__height__fath_001`
  - `ph_p_anthr__height__fath_001__01`
- *Excluded values:* None
- *Validation criterion:* None

Usage

```
vars_ph_p_anthr__height

compute_ph_p_anthr__fath_height__in(
  data,
  name = "ph_p_anthr__fath_height__in",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

character vector of all column names used to compute summary scores of ph_p_anthr__fath_height__in and ph_p_anthr__moth_height__in.

Examples

```
## Not run:
compute_ph_p_anthr__fath_height__in(data) |>
  select(
    all_of(c("ph_p_anthr__fath_height__in", vars_ph_p_anthr__height))
  )

## End(Not run)
```

---

vars_ph_p_cna *Compute "Child Nutrition Assessment [Parent]: Sum [Validation: No more than 0 missing or declined]"*

Description

Computes the summary score ph_p_cna_sum Child Nutrition Assessment [Parent]: Sum [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_p_cna_001
  - ph_p_cna_002
  - ph_p_cna_003
  - ph_p_cna_004

  - ph_p_cna_005
  - ph_p_cna_006
  - ph_p_cna_007
  - ph_p_cna_008
  - ph_p_cna_009
  - ph_p_cna_010
  - ph_p_cna_011
  - ph_p_cna_012
  - ph_p_cna_013
  - ph_p_cna_014
- *Excluded values:*
  - 999
  - 777
- *Validation criterion:* maximally 0 of 14 items missing

Usage

```
vars_ph_p_cna

compute_ph_p_cna_sum(
  data,
  name = "ph_p_cna_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_ph_p_cna is a character vector of all column names used to compute summary scores of ph_p_cna.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_p_cna_sum(data) |>
  select(
    all_of(c("ph_p_cna_sum", vars_ph_p_cna))
  )

## End(Not run)
```

`vars_ph_p_dhx_birthweight`
Compute "Developmental History [Parent]: Youth birth weight"

Description

Computes the summary score `ph_p_dhx_birthweight` Developmental History [Parent]: Youth birth weight

- *Summarized variables:*
  - `ph_p_dhx_002__01`
  - `ph_p_dhx_002__02`
- *Excluded values:*
  - 999
  - any value less than 0
- *Notes:*
  - Computed using only baseline (`ses-00A`) and four-year (`ses-04A`) data
  - The following transformations were made prior to computing the score:
    - if `ph_p_dhx_002__01` < 2, set it to 2
    - if `ph_p_dhx_002__01` > 15, set it to 15
    - if `ph_p_dhx_002__02` > 15 / 16, set it to 15 / 16
  - The following decisions were made based on discordance between baseline and four-year data:
    - if discordance is <= 1, take baseline weight
    - if discordance is > 1 and baseline weight is > 4, take baseline weight
    - else if discordance is > 1, take four-year weight
    - else if baseline weight is missing, take four-year weight
    - else, take baseline weight

Usage

```
vars_ph_p_dhx_birthweight

compute_ph_p_dhx_birthweight(
  data,
  name = "ph_p_dhx_birthweight",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized. NOTE: Only baseline and year 4 data has been used for this summary score.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_ph_p_dhx_birthweight is a character vector of all column names used to compute summary score of ph_p_dhx_birthweight.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_p_otbi *Compute "Ohio State Traumatic Brain Injury Screen [Parent]: Number of missing gating items"*

Description

Computes the summary score ph_p_otbi_nm Ohio State Traumatic Brain Injury Screen [Parent]: Number of missing gating items

- *Excluded values:*
  - 777
  - 999

Usage

```
vars_ph_p_otbi

compute_ph_p_otbi_nm(
  data,
  name = "ph_p_otbi_nm",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_ph_p_otbi is a character vector of all column names used to compute summary score of ph_p_otbi_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_p_otbi__loc__30m_count

Compute "Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness - Over 30 minutes): Count"

Description

Computes the summary score ph_p_otbi__loc__30m_count Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness - Over 30 minutes): Count

- *Summarized variables:*
  - ph_p_otbi_001
  - ph_p_otbi__loc_001
  - ph_p_otbi_002
  - ph_p_otbi__loc_002
  - ph_p_otbi_003
  - ph_p_otbi__loc_003
  - ph_p_otbi_004
  - ph_p_otbi__loc_004
  - ph_p_otbi_005
  - ph_p_otbi__loc_005
  - ph_p_otbi__loc__add_001
  - ph_p_otbi__loc__add_001__03
  - ph_p_otbi__rpt_001
  - ph_p_otbi__rpt__loc_001
  - ph_p_otbi_001__l

  - ph_p_otbi__loc_001__l
  - ph_p_otbi_002__l
  - ph_p_otbi__loc_002__l
  - ph_p_otbi_003__l
  - ph_p_otbi__loc_003__l
  - ph_p_otbi_004__l
  - ph_p_otbi__loc_004__l
  - ph_p_otbi_005__l
  - ph_p_otbi__loc_005__l
  - ph_p_otbi__loc__add_001__l
  - ph_p_otbi__loc__add_001__03__l
  - ph_p_otbi__rpt_001__l
  - ph_p_otbi__rpt__loc_001__l
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_ph_p_otbi__loc__30m_count

compute_ph_p_otbi__loc__30m_count(
  data,
  name = "ph_p_otbi__loc__30m_count",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_ph_p_otbi__loc__30m_count is a character vector of all column names used to compute summary score of ph_p_otbi__loc__30m_count.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_ph_p_otbi__loc_before15 *Compute "Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): LOC before the age of 15"*

Description

Computes the summary score ph_p_otbi__loc_before15 Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): LOC before the age of 15

- *Summarized variables:*
  - ph_p_otbi_001
  - ph_p_otbi__loc_001
  - ph_p_otbi__age_001
  - ph_p_otbi_002
  - ph_p_otbi__loc_002
  - ph_p_otbi__age_002
  - ph_p_otbi_003
  - ph_p_otbi__loc_003
  - ph_p_otbi__age_003
  - ph_p_otbi_004
  - ph_p_otbi__loc_004
  - ph_p_otbi__age_004
  - ph_p_otbi_005
  - ph_p_otbi__loc_005
  - ph_p_otbi__age_005
  - ph_p_otbi__loc__add_001
  - ph_p_otbi__loc__add_001__04
  - ph_p_otbi__rpt_001
  - ph_p_otbi__rpt__loc_001
  - ph_p_otbi__rpt__age_001a
  - ph_p_otbi__rpt_002
  - ph_p_otbi__rpt__loc__daz_002
  - ph_p_otbi__rpt__age_002a
  - ph_p_otbi__rpt_003
  - ph_p_otbi__rpt__loc__daz_003
  - ph_p_otbi__rpt__age_003a
  - ph_p_otbi_001__l
  - ph_p_otbi__loc_001__l
  - ph_p_otbi__age_001__l
  - ph_p_otbi_002__l
  - ph_p_otbi__loc_002__l

  - ph_p_otbi__age_002__l
  - ph_p_otbi_003__l
  - ph_p_otbi__loc_003__l
  - ph_p_otbi__age_003__l
  - ph_p_otbi_004__l
  - ph_p_otbi__loc_004__l
  - ph_p_otbi__age_004__l
  - ph_p_otbi_005__l
  - ph_p_otbi__loc_005__l
  - ph_p_otbi__age_005__l
  - ph_p_otbi__loc__add_001__l
  - ph_p_otbi__loc__add_001__04__l
  - ph_p_otbi__rpt_001__l
  - ph_p_otbi__rpt__loc_001__l
  - ph_p_otbi__rpt__age_001a__l
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_ph_p_otbi__loc_before15

compute_ph_p_otbi__loc_before15(
  data,
  name = "ph_p_otbi__loc_before15",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_ph_p_otbi__loc_before15 is a character vector of all column names used to compute summary score of ph_p_otbi__loc_before15.

Value

tbl. The input data frame with the summary score appended as a new column.

See Also

compute_ph_p_otbi__loc_tbiage()

---

vars_ph_p_otbi__loc_count

Compute "Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): Count"

Description

Computes the summary score ph_p_otbi__loc_count Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): Count

- *Summarized variables:*
  - ph_p_otbi_001
  - ph_p_otbi__loc_001
  - ph_p_otbi_002
  - ph_p_otbi__loc_002
  - ph_p_otbi_003
  - ph_p_otbi__loc_003
  - ph_p_otbi_004
  - ph_p_otbi__loc_004
  - ph_p_otbi_005
  - ph_p_otbi__loc_005
  - ph_p_otbi__loc__add_001
  - ph_p_otbi__loc__add_001__01
  - ph_p_otbi__rpt_001
  - ph_p_otbi__rpt__loc_001
  - ph_p_otbi__rpt_002
  - ph_p_otbi__rpt__loc__daz_002
  - ph_p_otbi__rpt_003
  - ph_p_otbi__rpt__loc__daz_003
  - ph_p_otbi_001__l
  - ph_p_otbi__loc_001__l
  - ph_p_otbi_002__l
  - ph_p_otbi__loc_002__l
  - ph_p_otbi_003__l
  - ph_p_otbi__loc_003__l
  - ph_p_otbi_004__l
  - ph_p_otbi__loc_004__l
  - ph_p_otbi_005__l
  - ph_p_otbi__loc_005__l

  - ph_p_otbi__loc__add_001__l
  - ph_p_otbi__loc__add_001__01__l
  - ph_p_otbi__rpt_001__l
  - ph_p_otbi__rpt__loc_001__l
- *Excluded values:*
  - 777
  - 999

Usage

```
vars_ph_p_otbi__loc_count

compute_ph_p_otbi__loc_count(
  data,
  name = "ph_p_otbi__loc_count",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_ph_p_otbi__loc_count is a character vector of all column names used to compute summary score of ph_p_otbi__loc_count.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_p_otbi__loc_tbiage

Compute "Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): Age of first injury with LOC"

Description

Computes the summary score ph_p_otbi__loc_tbiage Ohio State Traumatic Brain Injury Screen [Parent] (Loss of consciousness): Age of first injury with LOC

- *Summarized variables:*
  - ph_p_otbi_001
  - ph_p_otbi__loc_001
  - ph_p_otbi__age_001
  - ph_p_otbi_002
  - ph_p_otbi__loc_002
  - ph_p_otbi__age_002
  - ph_p_otbi_003
  - ph_p_otbi__loc_003
  - ph_p_otbi__age_003
  - ph_p_otbi_004
  - ph_p_otbi__loc_004
  - ph_p_otbi__age_004
  - ph_p_otbi_005
  - ph_p_otbi__loc_005
  - ph_p_otbi__age_005
  - ph_p_otbi__loc__add_001
  - ph_p_otbi__loc__add_001__04
  - ph_p_otbi__rpt_001
  - ph_p_otbi__rpt__loc_001
  - ph_p_otbi__rpt__age_001a
  - ph_p_otbi__rpt_002
  - ph_p_otbi__rpt__loc__daz_002
  - ph_p_otbi__rpt__age_002a
  - ph_p_otbi__rpt_003
  - ph_p_otbi__rpt__loc__daz_003
  - ph_p_otbi__rpt__age_003a
  - ph_p_otbi_001__l
  - ph_p_otbi__loc_001__l
  - ph_p_otbi__age_001__l
  - ph_p_otbi_002__l
  - ph_p_otbi__loc_002__l
  - ph_p_otbi__age_002__l
  - ph_p_otbi_003__l
  - ph_p_otbi__loc_003__l
  - ph_p_otbi__age_003__l
  - ph_p_otbi_004__l
  - ph_p_otbi__loc_004__l

  - ph_p_otbi__age_004__l
  - ph_p_otbi_005__l
  - ph_p_otbi__loc_005__l
  - ph_p_otbi__age_005__l
  - ph_p_otbi__loc__add_001__l
  - ph_p_otbi__loc__add_001__04__l
  - ph_p_otbi__rpt_001__l
  - ph_p_otbi__rpt__loc_001__l
  - ph_p_otbi__rpt__age_001a__l
- *Excluded values:*
  - 777
  - 999
  - any reported age less than or equal to 0
- *Notes:*
  - The output is set to NA for the following cases:
    * minimum age is less than 0
    * minimum age is higher than age at visit
    * no head or neck injury/impact is reported

Usage

```
vars_ph_p_otbi__loc_tbiage

compute_ph_p_otbi__loc_tbiage(
  data,
  name = "ph_p_otbi__loc_tbiage",
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_ph_p_otbi__loc_tbiage is a character vector of all column names used to compute summary score of ph_p_otbi__loc_tbiage.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_ph_p_otbi__rpt_count

Compute "Ohio State Traumatic Brain Injury Screen [Parent] (Repeated injuries): Count"

Description

Computes the summary score ph_p_otbi__rpt_count Ohio State Traumatic Brain Injury Screen [Parent] (Repeated injuries): Count [Validation: No more than 2 missing or declined at baseline and no more than 0 missing or declined at non-baseline events]

- *Summarized variables:*
  - ph_p_otbi__rpt_001
  - ph_p_otbi__rpt_002
  - ph_p_otbi__rpt_003
  - ph_p_otbi__rpt_001__l
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:*
  - maximally 2 item missing at baseline event
  - maximally 0 item missing at non-baseline events

Usage

```
vars_ph_p_otbi__rpt_count

compute_ph_p_otbi__rpt_count(
  data,
  name = "ph_p_otbi__rpt_count",
  exclude = c("777", "999"),
  combine = TRUE,
  max_na = 2
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 2).

Format

vars_ph_p_otbi__rpt_count is a character vector of all column names used to compute summary score of ph_p_otbi__rpt_count.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_p_otbi_tbiworst

Compute "Ohio State Traumatic Brain Injury Screen [Parent]: Worst injury overall"

Description

Computes the summary score ph_p_otbi_tbiworst Ohio State Traumatic Brain Injury Screen [Parent]: Worst injury overall

- *Summarized variables:*
  - ph_p_otbi_001
  - ph_p_otbi_002
  - ph_p_otbi_003
  - ph_p_otbi_004
  - ph_p_otbi_005
  - ph_p_otbi__loc__add_001
  - ph_p_otbi__rpt_001
  - ph_p_otbi_001__l
  - ph_p_otbi_002__l
  - ph_p_otbi_003__l
  - ph_p_otbi_004__l
  - ph_p_otbi_005__l
  - ph_p_otbi__loc__add_001__l
  - ph_p_otbi__rpt_001__l
  - ph_p_otbi__loc_001
  - ph_p_otbi__loc_002
  - ph_p_otbi__loc_003
  - ph_p_otbi__loc_004
  - ph_p_otbi__loc_005
  - ph_p_otbi__daz_001
  - ph_p_otbi__daz_002
  - ph_p_otbi__daz_003
  - ph_p_otbi__daz_004
  - ph_p_otbi__daz_005

  - ph_p_otbi__rpt__loc_001
  - ph_p_otbi__rpt__daz_001
  - ph_p_otbi__rpt_002
  - ph_p_otbi__rpt__loc__daz_002
  - ph_p_otbi__rpt_003
  - ph_p_otbi__rpt__loc__daz_003
  - ph_p_otbi__loc_001__l
  - ph_p_otbi__loc_002__l
  - ph_p_otbi__loc_003__l
  - ph_p_otbi__loc_004__l
  - ph_p_otbi__loc_005__l
  - ph_p_otbi__daz_001__l
  - ph_p_otbi__daz_002__l
  - ph_p_otbi__daz_003__l
  - ph_p_otbi__daz_004__l
  - ph_p_otbi__daz_005__l
  - ph_p_otbi__rpt__loc_001__l
  - ph_p_otbi__rpt__daz_001__l
  - ph_p_otbi__loc__add_001__02
  - ph_p_otbi__loc__add_001__03
  - ph_p_otbi__loc__add_001__02__l
  - ph_p_otbi__loc__add_001__03__l
- *Excluded values:*
  - 777
  - 999
- *Notes:*
  - Computed using the following summary scores:
    * ph_p_otbi__tbi1a
    * ph_p_otbi__tbi1b
    * ph_p_otbi__tbi2
    * ph_p_otbi__tbi3
    * ph_p_otbi__tbi4
    * ph_p_otbi__tbi5

Usage

```
vars_ph_p_otbi_tbiworst

compute_ph_p_otbi_tbiworst(
  data,
  name = "ph_p_otbi_tbiworst",
  keep_summaries = FALSE,
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
keep_summaries	logical. If TRUE, intermediate columns created to compute the summary score will be retained. If FALSE, the intermediate columns will be removed. Default set to FALSE.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_ph_p_otbi_tbiworst is a character vector of all column names used to compute summary score of ph_p_otbi_tbiworst.

Value

tbl. The input data frame with the summary score(s) appended as a new column.

---

vars_ph_p_pds__f *Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Female): Mean"*

Description

Computes the summary score ph_p_pds__f_mean Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Female): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - ph_p_pds_001
  - ph_p_pds_002
  - ph_p_pds_003
  - ph_p_pds__f_001
  - ph_p_pds__f_002
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 item missing
- *Notes:*
  - Values in ph_p_pds__f_002 were recoded:
    - "0" –> "1",
    - "1" –> "4"

Usage

```
vars_ph_p_pds__f

compute_ph_p_pds__f_mean(
  data,
  name = "ph_p_pds__f_mean",
  exclude = c("777", "999"),
  combine = TRUE,
  max_na = 1
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.

Format

vars_ph_p_pds__f is a character vector of all column names used to compute summary score of ph_p_pds__f_mean and ph_p_pds__f_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_p_pds__f_categ

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Female): Approximate tanner stages"

Description

Computes the summary score ph_p_pds__f_categ Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Female): Approximate tanner stages [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_p_pds_002
  - ph_p_pds__f_001

    - ph_p_pds__f_002

- *Excluded values:*
    - 777
    - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_p_pds__f_categ

compute_ph_p_pds__f_categ(
  data,
  name = "ph_p_pds__f_categ",
  exclude = c("777", "999"),
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.

Format

vars_ph_p_pds__f is a character vector of all column names used to compute summary score of ph_p_pds__f_categ and ph_p_pds__f__categ_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_ph_p_pds__m *Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Male): Mean"*

Description

Computes the summary score ph_p_pds__m_mean Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Male): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - ph_p_pds_001
  - ph_p_pds_002
  - ph_p_pds_003
  - ph_p_pds__m_001
  - ph_p_pds__m_002
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 item missing

Usage

```
vars_ph_p_pds__m

compute_ph_p_pds__m_mean(
  data,
  name = "ph_p_pds__m_mean",
  exclude = c("777", "999"),
  combine = TRUE,
  max_na = 1
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.

Format

vars_ph_p_pds__m is a character vector of all column names used to compute summary score of ph_p_pds__m_mean and ph_p_pds__m_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_p_pds__m_categ

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Male): Approximate tanner stages"

Description

Computes the summary score ph_p_pds__m_categ Pubertal Development Scale & Menstrual Cycle Survey History [Parent] (Male): Approximate tanner stages [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_p_pds_002
  - ph_p_pds__m_001
  - ph_p_pds__m_002
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_p_pds__m_categ

compute_ph_p_pds__m_categ(
  data,
  name = "ph_p_pds__m_categ",
  exclude = c("777", "999"),
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.

Format

vars_ph_p_pds__m is a character vector of all column names used to compute summary score of ph_p_pds__m_categ and ph_p_pds__m__categ_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_p_sds__da *Compute "Sleep Disturbance Scale [Parent] (Disorder of arousal): Sum [Validation: No more than 0 missing or declined]"*

Description

Computes the summary score ph_p_sds__da_sum Sleep Disturbance Scale [Parent] (Disorder of arousal): Sum [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_p_sds__da_001
  - ph_p_sds__da_002
  - ph_p_sds__da_003
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_p_sds__da

compute_ph_p_sds__da_sum(
  data,
  name = "ph_p_sds__da_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

character vector of all column names used to compute summary scores of ph_p_sds__da_sum and ph_p_sds__da_nm.

Examples

```
## Not run:
compute_ph_p_sds__da_sum(data) |>
  select(
    all_of(c("ph_p_sds__da_sum", vars_ph_p_sds__da))
  )

## End(Not run)
```

---

vars_ph_p_sds__dims *Compute "Sleep Disturbance Scale [Parent] (Disorders of initiating and maintaining sleep): Sum [Validation: No more than 0 missing or declined]"*

Description

Computes the summary score ph_p_sds__dims_sum Sleep Disturbance Scale [Parent] (Disorders of initiating and maintaining sleep): Sum [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_p_sds__dims_001
  - ph_p_sds__dims_002
  - ph_p_sds__dims_003
  - ph_p_sds__dims_004
  - ph_p_sds__dims_005
  - ph_p_sds__dims_006
  - ph_p_sds__dims_007
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_p_sds__dims

compute_ph_p_sds__dims_sum(
  data,
  name = "ph_p_sds__dims_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

character vector of all column names used to compute summary scores of ph_p_sds__dims_sum and ph_p_sds__dims_nm.

Examples

```
## Not run:
compute_ph_p_sds__dims_sum(data) |>
  select(
    all_of(c("ph_p_sds__dims_sum", vars_ph_p_sds__dims))
  )

## End(Not run)
```

`vars_ph_p_sds__does` *Compute "Sleep Disturbance Scale [Parent] (Disorders of excessive somnolence): Sum [Validation: No more than 0 missing or declined]"*

Description

Computes the summary score `ph_p_sds__does_sum` Sleep Disturbance Scale [Parent] (Disorders of excessive somnolence): Sum [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `ph_p_sds__does_001`
  - `ph_p_sds__does_002`
  - `ph_p_sds__does_003`
  - `ph_p_sds__does_004`
  - `ph_p_sds__does_005`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_p_sds__does

compute_ph_p_sds__does_sum(
  data,
  name = "ph_p_sds__does_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

character vector of all column names used to compute summary scores of ph_p_sds__does_sum and ph_p_sds__does_nm.

Examples

```
## Not run:
compute_ph_p_sds__does_sum(data) |>
  select(
    all_of(c("ph_p_sds__does_sum", vars_ph_p_sds__does))
  )

## End(Not run)
```

---

vars_ph_p_sds__hyphy *Compute "Sleep Disturbance Scale [Parent] (Sleep hyperhydrosis): Sum [Validation: No more than 0 missing or declined]"*

Description

Computes the summary score ph_p_sds__hyphy_sum Sleep Disturbance Scale [Parent] (Sleep hyperhydrosis): Sum [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_p_sds__hyphy_001
  - ph_p_sds__hyphy_002
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_p_sds__hyphy

compute_ph_p_sds__hyphy_sum(
  data,
  name = "ph_p_sds__hyphy_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

character vector of all column names used to compute summary scores of ph_p_sds__hyphy_sum and ph_p_sds__hyphy_nm.

Examples

```
## Not run:
compute_ph_p_sds__hyphy_sum(data) |>
  select(
    all_of(c("ph_p_sds__hyphy_sum", vars_ph_p_sds__hyphy))
  )

## End(Not run)
```

---

vars_ph_p_sds__sbd *Compute "Sleep Disturbance Scale [Parent] (Sleep breathing disorders): Sum [Validation: No more than 0 missing or declined]"*

Description

Computes the summary score ph_p_sds__sbd_sum Sleep Disturbance Scale [Parent] (Sleep breathing disorders): Sum [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_p_sds__sbd_001
  - ph_p_sds__sbd_002
  - ph_p_sds__sbd_003
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_p_sds__sbd

compute_ph_p_sds__sbd_sum(
  data,
  name = "ph_p_sds__sbd_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

character vector of all column names used to compute summary scores of ph_p_sds__sbd_sum and ph_p_sds__sbd_nm.

Examples

```
## Not run:
compute_ph_p_sds__sbd_sum(data) |>
  select(
    all_of(c("ph_p_sds__sbd_sum", vars_ph_p_sds__sbd))
```

```
  )

## End(Not run)
```

`vars_ph_p_sds__swtd` *Compute "Sleep Disturbance Scale [Parent] (Sleep-wake transition disorders): Sum [Validation: No more than 0 missing or declined]"*

Description

Computes the summary score `ph_p_sds__swtd_sum` Sleep Disturbance Scale [Parent] (Sleep-wake transition disorders): Sum [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - `ph_p_sds__swtd_001`
  - `ph_p_sds__swtd_002`
  - `ph_p_sds__swtd_003`
  - `ph_p_sds__swtd_004`
  - `ph_p_sds__swtd_005`
  - `ph_p_sds__swtd_006`
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_p_sds__swtd

compute_ph_p_sds__swtd_sum(
  data,
  name = "ph_p_sds__swtd_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`max_na`	integer, Maximum number of missing values allowed in the summary score. `NULL` means no limit.
`exclude`	character, Values to be excluded from the summary score.
`combine`	logical, If `TRUE`, the summary score will be appended to the input data frame. If `FALSE`, the summary score will be returned as a separate data frame.

Format

character vector of all column names used to compute summary scores of ph_p_sds__swtd_sum and ph_p_sds__swtd_nm.

Examples

```
## Not run:
compute_ph_p_sds__swtd_sum(data) |>
  select(
    all_of(c("ph_p_sds__swtd_sum", vars_ph_p_sds__swtd))
  )

## End(Not run)
```

---

vars_ph_p_sds_sum *Compute "Sleep Disturbance Scale [Parent]: Sum [Validation: No more than 0 missing or declined]"*

Description

Computes the summary score ph_p_sds_sum Sleep Disturbance Scale [Parent]: Sum [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_p_sds__dims_001
  - ph_p_sds__dims_002
  - ph_p_sds__dims_003
  - ph_p_sds__dims_004
  - ph_p_sds__dims_005
  - ph_p_sds__swtd_001
  - ph_p_sds__swtd_002
  - ph_p_sds__swtd_003
  - ph_p_sds__hyphy_001
  - ph_p_sds__dims_006
  - ph_p_sds__dims_007
  - ph_p_sds__swtd_004
  - ph_p_sds__sbd_001
  - ph_p_sds__sbd_002
  - ph_p_sds__sbd_003
  - ph_p_sds__hyphy_002
  - ph_p_sds__da_001
  - ph_p_sds__swtd_005
  - ph_p_sds__swtd_006
  - ph_p_sds__da_002

  - ph_p_sds__da_003
  - ph_p_sds__does_001
  - ph_p_sds__does_002
  - ph_p_sds__does_003
  - ph_p_sds__does_004
  - ph_p_sds__does_005
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_p_sds_sum

compute_ph_p_sds_sum(
  data,
  name = "ph_p_sds_sum",
  max_na = 0,
  exclude = c("777", "999"),
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score. NULL means no limit.
exclude	character, Values to be excluded from the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

character vector of all column names used to compute summary scores of ph_p_sds_sum and ph_p_sds_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_p_sds_sum(data) |>
  select(
    all_of(c("ph_p_sds_sum", vars_ph_p_sds_sum))
  )

## End(Not run)
```

`vars_ph_y_anthr__height`

Compute "Anthropometrics [Youth] (Height): Mean"

Description

Computes the summary score `ph_y_anthr__height_mean` Anthropometrics [Youth] (Height): Mean

- *Summarized variables:*
  - `ph_y_anthr__height__r01_001`
  - `ph_y_anthr__height__r02_001`
  - `ph_y_anthr__height__r03_001`
- *Excluded values:* none

Calculation:

There are at most 3 possible measurements, and the calculation is as follows:

- 0 missing, find the max and min of the three, and take the average of the min and max. Then compare the average to the third value.
  - third value < average -> mean(min, third value)
  - third value > average -> mean(max, third value)
  - third value = average -> third value
- 1 missing, mean of the rest two
- 2 missing, use the last one
- 3 missing, NA

Usage

```
vars_ph_y_anthr__height

compute_ph_y_anthr__height_mean(
  data,
  name = "ph_y_anthr__height_mean",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_ph_y_anthr__height is a character vector of all column names used to compute summary scores of ph_y_anthr__height.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_anthr__height_mean(data) |>
  select(
    all_of(c("ph_y_anthr__height_mean", vars_ph_y_anthr__height))
  )

## End(Not run)
```

---

vars_ph_y_anthr__weight

Compute "Anthropometrics [Youth] (Weight): Mean"

Description

Computes the summary score ph_y_anthr__weight_mean Anthropometrics [Youth] (Weight): Mean

- *Summarized variables:* * ph_y_anthr__weight__r01_001
  - ph_y_anthr__weight__r02_001
  - ph_y_anthr__weight__r03_001
- *Excluded values:* none

Calculation:

There are at most 3 possible measurements, and the calculation is as follows:

- 0 missing, find the max and min of the three, and take the average of the min and max. Then compare the average to the third value.
  - third value < average -> mean(min, third value)
  - third value > average -> mean(max, third value)
  - third value = average -> third value

- 1 missing, mean of the rest two
- 2 missing, use the last one
- 3 missing, NA

Usage

```
vars_ph_y_anthr__weight

compute_ph_y_anthr__weight_mean(
  data,
  name = "ph_y_anthr__weight_mean",
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_ph_y_anthr__weight is a character vector of all column names used to compute summary scores of ph_y_anthr__weight.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_anthr__weight_mean(data) |>
  select(
    all_of(c("ph_y_anthr__weight_mean", vars_ph_y_anthr__weight))
  )

## End(Not run)
```

vars_ph_y_bp__dia *Compute "Blood Pressure [Youth] (Diastolic): Mean"*

Description

Computes the summary score ph_y_bp__dia_mean Blood Pressure [Youth] (Diastolic): Mean

- *Summarized variables:*
  - ph_y_bp__dia__r01_001
  - ph_y_bp__dia__r01_002
  - ph_y_bp__dia__r01_003
  - ph_y_bp__dia__r02_001
  - ph_y_bp__dia__r02_002
  - ph_y_bp__dia__r03_001
  - ph_y_bp__dia__r03_002
- *Excluded values:* none

Usage

```
vars_ph_y_bp__dia

compute_ph_y_bp__dia_mean(data, name = "ph_y_bp__dia_mean", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_ph_y_bp__dia is a character vector of all column names used to compute summary scores of ph_y_bp__dia.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_bp__dia_mean(data) |>
  select(
    all_of(c("ph_y_bp__dia_mean", vars_ph_y_bp__dia))
  )

## End(Not run)
```

`vars_ph_y_bp__hrate` *Compute "Blood Pressure [Youth] (Heart rate): Mean"*

Description

Computes the summary score `ph_y_bp__hrate_mean` Blood Pressure [Youth] (Heart rate): Mean

- *Summarized variables:*
  - `ph_y_bp__hrate__r01_001`
  - `ph_y_bp__hrate__r01_002`
  - `ph_y_bp__hrate__r01_003`
  - `ph_y_bp__hrate__r02_001`
  - `ph_y_bp__hrate__r02_002`
  - `ph_y_bp__hrate__r03_001`
  - `ph_y_bp__hrate__r03_002`
- *Excluded values:* none

Usage

```
vars_ph_y_bp__hrate

compute_ph_y_bp__hrate_mean(data, name = "ph_y_bp__hrate_mean", combine = TRUE)
```

Arguments

`data`	tbl, Dataframe containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE`, the summary score will be appended to the input data frame. If `FALSE`, the summary score will be returned as a separate data frame.

Format

vars_ph_y_bp__hrate is a character vector of all column names used to compute summary scores of `ph_y_bp__hrate`.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_bp__hrate_mean(data) |>
  select(
    all_of(c("ph_y_bp__hrate_mean", vars_ph_y_bp__hrate))
  )

## End(Not run)
```

---

vars_ph_y_bp__sys *Compute "Blood Pressure [Youth] (Systolic): Mean"*

Description

Computes the summary score ph_y_bp__sys_mean Blood Pressure [Youth] (Systolic): Mean

- *Summarized variables:*
  - ph_y_bp__sys__r01_001
  - ph_y_bp__sys__r01_002
  - ph_y_bp__sys__r01_003
  - ph_y_bp__sys__r02_001
  - ph_y_bp__sys__r02_002
  - ph_y_bp__sys__r03_001
  - ph_y_bp__sys__r03_002
- *Excluded values:* none

Usage

```
vars_ph_y_bp__sys

compute_ph_y_bp__sys_mean(data, name = "ph_y_bp__sys_mean", combine = TRUE)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_ph_y_bp__sys is a character vector of all column names used to compute summary scores of ph_y_bp__sys.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_ph_y_bp__sys_mean(data) |>
  select(
    all_of(c("ph_y_bp__sys_mean", vars_ph_y_bp__sys))
  )

## End(Not run)
```

---

vars_ph_y_pds__f — *Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Female): Mean"*

Description

Computes the summary score ph_y_pds__f_mean Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Female): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - ph_y_pds_001
  - ph_y_pds_002
  - ph_y_pds_003
  - ph_y_pds__f_001
  - ph_y_pds__f_002
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 item missing

Usage

```
vars_ph_y_pds__f

compute_ph_y_pds__f_mean(
  data,
  name = "ph_y_pds__f_mean",
  exclude = c("777", "999"),
```

```
  combine = TRUE,
  max_na = 1
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.

Format

vars_ph_y_pds__f is a character vector of all column names used to compute summary score of ph_y_pds__f_mean and ph_y_pds__f_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_y_pds__f_categ

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Female): Approximate tanner stages"

Description

Computes the summary score ph_y_pds__f_categ Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Female): Approximate tanner stages [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_y_pds_002
  - ph_y_pds__f_001
  - ph_y_pds__f_002
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_y_pds__f_categ

compute_ph_y_pds__f_categ(
  data,
  name = "ph_y_pds__f_categ",
  exclude = c("777", "999"),
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.

Format

vars_ph_y_pds__f is a character vector of all column names used to compute summary score of ph_y_pds__f_categ and ph_y_pds__f__categ_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_ph_y_pds__m *Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Male): Mean"*

Description

Computes the summary score ph_y_pds__m_mean Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Male): Mean [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - ph_y_pds_001
  - ph_y_pds_002
  - ph_y_pds_003
  - ph_y_pds__m_001

  - ph_y_pds__m_002

- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 1 item missing

Usage

```
vars_ph_y_pds__m

compute_ph_y_pds__m_mean(
  data,
  name = "ph_y_pds__m_mean",
  combine = TRUE,
  exclude = c("777", "999"),
  max_na = 1
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.
exclude	character vector. Values to be excluded from the summary score calculation.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.

Format

vars_ph_y_pds__m is a character vector of all column names used to compute summary score of ph_y_pds__m_mean and ph_y_pds__m_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_ph_y_pds__m_categ

Compute "Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Male): Approximate tanner stages"

Description

Computes the summary score ph_y_pds__m_categ Pubertal Development Scale & Menstrual Cycle Survey History [Youth] (Male): Approximate tanner stages [Validation: No more than 0 missing or declined]

- *Summarized variables:*
  - ph_y_pds_002
  - ph_y_pds__m_001
  - ph_y_pds__m_002
- *Excluded values:*
  - 777
  - 999
- *Validation criterion:* maximally 0 items missing

Usage

```
vars_ph_y_pds__m_categ

compute_ph_y_pds__m_categ(
  data,
  name = "ph_y_pds__m_categ",
  combine = TRUE,
  exclude = c("777", "999"),
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.
exclude	character vector. Values to be excluded from the summary score calculation.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.

Format

vars_ph_y_pds__m is a character vector of all column names used to compute summary score of ph_y_pds__m_categ and ph_y_pds__m__categ_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_su_p_ksads__aud__past__sx`

Compute "KSADS - Alcohol Use Disorder [Parent] (Symptom - Past): Mean"

Description

Computes the summary score su_p_ksads__aud__past__sx_mean KSADS - Alcohol Use Disorder [Parent] (Symptom - Past): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - su_p_ksads__aud__actvdecr__past_sx
  - su_p_ksads__aud__crave__past_sx
  - su_p_ksads__aud__dwi__past_sx
  - su_p_ksads__aud__failrespons__past_sx
  - su_p_ksads__aud__haz__past_sx
  - su_p_ksads__aud__negimpct__interprs__past_sx
  - su_p_ksads__aud__overuse__past_sx
  - su_p_ksads__aud__prob__phys__past_sx
  - su_p_ksads__aud__prob__psych__past_sx
  - su_p_ksads__aud__reduce__dsr__past_sx
  - su_p_ksads__aud__reduce__unsucces__past_sx
  - su_p_ksads__aud__time__past_sx
  - su_p_ksads__aud__tol__past_sx
  - su_p_ksads__aud__withdr__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_su_p_ksads__aud__past__sx

compute_su_p_ksads__aud__past__sx_mean(
  data,
  name = "su_p_ksads__aud__past__sx_mean",
```

```
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__aud__past__sx is a character vector of all column names used to compute summary score of su_p_ksads__aud__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__aud__pres__sx

Compute "KSADS - Alcohol Use Disorder [Parent] (Symptom - Present): Mean"

Description

Computes the summary score `su_p_ksads__aud__pres__sx_mean` KSADS - Alcohol Use Disorder [Parent] (Symptom - Present): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `su_p_ksads__aud__actvdecr__pres_sx`
  - `su_p_ksads__aud__crave__pres_sx`
  - `su_p_ksads__aud__dwi__pres_sx`
  - `su_p_ksads__aud__failrespons__pres_sx`
  - `su_p_ksads__aud__haz__pres_sx`
  - `su_p_ksads__aud__negimpct__interprs__pres_sx`
  - `su_p_ksads__aud__overuse__pres_sx`
  - `su_p_ksads__aud__prob__phys__pres_sx`
  - `su_p_ksads__aud__prob__psych__pres_sx`
  - `su_p_ksads__aud__reduce__dsr__pres_sx`
  - `su_p_ksads__aud__reduce__unsucces__pres_sx`
  - `su_p_ksads__aud__time__pres_sx`
  - `su_p_ksads__aud__tol__pres_sx`
  - `su_p_ksads__aud__withdr__pres_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_su_p_ksads__aud__pres__sx

compute_su_p_ksads__aud__pres__sx_mean(
  data,
  name = "su_p_ksads__aud__pres__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the summary score column.
`max_na`	numeric, positive whole number. Number of missing items allowed. `NULL` means no limit.
`exclude`	character vector. Values to be excluded from the summary score calculation.
`combine`	logical. If `TRUE` (default), the summary score is is appended as a new column to the input data frame. If `FALSE`, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__aud__pres__sx is a character vector of all column names used to compute summary score of `su_p_ksads__aud__pres__sx_mean`

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

---

vars_su_p_ksads__dud__coc__past__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Cocaine - Past): Mean"

Description

Computes the summary score `su_p_ksads__dud__coc__past__sx_mean` KSADS - Drug Use Disorders [Parent] (Symptom: Cocaine - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - `su_p_ksads__dud__actvdecr__coc__past_sx`
  - `su_p_ksads__dud__crave__coc__past_sx`
  - `su_p_ksads__dud__dwi__coc__past_sx`
  - `su_p_ksads__dud__failrespons__coc__past_sx`
  - `su_p_ksads__dud__haz__coc__past_sx`
  - `su_p_ksads__dud__negimpct__interprs__coc__past_sx`
  - `su_p_ksads__dud__negimpct__obl__coc__past_sx`
  - `su_p_ksads__dud__overuse__coc__past_sx`
  - `su_p_ksads__dud__prob__phys__coc__past_sx`
  - `su_p_ksads__dud__prob__psych__coc__past_sx`
  - `su_p_ksads__dud__reduce__dsr__coc__past_sx`
  - `su_p_ksads__dud__reduce__unsucces__coc__past_sx`
  - `su_p_ksads__dud__time__coc__past_sx`
  - `su_p_ksads__dud__tol__coc__past_sx`

  - su_p_ksads__dud__withdr__coc__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__coc__past__sx_mean

compute_su_p_ksads__dud__coc__past__sx_mean(
  data,
  name = "su_p_ksads__dud__coc__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__coc__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__coc__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_p_ksads__dud__coc__pres__sx_mean
Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Cocaine - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__coc__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Cocaine - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__coc__pres_sx
  - su_p_ksads__dud__crave__coc__pres_sx
  - su_p_ksads__dud__dwi__coc__pres_sx
  - su_p_ksads__dud__failrespons__coc__pres_sx
  - su_p_ksads__dud__haz__coc__pres_sx
  - su_p_ksads__dud__negimpct__interprs__coc__pres_sx
  - su_p_ksads__dud__negimpct__obl__coc__pres_sx
  - su_p_ksads__dud__overuse__coc__pres_sx
  - su_p_ksads__dud__prob__phys__coc__pres_sx
  - su_p_ksads__dud__prob__psych__coc__pres_sx
  - su_p_ksads__dud__reduce__dsr__coc__pres_sx
  - su_p_ksads__dud__reduce__unsucces__coc__pres_sx
  - su_p_ksads__dud__time__coc__pres_sx
  - su_p_ksads__dud__tol__coc__pres_sx
  - su_p_ksads__dud__withdr__coc__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__coc__pres__sx_mean

compute_su_p_ksads__dud__coc__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__coc__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__coc__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__coc__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__hall__past__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Hallucinogen - Past): Mean"

Description

Computes the summary score su_p_ksads__dud__hall__past__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Hallucinogen - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__hall__past_sx
  - su_p_ksads__dud__crave__hall__past_sx
  - su_p_ksads__dud__dwi__hall__past_sx

  - su_p_ksads__dud__failrespons__hall__past_sx
  - su_p_ksads__dud__haz__hall__past_sx
  - su_p_ksads__dud__negimpct__interprs__hall__past_sx
  - su_p_ksads__dud__negimpct__obl__hall__past_sx
  - su_p_ksads__dud__overuse__hall__past_sx
  - su_p_ksads__dud__prob__phys__hall__past_sx
  - su_p_ksads__dud__prob__psych__hall__past_sx
  - su_p_ksads__dud__reduce__dsr__hall__past_sx
  - su_p_ksads__dud__reduce__unsucces__hall__past_sx
  - su_p_ksads__dud__time__hall__past_sx
  - su_p_ksads__dud__tol__hall__past_sx
  - su_p_ksads__dud__withdr__hall__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__hall__past__sx_mean

compute_su_p_ksads__dud__hall__past__sx_mean(
  data,
  name = "su_p_ksads__dud__hall__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__hall__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__hall__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__hall__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Hallucinogen - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__hall__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Hallucinogen - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__hall__pres_sx
  - su_p_ksads__dud__crave__hall__pres_sx
  - su_p_ksads__dud__dwi__hall__pres_sx
  - su_p_ksads__dud__failrespons__hall__pres_sx
  - su_p_ksads__dud__haz__hall__pres_sx
  - su_p_ksads__dud__negimpct__interprs__hall__pres_sx
  - su_p_ksads__dud__negimpct__obl__hall__pres_sx
  - su_p_ksads__dud__overuse__hall__pres_sx
  - su_p_ksads__dud__prob__phys__hall__pres_sx
  - su_p_ksads__dud__prob__psych__hall__pres_sx
  - su_p_ksads__dud__reduce__dsr__hall__pres_sx
  - su_p_ksads__dud__reduce__unsucces__hall__pres_sx
  - su_p_ksads__dud__time__hall__pres_sx
  - su_p_ksads__dud__tol__hall__pres_sx
  - su_p_ksads__dud__withdr__hall__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__hall__pres__sx_mean

compute_su_p_ksads__dud__hall__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__hall__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__hall__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__hall__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_p_ksads__dud__mj__past__sx_mean
Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Cannabis - Past): Mean"

Description

Computes the summary score su_p_ksads__dud__mj__past__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Cannabis - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__mj__past_sx
  - su_p_ksads__dud__crave__mj__past_sx
  - su_p_ksads__dud__dwi__mj__past_sx
  - su_p_ksads__dud__failrespons__mj__past_sx
  - su_p_ksads__dud__haz__mj__past_sx
  - su_p_ksads__dud__negimpct__interprs__mj__past_sx
  - su_p_ksads__dud__negimpct__obl__mj__past_sx
  - su_p_ksads__dud__overuse__mj__past_sx
  - su_p_ksads__dud__prob__phys__mj__past_sx
  - su_p_ksads__dud__prob__psych__mj__past_sx
  - su_p_ksads__dud__reduce__dsr__mj__past_sx
  - su_p_ksads__dud__reduce__unsucces__mj__past_sx
  - su_p_ksads__dud__time__mj__past_sx
  - su_p_ksads__dud__tol__mj__past_sx
  - su_p_ksads__dud__withdr__mj__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__mj__past__sx_mean

compute_su_p_ksads__dud__mj__past__sx_mean(
  data,
  name = "su_p_ksads__dud__mj__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__mj__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__mj__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__mj__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Cannabis - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__mj__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Cannabis - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__mj__pres_sx
  - su_p_ksads__dud__crave__mj__pres_sx
  - su_p_ksads__dud__dwi__mj__pres_sx

  - su_p_ksads__dud__failrespons__mj__pres_sx
  - su_p_ksads__dud__haz__mj__pres_sx
  - su_p_ksads__dud__negimpct__interprs__mj__pres_sx
  - su_p_ksads__dud__negimpct__obl__mj__pres_sx
  - su_p_ksads__dud__overuse__mj__pres_sx
  - su_p_ksads__dud__prob__phys__mj__pres_sx
  - su_p_ksads__dud__prob__psych__mj__pres_sx
  - su_p_ksads__dud__reduce__dsr__mj__pres_sx
  - su_p_ksads__dud__reduce__unsucces__mj__pres_sx
  - su_p_ksads__dud__time__mj__pres_sx
  - su_p_ksads__dud__tol__mj__pres_sx
  - su_p_ksads__dud__withdr__mj__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__mj__pres__sx_mean

compute_su_p_ksads__dud__mj__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__mj__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__mj__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__mj__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

---

vars_su_p_ksads__dud__nic__past__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Tobacco - Past): Mean"

Description

Computes the summary score `su_p_ksads__dud__nic__past__sx_mean` KSADS - Drug Use Disorders [Parent] (Symptom: Tobacco - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - `su_p_ksads__dud__actvdecr__nic__past_sx`
  - `su_p_ksads__dud__crave__nic__past_sx`
  - `su_p_ksads__dud__dwi__nic__past_sx`
  - `su_p_ksads__dud__failrespons__nic__past_sx`
  - `su_p_ksads__dud__haz__nic__past_sx`
  - `su_p_ksads__dud__negimpct__interprs__nic__past_sx`
  - `su_p_ksads__dud__negimpct__obl__nic__past_sx`
  - `su_p_ksads__dud__overuse__nic__past_sx`
  - `su_p_ksads__dud__prob__phys__nic__past_sx`
  - `su_p_ksads__dud__prob__psych__nic__past_sx`
  - `su_p_ksads__dud__reduce__dsr__nic__past_sx`
  - `su_p_ksads__dud__reduce__unsucces__nic__past_sx`
  - `su_p_ksads__dud__time__nic__past_sx`
  - `su_p_ksads__dud__tol__nic__past_sx`
  - `su_p_ksads__dud__withdr__nic__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__nic__past__sx_mean

compute_su_p_ksads__dud__nic__past__sx_mean(
  data,
  name = "su_p_ksads__dud__nic__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__nic__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__nic__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_p_ksads__dud__nic__pres__sx_mean
Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Tobacco - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__nic__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Tobacco - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__nic__pres_sx
  - su_p_ksads__dud__crave__nic__pres_sx
  - su_p_ksads__dud__dwi__nic__pres_sx
  - su_p_ksads__dud__failrespons__nic__pres_sx
  - su_p_ksads__dud__haz__nic__pres_sx
  - su_p_ksads__dud__negimpct__interprs__nic__pres_sx
  - su_p_ksads__dud__negimpct__obl__nic__pres_sx
  - su_p_ksads__dud__overuse__nic__pres_sx
  - su_p_ksads__dud__prob__phys__nic__pres_sx
  - su_p_ksads__dud__prob__psych__nic__pres_sx
  - su_p_ksads__dud__reduce__dsr__nic__pres_sx
  - su_p_ksads__dud__reduce__unsucces__nic__pres_sx
  - su_p_ksads__dud__time__nic__pres_sx
  - su_p_ksads__dud__tol__nic__pres_sx
  - su_p_ksads__dud__withdr__nic__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__nic__pres__sx_mean

compute_su_p_ksads__dud__nic__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__nic__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__nic__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__nic__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__opi__past__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Opiod - Past): Mean"

Description

Computes the summary score su_p_ksads__dud__opi__past__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Opiod - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__opi__past_sx
  - su_p_ksads__dud__crave__opi__past_sx
  - su_p_ksads__dud__dwi__opi__past_sx
  - su_p_ksads__dud__failrespons__opi__past_sx

  - su_p_ksads__dud__haz__opi__past_sx
  - su_p_ksads__dud__negimpct__interprs__opi__past_sx
  - su_p_ksads__dud__negimpct__obl__opi__past_sx
  - su_p_ksads__dud__overuse__opi__past_sx
  - su_p_ksads__dud__prob__phys__opi__past_sx
  - su_p_ksads__dud__prob__psych__opi__past_sx
  - su_p_ksads__dud__reduce__dsr__opi__past_sx
  - su_p_ksads__dud__reduce__unsucces__opi__past_sx
  - su_p_ksads__dud__time__opi__past_sx
  - su_p_ksads__dud__tol__opi__past_sx
  - su_p_ksads__dud__withdr__opi__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__opi__past__sx_mean

compute_su_p_ksads__dud__opi__past__sx_mean(
  data,
  name = "su_p_ksads__dud__opi__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__opi__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__opi__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__opi__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Opiod - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__opi__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Opiod - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__opi__pres_sx
  - su_p_ksads__dud__crave__opi__pres_sx
  - su_p_ksads__dud__dwi__opi__pres_sx
  - su_p_ksads__dud__failrespons__opi__pres_sx
  - su_p_ksads__dud__haz__opi__pres_sx
  - su_p_ksads__dud__negimpct__interprs__opi__pres_sx
  - su_p_ksads__dud__negimpct__obl__opi__pres_sx
  - su_p_ksads__dud__overuse__opi__pres_sx
  - su_p_ksads__dud__prob__phys__opi__pres_sx
  - su_p_ksads__dud__prob__psych__opi__pres_sx
  - su_p_ksads__dud__reduce__dsr__opi__pres_sx
  - su_p_ksads__dud__reduce__unsucces__opi__pres_sx
  - su_p_ksads__dud__time__opi__pres_sx
  - su_p_ksads__dud__tol__opi__pres_sx
  - su_p_ksads__dud__withdr__opi__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__opi__pres__sx_mean

compute_su_p_ksads__dud__opi__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__opi__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__opi__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__opi__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_p_ksads__dud__othdrg__past__sx_mean
Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Other drugs - Past): Mean"

Description

Computes the summary score su_p_ksads__dud__othdrg__past__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Other drugs - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__othdrg__past_sx
  - su_p_ksads__dud__crave__othdrg__past_sx
  - su_p_ksads__dud__dwi__othdrg__past_sx
  - su_p_ksads__dud__failrespons__othdrg__past_sx
  - su_p_ksads__dud__haz__othdrg__past_sx
  - su_p_ksads__dud__negimpct__interprs__othdrg__past_sx
  - su_p_ksads__dud__negimpct__obl__othdrg__past_sx
  - su_p_ksads__dud__overuse__othdrg__past_sx
  - su_p_ksads__dud__prob__phys__othdrg__past_sx
  - su_p_ksads__dud__prob__psych__othdrg__past_sx
  - su_p_ksads__dud__reduce__dsr__othdrg__past_sx
  - su_p_ksads__dud__reduce__unsucces__othdrg__past_sx
  - su_p_ksads__dud__time__othdrg__past_sx
  - su_p_ksads__dud__tol__othdrg__past_sx
  - su_p_ksads__dud__withdr__othdrg__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__othdrg__past__sx_mean

compute_su_p_ksads__dud__othdrg__past__sx_mean(
  data,
  name = "su_p_ksads__dud__othdrg__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__othdrg__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__othdrg__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__othdrg__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Other drugs - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__othdrg__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Other drugs - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__othdrg__pres_sx
  - su_p_ksads__dud__crave__othdrg__pres_sx
  - su_p_ksads__dud__dwi__othdrg__pres_sx

  - su_p_ksads__dud__failrespons__othdrg__pres_sx
  - su_p_ksads__dud__haz__othdrg__pres_sx
  - su_p_ksads__dud__negimpct__interprs__othdrg__pres_sx
  - su_p_ksads__dud__negimpct__obl__othdrg__pres_sx
  - su_p_ksads__dud__overuse__othdrg__pres_sx
  - su_p_ksads__dud__prob__phys__othdrg__pres_sx
  - su_p_ksads__dud__prob__psych__othdrg__pres_sx
  - su_p_ksads__dud__reduce__dsr__othdrg__pres_sx
  - su_p_ksads__dud__reduce__unsucces__othdrg__pres_sx
  - su_p_ksads__dud__time__othdrg__pres_sx
  - su_p_ksads__dud__tol__othdrg__pres_sx
  - su_p_ksads__dud__withdr__othdrg__pres_sx

- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__othdrg__pres__sx_mean

compute_su_p_ksads__dud__othdrg__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__othdrg__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__othdrg__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__othdrg__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

---

vars_su_p_ksads__dud__past__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom - Past): Mean"

Description

Computes the summary score `su_p_ksads__dud__past__sx_mean` KSADS - Drug Use Disorders [Parent] (Symptom - Past): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `su_p_ksads__dud__actvdecr__past_sx`
  - `su_p_ksads__dud__crave__past_sx`
  - `su_p_ksads__dud__dwi__past_sx`
  - `su_p_ksads__dud__failrespons__past_sx`
  - `su_p_ksads__dud__haz__past_sx`
  - `su_p_ksads__dud__negimpct__interprs__past_sx`
  - `su_p_ksads__dud__negimpct__obl__past_sx`
  - `su_p_ksads__dud__overuse__past_sx`
  - `su_p_ksads__dud__prob__phys__past_sx`
  - `su_p_ksads__dud__prob__psych__past_sx`
  - `su_p_ksads__dud__reduce__dsr__past_sx`
  - `su_p_ksads__dud__reduce__unsucces__past_sx`
  - `su_p_ksads__dud__tol__past_sx`
  - `su_p_ksads__dud__withdr__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_su_p_ksads__dud__past__sx_mean

compute_su_p_ksads__dud__past__sx_mean(
  data,
  name = "su_p_ksads__dud__past__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_p_ksads__dud__pcp__past__sx_mean
Compute "KSADS - Drug Use Disorders [Parent] (Symptom: PCP - Past): Mean"

Description

Computes the summary score su_p_ksads__dud__pcp__past__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: PCP - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__pcp__past_sx
  - su_p_ksads__dud__crave__pcp__past_sx
  - su_p_ksads__dud__dwi__pcp__past_sx
  - su_p_ksads__dud__failrespons__pcp__past_sx
  - su_p_ksads__dud__haz__pcp__past_sx
  - su_p_ksads__dud__negimpct__interprs__pcp__past_sx
  - su_p_ksads__dud__negimpct__obl__pcp__past_sx
  - su_p_ksads__dud__overuse__pcp__past_sx
  - su_p_ksads__dud__prob__phys__pcp__past_sx
  - su_p_ksads__dud__prob__psych__pcp__past_sx
  - su_p_ksads__dud__reduce__dsr__pcp__past_sx
  - su_p_ksads__dud__reduce__unsucces__pcp__past_sx
  - su_p_ksads__dud__time__pcp__past_sx
  - su_p_ksads__dud__tol__pcp__past_sx
  - su_p_ksads__dud__withdr__pcp__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__pcp__past__sx_mean

compute_su_p_ksads__dud__pcp__past__sx_mean(
  data,
  name = "su_p_ksads__dud__pcp__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__pcp__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__pcp__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__pcp__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: PCP - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__pcp__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: PCP - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__pcp__pres_sx
  - su_p_ksads__dud__crave__pcp__pres_sx
  - su_p_ksads__dud__dwi__pcp__pres_sx
  - su_p_ksads__dud__failrespons__pcp__pres_sx

  - su_p_ksads__dud__haz__pcp__pres_sx
  - su_p_ksads__dud__negimpct__interprs__pcp__pres_sx
  - su_p_ksads__dud__negimpct__obl__pcp__pres_sx
  - su_p_ksads__dud__overuse__pcp__pres_sx
  - su_p_ksads__dud__prob__phys__pcp__pres_sx
  - su_p_ksads__dud__prob__psych__pcp__pres_sx
  - su_p_ksads__dud__reduce__dsr__pcp__pres_sx
  - su_p_ksads__dud__reduce__unsucces__pcp__pres_sx
  - su_p_ksads__dud__time__pcp__pres_sx
  - su_p_ksads__dud__tol__pcp__pres_sx
  - su_p_ksads__dud__withdr__pcp__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__pcp__pres__sx_mean

compute_su_p_ksads__dud__pcp__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__pcp__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__pcp__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__pcp__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__pres__sx_mean *Compute "KSADS - Drug Use Disorders [Parent] (Symptom - Present): Mean"*

Description

Computes the summary score su_p_ksads__dud__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__pres_sx
  - su_p_ksads__dud__crave__pres_sx
  - su_p_ksads__dud__dwi__pres_sx
  - su_p_ksads__dud__failrespons__pres_sx
  - su_p_ksads__dud__haz__pres_sx
  - su_p_ksads__dud__negimpct__interprs__pres_sx
  - su_p_ksads__dud__negimpct__obl__pres_sx
  - su_p_ksads__dud__overuse__pres_sx
  - su_p_ksads__dud__prob__phys__pres_sx
  - su_p_ksads__dud__prob__psych__pres_sx
  - su_p_ksads__dud__reduce__dsr__pres_sx
  - su_p_ksads__dud__reduce__unsucces__pres_sx
  - su_p_ksads__dud__time__pres_sx
  - su_p_ksads__dud__tol__pres_sx
  - su_p_ksads__dud__withdr__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__pres__sx_mean

compute_su_p_ksads__dud__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_p_ksads__dud__sed__past__sx_mean
Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Sedatives - Past): Mean"

Description

Computes the summary score su_p_ksads__dud__sed__past__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Sedatives - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__sed__past_sx
  - su_p_ksads__dud__crave__sed__past_sx
  - su_p_ksads__dud__dwi__sed__past_sx
  - su_p_ksads__dud__failrespons__sed__past_sx
  - su_p_ksads__dud__haz__sed__past_sx
  - su_p_ksads__dud__negimpct__interprs__sed__past_sx
  - su_p_ksads__dud__negimpct__obl__sed__past_sx
  - su_p_ksads__dud__overuse__sed__past_sx
  - su_p_ksads__dud__prob__phys__sed__past_sx
  - su_p_ksads__dud__prob__psych__sed__past_sx
  - su_p_ksads__dud__reduce__dsr__sed__past_sx
  - su_p_ksads__dud__reduce__unsucces__sed__past_sx
  - su_p_ksads__dud__time__sed__past_sx
  - su_p_ksads__dud__tol__sed__past_sx
  - su_p_ksads__dud__withdr__sed__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__sed__past__sx_mean

compute_su_p_ksads__dud__sed__past__sx_mean(
  data,
  name = "su_p_ksads__dud__sed__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__sed__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__sed__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__sed__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Sedatives - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__sed__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Sedatives - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__sed__pres_sx
  - su_p_ksads__dud__crave__sed__pres_sx
  - su_p_ksads__dud__dwi__sed__pres_sx

  - su_p_ksads__dud__failrespons__sed__pres_sx
  - su_p_ksads__dud__haz__sed__pres_sx
  - su_p_ksads__dud__negimpct__interprs__sed__pres_sx
  - su_p_ksads__dud__negimpct__obl__sed__pres_sx
  - su_p_ksads__dud__overuse__sed__pres_sx
  - su_p_ksads__dud__prob__phys__sed__pres_sx
  - su_p_ksads__dud__prob__psych__sed__pres_sx
  - su_p_ksads__dud__reduce__dsr__sed__pres_sx
  - su_p_ksads__dud__reduce__unsucces__sed__pres_sx
  - su_p_ksads__dud__time__sed__pres_sx
  - su_p_ksads__dud__tol__sed__pres_sx
  - su_p_ksads__dud__withdr__sed__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__sed__pres__sx_mean

compute_su_p_ksads__dud__sed__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__sed__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__sed__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__sed__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__solv__past__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Solvent - Past): Mean"

Description

Computes the summary score su_p_ksads__dud__solv__past__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Solvent - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__solv__past_sx
  - su_p_ksads__dud__crave__solv__past_sx
  - su_p_ksads__dud__dwi__solv__past_sx
  - su_p_ksads__dud__failrespons__solv__past_sx
  - su_p_ksads__dud__haz__solv__past_sx
  - su_p_ksads__dud__negimpct__interprs__solv__past_sx
  - su_p_ksads__dud__negimpct__obl__solv__past_sx
  - su_p_ksads__dud__overuse__solv__past_sx
  - su_p_ksads__dud__prob__phys__solv__past_sx
  - su_p_ksads__dud__prob__psych__solv__past_sx
  - su_p_ksads__dud__reduce__dsr__solv__past_sx
  - su_p_ksads__dud__reduce__unsucces__solv__past_sx
  - su_p_ksads__dud__time__solv__past_sx
  - su_p_ksads__dud__tol__solv__past_sx
  - su_p_ksads__dud__withdr__solv__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__solv__past__sx_mean

compute_su_p_ksads__dud__solv__past__sx_mean(
  data,
  name = "su_p_ksads__dud__solv__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__solv__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__solv__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_p_ksads__dud__solv__pres__sx_mean
Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Solvent - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__solv__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Solvent - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__solv__pres_sx
  - su_p_ksads__dud__crave__solv__pres_sx
  - su_p_ksads__dud__dwi__solv__pres_sx
  - su_p_ksads__dud__failrespons__solv__pres_sx
  - su_p_ksads__dud__haz__solv__pres_sx
  - su_p_ksads__dud__negimpct__interprs__solv__pres_sx
  - su_p_ksads__dud__negimpct__obl__solv__pres_sx
  - su_p_ksads__dud__overuse__solv__pres_sx
  - su_p_ksads__dud__prob__phys__solv__pres_sx
  - su_p_ksads__dud__prob__psych__solv__pres_sx
  - su_p_ksads__dud__reduce__dsr__solv__pres_sx
  - su_p_ksads__dud__reduce__unsucces__solv__pres_sx
  - su_p_ksads__dud__time__solv__pres_sx
  - su_p_ksads__dud__tol__solv__pres_sx
  - su_p_ksads__dud__withdr__solv__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__solv__pres__sx_mean

compute_su_p_ksads__dud__solv__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__solv__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__solv__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__solv__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__stim__past__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Stimulants - Past): Mean"

Description

Computes the summary score su_p_ksads__dud__stim__past__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Stimulants - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__stim__past_sx
  - su_p_ksads__dud__crave__stim__past_sx
  - su_p_ksads__dud__dwi__stim__past_sx

  - su_p_ksads__dud__failrespons__stim__past_sx
  - su_p_ksads__dud__haz__stim__past_sx
  - su_p_ksads__dud__negimpct__interprs__stim__past_sx
  - su_p_ksads__dud__negimpct__obl__stim__past_sx
  - su_p_ksads__dud__overuse__stim__past_sx
  - su_p_ksads__dud__prob__phys__stim__past_sx
  - su_p_ksads__dud__prob__psych__stim__past_sx
  - su_p_ksads__dud__reduce__dsr__stim__past_sx
  - su_p_ksads__dud__reduce__unsucces__stim__past_sx
  - su_p_ksads__dud__time__stim__past_sx
  - su_p_ksads__dud__tol__stim__past_sx
  - su_p_ksads__dud__withdr__stim__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__stim__past__sx_mean

compute_su_p_ksads__dud__stim__past__sx_mean(
  data,
  name = "su_p_ksads__dud__stim__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__stim__past__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__stim__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_p_ksads__dud__stim__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Parent] (Symptom: Stimulants - Present): Mean"

Description

Computes the summary score su_p_ksads__dud__stim__pres__sx_mean KSADS - Drug Use Disorders [Parent] (Symptom: Stimulants - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_p_ksads__dud__actvdecr__stim__pres_sx
  - su_p_ksads__dud__crave__stim__pres_sx
  - su_p_ksads__dud__dwi__stim__pres_sx
  - su_p_ksads__dud__failrespons__stim__pres_sx
  - su_p_ksads__dud__haz__stim__pres_sx
  - su_p_ksads__dud__negimpct__interprs__stim__pres_sx
  - su_p_ksads__dud__negimpct__obl__stim__pres_sx
  - su_p_ksads__dud__overuse__stim__pres_sx
  - su_p_ksads__dud__prob__phys__stim__pres_sx
  - su_p_ksads__dud__prob__psych__stim__pres_sx
  - su_p_ksads__dud__reduce__dsr__stim__pres_sx
  - su_p_ksads__dud__reduce__unsucces__stim__pres_sx
  - su_p_ksads__dud__time__stim__pres_sx
  - su_p_ksads__dud__tol__stim__pres_sx
  - su_p_ksads__dud__withdr__stim__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_p_ksads__dud__stim__pres__sx_mean

compute_su_p_ksads__dud__stim__pres__sx_mean(
  data,
  name = "su_p_ksads__dud__stim__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_p_ksads__dud__stim__pres__sx_mean is a character vector of all column names used to compute summary score of su_p_ksads__dud__stim__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_y_alcexp__neg *Compute "Alcohol Expectancies (AEQ-AB) [Youth] (Strength of negative expectancies): Prorated sum"*

Description

Computes the summary score su_y_alcexp__neg_prsum Alcohol Expectancies (AEQ-AB) [Youth] (Strength of negative expectancies): Prorated sum

- *Summarized variables:*
  - su_y_alcexp__neg_001
  - su_y_alcexp__neg_002
  - su_y_alcexp__neg_003
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 3 items missing

Usage

```
vars_su_y_alcexp__neg

compute_su_y_alcexp__neg_prsum(
  data,
  name = "su_y_alcexp__neg_prsum",
  combine = TRUE,
  max_na = 1
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_alcexp__neg is a character vector of all column names used to compute summary score of su_y_alcexp__neg_prsum and su_y_alcexp__neg_nm

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_alcexp__pos *Compute "Alcohol Expectancies (AEQ-AB) [Youth] (Strength of positive expectancies): Prorated sum"*

Description

Computes the summary score su_y_alcexp__pos_prsum Alcohol Expectancies (AEQ-AB) [Youth] (Strength of positive expectancies): Prorated sum

- *Summarized variables:*
  - su_y_alcexp__pos_001
  - su_y_alcexp__pos_002
  - su_y_alcexp__pos_003
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 3 items missing

Usage

```
vars_su_y_alcexp__pos

compute_su_y_alcexp__pos_prsum(
  data,
  name = "su_y_alcexp__pos_prsum",
  combine = TRUE,
  max_na = 1
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_alcexp__pos is a character vector of all column names used to compute summary score of su_y_alcexp__pos_prsum and su_y_alcexp__pos_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_alchss *Compute "Alcohol Hangover Symptoms Scale (HSS) [Youth]: Sum"*

Description

Computes the summary score `su_y_alchss_sum` Alcohol Hangover Symptoms Scale (HSS) [Youth]: Sum

- *Summarized variables:*
  - `su_y_alchss_001`
  - `su_y_alchss_002`
  - `su_y_alchss_003`
  - `su_y_alchss_004`
  - `su_y_alchss_005`
  - `su_y_alchss_006`
  - `su_y_alchss_007`
  - `su_y_alchss_008`
  - `su_y_alchss_009`
  - `su_y_alchss_010`
  - `su_y_alchss_011`
  - `su_y_alchss_012`
  - `su_y_alchss_013`
  - `su_y_alchss_014`
  - `su_y_alchss_001__l`
  - `su_y_alchss_002__l`
  - `su_y_alchss_003__l`
  - `su_y_alchss_004__l`
  - `su_y_alchss_005__l`
  - `su_y_alchss_006__l`
  - `su_y_alchss_007__l`
  - `su_y_alchss_008__l`
  - `su_y_alchss_009__l`
  - `su_y_alchss_010__l`
  - `su_y_alchss_011__l`
  - `su_y_alchss_012__l`
  - `su_y_alchss_013__l`
  - `su_y_alchss_014__l`
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_su_y_alchss

compute_su_y_alchss_sum(
  data,
  name = "su_y_alchss_sum",
  max_na = 0,
  combine = TRUE
)
```

Arguments

data	tbl, Dataframe containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
max_na	integer, Maximum number of missing values allowed in the summary score.
combine	logical, If TRUE, the summary score will be appended to the input data frame. If FALSE, the summary score will be returned as a separate data frame.

Format

vars_su_y_alchss is a table of all column names used to compute summary score of su_y_alchss.

Value

tbl. The input data frame with the summary score appended as a new column.

Examples

```
## Not run:
compute_su_y_alchss_sum(data)

## End(Not run)
```

---

vars_su_y_alcprob *Compute "Alcohol Problem Index (RAPI) [Youth]: Prorated sum"*

Description

Computes the summary score su_y_alcprob_prsum Alcohol Problem Index (RAPI) [Youth]: Prorated sum [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - su_y_alcprob_001
  - su_y_alcprob_002
  - su_y_alcprob_003

- su_y_alcprob_004
- su_y_alcprob_005
- su_y_alcprob_006
- su_y_alcprob_007
- su_y_alcprob_008
- su_y_alcprob_009
- su_y_alcprob_010
- su_y_alcprob_012
- su_y_alcprob_016
- su_y_alcprob_017
- su_y_alcprob_018
- su_y_alcprob_001__l
- su_y_alcprob_002__l
- su_y_alcprob_003__l
- su_y_alcprob_004__l
- su_y_alcprob_005__l
- su_y_alcprob_006__l
- su_y_alcprob_007__l
- su_y_alcprob_008__l
- su_y_alcprob_009__l
- su_y_alcprob_010__l
- su_y_alcprob_012__l
- su_y_alcprob_016__l
- su_y_alcprob_017__l
- su_y_alcprob_018__l

- *Excluded values:* none
- *Validation criterion:* maximally 2 items missing

Usage

```
vars_su_y_alcprob

compute_su_y_alcprob_prsum(
  data,
  name = "su_y_alcprob_prsum",
  combine = TRUE,
  max_na = 2
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.

combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_alcprob is a table with pairs of baseline and longitudinal redcap fields used to compute summary score of su_y_alcprob_prsum and su_y_alcprob_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_alcsre__6mo *Compute "Alcohol Subject Response and Effects [Youth] (Last 6 months): Mean [Validation: None missing or declined]"*

Description

Computes the summary score su_y_alcsre__6mo_mean Alcohol Subject Response and Effects [Youth] (Last 6 months): Mean [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_alcsre__6mo_001
  - su_y_alcsre__6mo_002
  - su_y_alcsre__6mo_003
  - su_y_alcsre__6mo_004
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_su_y_alcsre__6mo

compute_su_y_alcsre__6mo_mean(
  data,
  name = "su_y_alcsre__6mo_mean",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Format

vars_su_y_alcsre__6mo is a character vector of all column names used to compute summary scores of `compute_su_y_alcsre__6mo` (`_mean`, `_count`, `_nm`).

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_su_y_alcsre__first5`

Compute "Alcohol Subject Response and Effects [Youth] (First 5 times ever drank): Mean [Validation: None missing or declined]"

Description

Computes the summary score `su_y_alcsre__first5_mean` Alcohol Subject Response and Effects [Youth] (First 5 times ever drank): Mean [Validation: None missing or declined]

- *Summarized variables:*
  - `su_y_alcsre__first5_001`
  - `su_y_alcsre__first5_002`
  - `su_y_alcsre__first5_003`
  - `su_y_alcsre__first5_004`
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_su_y_alcsre__first5

compute_su_y_alcsre__first5_mean(
  data,
  name = "su_y_alcsre__first5_mean",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Format

vars_su_y_alcsre__first5 is a character vector of all column names used to compute summary scores of `compute_su_y_alcsre__first5` (`_mean`, `_count`, `_nm`).

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_alcsre__hvy *Compute "Alcohol Subject Response and Effects [Youth] (Heaviest drinking period): Mean [Validation: None missing or declined]"*

Description

Computes the summary score `su_y_alcsre__hvy_mean` Alcohol Subject Response and Effects [Youth] (Heaviest drinking period): Mean [Validation: None missing or declined]

- *Summarized variables:*
  - `su_y_alcsre__hvy_001`
  - `su_y_alcsre__hvy_002`
  - `su_y_alcsre__hvy_003`
  - `su_y_alcsre__hvy_004`
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 4 items missing

Usage

```
vars_su_y_alcsre__hvy

compute_su_y_alcsre__hvy_mean(
  data,
  name = "su_y_alcsre__hvy_mean",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Format

vars_su_y_alcsre__hvy is a character vector of all column names used to compute summary scores of compute_su_y_alcsre__hvy (_mean, _count, _nm).

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_caff__coffee

Compute "Caffeine Use Questionnaire [Youth] (Coffee): Sum [Validation: None]"

Description

Computes the summary score su_y_caff__coffee_sum Caffeine Use Questionnaire [Youth] (Coffee): Sum [Validation: None]

- *Summarized variables:*
  - su_y_caff__coffee_001
  - su_y_caff__coffee_001__01__01
  - su_y_caff__coffee_001__01__02
  - su_y_caff__coffee_001__01__03
  - su_y_caff__coffee_001__02__01
  - su_y_caff__coffee_001__02__02
  - su_y_caff__coffee_001__02__03
  - su_y_caff__coffee_001__03__01
  - su_y_caff__coffee_001__03__02
  - su_y_caff__coffee_001__03__03
  - su_y_caff__coffee_001__04__01
  - su_y_caff__coffee_001__04__02
  - su_y_caff__coffee_001__04__03
  - su_y_caff__coffee_001__l
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
vars_su_y_caff__coffee

compute_su_y_caff__coffee_sum(
  data,
  name = "su_y_caff__coffee_sum",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_su_y_caff__coffee is a character vector of all column names used to compute `compute_su_y_caff__coffee_sum`.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_caff__energy

Compute "Caffeine Use Questionnaire [Youth] (Energy): Sum [Validation: None]"

Description

Computes the summary score `su_y_caff__energy_sum` Caffeine Use Questionnaire [Youth] (Energy): Sum [Validation: None]

- *Summarized variables:*
  - `su_y_caff__energy_001`
  - `su_y_caff__energy_001__l`
  - `su_y_caff__energy__shot_001__01`
  - `su_y_caff__energy__shot_001__02`
  - `su_y_caff__energy__drink_001__01__01`
  - `su_y_caff__energy__drink_001__01__02`
  - `su_y_caff__energy__drink_001__01__03`
  - `su_y_caff__energy__drink_001__02__01`
  - `su_y_caff__energy__drink_001__02__02`

  - su_y_caff__energy__drink_001__02__03
  - su_y_caff__energy__drink_001__03__01
  - su_y_caff__energy__drink_001__03__02
  - su_y_caff__energy__drink_001__03__03
  - su_y_caff__energy__drink_001__04__01
  - su_y_caff__energy__drink_001__04__02
  - su_y_caff__energy__drink_001__04__03

- *Excluded values:* none
- *Validation criterion:* none

Usage

```
vars_su_y_caff__energy

compute_su_y_caff__energy_sum(
  data,
  name = "su_y_caff__energy_sum",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_su_y_caff__energy is a character vector of all column names used to compute `compute_su_y_caff__energy_sum`.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_caff__energy__drink

Compute "Caffeine Use Questionnaire [Youth] (Energy drink): Sum [Validation: None]"

Description

Computes the summary score su_y_caff__energy__drink_sum Caffeine Use Questionnaire [Youth] (Energy drink): Sum [Validation: None]

- *Summarized variables:*
  - su_y_caff__energy__drink_001__01__01
  - su_y_caff__energy__drink_001__01__02
  - su_y_caff__energy__drink_001__01__03
  - su_y_caff__energy__drink_001__02__01
  - su_y_caff__energy__drink_001__02__02
  - su_y_caff__energy__drink_001__02__03
  - su_y_caff__energy__drink_001__03__01
  - su_y_caff__energy__drink_001__03__02
  - su_y_caff__energy__drink_001__03__03
  - su_y_caff__energy__drink_001__04__01
  - su_y_caff__energy__drink_001__04__02
  - su_y_caff__energy__drink_001__04__03
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
vars_su_y_caff__energy__drink

compute_su_y_caff__energy__drink_sum(
  data,
  name = "su_y_caff__energy__drink_sum",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_su_y_caff__energy__drink is a character vector of all column names used to compute compute_su_y_caff__energy__

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_caff__energy__shot *Compute "Caffeine Use Questionnaire [Youth] (Energy shot): Sum [Validation: None]"*

Description

Computes the summary score su_y_caff__energy__shot_sum Caffeine Use Questionnaire [Youth] (Energy shot): Sum [Validation: None]

- *Summarized variables:*
  - su_y_caff__energy__shot_001__01
  - su_y_caff__energy__shot_001__02
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
vars_su_y_caff__energy__shot

compute_su_y_caff__energy__shot_sum(
  data,
  name = "su_y_caff__energy__shot_sum",
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_su_y_caff__energy__shot is a character vector of all column names used to compute compute_su_y_caff__energy__sh

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_caff__espres

Compute "Caffeine Use Questionnaire [Youth] (Espresso): Sum [Validation: None]"

Description

Computes the summary score `su_y_caff__espres_sum` Caffeine Use Questionnaire [Youth] (Espresso): Sum [Validation: None]

- *Summarized variables:*
  - `su_y_caff__espres_001`
  - `su_y_caff__espres_001__01`
  - `su_y_caff__espres_001__02`
  - `su_y_caff__espres_001__l`
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
vars_su_y_caff__espres

compute_su_y_caff__espres_sum(
  data,
  name = "su_y_caff__espres_sum",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_su_y_caff__espres is a character vector of all column names used to compute `compute_su_y_caff__espres_sum`.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_caff__oth *Compute "Caffeine Use Questionnaire [Youth] (Other): Sum [Validation: None]"*

Description

Computes the summary score su_y_caff__oth_sum Caffeine Use Questionnaire [Youth] (Other): Sum [Validation: None]

- *Summarized variables:*
  - su_y_caff__oth_001__01
  - su_y_caff__oth_001__02
  - su_y_caff__oth_001__l
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
vars_su_y_caff__oth

compute_su_y_caff__oth_sum(data, name = "su_y_caff__oth_sum", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_su_y_caff__oth is a character vector of all column names used to compute compute_su_y_caff__oth_sum.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_caff__soda *Compute "Caffeine Use Questionnaire [Youth] (Soda): Sum [Validation: None]"*

Description

Computes the summary score su_y_caff__soda_sum Caffeine Use Questionnaire [Youth] (Soda) : Sum [Validation: None]

- *Summarized variables:*
  - su_y_caff__soda_001
  - su_y_caff__soda_001__01__01
  - su_y_caff__soda_001__01__02
  - su_y_caff__soda_001__01__03
  - su_y_caff__soda_001__02__01
  - su_y_caff__soda_001__02__02
  - su_y_caff__soda_001__02__03
  - su_y_caff__soda_001__03__01
  - su_y_caff__soda_001__03__02
  - su_y_caff__soda_001__03__03
  - su_y_caff__soda_001__04__01
  - su_y_caff__soda_001__04__02
  - su_y_caff__soda_001__04__03
  - su_y_caff__soda_001__l
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
vars_su_y_caff__soda

compute_su_y_caff__soda_sum(data, name = "su_y_caff__soda_sum", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_su_y_caff__soda is a character vector of all column names used to compute compute_su_y_caff__soda_sum.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_su_y_caff__suppl` *Compute "Caffeine Use Questionnaire [Youth] (Caffeine supplements): Sum [Validation: None]"*

Description

Computes the summary score `su_y_caff__suppl_sum` Caffeine Use Questionnaire [Youth] (Caffeine supplements): Sum [Validation: None]

- *Summarized variables:*
  - `su_y_caff__suppl_001__01__01`
  - `su_y_caff__suppl_001__01__02`
  - `su_y_caff__suppl_001__02__01`
  - `su_y_caff__suppl_001__02__02`
  - `su_y_caff__suppl_001__03__01`
  - `su_y_caff__suppl_001__03__02`
  - `su_y_caff__suppl_001__04__01`
  - `su_y_caff__suppl_001__04__02`
  - `su_y_caff__suppl_001__l`
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
vars_su_y_caff__suppl

compute_su_y_caff__suppl_sum(
  data,
  name = "su_y_caff__suppl_sum",
  combine = TRUE
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character. Name of the new column to be created (Default: the name used in the ABCD data release).
`combine`	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_su_y_caff__suppl is a character vector of all column names used to compute `compute_su_y_caff__suppl_sum`.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_su_y_caff__tea` *Compute "Caffeine Use Questionnaire [Youth] (Tea) : Sum [Validation: None]"*

Description

Computes the summary score `su_y_caff__tea_sum` Caffeine Use Questionnaire [Youth] (Tea) : Sum [Validation: None]

- *Summarized variables:*
  - `su_y_caff__tea_001`
  - `su_y_caff__tea_001__01__01`
  - `su_y_caff__tea_001__01__02`
  - `su_y_caff__tea_001__01__03`
  - `su_y_caff__tea_001__02__01`
  - `su_y_caff__tea_001__02__02`
  - `su_y_caff__tea_001__02__03`
  - `su_y_caff__tea_001__03__01`
  - `su_y_caff__tea_001__03__02`
  - `su_y_caff__tea_001__03__03`
  - `su_y_caff__tea_001__04__01`
  - `su_y_caff__tea_001__04__02`
  - `su_y_caff__tea_001__04__03`
  - `su_y_caff__tea_001__l`
- *Excluded values:* none
- *Validation criterion:* none

Usage

```
vars_su_y_caff__tea

compute_su_y_caff__tea_sum(data, name = "su_y_caff__tea_sum", combine = TRUE)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.

Format

vars_su_y_caff__tea is a character vector of all column names used to compute `compute_su_y_caff__tea_sum`.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_cigexp__neg *Compute "Cigarette Expectancies (ASCQ) [Youth] (Strength of negative expectancies): Prorated sum"*

Description

Computes the summary score `su_y_cigexp__neg_prsum` Cigarette Expectancies (ASCQ) [Youth] (Strength of negative expectancies): Prorated sum [Validation: No more than 0 missing or declined]

Note: all 0s are changed to NAs prior to calculating pro-rated sum

- *Summarized variables:*
  - `su_y_cigexp__neg_001`
  - `su_y_cigexp__neg_002`
- *Excluded values:*
  - 0
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_su_y_cigexp__neg

compute_su_y_cigexp__neg_prsum(
  data,
  name = "su_y_cigexp__neg_prsum",
  combine = TRUE,
  exclude = c("0"),
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
exclude	character vector. Values to be excluded from the summary score calculation.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_cigexp__neg is a character vector of all column names used to compute summary score of su_y_cigexp__neg_prsum and su_y_cigexp__neg_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_cigexp__pos *Compute "Cigarette Expectancies (ASCQ) [Youth] (Strength of positive expectancies): Prorated sum"*

Description

Computes the summary score su_y_cigexp__pos_prsum Cigarette Expectancies (ASCQ) [Youth] (Strength of positive expectancies): Prorated sum

Note: all 0s are changed to NAs prior to calculating pro-rated sum

- *Summarized variables:*
  - su_y_cigexp__pos_001
  - su_y_cigexp__pos_002
  - su_y_cigexp__pos_003
  - su_y_cigexp__pos_004
- *Excluded values:*
  - 0
- *Validation criterion:* maximally 2 of 4 items missing

Usage

```
vars_su_y_cigexp__pos

compute_su_y_cigexp__pos_prsum(
  data,
  name = "su_y_cigexp__pos_prsum",
  combine = TRUE,
  exclude = c("0"),
  max_na = 2
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
exclude	character vector. Values to be excluded from the summary score calculation.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_cigexp__pos is a character vector of all column names used to compute summary score of su_y_cigexp__pos_prsum and su_y_cigexp__pos_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_drgprob *Compute "Drug Problem Index (DAPI) [Youth]: Prorated sum"*

Description

Computes the summary score su_y_drgprob_prsum Drug Problem Index (DAPI) [Youth]: Prorated sum [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_drgprob_001
  - su_y_drgprob_002
  - su_y_drgprob_003
  - su_y_drgprob_004

  - su_y_drgprob_005
  - su_y_drgprob_006
  - su_y_drgprob_007
  - su_y_drgprob_008
  - su_y_drgprob_009
  - su_y_drgprob_010
  - su_y_drgprob_012
  - su_y_drgprob_013
  - su_y_drgprob_014
  - su_y_drgprob_015
  - su_y_drgprob_016
  - su_y_drgprob_017
  - su_y_drgprob_018
- *Excluded values:* none
- *Validation criterion:* maximally 3 items missing

Usage

```
vars_su_y_drgprob

compute_su_y_drgprob_prsum(
  data,
  name = "su_y_drgprob_prsum",
  combine = TRUE,
  max_na = 3
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_drgprob is a character vector of all column names used to compute summary score of su_y_drgprob_prsum and su_y_drgprob_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_ksads__aud__past__sx
Compute "KSADS - Alcohol Use Disorder [Youth] (Symptom - Past): Mean"

Description

Computes the summary score su_y_ksads__aud__past__sx_mean KSADS - Alcohol Use Disorder [Youth] (Symptom - Past): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - su_y_ksads__aud__actvdecr__past_sx
  - su_y_ksads__aud__crave__past_sx
  - su_y_ksads__aud__dwi__past_sx
  - su_y_ksads__aud__failrespons__past_sx
  - su_y_ksads__aud__haz__past_sx
  - su_y_ksads__aud__negimpct__interprs__past_sx
  - su_y_ksads__aud__overuse__past_sx
  - su_y_ksads__aud__prob__phys__past_sx
  - su_y_ksads__aud__prob__psych__past_sx
  - su_y_ksads__aud__reduce__dsr__past_sx
  - su_y_ksads__aud__reduce__unsucces__past_sx
  - su_y_ksads__aud__time__past_sx
  - su_y_ksads__aud__tol__past_sx
  - su_y_ksads__aud__withdr__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_su_y_ksads__aud__past__sx

compute_su_y_ksads__aud__past__sx_mean(
  data,
  name = "su_y_ksads__aud__past__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__aud__past__sx is a character vector of all column names used to compute summary score of su_y_ksads__aud__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__aud__pres__sx

Compute "KSADS - Alcohol Use Disorder [Youth] (Symptom - Present): Mean"

Description

Computes the summary score su_y_ksads__aud__pres__sx_mean KSADS - Alcohol Use Disorder [Youth] (Symptom - Present): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - su_y_ksads__aud__actvdecr__pres_sx
  - su_y_ksads__aud__crave__pres_sx
  - su_y_ksads__aud__dwi__pres_sx
  - su_y_ksads__aud__failrespons__pres_sx

  - su_y_ksads__aud__haz__pres_sx
  - su_y_ksads__aud__negimpct__interprs__pres_sx
  - su_y_ksads__aud__overuse__pres_sx
  - su_y_ksads__aud__prob__phys__pres_sx
  - su_y_ksads__aud__prob__psych__pres_sx
  - su_y_ksads__aud__reduce__dsr__pres_sx
  - su_y_ksads__aud__reduce__unsucces__pres_sx
  - su_y_ksads__aud__time__pres_sx
  - su_y_ksads__aud__tol__pres_sx
  - su_y_ksads__aud__withdr__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_su_y_ksads__aud__pres__sx

compute_su_y_ksads__aud__pres__sx_mean(
  data,
  name = "su_y_ksads__aud__pres__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__aud__pres__sx is a character vector of all column names used to compute summary score of su_y_ksads__aud__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

---

vars_su_y_ksads__dud__coc__past__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Cocaine - Past): Mean"

Description

Computes the summary score `su_y_ksads__dud__coc__past__sx_mean` KSADS - Drug Use Disorders [Youth] (Symptom: Cocaine - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - `su_y_ksads__dud__actvdecr__coc__past_sx`
  - `su_y_ksads__dud__crave__coc__past_sx`
  - `su_y_ksads__dud__dwi__coc__past_sx`
  - `su_y_ksads__dud__failrespons__coc__past_sx`
  - `su_y_ksads__dud__haz__coc__past_sx`
  - `su_y_ksads__dud__negimpct__interprs__coc__past_sx`
  - `su_y_ksads__dud__negimpct__obl__coc__past_sx`
  - `su_y_ksads__dud__overuse__coc__past_sx`
  - `su_y_ksads__dud__prob__phys__coc__past_sx`
  - `su_y_ksads__dud__prob__psych__coc__past_sx`
  - `su_y_ksads__dud__reduce__dsr__coc__past_sx`
  - `su_y_ksads__dud__reduce__unsucces__coc__past_sx`
  - `su_y_ksads__dud__time__coc__past_sx`
  - `su_y_ksads__dud__tol__coc__past_sx`
  - `su_y_ksads__dud__withdr__coc__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__coc__past__sx_mean

compute_su_y_ksads__dud__coc__past__sx_mean(
  data,
  name = "su_y_ksads__dud__coc__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__coc__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__coc__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_y_ksads__dud__coc__pres__sx_mean
Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Cocaine - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__coc__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Cocaine - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__coc__pres_sx
  - su_y_ksads__dud__crave__coc__pres_sx
  - su_y_ksads__dud__dwi__coc__pres_sx
  - su_y_ksads__dud__failrespons__coc__pres_sx
  - su_y_ksads__dud__haz__coc__pres_sx
  - su_y_ksads__dud__negimpct__interprs__coc__pres_sx
  - su_y_ksads__dud__negimpct__obl__coc__pres_sx
  - su_y_ksads__dud__overuse__coc__pres_sx
  - su_y_ksads__dud__prob__phys__coc__pres_sx
  - su_y_ksads__dud__prob__psych__coc__pres_sx
  - su_y_ksads__dud__reduce__dsr__coc__pres_sx
  - su_y_ksads__dud__reduce__unsucces__coc__pres_sx
  - su_y_ksads__dud__time__coc__pres_sx
  - su_y_ksads__dud__tol__coc__pres_sx
  - su_y_ksads__dud__withdr__coc__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__coc__pres__sx_mean

compute_su_y_ksads__dud__coc__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__coc__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__coc__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__coc__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__hall__past__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Hallucinogen - Past): Mean"

Description

Computes the summary score su_y_ksads__dud__hall__past__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Hallucinogen - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__hall__past_sx
  - su_y_ksads__dud__crave__hall__past_sx
  - su_y_ksads__dud__dwi__hall__past_sx

  - su_y_ksads__dud__failrespons__hall__past_sx
  - su_y_ksads__dud__haz__hall__past_sx
  - su_y_ksads__dud__negimpct__interprs__hall__past_sx
  - su_y_ksads__dud__negimpct__obl__hall__past_sx
  - su_y_ksads__dud__overuse__hall__past_sx
  - su_y_ksads__dud__prob__phys__hall__past_sx
  - su_y_ksads__dud__prob__psych__hall__past_sx
  - su_y_ksads__dud__reduce__dsr__hall__past_sx
  - su_y_ksads__dud__reduce__unsucces__hall__past_sx
  - su_y_ksads__dud__time__hall__past_sx
  - su_y_ksads__dud__tol__hall__past_sx
  - su_y_ksads__dud__withdr__hall__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__hall__past__sx_mean

compute_su_y_ksads__dud__hall__past__sx_mean(
  data,
  name = "su_y_ksads__dud__hall__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__hall__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__hall__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__hall__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Hallucinogen - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__hall__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Hallucinogen - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__hall__pres_sx
  - su_y_ksads__dud__crave__hall__pres_sx
  - su_y_ksads__dud__dwi__hall__pres_sx
  - su_y_ksads__dud__failrespons__hall__pres_sx
  - su_y_ksads__dud__haz__hall__pres_sx
  - su_y_ksads__dud__negimpct__interprs__hall__pres_sx
  - su_y_ksads__dud__negimpct__obl__hall__pres_sx
  - su_y_ksads__dud__overuse__hall__pres_sx
  - su_y_ksads__dud__prob__phys__hall__pres_sx
  - su_y_ksads__dud__prob__psych__hall__pres_sx
  - su_y_ksads__dud__reduce__dsr__hall__pres_sx
  - su_y_ksads__dud__reduce__unsucces__hall__pres_sx
  - su_y_ksads__dud__time__hall__pres_sx
  - su_y_ksads__dud__tol__hall__pres_sx
  - su_y_ksads__dud__withdr__hall__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__hall__pres__sx_mean

compute_su_y_ksads__dud__hall__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__hall__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__hall__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__hall__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_y_ksads__dud__mj__past__sx_mean
Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Cannabis - Past): Mean"

Description

Computes the summary score su_y_ksads__dud__mj__past__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Cannabis - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__mj__past_sx
  - su_y_ksads__dud__crave__mj__past_sx
  - su_y_ksads__dud__dwi__mj__past_sx
  - su_y_ksads__dud__failrespons__mj__past_sx
  - su_y_ksads__dud__haz__mj__past_sx
  - su_y_ksads__dud__negimpct__interprs__mj__past_sx
  - su_y_ksads__dud__negimpct__obl__mj__past_sx
  - su_y_ksads__dud__overuse__mj__past_sx
  - su_y_ksads__dud__prob__phys__mj__past_sx
  - su_y_ksads__dud__prob__psych__mj__past_sx
  - su_y_ksads__dud__reduce__dsr__mj__past_sx
  - su_y_ksads__dud__reduce__unsucces__mj__past_sx
  - su_y_ksads__dud__time__mj__past_sx
  - su_y_ksads__dud__tol__mj__past_sx
  - su_y_ksads__dud__withdr__mj__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__mj__past__sx_mean

compute_su_y_ksads__dud__mj__past__sx_mean(
  data,
  name = "su_y_ksads__dud__mj__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__mj__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__mj__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__mj__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Cannabis - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__mj__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Cannabis - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__mj__pres_sx
  - su_y_ksads__dud__crave__mj__pres_sx
  - su_y_ksads__dud__dwi__mj__pres_sx

  - su_y_ksads__dud__failrespons__mj__pres_sx
  - su_y_ksads__dud__haz__mj__pres_sx
  - su_y_ksads__dud__negimpct__interprs__mj__pres_sx
  - su_y_ksads__dud__negimpct__obl__mj__pres_sx
  - su_y_ksads__dud__overuse__mj__pres_sx
  - su_y_ksads__dud__prob__phys__mj__pres_sx
  - su_y_ksads__dud__prob__psych__mj__pres_sx
  - su_y_ksads__dud__reduce__dsr__mj__pres_sx
  - su_y_ksads__dud__reduce__unsucces__mj__pres_sx
  - su_y_ksads__dud__time__mj__pres_sx
  - su_y_ksads__dud__tol__mj__pres_sx
  - su_y_ksads__dud__withdr__mj__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__mj__pres__sx_mean

compute_su_y_ksads__dud__mj__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__mj__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__mj__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__mj__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- `"888"`: item skipped by branching. When at least one input value is observed, any `888` value is converted to "0" prior to averaging.
- `"555"`: module not administered. If any input variable is "555" leave the score as `NA`.
- `NA`: missing value. If at least one input value is observed, any `NA` values are converted to "0" prior to averaging. If all inputs are `NA`, the summary score remains `NA`.

Value

tbl. see `combine`.

`vars_su_y_ksads__dud__nic__past__sx_mean`
Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Tobacco - Past): Mean"

Description

Computes the summary score `su_y_ksads__dud__nic__past__sx_mean` KSADS - Drug Use Disorders [Youth] (Symptom: Tobacco - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - `su_y_ksads__dud__actvdecr__nic__past_sx`
  - `su_y_ksads__dud__crave__nic__past_sx`
  - `su_y_ksads__dud__dwi__nic__past_sx`
  - `su_y_ksads__dud__failrespons__nic__past_sx`
  - `su_y_ksads__dud__haz__nic__past_sx`
  - `su_y_ksads__dud__negimpct__interprs__nic__past_sx`
  - `su_y_ksads__dud__negimpct__obl__nic__past_sx`
  - `su_y_ksads__dud__overuse__nic__past_sx`
  - `su_y_ksads__dud__prob__phys__nic__past_sx`
  - `su_y_ksads__dud__prob__psych__nic__past_sx`
  - `su_y_ksads__dud__reduce__dsr__nic__past_sx`
  - `su_y_ksads__dud__reduce__unsucces__nic__past_sx`
  - `su_y_ksads__dud__time__nic__past_sx`
  - `su_y_ksads__dud__tol__nic__past_sx`
  - `su_y_ksads__dud__withdr__nic__past_sx`
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__nic__past__sx_mean

compute_su_y_ksads__dud__nic__past__sx_mean(
  data,
  name = "su_y_ksads__dud__nic__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__nic__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__nic__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_y_ksads__dud__nic__pres__sx_mean
Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Tobacco - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__nic__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Tobacco - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__nic__pres_sx
  - su_y_ksads__dud__crave__nic__pres_sx
  - su_y_ksads__dud__dwi__nic__pres_sx
  - su_y_ksads__dud__failrespons__nic__pres_sx
  - su_y_ksads__dud__haz__nic__pres_sx
  - su_y_ksads__dud__negimpct__interprs__nic__pres_sx
  - su_y_ksads__dud__negimpct__obl__nic__pres_sx
  - su_y_ksads__dud__overuse__nic__pres_sx
  - su_y_ksads__dud__prob__phys__nic__pres_sx
  - su_y_ksads__dud__prob__psych__nic__pres_sx
  - su_y_ksads__dud__reduce__dsr__nic__pres_sx
  - su_y_ksads__dud__reduce__unsucces__nic__pres_sx
  - su_y_ksads__dud__time__nic__pres_sx
  - su_y_ksads__dud__tol__nic__pres_sx
  - su_y_ksads__dud__withdr__nic__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__nic__pres__sx_mean

compute_su_y_ksads__dud__nic__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__nic__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__nic__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__nic__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__opi__past__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Opiod - Past): Mean"

Description

Computes the summary score su_y_ksads__dud__opi__past__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Opiod - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__opi__past_sx
  - su_y_ksads__dud__crave__opi__past_sx
  - su_y_ksads__dud__dwi__opi__past_sx
  - su_y_ksads__dud__failrespons__opi__past_sx

  - su_y_ksads__dud__haz__opi__past_sx
  - su_y_ksads__dud__negimpct__interprs__opi__past_sx
  - su_y_ksads__dud__negimpct__obl__opi__past_sx
  - su_y_ksads__dud__overuse__opi__past_sx
  - su_y_ksads__dud__prob__phys__opi__past_sx
  - su_y_ksads__dud__prob__psych__opi__past_sx
  - su_y_ksads__dud__reduce__dsr__opi__past_sx
  - su_y_ksads__dud__reduce__unsucces__opi__past_sx
  - su_y_ksads__dud__time__opi__past_sx
  - su_y_ksads__dud__tol__opi__past_sx
  - su_y_ksads__dud__withdr__opi__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__opi__past__sx_mean

compute_su_y_ksads__dud__opi__past__sx_mean(
  data,
  name = "su_y_ksads__dud__opi__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__opi__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__opi__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__opi__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Opiod - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__opi__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Opiod - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__opi__pres_sx
  - su_y_ksads__dud__crave__opi__pres_sx
  - su_y_ksads__dud__dwi__opi__pres_sx
  - su_y_ksads__dud__failrespons__opi__pres_sx
  - su_y_ksads__dud__haz__opi__pres_sx
  - su_y_ksads__dud__negimpct__interprs__opi__pres_sx
  - su_y_ksads__dud__negimpct__obl__opi__pres_sx
  - su_y_ksads__dud__overuse__opi__pres_sx
  - su_y_ksads__dud__prob__phys__opi__pres_sx
  - su_y_ksads__dud__prob__psych__opi__pres_sx
  - su_y_ksads__dud__reduce__dsr__opi__pres_sx
  - su_y_ksads__dud__reduce__unsucces__opi__pres_sx
  - su_y_ksads__dud__time__opi__pres_sx
  - su_y_ksads__dud__tol__opi__pres_sx
  - su_y_ksads__dud__withdr__opi__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__opi__pres__sx_mean

compute_su_y_ksads__dud__opi__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__opi__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__opi__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__opi__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_y_ksads__dud__othdrg__past__sx_mean
Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Other drugs - Past): Mean"

Description

Computes the summary score su_y_ksads__dud__othdrg__past__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Other drugs - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__othdrg__past_sx
  - su_y_ksads__dud__crave__othdrg__past_sx
  - su_y_ksads__dud__dwi__othdrg__past_sx
  - su_y_ksads__dud__failrespons__othdrg__past_sx
  - su_y_ksads__dud__haz__othdrg__past_sx
  - su_y_ksads__dud__negimpct__interprs__othdrg__past_sx
  - su_y_ksads__dud__negimpct__obl__othdrg__past_sx
  - su_y_ksads__dud__overuse__othdrg__past_sx
  - su_y_ksads__dud__prob__phys__othdrg__past_sx
  - su_y_ksads__dud__prob__psych__othdrg__past_sx
  - su_y_ksads__dud__reduce__dsr__othdrg__past_sx
  - su_y_ksads__dud__reduce__unsucces__othdrg__past_sx
  - su_y_ksads__dud__time__othdrg__past_sx
  - su_y_ksads__dud__tol__othdrg__past_sx
  - su_y_ksads__dud__withdr__othdrg__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__othdrg__past__sx_mean

compute_su_y_ksads__dud__othdrg__past__sx_mean(
  data,
  name = "su_y_ksads__dud__othdrg__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__othdrg__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__othdrg__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__othdrg__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Other drugs - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__othdrg__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Other drugs - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__othdrg__pres_sx
  - su_y_ksads__dud__crave__othdrg__pres_sx
  - su_y_ksads__dud__dwi__othdrg__pres_sx

  - su_y_ksads__dud__failrespons__othdrg__pres_sx
  - su_y_ksads__dud__haz__othdrg__pres_sx
  - su_y_ksads__dud__negimpct__interprs__othdrg__pres_sx
  - su_y_ksads__dud__negimpct__obl__othdrg__pres_sx
  - su_y_ksads__dud__overuse__othdrg__pres_sx
  - su_y_ksads__dud__prob__phys__othdrg__pres_sx
  - su_y_ksads__dud__prob__psych__othdrg__pres_sx
  - su_y_ksads__dud__reduce__dsr__othdrg__pres_sx
  - su_y_ksads__dud__reduce__unsucces__othdrg__pres_sx
  - su_y_ksads__dud__time__othdrg__pres_sx
  - su_y_ksads__dud__tol__othdrg__pres_sx
  - su_y_ksads__dud__withdr__othdrg__pres_sx

- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__othdrg__pres__sx_mean

compute_su_y_ksads__dud__othdrg__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__othdrg__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__othdrg__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__othdrg__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__past__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom - Past): Mean"

Description

Computes the summary score su_y_ksads__dud__past__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom - Past): Mean [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__past_sx
  - su_y_ksads__dud__crave__past_sx
  - su_y_ksads__dud__dwi__past_sx
  - su_y_ksads__dud__failrespons__past_sx
  - su_y_ksads__dud__haz__past_sx
  - su_y_ksads__dud__negimpct__interprs__past_sx
  - su_y_ksads__dud__negimpct__obl__past_sx
  - su_y_ksads__dud__overuse__past_sx
  - su_y_ksads__dud__prob__phys__past_sx
  - su_y_ksads__dud__prob__psych__past_sx
  - su_y_ksads__dud__reduce__dsr__past_sx
  - su_y_ksads__dud__reduce__unsucces__past_sx
  - su_y_ksads__dud__tol__past_sx
  - su_y_ksads__dud__withdr__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 2 of 14 items missing

Usage

```
vars_su_y_ksads__dud__past__sx_mean

compute_su_y_ksads__dud__past__sx_mean(
  data,
  name = "su_y_ksads__dud__past__sx_mean",
  max_na = 2,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_y_ksads__dud__pcp__past__sx_mean
Compute "KSADS - Drug Use Disorders [Youth] (Symptom: PCP - Past): Mean"

Description

Computes the summary score su_y_ksads__dud__pcp__past__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: PCP - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__pcp__past_sx
  - su_y_ksads__dud__crave__pcp__past_sx
  - su_y_ksads__dud__dwi__pcp__past_sx
  - su_y_ksads__dud__failrespons__pcp__past_sx
  - su_y_ksads__dud__haz__pcp__past_sx
  - su_y_ksads__dud__negimpct__interprs__pcp__past_sx
  - su_y_ksads__dud__negimpct__obl__pcp__past_sx
  - su_y_ksads__dud__overuse__pcp__past_sx
  - su_y_ksads__dud__prob__phys__pcp__past_sx
  - su_y_ksads__dud__prob__psych__pcp__past_sx
  - su_y_ksads__dud__reduce__dsr__pcp__past_sx
  - su_y_ksads__dud__reduce__unsucces__pcp__past_sx
  - su_y_ksads__dud__time__pcp__past_sx
  - su_y_ksads__dud__tol__pcp__past_sx
  - su_y_ksads__dud__withdr__pcp__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__pcp__past__sx_mean

compute_su_y_ksads__dud__pcp__past__sx_mean(
  data,
  name = "su_y_ksads__dud__pcp__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__pcp__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__pcp__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__pcp__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: PCP - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__pcp__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: PCP - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__pcp__pres_sx
  - su_y_ksads__dud__crave__pcp__pres_sx
  - su_y_ksads__dud__dwi__pcp__pres_sx
  - su_y_ksads__dud__failrespons__pcp__pres_sx

  - su_y_ksads__dud__haz__pcp__pres_sx
  - su_y_ksads__dud__negimpct__interprs__pcp__pres_sx
  - su_y_ksads__dud__negimpct__obl__pcp__pres_sx
  - su_y_ksads__dud__overuse__pcp__pres_sx
  - su_y_ksads__dud__prob__phys__pcp__pres_sx
  - su_y_ksads__dud__prob__psych__pcp__pres_sx
  - su_y_ksads__dud__reduce__dsr__pcp__pres_sx
  - su_y_ksads__dud__reduce__unsucces__pcp__pres_sx
  - su_y_ksads__dud__time__pcp__pres_sx
  - su_y_ksads__dud__tol__pcp__pres_sx
  - su_y_ksads__dud__withdr__pcp__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__pcp__pres__sx_mean

compute_su_y_ksads__dud__pcp__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__pcp__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__pcp__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__pcp__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__pres_sx
  - su_y_ksads__dud__crave__pres_sx
  - su_y_ksads__dud__dwi__pres_sx
  - su_y_ksads__dud__failrespons__pres_sx
  - su_y_ksads__dud__haz__pres_sx
  - su_y_ksads__dud__negimpct__interprs__pres_sx
  - su_y_ksads__dud__negimpct__obl__pres_sx
  - su_y_ksads__dud__overuse__pres_sx
  - su_y_ksads__dud__prob__phys__pres_sx
  - su_y_ksads__dud__prob__psych__pres_sx
  - su_y_ksads__dud__reduce__dsr__pres_sx
  - su_y_ksads__dud__reduce__unsucces__pres_sx
  - su_y_ksads__dud__time__pres_sx
  - su_y_ksads__dud__tol__pres_sx
  - su_y_ksads__dud__withdr__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__pres__sx_mean

compute_su_y_ksads__dud__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_y_ksads__dud__sed__past__sx_mean
Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Sedatives - Past): Mean"

Description

Computes the summary score su_y_ksads__dud__sed__past__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Sedatives - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__sed__past_sx
  - su_y_ksads__dud__crave__sed__past_sx
  - su_y_ksads__dud__dwi__sed__past_sx
  - su_y_ksads__dud__failrespons__sed__past_sx
  - su_y_ksads__dud__haz__sed__past_sx
  - su_y_ksads__dud__negimpct__interprs__sed__past_sx
  - su_y_ksads__dud__negimpct__obl__sed__past_sx
  - su_y_ksads__dud__overuse__sed__past_sx
  - su_y_ksads__dud__prob__phys__sed__past_sx
  - su_y_ksads__dud__prob__psych__sed__past_sx
  - su_y_ksads__dud__reduce__dsr__sed__past_sx
  - su_y_ksads__dud__reduce__unsucces__sed__past_sx
  - su_y_ksads__dud__time__sed__past_sx
  - su_y_ksads__dud__tol__sed__past_sx
  - su_y_ksads__dud__withdr__sed__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__sed__past__sx_mean

compute_su_y_ksads__dud__sed__past__sx_mean(
  data,
  name = "su_y_ksads__dud__sed__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__sed__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__sed__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__sed__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Sedatives - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__sed__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Sedatives - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__sed__pres_sx
  - su_y_ksads__dud__crave__sed__pres_sx
  - su_y_ksads__dud__dwi__sed__pres_sx

  - su_y_ksads__dud__failrespons__sed__pres_sx
  - su_y_ksads__dud__haz__sed__pres_sx
  - su_y_ksads__dud__negimpct__interprs__sed__pres_sx
  - su_y_ksads__dud__negimpct__obl__sed__pres_sx
  - su_y_ksads__dud__overuse__sed__pres_sx
  - su_y_ksads__dud__prob__phys__sed__pres_sx
  - su_y_ksads__dud__prob__psych__sed__pres_sx
  - su_y_ksads__dud__reduce__dsr__sed__pres_sx
  - su_y_ksads__dud__reduce__unsucces__sed__pres_sx
  - su_y_ksads__dud__time__sed__pres_sx
  - su_y_ksads__dud__tol__sed__pres_sx
  - su_y_ksads__dud__withdr__sed__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__sed__pres__sx_mean

compute_su_y_ksads__dud__sed__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__sed__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__sed__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__sed__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__solv__past__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Solvent - Past): Mean"

Description

Computes the summary score su_y_ksads__dud__solv__past__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Solvent - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__solv__past_sx
  - su_y_ksads__dud__crave__solv__past_sx
  - su_y_ksads__dud__dwi__solv__past_sx
  - su_y_ksads__dud__failrespons__solv__past_sx
  - su_y_ksads__dud__haz__solv__past_sx
  - su_y_ksads__dud__negimpct__interprs__solv__past_sx
  - su_y_ksads__dud__negimpct__obl__solv__past_sx
  - su_y_ksads__dud__overuse__solv__past_sx
  - su_y_ksads__dud__prob__phys__solv__past_sx
  - su_y_ksads__dud__prob__psych__solv__past_sx
  - su_y_ksads__dud__reduce__dsr__solv__past_sx
  - su_y_ksads__dud__reduce__unsucces__solv__past_sx
  - su_y_ksads__dud__time__solv__past_sx
  - su_y_ksads__dud__tol__solv__past_sx
  - su_y_ksads__dud__withdr__solv__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__solv__past__sx_mean

compute_su_y_ksads__dud__solv__past__sx_mean(
  data,
  name = "su_y_ksads__dud__solv__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__solv__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__solv__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_y_ksads__dud__solv__pres__sx_mean
Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Solvent - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__solv__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Solvent - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__solv__pres_sx
  - su_y_ksads__dud__crave__solv__pres_sx
  - su_y_ksads__dud__dwi__solv__pres_sx
  - su_y_ksads__dud__failrespons__solv__pres_sx
  - su_y_ksads__dud__haz__solv__pres_sx
  - su_y_ksads__dud__negimpct__interprs__solv__pres_sx
  - su_y_ksads__dud__negimpct__obl__solv__pres_sx
  - su_y_ksads__dud__overuse__solv__pres_sx
  - su_y_ksads__dud__prob__phys__solv__pres_sx
  - su_y_ksads__dud__prob__psych__solv__pres_sx
  - su_y_ksads__dud__reduce__dsr__solv__pres_sx
  - su_y_ksads__dud__reduce__unsucces__solv__pres_sx
  - su_y_ksads__dud__time__solv__pres_sx
  - su_y_ksads__dud__tol__solv__pres_sx
  - su_y_ksads__dud__withdr__solv__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__solv__pres__sx_mean

compute_su_y_ksads__dud__solv__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__solv__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__solv__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__solv__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__stim__past__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Stimulants - Past): Mean"

Description

Computes the summary score su_y_ksads__dud__stim__past__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Stimulants - Past): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__stim__past_sx
  - su_y_ksads__dud__crave__stim__past_sx
  - su_y_ksads__dud__dwi__stim__past_sx

  - su_y_ksads__dud__failrespons__stim__past_sx
  - su_y_ksads__dud__haz__stim__past_sx
  - su_y_ksads__dud__negimpct__interprs__stim__past_sx
  - su_y_ksads__dud__negimpct__obl__stim__past_sx
  - su_y_ksads__dud__overuse__stim__past_sx
  - su_y_ksads__dud__prob__phys__stim__past_sx
  - su_y_ksads__dud__prob__psych__stim__past_sx
  - su_y_ksads__dud__reduce__dsr__stim__past_sx
  - su_y_ksads__dud__reduce__unsucces__stim__past_sx
  - su_y_ksads__dud__time__stim__past_sx
  - su_y_ksads__dud__tol__stim__past_sx
  - su_y_ksads__dud__withdr__stim__past_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__stim__past__sx_mean

compute_su_y_ksads__dud__stim__past__sx_mean(
  data,
  name = "su_y_ksads__dud__stim__past__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__stim__past__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__stim__past__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

---

vars_su_y_ksads__dud__stim__pres__sx_mean

Compute "KSADS - Drug Use Disorders [Youth] (Symptom: Stimulants - Present): Mean"

Description

Computes the summary score su_y_ksads__dud__stim__pres__sx_mean KSADS - Drug Use Disorders [Youth] (Symptom: Stimulants - Present): Mean [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_ksads__dud__actvdecr__stim__pres_sx
  - su_y_ksads__dud__crave__stim__pres_sx
  - su_y_ksads__dud__dwi__stim__pres_sx
  - su_y_ksads__dud__failrespons__stim__pres_sx
  - su_y_ksads__dud__haz__stim__pres_sx
  - su_y_ksads__dud__negimpct__interprs__stim__pres_sx
  - su_y_ksads__dud__negimpct__obl__stim__pres_sx
  - su_y_ksads__dud__overuse__stim__pres_sx
  - su_y_ksads__dud__prob__phys__stim__pres_sx
  - su_y_ksads__dud__prob__psych__stim__pres_sx
  - su_y_ksads__dud__reduce__dsr__stim__pres_sx
  - su_y_ksads__dud__reduce__unsucces__stim__pres_sx
  - su_y_ksads__dud__time__stim__pres_sx
  - su_y_ksads__dud__tol__stim__pres_sx
  - su_y_ksads__dud__withdr__stim__pres_sx
- *Excluded values:*
  - 555
- *Validation criterion:* maximally 3 of 15 items missing

Usage

```
vars_su_y_ksads__dud__stim__pres__sx_mean

compute_su_y_ksads__dud__stim__pres__sx_mean(
  data,
  name = "su_y_ksads__dud__stim__pres__sx_mean",
  max_na = 3,
  exclude = c("555"),
  combine = TRUE
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the summary score column.
max_na	numeric, positive whole number. Number of missing items allowed. NULL means no limit.
exclude	character vector. Values to be excluded from the summary score calculation.
combine	logical. If TRUE (default), the summary score is is appended as a new column to the input data frame. If FALSE, the summary score is returned as a separate one-column data frame.

Format

vars_su_y_ksads__dud__stim__pres__sx_mean is a character vector of all column names used to compute summary score of su_y_ksads__dud__stim__pres__sx_mean

Details

KSADS summary scores are mostly calculating the means over variables, but there are two special codes to handle:

- "888": item skipped by branching. When at least one input value is observed, any 888 value is converted to "0" prior to averaging.
- "555": module not administered. If any input variable is "555" leave the score as NA.
- NA: missing value. If at least one input value is observed, any NA values are converted to "0" prior to averaging. If all inputs are NA, the summary score remains NA.

Value

tbl. see combine.

vars_su_y_mjexp__neg *Compute "Marijuana Expectancies (MEEQ-B) [Youth] (Strength of negative expectancies): Prorated sum"*

Description

Computes the summary score su_y_mjexp__neg_prsum Marijuana Expectancies (MEEQ-B) [Youth] (Strength of negative expectancies): Prorated sum [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - su_y_mjexp__neg_001
  - su_y_mjexp__neg_002
  - su_y_mjexp__neg_003
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 3 items missing

Usage

```
vars_su_y_mjexp__neg

compute_su_y_mjexp__neg_prsum(
  data,
  name = "su_y_mjexp__neg_prsum",
  combine = TRUE,
  max_na = 1
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.
combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_mjexp__neg is a character vector of all column names used to compute summary score of su_y_mjexp__neg_prsum and su_y_mjexp__neg_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_su_y_mjexp__pos` *Compute "Marijuana Expectancies (MEEQ-B) [Youth] (Strength of positive expectancies): Prorated sum"*

Description

Computes the summary score `su_y_mjexp__pos_prsum` Marijuana Expectancies (MEEQ-B) [Youth] (Strength of positive expectancies): Prorated sum [Validation: No more than 1 missing or declined]

- *Summarized variables:*
  - `su_y_mjexp__pos_001`
  - `su_y_mjexp__pos_002`
  - `su_y_mjexp__pos_003`
- *Excluded values:* none
- *Validation criterion:* maximally 1 of 3 items missing

Usage

```
vars_su_y_mjexp__pos

compute_su_y_mjexp__pos_prsum(
  data,
  name = "su_y_mjexp__pos_prsum",
  combine = TRUE,
  max_na = 1
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE` (default), the summary score will be appended to the input data frame. If `FALSE`, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_mjexp__pos is a character vector of all column names used to compute summary score of `su_y_mjexp__pos_prsum` and `su_y_mjexp__pos_nm`

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_mjprob *Compute "Marijuana Problem Index (MAPI) [Youth]: Prorated sum"*

Description

Computes the summary score su_y_mjprob_prsum Marijuana Problem Index (MAPI) [Youth]: Prorated sum [Validation: No more than 3 missing or declined]

- *Summarized variables:*
  - su_y_mjprob_001
  - su_y_mjprob_002
  - su_y_mjprob_003
  - su_y_mjprob_004
  - su_y_mjprob_005
  - su_y_mjprob_006
  - su_y_mjprob_007
  - su_y_mjprob_008
  - su_y_mjprob_009
  - su_y_mjprob_010
  - su_y_mjprob_011
  - su_y_mjprob_012
  - su_y_mjprob_016
  - su_y_mjprob_017
  - su_y_mjprob_018
- *Excluded values:* none
- *Validation criterion:* maximally 3 items missing

Usage

```
vars_su_y_mjprob

compute_su_y_mjprob_prsum(
  data,
  name = "su_y_mjprob_prsum",
  combine = TRUE,
  max_na = 3
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character, Name of the new column to be created. Default is the name in description, but users can change it.

combine	logical, If TRUE (default), the summary score will be appended to the input data frame. If FALSE, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
max_na	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_mjprob is a character vector of all column names used to compute summary score of su_y_mjprob_prsum and su_y_mjprob_nm.

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_mjsre *Compute "Marijuana Subjective Response and Effects [Youth] (Total): Sum - Positive score inverted [Validation: None missing or declined]"*

Description

Computes the summary score su_y_mjsre_sum Marijuana Subjective Response and Effects [Youth] (Total): Sum - Positive score inverted [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_mjsre__pos_001
  - su_y_mjsre__pos_002
  - su_y_mjsre__pos_003
  - su_y_mjsre__neg_001
  - su_y_mjsre__neg_002
  - su_y_mjsre__neg_003
  - su_y_mjsre__neg_004
  - su_y_mjsre__neg_005
  - su_y_mjsre__neg_006
  - su_y_mjsre__neg_007
  - su_y_mjsre__neg_008
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 11 items missing

Usage

```
vars_su_y_mjsre

compute_su_y_mjsre_sum(
  data,
  name = "su_y_mjsre_sum",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Format

vars_su_y_mjsre is a character vector of all column names used to compute summary scores of compute_su_y_mjsre (_sum, _nm).

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_mjsre__neg *Compute "Marijuana Subjective Response and Effects [Youth] (Negative): Sum [Validation: None missing or declined]"*

Description

Computes the summary score su_y_mjsre__neg_sum Marijuana Subjective Response and Effects [Youth] (Negative): Sum [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_mjsre__neg_001
  - su_y_mjsre__neg_002
  - su_y_mjsre__neg_003
  - su_y_mjsre__neg_004
  - su_y_mjsre__neg_005
  - su_y_mjsre__neg_006

  - su_y_mjsre__neg_007
  - su_y_mjsre__neg_008
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 8 items missing

Usage

```
vars_su_y_mjsre__neg

compute_su_y_mjsre__neg_sum(
  data,
  name = "su_y_mjsre__neg_sum",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Format

vars_su_y_mjsre__neg is a character vector of all column names used to compute summary scores of compute_su_y_mjsre__neg (_sum, _nm).

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_mjsre__pos *Compute "Marijuana Subjective Response and Effects [Youth] (Positive): Sum [Validation: None missing or declined]"*

Description

Computes the summary score su_y_mjsre__pos_sum Marijuana Subjective Response and Effects [Youth] (Positive): Sum [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_mjsre__pos_001

  - su_y_mjsre__pos_002
  - su_y_mjsre__pos_003

- *Excluded values:* none
- *Validation criterion:* maximally 0 of 3 items missing

Usage

```
vars_su_y_mjsre__pos

compute_su_y_mjsre__pos_sum(
  data,
  name = "su_y_mjsre__pos_sum",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Format

vars_su_y_mjsre__pos is a character vector of all column names used to compute summary scores of compute_su_y_mjsre__pos (_sum, _nm).

Value

tbl. The input data frame with the summary score appended as a new column.

---

vars_su_y_nicsre__chew

Compute "Nicotine Subjective Response and Effects [Youth] (Intensity of positive and negative effects of first smokeless tobacco or chew use): Sum - Negative score inverted [Validation: None missing or declined]"

Description

Computes the summary score su_y_nicsre__chew_sum Nicotine Subjective Response and Effects [Youth] (Intensity of positive and negative effects of first smokeless tobacco or chew use): Sum - Negative score inverted [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_nicsre__chew__pos_001
  - su_y_nicsre__chew__neg_001
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_su_y_nicsre__chew

compute_su_y_nicsre__chew_sum(
  data,
  name = "su_y_nicsre__chew_sum",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Format

vars_su_y_nicsre__chew is a character vector of all column names used to compute summary scores of compute_su_y_nicsre__chew (_sum, _nm).

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_nicsre__cig *Compute "Nicotine Subjective Response and Effects [Youth] (Intensity of positive and negative effects of first cigarette use): Sum - Negative score inverted [Validation: None missing or declined]"*

Description

Computes the summary score su_y_nicsre__cig_sum Nicotine Subjective Response and Effects [Youth] (Intensity of positive and negative effects of first cigarette use): Sum - Negative score inverted [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_nicsre__cig__pos_001
  - su_y_nicsre__cig__neg_001
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_su_y_nicsre__cig

compute_su_y_nicsre__cig_sum(
  data,
  name = "su_y_nicsre__cig_sum",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Format

vars_su_y_nicsre__cig is a character vector of all column names used to compute summary scores of compute_su_y_nicsre__cig (_sum, _nm).

Value

tbl. The input data frame with the summary score appended as a new column.

vars_su_y_nicsre__vape

Compute "Nicotine Subjective Response and Effects [Youth] (Intensity of positive and negative effects of first vape use): Sum - Negative score inverted [Validation: None missing or declined]"

Description

Computes the summary score su_y_nicsre__vape_sum Nicotine Subjective Response and Effects [Youth] (Intensity of positive and negative effects of first vape use): Sum - Negative score inverted [Validation: None missing or declined]

- *Summarized variables:*
  - su_y_nicsre__vape__pos_001
  - su_y_nicsre__vape__pos_001__v01
  - su_y_nicsre__vape__neg_001
  - su_y_nicsre__vape__neg_001__v01
- *Excluded values:* none
- *Validation criterion:* maximally 0 of 2 items missing

Usage

```
vars_su_y_nicsre__vape

compute_su_y_nicsre__vape_sum(
  data,
  name = "su_y_nicsre__vape_sum",
  combine = TRUE,
  max_na = 0
)
```

Arguments

data	tbl. Data frame containing the columns to be summarized.
name	character. Name of the new column to be created (Default: the name used in the ABCD data release).
combine	logical. If TRUE, the new column will be bound to the input data frame. If FALSE, the new column will be created as a new data frame.
max_na	numeric, positive whole number. Number of missing items allowed (Default: 0).

Format

vars_su_y_nicsre__vape is a character vector of all column names used to compute summary scores of compute_su_y_nicsre__vape (_sum, _nm).

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_su_y_nicvapeexp__neg`

Compute "ENDS Expectancies [Youth] (Strength of negative expectancies): Prorated sum"

Description

Computes the summary score `su_y_nicvapeexp__neg_prsum` ENDS Expectancies [Youth] (Strength of negative expectancies): Prorated sum [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `su_y_nicvapeexp__neg_001`
  - `su_y_nicvapeexp__neg_002`
  - `su_y_nicvapeexp__neg_003`
  - `su_y_nicvapeexp__neg_004`
- *Excluded values:* none
- *Validation criterion:* maximally 2 of 4 items missing

Usage

```
vars_su_y_nicvapeexp__neg

compute_su_y_nicvapeexp__neg_prsum(
  data,
  name = "su_y_nicvapeexp__neg_prsum",
  combine = TRUE,
  max_na = 2
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE` (default), the summary score will be appended to the input data frame. If `FALSE`, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_nicvapeexp__neg is a character vector of all column names used to compute summary score of `su_y_nicvapeexp__neg_prsum` and `su_y_nicvapeexp__neg_nm`

Value

tbl. The input data frame with the summary score appended as a new column.

`vars_su_y_nicvapeexp__pos`

Compute "ENDS Expectancies [Youth] (Strength of positive expectancies): Prorated sum"

Description

Computes the summary score `su_y_nicvapeexp__pos_prsum` ENDS Expectancies [Youth] (Strength of positive expectancies): Prorated sum [Validation: No more than 2 missing or declined]

- *Summarized variables:*
  - `su_y_nicvapeexp__pos_001`
  - `su_y_nicvapeexp__pos_002`
  - `su_y_nicvapeexp__pos_003`
  - `su_y_nicvapeexp__pos_004`
- *Excluded values:* none
- *Validation criterion:* maximally 2 of 4 items missing

Usage

```
vars_su_y_nicvapeexp__pos

compute_su_y_nicvapeexp__pos_prsum(
  data,
  name = "su_y_nicvapeexp__pos_prsum",
  combine = TRUE,
  max_na = 2
)
```

Arguments

`data`	tbl. Data frame containing the columns to be summarized.
`name`	character, Name of the new column to be created. Default is the name in description, but users can change it.
`combine`	logical, If `TRUE` (default), the summary score will be appended to the input data frame. If `FALSE`, the summary score for each participant will be returned as a separate data frame. (Default: TRUE)
`max_na`	numeric, positive whole number. Number of missing items allowed (Default: 1).

Format

vars_su_y_nicvapeexp__pos is a character vector of all column names used to compute summary score of `su_y_nicvapeexp__pos_prsum` and `su_y_nicvapeexp__pos_nm`.

Value

tbl. The input data frame with the summary score appended as a new column.

Index

∗ **datasets**
sui_substances, 812
tlfb_substances, 814
vars_ab_g_dyn__cohort_edu__cgs, 816
vars_ab_g_dyn__cohort_income__hhold__6lvl, 817
vars_ab_g_dyn__cohort_prtnrshp__employ, 818
vars_ab_g_stc__cohort_ethn, 819
vars_ab_g_stc__cohort_ethnrace__leg, 820
vars_ab_g_stc__cohort_ethnrace__mblack, 822
vars_ab_g_stc__cohort_ethnrace__meim, 824
vars_ab_g_stc__cohort_ethnrace__mhisp, 825
vars_ab_g_stc__cohort_race__nih, 827
vars_ab_p_demo__ntvam, 828
vars_fc_p_fes__cohes, 830
vars_fc_p_fes__confl, 831
vars_fc_p_fes__expr, 832
vars_fc_p_fes__intelcult, 833
vars_fc_p_fes__org, 835
vars_fc_p_fes__rec, 836
vars_fc_p_meim, 837
vars_fc_p_meim__commattach, 838
vars_fc_p_meim__explor, 839
vars_fc_p_nce, 840
vars_fc_p_nce__cc, 841
vars_fc_p_nce__isc, 842
vars_fc_p_nsc__ns, 843
vars_fc_p_pk__knowl, 844
vars_fc_p_psb, 845
vars_fc_p_vs__famil, 846
vars_fc_p_vs__famil__v01, 848
vars_fc_p_vs__indselfrel, 849
vars_fc_p_vs__obl, 851
vars_fc_p_vs__ref, 852
vars_fc_p_vs__relig, 853
vars_fc_p_vs__supp, 854
vars_fc_y_as__safe, 855
vars_fc_y_crpbi__cg1, 856
vars_fc_y_crpbi__cg2, 857
vars_fc_y_eut__ethn, 858
vars_fc_y_fes__cohes, 859
vars_fc_y_fes__confl, 861
vars_fc_y_lone, 862
vars_fc_y_meim, 863
vars_fc_y_meim__commattach, 864
vars_fc_y_meim__explor, 865
vars_fc_y_mnbs, 866
vars_fc_y_mnbs__edusupp, 867
vars_fc_y_mnbs__superv, 868
vars_fc_y_naa, 869
vars_fc_y_pm, 870
vars_fc_y_pnh, 871
vars_fc_y_psb, 872
vars_fc_y_rpi, 873
vars_fc_y_srpf__dis, 874
vars_fc_y_srpf__env, 875
vars_fc_y_srpf__involv, 876
vars_fc_y_vs__famil, 878
vars_fc_y_vs__famil__v01, 879
vars_fc_y_vs__indselfrel, 880
vars_fc_y_vs__obl, 882
vars_fc_y_vs__ref, 883
vars_fc_y_vs__relig, 884
vars_fc_y_vs__supp, 885
vars_fc_y_wpss, 886
vars_mh_p_abcl, 887
vars_mh_p_abcl__afs__frnd, 891
vars_mh_p_abcl__cg2, 892
vars_mh_p_abcl__critic, 893
vars_mh_p_abcl__dsm__adhd, 895
vars_mh_p_abcl__dsm__antsoc, 896

vars_mh_p_abcl__dsm__anx, 898
vars_mh_p_abcl__dsm__avoid, 899
vars_mh_p_abcl__dsm__dep, 900
vars_mh_p_abcl__dsm__somat, 902
vars_mh_p_abcl__su, 903
vars_mh_p_abcl__su__drg, 905
vars_mh_p_abcl__su__drunk, 906
vars_mh_p_abcl__su__nic, 907
vars_mh_p_abcl__synd__aggr, 908
vars_mh_p_abcl__synd__anxdep, 910
vars_mh_p_abcl__synd__attn, 911
vars_mh_p_abcl__synd__ext, 913
vars_mh_p_abcl__synd__int, 915
vars_mh_p_abcl__synd__intru, 917
vars_mh_p_abcl__synd__othpr, 918
vars_mh_p_abcl__synd__rule, 920
vars_mh_p_abcl__synd__som, 921
vars_mh_p_abcl__synd__tho, 923
vars_mh_p_abcl__synd__wthdr, 924
vars_mh_p_asr, 926
vars_mh_p_asr__afs__strng, 930
vars_mh_p_asr__critic, 931
vars_mh_p_asr__dsm__adhd, 933
vars_mh_p_asr__dsm__adhd__hypimp, 934
vars_mh_p_asr__dsm__adhd__inatt, 935
vars_mh_p_asr__dsm__antsoc, 937
vars_mh_p_asr__dsm__anx, 938
vars_mh_p_asr__dsm__avoid, 940
vars_mh_p_asr__dsm__dep, 941
vars_mh_p_asr__dsm__somat, 943
vars_mh_p_asr__synd__aggr, 944
vars_mh_p_asr__synd__anxdep, 945
vars_mh_p_asr__synd__attn, 947
vars_mh_p_asr__synd__ext, 948
vars_mh_p_asr__synd__int, 950
vars_mh_p_asr__synd__intru, 953
vars_mh_p_asr__synd__othpr, 954
vars_mh_p_asr__synd__rule, 956
vars_mh_p_asr__synd__som, 957
vars_mh_p_asr__synd__tho, 959
vars_mh_p_asr__synd__wthdr, 960
vars_mh_p_cbcl, 961
vars_mh_p_cbcl__dsm__adhd, 965
vars_mh_p_cbcl__dsm__anx, 967
vars_mh_p_cbcl__dsm__cond, 968
vars_mh_p_cbcl__dsm__dep, 970
vars_mh_p_cbcl__dsm__opp, 971
vars_mh_p_cbcl__dsm__somat, 972
vars_mh_p_cbcl__ocd, 974
vars_mh_p_cbcl__sct, 975
vars_mh_p_cbcl__strs, 976
vars_mh_p_cbcl__synd__aggr, 978
vars_mh_p_cbcl__synd__anxdep, 980
vars_mh_p_cbcl__synd__attn, 981
vars_mh_p_cbcl__synd__ext, 982
vars_mh_p_cbcl__synd__int, 984
vars_mh_p_cbcl__synd__othpr, 986
vars_mh_p_cbcl__synd__rule, 988
vars_mh_p_cbcl__synd__soc, 990
vars_mh_p_cbcl__synd__som, 991
vars_mh_p_cbcl__synd__tho, 992
vars_mh_p_cbcl__synd__wthdep, 994
vars_mh_p_ders__attun, 995
vars_mh_p_ders__catast, 997
vars_mh_p_ders__distract, 998
vars_mh_p_ders__negscnd, 1000
vars_mh_p_eatq__actv, 1001
vars_mh_p_eatq__affl, 1002
vars_mh_p_eatq__aggr, 1004
vars_mh_p_eatq__attn, 1005
vars_mh_p_eatq__depm, 1006
vars_mh_p_eatq__fear, 1008
vars_mh_p_eatq__frust, 1009
vars_mh_p_eatq__inhib, 1011
vars_mh_p_eatq__shy, 1012
vars_mh_p_eatq__surg, 1013
vars_mh_p_famhx__alc__moth__fath_indicator, 1015
vars_mh_p_famhx__alc__moth__fath_score, 1016
vars_mh_p_famhx__dep__moth__fath_indicator, 1017
vars_mh_p_famhx__dep__moth__fath_score, 1018
vars_mh_p_famhx__doc__moth__fath_indicator, 1019
vars_mh_p_famhx__doc__moth__fath_score, 1020
vars_mh_p_famhx__drg__moth__fath_indicator, 1021
vars_mh_p_famhx__drg__moth__fath_score, 1022
vars_mh_p_famhx__halluc__moth__fath_indicator, 1023

vars_mh_p_famhx__halluc__moth__fath_score, 1024
vars_mh_p_famhx__hosp__moth__fath_indicator, 1025
vars_mh_p_famhx__hosp__moth__fath_score, 1026
vars_mh_p_famhx__mania__moth__fath_indicator, 1028
vars_mh_p_famhx__mania__moth__fath_score, 1029
vars_mh_p_famhx__nerve__moth__fath_indicator, 1030
vars_mh_p_famhx__nerve__moth__fath_score, 1031
vars_mh_p_famhx__suic__moth__fath_indicator, 1032
vars_mh_p_famhx__suic__moth__fath_score, 1033
vars_mh_p_famhx__troub__moth__fath_indicator, 1034
vars_mh_p_famhx__troub__moth__fath_score, 1035
vars_mh_p_gbi, 1036
vars_mh_p_ksads__adhd__past__sx, 1038
vars_mh_p_ksads__adhd__pres__sx, 1039
vars_mh_p_ksads__agor__past__sx, 1041
vars_mh_p_ksads__agor__pres__sx, 1042
vars_mh_p_ksads__asd__past__sx, 1044
vars_mh_p_ksads__asd__pres__sx, 1045
vars_mh_p_ksads__bpd__past__sx, 1047
vars_mh_p_ksads__bpd__pres__sx, 1048
vars_mh_p_ksads__cond__past__sx, 1050
vars_mh_p_ksads__cond__pres__sx, 1052
vars_mh_p_ksads__dep__past__sx, 1053
vars_mh_p_ksads__dep__pres__sx, 1055
vars_mh_p_ksads__dmdd__sx, 1057
vars_mh_p_ksads__ed__past__sx, 1058
vars_mh_p_ksads__ed__pres__sx, 1059
vars_mh_p_ksads__gad__past__sx, 1061
vars_mh_p_ksads__gad__pres__sx, 1062
vars_mh_p_ksads__hom__past__sx, 1064
vars_mh_p_ksads__hom__pres__sx, 1065
vars_mh_p_ksads__ocd__past__sx, 1066
vars_mh_p_ksads__ocd__pres__sx, 1068
vars_mh_p_ksads__odd__past__sx, 1069
vars_mh_p_ksads__odd__pres__sx, 1071
vars_mh_p_ksads__panic__past__sx, 1072
vars_mh_p_ksads__panic__pres__sx, 1073
vars_mh_p_ksads__phobia__past__sx, 1075
vars_mh_p_ksads__phobia__pres__sx, 1076
vars_mh_p_ksads__psych__past__sx, 1077
vars_mh_p_ksads__psych__pres__sx, 1079
vars_mh_p_ksads__ptsd__past__sx, 1080
vars_mh_p_ksads__ptsd__pres__sx, 1082
vars_mh_p_ksads__sepanx__past__sx, 1084
vars_mh_p_ksads__sepanx__pres__sx, 1085
vars_mh_p_ksads__sleep__past__sx, 1087
vars_mh_p_ksads__sleep__pres__sx, 1088
vars_mh_p_ksads__socanx__past__sx, 1089
vars_mh_p_ksads__socanx__pres__sx, 1091

vars_mh_p_ksads__suic__past__sx, 1092
vars_mh_p_ksads__suic__pres__sx, 1094
vars_mh_p_ksads__tic__past__sx, 1095
vars_mh_p_ksads__tic__pres__sx, 1097
vars_mh_p_ple, 1098
vars_mh_p_ple__exp__v01, 1100
vars_mh_p_ple__exp__v02, 1102
vars_mh_p_ple__exp__v03, 1105
vars_mh_p_ple__exp__v04, 1108
vars_mh_p_ple__severity, 1110
vars_mh_p_ple__severity__v01, 1111
vars_mh_p_ple__severity__v02, 1113
vars_mh_p_ple__severity__v03, 1115
vars_mh_p_ple__severity__v04, 1117
vars_mh_p_ple__v01, 1118
vars_mh_p_ple__v02, 1120
vars_mh_p_ple__v03, 1122
vars_mh_p_ple__v04, 1124
vars_mh_p_ssrs, 1125
vars_mh_t_bpm, 1126
vars_mh_t_bpm__attn, 1128
vars_mh_t_bpm__ext, 1129
vars_mh_t_bpm__int, 1130
vars_mh_y_bisbas__bas__dr, 1132
vars_mh_y_bisbas__bas__fs, 1133
vars_mh_y_bisbas__bas__rr, 1134
vars_mh_y_bisbas__bas__rr__v01, 1135
vars_mh_y_bisbas__bis, 1137
vars_mh_y_bisbas__bis__v01, 1138
vars_mh_y_bpm, 1139
vars_mh_y_bpm__attn, 1141
vars_mh_y_bpm__ext, 1142
vars_mh_y_bpm__int, 1143
vars_mh_y_erq__reapp, 1144
vars_mh_y_erq__suppr, 1146
vars_mh_y_ksads__bpd__past__sx, 1147
vars_mh_y_ksads__bpd__pres__sx, 1149
vars_mh_y_ksads__cond__past__sx, 1150
vars_mh_y_ksads__cond__pres__sx, 1152
vars_mh_y_ksads__dep__past__sx, 1154
vars_mh_y_ksads__dep__pres__sx, 1155
vars_mh_y_ksads__dmdd__sx, 1157
vars_mh_y_ksads__ed__past__sx, 1158
vars_mh_y_ksads__ed__pres__sx, 1160
vars_mh_y_ksads__gad__past__sx, 1161
vars_mh_y_ksads__gad__pres__sx, 1163
vars_mh_y_ksads__ocd__past__sx, 1164
vars_mh_y_ksads__ocd__pres__sx, 1165
vars_mh_y_ksads__panic__past__sx, 1167
vars_mh_y_ksads__panic__pres__sx, 1168
vars_mh_y_ksads__ptsd__past__sx, 1170
vars_mh_y_ksads__ptsd__pres__sx, 1172
vars_mh_y_ksads__sleep__past__sx, 1174
vars_mh_y_ksads__sleep__pres__sx, 1175
vars_mh_y_ksads__socanx__past__sx, 1176
vars_mh_y_ksads__socanx__pres__sx, 1178
vars_mh_y_ksads__suic__past__sx, 1179
vars_mh_y_ksads__suic__pres__sx, 1181
vars_mh_y_pai, 1182
vars_mh_y_peq__overt__agg, 1184
vars_mh_y_peq__overt__vict, 1185
vars_mh_y_peq__rel__agg, 1186
vars_mh_y_peq__rel__vict, 1187
vars_mh_y_peq__rep__agg, 1188
vars_mh_y_peq__rep__vict, 1190
vars_mh_y_ple, 1191
vars_mh_y_ple__exp, 1192
vars_mh_y_ple__exp__v01, 1195
vars_mh_y_ple__exp__v02, 1197

vars_mh_y_ple__exp__v03, 1200
vars_mh_y_ple__severity, 1203
vars_mh_y_ple__severity__v01, 1204
vars_mh_y_ple__severity__v02, 1206
vars_mh_y_ple__severity__v03, 1208
vars_mh_y_ple__v01, 1210
vars_mh_y_ple__v02, 1212
vars_mh_y_ple__v03, 1214
vars_mh_y_pps__bother, 1216
vars_mh_y_pps__severity, 1217
vars_mh_y_pps_count, 1219
vars_mh_y_sup, 1221
vars_mh_y_upps__nurg, 1222
vars_mh_y_upps__pers, 1223
vars_mh_y_upps__plan, 1224
vars_mh_y_upps__purg, 1225
vars_mh_y_upps__sens, 1227
vars_mh_y_ysr, 1228
vars_mh_y_ysr__dsm__adhd, 1231
vars_mh_y_ysr__dsm__anx, 1233
vars_mh_y_ysr__dsm__cond, 1234
vars_mh_y_ysr__dsm__dep, 1236
vars_mh_y_ysr__dsm__opp, 1237
vars_mh_y_ysr__dsm__somat, 1238
vars_mh_y_ysr__pos, 1240
vars_mh_y_ysr__synd__aggr, 1241
vars_mh_y_ysr__synd__anxdep, 1243
vars_mh_y_ysr__synd__attn, 1244
vars_mh_y_ysr__synd__ext, 1246
vars_mh_y_ysr__synd__int, 1248
vars_mh_y_ysr__synd__othpr, 1249
vars_mh_y_ysr__synd__rule, 1251
vars_mh_y_ysr__synd__soc, 1252
vars_mh_y_ysr__synd__som, 1254
vars_mh_y_ysr__synd__tho, 1255
vars_mh_y_ysr__synd__wthdep, 1257
vars_nc_p_bdefs, 1258
vars_nc_y_ehis, 1260
vars_nt_p_yst__pmum, 1261
vars_nt_p_yst__screen__wkdy, 1262
vars_nt_p_yst__screen__wknd, 1263
vars_nt_y_stq__screen__wkdy, 1264
vars_nt_y_stq__screen__wknd, 1266
vars_ph_p_anthr__height, 1267
vars_ph_p_cna, 1268
vars_ph_p_dhx_birthweight, 1270
vars_ph_p_otbi, 1271
vars_ph_p_otbi__loc__30m_count, 1272
vars_ph_p_otbi__loc_before15, 1274
vars_ph_p_otbi__loc_count, 1276
vars_ph_p_otbi__loc_tbiage, 1277
vars_ph_p_otbi__rpt_count, 1280
vars_ph_p_otbi_tbiworst, 1281
vars_ph_p_pds__f, 1283
vars_ph_p_pds__f_categ, 1284
vars_ph_p_pds__m, 1286
vars_ph_p_pds__m_categ, 1287
vars_ph_p_sds__da, 1288
vars_ph_p_sds__dims, 1289
vars_ph_p_sds__does, 1291
vars_ph_p_sds__hyphy, 1292
vars_ph_p_sds__sbd, 1293
vars_ph_p_sds__swtd, 1295
vars_ph_p_sds_sum, 1296
vars_ph_y_anthr__height, 1298
vars_ph_y_anthr__weight, 1299
vars_ph_y_bp__dia, 1301
vars_ph_y_bp__hrate, 1302
vars_ph_y_bp__sys, 1303
vars_ph_y_pds__f, 1304
vars_ph_y_pds__f_categ, 1305
vars_ph_y_pds__m, 1306
vars_ph_y_pds__m_categ, 1308
vars_su_p_ksads__aud__past__sx, 1309
vars_su_p_ksads__aud__pres__sx, 1310
vars_su_p_ksads__dud__coc__past__sx_mean, 1312
vars_su_p_ksads__dud__coc__pres__sx_mean, 1314
vars_su_p_ksads__dud__hall__past__sx_mean, 1315
vars_su_p_ksads__dud__hall__pres__sx_mean, 1317
vars_su_p_ksads__dud__mj__past__sx_mean, 1319
vars_su_p_ksads__dud__mj__pres__sx_mean, 1320
vars_su_p_ksads__dud__nic__past__sx_mean, 1322
vars_su_p_ksads__dud__nic__pres__sx_mean, 1324
vars_su_p_ksads__dud__opi__past__sx_mean, 1325

vars_su_p_ksads__dud__opi__pres__sx_mean, 1327
vars_su_p_ksads__dud__othdrg__past__sx_mean, 1329
vars_su_p_ksads__dud__othdrg__pres__sx_mean, 1330
vars_su_p_ksads__dud__past__sx_mean, 1332
vars_su_p_ksads__dud__pcp__past__sx_mean, 1334
vars_su_p_ksads__dud__pcp__pres__sx_mean, 1335
vars_su_p_ksads__dud__pres__sx_mean, 1337
vars_su_p_ksads__dud__sed__past__sx_mean, 1339
vars_su_p_ksads__dud__sed__pres__sx_mean, 1340
vars_su_p_ksads__dud__solv__past__sx_mean, 1342
vars_su_p_ksads__dud__solv__pres__sx_mean, 1344
vars_su_p_ksads__dud__stim__past__sx_mean, 1345
vars_su_p_ksads__dud__stim__pres__sx_mean, 1347
vars_su_y_alcexp__neg, 1349
vars_su_y_alcexp__pos, 1350
vars_su_y_alchss, 1351
vars_su_y_alcprob, 1352
vars_su_y_alcsre__6mo, 1354
vars_su_y_alcsre__first5, 1355
vars_su_y_alcsre__hvy, 1356
vars_su_y_caff__coffee, 1357
vars_su_y_caff__energy, 1358
vars_su_y_caff__energy__drink, 1359
vars_su_y_caff__energy__shot, 1361
vars_su_y_caff__espres, 1362
vars_su_y_caff__oth, 1363
vars_su_y_caff__soda, 1364
vars_su_y_caff__suppl, 1365
vars_su_y_caff__tea, 1366
vars_su_y_cigexp__neg, 1367
vars_su_y_cigexp__pos, 1368
vars_su_y_drgprob, 1369
vars_su_y_ksads__aud__past__sx, 1371
vars_su_y_ksads__aud__pres__sx, 1372
vars_su_y_ksads__dud__coc__past__sx_mean, 1374
vars_su_y_ksads__dud__coc__pres__sx_mean, 1376
vars_su_y_ksads__dud__hall__past__sx_mean, 1377
vars_su_y_ksads__dud__hall__pres__sx_mean, 1379
vars_su_y_ksads__dud__mj__past__sx_mean, 1381
vars_su_y_ksads__dud__mj__pres__sx_mean, 1382
vars_su_y_ksads__dud__nic__past__sx_mean, 1384
vars_su_y_ksads__dud__nic__pres__sx_mean, 1386
vars_su_y_ksads__dud__opi__past__sx_mean, 1387
vars_su_y_ksads__dud__opi__pres__sx_mean, 1389
vars_su_y_ksads__dud__othdrg__past__sx_mean, 1391
vars_su_y_ksads__dud__othdrg__pres__sx_mean, 1392
vars_su_y_ksads__dud__past__sx_mean, 1394
vars_su_y_ksads__dud__pcp__past__sx_mean, 1396
vars_su_y_ksads__dud__pcp__pres__sx_mean, 1397
vars_su_y_ksads__dud__pres__sx_mean, 1399
vars_su_y_ksads__dud__sed__past__sx_mean, 1401
vars_su_y_ksads__dud__sed__pres__sx_mean, 1402
vars_su_y_ksads__dud__solv__past__sx_mean, 1404
vars_su_y_ksads__dud__solv__pres__sx_mean, 1406
vars_su_y_ksads__dud__stim__past__sx_mean, 1407
vars_su_y_ksads__dud__stim__pres__sx_mean, 1409
vars_su_y_mjexp__neg, 1411
vars_su_y_mjexp__pos, 1412

vars_su_y_mjprob, 1413
vars_su_y_mjsre, 1414
vars_su_y_mjsre__neg, 1415
vars_su_y_mjsre__pos, 1416
vars_su_y_nicsre__chew, 1417
vars_su_y_nicsre__cig, 1419
vars_su_y_nicsre__vape, 1420
vars_su_y_nicvapeexp__neg, 1421
vars_su_y_nicvapeexp__pos, 1422

check_assign_na, 24
combine_checkboxes, 25, *32*
combine_cols, 26
combine_levels, 27
compute_ab_g_dyn__cohort_edu__cgs (vars_ab_g_dyn__cohort_edu__cgs), 816
compute_ab_g_dyn__cohort_income__hhold__3lvl, 28
compute_ab_g_dyn__cohort_income__hhold__6lvl (vars_ab_g_dyn__cohort_income__hhold__6lvl), 817
compute_ab_g_dyn__cohort_income__hhold__6lvl(), *29*
compute_ab_g_dyn__cohort_prtnrshp__employ (vars_ab_g_dyn__cohort_prtnrshp__employ), 818
compute_ab_g_dyn_all, 29
compute_ab_g_stc__cohort_ethn (vars_ab_g_stc__cohort_ethn), 819
compute_ab_g_stc__cohort_ethnrace__leg (vars_ab_g_stc__cohort_ethnrace__leg), 820
compute_ab_g_stc__cohort_ethnrace__mblack (vars_ab_g_stc__cohort_ethnrace__mblack), 822
compute_ab_g_stc__cohort_ethnrace__meim (vars_ab_g_stc__cohort_ethnrace__meim), 824
compute_ab_g_stc__cohort_ethnrace__mhisp (vars_ab_g_stc__cohort_ethnrace__mhisp), 825
compute_ab_g_stc__cohort_race__nih (vars_ab_g_stc__cohort_race__nih), 827
compute_ab_g_stc_all, 30
compute_ab_p_demo__ntvam_all, 30
compute_ab_p_demo__ntvam_mean (vars_ab_p_demo__ntvam), 828
compute_age, 31
compute_famhx_endorsement, 31
compute_fc_p_fes__cohes_mean (vars_fc_p_fes__cohes), 830
compute_fc_p_fes__cohes_mean(), *34*
compute_fc_p_fes__cohes_nm, 33
compute_fc_p_fes__confl_mean (vars_fc_p_fes__confl), 831
compute_fc_p_fes__confl_mean(), *35*
compute_fc_p_fes__confl_nm, 34
compute_fc_p_fes__expr_mean (vars_fc_p_fes__expr), 832
compute_fc_p_fes__expr_mean(), *36*
compute_fc_p_fes__expr_nm, 35
compute_fc_p_fes__intelcult_mean (vars_fc_p_fes__intelcult), 833
compute_fc_p_fes__intelcult_mean(), *37*
compute_fc_p_fes__intelcult_nm, 36
compute_fc_p_fes__org_mean (vars_fc_p_fes__org), 835
compute_fc_p_fes__org_mean(), *38*
compute_fc_p_fes__org_nm, 37
compute_fc_p_fes__rec_mean (vars_fc_p_fes__rec), 836
compute_fc_p_fes__rec_mean(), *39*
compute_fc_p_fes__rec_nm, 38
compute_fc_p_fes_all, 39
compute_fc_p_meim__commattach_mean (vars_fc_p_meim__commattach), 838
compute_fc_p_meim__commattach_mean(), *40*
compute_fc_p_meim__commattach_nm, 39
compute_fc_p_meim__explor_mean (vars_fc_p_meim__explor), 839
compute_fc_p_meim__explor_mean(), *41*
compute_fc_p_meim__explor_nm, 40
compute_fc_p_meim_all, 41
compute_fc_p_meim_mean (vars_fc_p_meim), 837
compute_fc_p_meim_mean(), *42*
compute_fc_p_meim_nm, 42
compute_fc_p_nce__cc_mean (vars_fc_p_nce__cc), 841
compute_fc_p_nce__cc_mean(), *43*
compute_fc_p_nce__cc_nm, 43

compute_fc_p_nce__isc_mean
(vars_fc_p_nce__isc), 842
compute_fc_p_nce__isc_mean(), *44*
compute_fc_p_nce__isc_nm, 44
compute_fc_p_nce_all, 45
compute_fc_p_nce_mean (vars_fc_p_nce), 840
compute_fc_p_nce_mean(), *46*
compute_fc_p_nce_nm, 45
compute_fc_p_nsc__ns_mean
(vars_fc_p_nsc__ns), 843
compute_fc_p_nsc__ns_mean(), *47*
compute_fc_p_nsc__ns_nm, 46
compute_fc_p_nsc_all, 47
compute_fc_p_pk__knowl_mean
(vars_fc_p_pk__knowl), 844
compute_fc_p_pk__knowl_mean(), *48*
compute_fc_p_pk__knowl_nm, 48
compute_fc_p_pk_all, 49
compute_fc_p_psb_all, 49
compute_fc_p_psb_mean (vars_fc_p_psb), 845
compute_fc_p_psb_mean(), *50*
compute_fc_p_psb_nm, 50
compute_fc_p_vs__famil_mean
(vars_fc_p_vs__famil), 846
compute_fc_p_vs__famil_mean(), *52*, *849*
compute_fc_p_vs__famil_mean__v01
(vars_fc_p_vs__famil__v01), 848
compute_fc_p_vs__famil_mean__v01(), *53*
compute_fc_p_vs__famil_nm, 51
compute_fc_p_vs__famil_nm__v01, 52
compute_fc_p_vs__indselfrel_mean
(vars_fc_p_vs__indselfrel), 849
compute_fc_p_vs__indselfrel_mean(), *54*
compute_fc_p_vs__indselfrel_nm, 53
compute_fc_p_vs__obl_mean
(vars_fc_p_vs__obl), 851
compute_fc_p_vs__obl_mean(), *55*
compute_fc_p_vs__obl_nm, 54
compute_fc_p_vs__ref_mean
(vars_fc_p_vs__ref), 852
compute_fc_p_vs__ref_mean(), *56*
compute_fc_p_vs__ref_nm, 55
compute_fc_p_vs__relig_mean
(vars_fc_p_vs__relig), 853
compute_fc_p_vs__relig_mean(), *57*
compute_fc_p_vs__relig_nm, 56
compute_fc_p_vs__supp_mean
(vars_fc_p_vs__supp), 854
compute_fc_p_vs__supp_mean(), *58*
compute_fc_p_vs__supp_nm, 57
compute_fc_p_vs_all, 58
compute_fc_y_as__safe_mean
(vars_fc_y_as__safe), 855
compute_fc_y_as__safe_mean(), *59*
compute_fc_y_as__safe_nm, 59
compute_fc_y_as_all, 60
compute_fc_y_crpbi__cg1_mean
(vars_fc_y_crpbi__cg1), 856
compute_fc_y_crpbi__cg1_mean(), *61*
compute_fc_y_crpbi__cg1_nm, 60
compute_fc_y_crpbi__cg2_mean
(vars_fc_y_crpbi__cg2), 857
compute_fc_y_crpbi__cg2_mean(), *62*
compute_fc_y_crpbi__cg2_nm, 61
compute_fc_y_crpbi_all, 62
compute_fc_y_eut__ethn_mean
(vars_fc_y_eut__ethn), 858
compute_fc_y_eut__ethn_mean(), *63*
compute_fc_y_eut__ethn_nm, 63
compute_fc_y_eut_all, 64
compute_fc_y_fes__cohes_mean
(vars_fc_y_fes__cohes), 859
compute_fc_y_fes__cohes_mean(), *65*
compute_fc_y_fes__cohes_nm, 64
compute_fc_y_fes__confl_mean
(vars_fc_y_fes__confl), 861
compute_fc_y_fes__confl_mean(), *66*
compute_fc_y_fes__confl_nm, 65
compute_fc_y_fes_all, 66
compute_fc_y_lone_all, 67
compute_fc_y_lone_mean
(vars_fc_y_lone), 862
compute_fc_y_lone_mean(), *68*
compute_fc_y_lone_nm, 68
compute_fc_y_meim__commattach_mean
(vars_fc_y_meim__commattach), 864
compute_fc_y_meim__commattach_mean(), *69*
compute_fc_y_meim__commattach_nm, 69
compute_fc_y_meim__explor_mean
(vars_fc_y_meim__explor), 865
compute_fc_y_meim__explor_mean(), *70*
compute_fc_y_meim__explor_nm, 70

compute_fc_y_meim_all, 71
compute_fc_y_meim_mean
(vars_fc_y_meim), 863
compute_fc_y_meim_mean(), *72*
compute_fc_y_meim_nm, 71
compute_fc_y_mnbs__edusupp_mean
(vars_fc_y_mnbs__edusupp), 867
compute_fc_y_mnbs__edusupp_mean(), *73*
compute_fc_y_mnbs__edusupp_nm, 72
compute_fc_y_mnbs__superv_mean
(vars_fc_y_mnbs__superv), 868
compute_fc_y_mnbs__superv_mean(), *74*
compute_fc_y_mnbs__superv_nm, 73
compute_fc_y_mnbs_all, 74
compute_fc_y_mnbs_mean
(vars_fc_y_mnbs), 866
compute_fc_y_mnbs_mean(), *75*
compute_fc_y_mnbs_nm, 75
compute_fc_y_naa_all, 76
compute_fc_y_naa_mean (vars_fc_y_naa), 869
compute_fc_y_pm_all, 76
compute_fc_y_pm_mean (vars_fc_y_pm), 870
compute_fc_y_pm_mean(), *77*
compute_fc_y_pm_nm, 77
compute_fc_y_pnh_all, 78
compute_fc_y_pnh_nm, 78
compute_fc_y_pnh_sum (vars_fc_y_pnh), 871
compute_fc_y_pnh_sum(), *79*
compute_fc_y_psb_all, 79
compute_fc_y_psb_mean (vars_fc_y_psb), 872
compute_fc_y_psb_mean(), *80*
compute_fc_y_psb_nm, 80
compute_fc_y_rpi_all, 81
compute_fc_y_rpi_mean (vars_fc_y_rpi), 873
compute_fc_y_rpi_mean(), *82*
compute_fc_y_rpi_nm, 81
compute_fc_y_srpf__dis_mean
(vars_fc_y_srpf__dis), 874
compute_fc_y_srpf__dis_mean(), *83*
compute_fc_y_srpf__dis_nm, 82
compute_fc_y_srpf__env_mean
(vars_fc_y_srpf__env), 875
compute_fc_y_srpf__env_mean(), *84*
compute_fc_y_srpf__env_nm, 83
compute_fc_y_srpf__involv_mean
(vars_fc_y_srpf__involv), 876
compute_fc_y_srpf__involv_mean(), *85*
compute_fc_y_srpf__involv_nm, 84
compute_fc_y_srpf_all, 85
compute_fc_y_vs__famil_mean
(vars_fc_y_vs__famil), 878
compute_fc_y_vs__famil_mean(), *87*, *880*
compute_fc_y_vs__famil_mean__v01
(vars_fc_y_vs__famil__v01), 879
compute_fc_y_vs__famil_mean__v01(), *88*
compute_fc_y_vs__famil_nm, 86
compute_fc_y_vs__famil_nm__v01, 87
compute_fc_y_vs__indselfrel_mean
(vars_fc_y_vs__indselfrel), 880
compute_fc_y_vs__indselfrel_mean(), *89*
compute_fc_y_vs__indselfrel_nm, 88
compute_fc_y_vs__obl_mean
(vars_fc_y_vs__obl), 882
compute_fc_y_vs__obl_mean(), *90*
compute_fc_y_vs__obl_nm, 89
compute_fc_y_vs__ref_mean
(vars_fc_y_vs__ref), 883
compute_fc_y_vs__ref_mean(), *91*
compute_fc_y_vs__ref_nm, 90
compute_fc_y_vs__relig_mean
(vars_fc_y_vs__relig), 884
compute_fc_y_vs__relig_mean(), *92*
compute_fc_y_vs__relig_nm, 91
compute_fc_y_vs__supp_mean
(vars_fc_y_vs__supp), 885
compute_fc_y_vs__supp_mean(), *93*
compute_fc_y_vs__supp_nm, 92
compute_fc_y_vs_all, 93
compute_fc_y_wpss_all, 94
compute_fc_y_wpss_mean
(vars_fc_y_wpss), 886
compute_fc_y_wpss_mean(), *95*
compute_fc_y_wpss_nm, 94
compute_fitbit_activity_table, 95
compute_fitbit_activity_table(), *98*
compute_fitbit_activity_table_ext, 97
compute_fitbit_activity_week, 99
compute_fitbit_sleep_table, 100
compute_fitbit_sleep_table_ext, 102
compute_fitbit_sleep_week, 105
compute_fitbit_weekly_summary, 106
compute_mh_p_abcl__afs__frnd_nm

(vars_mh_p_abcl__afs__frnd), 891
compute_mh_p_abcl__afs__frnd_nm(), *108*, *109*
compute_mh_p_abcl__afs__frnd_sum, 107
compute_mh_p_abcl__afs__frnd_tscore, 108
compute_mh_p_abcl__cg2_sex (vars_mh_p_abcl__cg2), 892
compute_mh_p_abcl__critic_nm (vars_mh_p_abcl__critic), 893
compute_mh_p_abcl__critic_nm(), *111*, *113*
compute_mh_p_abcl__critic_sum, 110
compute_mh_p_abcl__critic_tscore, 111
compute_mh_p_abcl__dsm__adhd_nm (vars_mh_p_abcl__dsm__adhd), 895
compute_mh_p_abcl__dsm__adhd_nm(), *114*, *116*
compute_mh_p_abcl__dsm__adhd_sum, 113
compute_mh_p_abcl__dsm__adhd_tscore, 114
compute_mh_p_abcl__dsm__antsoc_nm (vars_mh_p_abcl__dsm__antsoc), 896
compute_mh_p_abcl__dsm__antsoc_nm(), *117*, *119*
compute_mh_p_abcl__dsm__antsoc_sum, 116
compute_mh_p_abcl__dsm__antsoc_tscore, 118
compute_mh_p_abcl__dsm__anx_nm (vars_mh_p_abcl__dsm__anx), 898
compute_mh_p_abcl__dsm__anx_nm(), *121*, *122*
compute_mh_p_abcl__dsm__anx_sum, 120
compute_mh_p_abcl__dsm__anx_tscore, 121
compute_mh_p_abcl__dsm__avoid_nm (vars_mh_p_abcl__dsm__avoid), 899
compute_mh_p_abcl__dsm__avoid_nm(), *124*, *125*
compute_mh_p_abcl__dsm__avoid_sum, 123
compute_mh_p_abcl__dsm__avoid_tscore, 124
compute_mh_p_abcl__dsm__dep_nm (vars_mh_p_abcl__dsm__dep), 900
compute_mh_p_abcl__dsm__dep_nm(), *127*, *129*
compute_mh_p_abcl__dsm__dep_sum, 126
compute_mh_p_abcl__dsm__dep_tscore, 127
compute_mh_p_abcl__dsm__somat_nm (vars_mh_p_abcl__dsm__somat), 902
compute_mh_p_abcl__dsm__somat_nm(), *130*, *131*
compute_mh_p_abcl__dsm__somat_sum, 129
compute_mh_p_abcl__dsm__somat_tscore, 130
compute_mh_p_abcl__su__drg_nm (vars_mh_p_abcl__su__drg), 905
compute_mh_p_abcl__su__drg_nm(), *133*, *134*
compute_mh_p_abcl__su__drg_sum, 132
compute_mh_p_abcl__su__drg_tscore, 133
compute_mh_p_abcl__su__drunk_nm (vars_mh_p_abcl__su__drunk), 906
compute_mh_p_abcl__su__drunk_nm(), *135*, *136*
compute_mh_p_abcl__su__drunk_sum, 134
compute_mh_p_abcl__su__drunk_tscore, 135
compute_mh_p_abcl__su__nic_nm (vars_mh_p_abcl__su__nic), 907
compute_mh_p_abcl__su__nic_nm(), *138*, *139*
compute_mh_p_abcl__su__nic_sum, 137
compute_mh_p_abcl__su__nic_tscore, 138
compute_mh_p_abcl__su_nm (vars_mh_p_abcl__su), 903
compute_mh_p_abcl__su_nm(), *140*, *142*
compute_mh_p_abcl__su_sum, 139
compute_mh_p_abcl__su_tscore, 141
compute_mh_p_abcl__synd__aggr_nm (vars_mh_p_abcl__synd__aggr), 908
compute_mh_p_abcl__synd__aggr_nm(), *143*, *145*
compute_mh_p_abcl__synd__aggr_sum, 142
compute_mh_p_abcl__synd__aggr_tscore, 144
compute_mh_p_abcl__synd__anxdep_nm

(vars_mh_p_abcl__synd__anxdep), 910
compute_mh_p_abcl__synd__anxdep_nm(), *146*, *148*
compute_mh_p_abcl__synd__anxdep_sum, 145
compute_mh_p_abcl__synd__anxdep_tscore, 147
compute_mh_p_abcl__synd__attn_nm (vars_mh_p_abcl__synd__attn), 911
compute_mh_p_abcl__synd__attn_nm(), *150*, *152*
compute_mh_p_abcl__synd__attn_sum, 149
compute_mh_p_abcl__synd__attn_tscore, 150
compute_mh_p_abcl__synd__ext_nm (vars_mh_p_abcl__synd__ext), 913
compute_mh_p_abcl__synd__ext_nm(), *154*, *156*
compute_mh_p_abcl__synd__ext_sum, 152
compute_mh_p_abcl__synd__ext_tscore, 154
compute_mh_p_abcl__synd__int_nm (vars_mh_p_abcl__synd__int), 915
compute_mh_p_abcl__synd__int_nm(), *158*, *160*
compute_mh_p_abcl__synd__int_sum, 156
compute_mh_p_abcl__synd__int_tscore, 158
compute_mh_p_abcl__synd__intru_nm (vars_mh_p_abcl__synd__intru), 917
compute_mh_p_abcl__synd__intru_nm(), *161*, *163*
compute_mh_p_abcl__synd__intru_sum, 160
compute_mh_p_abcl__synd__intru_tscore, 161
compute_mh_p_abcl__synd__othpr_nm (vars_mh_p_abcl__synd__othpr), 918
compute_mh_p_abcl__synd__othpr_nm(), *164*
compute_mh_p_abcl__synd__othpr_sum, 163
compute_mh_p_abcl__synd__rule_nm (vars_mh_p_abcl__synd__rule), 920
compute_mh_p_abcl__synd__rule_nm(), *166*, *167*
compute_mh_p_abcl__synd__rule_sum, 165
compute_mh_p_abcl__synd__rule_tscore, 166
compute_mh_p_abcl__synd__som_nm (vars_mh_p_abcl__synd__som), 921
compute_mh_p_abcl__synd__som_nm(), *169*, *170*
compute_mh_p_abcl__synd__som_sum, 168
compute_mh_p_abcl__synd__som_tscore, 169
compute_mh_p_abcl__synd__tho_nm (vars_mh_p_abcl__synd__tho), 923
compute_mh_p_abcl__synd__tho_nm(), *172*, *173*
compute_mh_p_abcl__synd__tho_sum, 171
compute_mh_p_abcl__synd__tho_tscore, 172
compute_mh_p_abcl__synd__wthdr_nm (vars_mh_p_abcl__synd__wthdr), 924
compute_mh_p_abcl__synd__wthdr_nm(), *175*, *176*
compute_mh_p_abcl__synd__wthdr_sum, 174
compute_mh_p_abcl__synd__wthdr_tscore, 175
compute_mh_p_abcl_all, 177
compute_mh_p_abcl_nm (vars_mh_p_abcl), 887
compute_mh_p_abcl_nm(), *181*, *185*
compute_mh_p_abcl_sum, 178
compute_mh_p_abcl_tscore, 182
compute_mh_p_asr__afs__strng_nm (vars_mh_p_asr__afs__strng), 930
compute_mh_p_asr__afs__strng_nm(), *187*
compute_mh_p_asr__afs__strng_sum, 186
compute_mh_p_asr__critic_nm (vars_mh_p_asr__critic), 931
compute_mh_p_asr__critic_nm(), *188*
compute_mh_p_asr__critic_sum, 187

compute_mh_p_asr__dsm__adhd__hypimp_nm (vars_mh_p_asr__dsm__adhd__hypimp), 934
compute_mh_p_asr__dsm__adhd__hypimp_nm(), *190*
compute_mh_p_asr__dsm__adhd__hypimp_sum, 189
compute_mh_p_asr__dsm__adhd__inatt_nm (vars_mh_p_asr__dsm__adhd__inatt), 935
compute_mh_p_asr__dsm__adhd__inatt_nm(), *191*
compute_mh_p_asr__dsm__adhd__inatt_sum, 190
compute_mh_p_asr__dsm__adhd_nm (vars_mh_p_asr__dsm__adhd), 933
compute_mh_p_asr__dsm__adhd_nm(), *193*
compute_mh_p_asr__dsm__adhd_sum, 192
compute_mh_p_asr__dsm__antsoc_nm (vars_mh_p_asr__dsm__antsoc), 937
compute_mh_p_asr__dsm__antsoc_nm(), *194*
compute_mh_p_asr__dsm__antsoc_sum, 193
compute_mh_p_asr__dsm__anx_nm (vars_mh_p_asr__dsm__anx), 938
compute_mh_p_asr__dsm__anx_nm(), *196*
compute_mh_p_asr__dsm__anx_sum, 195
compute_mh_p_asr__dsm__avoid_nm (vars_mh_p_asr__dsm__avoid), 940
compute_mh_p_asr__dsm__avoid_nm(), *197*
compute_mh_p_asr__dsm__avoid_sum, 196
compute_mh_p_asr__dsm__dep_nm (vars_mh_p_asr__dsm__dep), 941
compute_mh_p_asr__dsm__dep_nm(), *199*
compute_mh_p_asr__dsm__dep_sum, 198
compute_mh_p_asr__dsm__somat_nm (vars_mh_p_asr__dsm__somat), 943
compute_mh_p_asr__dsm__somat_nm(), *200*
compute_mh_p_asr__dsm__somat_sum, 199
compute_mh_p_asr__synd__aggr_nm (vars_mh_p_asr__synd__aggr), 944
compute_mh_p_asr__synd__aggr_nm(), *202*
compute_mh_p_asr__synd__aggr_sum, 201
compute_mh_p_asr__synd__anxdep_nm (vars_mh_p_asr__synd__anxdep), 945
compute_mh_p_asr__synd__anxdep_nm(), *203*
compute_mh_p_asr__synd__anxdep_sum, 202
compute_mh_p_asr__synd__attn_nm (vars_mh_p_asr__synd__attn), 947
compute_mh_p_asr__synd__attn_nm(), *205*
compute_mh_p_asr__synd__attn_sum, 204
compute_mh_p_asr__synd__ext_nm (vars_mh_p_asr__synd__ext), 948
compute_mh_p_asr__synd__ext_nm(), *207*
compute_mh_p_asr__synd__ext_sum, 205
compute_mh_p_asr__synd__int_nm (vars_mh_p_asr__synd__int), 950
compute_mh_p_asr__synd__int_nm(), *209*
compute_mh_p_asr__synd__int_sum, 207
compute_mh_p_asr__synd__intru_nm (vars_mh_p_asr__synd__intru), 953
compute_mh_p_asr__synd__intru_nm(), *211*
compute_mh_p_asr__synd__intru_sum, 210
compute_mh_p_asr__synd__othpr_nm (vars_mh_p_asr__synd__othpr), 954
compute_mh_p_asr__synd__othpr_nm(), *212*
compute_mh_p_asr__synd__othpr_sum, 211
compute_mh_p_asr__synd__rule_nm (vars_mh_p_asr__synd__rule), 956
compute_mh_p_asr__synd__rule_nm(), *214*
compute_mh_p_asr__synd__rule_sum, 213
compute_mh_p_asr__synd__som_nm (vars_mh_p_asr__synd__som), 957
compute_mh_p_asr__synd__som_nm(), *215*
compute_mh_p_asr__synd__som_sum, 214
compute_mh_p_asr__synd__tho_nm (vars_mh_p_asr__synd__tho), 959
compute_mh_p_asr__synd__tho_nm(), *217*
compute_mh_p_asr__synd__tho_sum, 216
compute_mh_p_asr__synd__wthdr_nm (vars_mh_p_asr__synd__wthdr), 960
compute_mh_p_asr__synd__wthdr_nm(),

218
compute_mh_p_asr__synd__wthdr_sum, 217
compute_mh_p_asr_all, 219
compute_mh_p_asr_nm *(*vars_mh_p_asr*)*, 926
compute_mh_p_asr_nm(), *223*
compute_mh_p_asr_sum, 219
compute_mh_p_cbcl__dsm__adhd_nm *(*vars_mh_p_cbcl__dsm__adhd*)*, 965
compute_mh_p_cbcl__dsm__adhd_nm(), *224*, *226*
compute_mh_p_cbcl__dsm__adhd_sum, 223
compute_mh_p_cbcl__dsm__adhd_tscore, 225
compute_mh_p_cbcl__dsm__anx_nm *(*vars_mh_p_cbcl__dsm__anx*)*, 967
compute_mh_p_cbcl__dsm__anx_nm(), *227*, *229*
compute_mh_p_cbcl__dsm__anx_sum, 226
compute_mh_p_cbcl__dsm__anx_tscore, 228
compute_mh_p_cbcl__dsm__cond_nm *(*vars_mh_p_cbcl__dsm__cond*)*, 968
compute_mh_p_cbcl__dsm__cond_nm(), *230*, *232*
compute_mh_p_cbcl__dsm__cond_sum, 229
compute_mh_p_cbcl__dsm__cond_tscore, 231
compute_mh_p_cbcl__dsm__dep_nm *(*vars_mh_p_cbcl__dsm__dep*)*, 970
compute_mh_p_cbcl__dsm__dep_nm(), *234*, *235*
compute_mh_p_cbcl__dsm__dep_sum, 233
compute_mh_p_cbcl__dsm__dep_tscore, 234
compute_mh_p_cbcl__dsm__opp_nm *(*vars_mh_p_cbcl__dsm__opp*)*, 971
compute_mh_p_cbcl__dsm__opp_nm(), *237*, *238*
compute_mh_p_cbcl__dsm__opp_sum, 236
compute_mh_p_cbcl__dsm__opp_tscore, 237
compute_mh_p_cbcl__dsm__somat_nm *(*vars_mh_p_cbcl__dsm__somat*)*, 972
compute_mh_p_cbcl__dsm__somat_nm(), *240*, *241*
compute_mh_p_cbcl__dsm__somat_sum, 239
compute_mh_p_cbcl__dsm__somat_tscore, 240
compute_mh_p_cbcl__ocd_nm *(*vars_mh_p_cbcl__ocd*)*, 974
compute_mh_p_cbcl__ocd_nm(), *243*, *244*
compute_mh_p_cbcl__ocd_sum, 242
compute_mh_p_cbcl__ocd_tscore, 243
compute_mh_p_cbcl__sct_nm *(*vars_mh_p_cbcl__sct*)*, 975
compute_mh_p_cbcl__sct_nm(), *246*, *247*
compute_mh_p_cbcl__sct_sum, 245
compute_mh_p_cbcl__sct_tscore, 246
compute_mh_p_cbcl__strs_nm *(*vars_mh_p_cbcl__strs*)*, 976
compute_mh_p_cbcl__strs_nm(), *248*, *250*
compute_mh_p_cbcl__strs_sum, 247
compute_mh_p_cbcl__strs_tscore, 249
compute_mh_p_cbcl__synd__aggr_nm *(*vars_mh_p_cbcl__synd__aggr*)*, 978
compute_mh_p_cbcl__synd__aggr_nm(), *252*, *254*
compute_mh_p_cbcl__synd__aggr_sum, 251
compute_mh_p_cbcl__synd__aggr_tscore, 252
compute_mh_p_cbcl__synd__anxdep_nm *(*vars_mh_p_cbcl__synd__anxdep*)*, 980
compute_mh_p_cbcl__synd__anxdep_nm(), *255*, *257*
compute_mh_p_cbcl__synd__anxdep_sum, 254
compute_mh_p_cbcl__synd__anxdep_tscore, 255
compute_mh_p_cbcl__synd__attn_nm *(*vars_mh_p_cbcl__synd__attn*)*, 981
compute_mh_p_cbcl__synd__attn_nm(), *258*, *260*
compute_mh_p_cbcl__synd__attn_sum, 257
compute_mh_p_cbcl__synd__attn_tscore, 259
compute_mh_p_cbcl__synd__ext_nm *(*vars_mh_p_cbcl__synd__ext*)*, 982
compute_mh_p_cbcl__synd__ext_nm(), *262*, *264*

compute_mh_p_cbcl__synd__ext_sum, 260
compute_mh_p_cbcl__synd__ext_tscore, 262
compute_mh_p_cbcl__synd__int_nm (vars_mh_p_cbcl__synd__int), 984
compute_mh_p_cbcl__synd__int_nm(), *266*, *268*
compute_mh_p_cbcl__synd__int_sum, 264
compute_mh_p_cbcl__synd__int_tscore, 266
compute_mh_p_cbcl__synd__othpr_nm (vars_mh_p_cbcl__synd__othpr), 986
compute_mh_p_cbcl__synd__othpr_nm(), *269*
compute_mh_p_cbcl__synd__othpr_sum, 268
compute_mh_p_cbcl__synd__rule_nm (vars_mh_p_cbcl__synd__rule), 988
compute_mh_p_cbcl__synd__rule_nm(), *271*, *273*
compute_mh_p_cbcl__synd__rule_sum, 270
compute_mh_p_cbcl__synd__rule_tscore, 271
compute_mh_p_cbcl__synd__soc_nm (vars_mh_p_cbcl__synd__soc), 990
compute_mh_p_cbcl__synd__soc_nm(), *274*, *276*
compute_mh_p_cbcl__synd__soc_sum, 273
compute_mh_p_cbcl__synd__soc_tscore, 275
compute_mh_p_cbcl__synd__som_nm (vars_mh_p_cbcl__synd__som), 991
compute_mh_p_cbcl__synd__som_nm(), *277*, *279*
compute_mh_p_cbcl__synd__som_sum, 276
compute_mh_p_cbcl__synd__som_tscore, 278
compute_mh_p_cbcl__synd__tho_nm (vars_mh_p_cbcl__synd__tho), 992
compute_mh_p_cbcl__synd__tho_nm(), *280*, *282*
compute_mh_p_cbcl__synd__tho_sum, 279
compute_mh_p_cbcl__synd__tho_tscore, 281
compute_mh_p_cbcl__synd__wthdep_nm (vars_mh_p_cbcl__synd__wthdep), 994
compute_mh_p_cbcl__synd__wthdep_nm(), *284*, *285*
compute_mh_p_cbcl__synd__wthdep_sum, 283
compute_mh_p_cbcl__synd__wthdep_tscore, 284
compute_mh_p_cbcl_all, 286
compute_mh_p_cbcl_nm (vars_mh_p_cbcl), 961
compute_mh_p_cbcl_nm(), *290*, *294*
compute_mh_p_cbcl_sum, 286
compute_mh_p_cbcl_tscore, 290
compute_mh_p_ders__attun_mean (vars_mh_p_ders__attun), 995
compute_mh_p_ders__attun_mean(), *295*
compute_mh_p_ders__attun_nm, 294
compute_mh_p_ders__catast_mean (vars_mh_p_ders__catast), 997
compute_mh_p_ders__catast_mean(), *297*
compute_mh_p_ders__catast_nm, 296
compute_mh_p_ders__distract_mean (vars_mh_p_ders__distract), 998
compute_mh_p_ders__distract_mean(), *298*
compute_mh_p_ders__distract_nm, 297
compute_mh_p_ders__negscnd_mean (vars_mh_p_ders__negscnd), 1000
compute_mh_p_ders__negscnd_mean(), *299*
compute_mh_p_ders__negscnd_nm, 298
compute_mh_p_ders_all, 299
compute_mh_p_eatq__actv_mean (vars_mh_p_eatq__actv), 1001
compute_mh_p_eatq__actv_mean(), *301*
compute_mh_p_eatq__actv_nm, 300
compute_mh_p_eatq__affl_mean (vars_mh_p_eatq__affl), 1002
compute_mh_p_eatq__affl_mean(), *302*
compute_mh_p_eatq__affl_nm, 301
compute_mh_p_eatq__aggr_mean (vars_mh_p_eatq__aggr), 1004
compute_mh_p_eatq__aggr_mean(), *303*
compute_mh_p_eatq__aggr_nm, 302
compute_mh_p_eatq__attn_mean

(vars_mh_p_eatq__attn), 1005
compute_mh_p_eatq__attn_mean(), *304*
compute_mh_p_eatq__attn_nm, 303
compute_mh_p_eatq__depm_mean (vars_mh_p_eatq__depm), 1006
compute_mh_p_eatq__depm_mean(), *305*
compute_mh_p_eatq__depm_nm, 304
compute_mh_p_eatq__fear_mean (vars_mh_p_eatq__fear), 1008
compute_mh_p_eatq__fear_mean(), *306*
compute_mh_p_eatq__fear_nm, 305
compute_mh_p_eatq__frust_mean (vars_mh_p_eatq__frust), 1009
compute_mh_p_eatq__frust_mean(), *307*
compute_mh_p_eatq__frust_nm, 306
compute_mh_p_eatq__inhib_mean (vars_mh_p_eatq__inhib), 1011
compute_mh_p_eatq__inhib_mean(), *308*
compute_mh_p_eatq__inhib_nm, 307
compute_mh_p_eatq__shy_mean (vars_mh_p_eatq__shy), 1012
compute_mh_p_eatq__shy_mean(), *309*
compute_mh_p_eatq__shy_nm, 308
compute_mh_p_eatq__ss__efcon_mean, 309
compute_mh_p_eatq__ss__efcon_mean(), *312*
compute_mh_p_eatq__ss__efcon_nm, 310
compute_mh_p_eatq__ss__negaff_mean, 312
compute_mh_p_eatq__ss__negaff_mean(), *314*
compute_mh_p_eatq__ss__negaff_nm, 313
compute_mh_p_eatq__ss__surg_mean, 315
compute_mh_p_eatq__ss__surg_mean(), *317*
compute_mh_p_eatq__ss__surg_nm, 316
compute_mh_p_eatq__surg_mean (vars_mh_p_eatq__surg), 1013
compute_mh_p_eatq__surg_mean(), *318*
compute_mh_p_eatq__surg_nm, 317
compute_mh_p_eatq_all, 318
compute_mh_p_famhx__alc__moth__fath_indicator (vars_mh_p_famhx__alc__moth__fath_indicator), 1015
compute_mh_p_famhx__alc__moth__fath_score (vars_mh_p_famhx__alc__moth__fath_score), 1016
compute_mh_p_famhx__dep__moth__fath_indicator (vars_mh_p_famhx__dep__moth__fath_indicator), 1017
compute_mh_p_famhx__dep__moth__fath_score (vars_mh_p_famhx__dep__moth__fath_score), 1018
compute_mh_p_famhx__doc__moth__fath_indicator (vars_mh_p_famhx__doc__moth__fath_indicator), 1019
compute_mh_p_famhx__doc__moth__fath_score (vars_mh_p_famhx__doc__moth__fath_score), 1020
compute_mh_p_famhx__drg__moth__fath_indicator (vars_mh_p_famhx__drg__moth__fath_indicator), 1021
compute_mh_p_famhx__drg__moth__fath_score (vars_mh_p_famhx__drg__moth__fath_score), 1022
compute_mh_p_famhx__halluc__moth__fath_indicator (vars_mh_p_famhx__halluc__moth__fath_indicator), 1023
compute_mh_p_famhx__halluc__moth__fath_score (vars_mh_p_famhx__halluc__moth__fath_score), 1024
compute_mh_p_famhx__hosp__moth__fath_indicator (vars_mh_p_famhx__hosp__moth__fath_indicator), 1025
compute_mh_p_famhx__hosp__moth__fath_score (vars_mh_p_famhx__hosp__moth__fath_score), 1026
compute_mh_p_famhx__mania__moth__fath_indicator (vars_mh_p_famhx__mania__moth__fath_indicator), 1028
compute_mh_p_famhx__mania__moth__fath_score (vars_mh_p_famhx__mania__moth__fath_score), 1029
compute_mh_p_famhx__nerve__moth__fath_indicator (vars_mh_p_famhx__nerve__moth__fath_indicator), 1030
compute_mh_p_famhx__nerve__moth__fath_score (vars_mh_p_famhx__nerve__moth__fath_score), 1031
compute_mh_p_famhx__suic__moth__fath_indicator (vars_mh_p_famhx__suic__moth__fath_indicator), 1032
compute_mh_p_famhx__suic__moth__fath_score (vars_mh_p_famhx__suic__moth__fath_score), 1033
compute_mh_p_famhx__troub__moth__fath_indicator

(vars_mh_p_famhx__troub__moth__fath_indicator), 1034
compute_mh_p_famhx__troub__moth__fath_score (vars_mh_p_famhx__troub__moth__fath_score), 1035
compute_mh_p_famhx_all, 319
compute_mh_p_gbi_all, 320
compute_mh_p_gbi_nm (vars_mh_p_gbi), 1036
compute_mh_p_gbi_nm(), *321*
compute_mh_p_gbi_sum, 320
compute_mh_p_ksads__adhd__past__sx_mean (vars_mh_p_ksads__adhd__past__sx), 1038
compute_mh_p_ksads__adhd__pres__sx_mean (vars_mh_p_ksads__adhd__pres__sx), 1039
compute_mh_p_ksads__adhd_all, 321
compute_mh_p_ksads__agor__past__sx_mean (vars_mh_p_ksads__agor__past__sx), 1041
compute_mh_p_ksads__agor__pres__sx_mean (vars_mh_p_ksads__agor__pres__sx), 1042
compute_mh_p_ksads__agor_all, 322
compute_mh_p_ksads__asd__past__sx_mean (vars_mh_p_ksads__asd__past__sx), 1044
compute_mh_p_ksads__asd__pres__sx_mean (vars_mh_p_ksads__asd__pres__sx), 1045
compute_mh_p_ksads__asd_all, 322
compute_mh_p_ksads__bpd__past__sx_mean (vars_mh_p_ksads__bpd__past__sx), 1047
compute_mh_p_ksads__bpd__pres__sx_mean (vars_mh_p_ksads__bpd__pres__sx), 1048
compute_mh_p_ksads__bpd_all, 323
compute_mh_p_ksads__cond__past__sx_mean (vars_mh_p_ksads__cond__past__sx), 1050
compute_mh_p_ksads__cond__pres__sx_mean (vars_mh_p_ksads__cond__pres__sx), 1052
compute_mh_p_ksads__cond_all, 323
compute_mh_p_ksads__dep__past__sx_mean (vars_mh_p_ksads__dep__past__sx), 1053
compute_mh_p_ksads__dep__pres__sx_mean (vars_mh_p_ksads__dep__pres__sx), 1055
compute_mh_p_ksads__dep_all, 324
compute_mh_p_ksads__dmdd__sx_mean (vars_mh_p_ksads__dmdd__sx), 1057
compute_mh_p_ksads__dmdd_all, 324
compute_mh_p_ksads__ed__past__sx_mean (vars_mh_p_ksads__ed__past__sx), 1058
compute_mh_p_ksads__ed__pres__sx_mean (vars_mh_p_ksads__ed__pres__sx), 1059
compute_mh_p_ksads__ed_all, 325
compute_mh_p_ksads__gad__past__sx_mean (vars_mh_p_ksads__gad__past__sx), 1061
compute_mh_p_ksads__gad__pres__sx_mean (vars_mh_p_ksads__gad__pres__sx), 1062
compute_mh_p_ksads__gad_all, 325
compute_mh_p_ksads__hom__past__sx_mean (vars_mh_p_ksads__hom__past__sx), 1064
compute_mh_p_ksads__hom__pres__sx_mean (vars_mh_p_ksads__hom__pres__sx), 1065
compute_mh_p_ksads__hom_all, 326
compute_mh_p_ksads__ocd__past__sx_mean (vars_mh_p_ksads__ocd__past__sx), 1066
compute_mh_p_ksads__ocd__pres__sx_mean (vars_mh_p_ksads__ocd__pres__sx), 1068
compute_mh_p_ksads__ocd_all, 326
compute_mh_p_ksads__odd__past__sx_mean (vars_mh_p_ksads__odd__past__sx), 1069
compute_mh_p_ksads__odd__pres__sx_mean (vars_mh_p_ksads__odd__pres__sx), 1071
compute_mh_p_ksads__odd_all, 327
compute_mh_p_ksads__panic__past__sx_mean (vars_mh_p_ksads__panic__past__sx), 1072
compute_mh_p_ksads__panic__pres__sx_mean

(vars_mh_p_ksads__panic__pres__sx), 1073
compute_mh_p_ksads__panic_all, 327
compute_mh_p_ksads__phobia__past__sx_mean (vars_mh_p_ksads__phobia__past__sx), 1075
compute_mh_p_ksads__phobia__pres__sx_mean (vars_mh_p_ksads__phobia__pres__sx), 1076
compute_mh_p_ksads__phobia_all, 328
compute_mh_p_ksads__psych__past__sx_mean (vars_mh_p_ksads__psych__past__sx), 1077
compute_mh_p_ksads__psych__pres__sx_mean (vars_mh_p_ksads__psych__pres__sx), 1079
compute_mh_p_ksads__psych_all, 328
compute_mh_p_ksads__ptsd__past__sx_mean (vars_mh_p_ksads__ptsd__past__sx), 1080
compute_mh_p_ksads__ptsd__pres__sx_mean (vars_mh_p_ksads__ptsd__pres__sx), 1082
compute_mh_p_ksads__ptsd_all, 329
compute_mh_p_ksads__sepanx__past__sx_mean (vars_mh_p_ksads__sepanx__past__sx), 1084
compute_mh_p_ksads__sepanx__pres__sx_mean (vars_mh_p_ksads__sepanx__pres__sx), 1085
compute_mh_p_ksads__sepanx_all, 329
compute_mh_p_ksads__sleep__past__sx_mean (vars_mh_p_ksads__sleep__past__sx), 1087
compute_mh_p_ksads__sleep__pres__sx_mean (vars_mh_p_ksads__sleep__pres__sx), 1088
compute_mh_p_ksads__sleep_all, 330
compute_mh_p_ksads__socanx__past__sx_mean (vars_mh_p_ksads__socanx__past__sx), 1089
compute_mh_p_ksads__socanx__pres__sx_mean (vars_mh_p_ksads__socanx__pres__sx), 1091
compute_mh_p_ksads__socanx_all, 330
compute_mh_p_ksads__suic__past__sx_mean (vars_mh_p_ksads__suic__past__sx), 1092
compute_mh_p_ksads__suic__pres__sx_mean (vars_mh_p_ksads__suic__pres__sx), 1094
compute_mh_p_ksads__suic_all, 331
compute_mh_p_ksads__tic__past__sx_mean (vars_mh_p_ksads__tic__past__sx), 1095
compute_mh_p_ksads__tic__pres__sx_mean (vars_mh_p_ksads__tic__pres__sx), 1097
compute_mh_p_ksads__tic_all, 331
compute_mh_p_ple__exp__bad_count, 332
compute_mh_p_ple__exp__bad_count__v01, 333
compute_mh_p_ple__exp__bad_count__v02, 335
compute_mh_p_ple__exp__bad_count__v03, 336
compute_mh_p_ple__exp__bad_count__v04, 338
compute_mh_p_ple__exp__good_count, 340
compute_mh_p_ple__exp__good_count__v01, 341
compute_mh_p_ple__exp__good_count__v02, 343
compute_mh_p_ple__exp__good_count__v03, 344
compute_mh_p_ple__exp__good_count__v04, 346
compute_mh_p_ple__exp_nm, 348
compute_mh_p_ple__exp_nm__v01, 349
compute_mh_p_ple__exp_nm__v02, 351
compute_mh_p_ple__exp_nm__v03, 352
compute_mh_p_ple__exp_nm__v04, 354
compute_mh_p_ple__severity__bad_mean, 355
compute_mh_p_ple__severity__bad_mean__v01, 357
compute_mh_p_ple__severity__bad_mean__v02, 360
compute_mh_p_ple__severity__bad_mean__v03, 363
compute_mh_p_ple__severity__bad_mean__v04, 365
compute_mh_p_ple__severity__bad_sum, 367
compute_mh_p_ple__severity__bad_sum__v01, 369

compute_mh_p_ple__severity__bad_sum__v02, 372
compute_mh_p_ple__severity__bad_sum__v03, 374
compute_mh_p_ple__severity__bad_sum__v04, 377
compute_mh_p_ple__severity__good_mean, 379
compute_mh_p_ple__severity__good_mean__v01, 381
compute_mh_p_ple__severity__good_mean__v02, 383
compute_mh_p_ple__severity__good_mean__v03, 386
compute_mh_p_ple__severity__good_mean__v04, 388
compute_mh_p_ple__severity__good_sum, 390
compute_mh_p_ple__severity__good_sum__v01 *(vars_mh_p_ple__exp__v01)*, 1100
compute_mh_p_ple__severity__good_sum__v02 *(vars_mh_p_ple__exp__v02)*, 1102
compute_mh_p_ple__severity__good_sum__v03 *(vars_mh_p_ple__exp__v03)*, 1105
compute_mh_p_ple__severity__good_sum__v04 *(vars_mh_p_ple__exp__v04)*, 1108
compute_mh_p_ple__severity_mean, 392
compute_mh_p_ple__severity_mean__v01, 394
compute_mh_p_ple__severity_mean__v02, 395
compute_mh_p_ple__severity_mean__v03, 397
compute_mh_p_ple__severity_mean__v04, 399
compute_mh_p_ple__severity_nm, 400
compute_mh_p_ple__severity_nm__v01, 402
compute_mh_p_ple__severity_nm__v02, 404
compute_mh_p_ple__severity_nm__v03, 405
compute_mh_p_ple__severity_nm__v04, 407
compute_mh_p_ple__severity_sum *(vars_mh_p_ple__severity)*, 1110
compute_mh_p_ple__severity_sum__v01 *(vars_mh_p_ple__severity__v01)*, 1111
compute_mh_p_ple__severity_sum__v02 *(vars_mh_p_ple__severity__v02)*, 1113
compute_mh_p_ple__severity_sum__v03 *(vars_mh_p_ple__severity__v03)*, 1115
compute_mh_p_ple__severity_sum__v04 *(vars_mh_p_ple__severity__v04)*, 1117
compute_mh_p_ple_all, 408
compute_mh_p_ple_count *(vars_mh_p_ple)*, 1098
compute_mh_p_ple_count__v01 *(vars_mh_p_ple__v01)*, 1118
compute_mh_p_ple_count__v02 *(vars_mh_p_ple__v02)*, 1120
compute_mh_p_ple_count__v03 *(vars_mh_p_ple__v03)*, 1122
compute_mh_p_ple_count__v04 *(vars_mh_p_ple__v04)*, 1124
compute_mh_p_ple_nm, 409
compute_mh_p_ple_nm__v01, 410
compute_mh_p_ple_nm__v02, 412
compute_mh_p_ple_nm__v03, 413
compute_mh_p_ple_nm__v04, 415
compute_mh_p_ssrs_all, 416
compute_mh_p_ssrs_nm *(vars_mh_p_ssrs)*, 1125
compute_mh_p_ssrs_nm(), *418*
compute_mh_p_ssrs_sum, 417
compute_mh_t_bpm__attn_nm *(vars_mh_t_bpm__attn)*, 1128
compute_mh_t_bpm__attn_nm(), *419*, *421*
compute_mh_t_bpm__attn_sum, 418
compute_mh_t_bpm__attn_tscore, 419
compute_mh_t_bpm__ext_nm *(vars_mh_t_bpm__ext)*, 1129
compute_mh_t_bpm__ext_nm(), *422*, *423*
compute_mh_t_bpm__ext_sum, 421
compute_mh_t_bpm__ext_tscore, 422
compute_mh_t_bpm__int_nm *(vars_mh_t_bpm__int)*, 1130
compute_mh_t_bpm__int_nm(), *425*, *426*
compute_mh_t_bpm__int_sum, 424
compute_mh_t_bpm__int_tscore, 425
compute_mh_t_bpm_all, 426
compute_mh_t_bpm_nm *(vars_mh_t_bpm)*,

1126
compute_mh_t_bpm_nm(), *428*, *430*
compute_mh_t_bpm_sum, 427
compute_mh_t_bpm_tscore, 428
compute_mh_y_bisbas__bas__dr_nm *(vars_mh_y_bisbas__bas__dr)*, 1132
compute_mh_y_bisbas__bas__dr_nm(), *431*
compute_mh_y_bisbas__bas__dr_sum, 430
compute_mh_y_bisbas__bas__fs_nm *(vars_mh_y_bisbas__bas__fs)*, 1133
compute_mh_y_bisbas__bas__fs_nm(), *432*
compute_mh_y_bisbas__bas__fs_sum, 431
compute_mh_y_bisbas__bas__rr_nm *(vars_mh_y_bisbas__bas__rr)*, 1134
compute_mh_y_bisbas__bas__rr_nm(), *434*
compute_mh_y_bisbas__bas__rr_nm__v01 *(vars_mh_y_bisbas__bas__rr__v01)*, 1135
compute_mh_y_bisbas__bas__rr_nm__v01(), *435*
compute_mh_y_bisbas__bas__rr_sum, 433
compute_mh_y_bisbas__bas__rr_sum__v01, 434
compute_mh_y_bisbas__bis_nm *(vars_mh_y_bisbas__bis)*, 1137
compute_mh_y_bisbas__bis_nm(), *436*
compute_mh_y_bisbas__bis_nm__v01 *(vars_mh_y_bisbas__bis__v01)*, 1138
compute_mh_y_bisbas__bis_nm__v01(), *437*
compute_mh_y_bisbas__bis_sum, 435
compute_mh_y_bisbas__bis_sum__v01, 436
compute_mh_y_bisbas_all, 438
compute_mh_y_bpm__attn_nm *(vars_mh_y_bpm__attn)*, 1141
compute_mh_y_bpm__attn_nm(), *439*, *441*
compute_mh_y_bpm__attn_sum, 438
compute_mh_y_bpm__attn_tscore, 440
compute_mh_y_bpm__ext_nm *(vars_mh_y_bpm__ext)*, 1142
compute_mh_y_bpm__ext_nm(), *442*, *444*
compute_mh_y_bpm__ext_sum, 441
compute_mh_y_bpm__ext_tscore, 442
compute_mh_y_bpm__int_nm *(vars_mh_y_bpm__int)*, 1143
compute_mh_y_bpm__int_nm(), *445*, *446*
compute_mh_y_bpm__int_sum, 444
compute_mh_y_bpm__int_tscore, 445
compute_mh_y_bpm_all, 447
compute_mh_y_bpm_nm *(vars_mh_y_bpm)*, 1139
compute_mh_y_bpm_nm(), *448*, *450*
compute_mh_y_bpm_sum, 447
compute_mh_y_bpm_tscore, 449
compute_mh_y_erq__reapp_mean *(vars_mh_y_erq__reapp)*, 1144
compute_mh_y_erq__reapp_mean(), *451*
compute_mh_y_erq__reapp_nm, 451
compute_mh_y_erq__suppr_mean *(vars_mh_y_erq__suppr)*, 1146
compute_mh_y_erq__suppr_mean(), *453*
compute_mh_y_erq__suppr_nm, 452
compute_mh_y_erq_all, 453
compute_mh_y_ksads__bpd__past__sx_mean *(vars_mh_y_ksads__bpd__past__sx)*, 1147
compute_mh_y_ksads__bpd__pres__sx_mean *(vars_mh_y_ksads__bpd__pres__sx)*, 1149
compute_mh_y_ksads__bpd_all, 454
compute_mh_y_ksads__cond__past__sx_mean *(vars_mh_y_ksads__cond__past__sx)*, 1150
compute_mh_y_ksads__cond__pres__sx_mean *(vars_mh_y_ksads__cond__pres__sx)*, 1152
compute_mh_y_ksads__cond_all, 454
compute_mh_y_ksads__dep__past__sx_mean *(vars_mh_y_ksads__dep__past__sx)*, 1154
compute_mh_y_ksads__dep__pres__sx_mean *(vars_mh_y_ksads__dep__pres__sx)*, 1155
compute_mh_y_ksads__dep_all, 455
compute_mh_y_ksads__dmdd__sx_mean *(vars_mh_y_ksads__dmdd__sx)*, 1157
compute_mh_y_ksads__dmdd_all, 455
compute_mh_y_ksads__ed__past__sx_mean *(vars_mh_y_ksads__ed__past__sx)*, 1158
compute_mh_y_ksads__ed__pres__sx_mean

(vars_mh_y_ksads__ed__pres__sx), 1160
compute_mh_y_ksads__ed_all, 456
compute_mh_y_ksads__gad__past__sx_mean (vars_mh_y_ksads__gad__past__sx), 1161
compute_mh_y_ksads__gad__pres__sx_mean (vars_mh_y_ksads__gad__pres__sx), 1163
compute_mh_y_ksads__gad_all, 456
compute_mh_y_ksads__ocd__past__sx_mean (vars_mh_y_ksads__ocd__past__sx), 1164
compute_mh_y_ksads__ocd__pres__sx_mean (vars_mh_y_ksads__ocd__pres__sx), 1165
compute_mh_y_ksads__ocd_all, 457
compute_mh_y_ksads__panic__past__sx_mean (vars_mh_y_ksads__panic__past__sx), 1167
compute_mh_y_ksads__panic__pres__sx_mean (vars_mh_y_ksads__panic__pres__sx), 1168
compute_mh_y_ksads__panic_all, 457
compute_mh_y_ksads__ptsd__past__sx_mean (vars_mh_y_ksads__ptsd__past__sx), 1170
compute_mh_y_ksads__ptsd__pres__sx_mean (vars_mh_y_ksads__ptsd__pres__sx), 1172
compute_mh_y_ksads__ptsd_all, 458
compute_mh_y_ksads__sleep__past__sx_mean (vars_mh_y_ksads__sleep__past__sx), 1174
compute_mh_y_ksads__sleep__pres__sx_mean (vars_mh_y_ksads__sleep__pres__sx), 1175
compute_mh_y_ksads__sleep_all, 458
compute_mh_y_ksads__socanx__past__sx_mean (vars_mh_y_ksads__socanx__past__sx), 1176
compute_mh_y_ksads__socanx__pres__sx_mean (vars_mh_y_ksads__socanx__pres__sx), 1178
compute_mh_y_ksads__socanx_all, 459
compute_mh_y_ksads__suic__past__sx_mean (vars_mh_y_ksads__suic__past__sx), 1179
compute_mh_y_ksads__suic__pres__sx_mean (vars_mh_y_ksads__suic__pres__sx), 1181
compute_mh_y_ksads__suic_all, 459
compute_mh_y_pai_all, 460
compute_mh_y_pai_nm (vars_mh_y_pai), 1182
compute_mh_y_pai_nm(), *461*
compute_mh_y_pai_sum, 460
compute_mh_y_peq__overt__agg_nm (vars_mh_y_peq__overt__agg), 1184
compute_mh_y_peq__overt__agg_nm(), *462*
compute_mh_y_peq__overt__agg_sum, 462
compute_mh_y_peq__overt__vict_nm (vars_mh_y_peq__overt__vict), 1185
compute_mh_y_peq__overt__vict_nm(), *464*
compute_mh_y_peq__overt__vict_sum, 463
compute_mh_y_peq__rel__agg_nm (vars_mh_y_peq__rel__agg), 1186
compute_mh_y_peq__rel__agg_nm(), *465*
compute_mh_y_peq__rel__agg_sum, 464
compute_mh_y_peq__rel__vict_nm (vars_mh_y_peq__rel__vict), 1187
compute_mh_y_peq__rel__vict_nm(), *466*
compute_mh_y_peq__rel__vict_sum, 465
compute_mh_y_peq__rep__agg_nm (vars_mh_y_peq__rep__agg), 1188
compute_mh_y_peq__rep__agg_nm(), *467*
compute_mh_y_peq__rep__agg_sum, 466
compute_mh_y_peq__rep__vict_nm (vars_mh_y_peq__rep__vict), 1190
compute_mh_y_peq__rep__vict_nm(), *469*
compute_mh_y_peq__rep__vict_sum, 468
compute_mh_y_peq_all, 469
compute_mh_y_ple__exp__bad_count, 470
compute_mh_y_ple__exp__bad_count__v01, 471
compute_mh_y_ple__exp__bad_count__v02, 473
compute_mh_y_ple__exp__bad_count__v03, 474
compute_mh_y_ple__exp__good_count, 476
compute_mh_y_ple__exp__good_count__v01,

478
compute_mh_y_ple__exp__good_count__v02, 479
compute_mh_y_ple__exp__good_count__v03, 481
compute_mh_y_ple__exp_nm, 483
compute_mh_y_ple__exp_nm__v01, 484
compute_mh_y_ple__exp_nm__v02, 486
compute_mh_y_ple__exp_nm__v03, 487
compute_mh_y_ple__severity__bad_mean, 489
compute_mh_y_ple__severity__bad_mean__v01, 491
compute_mh_y_ple__severity__bad_mean__v02, 494
compute_mh_y_ple__severity__bad_mean__v03, 496
compute_mh_y_ple__severity__bad_sum, 499
compute_mh_y_ple__severity__bad_sum__v01, 501
compute_mh_y_ple__severity__bad_sum__v02, 503
compute_mh_y_ple__severity__bad_sum__v03, 506
compute_mh_y_ple__severity__good_mean, 508
compute_mh_y_ple__severity__good_mean__v01, 511
compute_mh_y_ple__severity__good_mean__v02, 513
compute_mh_y_ple__severity__good_mean__v03, 516
compute_mh_y_ple__severity__good_sum *(vars_mh_y_ple__exp)*, 1192
compute_mh_y_ple__severity__good_sum__v01 *(vars_mh_y_ple__exp__v01)*, 1195
compute_mh_y_ple__severity__good_sum__v02 *(vars_mh_y_ple__exp__v02)*, 1197
compute_mh_y_ple__severity__good_sum__v03 *(vars_mh_y_ple__exp__v03)*, 1200
compute_mh_y_ple__severity_mean, 518
compute_mh_y_ple__severity_mean__v01, 520
compute_mh_y_ple__severity_mean__v02, 521
compute_mh_y_ple__severity_mean__v03, 523
compute_mh_y_ple__severity_nm, 525
compute_mh_y_ple__severity_nm__v01, 526
compute_mh_y_ple__severity_nm__v02, 528
compute_mh_y_ple__severity_nm__v03, 530
compute_mh_y_ple__severity_sum *(vars_mh_y_ple__severity)*, 1203
compute_mh_y_ple__severity_sum__v01 *(vars_mh_y_ple__severity__v01)*, 1204
compute_mh_y_ple__severity_sum__v02 *(vars_mh_y_ple__severity__v02)*, 1206
compute_mh_y_ple__severity_sum__v03 *(vars_mh_y_ple__severity__v03)*, 1208
compute_mh_y_ple_all, 531
compute_mh_y_ple_count *(vars_mh_y_ple)*, 1191
compute_mh_y_ple_count__v01 *(vars_mh_y_ple__v01)*, 1210
compute_mh_y_ple_count__v02 *(vars_mh_y_ple__v02)*, 1212
compute_mh_y_ple_count__v03 *(vars_mh_y_ple__v03)*, 1214
compute_mh_y_ple_nm, 532
compute_mh_y_ple_nm__v01, 533
compute_mh_y_ple_nm__v02, 535
compute_mh_y_ple_nm__v03, 536
compute_mh_y_pps__bother__no_count, 538
compute_mh_y_pps__bother__yes_count, 540
compute_mh_y_pps__bother__yes_count(), *545*, *547*, *1218*
compute_mh_y_pps__bother_nm *(vars_mh_y_pps__bother)*, 1216
compute_mh_y_pps__bother_nm(), *539*, *541*
compute_mh_y_pps__dist__curr_score, 541
compute_mh_y_pps__dist__curr_score(), *543*, *550–552*
compute_mh_y_pps__dist__pers_score, 542
compute_mh_y_pps__dist__pers_score(), *553*, *554*

compute_mh_y_pps__severity_mean, 543
compute_mh_y_pps__severity_nm (vars_mh_y_pps__severity), 1217
compute_mh_y_pps__severity_score, 546
compute_mh_y_pps__severity_score(), 542
compute_mh_y_pps_all, 547
compute_mh_y_pps_count (vars_mh_y_pps_count), 1219
compute_mh_y_pps_count(), 549, 1217
compute_mh_y_pps_nm, 548
compute_mh_y_ppsss__dist__curr_count, 550
compute_mh_y_ppsss__dist__curr_ever, 551
compute_mh_y_ppsss__dist__curr_first, 551
compute_mh_y_ppsss__dist__pers_count, 552
compute_mh_y_ppsss__dist__pers_ever, 553
compute_mh_y_ppsss__dist__pers_first, 554
compute_mh_y_ppsss_all, 555
compute_mh_y_sup_all, 555
compute_mh_y_sup_nm (vars_mh_y_sup), 1221
compute_mh_y_sup_nm(), 557
compute_mh_y_sup_sum, 556
compute_mh_y_upps__nurg_nm (vars_mh_y_upps__nurg), 1222
compute_mh_y_upps__nurg_nm(), 558
compute_mh_y_upps__nurg_sum, 557
compute_mh_y_upps__pers_nm (vars_mh_y_upps__pers), 1223
compute_mh_y_upps__pers_nm(), 559
compute_mh_y_upps__pers_sum, 558
compute_mh_y_upps__plan_nm (vars_mh_y_upps__plan), 1224
compute_mh_y_upps__plan_nm(), 560
compute_mh_y_upps__plan_sum, 559
compute_mh_y_upps__purg_nm (vars_mh_y_upps__purg), 1225
compute_mh_y_upps__purg_nm(), 562
compute_mh_y_upps__purg_sum, 561
compute_mh_y_upps__sens_nm (vars_mh_y_upps__sens), 1227
compute_mh_y_upps__sens_nm(), 563
compute_mh_y_upps__sens_sum, 562
compute_mh_y_upps_all, 563
compute_mh_y_ysr__dsm__adhd_nm (vars_mh_y_ysr__dsm__adhd), 1231
compute_mh_y_ysr__dsm__adhd_nm(), 565, 567
compute_mh_y_ysr__dsm__adhd_sum, 564
compute_mh_y_ysr__dsm__adhd_tscore, 565
compute_mh_y_ysr__dsm__anx_nm (vars_mh_y_ysr__dsm__anx), 1233
compute_mh_y_ysr__dsm__anx_nm(), 568, 570
compute_mh_y_ysr__dsm__anx_sum, 567
compute_mh_y_ysr__dsm__anx_tscore, 568
compute_mh_y_ysr__dsm__cond_nm (vars_mh_y_ysr__dsm__cond), 1234
compute_mh_y_ysr__dsm__cond_nm(), 571, 573
compute_mh_y_ysr__dsm__cond_sum, 570
compute_mh_y_ysr__dsm__cond_tscore, 571
compute_mh_y_ysr__dsm__dep_nm (vars_mh_y_ysr__dsm__dep), 1236
compute_mh_y_ysr__dsm__dep_nm(), 574, 576
compute_mh_y_ysr__dsm__dep_sum, 573
compute_mh_y_ysr__dsm__dep_tscore, 575
compute_mh_y_ysr__dsm__opp_nm (vars_mh_y_ysr__dsm__opp), 1237
compute_mh_y_ysr__dsm__opp_nm(), 577, 579
compute_mh_y_ysr__dsm__opp_sum, 576
compute_mh_y_ysr__dsm__opp_tscore, 577
compute_mh_y_ysr__dsm__somat_nm (vars_mh_y_ysr__dsm__somat), 1238
compute_mh_y_ysr__dsm__somat_nm(), 580, 581
compute_mh_y_ysr__dsm__somat_sum, 579
compute_mh_y_ysr__dsm__somat_tscore, 580
compute_mh_y_ysr__pos_nm (vars_mh_y_ysr__pos), 1240
compute_mh_y_ysr__pos_nm(), 583, 584
compute_mh_y_ysr__pos_sum, 582

compute_mh_y_ysr__pos_tscore, 583
compute_mh_y_ysr__synd__aggr_nm (vars_mh_y_ysr__synd__aggr), 1241
compute_mh_y_ysr__synd__aggr_nm(), *586*, *588*
compute_mh_y_ysr__synd__aggr_sum, 585
compute_mh_y_ysr__synd__aggr_tscore, 586
compute_mh_y_ysr__synd__anxdep_nm (vars_mh_y_ysr__synd__anxdep), 1243
compute_mh_y_ysr__synd__anxdep_nm(), *589*, *591*
compute_mh_y_ysr__synd__anxdep_sum, 588
compute_mh_y_ysr__synd__anxdep_tscore, 590
compute_mh_y_ysr__synd__attn_nm (vars_mh_y_ysr__synd__attn), 1244
compute_mh_y_ysr__synd__attn_nm(), *592*, *594*
compute_mh_y_ysr__synd__attn_sum, 591
compute_mh_y_ysr__synd__attn_tscore, 593
compute_mh_y_ysr__synd__ext_nm (vars_mh_y_ysr__synd__ext), 1246
compute_mh_y_ysr__synd__ext_nm(), *596*, *598*
compute_mh_y_ysr__synd__ext_sum, 594
compute_mh_y_ysr__synd__ext_tscore, 596
compute_mh_y_ysr__synd__int_nm (vars_mh_y_ysr__synd__int), 1248
compute_mh_y_ysr__synd__int_nm(), *600*, *602*
compute_mh_y_ysr__synd__int_sum, 598
compute_mh_y_ysr__synd__int_tscore, 600
compute_mh_y_ysr__synd__othpr_nm (vars_mh_y_ysr__synd__othpr), 1249
compute_mh_y_ysr__synd__othpr_nm(), *603*
compute_mh_y_ysr__synd__othpr_sum, 602
compute_mh_y_ysr__synd__rule_nm (vars_mh_y_ysr__synd__rule), 1251
compute_mh_y_ysr__synd__rule_nm(), *605*, *607*
compute_mh_y_ysr__synd__rule_sum, 604
compute_mh_y_ysr__synd__rule_tscore, 605
compute_mh_y_ysr__synd__soc_nm (vars_mh_y_ysr__synd__soc), 1252
compute_mh_y_ysr__synd__soc_nm(), *608*, *610*
compute_mh_y_ysr__synd__soc_sum, 607
compute_mh_y_ysr__synd__soc_tscore, 608
compute_mh_y_ysr__synd__som_nm (vars_mh_y_ysr__synd__som), 1254
compute_mh_y_ysr__synd__som_nm(), *611*, *613*
compute_mh_y_ysr__synd__som_sum, 610
compute_mh_y_ysr__synd__som_tscore, 611
compute_mh_y_ysr__synd__tho_nm (vars_mh_y_ysr__synd__tho), 1255
compute_mh_y_ysr__synd__tho_nm(), *614*, *616*
compute_mh_y_ysr__synd__tho_sum, 613
compute_mh_y_ysr__synd__tho_tscore, 614
compute_mh_y_ysr__synd__wthdep_nm (vars_mh_y_ysr__synd__wthdep), 1257
compute_mh_y_ysr__synd__wthdep_nm(), *617*, *619*
compute_mh_y_ysr__synd__wthdep_sum, 616
compute_mh_y_ysr__synd__wthdep_tscore, 617
compute_mh_y_ysr_all, 619
compute_mh_y_ysr_nm (vars_mh_y_ysr), 1228
compute_mh_y_ysr_nm(), *623*, *627*
compute_mh_y_ysr_sum, 620
compute_mh_y_ysr_tscore, 623
compute_nc_p_bdefs__sympt_count, 627

compute_nc_p_bdefs_all, 628
compute_nc_p_bdefs_nm, 629
compute_nc_p_bdefs_sum (vars_nc_p_bdefs), 1258
compute_nc_p_bdefs_sum(), *628*, *630*
compute_nc_y_ehis_all, 630
compute_nc_y_ehis_nm, 631
compute_nc_y_ehis_score (vars_nc_y_ehis), 1260
compute_nc_y_ehis_score(), *632*
compute_nt_p_yst__pmum_mean (vars_nt_p_yst__pmum), 1261
compute_nt_p_yst__pmum_nm, 632
compute_nt_p_yst__screen__wkdy_nm, 633
compute_nt_p_yst__screen__wkdy_sum (vars_nt_p_yst__screen__wkdy), 1262
compute_nt_p_yst__screen__wknd_nm, 634
compute_nt_p_yst__screen__wknd_sum (vars_nt_p_yst__screen__wknd), 1263
compute_nt_p_yst_all, 635
compute_nt_y_stq__screen__wkdy_nm, 635
compute_nt_y_stq__screen__wkdy_sum (vars_nt_y_stq__screen__wkdy), 1264
compute_nt_y_stq__screen__wknd_nm, 637
compute_nt_y_stq__screen__wknd_sum (vars_nt_y_stq__screen__wknd), 1266
compute_nt_y_stq_all, 638
compute_ph_meds_catg_all, 639
compute_ph_meds_catg_all(), *642*
compute_ph_meds_estuse_flags_all, 641
compute_ph_p_anthr__fath_height__cm, 642
compute_ph_p_anthr__fath_height__in (vars_ph_p_anthr__height), 1267
compute_ph_p_anthr__fath_height__in(), *643–645*
compute_ph_p_anthr__moth_height__cm, 643
compute_ph_p_anthr__moth_height__in, 644
compute_ph_p_anthr_all, 645
compute_ph_p_cna_all, 646
compute_ph_p_cna_nm, 647
compute_ph_p_cna_sum (vars_ph_p_cna), 1268
compute_ph_p_dhx_birthweight (vars_ph_p_dhx_birthweight), 1270
compute_ph_p_dhx_catg_all (compute_ph_meds_catg_all), 639
compute_ph_p_meds_catg_all (compute_ph_meds_catg_all), 639
compute_ph_p_meds_estuse_flags_all (compute_ph_meds_estuse_flags_all), 641
compute_ph_p_otbi__loc__30m_count (vars_ph_p_otbi__loc__30m_count), 1272
compute_ph_p_otbi__loc__30m_count(), *649*
compute_ph_p_otbi__loc__30m_nm, 648
compute_ph_p_otbi__loc__tbiage_nm, 649
compute_ph_p_otbi__loc_before15 (vars_ph_p_otbi__loc_before15), 1274
compute_ph_p_otbi__loc_count (vars_ph_p_otbi__loc_count), 1276
compute_ph_p_otbi__loc_count(), *650*
compute_ph_p_otbi__loc_nm, 650
compute_ph_p_otbi__loc_tbiage (vars_ph_p_otbi__loc_tbiage), 1277
compute_ph_p_otbi__loc_tbiage(), *649*, *1276*
compute_ph_p_otbi__rpt_count (vars_ph_p_otbi__rpt_count), 1280
compute_ph_p_otbi__rpt_count(), *651*
compute_ph_p_otbi__rpt_nm, 651
compute_ph_p_otbi_all, 652
compute_ph_p_otbi_nm (vars_ph_p_otbi), 1271
compute_ph_p_otbi_tbiworst (vars_ph_p_otbi_tbiworst), 1281
compute_ph_p_pds__f__categ_nm, 652
compute_ph_p_pds__f_categ (vars_ph_p_pds__f_categ), 1284
compute_ph_p_pds__f_categ(), *653*
compute_ph_p_pds__f_mean (vars_ph_p_pds__f), 1283
compute_ph_p_pds__f_mean(), *654*

compute_ph_p_pds__f_nm, 653
compute_ph_p_pds__m__categ_nm, 654
compute_ph_p_pds__m_categ
(vars_ph_p_pds__m_categ), 1287
compute_ph_p_pds__m_categ(), *655*
compute_ph_p_pds__m_mean
(vars_ph_p_pds__m), 1286
compute_ph_p_pds__m_mean(), *656*
compute_ph_p_pds__m_nm, 655
compute_ph_p_pds_all, 656
compute_ph_p_sds__da_nm, 657
compute_ph_p_sds__da_sum
(vars_ph_p_sds__da), 1288
compute_ph_p_sds__da_sum(), *658*
compute_ph_p_sds__dims_nm, 658
compute_ph_p_sds__dims_sum
(vars_ph_p_sds__dims), 1289
compute_ph_p_sds__dims_sum(), *659*
compute_ph_p_sds__does_nm, 659
compute_ph_p_sds__does_sum
(vars_ph_p_sds__does), 1291
compute_ph_p_sds__does_sum(), *660*
compute_ph_p_sds__hyphy_nm, 660
compute_ph_p_sds__hyphy_sum
(vars_ph_p_sds__hyphy), 1292
compute_ph_p_sds__hyphy_sum(), *661*
compute_ph_p_sds__sbd_nm, 661
compute_ph_p_sds__sbd_sum
(vars_ph_p_sds__sbd), 1293
compute_ph_p_sds__sbd_sum(), *661*
compute_ph_p_sds__swtd_nm, 662
compute_ph_p_sds__swtd_sum
(vars_ph_p_sds__swtd), 1295
compute_ph_p_sds__swtd_sum(), *662*
compute_ph_p_sds_all, 663
compute_ph_p_sds_nm, 663
compute_ph_p_sds_sum
(vars_ph_p_sds_sum), 1296
compute_ph_p_sds_sum(), *664*
compute_ph_y_anthr__height_mean
(vars_ph_y_anthr__height), 1298
compute_ph_y_anthr__height_mean(), *665*
compute_ph_y_anthr__height_nm, 665
compute_ph_y_anthr__weight_mean
(vars_ph_y_anthr__weight), 1299
compute_ph_y_anthr__weight_mean(), *666*
compute_ph_y_anthr__weight_nm, 666
compute_ph_y_anthr_all, 667
compute_ph_y_bp__dia_mean
(vars_ph_y_bp__dia), 1301
compute_ph_y_bp__dia_mean(), *668*
compute_ph_y_bp__dia_nm, 667
compute_ph_y_bp__hrate_mean
(vars_ph_y_bp__hrate), 1302
compute_ph_y_bp__hrate_mean(), *670*
compute_ph_y_bp__hrate_nm, 669
compute_ph_y_bp__sys_mean
(vars_ph_y_bp__sys), 1303
compute_ph_y_bp__sys_mean(), *671*
compute_ph_y_bp__sys_nm, 670
compute_ph_y_bp_all, 671
compute_ph_y_mctq__fd__bed__end__24h_t,
672
compute_ph_y_mctq__fd__bed__end__36h_t,
673
compute_ph_y_mctq__fd__bed__start__24h_t,
674
compute_ph_y_mctq__fd__bed__start__36h_t,
675
compute_ph_y_mctq__fd__bed_sum, 676
compute_ph_y_mctq__fd__sleep__end__24h_t,
677
compute_ph_y_mctq__fd__sleep__end__36h_t,
678
compute_ph_y_mctq__fd__sleep__mid__24h_t,
679
compute_ph_y_mctq__fd__sleep__mid__36h_t,
680
compute_ph_y_mctq__fd__sleep__onset__24h_t,
681
compute_ph_y_mctq__fd__sleep__onset__36h_t,
682
compute_ph_y_mctq__fd__sleep__start__24h_t,
683
compute_ph_y_mctq__fd__sleep__start__36h_t,
684
compute_ph_y_mctq__fd__sleep__waso_sum,
685
compute_ph_y_mctq__fd__sleep_dur, 686
compute_ph_y_mctq__fd__sleep_inertia,
687
compute_ph_y_mctq__fd__sleep_latent,
688
compute_ph_y_mctq__fd__sleep_period,
689
compute_ph_y_mctq__fd_count, 690

compute_ph_y_mctq__raw__36h_chrono, 691
compute_ph_y_mctq__school__leave__24h_t, 692
compute_ph_y_mctq__school__leave__36h_t, 693
compute_ph_y_mctq__school__start__24h_t, 694
compute_ph_y_mctq__school__start__36h_t, 695
compute_ph_y_mctq__sd__bed__end__24h_t, 697
compute_ph_y_mctq__sd__bed__end__36h_t, 698
compute_ph_y_mctq__sd__bed__start__24h_t, 699
compute_ph_y_mctq__sd__bed__start__36h_t, 700
compute_ph_y_mctq__sd__bed_sum, 701
compute_ph_y_mctq__sd__sleep__end__24h_t, 702
compute_ph_y_mctq__sd__sleep__end__36h_t, 703
compute_ph_y_mctq__sd__sleep__mid__24h_t, 704
compute_ph_y_mctq__sd__sleep__mid__36h_t, 705
compute_ph_y_mctq__sd__sleep__onset__24h_t, 706
compute_ph_y_mctq__sd__sleep__onset__36h_t, 707
compute_ph_y_mctq__sd__sleep__start__24h_t, 708
compute_ph_y_mctq__sd__sleep__start__36h_t, 709
compute_ph_y_mctq__sd__sleep__waso_sum, 710
compute_ph_y_mctq__sd__sleep_dur, 711
compute_ph_y_mctq__sd__sleep_inertia, 712
compute_ph_y_mctq__sd__sleep_latent, 713
compute_ph_y_mctq__sd__sleep_period, 714
compute_ph_y_mctq__sd_count, 715
compute_ph_y_mctq__sleep_dur, 716
compute_ph_y_mctq__sleep_loss, 718
compute_ph_y_mctq__sleep_period, 719
compute_ph_y_mctq__socjl_absl, 720
compute_ph_y_mctq__socjl_rel, 721
compute_ph_y_mctq_all, 722
compute_ph_y_mctq_chrono, 722
compute_ph_y_mctq_outlier, 723
compute_ph_y_meds_catg_all *(compute_ph_meds_catg_all)*, 639
compute_ph_y_meds_estuse_flags_all *(compute_ph_meds_estuse_flags_all)*, 641
compute_ph_y_pds__f__categ_nm, 724
compute_ph_y_pds__f_categ *(vars_ph_y_pds__f_categ)*, 1305
compute_ph_y_pds__f_categ(), *725*
compute_ph_y_pds__f_mean *(vars_ph_y_pds__f)*, 1304
compute_ph_y_pds__f_mean(), *726*
compute_ph_y_pds__f_nm, 725
compute_ph_y_pds__m__categ_nm, 726
compute_ph_y_pds__m_categ *(vars_ph_y_pds__m_categ)*, 1308
compute_ph_y_pds__m_categ(), *727*
compute_ph_y_pds__m_mean *(vars_ph_y_pds__m)*, 1306
compute_ph_y_pds__m_mean(), *728*
compute_ph_y_pds__m_nm, 727
compute_ph_y_pds_all, 728
compute_ss_use_onset_age, 729
compute_ss_use_onset_event, 731
compute_ss_use_onset_event(), *729*
compute_ss_use_yn, 733
compute_su_p_ksads__aud__past__sx_mean *(vars_su_p_ksads__aud__past__sx)*, 1309
compute_su_p_ksads__aud__pres__sx_mean *(vars_su_p_ksads__aud__pres__sx)*, 1310
compute_su_p_ksads__aud_all, 736
compute_su_p_ksads__dud__coc__past__sx_mean *(vars_su_p_ksads__dud__coc__past__sx_mean)*, 1312
compute_su_p_ksads__dud__coc__pres__sx_mean *(vars_su_p_ksads__dud__coc__pres__sx_mean)*, 1314
compute_su_p_ksads__dud__hall__past__sx_mean *(vars_su_p_ksads__dud__hall__past__sx_mean)*, 1315
compute_su_p_ksads__dud__hall__pres__sx_mean

(vars_su_p_ksads__dud__hall__pres__sx_mean), 1317
compute_su_p_ksads__dud__mj__past__sx_mean (vars_su_p_ksads__dud__mj__past__sx_mean), 1319
compute_su_p_ksads__dud__mj__pres__sx_mean (vars_su_p_ksads__dud__mj__pres__sx_mean), 1320
compute_su_p_ksads__dud__nic__past__sx_mean (vars_su_p_ksads__dud__nic__past__sx_mean), 1322
compute_su_p_ksads__dud__nic__pres__sx_mean (vars_su_p_ksads__dud__nic__pres__sx_mean), 1324
compute_su_p_ksads__dud__opi__past__sx_mean (vars_su_p_ksads__dud__opi__past__sx_mean), 1325
compute_su_p_ksads__dud__opi__pres__sx_mean (vars_su_p_ksads__dud__opi__pres__sx_mean), 1327
compute_su_p_ksads__dud__othdrg__past__sx_mean (vars_su_p_ksads__dud__othdrg__past__sx_mean), 1329
compute_su_p_ksads__dud__othdrg__pres__sx_mean (vars_su_p_ksads__dud__othdrg__pres__sx_mean), 1330
compute_su_p_ksads__dud__past__sx_mean (vars_su_p_ksads__dud__past__sx_mean), 1332
compute_su_p_ksads__dud__pcp__past__sx_mean (vars_su_p_ksads__dud__pcp__past__sx_mean), 1334
compute_su_p_ksads__dud__pcp__pres__sx_mean (vars_su_p_ksads__dud__pcp__pres__sx_mean), 1335
compute_su_p_ksads__dud__pres__sx_mean (vars_su_p_ksads__dud__pres__sx_mean), 1337
compute_su_p_ksads__dud__sed__past__sx_mean (vars_su_p_ksads__dud__sed__past__sx_mean), 1339
compute_su_p_ksads__dud__sed__pres__sx_mean (vars_su_p_ksads__dud__sed__pres__sx_mean), 1340
compute_su_p_ksads__dud__solv__past__sx_mean (vars_su_p_ksads__dud__solv__past__sx_mean), 1342
compute_su_p_ksads__dud__solv__pres__sx_mean (vars_su_p_ksads__dud__solv__pres__sx_mean), 1344
compute_su_p_ksads__dud__stim__past__sx_mean (vars_su_p_ksads__dud__stim__past__sx_mean), 1345
compute_su_p_ksads__dud__stim__pres__sx_mean (vars_su_p_ksads__dud__stim__pres__sx_mean), 1347
compute_su_p_ksads__dud_all, 736
compute_su_y_alcexp__neg_nm, 737
compute_su_y_alcexp__neg_prsum (vars_su_y_alcexp__neg), 1349
compute_su_y_alcexp__neg_prsum(), *737*
compute_su_y_alcexp__pos_nm, 738
compute_su_y_alcexp__pos_prsum (vars_su_y_alcexp__pos), 1350
compute_su_y_alcexp__pos_prsum(), *738*
compute_su_y_alcexp_all, 739
compute_su_y_alchss_all, 739
compute_su_y_alchss_count, 740
compute_su_y_alchss_nm, 741
compute_su_y_alchss_sum (vars_su_y_alchss), 1351
compute_su_y_alchss_sum(), *741*, *743*
compute_su_y_alcprob_all, 743
compute_su_y_alcprob_nm, 744
compute_su_y_alcprob_prsum (vars_su_y_alcprob), 1352
compute_su_y_alcprob_prsum(), *745*
compute_su_y_alcsre__6mo_count, 745
compute_su_y_alcsre__6mo_mean (vars_su_y_alcsre__6mo), 1354
compute_su_y_alcsre__6mo_nm, 746
compute_su_y_alcsre__first5_count, 747
compute_su_y_alcsre__first5_mean (vars_su_y_alcsre__first5), 1355
compute_su_y_alcsre__first5_nm, 748
compute_su_y_alcsre__hvy_count, 749
compute_su_y_alcsre__hvy_mean (vars_su_y_alcsre__hvy), 1356
compute_su_y_alcsre__hvy_nm, 750
compute_su_y_alcsre_all, 750
compute_su_y_caff__coffee_sum (vars_su_y_caff__coffee), 1357
compute_su_y_caff__energy__drink_sum (vars_su_y_caff__energy__drink), 1359

compute_su_y_caff__energy__shot_sum (vars_su_y_caff__energy__shot), 1361
compute_su_y_caff__energy_sum (vars_su_y_caff__energy), 1358
compute_su_y_caff__espres_sum (vars_su_y_caff__espres), 1362
compute_su_y_caff__oth_sum (vars_su_y_caff__oth), 1363
compute_su_y_caff__soda_sum (vars_su_y_caff__soda), 1364
compute_su_y_caff__suppl_sum (vars_su_y_caff__suppl), 1365
compute_su_y_caff__tea_sum (vars_su_y_caff__tea), 1366
compute_su_y_cigexp__neg_nm, 751
compute_su_y_cigexp__neg_prsum (vars_su_y_cigexp__neg), 1367
compute_su_y_cigexp__neg_prsum(), *751*, *752*
compute_su_y_cigexp__neg_prsum__v01, 752
compute_su_y_cigexp__pos_nm, 753
compute_su_y_cigexp__pos_prsum (vars_su_y_cigexp__pos), 1368
compute_su_y_cigexp__pos_prsum(), *753*, *755*
compute_su_y_cigexp__pos_prsum__v01, 754
compute_su_y_cigexp_all, 755
compute_su_y_drgprob_all, 755
compute_su_y_drgprob_nm, 756
compute_su_y_drgprob_prsum (vars_su_y_drgprob), 1369
compute_su_y_drgprob_prsum(), *757*
compute_su_y_ksads__aud__past__sx_mean (vars_su_y_ksads__aud__past__sx), 1371
compute_su_y_ksads__aud__pres__sx_mean (vars_su_y_ksads__aud__pres__sx), 1372
compute_su_y_ksads__aud_all, 757
compute_su_y_ksads__dud__coc__past__sx_mean (vars_su_y_ksads__dud__coc__past__sx_mean), 1374
compute_su_y_ksads__dud__coc__pres__sx_mean (vars_su_y_ksads__dud__coc__pres__sx_mean), 1376
compute_su_y_ksads__dud__hall__past__sx_mean (vars_su_y_ksads__dud__hall__past__sx_mean), 1377
compute_su_y_ksads__dud__hall__pres__sx_mean (vars_su_y_ksads__dud__hall__pres__sx_mean), 1379
compute_su_y_ksads__dud__mj__past__sx_mean (vars_su_y_ksads__dud__mj__past__sx_mean), 1381
compute_su_y_ksads__dud__mj__pres__sx_mean (vars_su_y_ksads__dud__mj__pres__sx_mean), 1382
compute_su_y_ksads__dud__nic__past__sx_mean (vars_su_y_ksads__dud__nic__past__sx_mean), 1384
compute_su_y_ksads__dud__nic__pres__sx_mean (vars_su_y_ksads__dud__nic__pres__sx_mean), 1386
compute_su_y_ksads__dud__opi__past__sx_mean (vars_su_y_ksads__dud__opi__past__sx_mean), 1387
compute_su_y_ksads__dud__opi__pres__sx_mean (vars_su_y_ksads__dud__opi__pres__sx_mean), 1389
compute_su_y_ksads__dud__othdrg__past__sx_mean (vars_su_y_ksads__dud__othdrg__past__sx_mean), 1391
compute_su_y_ksads__dud__othdrg__pres__sx_mean (vars_su_y_ksads__dud__othdrg__pres__sx_mean), 1392
compute_su_y_ksads__dud__past__sx_mean (vars_su_y_ksads__dud__past__sx_mean), 1394
compute_su_y_ksads__dud__pcp__past__sx_mean (vars_su_y_ksads__dud__pcp__past__sx_mean), 1396
compute_su_y_ksads__dud__pcp__pres__sx_mean (vars_su_y_ksads__dud__pcp__pres__sx_mean), 1397
compute_su_y_ksads__dud__pres__sx_mean (vars_su_y_ksads__dud__pres__sx_mean), 1399
compute_su_y_ksads__dud__sed__past__sx_mean (vars_su_y_ksads__dud__sed__past__sx_mean), 1401
compute_su_y_ksads__dud__sed__pres__sx_mean (vars_su_y_ksads__dud__sed__pres__sx_mean), 1402

compute_su_y_ksads__dud__solv__past__sx_mean (vars_su_y_ksads__dud__solv__past__sx_mean), 1404
compute_su_y_ksads__dud__solv__pres__sx_mean (vars_su_y_ksads__dud__solv__pres__sx_mean), 1406
compute_su_y_ksads__dud__stim__past__sx_mean (vars_su_y_ksads__dud__stim__past__sx_mean), 1407
compute_su_y_ksads__dud__stim__pres__sx_mean (vars_su_y_ksads__dud__stim__pres__sx_mean), 1409
compute_su_y_ksads__dud_all, 758
compute_su_y_mjexp__neg_nm, 758
compute_su_y_mjexp__neg_prsum (vars_su_y_mjexp__neg), 1411
compute_su_y_mjexp__neg_prsum(), *759*
compute_su_y_mjexp__pos_nm, 759
compute_su_y_mjexp__pos_prsum (vars_su_y_mjexp__pos), 1412
compute_su_y_mjexp__pos_prsum(), *760*
compute_su_y_mjexp_all, 760
compute_su_y_mjprob_all, 760
compute_su_y_mjprob_nm, 761
compute_su_y_mjprob_prsum (vars_su_y_mjprob), 1413
compute_su_y_mjprob_prsum(), *762*
compute_su_y_mjsre__neg_nm, 762
compute_su_y_mjsre__neg_sum (vars_su_y_mjsre__neg), 1415
compute_su_y_mjsre__pos_nm, 763
compute_su_y_mjsre__pos_sum (vars_su_y_mjsre__pos), 1416
compute_su_y_mjsre_all, 764
compute_su_y_mjsre_nm, 764
compute_su_y_mjsre_sum (vars_su_y_mjsre), 1414
compute_su_y_nicsre__chew_nm, 765
compute_su_y_nicsre__chew_sum (vars_su_y_nicsre__chew), 1417
compute_su_y_nicsre__cig_nm, 766
compute_su_y_nicsre__cig_sum (vars_su_y_nicsre__cig), 1419
compute_su_y_nicsre__vape_nm, 767
compute_su_y_nicsre__vape_sum (vars_su_y_nicsre__vape), 1420
compute_su_y_nicsre_all, 768
compute_su_y_nicvapeexp__neg_nm, 768
compute_su_y_nicvapeexp__neg_prsum (vars_su_y_nicvapeexp__neg), 1421
compute_su_y_nicvapeexp__neg_prsum(), *769*
compute_su_y_nicvapeexp__pos_nm, 769
compute_su_y_nicvapeexp__pos_prsum (vars_su_y_nicvapeexp__pos), 1422
compute_su_y_nicvapeexp__pos_prsum(), *770*
compute_su_y_nicvapeexp_all, 770
compute_su_y_sui__last__day_count, 771
compute_su_y_sui__onset_useage (sui_substances), 812
compute_su_y_sui__reg_useage, 772
compute_tlfb_abst (tlfb_substances), 814
compute_tlfb_abst(), *776*
compute_tlfb_dt, 774
compute_tlfb_maxdose, 777
compute_tlfb_mean, 779
compute_tlfb_totdose, 781
compute_tlfb_totdose_sum, 784
compute_tlfb_ud, 786
convert_time_mctq, 788
create_session_num, 790

filter_tlfb, 791

get_tscore_tbl, 793
get_tscore_tbl(), *811*

make_static, 794
map_mid_years(), *731*, *733*, *735*
md_bullet, 795

prepare_data_sdsu(), *729*, *731*, *734*

recode_levels, 796
rx_map, *640*, *642*

ss_count, 797
ss_count_cond, 800
ss_max, 800
ss_mean, 802
ss_mean_pos, 803
ss_nm, 805
ss_prsum, 806
ss_sum, 808
ss_tscore, 809

ss_tscore(), *109*, *112*, *115*, *119*, *122*, *125*, *128*, *131*, *134*, *136*, *139*, *141*, *145*, *148*, *151*, *155*, *159*, *162*, *167*, *170*, *173*, *176*, *185*, *225*, *228*, *229*, *232*, *235*, *238*, *241*, *244*, *247*, *250*, *253*, *256*, *259*, *260*, *264*, *268*, *272*, *273*, *275*, *276*, *278*, *279*, *282*, *285*, *294*, *420*, *423*, *426*, *429*, *430*, *440*, *443*, *446*, *450*, *566*, *569*, *572*, *573*, *575*, *576*, *578*, *581*, *584*, *587*, *588*, *591*, *594*, *598*, *602*, *606*, *609*, *612*, *615*, *618*, *626*
sui_substances, 812

tlfb_substances, 814

vars_ab_g_dyn__cohort_edu__cgs, 816
vars_ab_g_dyn__cohort_income__hhold__6lvl, 817
vars_ab_g_dyn__cohort_prtnrshp__employ, 818
vars_ab_g_stc__cohort_ethn, 819
vars_ab_g_stc__cohort_ethnrace__leg, 820
vars_ab_g_stc__cohort_ethnrace__mblack, 822
vars_ab_g_stc__cohort_ethnrace__meim, 824
vars_ab_g_stc__cohort_ethnrace__mhisp, 825
vars_ab_g_stc__cohort_race__nih, 827
vars_ab_p_demo__ntvam, 828
vars_fc_p_fes__cohes, 830
vars_fc_p_fes__confl, 831
vars_fc_p_fes__expr, 832
vars_fc_p_fes__intelcult, 833
vars_fc_p_fes__org, 835
vars_fc_p_fes__rec, 836
vars_fc_p_meim, 837
vars_fc_p_meim__commattach, 838
vars_fc_p_meim__explor, 839
vars_fc_p_nce, 840
vars_fc_p_nce__cc, 841
vars_fc_p_nce__isc, 842
vars_fc_p_nsc__ns, 843
vars_fc_p_pk__knowl, 844
vars_fc_p_psb, 845
vars_fc_p_vs__famil, 846
vars_fc_p_vs__famil__v01, 848
vars_fc_p_vs__indselfrel, 849
vars_fc_p_vs__obl, 851
vars_fc_p_vs__ref, 852
vars_fc_p_vs__relig, 853
vars_fc_p_vs__supp, 854
vars_fc_y_as__safe, 855
vars_fc_y_crpbi__cg1, 856
vars_fc_y_crpbi__cg2, 857
vars_fc_y_eut__ethn, 858
vars_fc_y_fes__cohes, 859
vars_fc_y_fes__confl, 861
vars_fc_y_lone, 862
vars_fc_y_meim, 863
vars_fc_y_meim__commattach, 864
vars_fc_y_meim__explor, 865
vars_fc_y_mnbs, 866
vars_fc_y_mnbs__edusupp, 867
vars_fc_y_mnbs__superv, 868
vars_fc_y_naa, 869
vars_fc_y_pm, 870
vars_fc_y_pnh, 871
vars_fc_y_psb, 872
vars_fc_y_rpi, 873
vars_fc_y_srpf__dis, 874
vars_fc_y_srpf__env, 875
vars_fc_y_srpf__involv, 876
vars_fc_y_vs__famil, 878
vars_fc_y_vs__famil__v01, 879
vars_fc_y_vs__indselfrel, 880
vars_fc_y_vs__obl, 882
vars_fc_y_vs__ref, 883
vars_fc_y_vs__relig, 884
vars_fc_y_vs__supp, 885
vars_fc_y_wpss, 886
vars_mh_p_abcl, 887
vars_mh_p_abcl__afs__frnd, 891
vars_mh_p_abcl__cg2, 892
vars_mh_p_abcl__critic, 893
vars_mh_p_abcl__dsm__adhd, 895
vars_mh_p_abcl__dsm__antsoc, 896
vars_mh_p_abcl__dsm__anx, 898
vars_mh_p_abcl__dsm__avoid, 899
vars_mh_p_abcl__dsm__dep, 900
vars_mh_p_abcl__dsm__somat, 902
vars_mh_p_abcl__su, 903
vars_mh_p_abcl__su__drg, 905
vars_mh_p_abcl__su__drunk, 906
vars_mh_p_abcl__su__nic, 907

vars_mh_p_abcl__synd__aggr, 908
vars_mh_p_abcl__synd__anxdep, 910
vars_mh_p_abcl__synd__attn, 911
vars_mh_p_abcl__synd__ext, 913
vars_mh_p_abcl__synd__int, 915
vars_mh_p_abcl__synd__intru, 917
vars_mh_p_abcl__synd__othpr, 918
vars_mh_p_abcl__synd__rule, 920
vars_mh_p_abcl__synd__som, 921
vars_mh_p_abcl__synd__tho, 923
vars_mh_p_abcl__synd__wthdr, 924
vars_mh_p_asr, 926
vars_mh_p_asr__afs__strng, 930
vars_mh_p_asr__critic, 931
vars_mh_p_asr__dsm__adhd, 933
vars_mh_p_asr__dsm__adhd__hypimp, 934
vars_mh_p_asr__dsm__adhd__inatt, 935
vars_mh_p_asr__dsm__antsoc, 937
vars_mh_p_asr__dsm__anx, 938
vars_mh_p_asr__dsm__avoid, 940
vars_mh_p_asr__dsm__dep, 941
vars_mh_p_asr__dsm__somat, 943
vars_mh_p_asr__synd__aggr, 944
vars_mh_p_asr__synd__anxdep, 945
vars_mh_p_asr__synd__attn, 947
vars_mh_p_asr__synd__ext, 948
vars_mh_p_asr__synd__int, 950
vars_mh_p_asr__synd__intru, 953
vars_mh_p_asr__synd__othpr, 954
vars_mh_p_asr__synd__rule, 956
vars_mh_p_asr__synd__som, 957
vars_mh_p_asr__synd__tho, 959
vars_mh_p_asr__synd__wthdr, 960
vars_mh_p_cbcl, 961
vars_mh_p_cbcl__dsm__adhd, 965
vars_mh_p_cbcl__dsm__anx, 967
vars_mh_p_cbcl__dsm__cond, 968
vars_mh_p_cbcl__dsm__dep, 970
vars_mh_p_cbcl__dsm__opp, 971
vars_mh_p_cbcl__dsm__somat, 972
vars_mh_p_cbcl__ocd, 974
vars_mh_p_cbcl__sct, 975
vars_mh_p_cbcl__strs, 976
vars_mh_p_cbcl__synd__aggr, 978
vars_mh_p_cbcl__synd__anxdep, 980
vars_mh_p_cbcl__synd__attn, 981
vars_mh_p_cbcl__synd__ext, 982
vars_mh_p_cbcl__synd__int, 984
vars_mh_p_cbcl__synd__othpr, 986
vars_mh_p_cbcl__synd__rule, 988
vars_mh_p_cbcl__synd__soc, 990
vars_mh_p_cbcl__synd__som, 991
vars_mh_p_cbcl__synd__tho, 992
vars_mh_p_cbcl__synd__wthdep, 994
vars_mh_p_ders__attun, 995
vars_mh_p_ders__catast, 997
vars_mh_p_ders__distract, 998
vars_mh_p_ders__negscnd, 1000
vars_mh_p_eatq__actv, 1001
vars_mh_p_eatq__affl, 1002
vars_mh_p_eatq__aggr, 1004
vars_mh_p_eatq__attn, 1005
vars_mh_p_eatq__depm, 1006
vars_mh_p_eatq__fear, 1008
vars_mh_p_eatq__frust, 1009
vars_mh_p_eatq__inhib, 1011
vars_mh_p_eatq__shy, 1012
vars_mh_p_eatq__surg, 1013
vars_mh_p_famhx__alc__moth__fath_indicator, 1015
vars_mh_p_famhx__alc__moth__fath_score, 1016
vars_mh_p_famhx__dep__moth__fath_indicator, 1017
vars_mh_p_famhx__dep__moth__fath_score, 1018
vars_mh_p_famhx__doc__moth__fath_indicator, 1019
vars_mh_p_famhx__doc__moth__fath_score, 1020
vars_mh_p_famhx__drg__moth__fath_indicator, 1021
vars_mh_p_famhx__drg__moth__fath_score, 1022
vars_mh_p_famhx__halluc__moth__fath_indicator, 1023
vars_mh_p_famhx__halluc__moth__fath_score, 1024
vars_mh_p_famhx__hosp__moth__fath_indicator, 1025
vars_mh_p_famhx__hosp__moth__fath_score, 1026
vars_mh_p_famhx__mania__moth__fath_indicator, 1028
vars_mh_p_famhx__mania__moth__fath_score, 1029

vars_mh_p_famhx__nerve__moth__fath_indicator, 1030
vars_mh_p_famhx__nerve__moth__fath_score, 1031
vars_mh_p_famhx__suic__moth__fath_indicator, 1032
vars_mh_p_famhx__suic__moth__fath_score, 1033
vars_mh_p_famhx__troub__moth__fath_indicator, 1034
vars_mh_p_famhx__troub__moth__fath_score, 1035
vars_mh_p_gbi, 1036
vars_mh_p_ksads__adhd__past__sx, 1038
vars_mh_p_ksads__adhd__pres__sx, 1039
vars_mh_p_ksads__agor__past__sx, 1041
vars_mh_p_ksads__agor__pres__sx, 1042
vars_mh_p_ksads__asd__past__sx, 1044
vars_mh_p_ksads__asd__pres__sx, 1045
vars_mh_p_ksads__bpd__past__sx, 1047
vars_mh_p_ksads__bpd__pres__sx, 1048
vars_mh_p_ksads__cond__past__sx, 1050
vars_mh_p_ksads__cond__pres__sx, 1052
vars_mh_p_ksads__dep__past__sx, 1053
vars_mh_p_ksads__dep__pres__sx, 1055
vars_mh_p_ksads__dmdd__sx, 1057
vars_mh_p_ksads__ed__past__sx, 1058
vars_mh_p_ksads__ed__pres__sx, 1059
vars_mh_p_ksads__gad__past__sx, 1061
vars_mh_p_ksads__gad__pres__sx, 1062
vars_mh_p_ksads__hom__past__sx, 1064
vars_mh_p_ksads__hom__pres__sx, 1065
vars_mh_p_ksads__ocd__past__sx, 1066
vars_mh_p_ksads__ocd__pres__sx, 1068
vars_mh_p_ksads__odd__past__sx, 1069
vars_mh_p_ksads__odd__pres__sx, 1071
vars_mh_p_ksads__panic__past__sx, 1072
vars_mh_p_ksads__panic__pres__sx, 1073
vars_mh_p_ksads__phobia__past__sx, 1075
vars_mh_p_ksads__phobia__pres__sx, 1076
vars_mh_p_ksads__psych__past__sx, 1077
vars_mh_p_ksads__psych__pres__sx, 1079
vars_mh_p_ksads__ptsd__past__sx, 1080
vars_mh_p_ksads__ptsd__pres__sx, 1082
vars_mh_p_ksads__sepanx__past__sx, 1084
vars_mh_p_ksads__sepanx__pres__sx, 1085
vars_mh_p_ksads__sleep__past__sx, 1087
vars_mh_p_ksads__sleep__pres__sx, 1088
vars_mh_p_ksads__socanx__past__sx, 1089
vars_mh_p_ksads__socanx__pres__sx, 1091
vars_mh_p_ksads__suic__past__sx, 1092
vars_mh_p_ksads__suic__pres__sx, 1094
vars_mh_p_ksads__tic__past__sx, 1095
vars_mh_p_ksads__tic__pres__sx, 1097
vars_mh_p_ple, 1098
vars_mh_p_ple__exp *(vars_mh_p_ple)*, 1098
vars_mh_p_ple__exp__v01, 1100
vars_mh_p_ple__exp__v02, 1102
vars_mh_p_ple__exp__v03, 1105
vars_mh_p_ple__exp__v04, 1108
vars_mh_p_ple__severity, 1110
vars_mh_p_ple__severity__v01, 1111
vars_mh_p_ple__severity__v02, 1113
vars_mh_p_ple__severity__v03, 1115
vars_mh_p_ple__severity__v04, 1117
vars_mh_p_ple__v01, 1118
vars_mh_p_ple__v02, 1120
vars_mh_p_ple__v03, 1122
vars_mh_p_ple__v04, 1124
vars_mh_p_ssrs, 1125
vars_mh_t_bpm, 1126
vars_mh_t_bpm__attn, 1128
vars_mh_t_bpm__ext, 1129
vars_mh_t_bpm__int, 1130
vars_mh_y_bisbas__bas__dr, 1132
vars_mh_y_bisbas__bas__fs, 1133
vars_mh_y_bisbas__bas__rr, 1134
vars_mh_y_bisbas__bas__rr__v01, 1135
vars_mh_y_bisbas__bis, 1137
vars_mh_y_bisbas__bis__v01, 1138
vars_mh_y_bpm, 1139
vars_mh_y_bpm__attn, 1141
vars_mh_y_bpm__ext, 1142
vars_mh_y_bpm__int, 1143
vars_mh_y_erq__reapp, 1144
vars_mh_y_erq__suppr, 1146
vars_mh_y_ksads__bpd__past__sx, 1147
vars_mh_y_ksads__bpd__pres__sx, 1149
vars_mh_y_ksads__cond__past__sx, 1150
vars_mh_y_ksads__cond__pres__sx, 1152

vars_mh_y_ksads__dep__past__sx, 1154
vars_mh_y_ksads__dep__pres__sx, 1155
vars_mh_y_ksads__dmdd__sx, 1157
vars_mh_y_ksads__ed__past__sx, 1158
vars_mh_y_ksads__ed__pres__sx, 1160
vars_mh_y_ksads__gad__past__sx, 1161
vars_mh_y_ksads__gad__pres__sx, 1163
vars_mh_y_ksads__ocd__past__sx, 1164
vars_mh_y_ksads__ocd__pres__sx, 1165
vars_mh_y_ksads__panic__past__sx, 1167
vars_mh_y_ksads__panic__pres__sx, 1168
vars_mh_y_ksads__ptsd__past__sx, 1170
vars_mh_y_ksads__ptsd__pres__sx, 1172
vars_mh_y_ksads__sleep__past__sx, 1174
vars_mh_y_ksads__sleep__pres__sx, 1175
vars_mh_y_ksads__socanx__past__sx, 1176
vars_mh_y_ksads__socanx__pres__sx, 1178
vars_mh_y_ksads__suic__past__sx, 1179
vars_mh_y_ksads__suic__pres__sx, 1181
vars_mh_y_pai, 1182
vars_mh_y_peq__overt__agg, 1184
vars_mh_y_peq__overt__vict, 1185
vars_mh_y_peq__rel__agg, 1186
vars_mh_y_peq__rel__vict, 1187
vars_mh_y_peq__rep__agg, 1188
vars_mh_y_peq__rep__vict, 1190
vars_mh_y_ple, 1191
vars_mh_y_ple__exp, 1192
vars_mh_y_ple__exp__v01, 1195
vars_mh_y_ple__exp__v02, 1197
vars_mh_y_ple__exp__v03, 1200
vars_mh_y_ple__severity, 1203
vars_mh_y_ple__severity__v01, 1204
vars_mh_y_ple__severity__v02, 1206
vars_mh_y_ple__severity__v03, 1208
vars_mh_y_ple__v01, 1210
vars_mh_y_ple__v02, 1212
vars_mh_y_ple__v03, 1214
vars_mh_y_pps__bother, 1216
vars_mh_y_pps__severity, 1217
vars_mh_y_pps_count, 1219
vars_mh_y_sup, 1221
vars_mh_y_upps__nurg, 1222
vars_mh_y_upps__pers, 1223
vars_mh_y_upps__plan, 1224
vars_mh_y_upps__purg, 1225
vars_mh_y_upps__sens, 1227
vars_mh_y_ysr, 1228
vars_mh_y_ysr__dsm__adhd, 1231
vars_mh_y_ysr__dsm__anx, 1233
vars_mh_y_ysr__dsm__cond, 1234
vars_mh_y_ysr__dsm__dep, 1236
vars_mh_y_ysr__dsm__opp, 1237
vars_mh_y_ysr__dsm__somat, 1238
vars_mh_y_ysr__pos, 1240
vars_mh_y_ysr__synd__aggr, 1241
vars_mh_y_ysr__synd__anxdep, 1243
vars_mh_y_ysr__synd__attn, 1244
vars_mh_y_ysr__synd__ext, 1246
vars_mh_y_ysr__synd__int, 1248
vars_mh_y_ysr__synd__othpr, 1249
vars_mh_y_ysr__synd__rule, 1251
vars_mh_y_ysr__synd__soc, 1252
vars_mh_y_ysr__synd__som, 1254
vars_mh_y_ysr__synd__tho, 1255
vars_mh_y_ysr__synd__wthdep, 1257
vars_nc_p_bdefs, 1258
vars_nc_y_ehis, 1260
vars_nt_p_yst__pmum, 1261
vars_nt_p_yst__screen__wkdy, 1262
vars_nt_p_yst__screen__wknd, 1263
vars_nt_y_stq__screen__wkdy, 1264
vars_nt_y_stq__screen__wknd, 1266
vars_ph_p_anthr__height, 1267
vars_ph_p_cna, 1268
vars_ph_p_dhx_birthweight, 1270
vars_ph_p_otbi, 1271
vars_ph_p_otbi__loc__30m_count, 1272
vars_ph_p_otbi__loc_before15, 1274
vars_ph_p_otbi__loc_count, 1276
vars_ph_p_otbi__loc_tbiage, 1277
vars_ph_p_otbi__rpt_count, 1280
vars_ph_p_otbi_tbiworst, 1281
vars_ph_p_pds__f, 1283
vars_ph_p_pds__f_categ, 1284
vars_ph_p_pds__m, 1286
vars_ph_p_pds__m_categ, 1287
vars_ph_p_sds__da, 1288
vars_ph_p_sds__dims, 1289
vars_ph_p_sds__does, 1291
vars_ph_p_sds__hyphy, 1292
vars_ph_p_sds__sbd, 1293
vars_ph_p_sds__swtd, 1295
vars_ph_p_sds_sum, 1296

vars_ph_y_anthr__height, 1298
vars_ph_y_anthr__weight, 1299
vars_ph_y_bp__dia, 1301
vars_ph_y_bp__hrate, 1302
vars_ph_y_bp__sys, 1303
vars_ph_y_pds__f, 1304
vars_ph_y_pds__f_categ, 1305
vars_ph_y_pds__m, 1306
vars_ph_y_pds__m_categ, 1308
vars_su_p_ksads__aud__past__sx, 1309
vars_su_p_ksads__aud__pres__sx, 1310
vars_su_p_ksads__dud__coc__past__sx_mean, 1312
vars_su_p_ksads__dud__coc__pres__sx_mean, 1314
vars_su_p_ksads__dud__hall__past__sx_mean, 1315
vars_su_p_ksads__dud__hall__pres__sx_mean, 1317
vars_su_p_ksads__dud__mj__past__sx_mean, 1319
vars_su_p_ksads__dud__mj__pres__sx_mean, 1320
vars_su_p_ksads__dud__nic__past__sx_mean, 1322
vars_su_p_ksads__dud__nic__pres__sx_mean, 1324
vars_su_p_ksads__dud__opi__past__sx_mean, 1325
vars_su_p_ksads__dud__opi__pres__sx_mean, 1327
vars_su_p_ksads__dud__othdrg__past__sx_mean, 1329
vars_su_p_ksads__dud__othdrg__pres__sx_mean, 1330
vars_su_p_ksads__dud__past__sx_mean, 1332
vars_su_p_ksads__dud__pcp__past__sx_mean, 1334
vars_su_p_ksads__dud__pcp__pres__sx_mean, 1335
vars_su_p_ksads__dud__pres__sx_mean, 1337
vars_su_p_ksads__dud__sed__past__sx_mean, 1339
vars_su_p_ksads__dud__sed__pres__sx_mean, 1340
vars_su_p_ksads__dud__solv__past__sx_mean, 1342
vars_su_p_ksads__dud__solv__pres__sx_mean, 1344
vars_su_p_ksads__dud__stim__past__sx_mean, 1345
vars_su_p_ksads__dud__stim__pres__sx_mean, 1347
vars_su_y_alcexp__neg, 1349
vars_su_y_alcexp__pos, 1350
vars_su_y_alchss, 1351
vars_su_y_alcprob, 1352
vars_su_y_alcsre__6mo, 1354
vars_su_y_alcsre__first5, 1355
vars_su_y_alcsre__hvy, 1356
vars_su_y_caff__coffee, 1357
vars_su_y_caff__energy, 1358
vars_su_y_caff__energy__drink, 1359
vars_su_y_caff__energy__shot, 1361
vars_su_y_caff__espres, 1362
vars_su_y_caff__oth, 1363
vars_su_y_caff__soda, 1364
vars_su_y_caff__suppl, 1365
vars_su_y_caff__tea, 1366
vars_su_y_cigexp__neg, 1367
vars_su_y_cigexp__pos, 1368
vars_su_y_drgprob, 1369
vars_su_y_ksads__aud__past__sx, 1371
vars_su_y_ksads__aud__pres__sx, 1372
vars_su_y_ksads__dud__coc__past__sx_mean, 1374
vars_su_y_ksads__dud__coc__pres__sx_mean, 1376
vars_su_y_ksads__dud__hall__past__sx_mean, 1377
vars_su_y_ksads__dud__hall__pres__sx_mean, 1379
vars_su_y_ksads__dud__mj__past__sx_mean, 1381
vars_su_y_ksads__dud__mj__pres__sx_mean, 1382
vars_su_y_ksads__dud__nic__past__sx_mean, 1384
vars_su_y_ksads__dud__nic__pres__sx_mean, 1386
vars_su_y_ksads__dud__opi__past__sx_mean, 1387
vars_su_y_ksads__dud__opi__pres__sx_mean, 1389

vars_su_y_ksads__dud__othdrg__past__sx_mean, 1391
vars_su_y_ksads__dud__othdrg__pres__sx_mean, 1392
vars_su_y_ksads__dud__past__sx_mean, 1394
vars_su_y_ksads__dud__pcp__past__sx_mean, 1396
vars_su_y_ksads__dud__pcp__pres__sx_mean, 1397
vars_su_y_ksads__dud__pres__sx_mean, 1399
vars_su_y_ksads__dud__sed__past__sx_mean, 1401
vars_su_y_ksads__dud__sed__pres__sx_mean, 1402
vars_su_y_ksads__dud__solv__past__sx_mean, 1404
vars_su_y_ksads__dud__solv__pres__sx_mean, 1406
vars_su_y_ksads__dud__stim__past__sx_mean, 1407
vars_su_y_ksads__dud__stim__pres__sx_mean, 1409
vars_su_y_mjexp__neg, 1411
vars_su_y_mjexp__pos, 1412
vars_su_y_mjprob, 1413
vars_su_y_mjsre, 1414
vars_su_y_mjsre__neg, 1415
vars_su_y_mjsre__pos, 1416
vars_su_y_nicsre__chew, 1417
vars_su_y_nicsre__cig, 1419
vars_su_y_nicsre__vape, 1420
vars_su_y_nicvapeexp__neg, 1421
vars_su_y_nicvapeexp__pos, 1422